Voltaris Mobility - Product Specification Sheet

Voltaris NMC-800 EV Battery Pack

80 kWh lithium-ion traction battery pack for mid-size electric passenger vehicles.

1. Identification

Battery identifier	BAT-EU-2027-000214
Battery category	Electric vehicle battery (EV)
Manufacturer	Voltaris Cell Systems Sp. z o.o. (MFR-EU-001982)
Manufacturer address	ul. Przemyslowa 8, 62-052 Komorniki, Poland
Place of manufacture	Komorniki, Poland
Date of manufacture	February 2027

2. Electrical characteristics

Rated capacity	220 Ah
Nominal voltage	360 V
Minimum voltage	288 V
Maximum voltage	403 V
Original power capability (nominal)	150 kW
Initial round-trip energy efficiency (nominal)	95 %
Initial internal resistance (nominal)	cell 0.0012 ohm, pack 0.135 ohm
Expected lifetime (nominal)	2500 cycles (IEC 62660-1, 25 °C, 1C/1C, 100% DoD)

3. Physical

Nominal mass	482 kg
Idle temperature range	-20 °C to 45 °C

FICTITIOUS SAMPLE DOCUMENT - invented for software testing. Not a real product, company or certificate.

4. Materials and composition

Chemistry	Lithium nickel manganese cobalt oxide (NMC 811), graphite anode
Critical raw materials	Lithium, cobalt, nickel, natural graphite

Hazardous substances: Lithium hexafluorophosphate (LiPF6) 1.1% of pack mass; ethylene carbonate 2.4%; cobalt compounds 3.2%; nickel compounds 9.8%.

5. Carbon footprint

Life-cycle carbon footprint per kWh of total energy over the service life: 41.8 kg CO2e/kWh

Carbon footprint performance class: Class B

6. Recycled content (pre- and post-consumer combined)

Material	Recycled share
Cobalt	22 %
Lithium	11 %
Nickel	16 %
Lead	0 %

FICTITIOUS SAMPLE DOCUMENT - invented for software testing. Not a real product, company or certificate.