Arbor Test Laboratories - Test Report AT-2026-1184

Client: Arbor Mobility Components S.L.

Test item

The test item is a CityGlide CG-48-14 e-bike battery, a light means of transport (LMT) battery, serial number CG48-2026-0007731, manufactured on 14 September 2026 by Arbor Mobility Components S.L., Calle de la Industria 14, 46980 Paterna, Spain, at its plant in Paterna, Spain. The pack is built from 16 lithium iron phosphate (LiFePO4) prismatic cells in series. According to the manufacturer the rated capacity is 14 Ah and the nominal voltage is 51.2 V. The discharge cut-off (minimum voltage) is 40.0 V and the end-of-charge (maximum voltage) is 58.4 V. The nominal mass declared on the label is 3.9 kg.

Results

Capacity measured at 0.5C and 25 °C was 13.8 Ah, which is within the tolerance of the rated value. The maximum continuous power capability was 750 W. The typical initial round-trip energy efficiency was 96.1 % at 0.5C. The typical pack internal resistance (DC, 25 °C, 50% SoC) was 85 mOhm. Expected lifetime is 2000 cycles (nominal) to 80% of rated capacity. Operating temperature range (discharge): -10 °C to 55 °C.

FICTITIOUS SAMPLE DOCUMENT - invented for software testing. Not a real product, company or certificate.

Sustainability declarations supplied by the client

Critical raw materials present: lithium, natural graphite.

Hazardous substances: electrolyte containing lithium hexafluorophosphate (LiPF6).

Carbon footprint: 72.4 kg CO2e/kWh (declared by the client, not verified by this laboratory).

Recycled lithium content: 4 % (pre- and post-consumer combined).

Approved by: J. Doe, Head of Laboratory. This report covers only the item tested.

FICTITIOUS SAMPLE DOCUMENT - invented for software testing. Not a real product, company or certificate.