Voltaris Mobility - Product Specification Sheet

Voltaris NMC-800 EV Battery Pack

80 kWh lithium-ion traction battery pack for mid-size electric passenger vehicles.

1. Identification

Battery identifier	BAT-EU-2027-000214
Battery category	Electric vehicle battery (EV)
Manufacturer	Voltaris Cell Systems Sp. z o.o. (MFR-EU-001982)
Manufacturer address	ul. Przemyslowa 8, 62-052 Komorniki, Poland
Manufacturer contact	compliance@voltaris-cells.example
Place of manufacture	Komorniki, Poland
Date of manufacture	February 2027
Commodity code (CN)	8507 60 00
Warranty	8 years or 160 000 km, whichever comes first

2. Electrical characteristics

Rated capacity	220 Ah
Nominal voltage	360 V
Minimum voltage	288 V
Maximum voltage	403 V
Original power capability (nominal)	150 kW
Initial round-trip energy efficiency (nominal)	95 %
Initial internal resistance (nominal)	cell 0.0012 ohm, pack 0.135 ohm
Expected lifetime (nominal)	2500 cycles (IEC 62660-1, 25 °C, 1C/1C, 100% DoD)

3. Physical

Nominal mass	482 kg
Idle temperature range	-20 °C to 45 °C
Extinguishing agent	Large amounts of water; do not use CO2 on a burning pack

FICTITIOUS SAMPLE DOCUMENT - invented for software testing. Not a real product, company or certificate.

4. Materials and composition

Chemistry	Lithium nickel manganese cobalt oxide (NMC 811), graphite anode
Critical raw materials	Lithium, cobalt, nickel, natural graphite
Electrode and electrolyte	Cathode NMC 811; anode natural graphite; electrolyte LiPF6 in EC/DMC
Module part number	VM-811-12 (12 per pack); BMS board VB-360-02

Hazardous substances: Lithium hexafluorophosphate (LiPF6) 1.1% of pack mass; ethylene carbonate 2.4%; cobalt compounds 3.2%; nickel compounds 9.8%.

5. Carbon footprint

Life-cycle carbon footprint per kWh of total energy over the service life: 41.8 kg CO2e/kWh

Carbon footprint performance class: Class B

Life-cycle stage	kg CO2e/kWh
Raw material acquisition and pre-processing	27.6
Main product production	11.2
Distribution	0.9
End of life and recycling	2.1

6. Recycled content (pre- and post-consumer combined)

Material	Recycled share	Pre-consumer	Post-consumer
Cobalt	22 %	14 %	8 %
Lithium	11 %	6 %	5 %
Nickel	16 %	10 %	6 %
Lead	0 %	0 %	0 %

Renewable content share: 2 %

7. Durability

Expected lifetime	8 calendar years
Cycle-life reference test	IEC 62660-1
C-rate of cycle-life test	1C
Capacity threshold for exhaustion	70 % of rated capacity
Round-trip energy efficiency at 50 % of cycle life	92 %
Maximum permitted battery power	180 kW

FICTITIOUS SAMPLE DOCUMENT - invented for software testing. Not a real product, company or certificate.