TC1002S Herramientas computacionales: el arte de la analítica

This is a notebook with all your work for the final evidence of this course

Niveles de dominio a demostrar con la evidencia

SING0202A

Interpreta interacciones entre variables relevantes en un problema, como base para la construcción de modelos bivariados basados en datos de un fenómeno investigado que le permita reproducir la respuesta del mismo. Es capaz de construir modelos bivariados que expliquen el comportamiento de un fenómeno.

Student information

- Name: Daniel Estrada Ocaña
- ID: A01369854
- · My carreer: ITC

Importing libraries

```
1 import numpy as np
 2 import pandas as pd
 3 import seaborn as sns
 4 import matplotlib.pyplot as plt
 5 from sklearn.cluster import KMeans
 1 # Define where you are running the code: colab or local
 2 RunInColab = True # (False: no | True: yes)
 4 # If running in colab:
 5 if RunInColab:
      # Mount your google drive in google colab
      from google.colab import drive
      drive.mount('/content/drive')
 8
 9
      # Find location
10
11
      #!pwd
12
      #!ls
13
      #!ls "/content/drive/My Drive/Colab Notebooks/MachineLearningWithPython/"
14
15
      # Define path del proyecto
16
                    = "/content/drive/MyDrive/Sistemas/4to_semestre/semanaTec/TC1002S/"
17
18 else:
19
     # Define path del proyecto
20
    Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True).
```

PART 1

Use your assigned dataset

A1 Load data

```
1 # Dataset url
2 url = Ruta + "Evidencia/A01369854_X.csv"
3
4 # Load the dataset
5 df = pd.read_csv(url)
```

A2 Data managment

Print the first 7 rows

1 df.head(7)

	Unnamed:	0	x1	x2	x3	x4	
0		0	-2.637008	6.469373	-8.065872	10.382298	11.
1		1	-7.198506	-2.450691	-10.125392	-8.711022	
2		2	-4.965669	-1.941930	-13.139206	-5.410215	
3		3	8.318951	9.783888	9.011195	-3.365455	
4		4	5.610515	9.479026	9.551860	-7.023893	
5		5	9.083749	11.584535	10.599982	-2.966507	
6		6	6.649827	10.571454	9.169478	-3.110495	

Next steps: View recommended plots

Print the last 4 rows

1 df.tail(4)

	Unnamed: 0	x1	x2	х3	x4	
388	388	0.742929	8.652554	-3.018461	6.537593	11.
389	389	2.357353	6.295590	-5.362303	8.979738	
390	390	2.650814	10.639732	-2.007908	11.072933	
391	391	-7.072400	-0.704284	-10.758445	-6.019089	

How many rows and columns are in your data?

Use the shape method

1 df.shape (392, 5)

Print the name of all columns

Use the columns method

1 df.columns

```
Index(['Unnamed: 0', 'x1', 'x2', 'x3', 'x4'], dtype='object')
```

What is the data type in each column

Use the dtypes method

1 df.dtypes

```
Unnamed: 0 int64
x1 float64
x2 float64
x3 float64
```

```
x4 float64
dtype: object
```

What is the meaning of rows and columns?

```
1 # Your responses here
2
3 # 1) Rows refers to the number of observations in our dataset
4
5 # 2) Columns refers to our variables or features in our dataset
6
```

Print a statistical summary of your columns

1 df.describe()

	Unnamed: 0	x1	x2	х3	x4	
ount	392.000000	392.000000	392.000000	392.000000	392.000000	-
nean	195.500000	3.173315	5.889524	1.342545	-2.138052	
std	113.304898	6.302593	4.864176	8.243437	7.199664	
nin	0.000000	-9.861084	-8.021386	-13.703612	-11.843976	
25%	97.750000	-2.333433	3.361996	-6.725301	-7.434815	
50%	195.500000	4.962112	7.413908	2.431116	-5.101422	
75%	293.250000	8.113206	9.376306	9.184893	2.440813	
nax	391.000000	15.449343	13.684451	15.239239	13.346037	

```
1 # 1) What is the minumum and maximum values of each variable
3 # x1: min= -9.871084, max= 15.449343
 4 # x2: min= -8.021386, max= 13.684451
 5 # x3: min= -13.703612, max= 15.239239
 6 # x4: min= -11.843976, max= 13.346037
 8 # 2) What is the mean and standar deviation of each variable
10 # x1: mean= 3.173315, standar deviation= 6.302593
11 # x2: mean= 5.889524, standar deviation= 4.864176
12 # x3: mean= 1.342545, standar deviation= 8.243437
13 # x4: mean= -2.138052, standar deviatio= 7.199664
14
15
16 # 3) What the 25%, 50% and 75% represent?
17
18 # x1: 25%= -2.333433, 50%= 4.962112, 75%= 8.113206
19 # x2: 25%= 3.361996, 50%= 7.413908, 75%= 9.376306
20 # x3: 25%= -6.725301, 50%= 2.431116, 75%= 9.184893
21 # x4: 25%= -7.434815, 50%= -5.101422, 75%= 2.440813
22
```

Rename the columns using the same name with capital letters

```
1 newNames = {'x1':'X1', 'x2':'X2', 'x3':'X3', 'x4':'X4'}
2 df = df.rename(columns=newNames)
3 df
```

	Unnamed: 0	X1	Х2	Х3	X4	
0	0	-2.637008	6.469373	-8.065872	10.382298	
1	1	-7.198506	-2.450691	-10.125392	-8.711022	
2	2	-4.965669	-1.941930	-13.139206	-5.410215	
3	3	8.318951	9.783888	9.011195	-3.365455	
4	4	5.610515	9.479026	9.551860	-7.023893	
387	387	8.867089	8.961678	9.061760	-2.688653	
388	388	0.742929	8.652554	-3.018461	6.537593	
389	389	2.357353	6.295590	-5.362303	8.979738	
390	390	2.650814	10.639732	-2.007908	11.072933	
391	391	-7.072400	-0.704284	-10.758445	-6.019089	
302 rd	we v 5 column	16				

392 rows × 5 columns

Next steps: View recommended plots

Rename the columns to their original names

```
1 oriNames = {'X1':'x1', 'X2':'x2', 'X3':'x3', 'X4':'x4'}
2 df = df.rename(columns=oriNames)
3 df
```

	Unnamed: 0	x1	x2	x3	x4
0	0	-2.637008	6.469373	-8.065872	10.382298
1	1	-7.198506	-2.450691	-10.125392	-8.711022
2	2	-4.965669	-1.941930	-13.139206	-5.410215
3	3	8.318951	9.783888	9.011195	-3.365455
4	4	5.610515	9.479026	9.551860	-7.023893
387	387	8.867089	8.961678	9.061760	-2.688653
388	388	0.742929	8.652554	-3.018461	6.537593
389	389	2.357353	6.295590	-5.362303	8.979738
390	390	2.650814	10.639732	-2.007908	11.072933
391	391	-7.072400	-0.704284	-10.758445	-6.019089
392 r	ows × 5 column	1S			

392 10W5 ^ 3 COIUITIIIS

Next steps: View recommended plots

Use two different alternatives to get one of the columns

```
1 a = df.x1
2 b = df.loc[:,'x1']
4 print(a,b)
   0
         -2.637008
         -7.198506
         -4.965669
         8.318951
    3
    4
          5.610515
          8.867089
    387
          0.742929
    388
          2.357353
    389
    390
          2.650814
```

```
Name: x1, Length: 392, dtype: float64 0
                                          -2.637008
     -7.198506
1
      -4.965669
2
3
      8.318951
      5.610515
387
      8.867089
388
      0.742929
389
      2.357353
     2.650814
390
391 -7.072400
Name: x1, Length: 392, dtype: float64
```

Get a slice of your data set: second and thrid columns and rows from 62 to 72

1 df.iloc[62:72, 2:4]

	x2	х3	
62	-8.021386	-8.064350	11
63	6.346805	8.935645	
64	7.172351	11.568654	
65	0.237704	-6.323923	
66	8.952647	-1.928209	
67	6.119641	-0.663169	
68	9.973920	-1.747450	
69	12.474618	9.468129	
70	-3.208477	-10.540776	
71	6.457696	-5.976781	

For the second and thrid columns, calculate the number of null and not null values and verify that their sum equals the total number of rows

```
1 columnas = ['x2','x3']
3 print('Null values: \n', df[columnas].isnull().sum())
4 print('Not Null values: \n', df[columnas].notnull().sum())
5 print('Total number of rows:', df.shape[0])
6
8 print(df.shape[0]==df[columnas].notnull().sum())
   Null values:
   x2 0
x3 0
   dtype: int64
   Not Null values:
         392
    x3 392
    dtype: int64
    Total number of rows: 392
    x2 True
    x3
         True
    dtype: bool
```

Discard the last column

```
1 df.drop('x4', axis=1, inplace=True)
2
3 df
```

	Unnamed: 0	x1	x2	х3	
0	0	-2.637008	6.469373	-8.065872	11.
1	1	-7.198506	-2.450691	-10.125392	
2	2	-4.965669	-1.941930	-13.139206	
3	3	8.318951	9.783888	9.011195	
4	4	5.610515	9.479026	9.551860	
387	387	8.867089	8.961678	9.061760	
388	388	0.742929	8.652554	-3.018461	
389	389	2.357353	6.295590	-5.362303	
390	390	2.650814	10.639732	-2.007908	
391	391	-7.072400	-0.704284	-10.758445	
200	41				

392 rows × 4 columns

Next steps: View recommended plots

Questions

Based on the previos results, provide a description of yout dataset


Your response:

My dataset has 392 observations (rows) and 4 variables (columns), it consist of numerical values across four columns labeled x1, x2, x3, and x4. Without any more information, it seems like a tabular dataset with numerical values across different variables.

A3 Data visualization

Plot in the same figure the histogram of two variables

```
1 plt.hist(df['x1'], bins=len(df), alpha=0.8, label='x1')
2 plt.hist(df['x2'], bins=len(df), alpha=0.8, label='x2')
3 plt.title('x1 and x2')
4 plt.xlabel('Values')
5 plt.ylabel('Frequency')
6 plt.legend()
7 plt.show()
```




Based on these plots, provide a description of your data:

Your response here:

We can see that the histogram of x1 and x2 appears to have a roughly symmetric distribution, centered around the mean, with values ranging from negative to positive mostly in range between 5-10. While analyzed separately, there may be some overlap between the distributions of x1 and x2, indicating potential correlation or relationship between these variables


Plot in the same figure the boxplot of two variables

```
1 plt.boxplot([df['x1'], df['x2']])
2 plt.title('Boxplots of x1 and x2')
3 plt.ylabel('Values')
4 plt.xticks([1, 2], ['x1', 'x2'])
5 plt.show()
```



Plot the scatter plot of two variables

```
1 plt.scatter(df.x1, df.x2, color='b', s=50, marker='o', alpha=0.8)
2 plt.title('Scatter Plot between x1 and x2')
3 plt.xlabel('x1')
4 plt.ylabel('x2')
5 plt.show()
```



Ouestions

Based on the previos plots, provide a description of yout dataset

Your response:

Based on the histograms and scatter plot between x1 and x2, both variables exhibit symmetric distributions with values spanning from negative to positive. The scatter plot suggests a positive correlation between x1 and x2, as data points tend to form a linear pattern. We can observ that there are 3 groups (cluster) or even more, but two are more visible.

Loading the dataframe again to recover the fourth column that was eliminated before

```
1 df = pd.read_csv(url)
2
3 df
```

	Unnamed: 0	x1	x2	х3	x4	
0	0	-2.637008	6.469373	-8.065872	10.382298	
1	1	-7.198506	-2.450691	-10.125392	-8.711022	
2	2	-4.965669	-1.941930	-13.139206	-5.410215	
3	3	8.318951	9.783888	9.011195	-3.365455	
4	4	5.610515	9.479026	9.551860	-7.023893	
387	387	8.867089	8.961678	9.061760	-2.688653	
388	388	0.742929	8.652554	-3.018461	6.537593	
389	389	2.357353	6.295590	-5.362303	8.979738	
390	390	2.650814	10.639732	-2.007908	11.072933	
391	391	-7.072400	-0.704284	-10.758445	-6.019089	
392 r	ows × 5 columr	ıs				

Next steps: View recommended plots

A4 Kmeans

Do Kmeans clustering assuming a number of clusters according to your scatter plot

```
1 K = 3
3 km = KMeans(n_clusters=K, n_init="auto")
5 yestimated = km.fit_predict(df[['x1','x2','x3','x4']])
6
8 yestimated
    \mathsf{array}([\,0,\ 2,\ 2,\ 1,\ 1,\ 1,\ 1,\ 2,\ 2,\ 1,\ 1,\ 2,\ 0,\ 0,\ 2,\ 1,\ 1,\ 1,\ 1,\ 2,\ 0,\ 2,
           2, 1, 1, 0, 1, 0, 0, 1, 0, 0, 0, 1, 0, 2, 0, 1, 1, 0, 1, 1, 1, 2,
           1, 1, 2, 1, 1, 1, 1, 0, 0, 1, 1, 1, 1, 1, 1, 1, 0, 2, 2, 1, 1, 2,
           0,\ 0,\ 0,\ 1,\ 2,\ 0,\ 1,\ 1,\ 0,\ 0,\ 2,\ 0,\ 1,\ 1,\ 1,\ 1,\ 0,\ 1,\ 1,\ 1,\ 1,
           1, 2, 2, 0, 1, 2, 1, 0, 1, 1, 2, 0, 2, 1, 1, 0, 1, 0, 2, 1, 1, 0,
           1, 2, 1, 2, 1, 1, 1, 2, 1, 0, 2, 1, 0, 2, 2, 2, 0, 1, 0, 2, 1, 0,
           1, 2, 2, 1, 1, 2, 1, 1, 1, 1, 2, 1, 2, 1, 0, 1, 1, 2, 1, 1, 1,
           0, 2, 2, 2, 1, 2, 2, 1, 1, 1, 1, 2, 1, 0, 0, 1, 2, 2, 0, 1, 1, 1,
           1, 2, 1, 0, 1, 1, 2, 2, 1, 0, 1, 1, 1, 1, 1, 1, 1, 0, 0, 2, 0, 2,
           2, 1, 1, 1, 0, 1, 0, 0, 1, 0, 1, 1, 0, 1, 0, 2, 1, 0, 1, 1, 0,
           2, 1, 0, 1, 1, 1, 1, 2, 0, 1, 1, 1, 2, 1, 1, 0, 1, 1, 2, 2, 1, 0,
           1, 1, 0, 0, 1, 1, 1, 2, 0, 1, 1, 0, 1, 1, 0, 2, 1, 2, 0, 1, 2, 1,
           1, 1, 1, 1, 2, 1, 1, 2, 0, 1, 0, 1, 2, 1, 0, 1, 1, 2, 2, 0, 0, 1,
           1, 1, 0, 0, 1, 0, 0, 1, 2, 1, 2, 0, 1, 0, 1, 2, 1, 1, 2, 1, 1, 2,
           2, 1, 1, 2, 1, 0, 0, 1, 1, 0, 1, 0, 1, 2, 1, 2, 1, 1, 2, 1, 1, 1,
           0, 1, 2, 2, 1, 2, 2, 0, 1, 1, 0, 1, 0, 2, 2, 0, 1, 2, 2, 2, 2,
```

```
2, 1, 0, 1, 2, 1, 1, 1, 2, 1, 2, 2, 0, 0, 1, 0, 1, 1, 2, 0, 0, 2, 0, 0, 1, 2, 2, 0, 0, 0, 1, 1, 1, 2, 0, 1, 0, 0, 0, 2], dtype=int32)
```

Add to your dataset a column with the estimated cluster to each data point

```
1 df['yestimated'] = yestimated
2
3 df
```

	Unnamed: 0	x1	x2	x3	x4	yestimated			
0	0	-2.637008	6.469373	-8.065872	10.382298	0	11.		
1	1	-7.198506	-2.450691	-10.125392	-8.711022	2			
2	2	-4.965669	-1.941930	-13.139206	-5.410215	2			
3	3	8.318951	9.783888	9.011195	-3.365455	1			
4	4	5.610515	9.479026	9.551860	-7.023893	1			
387	387	8.867089	8.961678	9.061760	-2.688653	1			
388	388	0.742929	8.652554	-3.018461	6.537593	0			
389	389	2.357353	6.295590	-5.362303	8.979738	0			
390	390	2.650814	10.639732	-2.007908	11.072933	0			
391	391	-7.072400	-0.704284	-10.758445	-6.019089	2			
392 rd	392 rows × 6 columns								

002 10W3 ·· 0 00IdiTill3

Next steps: View recommended plots

Print the number associated to each cluster

```
1 df.yestimated.unique()
```

```
array([0, 2, 1], dtype=int32)
```

Print the centroids

1 km.cluster_centers_

```
array([[ 2.74604124, 7.39604345, -5.00441767, 9.52674172], [ 8.13425613, 8.93631206, 9.29529553, -5.3125144 ], [ -6.32129211, -1.710573 , -8.21599227, -7.4539196 ]])
```


Print the intertia metric

1 km.inertia_

6864.785555633871

Plot a scatter plot of your data using different color for each cluster. Also plot the centroids

```
1 df0 = df[df.yestimated==0]
2 df1 = df[df.yestimated==1]
3 df2 = df[df.yestimated==2]
4
5
6 # Scatter plot of each cluster
7 plt.scatter(df0.x1, df0.x2, label='Cluster 0', c='r', marker='o', s=32, alpha=0.3)
8 plt.scatter(df1.x1, df1.x2, label='Cluster 1', c='g', marker='o', s=32, alpha=0.3)
9 plt.scatter(df2.x1, df2.x2, label='Cluster 2', c='b', marker='o', s=32, alpha=0.3)
10
11 # Plot centrodides
12 plt.scatter(km.cluster_centers_[:,0], km.cluster_centers_[:,1], color='black', marker='*', label='Centroides', s=256)
13
14 plt.title('Scatter plot using x1 and x2')
15 plt.xlabel('x1')
16 plt.ylabel('x2')
17 plt.legend()
18 plt.show()
```



Ouestions

Provides a detailed description of your results

Your response:


We can see that creating 3 cluster points is pretty acurate, on this scatter plot we only use x1 and x2, but to know for sure if using any other variable will be as precise we can create and albow point. Just to verify that the number of cluster points is correct.

A5 Elbow plot

Compute the Elbow plot

```
1 sse = []
2
3 # Define values of k
4 \text{ k\_rng} = \text{range}(1,10)
6 # For each k
7 for k in k_rng:
8
      # Create model
      km = KMeans(n_clusters=k, n_init="auto")
9
       # Do K-means clustering
       km.fit_predict(df[['x1','x2', 'x3', 'x4']])
11
12
       # Save sse for each k
13
       sse.append(km.inertia_)
```

```
1 plt.plot(k_rng,sse, 'o-', markersize=8)
2
3 plt.title('Elbow plot')
4 plt.xlabel('K')
5 plt.ylabel('Sum of squared error')
6 plt.show()
```



Questions

What is the best number of clusters K? (argue your response)

Your response: K = 3, we can be sure of this because on the elbow plot, thats where the decrease rate gets lower.

Does this number of clusters agree with your inital guess? (argue your response, no problem at all if they do not agree)

Your response:

Yes, the agreement between the number of clusters obtained from the elbow point method and the initial guess suggests that the structure of the data aligns well with the prior assumption regarding the number of distinct groups or clusters present. This agreement validates the initial hypothesis and indicates that the clustering algorithm successfully captured the inherent patterns in the data. It also enhances the interpretability and consistency of the analysis, providing confidence in the understanding of the data's organization.

PART 2

Descipcion de tu percepcion del nivel de desarrollo de la subcompetencia

SING0202A Interpretación de variables

Escribe tu description del nivel de logro del siguiente criterio de la subcompetencia

Interpreta interacciones. Interpreta interacciones entre variables relevantes en un problema, como base para la construcción de modelos bivariados basados en datos de un fenómeno investigado que le permita reproducir la respuesta del mismo.

Tu respuesta:

En base a esta subcompetencia, creo que la interpretación de variables es fácil de desarrollar. Siempre tenemos que comprender el tipo de información con la que estamos trabajando, ya sean números enteros, flotantes, o incluso strings, y de esta forma será más fácil de comprender el uso o el origen de estas variables. Cuando no viene ninguna descripción o interpretación de las variables es necesario analizar toda la información para poder darle una interpretación y sea así más fácil su manejo para desarrollar modelos y utilizar la información de manera sencilla y correcta.

Escribe tu description del nivel de logro del siguiente criterio de la subcompetencia

B1_MySolution.ipynb - Colaboratory

Construcción de modelos. Es capaz de construir modelos bivariados que expliquen el comportamiento de un fenómeno.

Tu respuesta:

Gracias a la evidencia puedo comprobar que soy capaz de contruir modelos bivariados, manejando de manera correcta las variables, comprendiendo su tipo e incluso interpretando su significado para poder visualizar la información, y así usarla con fines de modelos de entrenamiento de IA.

1 #FINAL DEL DOCUMENTO

2 #