Android engineer terminal tool v.1.1 stable

Date: November 21, 2011

Author: Jessay Chen

Abstact

This is a debugging tool HyperTerminal android I2C, according to the characters in brackets corresponding command execution, run the platform arm9, arm11.

Need to save the raw data of the user, the program copied to "/ data" path, the path for the user to read and write.

1. Install and run.

To pixi2c copied to the system through the HyperTerminal program execution into the appropriate directory, such as the menu display:



If the device displays the following error appears, look /dev/pixcir_i2c_ts0

2. Calibrate

Press 'C' key to do “Calibrate”, the correct result as follows:



If fails, display “Calibrate failed”.

3. Debug mode

Press 'D' key to do “Debug mode”, press ‘Enter’ to stop, shown below:



4. Internal mode

Press 'I' key to do “Internal mode”, press ‘Enter’ to stop, shown below:



5. Raster mode

Press 'S' key to do “Raster mode”, press “Enter”to stop, shown below:



6. Bootloader

Press 'B' key to do “Bootloader”, shown below:



Show "Download Successfully.", if it fails displays "Download failed".

7. Read EEPROM

Press 'R' key to do “Read EEPROM”, input address and bytes, such as:



8. Read CRC

press 'Z' key to do “read CRC”, shown below:



9. TP Reset

Press 'T' key to do “TP Reset”, such as:

10. About

Press 'A' key to do “About”, such as:



11. Show menu and Exit

Press 'M' key to do “Show menu again”, press the 'X' to exit , as follows: