# Session 4 Handout

# 1. Using while loops

The following code assumes that you have a correct orderQuantity function from last session in a session3.py file in the current directory.

```
[1]: from session3 import orderQuantity
     while True:
         userInput=input('Enter inventory (or done): ')
         if userInput=='done':
             break
         elif userInput=='skip':
             continue
         inventory=int(userInput)
         print ('Order', orderQuantity(inventory), 'units.')
Enter inventory (or done): skip
Enter inventory (or done): 30
Order 70 units.
Enter inventory (or done): 25
Order 75 units.
Enter inventory (or done): done
 Alternative implementation without using break or continue.
[]: userInput=input('Enter inventory (or done): ')
     while userInput!='done':
         if userInput!='skip':
             inventory=int(userInput)
             print ('Order', orderQuantity(inventory), 'units.')
         userInput=input('Enter inventory (or done): ')
```

**Q1:** Write a program to repeatedly ask the user to input the number of hours worked, and display the total pay, assuming that the rate for first 40 hours is 10/hour, and the rate for additional hours is 15/hour. The program should terminate whenever the user inputs done.

#### [2]:

```
Enter hours worked (or done): 38
Pay is 380.0
Enter hours worked (or done): 42
Pay is 430.0
Enter hours worked (or done): done
```

(optional) Q2: Rewrite the code in Q1 but do not use break.

The following function uses try and except (see PY4E Chapter 3) for checking whether a certain value is convertable to a float.

```
[3]: def isNumber(x): try:
```

```
float(x)
    return True
    except:
        return False

    print(isNumber(3))
    print(isNumber('3'))
    print(isNumber('three'))

True
True
False
```

Q3: Modify the first example of this handout so that if the user does not input done nor an integer, then the program prints Invalid input. and asks for another input. (Hint: first write an isInteger(x) function by modifying the above, then use an if statement to decide whether to convert the input to an integer, or display Invalid input.)

### [4]:

```
Enter inventory (or done): 2.5
Invalid input.
Enter inventory (or done): 30
Order 70 units.
Enter inventory (or done): thirty
Invalid input.
Enter inventory (or done): done
```

# 2. Using for loops

**Q4:** Modify the first example of the handout to use a for loop instead of a while loop, and limit the number of iterations to at most 5.