

Sample Order Status API Responses

Merchant: Corp Culture | Merchant ID: SG5903 | Environment: UAT

API: GET https://smartgateway.hdfcuat.bank.in/orders/{order_id}

Purpose: Sample responses stored/used during dual inquiry verification for HDFC bank audit.

Prepared on: 12 September 2026

1. SUCCESS (CHARGED) - Sample

Use case: Payment completed successfully. Dual inquiry returns matching CHARGED status and amount.

```
{
  "id": "ordeh_uat_7f3a91c2b8e04d1a",
  "order_id": "CCMTXW58UT2Z5BHE",
  "status": "CHARGED",
  "status_id": 21,
  "amount": 1250.00,
  "currency": "INR",
  "customer_id": "C66F1A2B3C4D5E6F7G8",
  "customer_email": "customer@example.com",
  "customer_phone": "9876543210",
  "payment_method": "UPI",
  "payment_method_type": "UPI",
  "txn_id": "HDFCUATTXN240912001",
  "txn_uuid": "txn_uat_9c21ab44",
  "date_created": "2026-09-12T10:15:22Z",
  "payment_gateway_response": {
    "rrn": "425612349876",
    "epg_txn_id": "EPG425612349876",
    "auth_id_code": "A1B2C3",
    "resp_code": "00",
    "resp_message": "Transaction Successful"
  },
  "txn_detail": {
    "status": "CHARGED",
    "gateway": "HDFC",
    "rrn": "425612349876",
    "txn_id": "HDFCUATTXN240912001"
  },
  "udf1": null,
  "udf2": null,
  "udf3": null,
  "udf4": null,
  "udf5": null
}
```

2. FAILED (AUTHORIZATION_FAILED) - Sample

Use case: Customer payment declined / authorization failed.

```
{
  "id": "ordeh_uat_11aa22bb33cc44dd",
  "order_id": "CCN8K2P9Q1R4S7T0",
  "status": "AUTHORIZATION_FAILED",
  "status_id": 27,
  "amount": 899.00,
  "currency": "INR",
  "customer_id": "C66F1A2B3C4D5E6F7G8",
  "customer_email": "customer@example.com",
  "customer_phone": "9876543210",
  "payment_method": "CARD",
  "payment_method_type": "CARD",
  "txn_id": "HDFCUATTXN240912002",
  "date_created": "2026-09-12T11:02:10Z",
  "payment_gateway_response": {
    "rrn": "NA",

```

```
{
  "epg_txn_id": "NA",
  "auth_id_code": "NA",
  "resp_code": "05",
  "resp_message": "Do not honour / Authorization failed"
},
"txn_detail": {
  "status": "AUTHORIZATION_FAILED",
  "gateway": "HDFC",
  "rrn": "NA"
},
"udf2": null
}
```

3. PENDING (PENDING_VBV / AUTHORIZING) - Sample

Use case: UPI collect / 3DS in progress. Merchant keeps polling Status API (dual inquiry).

```
{
  "id": "ordeh_uat_55ee66ff77889900",
  "order_id": "CCP1A2B3C4D5E6F7",
  "status": "PENDING_VBV",
  "status_id": 23,
  "amount": 2499.50,
  "currency": "INR",
  "customer_id": "C66F1A2B3C4D5E6F7G8",
  "customer_email": "customer@example.com",
  "customer_phone": "9876543210",
  "payment_method": "UPI",
  "payment_method_type": "UPI",
  "txn_id": "HDFCUATTXN240912003",
  "date_created": "2026-09-12T11:20:45Z",
  "payment_gateway_response": {
    "rrn": "NA",
    "epg_txn_id": "NA",
    "auth_id_code": "NA",
    "resp_code": "PENDING",
    "resp_message": "Awaiting customer approval"
  },
  "txn_detail": {
    "status": "PENDING_VBV",
    "gateway": "HDFC",
    "rrn": "NA"
  },
  "udf2": null
}
```

4. Dual Inquiry Snapshot (as stored by merchant)

On response/verify, Status API is called twice. Merchant stores both results for audit.

```
{
  "id": "ordeh_uat_7f3a91c2b8e04d1a",
  "status": "CHARGED",
  "amount": 1250.00,
  "currency": "INR",
  "order_id": "CCMTXW58UT2Z5BHE",
  "payment_method": "UPI",
  "txn_id": "HDFCUATTXN240912001",
  "txn_detail": {
    "status": "CHARGED",
    "gateway": "HDFC",
    "rrn": "425612349876"
  },
  "payment_gateway_response": {
    "rrn": "425612349876",
    "epg_txn_id": "EPG425612349876",
    "auth_id_code": "A1B2C3",
    "resp_message": "Transaction Successful"
  }
}
```

```
{,
  "capturedAt": "2026-09-12T10:16:05.120Z",
  "dualInquiry": {
    "consistent": true,
    "firstStatus": "CHARGED",
    "secondStatus": "CHARGED",
    "firstAmount": 1250.00,
    "secondAmount": 1250.00
  }
}
```

5. Merchant handling notes

- Success: status = CHARGED (and dual inquiry consistent) AND amount >= session amount => mark Paid, show success page.
- Failed: AUTHORIZATION_FAILED / AUTHENTICATION_FAILED / JUSPAY_DECLINED / FAILED => mark Failed.
- Pending: NEW / PENDING_VBV / AUTHORIZING => keep polling; do not fulfill order.
- UDF2 is not used.
- Order ID example length: CCMTXW58UT2Z5BHE = 16 chars (< 21), alphanumeric, non-sequential.