

Create and rotate a triangle about the origin and a fixed point.

```
#include<GL/glut.h>
#include<stdio.h>

int x,y;
int rFlag=0;

void draw_pixel(float x1,float y1)
{
    glColor3f(0.0,0.0,1.0);
    glPointSize(5.0);
    glBegin(GL_POINTS);
    glVertex2f(x1,y1);
    glEnd();
}

void triangle()
{
    glColor3f(1.0,0.0,0.0);
    glBegin(GL_POLYGON);
        glVertex2f(100,100);
        glVertex2f(250,400);
        glVertex2f(400,100);
    glEnd();
}

float th=0.0;
float trX=0.0,trY=0.0;
void display()
{
    glClear(GL_COLOR_BUFFER_BIT);
    glLoadIdentity();

    if(rFlag==1) //Rotate Around origin
    {
        trX=0.0;
        trY=0.0;
        th+=0.1;
        draw_pixel(0.0,0.0);
    }
    if(rFlag==2) //Rotate Around Fixed Point
    {
```

```

    trX=x;
    trY=y;
    th+=0.1;
    draw_pixel(x,y);
}
glTranslatef(trX,trY,0.0);
glRotatef(th,0.0,0.0,1.0);
glTranslatef(-trX,-trY,0.0);
triangle();
glutPostRedisplay();
glutSwapBuffers();
}
void myInit()
{
    glClearColor(0.0,0.0,0.0,1.0);
    glMatrixMode(GL_PROJECTION);
    glLoadIdentity();
    gluOrtho2D(-500.0, 500.0, -500.0, 500.0);
    glMatrixMode(GL_MODELVIEW);
}

```

```

void rotateMenu (int option)
{
    if(option==1)
        rFlag=1;
    if(option==2)
        rFlag=2;
    if(option==3)
        rFlag=3;
}
void main(int argc, char **argv)
{
    printf( "Enter Fixed Points (x,y) for Roration: \n");
    scanf("%d %d", &x, &y);
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_DOUBLE|GLUT_RGB);
    glutInitWindowSize(500, 500);
    glutInitWindowPosition(0, 0);
    glutCreateWindow("Create and Rotate Triangle");
    myInit();
    glutDisplayFunc(display);
    glutCreateMenu(rotateMenu);
    glutAddMenuEntry("Rotate around ORIGIN",1);
    glutAddMenuEntry("Rotate around FIXED POINT",2);
}

```

```
glutAddMenuEntry("Stop Rotation",3);  
glutAttachMenu(GLUT_RIGHT_BUTTON);  
glutMainLoop();  
}
```

OUTPUT :



