

Bootstrap5

=====

It most popular HTML, CSS , JavaScript framework developed by Twitter to develop web applications.

It is absolutely free to download and use.

It is developed by Mark Otto and Jacob Thornton at Twitter.

It was released to the public on GITHUB in 2011.

Bootstrap contains HTML and CSS based design templates for typography , forms, tables, buttons and etc.

It contains number of javascript plugins.

Bootstrap4 was release on January 18 , 2018.

Bootstrap5 was the extension of Bootstrap4 was release on May 5, 2021.

Advantages of Bootstrap

=====

1) It is easy to learn and easy to use.

2) It is used to develop responsive web designs.

3) It saves lot of development time.

4) It is a consistent framework.

5) Good documentation and community support.

6) It supports greates Grid System.

7) It contains javascript plugin's along with Juery.

Bootstrap color

=====

By using utility classes change the color of a text.

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>mypage!</title>
```

```
    <!-- bootstrap cdn link -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
></script>
```

```
</head>
```

```
<body>
```

```
  <h1 class="text-primary"> text primary </h1>
```

```
  <h1 class="text-secondary"> text secondary </h1>
```

```
  <h1 class="text-info"> text info </h1>
```

```
  <h1 class="text-warning"> text warning </h1>
```

```
  <h1 class="text-success"> text success </h1>
```

```
  <h1 class="text-danger"> text danger </h1>
```

```
  <h1 class="text-light"> text light </h1>
```

```
  <h1 class="text-dark"> text dark </h1>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>mypage!</title>
```

```
  <!-- bootstrap cdn link -->
```

```
  <meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
></script>

<style type="text/css">
    .text-brown
    {
        color:#B33771;
    }
</style>

</head>
<body>
    <h1 class="text-primary"> text primary </h1>
    <h1 class="text-secondary"> text secondary </h1>
    <h1 class="text-info"> text info </h1>
    <h1 class="text-warning"> text warning </h1>
    <h1 class="text-success"> text success </h1>
    <h1 class="text-danger"> text danger </h1>
    <h1 class="text-light"> text light </h1>
    <h1 class="text-dark"> text dark </h1>
    <h1 class="text-brown"> text Brown </h1>
</body>
</html>
```

Bootstrap background

=====

In bootstrap background color can be applied to any element/tag.

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>mypage!</title>
```

```
    <!-- bootstrap cdn link -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
    rel="stylesheet">
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
    ></script>
```

```
    <style type="text/css">
```

```
        .bg-brown
```

```
        {
```

```
            background-color:#B33771;
```

```
        }
```

```
</style>

</head>
<body>
    <h1 class="bg-primary"> text primary </h1>
    <h1 class="bg-secondary"> text secondary </h1>
    <h1 class="bg-info"> text info </h1>
    <h1 class="bg-warning"> text warning </h1>
    <h1 class="bg-success"> text success </h1>
    <h1 class="bg-danger"> text danger </h1>
    <h1 class="bg-light"> text light </h1>
    <h1 class="bg-dark"> text dark </h1>
    <h1 class="bg-brown"> text Brown </h1>
</body>
</html>
```

Bootstrap border

=====

Border utility is used to change quickly the border-style and border-radius of an element.

It is mainly used for images, buttons and etc.

we can use border classes to an element to remove all borders or add some borders.

Add classes to an element to easily rounds its corners.

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>mypage!</title>
```

```
    <!-- bootstrap cdn link -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
></script>
```

```
</head>
```

```
<body>
```

```
    <span class="border"> span1 tag</span>
```

```
    <span class="border-top"> span2 tag </span>
```

```
    <span class="border-start"> span3 tag </span>
```

```
    <span class="border-bottom"> span4 tag </span>
```

```
    <span class="border-end"> span5 tag </span>
```

```
</body>
```

```
</html>
```

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>mypage!</title>
```

```
    <!-- bootstrap cdn link -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
></script>
```

```
</head>
```

```
<body>
```

```
    <span class="border border-primary"> span1 tag</span>
```

```
    <span class="border-top border-info"> span2 tag </span>
```

```
    <span class="border-start border-danger"> span3 tag </span>
```

```
    <span class="border-bottom border-success"> span4 tag </span>
```

```
    <span class="border-end border-dark"> span5 tag </span>
```

```
</body>
```

```
</html>
```


ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>mypage!</title>
```

```
  <!-- bootstrap cdn link -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
  rel="stylesheet">
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
  ></script>
```

```
</head>
```

```
<body>
```

```
  
```

```
  
```

```

```

```

```

```

```

```
</body>
```

```
</html>
```

Bootstrap sizing

=====

IT is used to size the element by using sizing utility classes.

we can easily make an element wide or a tall with our width and height utility.

It supports for 25%,50%,75% and 100% by default.

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>MyPage!</title>
```

```
  <!-- add bootstrap plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
  <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"></script>
```

```
  <style>
```

```
    .w-60
```

```
    {
```

```
      width:60%;
```

```
    }
```

```
  </style>
```

```
</head>
<body>
  <br>

  <div class="bg-primary w-25">Div1</div>
  <div class="bg-info w-50">Div2</div>
  <div class="bg-warning w-75">Div3</div>
  <div class="bg-success w-100">Div4</div>
  <div class="bg-danger w-60">Div5</div>
</body>
</html>
```

ex:

```
<!DOCTYPE html>
<html>
<head>
  <title>mypage!</title>
  <!-- bootstrap cdn link -->
  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-scale=1">

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
></script>
```

```
</head>
```

```
<body>
```

```
    
```

```
    <br>
```

```
    
```

```
    <br>
```

```
    
```

```
    <br>
```

```
    
```

```
</body>
```

```
</html>
```

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>mypage!</title>
```

```

    <!-- bootstrap cdn link -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
    rel="stylesheet">

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
    ></script>

    <style type="text/css">
        .w-60
        {
            width:60%;
        }
        .h-60
        {
            height:60%;
        }
    </style>
</head>
<body>
    

    <br>
    

```

```
<br>


<br>


<br>

```

```
</body>
```

```
</html>
```

Bootstrap containers

=====

Containers are used to pad the content inside of them.

In bootstrap there are two containers classes available.

1)container-fluid

2)container

ex:

```
<!DOCTYPE html>
```

```

<html>
<head>
    <title>mypage!</title>
    <!-- bootstrap cdn link -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
></script>

</head>
<body>

    <div class="container-fluid bg-info">
        <h1>Heading Tag</h1>
        <p>Paragraph Tag</p>
    </div>

</body>
</html>

```

ex:

```
<!DOCTYPE html>
```



```

<html>
<head>
    <title>mypage!</title>
    <!-- bootstrap cdn link -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"
></script>

</head>
<body>

    <div class="container bg-warning">
        <h1>Heading Tag</h1>
        <p>Paragraph Tag</p>
    </div>

</body>
</html>

```

Bootstrap Display

=====

We have following list of bootstrap display utility classes.

ex:

d-none

d-block

d-inline

d-inline-block

d-none

<!DOCTYPE html>

<html>

<head>

<title>MyPage!</title>

<!-- add bootstrap plugins -->

<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

</head>

<body>

<div class="container">

<h1 class="d-none"> This is Heading Tag </h1>

<p class="d-none"> This is paragraph Tag </p>

</div>

```

        </body>
</html>

d-block
-----

<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <!-- add bootstrap plugins -->
        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>
        <div class="container">
            <span class="d-block"> It is a inline element </span>
            <span class="d-block"> It is a inline element </span>
            <span class="d-block"> It is a inline element </span>
        </div>

```

```

        </body>
</html>

d-inline
-----

<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <!-- add bootstrap plugins -->
        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>
        <div class="container">
            <div class="d-inline"> This is div1 tag</div>
            <div class="d-inline"> This is div2 tag</div>
            <div class="d-inline"> This is div3 tag</div>
        </div>

```

```

        </body>
</html>

d-inline-block
-----

<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <!-- add bootstrap plugins -->
        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>
        <div class="container-fluid">
            <span class="border border-primary d-inline-block w-25"> Span1
tag</span>
            <span class="border border-secondary d-inline-block w-25"> Span2
tag</span>

```

```
        <span class="border border-info d-inline-block w-25"> Span3 tag</span>
    </div>

</body>
</html>
```

Bootstrap spacing

=====

Spacing utility is used to assign the responsive friendly margin or padding values to an element or a subset of its sides with shorthand classes.

It includes individual properties , all properties ,vertical properties and horizontal properties.

bootstrap margin

=====

m - for classes that set margin

Where sides is one of:

t - for classes that set margin-top or padding-top

b - for classes that set margin-bottom or padding-bottom

s - (start) for classes that set margin-left or padding-left in LTR, margin-right or padding-right in RTL

e - (end) for classes that set margin-right or padding-right in LTR, margin-left or padding-left in RTL

x - for classes that set both *-left and *-right

y - for classes that set both *-top and *-bottom

blank - for classes that set a margin or padding on all 4 sides of the element

Where size is one of:

0 - for classes that eliminate the margin or padding by setting it to 0

1 - (by default) for classes that set the margin or padding to \$spacer * .25

2 - (by default) for classes that set the margin or padding to \$spacer * .5

3 - (by default) for classes that set the margin or padding to \$spacer

4 - (by default) for classes that set the margin or padding to \$spacer * 1.5

5 - (by default) for classes that set the margin or padding to \$spacer * 3

auto - for classes that set the margin to auto

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
<body>
    <div class="container">

        <h1 class="border border-primary m-1">This is heading 1</h1>
        <h1 class="border border-primary m-2">This is heading 2</h1>
        <h1 class="border border-primary m-3">This is heading 3</h1>
        <h1 class="border border-primary m-4">This is heading 4</h1>
        <h1 class="border border-primary m-5">This is heading 5</h1>

    </div>
</body>
</html>
```

ex:

```
<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">
```



```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
<div class="container-fluid">
```

```
<h1 class="border border-primary mt-5">This is heading 1</h1>
```

```
<h1 class="border border-primary mb-5">This is heading 2</h1>
```

```
<h1 class="border border-primary ms-5">This is heading 3</h1>
```

```
<h1 class="border border-primary me-5">This is heading 4</h1>
```

```
<h1 class="border border-primary mx-5">This is heading 5</h1>
```

```
<h1 class="border border-primary my-5">This is heading 6</h1>
```

```
</div>
```

```
</body>
```

```
</html>
```

Bootstrap padding

=====

p - for classes that set padding

Where sides is one of:

t - for classes that set margin-top or padding-top

b - for classes that set margin-bottom or padding-bottom

s - (start) for classes that set margin-left or padding-left in LTR, margin-right or padding-right in RTL

e - (end) for classes that set margin-right or padding-right in LTR, margin-left or padding-left in RTL

x - for classes that set both *-left and *-right

y - for classes that set both *-top and *-bottom

blank - for classes that set a margin or padding on all 4 sides of the element

Where size is one of:

0 - for classes that eliminate the margin or padding by setting it to 0

1 - (by default) for classes that set the margin or padding to \$spacer * .25

2 - (by default) for classes that set the margin or padding to \$spacer * .5

3 - (by default) for classes that set the margin or padding to \$spacer

4 - (by default) for classes that set the margin or padding to \$spacer * 1.5

5 - (by default) for classes that set the margin or padding to \$spacer * 3

auto - for classes that set the margin to auto

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
<div class="container-fluid">
```

```
<h1 class="border border-primary p-1">This is heading 1</h1>
```

```
<h1 class="border border-primary p-2">This is heading 2</h1>
```

```
<h1 class="border border-primary p-3">This is heading 3</h1>
```

```
<h1 class="border border-primary p-4">This is heading 4</h1>
```

```
<h1 class="border border-primary p-5">This is heading 5</h1>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>

  <head>

    <title>MyPage!</title>

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">

    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>

  </head>
  <body>

    <div class="container-fluid">

      <h1 class="border border-primary pt-5">This is heading 1</h1>
      <h1 class="border border-primary pb-5">This is heading 2</h1>
      <h1 class="border border-primary ps-5">This is heading 3</h1>
      <h1 class="border border-primary pe-5">This is heading 4</h1>
      <h1 class="border border-primary px-5">This is heading 5</h1>
      <h1 class="border border-primary py-5">This is heading 6</h1>

    </div>

  </body>
</html>
```

Bootstrap 5 Grid System

=====

Bootstrap's grid system is built with flexboxes.

To create a row in a grid system we need to use "row" class.

It allows to create 12 columns in a single row and It is not required that we must use all 12 columns.

The Grid system is responsive and the column will rearrange automatically dependent upon the screen size.

Grid class

According Bootstrap5 ,A grid system contains 6 classes.

col- - extra small device

col-sm- - small devices

col-md- - medium devices

col-lg- - large devices

col-xl- - xlarge devices.

col-xxl- - too xlarge device

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
    <div class="row">
```

```
      <!-- 1 column occupies 12 column space -->
```

```
        <div class="col bg-primary">column1</div>
    </div>

</div>

</body>
</html>
```

ex:2

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

</head>
<body>

    <div class="container-fluid mt-5">
```

```

        <div class="row">
            <!-- 2 columns occupies 6 column space -->
            <div class="col bg-primary">column1</div>

            <div class="col bg-info">column2</div>
        </div>

    </div>

</body>
</html>

```

ex:3

```

<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

```



```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
    <div class="container-fluid mt-5">
```

```
        <div class="row">
```

```
            <!-- 3 columns occupies 4 column space -->
```

```
            <div class="col bg-primary">column1</div>
```

```
            <div class="col bg-info">column2</div>
```

```
            <div class="col bg-warning">column3</div>
```

```
        </div>
```

```
    </div>
```

```
</body>
```

```
</html>
```

ex:4

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
<!-- add bootstrap 5 plugins -->

<meta charset="utf-8">


<meta name="viewport" content="width=device-width, initial-scale=1">


<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >


<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>


</head>
<body>

    <div class="container-fluid mt-5">

        <div class="row">

            <!-- 4 columns occupies 3 column space -->
            <div class="col bg-primary">column1</div>

            <div class="col bg-info">column2</div>

            <div class="col bg-warning">column3</div>

            <div class="col bg-success">column4</div>

        </div>

    </div>
```

```
</body>
```

```
</html>
```

ex:5

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
    <div class="container-fluid mt-5">
```

```
        <div class="row">
```

```
            <!-- 5 columns occupies 3 column space -->
```

```
            <div class="col bg-primary">column1</div>
```

```
<div class="col bg-info">column2</div>
```

```
<div class="col bg-warning">column3</div>
```

```
<div class="col bg-success">column4</div>
```

```
<div class="col bg-danger">column5</div>
```

```
</div>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:6

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
    <div class="container-fluid mt-5">
```

```
        <div class="row">
```

```
            <div class="col-2 bg-primary">column1</div>
```

```
            <div class="col-4 bg-info">column2</div>
```

```
            <div class="col-6 bg-warning">column3</div>
```

```
        </div>
```

```
    </div>
```

```
</body>
```

```
</html>
```

ex:7

```
<!DOCTYPE html>
```

```
<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>

</head>

<body>

    <div class="container-fluid mt-5">

        <div class="row">

            <div class="col-lg-4 bg-primary">column1</div>

            <div class="col-lg-4 bg-info">column2</div>

            <div class="col-lg-4 bg-warning">column3</div>

        </div>

        <br><br>

        <div class="row">

            <div class="col-lg-4 col-md-4 bg-primary">column1</div>

            <div class="col-lg-4 col-md-4 bg-info">column2</div>
```

```

        <div class="col-lg-4 col-md-4 bg-warning">column3</div>
    </div>
    <br><br>
    <div class="row">
        <div class="col-lg-4 col-md-4 col-sm-4 bg-
primary">column1</div>
        <div class="col-lg-4 col-md-4 col-sm-4 bg-info">column2</div>
        <div class="col-lg-4 col-md-4 col-sm-4 bg-
warning">column3</div>
    </div>

    <br><br>
    <div class="row">
        <div class="col-lg-4 col-md-4 col-sm-4 col-12 bg-
primary">column1</div>
        <div class="col-lg-4 col-md-4 col-sm-4 col-12 bg-
info">column2</div>
        <div class="col-lg-4 col-md-4 col-sm-4 col-12 bg-
warning">column3</div>
    </div>

</div>
</body>

</html>

```

Bootstrap images

=====

3 classes to display the images.

1)rounded image (rounded)

2)circle image (rounded-circle)

3)thumbnail (img-thumbnail)

1)rounded image

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```



```

        <div class="container-fluid mt-5">
            
        </div>
    </body>
</html>

```

2)circle image

```

-----
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

</head>
<body>

```

```
        <div class="container-fluid mt-5">
            
        </div>
    </body>
</html>
```

3)thumbnail image

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

</head>
<body>

    <div class="container-fluid mt-5">
```

```
        
    </div>

</body>
</html>
```

Bootstrap float

=====

Bootstrap float is used for alignment of an element.

ex:1

```
<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```

</head>
<body>
    <div class="container-fluid mt-5">
        
        
    </div>
</body>
</html>

```

ex:2

```

<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

```

```

</head>
<body>

    <div class="container-fluid mt-5">

        

    </div>

</body>
</html>

```

Bootstrap Design

=====

```

<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

```

```

</head>
<body>

    <div class="container-fluid mt-5">

        <div class="row">

            <div class="col-lg-4 col-md-4 col-sm-6 col-12">
                
            </div>

            <div class="col-lg-4 col-md-4 col-sm-6 col-12">
                
            </div>

            <div class="col-lg-4 col-md-4 col-sm-6 col-12">
                
            </div>

        </div>

    </div>

</body>
</html>

```

Bootstrap Tables

=====

A table is used to represent our data in the form of rows and columns.

A "table" class is used to represent bootstrap table.

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <!-- add bootstrap plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>
```

```
  </head>
```

```
  <body>
```

```
    <div class="container mt-5">
```

```
      <table class="table">
```

```
        <tr>
```

```
          <th>ID</th>
```

```

                <th>NAME</th>
                <th>EMAIL</th>
            </tr>
            <tr>
                <td>101</td>
                <td>Alan</td>
                <td>alan@gmail.com</td>
            </tr>
            <tr>
                <td>102</td>
                <td>Jose</td>
                <td>jose@zoho.com</td>
            </tr>
            <tr>
                <td>103</td>
                <td>Nelson</td>
                <td>nelson@outlook.com</td>
            </tr>
            <tr>
                <td>104</td>
                <td>Jack</td>
                <td>jack@yahoo.com</td>
            </tr>
        </table>
    </div>
```



```

        </body>
</html>

ex:2
----
<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <!-- add bootstrap plugins -->
        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>

        <div class="container mt-5">

            <table class="table table-bordered">

                <tr>

```

```
<th>ID</th>
<th>NAME</th>
<th>EMAIL</th>
</tr>
<tr>
<td>101</td>
<td>Alan</td>
<td>alan@gmail.com</td>
</tr>
<tr>
<td>102</td>
<td>Jose</td>
<td>jose@zoho.com</td>
</tr>
<tr>
<td>103</td>
<td>Nelson</td>
<td>nelson@outlook.com</td>
</tr>
<tr>
<td>104</td>
<td>Jack</td>
<td>jack@yahoo.com</td>
</tr>
</table>
```

```
        </div>

    </body>
</html>
```

ex:3

```
<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <!-- add bootstrap plugins -->
        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>
        <div class="container mt-5">

            <table class="table table-borderless">
```

```
<tr>
    <th>ID</th>
    <th>NAME</th>
    <th>EMAIL</th>
</tr>
<tr>
    <td>101</td>
    <td>Alan</td>
    <td>alan@gmail.com</td>
</tr>
<tr>
    <td>102</td>
    <td>Jose</td>
    <td>jose@zoho.com</td>
</tr>
<tr>
    <td>103</td>
    <td>Nelson</td>
    <td>nelson@outlook.com</td>
</tr>
<tr>
    <td>104</td>
    <td>Jack</td>
    <td>jack@yahoo.com</td>
</tr>
```

```
</table>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:4

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <!-- add bootstrap plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>
```

```
  </head>
```

```
  <body>
```

```
    <div class="container mt-5">
```

```
<table class="table table-bordered table-striped">
```

```
<tr>
```

```
<th>ID</th>
```

```
<th>NAME</th>
```

```
<th>EMAIL</th>
```

```
</tr>
```

```
<tr>
```

```
<td>101</td>
```

```
<td>Alan</td>
```

```
<td>alan@gmail.com</td>
```

```
</tr>
```

```
<tr>
```

```
<td>102</td>
```

```
<td>Jose</td>
```

```
<td>jose@zoho.com</td>
```

```
</tr>
```

```
<tr>
```

```
<td>103</td>
```

```
<td>Nelson</td>
```

```
<td>nelson@outlook.com</td>
```

```
</tr>
```

```
<tr>
```

```
<td>104</td>
```

```
<td>Jack</td>
```

```
<td>jack@yahoo.com</td>
```

```
</tr>
```

```
        </table>

    </div>

</body>
</html>
```

ex:5

```
<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <!-- add bootstrap plugins -->
        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>
```

```
<div class="container mt-5">
```

```
<table class="table table-bordered table-hover">
```

```
<tr>
```

```
<th>ID</th>
```

```
<th>NAME</th>
```

```
<th>EMAIL</th>
```

```
</tr>
```

```
<tr>
```

```
<td>101</td>
```

```
<td>Alan</td>
```

```
<td>alan@gmail.com</td>
```

```
</tr>
```

```
<tr>
```

```
<td>102</td>
```

```
<td>Jose</td>
```

```
<td>jose@zoho.com</td>
```

```
</tr>
```

```
<tr>
```

```
<td>103</td>
```

```
<td>Nelson</td>
```

```
<td>nelson@outlook.com</td>
```

```
</tr>
```

```
<tr>
```

```
<td>104</td>
```

```
<td>Jack</td>
```



```
 jack@yahoo.com |
```

Bootstrap List

=====

Bootstrap list is used to represent list of items.

A "list-group" class is used to represent unordered list.

A "list-group-item" class is used to represent list of item.

ex:1

```

<!DOCTYPE html>

```

```

<html>

```

```

  <head>

```

```

    <title>MyPage!</title>

```

```

    <!-- add bootstrap plugins -->

```

```

    <meta charset="utf-8">

```

```

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

</head>
<body>

    <div class="container mt-5">

        <ul class="list-group">
            <li class="list-group-item">ReactJS</li>
            <li class="list-group-item">AngularJS</li>
            <li class="list-group-item">VueJS</li>
            <li class="list-group-item">Backbone</li>
        </ul>

    </div>

</body>
</html>

```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>

  <title>MyPage!</title>

  <!-- add bootstrap plugins -->
  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-scale=1">

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

  <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

</head>
<body>

  <div class="container mt-5">
    <div class="w-50 mx-auto">
      <ul class="list-group">
        <li class="list-group-item">ReactJS</li>
        <li class="list-group-item">AngularJS</li>
        <li class="list-group-item">VueJS</li>
        <li class="list-group-item">Backbone</li>
      </ul>
    </div>
  </div>

</body>
```

```
</html>
```

ex:3

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <!-- add bootstrap plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>
```

```
  </head>
```

```
  <body>
```

```
    <div class="container mt-5">
```

```
      <div class="w-50 mx-auto">
```

```
        <ul class="list-group">
```

```
          <li class="list-group-item active">ReactJS</li>
```

```
          <li class="list-group-item">AngularJS</li>
```

```
          <li class="list-group-item">VueJS</li>
```

```

        <li class="list-group-item disabled">Backbone</li>
    </ul>
</div>

</div>

</body>
</html>

```

Bootstrap badge

=====

Bootstrap Badges are used to add additional information to any content like count and label.

ex:1

```

<!DOCTYPE html>

<html>

    <head>

        <title>MyPage!</title>

        <!-- add bootstrap plugins -->

        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

```

```

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>
        <div class="container mt-5">
            <div class="w-50 mx-auto">
                <ul class="list-group">
                    <li class="list-group-item">
                        Likes <span class="badge bg-primary">10</span>
                    </li>
                    <li class="list-group-item">
                        Subscribes <span class="badge bg-info">1K</span>
                    </li>
                    <li class="list-group-item">
                        Shares <span class="badge bg-
warning">10K</span>
                    </li>
                    <li class="list-group-item">
                        Comments <span class="badge bg-
success">1M</span>
                    </li>
                </ul>
            </div>
        </div>
    </body>

```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <!-- add bootstrap plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>
```

```
  </head>
```

```
  <body>
```

```
    <div class="container mt-5">
```

```
      <div class="w-50 mx-auto">
```

```
        <ul class="list-group">
```

```
          <li class="list-group-item">
```

```

HTML <span class="badge bg-
primary">Basic</span>
</li>
<li class="list-group-item">
CSS <span class="badge bg-
info">Intermediate</span>
</li>
<li class="list-group-item">
BOOTSTRAP <span class="badge bg-
warning">Advanced</span>
</li>
<li class="list-group-item">
JAVASCRIPT <span class="badge bg-success">Entry
Level</span>
</li>
</ul>
</div>
</div>
</body>
</html>

```

Bootstrap alerts

=====

A "alert" class is used to represent bootstrap alert.

We can use alert class along with contextual classes.

ex:

alert-danger
alert-info
alert-success
alert-warning
and etc.

ex:1

<!DOCTYPE html>

<html>

<head>

<title>MyPage!</title>

<!-- add bootstrap plugins -->

<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

</head>

<body>

```

<div class="container mt-5">

    <div class="alert alert-danger">
        <strong>Danger!</strong> Please don't try this.
    </div>

    <div class="alert alert-info">
        <strong>Alert!</strong> Think twice before you take any
decision.
    </div>

    <div class="alert alert-warning">
        <strong>Warning!</strong> Keep a distance.
    </div>

    <div class="alert alert-success">
        <strong>Yahoo!</strong> You transaction done
successfully.
    </div>

</div>

</body>
</html>

```

ex:2

```

<!DOCTYPE html>

<html>

    <head>

```

```

<title>MyPage!</title>

<!-- add bootstrap plugins -->
<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

</head>
<body>

    <div class="container mt-5">

        <div class="alert alert-danger collapse">
            <strong>Danger!</strong> Please don't try this.
        </div>

    </div>

</body>
</html>

```

ex:3

```
<!DOCTYPE html>
```

```
<html>

  <head>

    <title>MyPage!</title>

    <!-- add bootstrap plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

  </head>

  <body>

    <div class="container mt-5">

      <div class="alert alert-danger alert-dismissible" >

        <strong>Danger!</strong> Please don't try this.

        <span class="btn-close" data-bs-dismiss="alert"></span>

      </div>

    </div>

  </body>

</html>
```

Bootstrap Buttons

=====

The `.btn` class is intended to be used in conjunction with our button variants, or to serve as a basis for your own custom styles.

WE need to use `btn` along with contextual classes

ex:

`btn-primary`

`btn-info`

`btn-danger`

and etc.

A `.btn-outline-*` ones to remove all background images and colors on any button.

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <!-- add bootstrap plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >
```

```
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>
```

```
</head>
```

```
<body>
```

```
<div class="container mt-5">
```

```
<button class="btn btn-primary">primary</button>
```

```
<button class="btn btn-secondary">secondary</button>
```

```
<button class="btn btn-info">info</button>
```

```
<button class="btn btn-warning">warning</button>
```

```
<button class="btn btn-danger">danger</button>
```

```
<button class="btn btn-success">success</button>
```

```
<button class="btn btn-dark">dark</button>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>

  <title>MyPage!</title>

  <!-- add bootstrap plugins -->
  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-scale=1">

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

  <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

</head>
<body>

  <div class="container mt-5">

    <button class="btn btn-outline-primary">primary</button>
    <button class="btn btn-outline-secondary">secondary</button>
    <button class="btn btn-outline-info">info</button>
    <button class="btn btn-outline-warning">warning</button>
    <button class="btn btn-outline-danger">danger</button>
    <button class="btn btn-outline-success">success</button>
    <button class="btn btn-outline-dark">dark</button>

  </div>
```

```

        </body>
</html>

ex:3
----
<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <!-- add bootstrap plugins -->
        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

    </head>
    <body>

        <div class="container mt-5">

            <a href="" class="btn btn-primary"> Home </a>

```



```
<br><br>
```

```
<a href="" class="btn btn-outline-primary"> Home </a>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:4

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>MyPage!</title>
```

```
<!-- add bootstrap plugins -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >
```

```
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>
```

```
</head>
```

```
<body>

    <div class="container mt-5">

        <button class="btn btn-link">button1</button>

        <br><br>

        <button class="btn btn-link">button2</button>

    </div>

</body>
</html>
```

ex:5

```
<!DOCTYPE html>
<html>
  <head>
    <title>MyPage!</title>

    <!-- add bootstrap plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet" >

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"> </script>

</head>
<body>
    <div class="container mt-5">

        <button class="btn btn-primary">
            Notification <span class="badge bg-light text-
primary">10</span>
        </button>

    </div>
</body>
</html>

```

Bootstrap Glyphicons

=====

Bootstrap includes 260 glyphs from the Glyphicon Halflings set.

Glyphicons Halflings are normally not available for free, but their creator has made them available

for Bootstrap free of cost.

We will see bootstrap glyphs to display the icons in a web page.

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>
```

```
    <!-- Bootstrap CDN LINK for Icons -->
```

```
    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">
```

```
  </head>
```

```
  <body>
```

```
    <div class="container mt-5">
```

```
      <span class="bi bi-heart text-danger"></span>
```

```
        </div>

    </body>
</html>
```

ex:2

```
<!DOCTYPE html>

<html>

    <head>

        <title>MyPage!</title>

        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

        <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>

        <!-- Bootstrap CDN LINK for Icons -->

        <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">

    </head>
```

```

<body>

    <div class="container mt-5">

        <button class="bi bi-search btn btn-
primary">Search</button>

    </div>

</body>
</html>

```

ex:3

```

<!DOCTYPE html>
<html>
    <head>
        <title>MyPage!</title>

        <meta charset="utf-8">

        <meta name="viewport" content="width=device-width, initial-scale=1">

```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap CDN LINK for Icons -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<div class="container mt-5">
```

```
<span class="bi bi-facebook text-primary"> </span>
```

```
<span class="bi bi-twitter"> </span>
```

```
<span class="bi bi-instagram"> </span>
```

```
<span class="bi bi-youtube"> </span>
```

```
<span class="bi bi-whatsapp text-success"> </span>
```

```
</div>
```

```
</body>
```

```
</html>
```

Bootstrap Cards

=====

A card in Bootstrap 5 is a bordered box with some padding around its content. It includes options for headers, footers, content, colors, etc.

A basic card is created with the `.card` class, and content inside the card has a `.card-body` class:

The `.card-header` class adds a heading to the card and the `.card-footer` class adds a footer to the card.

Use `.card-title` to add card titles to any heading element.

The `.card-text` class is used to remove bottom margins for a `<p>` element if it is the last child (or the only one) inside `.card-body`.

Add `.card-img-top` to an `` to place the image at the top inside the card.

Note that we have added the image outside of the `.card-body` to span the entire width:

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```



```
<!-- add bootstrap 5 plugins -->

<meta charset="utf-8">


<meta name="viewport" content="width=device-width, initial-scale=1">


<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >


<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>


<!-- Bootstrap Font Icon CSS -->

<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">


</head>

<body>

    <div class="container mt-5">

        <div class="card">

            <div class="card-header">

                Heading

            </div>

            <div class="card-body">

                Body

            </div>

            <div class="card-footer">

                Footing

            </div>

        </div>

    </div>

</body>

</html>
```

```

        </div>
    </div>

</div>

</body>
</html>

```

ex:2

```

<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

    <!-- Bootstrap Font Icon CSS -->

    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">

```

```

</head>
<body>

    <div class="container mt-5">

        <div class="card">

            <div class="card-header">

                Heading

            </div>

            <div class="card-body">

                <div class="card-title">Bootstrap</div>

                <div class="card-text">Bootstrap is a css framework</div>

            </div>

            <div class="card-footer">

                Footing

            </div>

        </div>

    </div>

</body>
</html>

```

ex:3

```

<!DOCTYPE html>
<html>

    <head>

```

```
<title>MyPage!</title>
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css"
rel="stylesheet">
```

```
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap CDN LINK for Icons -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<div class="container mt-5">
```

```
<div class="row">
```

```
<div class="col-4">
```

```
<div class="card">
```

```

```

```
<div class="card-body">
```

Thumbnail-1</h2>

Illustration</p>

```
<h2 class="card-title text-center">
```

```
<p class="card-text text-center">
```

```
</div>
```

```
</div>
```

```
</div>
```

img-fluid"/>

Thumbnail-3</h2>

Illustration</p>

```
<div class="col-4">
```

```
<div class="card">
```

```

```

```
<h2 class="card-title text-center">
```

```
<p class="card-text text-center">
```

```
</div>
```

```
</div>
```

```
</div>
```

img-fluid"/>

Thumbnail-3</h2>

Illustration</p>

```
<div class="col-4">
```

```
<div class="card">
```

```

```

```
<h2 class="card-title text-center">
```

```
<p class="card-text text-center">
```

```

</div>
</div>
</div>

</div>

</div>

</body>
</html>

```

Bootstrap Collapse Plugin

=====

Collapsibles are useful when you want to hide and show large amount of content:

A data-bs-toggle="collapse" attribute is used to show and hide the content.

A data-bs-target attribute is used to connect a button with div tag.

A "collapse" class inside <div> is used to hide/collapse the content for first time.

ex:1

```

<!DOCTYPE html>
<html>
<head>

```

```

<title>IHUB TALENT</title>

<!-- add bootstrap 5 plugins -->

<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>

<!-- Bootstrap Font Icon CSS -->

<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <div class="container mt-5">

        <button class="btn btn-primary" data-bs-toggle="collapse"
            data-bs-target="#myId"> Toggle </button>

        <h1 id="myId" class="collapse">This is heading tag</h1>

    </div>

</body>

```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
    <!-- Bootstrap Font Icon CSS -->
```

```
    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```



```
<a href="#myId" data-bs-toggle="collapse"> Toggle </a>
```

```
<h1 id="myId" class="collapse">This is heading tag</h1>
```

```
</div>
```

```
</body>
```

```
</html>
```

> Bootstrap collapse plugin with cards

=====

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```

<!-- Bootstrap Font Icon CSS -->

<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <div class="container mt-5">

        <div class="card">

            <div class="card-header">

                <button class="btn btn-outline-primary"
                    data-bs-toggle="collapse"
                    data-bs-target="#myId"> Toggle </button>

            </div>

            <div class="card-body collapse" id="myId">

                <div class="row">

                    <div class="col-4">

                        

                    </div>

                    <div class="col-4">

                        

                    </div>

                    <div class="col-4">

                        

                    </div>

                </div>

            </div>

        </div>

    </div>

```

```

                                </div>
                            </div>
                    </div>

                </div>

        </div>

</body>
</html>

```

Bootstrap responsive navbar

=====

Navbars require a wrapping `.navbar` with `.navbar-expand{-sm|-md|-lg|-xl|-xxl}` for responsive collapsing and color scheme classes.

Navbars and their contents are fluid by default.

Change the container to limit their horizontal width in different ways.

Use our spacing and flex utility classes for controlling spacing and alignment within navbars.

Navbars are responsive by default, but you can easily modify them to change that.

Responsive behavior depends on our Collapse JavaScript plugin.

`.navbar-brand` for your company, product, or project name.

.navbar-nav for a full-height and lightweight navigation (including support for dropdowns).

.navbar-toggler for use with our collapse plugin and other navigation toggling behaviors.

Flex and spacing utilities for any form controls and actions.

.navbar-text for adding vertically centered strings of text.

.collapse.navbar-collapse for grouping and hiding navbar contents by a parent breakpoint.

Add an optional .navbar-scroll to set a max-height and scroll expanded navbar content.

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<nav class="navbar navbar-expand-lg navbar-light bg-light">
```

```
<div class="container-fluid">
```

```
<a class="navbar-brand" href="#">IHUBTALENT</a>
```

```
<button class="navbar-toggler"
```

```
data-bs-toggle="collapse"
```

```
data-bs-target="#navbarId">
```

```
<span class="navbar-toggler-icon"></span>
```

```
</button>
```

```
<div class="collapse navbar-collapse" id="navbarId">
```

```
<ul class="navbar-nav ">
```

```
<li class="nav-item">
```

```
<a class="nav-link active" href="#">Home</a>
```

```
</li>
```

```
<li class="nav-item">
```

```
<a class="nav-link active" href="#">About</a>
```

```
</li>
```

```

        <li class="nav-item">
            <a class="nav-link active" href="#">Service</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active" href="#">Portfolio</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active" href="#">Contact</a>
        </li>
    </ul>
</div>
</div>
</nav>
</body>
</html>

```

ex:2

```

<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<nav class="navbar navbar-expand-lg navbar-dark bg-dark">
```

```
<div class="container-fluid">
```

```
<a class="navbar-brand" href="#">IHUBTALENT</a>
```

```
<button class="navbar-toggler"
```

```
data-bs-toggle="collapse"
```

```
data-bs-target="#navbarId">
```

```
<span class="navbar-toggler-icon"></span>
```

```
</button>
```

```
<div class="collapse navbar-collapse" id="navbarId">
```

```
<ul class="navbar-nav ">
```

```
<li class="nav-item">
```

```
<a class="nav-link active" href="#">Home</a>
```

```
</li>
```

```

        <li class="nav-item">
            <a class="nav-link active" href="#">About</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active" href="#">Service</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active" href="#">Portfolio</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active" href="#">Contact</a>
        </li>
    </ul>
</div>
</div>
</nav>
</body>
</html>

```

ex:3

```

<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

```



```

<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>

<!-- Bootstrap Font Icon CSS -->

<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <nav class="navbar navbar-expand-lg navbar-dark bg-dark fixed-top">

        <div class="container-fluid">

            <a class="navbar-brand" href="#">IHUBTALENT</a>

            <button class="navbar-toggler"
                data-bs-toggle="collapse"
                data-bs-target="#navbarId">

                <span class="navbar-toggler-icon"></span>

            </button>

            <div class="collapse navbar-collapse" id="navbarId">

                <ul class="navbar-nav ">

```

```
<li class="nav-item">
    <a class="nav-link active" href="#">Home</a>
</li>
<li class="nav-item">
    <a class="nav-link active" href="#">About</a>
</li>
<li class="nav-item">
    <a class="nav-link active" href="#">Service</a>
</li>
<li class="nav-item">
    <a class="nav-link active" href="#">Portfolio</a>
</li>
<li class="nav-item">
    <a class="nav-link active" href="#">Contact</a>
</li>
</ul>
</div>
</div>
</nav>
```

```
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
```

```
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
<h1>This is heading tag </h1>
</body>
</html>
```

Bootstrap Scrollspy

=====

The scrollspy plugin automatically highlights the navigation links based on the scroll position to indicate where the user is currently on the page.

```
<!DOCTYPE html>
<html>
<head>
  <title>IHUB TALENT</title>

  <!-- add bootstrap 5 plugins -->
  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
<style>
```

```
  .section1
```

```
  {
```

```
    width: 100%;
```

```
    height: 560px;
```

```
    background-color: #C4E538;
```

```
  }
```

```
  .section2
```

```
  {
```

```
    width: 100%;
```

```
    height: 560px;
```

```
    background-color: #ED4C67;
```

```
  }
```

```
  .section3
```

```
  {
```

```
    width: 100%;
```

```
    height: 560px;
```

```
    background-color: #9980FA;
```

```

    }
    .section4
    {
        width: 100%;
        height: 560px;
        background-color: #12CBC4;
    }
    .section5
    {
        width: 100%;
        height: 560px;
        background-color: #833471;
    }

</style>

</head>
<body>

    <nav class="navbar navbar-expand-lg navbar-dark bg-dark fixed-top">
        <div class="container-fluid">
            <a class="navbar-brand" href="#">IHUBTALENT</a>

            <button class="navbar-toggler"
                data-bs-toggle="collapse"
                data-bs-target="#navbarId">

```

```

        <span class="navbar-toggler-icon"></span>
    </button>
    <div class="collapse navbar-collapse" id="navbarId">
        <ul class="navbar-nav ">
            <li class="nav-item">
                <a class="nav-link active" href="#homeId">Home</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active" href="#aboutId">About</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active" href="#serviceId">Service</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#portfolioId">Portfolio</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active" href="#contactId">Contact</a>
            </li>
        </ul>
    </div>
</div>
</nav>

<section class="section1" id="homeId">
    <h1 class="pt-5 text-center">

```

Home Page

</h1>

</section>

<section class="section2" id="aboutId">

<h1 class="pt-5 text-center">

About Page

</h1>

</section>

<section class="section3" id="serviceId">

<h1 class="pt-5 text-center">

Service Page

</h1>

</section>

<section class="section4" id="portfolioId">

<h1 class="pt-5 text-center">

Portfolio Page

</h1>

</section>

<section class="section5" id="contactId">

<h1 class="pt-5 text-center">

Contact Page

</h1>

</section>

</body>

</html>

Bootstrap5 forms

=====

Bootstrap 5 supports two types of form layouts.

1) Stacked Forms

2) Inline forms

1) Stacked Forms

=====

All textual `<input>` and `<textarea>` elements with class `.form-control` get proper form styling.

we add a `.form-label` class to each label element to ensure correct padding.

Checkboxes have different markup. They are wrapped around a container element with `.form-check`, and labels have a class of `.form-check-label`, while checkboxes and radio buttons use `.form-check-input`.

ex:1

```
<!DOCTYPE html>
```

```
<html>
```



```

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>

    <!-- Bootstrap Font Icon CSS -->

    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <div class="container mt-5">

        <!-- stack form -->

        <form action="">

            <label class="my-3">UserName:</label>

            <input type="text" name="t1" class="form-control"
placeholder="username" autocomplete="off" />

```

```

        <label class="my-3">Password:</label>
        <input type="password" name="t1" class="form-control"
placeholder="password" />

        <input type="submit" value="submit" class="btn btn-primary my-
5 w-100"/>

    </form>

</div>
</body>
</html>

```

ex:2

```

<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <div class="w-50">
```

```
            <!-- stack form -->
```

```
            <form action="">
```

```
                <label class="my-3">UserName:</label>
```

```
                <input type="text" name="t1" class="form-control"
placeholder="username" autocomplete="off" />
```

```
                <label class="my-3">Password:</label>
```

```
                <input type="password" name="t1" class="form-control"
placeholder="password" />
```

```
                <input type="submit" value="submit" class="btn btn-primary my-
5 w-100"/>
```

```
            </form>
```

```
</div>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:3

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
  <!-- Bootstrap Font Icon CSS -->
```

```
  <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```

</head>
<body>
    <div class="container mt-5">

        <form action="">
            <label>Address:</label>
            <textarea name="t1" rows="5" cols="10" class="form-
control"></textarea>
        </form>

    </div>
</body>
</html>

```

ex:4

```

<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <form action="">
```

```
            <div class="form-check">
```

```
                <input type="radio" name="t1" value="male" class="form-check-input"/>
```

```
                <label class="form-check-label">MALE</label>
```

```
            </div>
```

```
            <div class="form-check">
```

```
                <input type="radio" name="t1" value="female" class="form-check-input"/>
```

```
                <label class="form-check-label">FEMALE</label>
```

```
            </div>
```

```
        </form>
```

```

        </div>

</body>
</html>

ex:5
-----

<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>

    <!-- Bootstrap Font Icon CSS -->

    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <div class="container mt-5">

```

```
<form action="">
```

```
    <div class="form-check">
```

```
        <input type="checkbox" name="t1" value="married" class="form-check-input"/>
```

```
        <label class="form-check-label">MARRIED</label>
```

```
    </div>
```

```
    <div class="form-check">
```

```
        <input type="checkbox" name="t1" value="single" class="form-check-input"/>
```

```
        <label class="form-check-label">SINGLE</label>
```

```
    </div>
```

```
</form>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:6

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```



```

<!-- add bootstrap 5 plugins -->

<meta charset="utf-8">


<meta name="viewport" content="width=device-width, initial-scale=1">


<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >


<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>


<!-- Bootstrap Font Icon CSS -->

<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <div class="container mt-5">


        <form action="">


            <label>Select Country:</label>

            <select name="t1" class="form-select">

                <option value="">none</option>

                <option value="india">India</option>

                <option value="america">America</option>

                <option value="australia">Australia</option>

                <option value="canada">Canada</option>

```

```
</select>
```

```
</form>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:7

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
  <!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-  
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <form action="">
```

```
            <label>Performance Rating :</label>
```

```
            <input type="range" name="t1" class="form-range"/>
```

```
        </form>
```

```
    </div>
```

```
</body>
```

```
</html>
```

ex:8

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

<!-- Bootstrap Font Icon CSS -->
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">
</head>
<body>

    <div class="container mt-5">

        <form action="">

            <div class="input-group">

                <label class="input-group-text">www.</label>

                <input type="text" name="t1"/>

                <label class="input-group-text">.com</label>

            </div>

        </form>

```

```
        </div>

</body>
</html>
```

Inline Forms

=====

If you want your form elements to appear side by side, use `.row` and `.col`.

ex:

```
<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>

    <!-- Bootstrap Font Icon CSS -->

    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <form action="">
```

```
            <div class="row">
```

```
                <div class="col-2">
```

```
                    <label>UserName:</label>
```

```
                </div>
```

```
                <div class="col-3">
```

```
                    <input type="text" name="t1"/>
```

```
                </div>
```

```
                <div class="col-2">
```

```
                    <label>Password:</label>
```

```
                </div>
```

```
                <div class="col-3">
```

```
                    <input type="password" name="t1"/>
```

```
                </div>
```

```
                <div class="col-2">
```

```
                    <input type="submit" value="submit"/>
```

```
                </div>
```

```
            </div>
```

```
        </form>
```

```
</div>

</body>
</html>
```

> Bootstrap Carousel

=====

A .carousel class creates a carousel

A .slide class adds a CSS transition and animation effect when sliding from one item to the next. Remove this class if you do not want this effect.

A .carousel-inner class adds slides to the carousel.

A .carousel-item class specifies the content of each slide.

Add elements inside <div class="carousel-caption"> within each <div class="carousel-item"> to create a caption for each slide.

A .carousel-indicators class adds indicators for the carousel.

These are the little dots at the bottom of each slide (which indicates how many slides there are in the carousel, and which slide the user are currently viewing).

A .carousel-control-prev class adds a left (previous) button to the carousel, which allows the user to go back between the slides.

A .carousel-control-next class adds a right (next) button to the carousel, which allows the user to go forward between the slides.

A .carousel-control-prev-icon class used together with .carousel-control-prev to create a "previous" button.

A .carousel-control-next-icon class used together with .carousel-control-next to create a "next" button.

```
<!DOCTYPE html>
<html>
<head>
  <title>IHUB TALENT</title>

  <!-- add bootstrap 5 plugins -->
  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-scale=1">

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

  <!-- Bootstrap Font Icon CSS -->
```



```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-  
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <div id="carouselId" class="carousel slide" data-bs-ride="carousel">
```

```
            <div class="carousel-indicators">
```

```
                <button type="button" data-bs-target="#carouselId" data-bs-slide-to="0"  
class="active"></button>
```

```
                <button type="button" data-bs-target="#carouselId" data-bs-slide-to="1"  
></button>
```

```
                <button type="button" data-bs-target="#carouselId" data-bs-slide-to="2"  
></button>
```

```
            </div>
```

```
        <div class="carousel-inner">
```

```
            <div class="carousel-item active">
```

class="w-100 mx-auto d-block"/>

<h1>Washington DC</h1>

<p>Our Team Is Our Strength</p>

</div>

</div>

<div class="carousel-item">

class="w-100 mx-auto d-block"/>

<h1>Los Angeles</h1>

<p>Our Work Is Our Identity</p>

</div>

</div>

<div class="carousel-item">

class="w-100 mx-auto d-block"/>


```

Practice</p>
</div>
</div>
</div>
<button class="carousel-control-prev" type="button" data-bs-target="#carouselId" data-bs-slide="prev">
  <span class="carousel-control-prev-icon"></span>
  <span class="visually-hidden">Previous</span>
</button>
<button class="carousel-control-next" type="button" data-bs-target="#carouselId" data-bs-slide="next">
  <span class="carousel-control-next-icon"></span>
  <span class="visually-hidden">Next</span>
</button>
</div>
</div>
</body>
</html>

```