

 <b>UNISIL</b>	<b>BLOWING AGENTS</b>			<b>MLA</b> <b>GROUP</b>
	SYNTHETIC SILICA PRODUCTS, 111/230, HARSH NAGAR, KANPUR Tel. : (0512)-3099938,2554110, Fax No. : 0512-2526257 E-mail: <a href="mailto:mktg@mlagroup.com">mktg@mlagroup.com</a> , <a href="mailto:sales@mlagroup.com">sales@mlagroup.com</a>			
	Doc. No. : SSP/ADC-SPEC/05	Issue No.: 05	DATE : 01.0.2004	

### TYPICAL PHYSIO-CHEMICAL PROPERTIES

PROPERTES	UNIT	ADC- F- 5200
Odor	--	Odorless
Average Particle Size	micron	8-10
pH Value	-	8.5-10.0
Moisture	%max.	0.5
Decomposition Temperature	°C	162± 2
Gas composition	--	N <sub>2</sub> & CO, CO <sub>2</sub>
Gas evolution	Cc/gm	115-125
300 mesh residue	% max	0.5
Colour	--	Pale yellow powder
Packing	Kg/bag	25

\* At the time of packing.

**Grades available:** ADC-L2, L5, H2/H5, F2, EV, PT, Single pack (EVA-08), Twin Pack

### Applications:

- Wood plastic composite
- PVC doors and windows
- PVC foamed panels
- PVC foam board

---

This information and our technical advice-whether verbal, in writing or by way of trials are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sales and Delivery.