



# LAB 1 : Getting Started With Web Development


## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT

### Objective:

In this lab we are going to create a virtual environment. So we will install the flask package inside this virtual environment. As we do not install into our main python system, so every project is not going to be affected with the packages updates etc.

### Steps:

1. Create a new folder to save all our virtual project.




2. Create virtual environment, activate it and install flask inside

```
Command Prompt - flask run
Microsoft Windows [Version 10.0.18362.720]
(c) 2019 Microsoft Corporation. All rights reserved.

C:\Users\ASUS>D:
D:\>cd python\virtualenv
D:\python\virtualenv>py -m venv project3
D:\python\virtualenv>project3\Scripts\activate.bat
(project3) D:\python\virtualenv>pip list
package      version
-----
pip           19.0.3
setuptools    40.8.0
You are using pip version 19.0.3, however version 20.0.2 is available.
You should consider upgrading via the 'python -m pip install --upgrade pip' command.
(project3) D:\python\virtualenv>pip install flask
Collecting flask
  Using cached https://files.pythonhosted.org/packages/9b/93/628509b8d5dc749656a9641f4caf13540e2cdec85276964ff8f43bbb1d3b/Flask-1.1.1-py2.py3-none-any.whl
Collecting itsdangerous>=0.24 (from flask)
  Using cached https://files.pythonhosted.org/packages/76/ae/44b03b253d6fade317f32c24d100b3b35c2239807046a4c953c7b89fa9e/itsdangerous-1.1.0-py2.py3-none-any.whl
Collecting Jinja2>=2.10.1 (from flask)
  Using cached https://files.pythonhosted.org/packages/27/24/4f35961e5c669e96f6559760042a55b9bcfdb82b9bdb3c8753dbe042e35/Jinja2-2.11.1-py2.py3-none-any.whl
Collecting Werkzeug>=0.15 (from flask)
```

3. Code our first web app and saves as app.py, type all files inside project3 folder.

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT



#### 4. Export and run

\* change set project3 = app.py to set FLASK\_APP = app.py

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT

```
Command Prompt - flask run

(project3) D:\python\virtualenv>cd project3
                                     directory to project3
(project3) D:\python\virtualenv\project3>set project3 = app.py
                                     export app.py
(project3) D:\python\virtualenv\project3>flask run
                                     run the code
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: off
* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
                                     url for our web app
127.0.0.1 - - [26/Mar/2020 13:11:24] "[37mGET / HTTP/1.1[0m" 200 -
127.0.0.1 - - [26/Mar/2020 13:11:24] "[33mGET /favicon.ico HTTP/1.1[0m" 404 -

(project3) D:\python\virtualenv\project3>flask run
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: off
* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
```

5. Go to <http://127.0.0.1:5000/> in your browser



6. To run in debug mode, append this code. In debug mode you don't need to stop if you change your code. Save your new codes and refresh the page only.

```
D:\python\virtualenv\project4\app.py - Sublime Text (UNREGISTERED)
File Edit Selection Find View Goto Tools Project Preferences Help


app.py
1 | from flask import Flask
2
3 | app = Flask(__name__)
4
5 | @app.route('/')
6
7 | def hello():
8 |     return '<h1> Hello KISMEC! </h1>'
9
10 | if __name__ == '__main__':
11 |     app.run(debug=True)
12
```

7. Run your code - python app.py

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT

```
(project4) D:\python\virtualenv\project4>python app.py
* Serving Flask app "app" (lazy loading)
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: on
* Restarting with stat
* Debugger is active!
* Debugger PIN: 118-677-302
* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
```

8. We want to create page with a route





```
D:\python\virtualenv\project4\app.py - Sublime Text (UNREGISTERED)
File Edit Selection Find View Goto Tools Project Preferences Help

app.py
1 from flask import Flask
2
3 app = Flask(__name__)
4
5 @app.route('/')
6 def hello():
7     return '<h1> Hello KISMEC SP! </h1>'
8
9 @app.route('/about')
10 def about():
11     return '<h1> About KISMEC SP! </h1>'
12
13 if __name__ == '__main__':
14     app.run(debug=True)
15
```

9. Route home + no route

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT




Template

1. Create new folder and name it “templates”

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT


__pycache__	19/5/2020 1:05 PM	File folder	
Include	19/5/2020 11:27 AM	File folder	
Lib	19/5/2020 11:27 AM	File folder	
Scripts	19/5/2020 11:28 AM	File folder	
templates	19/5/2020 1:10 PM	File folder	
app	19/5/2020 12:58 PM	PY File	1 KB
pyvenv.cfg	19/5/2020 11:27 AM	CFG File	1 KB

2. Create new html file and save in templates folder  
Ctrl-shift-p



## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT

3. Code in html language




The image shows two screenshots of a code editor interface. The top screenshot shows a file named 'app.py' with a single line of code: 'html'. A yellow text overlay says 'type html and press tab'. The bottom screenshot shows the same file with the following HTML code written:

```
1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title></title>
5 </head>
6 <body>
7
8 </body>
9 </html>
```

4. Import render\_template



## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT




```
1  from flask import Flask, render template
2
3  app = Flask(__name__)
4
5  @app.route('/')
6
7  def index():
8      return '<h1> Hello World!!! </h1>'
9
10 @app.route('/about')
11
12 def about():
13     return render_template('about.html')
14
15 if __name__ == '__main__':
16     app.run(debug=True)
```

Pass in keyword arguments to the template, like in the example with my\_string


1. Render value to the template

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT



```
1 from flask import Flask, render_template
2
3 app = Flask(__name__)
4
5 @app.route('/')
6
7 def index():
8     return '<h1> Hello World!!! </h1>'
9
10 @app.route('/about')
11
12 def about():
13     return render_template('about.html', my_string="Passed value")
14
15 if __name__ == '__main__':
16     app.run(debug=True)
```

2. Take the value from flask app



```
1 <!DOCTYPE html>
2 <html>
3 <head>
4     <title>About</title>
5 </head>
6 <body>
7     <h1>About Page</h1>
8     <h2>{{my_string}}</h2>
9 </body>
10 </html>
```

Reference: <https://realpython.com/primer-on-jinja-templating/>,  
<https://jinjapalletsprojects.com/en/2.11.x/templates/#template-inheritance>

There are a few kinds of delimiters. The default Jinja delimiters are configured as follows:

- `{% ... %}` for Statements
- `{{ ... }}` for Expressions to print to the template output
- `{# ... #}` for Comments not included in the template output
- `# ... ##` for Line Statements

With list

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT

```
app.py about.html x
1 from flask import Flask, render_template
2
3 app = Flask(__name__)
4
5 my_list = ['hello','hi','assalamualaikum']
6
7
8 @app.route('/')
9
10 def index():
11     return '<h1> Hello World!!! </h1>'
12
13 @app.route('/about')
14
15 def about():
16     return render_template('about.html', my_string="Passed value", my_list=my_list)
17
18 if __name__ == '__main__':
19     app.run(debug=True)
20
```

```
app.py about.html x
1 <!DOCTYPE html>
2 <html>
3 <head>
4     <title>About</title>
5 </head>
6 <body>
7     <h1>About Page</h1>
8     <h2>{{my_string}}</h2>
9     <h2>{{my_list[1]}}</h2>
10 </body>
11 </html>
```




For loop

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT

```
app.py x about.html x
1 from flask import Flask, render_template
2
3 app = Flask(__name__)
4
5 my_list = ['hello', 'hi', 'assalamualaikum']
6
7 my_dict = [
8     {
9
10         'name': 'wijdan',
11         'age': 27,
12         'dateofbirth': '30 Oct 1993'
13     },
14     {
15
16         'name': 'mimi',
17         'age': 27,
18         'dateofbirth': '30 Nov 1993'
19     }
20 ]
21
22 @app.route('/')
23
24 def index():
25     return '<h1> Hello World!!! </h1>'
26
27 @app.route('/about')
28
29 def about():
30     return render_template('about.html', my_string="Passed value", my_list=my_list, my_dict=my_dict)
31
32 if __name__ == '__main__':
33     app.run(debug=True)
34
```

```
app.py x about.html x
1 <!DOCTYPE html>
2 <html>
3 <head>
4     <title>About</title>
5 </head>
6 <body>
7     <h1>About Page</h1>
8     <h2>{{my_string}}</h2>
9     <h2>{{my_list[1]}}</h2>
10
11     {% for n in my_dict %}
12
13         <h1>{{n.name}}</h1>
14         <p>{{n.age}}</p>
15         <p>{{n.dateofbirth}}</p>
16     {% endfor %}
17 </body>
18 </html>
```



References:

## LAB 1: GETTING STARTED WITH WEB DEVELOPMENT

1. <https://blog.miguelgrinberg.com/post/designing-a-restful-api-with-python-and-flask>