OBJECT-ORIENTED PROGRAMMING (CSF3043)

K1

LECTURER: PN. NOOR HAFHIZAH

DEMONSTRATOR : MOHD ARIZAL SHAMSIL BIN MAT ARIFIN

NAME : ARUN MUGILAN A/L SARGUNAN

MATRICS NO.: S63746

LAB MODULE: 8


ColorSelectFrame - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/**
 *
 * ARUNMUGILAN A/L SARGUNAN S63746
 */
import java.awt.BorderLayout;
import javax.swing.JFrame;
import javax.swing.JButton;
import javax.swing.JCheckBox;
import javax.swing.JComboBox;
import javax.swing.JPanel;
public class ColorSelectFrame extends JFrame{
private JButton okJButton;
private JButton cancelJButton;
private JCheckBox backgroundJCheckBox;
private JCheckBox foregroundJCheckBox;
private JComboBox colorJComboBox;
private JPanel panel;
private JPanel panel2;
public ColorSelectFrame () {
super ("CSE3101-OO Programming");
setLayout (new BorderLayout());
colorJComboBox = new JComboBox();
colorJComboBox.addItem ("RED");
add(colorJComboBox, BorderLayout.NORTH);
panel= new JPanel();
backgroundJCheckBox = new JCheckBox("Background");
foregroundJCheckBox = new JCheckBox("Foreground");
panel.add(backgroundJCheckBox);
panel.add(foregroundJCheckBox);
add(panel, BorderLayout.CENTER);
okJButton = new JButton ("Ok");
cancelJButton = new JButton ("Cancel");
panel2 = new JPanel();
panel2.add(okJButton);
panel2.add(cancelJButton);
add(panel2, BorderLayout.SOUTH);
}
}
colorselectframe.ColorSelectFrame
50:2
INS


ColorSelectFrame - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
 * To change this license header, choose License Headers in Project Properties.
 * To change this template file, choose Tools | Templates
 * and open the template in the editor.
 */
package colorselectframe;
/**
 *
 * ARUNMUGILAN A/L SARGUNAN S63746
 */
import javax.swing.JFrame;
public class ColorSelect {
public static void main (String args []){
ColorSelectFrame colorSelectFrame = new ColorSelectFrame();
colorSelectFrame.setDefaultCloseOperation (JFrame.EXIT_ON_CLOSE);
colorSelectFrame.setSize (300, 125);
colorSelectFrame.setVisible(true);
}
}
colorselectframe.ColorSelect
main
15:47
INS


ColorSelectFrame - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Search (Ctrl+I)
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package colorselectframe;
/**
*
* ARUNMUGILAN A/L SARGUNAN S63746
*/
import javax.swing.JFrame;
public class ColorSelect {
public static void main (String args []){
ColorSelectFrame colorSelectFrame = new ColorSelectFram
colorSelectFrame.setDefaultCloseOperation (JFrame.EXIT_
colorSelectFrame.setSize (300, 125);
colorSelectFrame.setVisible(true);
}
}
CSE3101-OO Programm...
RED
Background
Foreground
Ok
Cancel
Output - ColorSelectFrame (run)
run:
Output
ColorSelectFrame (run)
running...
15:47
INS




```
/**
 *
 * ARUN MUGILAN A/L SARGUNAN S63746
 */

import java.awt.event.*;
import javax.swing.*;

public class Rectangle implements ActionListener{
    private static JLabel Length, Width, s, r;
    private static JTextField getLength, getWidth;
    private static JButton Calculate;
    private String length, width;
    private int L, W;


    public static void main(String[] args) {
        JPanel panel = new JPanel();
        JFrame frame = new JFrame("Area and Parameter Calculator");
        frame.setSize(500, 400);
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        frame.add(panel);

        panel.setLayout(null);
        Length = new JLabel("Length");
        Length.setBounds(15, 25, 85, 35);
        panel.add(Length);

        getLength=new JTextField(20);
        getLength.setBounds(60, 30, 175, 35);
        panel.add(getLength);


        Width = new JLabel("Width");
        Width.setBounds(20, 70, 90, 35);
        panel.add(Width);

        getWidth=new JTextField(20);
        getWidth.setBounds(60, 70, 175, 35);
        panel.add(getWidth);

        Calculate= new JButton("Calculate");
        Calculate.setBounds(20, 110, 90, 35);
        Calculate.addActionListener((ActionListener) new Rectangle());
        panel.add(Calculate);

        s = new JLabel();
        s.setBounds(20, 150, 90, 35);
```




```
        getLength.setBounds(60, 30, 175, 35);
        panel.add(getLength);


        Width = new JLabel("Width");
        Width.setBounds(20, 70, 90, 35);
        panel.add(Width);

        getWidth=new JTextField(20);
        getWidth.setBounds(60, 70, 175, 35);
        panel.add(getWidth);

        Calculate= new JButton("Calculate");
        Calculate.setBounds(20, 110, 90, 35);
        Calculate.addActionListener((ActionListener) new Rectangle());
        panel.add(Calculate);

        s = new JLabel();
        s.setBounds(20, 150, 90, 35);
        s.setSize(10000, 40);
        panel.add(s);

        r = new JLabel();
        r.setBounds(20, 170, 90, 35);
        r.setSize(10000, 50);
        panel.add(r);

        frame.setVisible(true);

    }

    public void actionPerformed(ActionEvent e) {
        length=getLength.getText();
        width=getWidth.getText();
        L =Integer.parseInt(length);
        W =Integer.parseInt(width);

       Area area= new Area();
       Perimeter perimeter=new Perimeter();
        String q ="Area: "+area.Area(L, W));
        s.setText(q);
        String t ="Perimeter: "+perimeter.Perimeter(L, W));
        r.setText(t);
        // System.out.println(s);
    }
}
```


Rectangle - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Search (Ctrl+I)
<default config>
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package rectangle;
/**
*
* ARUN MUGILAN A/L SARGUNAN S63746
*/
public class Perimeter {
private int length;
private int width;
public int Perimeter(int length, int width){
return(length*2 + width*2);
}
}
Output
1:1
INS


Rectangle - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Search (Ctrl+I)
<default config>
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package rectangle;
/**
*
* ARUN MUGILAN A/L SARGUNAN S63746
*/
public class Area {
private int length;
private int width;
public int Area(int length, int width){
return(length* width);
}
}
Output
1:1
INS


Area and Parameter Calculator
Length
11
Width
21
Calculate
Area: 231
Perimeter: 64
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Calculate.addActionListener((ActionListener) new Rectangle());
panel.add(Calculate);
s = new JLabel();
s.setBounds(20, 150, 90, 35);
s.setSize(10000, 40);
panel.add(s);
r = new JLabel();
r.setBounds(20, 170, 90, 35);
r.setSize(10000, 50);
panel.add(r);
Output - Rectangle (run)
run:
Output
Rectangle (run)
running...
1:1
INS


ConvertFrame - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package convertframe;
/**
*
* ARUNMUGILAN A/L SARGUNAN S63746
*/
import java.awt.BorderLayout;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;
import javax.swing.JFrame;
import javax.swing.JLabel;
import javax.swing.JTextField;
public class ConvertFrame extends JFrame {
private JLabel label1;
private JLabel label2;
private JTextField temperatureF;
public ConvertFrame(){
super("Temperature converter");
label1 = new JLabel ("Enter Fahrenheit temperature : ");
temperatureF = new JTextField (10);
temperatureF.addActionListener(
new ActionListener(){
public void actionPerformed(ActionEvent e){
int temp = Integer.parseInt(temperatureF.getText());
int celcius = (int)(5.0f/ 9.0f * (temp-32));
label2.setText("Temperature in Celcius is :"+celcius);
}
});
label2 = new JLabel ("Temperature in Celcius is : ");
setLayout (new BorderLayout());
add(label1, BorderLayout.NORTH);
add(temperatureF, BorderLayout.CENTER);
add(label2, BorderLayout.SOUTH);
}
}
Output
18:1
INS


ConvertFrame - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package convertframe;
/**
*
* ARUNMUGILAN A/L SARGUNAN S63746
*/
import javax.swing.JFrame;
public class Convert {
public static void main (String args []){
ConvertFrame C1 = new ConvertFrame();
C1.setDefaultCloseOperation (JFrame.EXIT_ON_CLOSE);
C1.setSize (1000, 400);
C1.setVisible(true);
}
}
Output
10:4/1:31
INS


ConvertFrame - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Search (Ctrl+I)
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package convertframe;
/**
*
* @author SABARUDDIN A/L RAHMAN S437544
*/
import javax.swing.JFrame;
public class Convert {
public static void main (String args []){
ConvertFrame C1 = new ConvertFrame();
C1.setDefaultCloseOperation (JFrame.EXIT_ON
C1.setSize (1000, 400);
C1.setVisible(true);
}
}
Temperature converter
Enter Fahrenheit temperature :
44
Temperature in Celcius is :6
Output - ConvertFrame (run)
run:
Output
ConvertFrame (run)
running...
10:4/1:31
INS


Font - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
* ARUNMUGILAN A/L SARGUNAN S63746
*/
import java.awt.*;
import java.awt.Font;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;
import javax.swing.*;
public class FontFrame extends JFrame implements ActionListener {
private String a;
private JTextField textField = new JTextField(15);
private JRadioButton arial = new JRadioButton("Lucida Handwriting",true);
private JRadioButton alg = new JRadioButton("Algerian",false);
private JRadioButton tnr = new JRadioButton("Times New Roman",false);
private JRadioButton clb = new JRadioButton("Calibri",false);;
private ButtonGroup group = new ButtonGroup();
public FontFrame(){
super("Changing text program");
setLayout (new FlowLayout());
add(textField);
a="Programming is Good";
add (arial);
add (alg);
add (tnr);
add (clb);
group.add(arial);
group.add(alg);
group.add(tnr);
group.add(clb);
arial.addActionListener(this);
alg.addActionListener(this);
tnr.addActionListener(this);
clb.addActionListener(this);
}
public void actionPerformed(ActionEvent e){
if (e.getActionCommand() == "Lucida Handwriting"){
textField.setText(a);
textField.setFont(new Font ("Lucida Handwriting" , Font.PLAIN, 14));
}
else if (e.getActionCommand() == "Algerian") {
font.FontFrame
FontFrame
Output
28:17
INS


Font - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
private JRadioButton clb = new JRadioButton("Calibri",false);;
private ButtonGroup group = new ButtonGroup();
public FontFrame(){
super("Changing text program");
setLayout (new FlowLayout());
add(textField);
a="Programming is Good";
add (arial);
add (alg);
add (tnr);
add (clb);
group.add(arial);
group.add(alg);
group.add(tnr);
group.add(clb);
arial.addActionListener(this);
alg.addActionListener(this);
tnr.addActionListener(this);
clb.addActionListener(this);
}
public void actionPerformed(ActionEvent e){
if (e.getActionCommand() == "Lucida Handwriting"){
textField.setText(a);
textField.setFont(new Font ("Lucida Handwriting" , Font.PLAIN, 14));
}
else if (e.getActionCommand() == "Algerian") {
textField.setText(a);
textField.setFont(new Font ("Algerian" , Font.PLAIN , 14));
}
else if (e.getActionCommand() == "Times New Roman") {
textField.setText(a);
textField.setFont(new Font ("Times New Roman" , Font.PLAIN , 14));
}
else{
textField.setText(a);
textField.setFont(new Font ("Calibri" , Font.PLAIN , 14));
}
}
}
font.FontFrame
FontFrame
Output
28:17
INS


Font - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package font;
/**
*
* ARUNMUGILAN A/L SARGUNAN S63746
*/
import javax.swing.JFrame;
public class Font {
public static void main(String[] args) {
// TODO code application logic here
FontFrame go = new FontFrame();
go.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
go.setSize(317,220);
go.setVisible(true);
}
}
font.Font
main
go
Output
17:37
INS

Font - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Changing text program
PROGRAMMING IS GOOD
Lucida Handwriting
Algerian
Times New Roman
Calibri
Output - Font (run)
run:
Output
Font (run)
running...
17:37
INS


Font - NetBeans IDE 8.2
File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help
Search (Ctrl+I)
Start Page
ColorSelectFrame.java
ColorSelect.java
ConvertFrame.java
Convert.java
FontFrame.java
Font.java
Area.java
Rectangle.java
Perimeter.java
Source
History
/*
* To change this license header, choose License Headers in Project Properties.
* To change this template file, choose Tools | Templates
* and open the template in the editor.
*/
package font;
/**
*
* ARUNMUGILAN A/L SARGUNAN S63746
*/
import javax.swing.JFrame;
public class Font {
public static void main(String[] args) {
// TODO code application logic here
FontFrame go = new FontFrame();
go.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE
go.setSize(317,220);
go.setVisible(true);
}
}
Changing text program
rogramming is Good
Lucida Handwriting
Algerian
Times New Roman
Calibri
Output - Font (run)
run:
Output
Font (run)
running...
17:37
INS