

GE23131-Programming Using C-2024

Quiz navigation

1

2

Show one page at a time

Finish review

Status	Finished
Started	Tuesday, 14 January 2025, 8:48 AM
Completed	Tuesday, 14 January 2025, 8:54 AM
Duration	6 mins 1 sec

Question 1

Correct

Marked out of 1.00

Flag question

A binary number is a combination of 1s and 0s. Its n^{th} least significant digit is the n^{th} digit starting from the right starting with 1. Given a decimal number, convert it to binary and determine the value of the the 4th least significant digit.

Example

number = 23

- Convert the decimal number 23 to binary number: $23^{10} = 2^4 + 2^2 + 2^1 + 2^0 = (10111)_2$.
- The value of the 4th index from the right in the binary representation is 0.

Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159818&cmid=194

REC-CIS

Function Description

Complete the function fourthBit in the editor below.

fourthBit has the following parameter(s):

int number: a decimal integer

Returns:

int: an integer 0 or 1 matching the 4th least significant digit in the binary representation of number.

Constraints

$0 \leq \text{number} < 2^{31}$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

Type here to search

24°C Mostly clear

02:36
17-01-2025

Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159818&cmid=194

REC-CIS

STDIN Function

32 → number = 32

Sample Output 0

0

Explanation 0

- Convert the decimal number 32 to binary number: $32_{10} = (100000)_2$.
- The value of the 4th index from the right in the binary representation is 0.

Sample Case 1

Sample Input 1

STDIN Function

Type here to search

Links

24°C Mostly clear

02:36
17-01-2025

REC-CIS

```
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER number as parameter.
6  */
7
8  int fourthBit(int number)
9  {
10     int binary[32];
11     int i=0;
12     while(number>0)
13     {
14         binary[i]=number%2;
15         number/=2;
16         i++;
17     }
18     if(i>=4)
19     {
20         return binary[3];
21     }
22     else
23     return 0;
24 }
```

	Test	Expected	Got	
✓	printf("%d", fourthBit(32))	0	0	✓

Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159818&cmid=194

REC-CIS

Question 2
Correct
Marked out of 1.00
[Flag question](#)

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the list, sorted ascending. If there is no p^{th} element, return 0.

Example

$n = 20$
 $p = 3$

The factors of 20 in ascending order are {1, 2, 4, 5, 10, 20}. Using 1-based indexing, if $p = 3$, then 4 is returned. If $p > 6$, 0 would be returned.

Function Description

Complete the function `pthFactor` in the editor below.

`pthFactor` has the following parameter(s):

- `int n`: the integer whose factors are to be found
- `int p`: the index of the factor to be returned

Type here to search

Links

24°C Mostly clear

02:36
17-01-2025

Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159818&cmid=194

REC-CIS

pthFactor has the following parameter(s):

- int n: the integer whose factors are to be found
- int p: the index of the factor to be returned

Returns:

int: the long integer value of the p^{th} integer factor of n or, if there is no factor at that index, then 0 is returned

Constraints

$$1 \leq n \leq 10^{15}$$
$$1 \leq p \leq 10^9$$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n, the number to factor.

and Branching - if

Windows taskbar: Type here to search, 24°C Mostly clear, 02:36, 17-01-2025

Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159818&cmid=194

REC-CIS

The second line contains an integer p , the 1-based index of the factor to return.

Sample Case 0

Sample Input 0

STDIN	Function
10	$\rightarrow n = 10$
3	$\rightarrow p = 3$

Sample Output 0

5

Explanation 0

Factoring $n = 10$ results in $\{1, 2, 5, 10\}$. Return the $p = 3^{\text{rd}}$ factor, 5, as the answer.

Type here to search

Links

24°C Mostly clear

02:36
17-01-2025

Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159818&cmid=194

REC-CIS

5 → p = 5

Sample Output 1

0

Explanation 1

Factoring n = 10 results in {1, 2, 5, 10}. There are only 4 factors and p = 5, therefore 0 is returned as the answer.

Sample Case 2

Sample Input 2

STDIN	Function
1 → n = 1	
1 → p = 1	

Sample Output 2

and Branching ... if

Type here to search

24°C Mostly clear

02:36
17-01-2025

REC-CIS

```
2  * Complete the 'pthFactor' function below.
3  *
4  * The function is expected to return a LONG_INTEGER.
5  * The function accepts following parameters:
6  * 1. LONG_INTEGER n
7  * 2. LONG_INTEGER p
8  */
9
10 long pthFactor(long n, long p)
11 {
12     int count=0;
13     for(long i=1;i<=n;i++)
14     {
15         if(n%i==0)
16         {
17             count++;
18             if(count==p)
19             {
20                 return i;
21             }
22         }
23     }
24     return 0;
25 }
```

Test	Expected	Got

REC-CIS

GE23131-Programming Using C-2024

Quiz navigation



Show one page at a time

Finish review

Status	Finished
Started	Tuesday, 14 January 2025, 8:56 AM
Completed	Tuesday, 14 January 2025, 9:41 AM
Duration	44 mins 12 secs

Question 1
Correct
Marked out of 1.00
Flag question

You are a bank account hacker. Initially you have 1 rupee in your account, and you want exactly N rupees in your account. You wrote two hacks, first hack can multiply the amount of money you own by 10, while the second can multiply it by 20. These hacks can be used any number of time. Can you achieve the desired amount N using these hacks.

Constraints:

$$1 \leq T \leq 100$$

$$1 \leq N \leq 10^{12}$$

Week-12-Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159840&cmid=397

REC-CIS

Constraints:

$1 \leq T \leq 100$
 $1 \leq N \leq 10^{12}$

Input

- The test case contains a single integer N.

Output

For each test case, print a single line containing the string "1" if you can make exactly N rupees or "0" otherwise.

SAMPLE INPUT

1

SAMPLE OUTPUT

Type here to search

REC-CIS

```
1 /*
2  * Complete the 'myFunc' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER n as parameter.
6  */
7
8 int myFunc(int n)
9 {
10     if(n==1)
11         return 1;
12     if(n%10==0)
13         if(myFunc(n/10)==1)
14             return 1;
15     if(n%20==0)
16         if(myFunc(n/20)==1)
17             return 1;
18
19     return 0;
20 }
21
```

	Test	Expected	Got	
✓	printf("%d", myFunc(1))	1	1	✓

Week-12-Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159840&cmid=397

REC-CIS

Question **2**

Correct

Marked out of 1.00

Flag question

Find the number of ways that a given integer, X , can be expressed as the sum of the N^{th} powers of unique, natural numbers.

For example, if $X = 13$ and $N = 2$, we have to find all combinations of unique squares adding up to **13**. The only solution is $2^2 + 3^2$.

Function Description

Complete the powerSum function in the editor below. It should return an integer that represents the number of possible combinations.

powerSum has the following parameter(s):

- X: the integer to sum to
- N: the integer power to raise numbers to

Input Format

The first line contains an integer X .

Type here to search

Links

24°C Mostly clear

02:37
17-01-2025

Week-12-Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159840&cmid=397

REC-CIS

The first line contains an integer X .
The second line contains an integer N .

Constraints

$1 \leq X \leq 1000$
 $2 \leq N \leq 10$

Output Format

Output a single integer, the number of possible combinations calculated.

Sample Input 0

10
2

Sample Output 0

Type here to search

Links

24°C Mostly clear

ENG

02:37
17-01-2025

Week-12-Coding: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159840&cmid=397

REC-CIS

Sample Input 1

100
2

Sample Output 1

3

Explanation 1

$$100 = (10^2) = (6^2 + 8^2) = (1^2 + 3^2 + 4^2 + 5^2 + 7^2)$$

Sample Input 2

100
3

Sample Output 2

Type here to search

24°C Mostly clear 02:37 17-01-2025

REC-CIS

```
1  /*
2  * Complete the 'powerSum' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts following parameters:
6  * 1. INTEGER x
7  * 2. INTEGER n
8  */
9
10 int powerSum(int x, int m, int n)
11 {
12     int temp;
13     temp=1;
14     for(int i=1;i<=n;i++)
15         temp=temp*m;
16     if(temp==x)
17         return 1;
18     if(temp>x)
19         return 0;
20     return powerSum(x,m+1,n)+powerSum(x-temp,m+1,n);
21 }
```

	Test	Expected	Got	
✓	printf("%d", powerSum(10, 1, 2))	1	1	✓