Gate Assignment

RONGALA ARUN SIDDARDHA - AI20BTECH11019

Download latex code from

https://github.com/ArunSiddardha/EE900/tree/main/ Gate_assignment/Gate_Assignment.tex

GATE-EC 2009 Q.41

Consider a system whose input x and input y are related by the equation,

$$y(t) = \int_{-\infty}^{\infty} x(t - \tau) h(2\tau) d\tau$$

where h(t) is shown in the graph. Which of the following properties are possessed by the system?

BIBO: Bounded input gives a bounded output

casual: the system is casual LP: The system is low pass

LTI: The system is linear and time-variant




Fig. 1: h(t)

- 1) Casual,LP
- 2) BBIO, LTI
- 3) BIBO,casual,LTI
- 4) LP,LTI

SOLUTION

Answer: 2

Lets take $\mathbf{h}(\mathbf{t})$ as $\sin(t)$ in the interval of - π to π .

LTI

We say that a system is **linear** if and only if it follows the Principle of Superposition, i.e Law of Additivity and Law of Homogeneity.

A system is said to be **time invariant** if the output

signal does not depend on the absolute time, i.e a time delay on the input signal directly equates to the delay in the output signal.

The system relating the input signal x(t) and output signal y(t), given by

$$y(t) = \int_{-\infty}^{\infty} x(t - \tau) h(2\tau) d\tau \qquad (0.0.1)$$

is linear and time invariant in nature.

From (0.0.1), we can say the system is linear if it follows both the laws of Additivity and Homogeneity.

Law of Additivity:

Let the two input signals be $x_1(t)$ and $x_2(t)$, and their corresponding output signals be $y_1(t)$ and $y_2(t)$, then:

$$y_1(t) = \int_{-\infty}^{\infty} x_1(t-\tau) h(2\tau) d\tau$$
 (0.0.2)

$$y_2(t) = \int_{-\infty}^{\infty} x_2(t-\tau) h(2\tau) d\tau$$
 (0.0.3)

$$y_1(t) + y_2(t) = \int_{t-T}^{t} \left[x_1(t-\tau)h(2\tau) + x_2(t-\tau)h(2\tau) \right] d\tau$$
(0.04)

Now, consider the input signal of $x_1(t) + x_2(t)$, then the corresponding output signal is given by y'(t):

$$y'(t) = \int_{t-T}^{t} \left[x_1 (t - \tau) h (2\tau) + x_2 (t - \tau) h (2\tau) \right] d\tau$$
(0.0.5)

Clearly, from (0.0.4) and (0.0.5):

$$y'(t) = y_1(t) + y_2(t)$$
 (0.0.6)

Thus, the Law of Additivity holds.

Law of Homogeneity:

Consider an input signal kx(t), where k is any constant. Let the corresponding output be given by

y'(t), then:

$$y'(t) = \int_{-\infty}^{\infty} kx (t - \tau) h(2\tau) d\tau \qquad (0.0.7)$$

$$=k\int_{-\infty}^{\infty}x\left(t-\tau\right)h\left(2\tau\right)d\tau\tag{0.0.8}$$

$$= ky(t) \qquad (0.0.9)$$

Clearly, from (0.0.9),

$$y'(t) = ky(t)$$
 (0.0.10)

Thus, the Law of Homogeneity holds. Since both the Laws hold, the system satisfies the Principle of Superposition, and is thus, a **linear** system.

BIBO:

We say that a system is BIBO stable if bounded input x(t) gives bounded input y(t). Here since h(t) is bounded if we give a bounded input x(t) and the integral is also is in between two bounded inputs so we get a bounded value of y(t). So the system is **BIBO stable**.

Therefore, The answer is **option 2**Taking the laplace transform form for the h(t)

$$H(s) = \int_{0}^{\infty} h(t)e^{-st}dt$$
 (0.0.11)


$$H(s) = \int_0^\infty \sin(t)e^{-st}dt \qquad (0.0.12)$$

$$H(s) = \frac{\cos(t) - s\sin(t)}{1 + s^2} e^{-st} \bigg|_0^{\infty}$$
 (0.0.13)

$$H(s) = 0 - \frac{1 - 0}{1 + s^2} \tag{0.0.14}$$

$$H(s) = \frac{-1}{1+s^2} \tag{0.0.15}$$

The laplace transform of the above function



also posses BBIO(because bounded input produces bounded output),LTI(trivial) properties.

So for the laplace transform also option 2 is correct