RAJALAKSHMI ENGINEERING COLLEGE

Arunchunai Nilesh S 251801026-2025-AIDS

A2

Started on	Monday, 31 August 2026, 1:58 PM
State	Finished
Completed on	Monday, 31 August 2026, 2:00 PM
Time taken	1 min 22 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int count(int arr[], int left, int right, int num)
{
    int i, c = 0;
    for (i = left; i <= right; i++)
    {
        if (arr[i] == num)
            c++;
    }
    return c;
}
int majorityElement(int arr[], int left, int right)
{
    if (left == right)
        return arr[left];
    int mid = left + (right - left) / 2;
    int leftMajority = majorityElement(arr, left, mid);
    int rightMajority = majorityElement(arr, mid + 1, right);
    if (leftMajority == rightMajority)
        return leftMajority;
    int leftCount = count(arr, left, right, leftMajority);
    int rightCount = count(arr, left, right, rightMajority);
    if (leftCount > rightCount)
        return leftMajority;
    else
        return rightMajority;
}
int main()
{
    int n, i;
    scanf("%d", &n);
    int arr[n];
    for (i = 0; i < n; i++)
    {
```

```
35          scanf("%d", &arr[i]);
36      }
37      printf("%d", majorityElement(arr, 0, n - 1));
38      return 0;
39  }
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course