



Sai
SAI RAM
ENGINEERING COLLEGE
INSTITUTE OF TECHNOLOGY

West Tambaram, Chennai - 44



YEAR

II

SEM

IV

CS8492

DATABASE MANAGEMENT SYSTEMS
(Common to CSE & IT)

UNIT No. 1

1.5 RELATIONAL MODEL

Version: 1.1



Relational Model Concepts

1. **Attribute:** Each column in a Table. Attributes are the properties which define a relation. e.g., Student_Rollno, NAME, etc.
2. **Tables** – In the Relational model the, relations are saved in the table format. It is stored along with its entities. A table has two properties rows and columns. Rows represent records and columns represent attributes.
3. **Tuple** – It is nothing but a single row of a table, which contains a single record.
4. **Relation Schema:** A relation schema represents the name of the relation with its attributes.
5. **Degree:** The total number of attributes which in the relation is called the degree of the relation.
6. **Cardinality:** Total number of rows present in the Table.
7. **Column:** The column represents the set of values for a specific attribute.
8. **Relation instance** – Relation instance is a finite set of tuples in the RDBMS system. Relation instances never have duplicate tuples.
9. **Relation key** - Every row has one, two or multiple attributes, which is called relation key.
10. **Attribute domain** – Every attribute has some pre-defined value and scope which is known as attribute domain

Table also called Relation

© guru99.com

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive

Primary Key (points to CustomerID)

Domain Ex: NOT NULL (points to CustomerName)

Tuple OR Row (points to the rows of the table)
Total # of rows is **Cardinality**

Column OR Attributes (points to the columns of the table)
Total # of column is **Degree**

Relational Integrity Constraints

Relational Integrity constraints in DBMS are referred to conditions which must be present for a valid relation. These Relational constraints in DBMS are derived from the rules in the mini-world that the database represents.

There are many types of Integrity Constraints in DBMS. Constraints on the Relational database management system is mostly divided into three main categories are:

1.

Domain Constraints

Domain constraints can be violated if an attribute value is not appearing in the corresponding domain or it is not of the appropriate data type.

Domain constraints specify that within each tuple, and the value of each attribute must be unique. This is specified as data types which include standard data types integers, real numbers, characters, Booleans, variable length strings, etc.

Example:

```
Create DOMAIN CustomerName  
CHECK (value not NULL)
```

The example shown demonstrates creating a domain constraint such that CustomerName is not NULL

Key Constraints

An attribute that can uniquely identify a tuple in a relation is called the key of the table. The value of the attribute for different tuples in the relation has to be unique.

Example:

In the given table, CustomerID is a key attribute of Customer Table. It is most likely to have a single key for one customer, CustomerID =1 is only for the CustomerName =" Google".

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive

Referential Integrity Constraints

Referential Integrity constraints in DBMS are based on the concept of Foreign Keys. A foreign key is an important attribute of a relation which should be referred to in other relationships. Referential integrity constraint state happens where relation refers to a key attribute of a different or same relation. However, that key element must exist in the table.

Example:

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive

Customer

InvoiceNo	CustomerID	Amount
1	1	\$100
2	1	\$200
3	2	\$150

Billing

In the above example, we have 2 relations, Customer and Billing.

Tuple for CustomerID =1 is referenced twice in the relation Billing. So we know CustomerName=Google has billing amount \$300

Operations in Relational Model

Four basic update operations performed on relational database model are

Insert, update, delete and select.


- Insert is used to insert data into the relation
- Delete is used to delete tuples from the table.
- Modify allows you to change the values of some attributes in existing tuples.
- Select allows you to choose a specific range of data.

Whenever one of these operations are applied, integrity constraints specified on the relational database schema must never be violated.

Insert Operation

The insert operation gives values of the attribute for a new tuple which should be inserted into a relation.

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive



CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive
4	Alibaba	Active

Update Operation

You can see that in the below-given relation table CustomerName= 'Apple' is updated from Inactive to Active.

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive
4	Alibaba	Active




CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Active
4	Alibaba	Active

Delete Operation

To specify deletion, a condition on the attributes of the relation selects the tuple to be deleted.

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Active
4	Alibaba	Active



CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
4	Alibaba	Active

In the above-given example, CustomerName= "Apple" is deleted from the table.

The Delete operation could violate referential integrity if the tuple which is deleted is referenced by foreign keys from other tuples in the same database.

Select Operation

CustomerID	CustomerName	Status		CustomerID	CustomerName	Status
1	Google	Active		2	Amazon	Active
2	Amazon	Active				
4	Alibaba	Active				

In the above-given example, CustomerName="Amazon" is selected

Best Practices for creating a Relational Model

- Data need to be represented as a collection of relations
- Each relation should be depicted clearly in the table
- Rows should contain data about instances of an entity
- Columns must contain data about attributes of the entity
- Cells of the table should hold a single value
- Each column should be given a unique name
- No two rows can be identical
- The values of an attribute should be from the same domain

Advantages of using Relational Model

- **Simplicity:** A Relational data model in DBMS is simpler than the hierarchical and network model.
- **Structural Independence:** The relational database is only concerned with data and not with a structure. This can improve the performance of the model.
- **Easy to use:** The Relational model in DBMS is easy as tables consisting of rows and columns are quite natural and simple to understand
- **Query capability:** It makes possible for a high-level query language like SQL to avoid complex database navigation.

- **Data independence:** The Structure of Relational database can be changed without having to change any application.
- **Scalable:** Regarding a number of records, or rows, and the number of fields, a database should be enlarged to enhance its usability.

Disadvantages of using Relational Model

- Few relational databases have limits on field lengths which can't be exceeded.
- Relational databases can sometimes become complex as the amount of data grows, and the relations between pieces of data become more complicated.
- Complex relational database systems may lead to isolated databases where the information cannot be shared from one system to another.