# MySQL

October 13, 2023

#### 1 Connection

```
[1]: import mysql.connector
conn=mysql.connector.connect(
    host="localhost",
    user="root",
    password="",
    db="employee"

)
cur = conn.cursor()
```

#### 2 Table Creation

```
[]: cur.execute("CREATE TABLE emp (e_id INT ,e_name VARCHAR(50),e_desig_

→VARCHAR(50),e_sal INT,e_addr VARCHAR(90),e_phno INT)")
```

# 3 Insert Single Record

```
[]: sql = "INSERT INTO emp VALUES (1001, 'Anto', 'tester', 50000, 'Tuticorin', 

→ '9548755375')"

cur.execute(sql)

conn.commit()
```

### 4 Insert Multiple Records

```
[33]: sql = "INSERT INTO emp (e_id, e_name, e_desig, e_sal, e_addr, e_phno) VALUES_\( \times (\%\s, \%\s, \%\s, \%\s, \%\s)\)"

val = [(1002, 'Sharan', 'tester', 50000, 'Bangalore', '9548755375'),

(1003, 'Darun', 'developer', 70000, 'Chennai', '9543655375'),

(1004, 'Ajith', 'manager', 40000, 'Coimabatore', '958855375'),
```

#### 5 Select Table

### 6 Update Record

```
[4]: cur.execute("UPDATE emp SET e_desig='manager' where e_name='Sharan'") conn.commit()
```

# 7 Order by

```
[5]: cur.execute("SELECT * FROM emp ORDER BY e_name")
a= cur.fetchall()
for x in a:
    print(x)

(1004, 'Ajith', 'manager', 40000, 'Coimabatore', 958855375)
(1001, 'Anto', 'tester', 50000, 'Tuticorin', 9548755375)
(1003, 'Darun', 'developer', 70000, 'Chennai', 9543655375)
(1008, 'Haran', 'Designer', 890000, 'Trivandrum', 95487550968)
(1007, 'Krish', 'HR', 120000, 'Saudi', 9548755867)
(1005, 'Prakash', 'clerk', 110000, 'Mumbai', 952589375)
```

```
(1002, 'Sharan', 'manager', 50000, 'Bangalore', 9548755375)
(1006, 'Velan', 'security', 90000, 'Madurai', 9548755089)
```

### 8 Delete record

```
[9]: cur.execute("DELETE FROM emp WHERE e_id='1006'")
conn.commit()
```