

# Kubernetes **regcred** – Quick Runbook

## 1. What is **regcred**?

**regcred** is a Kubernetes Secret used to authenticate with a private Docker/container registry.

In this cluster:

Cluster: sqs-india-demo-eks  
Namespace: bominsso-prod  
Secret: regcred  
Registry: registry.devopsark.com

It is normally used by pods to pull private Docker images.

## 2. Check the Secret

```
kubectl get secret regcred -n bominsso-prod
```

Expected:

| NAME    | TYPE                           | DATA | AGE |
|---------|--------------------------------|------|-----|
| regcred | kubernetes.io/dockerconfigjson | 1    | ... |

## 3. Check which registry it uses

```
kubectl get secret regcred -n bominsso-prod \
-o jsonpath='{.data.\.dockerconfigjson}' | base64 -d | jq -r '.auths | keys[]'
```

Expected:

```
registry.devopsark.com
```

## 4. Check the stored username

```
kubectl get secret regcred -n bominsso-prod \
-o jsonpath='{.data.\.dockerconfigjson}' | base64 -d | \
jq -r '.auths["registry.devopsark.com"].auth' | base64 -d | cut -d: -f1
```

## 5. Check which Deployments use **regcred**

```
kubectl get deployments -n bominsso-prod \
-o jsonpath='{range .items[*]}{.metadata.name}{ " -> " }
"{.spec.template.spec.imagePullSecrets[*].name}{ " \n " }{end}'
```

Example:

```
backend -> regcred
frontend -> regcred
```

## 6. Update **regcred**

Use this when the registry password/token has expired or changed.

Replace:

```
YOUR_USERNAME  
YOUR_PASSWORD_OR_TOKEN
```

with the new registry credentials.

```
kubectl create secret docker-registry regcred \  
-n bominsoproduct \  
--docker-server=registry.devopsark.com \  
--docker-username='YOUR_USERNAME' \  
--docker-password='YOUR_PASSWORD_OR_TOKEN' \  
--dry-run=client -o yaml | kubectl apply -f -
```

**Do not delete the existing Secret first.**

The command updates the existing **regcred**.

## 7. Verify the Secret

```
kubectl get secret regcred -n bominsoproduct
```

Check the registry again:

```
kubectl get secret regcred -n bominsoproduct \  
-o jsonpath='{.data.\.dockerconfigjson}' | base64 -d | jq -r '.auths | keys[]'
```

Expected:

```
registry.devopsark.com
```

## 8. If Pods are still failing

Check pods:

```
kubectl get pods -n bominsoproduct
```

If you see:

```
ImagePullBackOff  
ErrImagePull
```

check the pod:

```
kubectl describe pod <POD_NAME> -n bominsoproduct
```

Look at the **Events** section for the image-pull error.

---

## 9. Restart a Failed Pod

If the credentials were updated and the pod is still using the old failed attempt:

```
kubectl delete pod <POD_NAME> -n bomins0-prod
```

The Deployment will automatically create a new pod.

Then check:

```
kubectl get pods -n bomins0-prod
```

## Quick Commands

### Check Secret

```
kubectl get secret regcred -n bomins0-prod
```

### Check Registry

```
kubectl get secret regcred -n bomins0-prod \
-o jsonpath='{.data.\.dockerconfigjson}' | base64 -d | jq -r '.auths | keys[]'
```

### Update Secret

```
kubectl create secret docker-registry regcred \
-n bomins0-prod \
--docker-server=registry.devopsark.com \
--docker-username='YOUR_USERNAME' \
--docker-password='YOUR_PASSWORD_OR_TOKEN' \
--dry-run=client -o yaml | kubectl apply -f -
```

### Check Pods

```
kubectl get pods -n bomins0-prod
```

### Check Pod Error

```
kubectl describe pod <POD_NAME> -n bomins0-prod
```

### Restart Failed Pod

```
kubectl delete pod <POD_NAME> -n bomins0-prod
```

**Important:** Never paste the decoded `.dockerconfigjson` or the registry password/token into tickets, chats, or documentation.