ECE 321: Software Requirements Engineering Assignment 3

Arun Woosaree

1514457

October 30, 2018

Axioms begin on next page

algebra QueueOfCars

> imports Integer, Boolean;
> introduces

>> sorts Queue, Car;

> operations

>> New: → Queue;
>> CarArrives: Car x Queue → Queue;
>> CarDeparts: Queue → Queue;
>> IsEmpty: Queue → Boolean;
>> NumberOfCars: Queue → Integer;
>> Longer: Queue x Integer → Boolean;
>> FirstCar: Queue → Car;
>> Equal: Queue x Queue → Boolean;
>> WhichQueue: Queue x Queue x Car → Integer;
>> Position: Car x Queue → Integer;

> constrains New, CarArrives, CarDeparts, IsEmpty, NumberOfCars, Longer, FirstCar, Equal, WhichQueue, Position, so that Queue generated by [New, CarArrives]

for all [q:Queue, q1:Queue, c:Car, c1:Car i:Integer]

CarDeparts(New) = error;
CarDeparts(CarArrives(c,q)) =

if IsEmpty(q) then q;
else CarArrives(c,CarDeparts(q));

IsEmpty(New) = true;
IsEmpty(CarArrives(c,q)) = false;
NumberOfCars(New) = 0;
NumberOfCars(CarArrives(c,q)) = NumberOfCars(q) + 1;
Longer(New, i) = false;
Longer(CarArrives(c,q), i) =

if (i < NumberOfCars(q) + 1) then true;
else false;

FirstCar(New) = error;
FirstCar(CarArrives(c,q)) =

if IsEmpty(q) then c;
else FirstCar(q);

Equal(New, New) = true;
Equal(CarArrives(c,q), New) = false;
Equal(New, CarArrives(c,q)) = false;
Equal(CarArrives(c,q), CarArrives(c1,q1)) =

if (NumberOfCars(q) == NumberOfCars(q1)) then true;
else false;

WhichQueue(New, New, c) = 0;
WhichQueue(New, CarArrives(c,q), c1) =

if (Position(c1,q > -1) then 2;
else 0;

WhichQueue(CarArrives(c,q), New, c1) =

if (Position(c1,q > -1) then 1;
else 0;

WhichQueue(CarArrives(c,q), CarArrives(c1,q1), c2) =

    if Position(c2,q) > -1 then 1;
    else if Positon(c2, q1) > -1 then 2;
    else 0;

Position(c, New) = -1;
Position(c1, CarArrives(c,q)) =

    if (c1 == c) then NumberOfCars(q);
    else Position(c1,q);

end QueueOfCars