

**Version 1.4**  
**12/19/19**

# Important Prerequisites and Setup

2

- Have a recent version of Git downloaded and running on your system

<https://www.git-scm.org/>

- If you don't already have one, sign up for a free Github account

<https://www.github.com>

- Download (and print if desired) labs doc from

<https://github.com/brentlaster/safaridocs/blob/master/git-fun-labs.pdf>

(Above is automatic download link. Can also go to

<https://github.com/brentlaster/safaridocs> and get git-fun-labs.pdf.

2

# Git Fundamentals

**Brent Laster**





# About me

- Director, R&D
- Global trainer – training (Git, Jenkins, Gradle, Gerriit, Continuous Pipelines)
- Author -
  - OpenSource.com
  - Professional Git book
  - Jenkins 2 – Up and Running book
  - Continuous Integration vs. Continuous Delivery vs. Continuous Deployment mini-book on Safari
- <https://www.linkedin.com/in/brentlaster>
- @BrentCLaster

# Book – Professional Git

- Extensive Git reference, explanations, and examples
- First part for non-technical
- Beginner and advanced reference
- Hands-on labs

**Professional Git** 1st Edition  
by Brent Laster (Author)

★★★★★ 7 customer reviews

[Look inside](#)



Amazon Customer

★★★★★ I can't recommend this book more highly

February 12, 2017

Format: Kindle Edition

Brent Laster's book is in a different league from the many print and video sources that I've looked at in my attempt to learn Git. The book is extremely well organized and very clearly written. His decision to focus on Git as a local application for the first several chapters, and to defer discussion about it as a remote application until later in the book, works extremely well.

Laster has also succeeded in writing a book that should work for both beginners and people with a fair bit of experience with Git. He accomplishes this by offering, in each chapter, a core discussion followed by more advanced material and practical exercises.

I can't recommend this book more highly.

★★★★★ Ideal for hands-on reading and experimentation


February 23, 2017

Format: Paperback | [Verified Purchase](#)

I just finished reading Professional Git, which is well organized and clearly presented. It works as both a tutorial for newcomers and a reference book for those more experienced. I found it ideal for hands-on reading and experimentation with things you may not understand at first glance. I was already familiar with Git for everyday use, but I've always stuck with a convenient subset. It was great to be able to finally get a much deeper understanding. I highly recommend the book.

# Jenkins 2 Book

- Jenkins 2 – Up and Running
- Deployment pipeline automation as code
- “It’s an ideal book for those who are new to CI/CD, as well as those who have been using Jenkins for many years. This book will help you discover and rediscover Jenkins.” *By Kohsuke*



★★★★★ This is highly recommended reading for anyone looking to use Jenkins 2 to ...

By [Leila](#) on June 2, 2018

Format: Paperback

Brent really knows his stuff. I'm already a few chapters in, and I'm finding the content incredibly engaging. This is highly recommended reading for anyone looking to use Jenkins 2 to implement CD pipelines in their code.

★★★★★ A great resource

By [Brian](#) on June 2, 2018

Format: Paperback

I have to admit that most of the information I get usually comes through the usual outlets: stack overflow, Reddit, and others. But I've realized that having a comprehensive resource is far better than hunting and pecking for scattered answers across the web. I'm so glad I got this book!





# What is Git?

7

- Distributed Version Control System
- Open source
- Available for multiple platforms
- Roots in source control efforts for Linux Kernel
- Primary developer – Linus Torvalds
- Been around since 2005

7



# Git Design Goals

8

- Speed
- Simple design
- Strong support for branching
- Distributed nature
- Ability to handle large projects efficiently
- Disconnected support





# Installation

9

## Debian/Ubuntu

```
$ apt-get install git
```

## Fedora (up to 21)

```
$ yum install git
```

## Fedora (22 and beyond)

```
$ dnf install git
```

## FreeBSD

```
$ cd /usr/ports/devel/git
```

```
$ make install
```

## Gentoo

```
$ emerge --ask --verbose dev-vcs/git
```

## OpenBSD

```
$ pkg_add git
```

## Solaris 11 Express


```
$ pkg install developer/versioning/git
```

9

# Ecosystem: Public hosting

10

- Github, Bitbucket, etc.




10

# Ecosystem: Self-hosting

11

- GitLab, Enterprise GitHub




11



# Ecosystem: Ease-of-use Packages


12



## SourceTree

Platforms: Mac, Windows


Price: Free



## Git Extensions

Platforms: Windows


Price: Free



## SmartGit

Platforms: Windows, Mac, Linux

Price: \$79/user / Free for non-commercial use



## git-cola


Platforms: Windows, Mac, Linux

Price: Free



## GitUp

Platforms: Mac



## GitEye

Platforms: Windows, Mac, Linux

12

# Ecosystem: Tools that Incorporate Git

13

The screenshot shows the GitHub web interface for a pull request. The browser address bar shows 'localhost:8081/#/c/1/1'. The page has tabs for 'All', 'My', 'Projects', 'People', and 'Documentation'. Below these are sub-tabs for 'Changes', 'Drafts', 'Draft Comments', 'Watched Changes', 'Starred Changes', and 'Groups'. The main content area shows 'Change 1 - Needs Code-Review' with the text 'it's a fact' and a 'Change-Id: I8502da0e6b037cc9dafde806c46c6e6c66f5b301'. A code review overlay is visible on the right, showing a comment 'Looks fine.' and a 'Code-Review' section with a 'Post' button. Below the overlay, the commit details are shown: Author 'Workshop User <NfjsUser1@gmail.com>', Committer 'Workshop User <NfjsUser1@gmail.com>', Commit '2f9778a9d7b935990a61fc6139ed7ae668d8c5af', Parent(s) 'cd4e6d1aa38922c9d5135f3463d345efe0506a30', and Change-Id 'I8502da0e6b037cc9dafde806c46c6e6c66f5b301'. The 'Files' section shows a table with columns 'File Path', 'Comments', and 'Size'. The file 'captains.log' is listed with 1 comment and a size of +1, -0. The 'History' section shows a table with columns 'Contributor', 'Action', and 'Time'. The entry 'Spock (Contributor)' is listed with the action 'Uploaded patch set 1.' and the time '1:54 PM'.

localhost:8081/#/c/1/1

All My Projects People Documentation

Changes Drafts Draft Comments Watched Changes Starred Changes Groups

Change 1 - Needs Code-Review

it's a fact

Change-Id: I8502da0e6b037cc9dafde806c46c6e6c66f5b301

Reply...

Patch Sets (1/1) Download

Looks fine.

-1 0 +1

Code-Review ☐ ☐ ☒ Looks good to me, but someone else must approve

Post Cancel

Post reply (Shortcut: Ctrl+Enter)

Code-Review

Author Workshop User <NfjsUser1@gmail.com> Oct 19, 2015 1:53 PM

Committer Workshop User <NfjsUser1@gmail.com> Oct 19, 2015 1:53 PM

Commit 2f9778a9d7b935990a61fc6139ed7ae668d8c5af

Parent(s) cd4e6d1aa38922c9d5135f3463d345efe0506a30

Change-Id I8502da0e6b037cc9dafde806c46c6e6c66f5b301

Files

Open All Diff against: Base Edit

File Path Comments Size

☐ Commit Message

☒ captains.log 1 +1, -0

History

Expand All

Spock (Contributor) Uploaded patch set 1. 1:54 PM

13


# Git Interfaces

- Many different interfaces exist for working with Git
- Many GUI interfaces
- Command line interface
- Products that script the command line
- Other products such as Gerrit that wrap around Git
- We teach the command line interface because
  - GUI interfaces can all be different - there is not a standard
  - GUI interfaces may change or go away
  - If a GUI interface does not provide some piece of Git functionality, the functionality can be done with the command line
  - If you understand the command line, you can usually find which command in a GUI is used to do the operation




# Centralized vs. Distributed VCS


Centralized Version Control Model



Distributed Version Control Model





# Git in One Picture





# Git Granularity (What is a unit?)

17

- In traditional source control, the unit of granularity is usually a file




- In Git, the unit of granularity is usually a tree






# Delta Storage Model




# Snapshot Storage Model

19



# Compressing Files

20





# Staging Area: Why?

## Prepare


- *Stores info about what will go into next commit*
- *Allows you to control what part of the working tree go into the next commit*
- *Allows you to queue up individual changes*
  - *Bundle a collection of specific changes to go into a commit*
  - *Get them out of your working directory (i.e. “check them off”)*
- *Helps you split up one large change into multiple commits*

## Repair

- *Allows you to “amend” last commit – redo*

## Merging with conflicts

- *When merge happens, changes that merge cleanly are updated both in working directory and in staging area*
- *Changes that did not merge cleanly are left in your working directory*
- *Diff between working directory and staging area shows differences*




1. Modify files in working directory
2. Stage files, adding snapshot to staging area
3. Commit – promotes files from the staging area into permanent snapshot in the local repo (stored in .git directory)

# Initializing a Repo and Adding Files (commands)

- **git init**
  - For creating a repository in a directory with existing files
  - Creates repository skeleton in .git directory
- **git add**
  - Tells git to start tracking files
  - Patterns: `git add *.c` or `git add .` (. = files and dirs recursively)
- **git commit**
  - Promotes files into the local repository
  - Uses `-m` to supply a comment
  - Commits everything unless told otherwise





# SHA1



24

```
$ git commit -m "initial add of file1.c"  
[master b41b186] initial add of file1.c  
1 file changed, 3 insertions(+)  
create mode 100644 file1.c
```

- Everything in Git is check-summed before it is stored and is then referred to by that checksum. Built into Git low-level functions.
- That means it's not possible to change the contents of any file or directory without Git knowing about it. i.e. avoids file corruption or tampering.
- Mechanism that Git uses for this checksum is called a SHA-1 hash.
- 40-character string of hex characters.
- Calculated based on contents of a file or directory structure.
- Example: **b41b186552252987aa493b52f8696cd6d3b00373**
- Used throughout Git.
- Git stores/points to everything by hash value of the contents in its database.

Remember: You can always get a handle to a snapshot via a SHA1.

# Committing Changes

- **Commits to local repo only - not remote**
- **Records a snapshot of your local working area that you can switch back to or compare to later**
- **Requires commit message**
  - **Pass by `-m "<message>"`**
  - **If no `-m`, brings up configured editor so you can type it**
- **Commit output**
  - **which branch you committed to**
  - **what SHA-1 checksum the commit has**
  - **how many files were changed**
  - **statistics about lines added and removed in the commit.**




# Git Workflow

*Staging Area Use: Prepare...*

**git commit -m "<comment>"**

**git add .**

**git add -p**







# Undoing/Updating Things

- **git commit --amend**
  - Allows you to “fix” last commit
  - Updates last commit using staging area
  - With nothing new in staging area, just updates comment (commit message)
  - Example:
    - » **git commit -m “my first update”**
    - » **git add newfile.txt** (add command stages it into staging area)
    - » **git commit --amend**
    - » This updated commit takes the place of the first (updates instead of adding another in the chain)

# Git Workflow

*Staging Area Use:Repair...*

**git add .**  
**git commit --amend**



# Initial User Configuration

- Command: **git config**
- Main things to set
  - User name
    - \$ git config --global user.name "John Doe"
  - Email address
    - \$ git config --global user.email [johnndoe@example.com](mailto:johnndoe@example.com)
- Notes
  - Use --global to persist options for all repos of this user
  - Check config value with
    - \$ git config --list (or git config -l)
    - \$ git config <property> as in git config user.name
  - Can also set many other things – like diff tool and end-of-line settings



# Configuring your default editor in Git

- Editor defaults (generally)
  - Windows : notepad, Linux : vim
- Can set via OS (for example export EDITOR variable)
- Setting for Git only
  - Set core.editor in your config file: **git config --global core.editor "vim"**
  - Set the GIT\_EDITOR environment variable: **export GIT\_EDITOR=vim**
- Examples
  - git config core.editor vim (Linux)
  - git config --global core.editor "nano" (mac)
  - git config --global core.editor "'c:\program files\windows nt\accessories\wordpad.exe'"(windows)
  - git config --global core.editor "'C:/Program Files (x86)/Notepad++/notepad++.exe'"
  - (Git bash shell for Windows)

Work through the steps – some questions for thought included

## Creating Files

In the workshop, we're not concerned about contents of files.  
We just need some files to play with.

Lazy way to create a file – in a terminal:

`$ echo stuff > file1.c` (even lazier way `$ date > file1.c`)

Lazy way to append to a file – in a terminal:

`$ echo "more stuff" >> file1.c`

Can use editor if you prefer...

## Creating and Exploring a Git Repository and Managing Content

Purpose: In this lab, we'll create an empty Git repository on your local disk and stage and commit content into it.



# Git and File/Directory Layouts

33

## Local Repository File Layout

### Git snapshot

COMMIT	807805e...
Author	Brent Laster <Brent.Laster@sas.com>
Date	Thu Aug 2 19:55:38 2012
Comment	Initial Push
Link	4c7637a... (TREE ./)

### Working directory

dir: proj1

file1.java

file2.java

TREE	4c7637a... (./)
Link	88bee8f... (TREE proj1 040000)

TREE	88bee8f... (proj1)
Link	ba2906d... (BLOB file1.java 100644)
Link	3a0e351... (BLOB file2.java 100644)

BLOB ba2906d... (file1.java)

main...

BLOB 3a0e351... (file2.java)


subs...

```
$ tree.sh -*.git
COMMIT_EDITMSG
HEAD
config
description
hooks
    applypatch-msg.sample
    commit-msg.sample
    post-commit.sample
    post-receive.sample
    post-update.sample
    pre-applypatch.sample
    pre-commit.sample
    pre-rebase.sample
    prepare-commit-msg.sample
    update.sample
index
info
    exclude
logs
    HEAD
    refs
        heads
            master
objects
    3a
        0e351dc84e32a bec 5d4d d223c 5abd abd5 7b 7f5
    4c
        7637a4b66aefc1 ee877eaa 1afc706 10f0ee7cc
    80
        7805ea7ae9fdf 1b06e876 af6e9a69a34 9b52a3
    88
        bee8f0c181784d 605eabe35fb04a5a44 3ae6b7
    ba
        2906d0666cf7 26c 7eaa dd2cd3d b6 15de df df3a
    info
        *
    pack
        *
refs
    heads
        master
    tags
        *
```

33

# Starting Work with Git – Multiple Repositories

The repository (.git directory) lives in the local directory tree.



# Autocomplete

- Enabled in BASH shell
- Can be enabled in other environments via file in git source
- Git <start of command><tab> (may have to hit it twice if multiple options)
- Git command --<start of option><tab>
- Examples:
  - **git co <tab><tab>**
  - **git com <tab>**
  - **git list --s<tab> (note double -'s)**





# Getting Help

- `git <command> -h`

Brings up on screen list of options


- `git <command> --help`

- `git help <command>`

Brings up html man page

# Line Endings

- `git config core.autocrlf`




# Git Config file

- **Scope**
  - Local (repo)
    - » **.git/config**
  - Global (user)
    - » **~/.gitconfig**
  - System (all users on a system)
    - » **<usr|usr/local> /etc/gitconfig**
- **Divided into sections**
- **Can have user settings, aliases, etc.**
- **Text file that can be edited, but safer to use git config**




# Understanding Git Configuration Files Scope<sup>39</sup>



# Git Configuration Layout – Multiple Confs

40



40

# Terminology: File States in Working Directory

Files in your working directory can be in one of two main states:

- **Tracked**
  - Were in the last snapshot (last commit)
  - Can be
    - Unmodified - same as what's in Git
    - Modified - different from what's in Git
    - Staged
    - OR -
- **Untracked**
  - Everything else
  - Not in last snapshot
  - Not in staging area

## 3 questions to think about for determining status

- Is Git aware of the file (is it in Git)? tracked or untracked
- What is in the staging area?
- What is the relationship of the latest version in Git to the version in the working directory?



# File Status Lifecycle

1. Files start out in wd (rev a)  
 Git aware? No – **untracked** files  
 Anything staged? No = Changes **not staged** for commit  
 Git compared to WD: N/A


2. (Git) Add file.  
 Git aware: Yes – **tracked**  
 Anything staged? Rev a staged = Changes **to be committed**  
 Git compared to WD: Same - **unmodified**

3. Edit in working directory (rev b)  
 Git aware: Yes – **tracked**  
 Anything staged? Rev a **staged (to be committed)**  
 Git compared to WD : Different – **modified**

4. (Git) Add file. **Tracked**, rev b **staged** (rev a overwritten), **unmodified**

5. (Git) Commit. **Tracked**, Staged: Nothing, **unmodified**

“nothing to commit (working directory clean)”



\* “Changes to be committed” = staged

\* “Changes not staged for commit” = wd

- **Command: `git status`**
  - Primary tool for showing which files are in which state
  - `-s` is short option - output `<1 or more characters><filename>`
    - » `??` = untracked
    - » `M` = modified
    - » `A` = added
    - » `D` = deleted
    - » `R` = renamed
    - » `C` = copied
    - » `U` = updated but unmerged
  - `-b` option – always show branch and tracking info
- **Common usage: `git status -sb`**

# Updating a file that Git knows about

- How do we update a file that git knows about?
  - **Stage it (git add .)**
  - **Commit it (git commit)**
  - **Shortcut syntax : git commit -am “<comment>”**
    - » **Doesn't add new files (untracked ones)**



# Git Special References: Head and Index

45

- **Head**
  - Snapshot of your last commit
  - Next parent (in chain of commits)
  - Pointer to current branch reference (reference = SHA1)
  - **Think of HEAD as pointer to last commit on current branch**
- **Index (Staging Area)**
  - Place where changes for the next commit get registered
  - Temporary staging area for what you're working on
  - Proposed next commit
- **Cache - old name for index**
- **Think of cache, index, and staging area as all the same**

45

# Showing Differences

- Command : **git diff**
- Default is to show changes in the working directory that are not yet staged.
- If something is staged, shows diff between working directory and staging area.
- Option of **--cached** or **--staged** shows difference between staging area and last commit (HEAD)
- **git diff <reference>** shows differences between working directory and what <reference> points to – example “git diff HEAD”


# Understanding File Diffs

1. Assume file (rev a) created, added and committed in the staging area.
2. Assume file (rev b) created, added and committed in the staging area.
3. Assume file (rev c) created, added and committed in the staging area.

**Git diff --staged**  
 Git diff --staged compares:  
 Working Directory to Local Repo  
 Results: Differences between Staging Area and Local Repo  
 Local Repo Differences between WD and Local Repo

```

MINGW32:~/diffpp
$ git diff --staged
diff --git c/file1.txt i/file1.txt
index 257cc56..12955d3 100644
--- c/file1.txt
+++ i/file1.txt
@@ -1,2 @@
foo
+more
sasbcl@L75088 ~/diffpp (master)
$
  
```





## Tracking Content through the File Status Lifecycle

**Purpose:** In this lab, we'll work through some simple examples of updating files in a Local Environment and viewing the status and differences between the various levels along the way.

# History

- Command: **git log**
- With no options, shows name, sha1, email, commit message in reverse chronological order (newest first)
- -p option shows patch – or differences in each commit
  - Shortcut : git show
- -# -shows last # commits
- --stat – shows statistics on number of changes
- --pretty=oneline|short|full|fuller
- --format – allows you to specify your own output format
- --oneline and --format can be very useful for machine parsing
- Time-limiting options --since|until|after|before (i.e. --since=2.weeks or --before=3.19.2011)
- gitk tool also has history visualizer

# Sample git log format

- **git log --pretty=format:"%h %ad | %s%d [%an]" --graph --date=short**
- **In detail...**
  - **--pretty="..."** defines the output format.
  - **%h** is the abbreviated hash of the commit
  - **%d** commit decorations (e.g. branch heads or tags)
  - **%ad** is the commit date
  - **%s** is the comment
  - **%an** is the name of the author
  - **--graph** tells git to display the commit tree in the form of an ASCII graph layout
  - **--date=short** keeps the date format short and nice



# Git log examples

- `git log --pretty=oneline --max-count=2`
- `git log --pretty=oneline --since='5 minutes ago'`
- `git log --pretty=oneline --until='5 minutes ago'`
- `git log --pretty=oneline --author=<your name>`
- `git log --pretty=oneline --all`
- `git log --oneline --decorate`

# Git Aliases

- Allow you to assign alternatives for command and option strings
- Can set using
  - `git config alias.<name> <operation>`
- Example
  - `git config --global alias.co checkout`
  - After, “git co” = “git checkout”
- Example aliases (as they would appear inside config file)

[alias]

co = checkout

ci = commit


st = status

br = branch

hist = log --pretty=format:\'"%h %ad | %s%d [%an]\'" --graph --date=short

# Seeing History Visually

- gitk – graphical interface that comes with most git
- Shows history of local repository (not remote) in working directory
- Also useful to be able to see how changes look graphically






# Tags in git

- **Command:** **git tag**
- **Two types**
  - **Lightweight** – like regular tag, pointer to specific commit
  - **Annotated** – stored as full object in the database
    - » **Checksummed**
    - » **Contain full email and date, tagger name, and comment**
    - » **Created by `git tag -a <tag> -m <message>`**
- **Create a tag**
  - **Git tag <tagname> <hash>**
- **Show tags**
  - **Git tag (lists tags out)**
  - **Git show <tag> - shows detail**

# Notes about Tags

- You tag commits (hashes), not files
- A tag is a reference (pointer) to a commit that stays with that commit
- To reference a file via a tag, you need to qualify with the file name (since the tag refers to entire commit)



## Working with Changes Over Time and Using Tags

Purpose: In this lab, we'll work through some simple examples of using the Git log commands to see the flexibility it offers as well as creating an alias to help simplify using it. We'll also look at how to tag commits to have another way to reference them.



# Supporting Files - .gitignore

- Tells git to not track files or directories (normally listed in a file named .gitignore)
- Operations such as `git add .` will skip files listed in .gitignore
- Rules
  - Blank lines or lines starting with `#` are ignored.
  - Standard glob patterns work.
  - You can end patterns with a forward slash (`/`) to specify a directory.
  - You can negate a pattern by starting it with an exclamation point (`!`).
- What types of things might we want git to ignore?

# Supporting Files - .gitattributes

- A git attributes file is a simple text file that gives attributes to pathname – meaning git applies some special setting to a path or file type.
- Attributes are set/stored either in a .gitattributes file in one of your directories (normally the root of your project) or in the .git/info/attributes file if you don't want the attributes file committed with your project.
- Example use: dealing with binary files
- To tell git to treat all obj files as binary data, add the following line to your .gitattributes file:
  - \*.obj binary
  - With this setup, git won't try to convert or fix eol issues. It also won't try to compute or print a diff for changes in this file when you run git show or git diff on your project.

# Git Attributes File – Example

59

- Basic example

```
# Set default behaviour, in case users don't have core.autocrlf set.
* text=auto

# Explicitly declare text files we want to always be normalized and converted
# to native line endings on checkout.
*.c text
*.h text

# Declare files that will always have CRLF line endings on checkout.
*.sln text eol=crlf

# Denote all files that are truly binary and should not be modified.
*.png binary
*.jpg binary
```

- Advantage is that this can be put with your project in git. Then, the end of line configuration now travels with your repository. You don't need to worry about whether or not all users have the proper line ending configuration.
- Some sample gitattributes files in GitHub for certain set of languages.

59



# Removing files


- Command: **git rm**
- Process: Operations removes from tracked files, stages deletion, and then you commit to complete it
- Git rm
  - Removes it from your working directory (via `rm <file>`) so it doesn't show up in tracked files
  - Stages removal
- If you have a staged version **AND** a different modified version, git will warn you
  - Use the `-f` option to force the removal
- Can remove just from the staging area using `--cached` option on `git rm`
- Can provide files, directories, or file globs to command

# Git Workflow for operations like rm

1. Git performs the operation in the working directory
2. Git stages the change
3. User commits to finalize the operation in the repository.

**git rm file2**

**git commit -m "finalize rm"**



# Discarding Changes



- **Local changes before staging**
  - use git checkout (to get latest version from repository to working dir)
- **Changes already staged**
  - git reset HEAD <filename>
    - » Resets branch pointer
    - » Can use manual edit or checkout to update directory
- **Getting back to a clean working directory AND staging area**
  - git reset --hard HEAD
- **Think of reset as a “rollback” (moves HEAD pointer back to a previous commit but does not delete existing commits)**
- **Supporting command: git stash**
  - saves off state
  - use git stash pop or git stash apply to get old state back



# Git Stash


- Keep a backup queue of your work
  - command: **git stash**
  - saves off state
  - use **git stash pop** or **git stash apply** to get old state back

```
$ git stash pop --stash@{0}
```



# Reset and Revert



- `Reset --` allows you to “roll back” so that your branch points at a previous commit ; optionally also update working directory to that commit
- Use case - you want to update your local environment back to a previous point in time; you want to overwrite or a local change you’ve made
- Warning: `--hard` overwrites everything
- `Revert --` allow you to “undo” by adding a new change that cancels out effects of previous one
- Use case - you want to cancel out a previous change but not roll things back
- Note: The net result of using `reset` vs. `revert` can be the same. If so, and content that is being reset/revert has been pushed such that others may be consuming it, preference is for `revert`.



`git reset --hard 87ba8bc`

`git reset current~1 [--mixed]`

`git revert HEAD`





# Renaming Files

- **Git doesn't track metadata about renames, but infers it**
- **Git mv command renames a file**
- **Git will show “renamed” in status after a mv**
- **The mv command is equivalent to:**
  - **mv (old local file) (new local file)**
  - **git rm old file**
  - **git add new file**

# What is a branch in source control?

- Line of development
- Collection of specific versions of a group of files tagged in a common way
  - `cvs rtag -a -D <date/time> -r DERIVED_FROM -b NEW_BRANCH PATHS_TO_BRANCH`
- End result is I have an easy “handle” to get all of the files in the repository associated with that identifier – the branch name
  - `cvs co -r BRANCH_NAME PATHS`
- So – what you end up with in your working directory when you check out a branch is a set of specific versions of the files from the group, or a ...

# Snapshot! What is a snapshot (in GIT)?


68

- Line of development associated with a specific change
- Collection of specific versions of a group of files associated with a specific commit
- End result is I have a “handle” to get all of the versions of files in the repository associated with that commit – handle = SHA1 for that commit
- What you end up with in your working directory when you check out a branch is a set of specific versions of the files from the group.




# Branches

- Remember, git stores data as a series of snapshots, not deltas or changesets
- Commits point to snapshots – and the commit that came before them




# Commit SHA1's are a handle to a snapshot<sup>70</sup>



# Lightweight Branching

71

- A branch in git is simply a lightweight, movable pointer to a commit
- Default branch is named master
- As you initially make commits, you're given a branch pointer that points to the last commit you made. Every time you commit, it moves forward automatically.



- A branch in Git is just a simple file that contains the 40 character SHA-1 checksum of the commit it points to, branches are cheap to create and destroy. Creating a new branch is as quick and easy as writing 41 bytes to a file (40 characters and a newline).
- And, because we're recording the parents when we commit, finding a proper merge base for merging is automatically done for us and is generally very easy to do.

71



# Creating and using a new branch


72

- Create a branch : **git branch <branch>**
  - Creating a new branch creates a new pointer

Git keeps a special pointer called HEAD that always points to the current branch.

## git branch testing

- Change to a branch: **git checkout <branch>**
  - Moves HEAD to point to <branch>
  - Updates working directory contents with last commit from <branch> - if existing branch



## git checkout testing

- Branch pointers advance with new commits

72

# Switching between Branches

73

Command: `git checkout <branch>`  
`git checkout master`

- **Does three things**

- Moves HEAD pointer back to <branch>
- Reverts files in working directory to snapshot pointed to by <branch>
- Updates indicators


`git checkout testing`

`git checkout master`

`git checkout testing`

- **`git branch`**

- \* master
- \* testing



73

# Which Branch am I on/in?

- Command: **git branch** <no arguments>
- “\*” is indicator of which one you’re on
- Prompt will also change in some configurations
  - If it doesn’t, can be setup.



# “Topic and Feature Branches”

## ■ Topic Branches

- Term for a temporary branch to try something out
- Easy to try things in or come back to later
- Generally, create simple name based on type of work you’re going to try – i.e. `web_client`
- Maintainer of a project may “namespace” these – as in adding initials on the front – i.e. `abc/web_client`
- Create just as any other branch

```
$ git branch abc/web_client
```

```
$ git checkout -b web_client
```

## ■ Feature Branches

- Term for a branch to develop a feature
- Intended for limited lifetime
- Merge back into main line of development

## Working with Branches

Purpose: In this lab, we'll start working with branches by creating a new branch and making changes on it.

# Merging Branches

- Command: **git merge <branch>**
- Relative to current branch
- Current branch is branch being merged into
- <branch> is branch being merged from
- Ensure everything is committed first



# Merging: What is a Fast-forward?

- Assume you have three branches as below
- You want to merge hotfix into master (so master will have your hotfix for future development)

```
$ git checkout master
```


```
$ git merge hotfix
```

```
Updating f42c576..3a0874c
```

```
Fast Forward
```

```
README | 1-
```

```
1 files changed, 0 insertions(+) 1 deletions (-)
```




About “Fast Forward” – because commit pointed to by branch merged was directly “upstream” of the current commit, Git moves the pointer forward

(Both branches were in the same line of development, so the net result is that master and hotfix point to the same commit)

# Merging: What is a 3-way Merge?

- Assume branching scenario below
  - master and feature branches have both diverged (changed) since their last common ancestor (commit/snapshot)
- Intent is to change to master and merge in feature
- Current commit on target branch isn't a direct ancestor of current commit on branch you're merging in (i.e. C4 isn't on the same line of development as C5)
- Git does 3-way merge using common ancestor
- Instead of just moving branch pointer forward, Git creates a new snapshot and a new commit that points to it called a "merge commit"



\$ git checkout master  
\$ git merge feature

# Merge Conflicts

- If you encounter a merge conflict during a merge operation
  - Will get CONFLICT message
  - Git pauses merge in place
  - To see which files are unmerged, use `git status` – will see “unmerged: or both modified: <filename>”
  - Adds <<<<< and >>> markers in the file
- After resolution, run `git add` and then commit
- Can also run `git mergetool` to resolve graphically



# Merge Scenario – Branches with Conflicts

**\$ git checkout master**

**\$ git merge feature**

**\$ git status**

Changes to be committed:

modified: File 1

modified: File 3


Unmerged paths

both modified: File 2

**[fix conflicts]**

**\$ git add .**

**\$ git commit -m  
“finalize merge”**



Staging Area


File 2

Working Directory

## Practice with Merging

Purpose: In this lab, we'll work through some simple branch merging.

# Git in One Picture





# Cloning a Remote Repo to get a Local Repo<sup>84</sup>

- **Command: `git clone`**
  - Use to get a copy of an existing repository from a system
  - Syntax: `git clone <url> <optional new name>`
  - Clone vs. checkout
    - » Git pulls nearly all data from cloned area – files, history, etc.
    - » Creates a directory with the project name
    - » Checks out working copy of latest version
    - » Does a bit more than fetch and pull – tracks local branch to remote branch
  - After cloning, have full access to files, histories, etc.

# Git Remote References “remotes”

85

85

- The term “remote” can either refer to:
  - An actual remote repository
  - A reference to such a repository
- For local use, Git provides references/aliases/nicknames that map to a remote repository location
- The default one of these is “origin”
- The reference “origin” is automatically setup (mapped) for you when you clone
- Example: `origin = https://github.com/<path>`
- This mapped name is what you use in local commands to tell git you want to push/pull/fetch/clone to/from the mapped remote repository
- Example: `git pull origin <branch>`

85

# Git Remote Repositories

- Remote repositories
  - Think “server-side”
  - Versions of projects hosted on network or internet
  - Push or pull from (as opposed to checkout/add/commit)
  - Generally have read-only or read-write access
  - Handle + url
- Public as opposed to private (local)
- Multiple protocols for data transfer
  - Local – shared folder, easy for collaboration, slow, not for widespread use
  - SSH – standard with authentication, no anonymous access
  - Git – fastest, but no authentication
  - Http - easy, but inefficient
  - Https – easy and authenticated (temporarily)



# Working with Handles to Remotes

87

- Seeing what you have access to
  - Git remote (short handle by default, -v shows url)
  - “origin” – special name that git gives to remote you cloned from
  - Ssh urls (git@<blah> vs. git protocol git://) and https indicates ones you can push to
  - Git remote show (shortname) – shows extended info about remote
- Adding a remote
  - Think of adding access to existing one
  - Git remote add [shortname (handle)] [url]
    - » Example : git remote add remote2 https://github.com/userid/projectpath
- Renaming shortname
  - Git remote rename <old> <new>
  - Renames remote branches too
- Removing a reference
  - Git remote rm (shortname)

87

# Working with Remotes

- Retrieve latest from git remote (getting what you don't have)
  - Git fetch (shortname) as in `git fetch brent`
  - Note that you are getting the full repository (history, branches, basically everything)
  - Fetch pulls the data to the local repository – it doesn't merge or disturb your local content
- Retrieve latest and merge
  - Git pull
  - By default, git clone automatically sets up to track changes on master branch
  - Pull does a “fetch and merge”
- Pushing back to the server (remote)
  - Git push (shortname) (branch)
  - Only works if you have correct access and remote content hasn't been change
  - If remote content has been changed, then would have to fetch latest and merge (like cvs up-to-date check)

# Git Remotes Example


89

```
$ git clone https://github.com/userid/projectpath
$ git remote -v
origin https://github.com/userid/projectpath(fetch)
origin https://github.com/userid/projectpath (pull)

$ <edit File A and File C>
$ git commit -am "...
$ git push origin master
(default is origin and master so could just "git push")

$ git remote rm origin
$ git remote add project1 https://github.com/userid/projectpath
$ git remote -v
project1 https://github.com/userid/projectpath(fetch)
project1 https://github.com/userid/projectpath (pull)

$ <edit File B>
$ git commit -am "...
$ git push project1
(or git push project1 master)
```



89



# Working with a Remote and Multiple Users


90

User 1

```
$ git clone ...  
$ <edit File A and File C>  
$ git commit -am "..."  
$ git push  
$ git fetch
```

User 2

```
$ git clone ...  
$ <edit File B>  
$ git commit -am "..."  
$ git push  
$ git pull  
$ git push
```



90

## Using the Overall Workflow with a Remote Repository

**Purpose:** In this lab, you'll get some practice with remotes by working with a Github account, forking a repository, cloning it down to your system to work with, rebasing changes, and dealing with conflicts at push time.

# That's all - thanks!

## Professional Git 1st Edition

by Brent Laster (Author)



7 customer reviews

[Look inside](#) ↓

