



Operational flightplan

DEP		Off block		Take-off	
DEST		On block		Landing	

TROMSØ					WIND		ACC		Fuel				Altitude				Intermediate			Time			Fuel remaining		
From	TAS	TT	VAR	MT	Dir/Vel	WCA	Dist	Time	FF	Int	Acc	To	MSA	PL	MH	GS	Dist	Time	ETO	ATO	Diff	EST	ACT	Freq	
1																									
2																									
3																									
4																									
5																									
6																									
7																									
8																									
9																									
10																									
11																									
12																									
13																									
14																									
15																									
16																									
Total												Total													
Alt.																									
Total												Total													

Date		Flight time	
Lesson		Block time	
Reg:		Fuel Dep	
		Fuel Rem	
CREW		PASSENGERS	
PIC:			

Dep. ATIS	Clearances/Notes
Arr. ATIS	

MASS & BALANCE			
A/C REG:	Weight (lbs)	Arm (in)	Moment (in-lbs)
Basic Empty Mass			
Pilot - Left Seat		37,0	
Pilot or Passenger - Right Seat		37,0	
Rear Passengers		74,0	
Fuel		46,5	
Baggage Area A		97,0	
Baggage Area B		116,0	
Baggage Area C		129,0	
Total Takeoff Mass			
Enroute fuel consumed		46,5	
Last Minute Change			
Total Landing Mass			

FUEL REQUIREMENTS			
	US Gallons	Pounds (lbs)	Time (hh:mm)
Trip Fuel (incl. 1,7 for startup, taxi, takeoff)			
Alternate Fuel			
Contingency Fuel			
Extra fuel			
Final Reserve			
Total Fuel Required			
Total Fuel Onboard			
Endurance (incl. final reserve)			

SPEEDS	
V _X	65
V _Y	80
V _A 3100	110
2600	101
2100	91
V _{NO}	140
V _A	
V _{GLIDE}	

CRUISE					
ALT	OAT	RPM	MP	TAS	FF

APPROACH		
MIN FLT	MSA	MDA/DA

MAX CROSSWIND	
DEP	DEST

DEP. AERODROME					
RWY		Elevation		Flaps	20°
W/V		X-Wind		P. Alt	
QNH		Temp.		D. Alt	

DEST. AERODROME					
RWY		Elevation		Flaps	30°
W/V		X-Wind		P. Alt	
QNH		Temp.		D. Alt	

Uncorrected <i>short field</i> take-off distance			
H-Wind		Wind correction (no corr. < 9kts)	
RWY stat.		Brk action	Correction
Corrected take-off distance			
Performance factor	25 %	Req. take-off distance	
			TODA

Uncorrected <i>short field</i> landing distance			
H-Wind	0	Wind correction (according to POH)	
RWY stat.		Brk action	Correction
Corrected landing distance			
Performance factor	43 %	Req. landing distance	
			LDA

APPROACH MINIMAS		
	Ceiling	Visibility
Dest.		
Alt. 1		
Alt. 2		
T/O Alt.		



PLANNING MINIMAS		
	Ceiling	Visibility
Dest.		
Alt. 1		
Alt. 2		
T/O Alt.		

 STUDENT

 INSTRUCTOR

