MAPS_CANDIDATES BATCH2

PREREG: MAPS_CANDIDATES/BATCH2 (Map-C7 to Map-C11)

Written 2026-10-24 at about 6:35 PM CDT, before any BATCH2 test. Owner: Arvin Hampton. New files only. CORE_FREEZE. All maps are **Category B** until proved; a pass is a survived prediction, not a Residual–Resonant bridge. C1–C6 are not reused. No T3/O_res/Π q-series is constructed. Runs: nice, OMP_NUM_THREADS=1, ulimit -v 3000000. Sources: - Modular: the 35-component law vector symbols (A35_lawspace_exact/symbols.py T_rows, phases e(k/9800)); Prop. Z (Zwegers law (35^{−1/2}M, T), χ = 1, order17); hybrid shadow (order15); A_1 split, P-even $A_1 = 0$ (order17). - Residual: canonical T3 (oct17-master/README.md); L = 18+521 = 539; N_star = 14 (grok-chats/raw/chat-03.txt).

Map-C7: T-matrix order vs the 7-part of 539 (modular → residual)

Source: M_T on the 105 symbols (monomial, phases e(k/9800)). Target: $539 = 7^2 \cdot 11$. Prediction (NEW): the order of M_T as a 105×105 monomial matrix is divisible by 49, and is not divisible by 11. PASS iff both hold (exact integer arithmetic).

Map-C8: maximum free T3 depth on [1,539] vs the window (residual-internal)

Prediction (NEW): max_{1≤n≤539} (free T3 steps from n to 1) = 18. PASS iff the maximum is exactly 18 and every n reaches 1 (cap 10^5 steps).

Map-C9: short-basin count vs the body (residual-internal)

Prediction (NEW): #{n ∈ [1,539] : free T3 steps to 1 ≤ 14} = 521. PASS iff the count is exactly 521.

Map-C10: hybrid shadow → Π segments (modular → Resonant). OPEN

Source: four shadow pieces (three P-odd unary thetas plus the P-even e_2 Laplacian defect). Target: Π. Prediction: Π, written as a 539-step word, splits into exactly 4 maximal segments of constant T3 branch-type class, with lengths ordered like the theta norms (1/34 < 5/2 < 35/4). Next measurement: a written, hashed 539-step Π from residual sources. Not available, so OPEN.

Map-C11: P-even $A_1 = 0$ → ±1 balance on the fibre blocks (modular → residual). OPEN

Prediction: under a written ±1 grading of O_res elements, every one of the 8 fibre blocks has signed sum 0 for the 68-blocks, with an odd defect ±1 for the 67-blocks. Next measurement: a written ±1 grading on O_res (none located). OPEN. # RESULTS: BATCH2 PREREG.md sha256 7d88884cec365b4c184be5ebd04b0bd20308e277c47b86b789243d3570b4fb95, hashed before tests. Script scripts/b2.py (hash in scripts/SHA256SUMS); data data/b2.json; log logs/b2.log. Exact integer arithmetic, under 1 s.

Map	Prediction	Measured	Verdict	Cat
C7	49 | ord(M_T), 11 ∤ ord(M_T)	ord(M_T) = 140 = 2²·5·7	**FAIL** (7 divides it, 49 does not)	B
C8	max free T3 depth on [1,539] = 18	29 (n = 487); all n reach 1	**FAIL**	B
C9	#{depth ≤ 14} = 521	434	**FAIL**	B
C10	Π splits into 4 segments ordered by theta norms	no written Π	**OPEN**	B
C11	±1 balance on the 8 fibre blocks from P-even $A_1 = 0$	no written grading	**OPEN**	B

No bridge claim. Post-hoc only: ord(M_T) = 140 equals the discriminant of Q(√35), consistent with the T-law of a level-140 Weil-type representation; this is expected modular structure, not a residual link. # NOTES: BATCH2 - E1–E3 and RG1/RG1′ were read in order14–order17 (RG1′ is iff, by order16 Lemma). No E-series files were found inside MAPS_CANDIDATES; nothing there was reused. - C7's target (7² in 539) was a guess at a residual 7-adic match. The FAIL is clean: the T-order carries 7¹ only. - C8/C9 are residual-internal tests of free T3 depth (Option 3 free basins), with sharp numerical targets taken from the packaging. Both FAIL. They are consistent with the locked view that 539 is an engineered budget, not a free-dynamics count. - C10/C11 need written

residual objects (a 539-step Π; a ±1 grading on O_res). Do not construct them here; doing so would invent the target. - Still OPEN from batch 1: C6 (also needs a written Π). - CORE_FREEZE; new files only; no push, no sends.