order37 RESULTS: RG34 (per-point miss vs den(x))
PREREG sha256 98279e7a15f162b19d99522cf06dfd23147ac0529a5e0f64d5c1fca14925fa41 (hashed before numerics). Stored arrays only (order19 C2b); full 216-point grid.
Global: $\hat{\kappa} \approx 1.0000147 - 0.00034i$; $r_{global} = 0.0030492$ (reproduces orders 34–36).
RG34: FAIL (Category B)
Rule: $r_{pred}(x) = r(1)/den(x)^2$, with $c = r(1) = 0.1408$ and $p = 2$ fixed.

metric	value	threshold
median relative error e	0.592	PASS ≤ 0.10, FAIL ≥ 0.5
90th percentile e	0.876	PASS ≤ 0.25

c-free cancellation, median of $r \cdot d^2/r(1)$ per denominator d (≈ 1 under the hypothesis):
d = 1: 0.60 | 2: 1.05 | 3: 1.33 | 4: 1.58 | 5: 1.72 | 6: 1.90 | 7: 2.01 | 8: 2.19 | 9: 2.28 | 10: 2.41 | 11: 2.56 | 12: 2.69 | 13: 2.80 | 14: 2.84 | 15: 2.98
The ratio grows steadily with d, so the decay is slower than den^{−2}. (d = 1 is below 1 because the x = 1 point is the largest of the den = 1 points.) Prediction FAIL (blind): correct.
Diagnostics (reported only, not verdict)
- Spearman(r, den) = −0.67; Spearman(r, |num(x)|) = −0.96; Spearman(r, max(den, |num|)) = −0.94.
- Log-log slope $\hat{p} \approx 1.41$ (against den) and 1.44 (against max). Not fitted into any claim.
- The miss is ordered far more tightly by |num(x)| = den(−1/x), the side where L_B's aliasing ($N' = 2|num|$) acts, than by den(x).

Point-by-point table: data/o37.json (x, den, r, r_pred, e).
Category
B only. A: none. v11: no. Ξ: not identified. E1–E3 OPEN.

order37 NOTES
- The den^{−2} ($1/k^2$) form fails; the miss decays roughly like a power ≈ 1.4 and is organised by |num(x)| (Spearman −0.96), i.e. by the aliasing period N' at $-1/x$. This was noticed post hoc; any test of it must be preregistered fresh, with no fitted p.
- Open next step (order38, not started), the alternate route as instructed: preregister a reference space equal to the span of the Bernoulli-sum columns {C2b_l(x)} (and their $-1/x$ images), and measure the law miss as the leftover of S outside that span, with no fit, against r. Optional secondary: a written |num(x)|-ordering prediction (e.g. a monotone decrease of the per-|num| median r) with a fixed threshold.
- Naming: RG* only, no labels L1–L7. Geometric only; MAPS_CANDIDATES untouched; no Resonant objects; no new Bernoulli objects; no bridge claim; CORE_FREEZE. nice, OMP_NUM_THREADS=1; ~2 s; no push or sends; new files only.