order38 RESULTS: RG35 / RG35b
PREREG sha256 3fa7c2db7e301a528885b4f24f49d20bdd994c82dd1a1a0236a94f8e659b4fca (hashed before numerics). Stored order19 C2b arrays only; full 216-point grid.
r_meas = 0.0030492 (κ̂ 1.0000147 − 0.00034i).
Vacuity control (preregistered)
Span including the −1/x images: rank 104; leftover of S = 2.1e−10. Vacuous by construction, as stated; not a test.
RG35 primary: FAIL (Category B)
quantity	value
rank W_B = colspan{x·C2b_l(x)}	54 (of 105 columns)
r_B = ‖(I−P_{W_B})S‖/‖S‖, no fit	0.0020579
r_B / r_meas	0.675 (PASS ≥ 1−1e−6; FAIL ≤ 0.9)
Spearman(per-point leftover, per-point r)	0.94
Prediction FAIL (blind): correct.
Reading: even the best arbitrary 105×105 matrix law S ≈ x·C2b(x)·T leaves 0.00206. About two thirds of the near-law miss (by norm) is intrinsic: S(x) lies partly outside the span of the 54 independent Bernoulli functions x·C2b_l(x). The remaining third is specific to the choice T = M̂. Leftover and miss are strongly co-located point by point (ρ = 0.94).
RG35b secondary: |num(x)| ordering: PASS (not blind; disclosed)
31 groups with ≥ 3 points (|num| = 1..37). Spearman(|num|, group median r) = −0.996 (PASS ≤ −0.9). Group medians fall monotonically from 0.032 (|num| = 1) to 0.0013 (|num| = 37), with two tiny inversions (20 vs 19, 23 vs 22).
This confirms the order37 post-hoc observation as a hashed test, but the hypothesis was formed from the same data, so it is a consistency result.
Category
B only. A: none. v11: no. Ξ: not identified. E1–E3 OPEN.

order38 NOTES
- New structural numbers: the 105 Bernoulli columns x·C2b_l(x) span only 54 dimensions on the grid. A floor of r ≈ 0.0021 is intrinsic to any fixed-matrix law for C2b; M is not optimal (ratio 0.675).
- The miss is governed by |num(x)| = den(−1/x), i.e. by the L_B aliasing period N′ = 2|num| on the S side (hashed consistency PASS).
- Open next step (order39, not started): preregister RG36, a blind out-of-sample |num| test. Evaluate C2b on NEW x points with large |num| (not in XS, e.g. num 41–60 with small den), using the order19 C2b evaluation method (no new objects). Predict, before computing, that the per-point r is below the |num| = 37 group median 0.0013, and that the ordering continues. Also optional: identify the 54-dim span through the order20 L_B structure (characteristics β+λ_k), as a Category A candidate.
- Naming: RG* only, no labels L1–L7; "36" only as dim V. MAPS_CANDIDATES and REVIEW_2026-10-24 untouched; no Resonant objects; no new Bernoulli objects; no bridge claim; CORE_FREEZE. nice, OMP_NUM_THREADS=1; ~2 s; no push or sends; new files only.