PI_MAX_PURSUE — PREREG (written before tests)
Rule accepted (Arvin, 2026-10-24, "Max... Pursue"): Π := Π*_max = (01)^269 0 (DISCOVER_PI_RULE RP4), plus g=(−1)^τ, P_res (u≡3 mod 9). CORE_FREEZE. C10 FAIL (closed), C11 FAIL (closed); not re-run.

Tests (predefined, Category A, exact)
- PM1 (identity): sha256(bytes(Π)) built as [0,1]*269+[0] equals c2c26fdae7b1e1f677799f9a6a210c429ea9c1f4b23f48ae1bbc66aab54f8d87 (DISCOVER_PI_RULE/data/tests.json). PASS iff equal.
- PM2 (word facts): len=539, #1s (hits)=269, #0s=270, minimal period 2, digram counts 01=269, 10=269, 00=11=0. Recorded as data, not as a bridge.
- C6 gate (decision rule): C6 runs only if the written sources (MAPS_CANDIDATES/PREREG Map-C6; A35 REPORT; BRIDGE_C_35 REPORT entry 94; PATTERN_S_MARKOV) give a map letter∈{0,1} → power of M_S. If no such clause is written, C6 = OPEN. Note: "539 mod 4 = 3" alone is word-independent, so it cannot test Π (vacuous) and does not count.
- RP-PI1 gate (new map): a Residual↔Resonant prediction counts as forced only if a written identity ties 269, 270, period 2, or digram mass "01" to a written modular object with no free assignment. Candidates checked: (a) period 2 ↔ ord(M_S²)=2 (S²=P); (b) period 2 ↔ the period-2 closed class (0,1)↔(1,0) of the |S|² chain (PATTERN_S_MARKOV); (c) 269/270 ↔ written integers 539=18+521, 105, 35, 7²·11, 140, 72; (d) "01" mass 269/538 ↔ shadow/theta statistic. Any candidate needing a letter→state assignment or an unwritten identity is dropped (OPEN), not tested.
Bridge claim: only on a non-vacuous PASS of a forced map.
PI_MAX_PURSUE — RESULTS
PREREG sha256 142fc6a0169e4d17826784af31d3ad3da44a0f112b57e6be3fdcc26e5d74a4d1 (hashed before the run). Script hash: scripts/SHA256SUMS. Data: data/pursue.json.

Test	Result	Cat
PM1 sha256 of Π*_max = c2c26fda…	**PASS** (match with DISCOVER_PI_RULE)	A
PM2 word facts	len 539, hits 269, zeros 270, period 2, digrams 01=10=269, 00=11=0	A (data)
C6	**OPEN**: no written letter→M_S-power map; "539≡3 mod 4" is word-independent (vacuous)	—
RP-PI1(a) period 2 ↔ ord(M_S²)=2	dropped: equality of the integer 2 only; no written map from the word to S²	not forced
RP-PI1(b) period 2 ↔ |S|² chain period-2 class	dropped: needs a free choice of letter 0 → coset (0,1) or (1,0)	not forced
RP-PI1(c) 269/270 ↔ written integers	269 prime, coprime to 18,521,105,35,140,72,539. 270=18·15, but no written identity; the 3^270 HQH claim is retracted (conflict-brief item 7)	not forced
RP-PI1(d) "01" mass ↔ shadow/theta statistic	no written statistic with value 269 or 269/538	not forced
C10, C11	FAIL (closed earlier; not re-run)	—

Bridge: **NO** (no forced map, so nothing non-vacuous to pass).
NOTES
- Acceptance recorded: Π := Π*_max = (01)^269 0, sha256 c2c26fdae7b1e1f677799f9a6a210c429ea9c1f4b23f48ae1bbc66aab54f8d87, rule RP4 (P_res hit count including w_539). Accepted 2026-10-24 by Arvin ("Max... Pursue"). Also accepted: g=(−1)^τ; P_res (u≡3 mod 9). Verified by PM1.
- C6 missing clause: the sources (A35 REPORT: S⁴=1, (ST)³=S²; BRIDGE_C_35 REPORT entry 94; Cross-Review C5: S²=P, S_lab=ρ(S)⁻¹) define M_S but never a reading of a 0/1 word as M_S powers. Needed clause: "letter b ↦ M_S^{f(b)}" with f written (and a convention S vs S_lab=S⁻¹). Every choice of f is an invention, so C6 stays OPEN.
- Remaining free choices beyond RP4: (1) letter→group-element map f; (2) S vs S⁻¹ convention for the product; (3) letter→coset assignment for the |S|² chain; (4) any identity linking 269/270 to a modular integer.
- Lock: CORE_FREEZE; no L1–L7; no α1/Ξ/new fibres; T3/E1–E3 not built (no

written recipe) and stay OPEN; DISCOVER_PI_RULE/ and Bridge C order*/papers untouched; no push/send.