order39 RESULTS: RG36 (blind |num| ordering on new points)
PREREG sha256 e25a92538820ff61f0b507cf432a0ee5d55f4dd1fb49c6490a5e1727b036773d (hashed before numerics).
Method: order19 comps() verbatim. κ̃fixed (1.0000147 − 0.00034i) and M fixed; no refit. 12 new points, none in XS.
RG36: FAIL (Category B)
x	r	x	r	x	r
41	0.01180	41/2	0.00551	41/3	0.00437
43	0.01147	43/2	0.00534	43/3	0.00426
47	0.01096	47/2	0.00503	47/3	0.00400
53	0.01026			53/3	0.00372
59	0.00965				
- Below the reference 0.0013404: 0/12. Median of the new points: 0.00543, about 4× the reference.
- Pooled Spearman: −0.55 (PASS required ≤ −0.9).
- FAIL by both FAIL conditions. The prediction PASS (blind) was **wrong**.
Reading
- The |num| ordering seen in orders 37–38 does not extrapolate. In the 216-point grid, large |num| goes together with moderate den. With den ∈ {1, 2, 3} fixed small, large |num| does not drive r down to the 1e−3 level.
- Within each fixed den, r still decreases with |num| (den 1: 0.0118 → 0.0096; den 3: 0.0044 → 0.0037), and for fixed |num| r decreases with den (e.g. 41: 0.0118 / 0.0055 / 0.0044).
- The miss depends on both num and den; neither alone orders it. The order38 RG35b PASS was confounded by the composition of the XS grid, which is exactly why it was labelled a consistency result.
Optional 54-dim span subtest
Not run (preregistered as deferred; it would be circular).
Category
B only. A: none. v11: no. Ξ: not identified. E1–E3 OPEN.

order39 NOTES
- Lesson: grid-composition confounding. Orderings found on XS must be tested off-grid along fixed-den and fixed-num lines.
- Pattern from the new points (post hoc, to be hashed before any verdict use): r decreases with both |num| and den. At fixed den = 1, r ≈ 0.0118 → 0.0096 for num 41 → 59, a slow decay.
- Open next step (order40, not started): preregister RG37, a two-variable blind test on a fixed new design (e.g. num ∈ {61, 67, 71} × den ∈ {1, 2, 4, 5}). Write a monotonicity prediction in BOTH variables (r strictly decreasing along each line) with a fixed rule and no fitted exponent. Or step back to an exact source: derive the per-point miss from L_B at x = n integer, where N′ = 2n and the structure is simplest, as a Category A candidate.
- Naming: RG* only, no labels L1–L7; "36" only as dim V. MAPS_CANDIDATES and REVIEW_2026-10-24 untouched; no Resonant objects; no new Bernoulli objects; no bridge claim; CORE_FREEZE. nice, OMP_NUM_THREADS=1, 3 GB, ~5 s; no push or sends; new files only.