Name: Arvind Patil
Roll No. 2401079
Class: T21

EXPERIMENT NO.: 05

AIM:

To set up a Continuous Integration (CI) Pipeline using Jenkins and GitHub Actions for automatically building and testing an application.

THEORY:

Continuous Integration (CI) is a software development practice in which developers frequently integrate their code changes into a shared repository. Whenever new code is pushed to the repository, an automated CI pipeline can perform tasks such as building the application, running tests, and checking whether the code works correctly.

· Continuous Integration helps developers detect errors early.

· Developers push their source code to a version control system such as GitHub.

· A CI tool automatically detects changes made to the source code repository.

· The application is automatically built and tested.

· If all tests are successful, the pipeline is marked as successful.

· If a build or test fails, the pipeline reports a failure.

· Jenkins and GitHub Actions are commonly used tools for implementing Continuous Integration.

Jenkins is an automation server that allows developers to create pipelines for building, testing, and deploying applications.

GitHub Actions is a CI/CD automation platform integrated directly with GitHub repositories. Workflows can automatically run when events such as a code push or pull request occur.

A typical Continuous Integration process is represented as:

Developer
↓

Name: Arvind Patil
Roll No. 2401079
Class: T21

Push Code to GitHub
↓
CI Pipeline Triggered
↓
Install Dependencies
↓
Build Application
↓
Run Tests
↓
Success / Failure Report

Network / Software Setup

Components Required

· Computer/Laptop

· Jenkins

· Git

· GitHub Account

· Node.js Application (Test Application)

· Internet Connection

· GitHub Repository

Sample Application Structure

test-application/
│
├── package.json
├── index.js

Name: Arvind Patil
Roll No. 2401079
Class: T21

```
├── test/
│   └── app.test.js
│
├── Jenkinsfile
│
└── .github/
    └── workflows/
        └── ci.yml
```

Sample Application

index.js

```
function add(a, b) {
  return a + b;
}

module.exports = { add };
```

package.json

```
{
  "name": "jenkins-ci-demo",
  "version": "1.0.0",
  "scripts": {
    "test": "node test/app.test.js"
  }
}
```

Name: Arvind Patil
Roll No. 2401079
Class: T21

test/app.test.js

```
const { add } = require("../index");

if (add(2, 3) !== 5) {
   console.error("Test Failed!");
   process.exit(1);
}

console.log("Test Passed Successfully!");
```

Jenkins Pipeline Setup

Jenkinsfile

Create a file named Jenkinsfile in the root directory of the project.

```
pipeline {
   agent any

   stages {

      stage('Checkout') {
         steps {
            checkout scm
         }
      }

      stage('Install Dependencies') {
         steps {
            sh 'npm install'
         }
      }

      stage('Run Tests') {
         steps {
            sh 'npm test'
```

Name: Arvind Patil
Roll No. 2401079
Class: T21

```
            }
        }

        stage('Build Status') {
            steps {
                echo 'Continuous Integration Pipeline Completed Successfully!'
            }
        }
    }
}
```

The Jenkins pipeline performs the following operations:

Checkout Source Code
↓
Install Dependencies
↓
Run Tests
↓
Generate Build Status

GitHub Actions Setup

Create the following directory structure:

.github/workflows/

Inside the workflows folder, create a file named:

ci.yml

GitHub Actions Workflow

name: Continuous Integration

Name: Arvind Patil
Roll No. 2401079
Class: T21

```
on:
  push:
    branches:
      - main

  pull_request:
    branches:
      - main

jobs:
  build-and-test:

    runs-on: ubuntu-latest

    steps:

      - name: Checkout Repository
        uses: actions/checkout@v4

      - name: Setup Node.js
        uses: actions/setup-node@v4

      - name: Install Dependencies
        run: npm install

      - name: Run Tests
        run: npm test
```

The GitHub Actions workflow is automatically triggered when:

· Code is pushed to the main branch.

· A pull request is created for the main branch.

Procedure

1. Open the computer and ensure that Git, Jenkins, and Node.js are installed.

Name: Arvind Patil
Roll No. 2401079
Class: T21

2. Create a simple test application.

3. Create the required project files such as index.js, package.json, and the test file.

4. Test the application locally using:

npm test

5. Create a GitHub repository for the application.

6. Initialize the local project as a Git repository.

git init

7. Add the project files to Git.

git add .

8. Commit the source code.

git commit -m "Initial CI application"

9. Connect the local repository to GitHub.

10. Push the project to the GitHub repository.

Jenkins Configuration Procedure

11. Start the Jenkins server.

12. Open Jenkins in a web browser.

http://localhost:8080

13. Click on **New Item**.

Name: Arvind Patil
Roll No. 2401079
Class: T21

14. Enter a name for the project.

Example:

CI-Pipeline-Demo

15. Select **Pipeline** as the project type.

16. Click **OK**.

17. In the Pipeline configuration, select:

Pipeline script from SCM

18. Select:

Git

as the Source Code Management system.

19. Enter the GitHub repository URL.

20. Select the required branch, such as:

*/main

21. Enter the script path:

Jenkinsfile

22. Save the pipeline configuration.

23. Click **Build Now** to execute the Jenkins pipeline.

24. Observe the different stages of the Jenkins pipeline.

Name: Arvind Patil
Roll No. 2401079
Class: T21

GitHub Actions Procedure

25. Create a .github/workflows directory in the project repository.

26. Create the GitHub Actions workflow file named:

ci.yml

27. Add the Continuous Integration workflow configuration.

28. Commit and push the workflow file to GitHub.

```
git add .
git commit -m "Add CI workflow"
git push origin main
```

29. Open the GitHub repository.

30. Navigate to the **Actions** tab.

31. Observe the automatically triggered workflow.

32. Verify the following CI stages:

Checkout Repository
↓
Setup Node.js
↓
Install Dependencies
↓
Run Tests


CI Pipeline Observation

Step	CI Stage	Operation	Observation
1	Source Code	Code pushed to GitHub	Repository receives updated source code

Name: Arvind Patil
Roll No. 2401079
Class: T21

2	Pipeline Trigger	Jenkins/GitHub Actions starts	CI process begins automatically or manually
3	Checkout	Source code is downloaded	Latest version of application is obtained
4	Dependencies	Required packages are installed	Application environment is prepared
5	Testing	Automated tests are executed	Application functionality is verified
6	Result	Pipeline status generated	Build is marked as Success or Failure

Continuous Integration Workflow



Name: Arvind Patil
Roll No. 2401079
Class: T21

Expected Result

· The application source code is successfully stored in the GitHub repository.

· Jenkins successfully checks out the source code.

· The CI pipeline installs the required dependencies.


· Automated tests are executed successfully.

· Jenkins displays the status of the pipeline.


· GitHub Actions automatically runs the CI workflow after a push or pull request.

· The workflow status is displayed as either successful or failed.

Screenshot:





Name: Arvind Patil
Roll No. 2401079
Class: T21






Name: Arvind Patil
Roll No. 2401079
Class: T21





Name: Arvind Patil
Roll No. 2401079
Class: T21



Result:

The Continuous Integration Pipeline was successfully set up using Jenkins and GitHub Actions. The application source code was automatically checked out, dependencies were installed, and automated tests were executed. The pipeline successfully reported the build status.

CONCLUSION:

Thus, a Continuous Integration Pipeline was successfully implemented using Jenkins and GitHub Actions. The experiment demonstrated how source code changes can be automatically integrated, built, and tested using a CI pipeline. This process helps identify errors early and improves the reliability and quality of software development.