



```
create mode 100644 button.html
 create mode 100644 ch1.html
 create mode 100644 day1.css
 create mode 100644 day1.html
 create mode 100644 grid.html
 create mode 100644 taxi.css
create mode 100644 taxi.html
 create mode 100644 text.html
create mode 100644 website.html
PS C:\Users\arvin\OneDrive\Desktop\html-css-course\intro-to-html> git remote add origin https://github.com/Arvindan-S/Html-inro.git
PS C:\Users\arvin\OneDrive\Desktop\html-css-course\intro-to-html> git remote add origin https://github.com/your-username/my-website.git
error: remote origin already exists.
PS C:\Users\arvin\OneDrive\Desktop\html-css-course\intro-to-html> git remote add origin https://github.com/Arvindan-S/Html-inro.git
error: remote origin already exists.
PS C:\Users\arvin\OneDrive\Desktop\html-css-course\intro-to-html> \ \mbox{git} \ \ \mbox{branch} \ \ \mbox{-}\mbox{M} \ \mbox{main}
>> git push -u origin main
fatal: User cancelled dialog.
Enumerating objects: 12, done.
Counting objects: 100% (12/12), done.
Delta compression using up to 12 threads
Compressing objects: 100% (12/12), done.
Writing objects: 100% (12/12), 3.10 KiB \mid 396.00 KiB/s, done.
Total 12 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/Arvindan-S/Html-inro.git
 * [new branch]
                     main -> main
branch 'main' set up to track 'origin/main'.
PS C:\Users\arvin\OneDrive\Desktop\html-css-course\intro-to-html> m
```

TERMINAL

