Tutorial Problem Set #2

- Sample executables can be found in the course git repository directory (run `git pull`).
- Completing the problem set will reduce the weight of the final exam by 0.5%. To complete a problem set, you must pass at least 50% of the secret tests.
- You may assume all input is valid. Tutorial problems NEVER require checking for invalid inputs.
- You may only import the following libraries: `iostream`, `string`, and `sstream`.

Question

In the Pokémon games, trainers carry a party of up to six Pokémon with them. In this question, you will write methods for a struct `Party` that maintains such a party.

The `Party` will have the following fields:

```
struct Party {
    string pokemon[6];
    int size = 0;
};
```

You will implement:

1. `operator«`, which prints the size and contents of the party to an `ostream`.
2. `operator»`, which reads a single word (the name of a Pokémon) from an `istream` and adds it to the end of the party.
3. `operator-`, which, given a party and an index `i`, returns a new party with the Pokémon at index `i` removed and subsequent Pokémon shifted down.

Starter files are provided: you are given a sample executable, starter code, and a sample input/output. You are given a "test harness" by which you can test the methods you implement. The test harness supports the following commands:

- `q`: Quits the program.
- `c Pikachu`: Catches a Pokémon, adding the string "Pikachu" to the end of the party. `Pikachu` can be replaced with any word.
- `p`: Prints the party.
- `r 3`: Removes the Pokémon at index 3 from the party and shifts the others down. `3` can be replaced with any valid index into the `pokemon` array (that is, $0 \leq i <$ `size`).

Submission

Submit your solution in a file called `main.cc`. Save your file in the folder `tutorial2` in the MarkUs repo and push the changes.