

ACM-ICPC TEAM REFERENCE DOCUMENT

Universidad Privada de Santa Cruz de la Sierra - UPSA

Contents

1	Data Structures	1
1.1	Fenwick Tree	1
1.2	Longest Common Ancestor	1
1.3	Ranged Fenwick Tree	2
1.4	Segment Tree	3
2	General	5
2.1	Inversion Counting	5
2.2	Longest Increasing Subsequence	5
3	Geometry	6
3.1	Geometry	6
4	Graphs	11
4.1	Articulation Points	11
4.2	Bridges	12
4.3	Disjoint Sets	13
4.4	Erdos Gallai	13
4.5	Heavy Light Decomposition	13
4.6	Max Cardinality Bipartite Matching Iterative	14
4.7	Max Cardinality Bipartite Matching Recursive	15
4.8	Max Flow With Min Cost	15
4.9	Max Flow	16
4.10	Strongly Connected Components	16
4.11	Tree Center	17
5	Java	17
5.1	Fast Input Output Template	17

6	Math	19
6.1	Big Integer	19
6.2	Chinese Remainder Theorem	20
6.3	Combinations	20
6.4	Deterministic Miller Rabin	20
6.5	Extended Gcd	21
6.6	Factorial Prime Factors	21
6.7	Least Significant Bit Position	21
7	Strings	22
7.1	Knuth Morris Pratt	22
7.2	Minimum String Rotation	22
7.3	Trie	22
7.4	Z Function	23

1 Data Structures

1.1 Fenwick Tree

```
// Most of the implementation comes from e-maxx.ru, although several
// things can also be found on the TopCoder tutorial about BITs
// community.topcoder.com/tc?module=Static&dl=tutorials&d2=binaryIndexedTrees
// e-maxx.ru/algo/fenwick_tree
template <typename T>
class FenwickTree {
public:
    FenwickTree() {}

    FenwickTree(unsigned int n) { Init(n); }

    T Query(int x) const {
        T result = 0;
        for (int i = x; i >= 0; i = (i & (i + 1)) - 1) result += data[i];
        return result;
    }

    T QueryInterval(int x, int y) const { return Query(y) - Query(x - 1); }

    T QuerySingle(int x) const {
        T result = data[x];
        if (x > 0) {
            int y = (x & (x + 1)) - 1;
            x -= 1;
            while (x != y) {
                result -= data[x];
                x = (x & (x + 1)) - 1;
            }
        }
        return result;
    }

    void Update(int x, T delta) {
        for (int i = x; i < (int)data.size(); i = (i | (i + 1))) data[i] += delta;
    }

    unsigned int size() const { return data.size(); }

    void Init(unsigned int n) { data.assign(n, 0); }

    vector<T> data;
};

// Extension of the Fenwick Tree to 2D
template <typename T>
class FenwickTree2D {
public:
    FenwickTree2D() {}
```

```
FenwickTree2D(unsigned int m, unsigned int n) { Init(m, n); }

T Query(int x, int y) const {
    T result = 0;
    for (int i = x; i >= 0; i = (i & (i + 1)) - 1) result += data[i].Query(y);
    return result;
}

void Update(int x, int y, T delta) {
    for (int i = x; i < (int)data.size(); i = (i | (i + 1)))
        data[i].Update(y, delta);
}

void Init(unsigned int m, unsigned int n) {
    if (data.size() == m) {
        for (int i = 0; i < (int)m; i++) data[i].Init(n);
    } else {
        data.assign(m, FenwickTree<T>(n));
    }
}

vector<FenwickTree<T> > data;
};

/*
** BIT Linear Construction Snippet
**

class Fenwick{
    int *m, N;
public:
    Fenwick(int a[], int n);
};

Fenwick::Fenwick(int a[], int n){
    N = n;
    m = new int[N];
    memset(m, 0, sizeof(int)*N);
    for(int i=0;i<N;++i){
        m[i] += a[i];
        if((i|(i+1))<N) m[i|(i+1)] += m[i];
    }
}

*/
```

1.2 Longest Common Ancestor

```
#define MAX_N 100000
#define LOG2_MAXN 16
```

```
// NOTA : memset(parent,-1,sizeof(parent));
int N, parent[MAX_N], L[MAX_N];
int P[MAX_N][LOG2_MAXN + 1];

int get_level(int u) {
    if (L[u] != -1)
        return L[u];
    else if (parent[u] == -1)
        return 0;
    return 1 + get_level(parent[u]);
}

void init() {
    memset(L, -1, sizeof(L));
    for (int i = 0; i < N; ++i) L[i] = get_level(i);

    memset(P, -1, sizeof(P));

    for (int i = 0; i < N; ++i) P[i][0] = parent[i];

    for (int j = 1; (1 << j) < N; ++j)
        for (int i = 0; i < N; ++i)
            if (P[i][j - 1] != -1) P[i][j] = P[P[i][j - 1]][j - 1];
}

int LCA(int p, int q) {
    if (L[p] < L[q]) swap(p, q);

    int log = 1;
    while ((1 << log) <= L[p]) ++log;
    --log;

    for (int i = log; i >= 0; --i)
        if (L[p] - (1 << i) >= L[q]) p = P[p][i];

    if (p == q) return p;

    for (int i = log; i >= 0; --i) {
        if (P[p][i] != -1 && P[p][i] != P[q][i]) {
            p = P[p][i];
            q = P[q][i];
        }
    }

    return parent[p];
}
```

1.3 Ranged Fenwick Tree

```
#include <iostream>
#include <algorithm>
#include <vector>
#include <cstring>
using namespace std;

// Implementation based on the code provided at Petr's blog. Nevertheless,
// an easy and helpful explanation can be found in TopCoder's forums
// http://petr-mitrichev.blogspot.com/2013/05/fenwick-tree-range-updates.html
// http://apps.topcoder.com/forums/?module=RevisionHistory&messageID=1407869
template <typename T>
class RangedFenwickTree {
public:
    RangedFenwickTree() {}

    RangedFenwickTree(unsigned int n) { Init(n); }

    T Query(int at) const {
        T mul = 0, add = 0;
        int start = at;
        while (at >= 0) {
            mul += dataMul[at];
            add += dataAdd[at];
            at = (at & (at + 1)) - 1;
        }
        return mul * start + add;
    }

    T QueryInterval(int x, int y) const { return Query(y) - Query(x - 1); }

    void Update(int x, int y, T delta) {
        InternalUpdate(x, delta, -delta * (x - 1));
        if (y + 1 < (int)this->size()) InternalUpdate(y + 1, -delta, delta * y);
    }

    unsigned int size() const { return dataMul.size(); }

    void Init(unsigned int n) {
        dataMul.assign(n, 0);
        dataAdd.assign(n, 0);
    }

    vector<T> dataMul, dataAdd;

private:
    void InternalUpdate(int x, T mul, T add) {
        for (int i = x; i < (int)this->size(); i = (i | (i + 1))) {
            dataMul[i] += mul;
            dataAdd[i] += add;
        }
    }
};
```

```
// Extension of the Ranged Fenwick Tree to 2D
template <typename T>
class RangedFenwickTree2D {
public:
    RangedFenwickTree2D() {}

    RangedFenwickTree2D(unsigned int m, unsigned int n) { Init(m, n); }

    T Query(int x, int y) const {
        T mul = 0, add = 0;
        for (int i = x; i >= 0; i = (i & (i + 1)) - 1) {
            mul += dataMul[i].Query(y);
            add += dataAdd[i].Query(y);
        }
        return mul * x + add;
    }

    T QuerySubmatrix(int x1, int y1, int x2, int y2) const {
        T result = Query(x2, y2);
        if (x1 > 0) result -= Query(x1 - 1, y2);
        if (y1 > 0) result -= Query(x2, y1 - 1);
        if (x1 > 0 && y1 > 0) result += Query(x1 - 1, y1 - 1);
        return result;
    }

    void Update(int x1, int y1, int x2, int y2, T delta) {
        for (int i = x1; i < (int)dataMul.size(); i |= i + 1) {
            dataMul[i].Update(y1, y2, delta);
            dataAdd[i].Update(y1, y2, -delta * (x1 - 1));
        }
        for (int i = x2 + 1; i < (int)dataMul.size(); i |= i + 1) {
            dataMul[i].Update(y1, y2, -delta);
            dataAdd[i].Update(y1, y2, delta * x2);
        }
    }

    void Init(unsigned int m, unsigned int n) {
        // dataMul efficient initialization
        if (dataMul.size() == m) {
            for (int i = 0; i < (int)m; i++) dataMul[i].Init(n);
        } else {
            dataMul.assign(m, RangedFenwickTree<T>(n));
        }
        // dataAdd efficient initialization
        if (dataAdd.size() == m) {
            for (int i = 0; i < (int)m; i++) dataAdd[i].Init(n);
        } else {
            dataAdd.assign(m, RangedFenwickTree<T>(n));
        }
    }

    vector<RangedFenwickTree<T> > dataMul, dataAdd;
};
```

```
int main() {
    // EXAMPLE USAGE
    // Solution for http://www.spoj.com/problems/USUBQSUB/

    ios_base::sync_with_stdio(0);
    cin.tie(0);

    int n, m;
    cin >> n >> m;
    RangedFenwickTree2D<long long> f(n + 1, n + 1);
    while (m--) {
        int kind, x1, y1, x2, y2;
        cin >> kind >> x1 >> y1 >> x2 >> y2;
        if (kind == 1) {
            cout << f.QuerySubmatrix(x1, y1, x2, y2) << '\n';
        } else {
            int value;
            cin >> value;
            f.Update(x1, y1, x2, y2, value);
        }
    }

    return 0;
}
```

1.4 Segment Tree

```
#include <bits/stdc++.h>
using namespace std;

/*
** Generic segment tree with lazy propagation (requires C++11)
** Sample node implementation that supports
** Query: sum of the elements in range [a, b)
** Update: add a given value X to every element in range [a, b)
*/

struct StNode {
    using NodeType = StNode;
    using i64 = long long;
    i64 val; // Sum of the interval
    i64 lazy; // Sumation pending to apply to children

    // Used, while creating the tree, to update the Node content according to
    // the value given by the ValueProvider
    void set(const NodeType& from) {
        val = from.val;
        lazy = identity().lazy;
    }
};
```

```

    }

    // Updates the Node content to store the result of the 'merge' operation
    // applied on the children.
    // The tree will always call push_lazy() on the Node *before* calling merge()
    void merge(const NodeType& le, const NodeType& ri) {
        val = le.val + ri.val;
        lazy = identity().lazy;
    }

    // Used to update the Node content in a tree update command
    void update(const NodeType& from) {
        auto new_value = from.val;
        val += (e - s) * new_value;
        lazy += new_value;
    }

    // Pushes any pending lazy updates to children
    void push_lazy(NodeType& le, NodeType& ri) {
        if (lazy == identity().lazy) {
            return;
        }

        le.lazy += lazy;
        le.val += (le.e - le.s) * lazy;

        ri.lazy += lazy;
        ri.val += (ri.e - ri.s) * lazy;

        lazy = identity().lazy;
    }

    // This function should return a NodeType instance such that calling
    // Y.merge(X, identity()) or Y.merge(identity(), X) for any Node X with no
    // pending updates should make Y match X exactly.
    static NodeType identity() {
        static auto tmp = (NodeType){0, 0};
        return tmp;
    }

    // Internal tree data
    int son[2]; // Children of this node
    int s, e; // Interval [s, e), covered by this node
};

template <class Node>
struct SegmentTree {
    using ValueProvider = function<Node(int)>;
    vector<Node> T;

    SegmentTree(int n, const ValueProvider& vp = [] (int pos) {
        return Node::identity();
    }) {

```

```

        Node nd;
        nd.son[0] = nd.son[1] = -1;
        nd.s = 0, nd.e = n;

        T.reserve(4 * n);
        T.emplace_back(std::move(nd));

        init(vp, 0);
    }

    void init(const ValueProvider& vp, int u) {
        Node& n = T[u];

        if (n.e - n.s == 1) {
            n.set(vp(n.s));
            return;
        }

        Node le(n), ri(n);

        le.e = (n.s + n.e) / 2;
        n.son[0] = T.size();
        T.emplace_back(std::move(le));
        init(vp, n.son[0]);

        ri.s = le.e;
        n.son[1] = T.size();
        T.emplace_back(std::move(ri));
        init(vp, n.son[1]);

        n.merge(T[n.son[0]], T[n.son[1]]);
    }

    void update(int le, int ri, const Node& val, int u = 0) {
        Node& n = T[u];
        if (le >= n.e || n.s >= ri) return;

        if (n.s == le && n.e == ri) {
            n.update(val);
            return;
        }

        n.push_lazy(T[n.son[0]], T[n.son[1]]);

        update(le, min(T[n.son[0]].e, ri), val, n.son[0]);
        update(max(T[n.son[1]].s, le), ri, val, n.son[1]);
        n.merge(T[n.son[0]], T[n.son[1]]);
    }

    Node query(int le, int ri, int u = 0) {
        Node& n = T[u];
        if (n.e <= le || n.s >= ri) return Node::identity();
        if (n.s == le && n.e == ri) return n;
    }

```

```

n.push_lazy(T[n.son[0]], T[n.son[1]]);

Node r1, r2, r3;
r1 = query(le, min(T[n.son[0]].e, ri), n.son[0]);
r2 = query(max(T[n.son[1]].s, le), ri, n.son[1]);
r3.merge(r1, r2);
return r3;
}
};

/*
** USAGE SAMPLE
** http://www.spoj.com/problems/HORRIBLE/
*/
int main() {
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);

    int tc;
    cin >> tc;

    for (int cas = 1; cas <= tc; ++cas) {
        int n, c;
        cin >> n >> c;

        SegmentTree<StNode> st(n);

        for (int i = 0; i < c; ++i) {
            int k, p, q;
            cin >> k >> p >> q;
            p -= 1;

            if (k == 0) {
                int v;
                cin >> v;
                st.update(p, q, (StNode){v});
            } else {
                auto sum = st.query(p, q).val;
                cout << sum << '\n';
            }
        }

        return 0;
    }
}

```

2 General

2.1 Inversion Counting

```

int v[MAX], sortedV[MAX];

// Merge sort with inversion counting
long long mergeSort(int *V, int lo, int hi) {
    if (lo >= hi) {
        return 0;
    } else {
        int m1 = (lo + hi) / 2, m2 = m1 + 1;
        long long r = 0, rA, rB;
        int i = lo, j = m2, k = 0;

        rA = mergeSort(V, lo, m1);
        rB = mergeSort(V, m2, hi);

        while (i <= m1 && j <= hi) {
            if (V[j] < V[i]) {
                r += (m1 - i + 1);
                sortedV[k++] = V[j++];
            } else {
                sortedV[k++] = V[i++];
            }
        }

        if (i > m1) {
            i = j;
            j = hi;
        } else {
            j = m1;
        }

        while (i <= j) {
            sortedV[k++] = V[i++];
        }

        memcpy(V + lo, sortedV, (hi - lo + 1) * sizeof(int));

        return r + rA + rB;
    }
}

```

2.2 Longest Increasing Subsequence

```

#include <vector>
/* Finds longest strictly increasing subsequence. O(n log k) algorithm. */
void find_lis(vector<int> &a, vector<int> &b) {
    vector<int> p(a.size());
    int u, v;

    if (a.empty()) return;

    b.push_back(0);
    for (size_t i = 1; i < a.size(); i++) {
        // If next element a[i] is greater than last element of current longest
        // subsequence a[b.back()], just push it at back of "b" and continue
        if (a[b.back()] < a[i]) {
            p[i] = b.back();
            b.push_back(i);
            continue;
        }
        // Binary search to find the smallest element referenced by b which is just
        // bigger than a[i]
        // Note : Binary search is performed on b (and not a). Size of b is always
        // <= k and hence contributes O(log k) to complexity.
        for (u = 0, v = b.size() - 1; u < v;) {
            int c = (u + v) / 2;
            if (a[b[c]] < a[i])
                u = c + 1;
            else
                v = c;
        }
        // Update b if new value is smaller then previously referenced value
        if (a[i] < a[b[u]]) {
            if (u > 0) p[i] = b[u - 1];
            b[u] = i;
        }
    }
    for (u = b.size(), v = b.back(); u--; v = p[v]) b[u] = v;
}

```

3 Geometry

3.1 Geometry

```

#define EPS 1e-8
#define PI acos(-1)
#define Vector Point

struct Point {
    double x, y;

```

```

Point() {}
Point(double a, double b) {
    x = a;
    y = b;
}

double mod2() { return x * x + y * y; }
double mod() { return sqrt(x * x + y * y); }
double arg() { return atan2(y, x); }
Point ort() { return Point(-y, x); }
Point unit() {
    double k = mod();
    return Point(x / k, y / k);
}

Point operator+(const Point &a, const Point &b) {
    return Point(a.x + b.x, a.y + b.y);
}
Point operator-(const Point &a, const Point &b) {
    return Point(a.x - b.x, a.y - b.y);
}
Point operator/(const Point &a, double k) { return Point(a.x / k, a.y / k); }
Point operator*(const Point &a, double k) { return Point(a.x * k, a.y * k); }

bool operator==(const Point &a, const Point &b) {
    return abs(a.x - b.x) < EPS && abs(a.y - b.y) < EPS;
}
bool operator!=(const Point &a, const Point &b) { return !(a == b); }
bool operator<(const Point &a, const Point &b) {
    if (abs(a.x - b.x) > EPS) return a.x < b.x;
    return a.y + EPS < b.y;
}

##### FUNCIONES BASICAS #####

double dist(const Point &A, const Point &B) {
    return hypot(A.x - B.x, A.y - B.y);
}

double cross(const Vector &A, const Vector &B) { return A.x * B.y - A.y * B.x; }
double dot(const Vector &A, const Vector &B) { return A.x * B.x + A.y * B.y; }
double area(const Point &A, const Point &B, const Point &C) {
    return cross(B - A, C - A);
}

// Heron triangulo y cuadrilatero ciclico
// http://mathworld.wolfram.com/CyclicQuadrilateral.html
// http://www.spoj.pl/problems/QUADAREA/

double areaHeron(double a, double b, double c) {
    double s = (a + b + c) / 2;
    return sqrt(s * (s - a) * (s - b) * (s - c));
}

```

```
double circumradius(double a, double b, double c) {
    return a * b * c / (4 * areaHeron(a, b, c));
}

double areaHeron(double a, double b, double c, double d) {
    double s = (a + b + c + d) / 2;
    return sqrt((s - a) * (s - b) * (s - c) * (s - d));
}

double circumradius(double a, double b, double c, double d) {
    return sqrt((a * b + c * d) * (a * c + b * d) * (a * d + b * c)) /
        (4 * areaHeron(a, b, c, d));
}

#### DETERMINA SI P PERTENECE AL SEGMENTO AB
#####
bool between(const Point &A, const Point &B, const Point &P) {
    return P.x + EPS >= min(A.x, B.x) && P.x <= max(A.x, B.x) + EPS &&
        P.y + EPS >= min(A.y, B.y) && P.y <= max(A.y, B.y) + EPS;
}

bool onSegment(const Point &A, const Point &B, const Point &P) {
    return abs(area(A, B, P)) < EPS && between(A, B, P);
}

#### DETERMINA SI EL SEGMENTO P1Q1 SE INTERSECTA CON EL SEGMENTO P2Q2
#####
// funciona para cualquiera P1, P2, P3, P4
bool intersects(const Point &P1, const Point &P2, const Point &P3,
    const Point &P4) {
    double A1 = area(P3, P4, P1);
    double A2 = area(P3, P4, P2);
    double A3 = area(P1, P2, P3);
    double A4 = area(P1, P2, P4);

    if (((A1 > 0 && A2 < 0) || (A1 < 0 && A2 > 0)) &&
        ((A3 > 0 && A4 < 0) || (A3 < 0 && A4 > 0)))
        return true;

    else if (A1 == 0 && onSegment(P3, P4, P1))
        return true;
    else if (A2 == 0 && onSegment(P3, P4, P2))
        return true;
    else if (A3 == 0 && onSegment(P1, P2, P3))
        return true;
    else if (A4 == 0 && onSegment(P1, P2, P4))
        return true;
    else
        return false;
}

#### DETERMINA SI A, B, M, N PERTENECEN A LA MISMA RECTA
```

```
#####
bool sameLine(Point P1, Point P2, Point P3, Point P4) {
    return area(P1, P2, P3) == 0 && area(P1, P2, P4) == 0;
}

#### SI DOS SEGMENTOS O RECTAS SON PARALELOS
#####
bool isParallel(const Point &P1, const Point &P2, const Point &P3,
    const Point &P4) {
    return cross(P2 - P1, P4 - P3) == 0;
}

#### PUNTO DE INTERSECCION DE DOS RECTAS NO PARALELAS
#####
Point lineIntersection(const Point &A, const Point &B, const Point &C,
    const Point &D) {
    return A + (B - A) * (cross(C - A, D - C) / cross(B - A, D - C));
}

Point circumcenter(const Point &A, const Point &B, const Point &C) {
    return (A + B + (A - B).ort() * dot(C - B, A - C) / cross(A - B, A - C)) / 2;
}

#### FUNCIONES BASICAS DE POLIGONOS
#####
bool isConvex(const vector<Point> &P) {
    int n = P.size(), pos = 0, neg = 0;
    for (int i = 0; i < n; i++) {
        double A = area(P[i], P[(i + 1) % n], P[(i + 2) % n]);
        if (A < 0)
            neg++;
        else if (A > 0)
            pos++;
    }
    return neg == 0 || pos == 0;
}

double area(const vector<Point> &P) {
    int n = P.size();
    double A = 0;
    for (int i = 1; i <= n - 2; i++) A += area(P[0], P[i], P[i + 1]);
    return abs(A / 2);
}

bool pointInPoly(const vector<Point> &P, const Point &A) {
    int n = P.size(), cnt = 0;
    for (int i = 0; i < n; i++) {
        int inf = i, sup = (i + 1) % n;
        if (P[inf].y > P[sup].y) swap(inf, sup);
        if (P[inf].y <= A.y && A.y < P[sup].y)
            if (area(A, P[inf], P[sup]) > 0) cnt++;
    }
    return (cnt % 2) == 1;
}
```



```

##### CONVEX HULL
#####
// O(nh)
vector<Point> ConvexHull(vector<Point> S) {
    sort(all(S));

    int it = 0;
    Point primero = S[it], ultimo = primero;

    int n = S.size();

    vector<Point> convex;
    do {
        convex.push_back(S[it]);
        it = (it + 1) % n;

        for (int i = 0; i < S.size(); i++) {
            if (S[i] != ultimo && S[i] != S[it]) {
                if (area(ultimo, S[it], S[i]) < EPS) it = i;
            }
        }

        ultimo = S[it];
    } while (ultimo != primero);

    return convex;
}

// O(n log n)
vector<Point> ConvexHull(vector<Point> P) {
    sort(P.begin(), P.end());
    int n = P.size(), k = 0;
    Point H[2 * n];

    for (int i = 0; i < n; ++i) {
        while (k >= 2 && area(H[k - 2], H[k - 1], P[i]) <= 0) --k;
        H[k++] = P[i];
    }

    for (int i = n - 2, t = k; i >= 0; --i) {
        while (k > t && area(H[k - 2], H[k - 1], P[i]) <= 0) --k;
        H[k++] = P[i];
    }

    return vector<Point>(H, H + k - 1);
}

##### DETERMINA SI P ESTA EN EL INTERIOR DEL POLIGONO CONVEXO A
#####

// O (log n)
bool isInConvex(vector<Point> &A, const Point &P) {

```

```

    int n = A.size(), lo = 1, hi = A.size() - 1;

    if (area(A[0], A[1], P) <= 0) return 0;
    if (area(A[n - 1], A[0], P) <= 0) return 0;

    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;

        if (area(A[0], A[mid], P) > 0)
            lo = mid;
        else
            hi = mid;
    }

    return area(A[lo], A[hi], P) > 0;
}

// O(n)
Point norm(const Point &A, const Point &O) {
    Vector V = A - O;
    V = V * 10000000000.0 / V.mod();
    return O + V;
}

bool isInConvex(vector<Point> &A, vector<Point> &B) {
    if (!isInConvex(A, B[0]))
        return 0;
    else {
        int n = A.size(), p = 0;

        for (int i = 1; i < B.size(); i++) {
            while (!intersects(A[p], A[(p + 1) % n], norm(B[i], B[0]), B[0]))
                p = (p + 1) % n;

            if (area(A[p], A[(p + 1) % n], B[i]) <= 0) return 0;
        }

        return 1;
    }
}

##### SMALLEST ENCLOSING CIRCLE O(n)
#####
// http://www.cs.uu.nl/docs/vakken/ga/slides4b.pdf
// http://www.spoj.pl/problems/ALIENS/

pair<Point, double> enclosingCircle(vector<Point> P) {
    random_shuffle(P.begin(), P.end());

    Point O(0, 0);
    double R2 = 0;

    for (int i = 0; i < P.size(); i++) {

```

```

    if ((P[i] - O).mod2() > R2 + EPS) {
        O = P[i], R2 = 0;
        for (int j = 0; j < i; j++) {
            if ((P[j] - O).mod2() > R2 + EPS) {
                O = (P[i] + P[j]) / 2, R2 = (P[i] - P[j]).mod2() / 4;
                for (int k = 0; k < j; k++)
                    if ((P[k] - O).mod2() > R2 + EPS)
                        O = circumcenter(P[i], P[j], P[k]), R2 = (P[k] - O).mod2();
            }
        }
    }
    return make_pair(O, sqrt(R2));
}

//##### CLOSEST PAIR OF POINTS
//#####
bool XYorder(Point P1, Point P2) {
    if (P1.x != P2.x) return P1.x < P2.x;
    return P1.y < P2.y;
}
bool YXorder(Point P1, Point P2) {
    if (P1.y != P2.y) return P1.y < P2.y;
    return P1.x < P2.x;
}
double closest_recursive(vector<Point> vx, vector<Point> vy) {
    if (vx.size() == 1) return le20;
    if (vx.size() == 2) return dist(vx[0], vx[1]);

    Point cut = vx[vx.size() / 2];

    vector<Point> vxL, vxR;
    for (int i = 0; i < vx.size(); i++)
        if (vx[i].x < cut.x || (vx[i].x == cut.x && vx[i].y <= cut.y))
            vxL.push_back(vx[i]);
        else
            vxR.push_back(vx[i]);

    vector<Point> vyL, vyR;
    for (int i = 0; i < vy.size(); i++)
        if (vy[i].x < cut.x || (vy[i].x == cut.x && vy[i].y <= cut.y))
            vyL.push_back(vy[i]);
        else
            vyR.push_back(vy[i]);

    double dL = closest_recursive(vxL, vyL);
    double dR = closest_recursive(vxR, vyR);
    double d = min(dL, dR);

    vector<Point> b;
    for (int i = 0; i < vy.size(); i++)
        if (abs(vy[i].x - cut.x) <= d) b.push_back(vy[i]);

```

```

    for (int i = 0; i < b.size(); i++)
        for (int j = i + 1; j < b.size(); j++)
            d = min(d, dist(b[i], b[j]));

    return d;
}
double closest(vector<Point> points) {
    vector<Point> vx = points, vy = points;
    sort(vx.begin(), vx.end(), XYorder);
    sort(vy.begin(), vy.end(), YXorder);

    for (int i = 0; i + 1 < vx.size(); i++)
        if (vx[i] == vx[i + 1]) return 0.0;

    return closest_recursive(vx, vy);
}

// INTERSECCION DE CIRCULOS
vector<Point> circleCircleIntersection(Point O1, double r1, Point O2,
double r2) {
    vector<Point> X;

    double d = dist(O1, O2);

    if (d > r1 + r2 || d < max(r2, r1) - min(r2, r1))
        return X;
    else {
        double a = (r1 * r1 - r2 * r2 + d * d) / (2.0 * d);
        double b = d - a;
        double c = sqrt(abs(r1 * r1 - a * a));

        Vector V = (O2 - O1).unit();
        Point H = O1 + V * a;

        X.push_back(H + V.ort() * c);

        if (c > EPS) X.push_back(H - V.ort() * c);
    }

    return X;
}

// LINEA AB vs CIRCULO (O, r)
// 1. Mucha perdida de precision, reemplazar por resultados de formula.
// 2. Considerar line o segment

vector<Point> lineCircleIntersection(Point A, Point B, Point O, long double r) {
    vector<Point> X;

    Point H1 = O + (B - A).ort() * cross(O - A, B - A) / (B - A).mod2();
    long double d2 = cross(O - A, B - A) * cross(O - A, B - A) / (B - A).mod2();

    if (d2 <= r * r + EPS) {

```

```

    long double k = sqrt(abs(r * r - d2));

    Point P1 = H1 + (B - A) * k / (B - A).mod();
    Point P2 = H1 - (B - A) * k / (B - A).mod();

    if (between(A, B, P1)) X.push_back(P1);

    if (k > EPS && between(A, B, P2)) X.push_back(P2);
}

return X;
}

##### PROBLEMAS BASICOS
#####
void CircumscribedCircle() {
    int x1, y1, x2, y2, x3, y3;
    scanf("%d %d %d %d %d %d", &x1, &y1, &x2, &y2, &x3, &y3);

    Point A(x1, y1), B(x2, y2), C(x3, y3);

    Point P1 = (A + B) / 2.0;
    Point P2 = P1 + (B - A).ort();
    Point P3 = (A + C) / 2.0;
    Point P4 = P3 + (C - A).ort();

    Point CC = lineIntersection(P1, P2, P3, P4);
    double r = dist(A, CC);

    printf("%.6lf,%.6lf,%.6lf\n", CC.x, CC.y, r);
}

void InscribedCircle() {
    int x1, y1, x2, y2, x3, y3;
    scanf("%d %d %d %d %d %d", &x1, &y1, &x2, &y2, &x3, &y3);

    Point A(x1, y1), B(x2, y2), C(x3, y3);

    Point AX = A + (B - A).unit() + (C - A).unit();
    Point BX = B + (A - B).unit() + (C - B).unit();

    Point CC = lineIntersection(A, AX, B, BX);
    double r = abs(area(A, B, CC) / dist(A, B));

    printf("%.6lf,%.6lf,%.6lf\n", CC.x, CC.y, r);
}

vector<Point> TangentLineThroughPoint(Point P, Point C, long double r) {
    vector<Point> X;

    long double h2 = (C - P).mod2();
    if (h2 < r * r)
        return X;

```

```

    else {
        long double d = sqrt(h2 - r * r);

        long double m1 = (r * (P.x - C.x) + d * (P.y - C.y)) / h2;
        long double n1 = (P.y - C.y - d * m1) / r;

        long double n2 = (d * (P.x - C.x) + r * (P.y - C.y)) / h2;
        long double m2 = (P.x - C.x - d * n2) / r;

        X.push_back(C + Point(m1, n1) * r);
        if (d != 0) X.push_back(C + Point(m2, n2) * r);

        return X;
    }
}

void TangentLineThroughPoint() {
    int xc, yc, r, xp, yp;
    scanf("%d %d %d %d %d", &xc, &yc, &r, &xp, &yp);

    Point C(xc, yc), P(xp, yp);

    double hyp = dist(C, P);
    if (hyp < r)
        printf("[]\n");
    else {
        double d = sqrt(hyp * hyp - r * r);

        double m1 = (r * (P.x - C.x) + d * (P.y - C.y)) / (r * r + d * d);
        double n1 = (P.y - C.y - d * m1) / r;
        double ang1 = 180 * atan(-m1 / n1) / PI + EPS;
        if (ang1 < 0) ang1 += 180.0;

        double n2 = (d * (P.x - C.x) + r * (P.y - C.y)) / (r * r + d * d);
        double m2 = (P.x - C.x - d * n2) / r;
        double ang2 = 180 * atan(-m2 / n2) / PI + EPS;
        if (ang2 < 0) ang2 += 180.0;

        if (ang1 > ang2) swap(ang1, ang2);

        if (d == 0)
            printf("[%.6lf]\n", ang1);
        else
            printf("[%.6lf,%.6lf]\n", ang1, ang2);
    }
}

void CircleThroughAPointAndTangentToALineWithRadius() {
    int xp, yp, x1, y1, x2, y2, r;
    scanf("%d %d %d %d %d %d", &xp, &yp, &x1, &y1, &x2, &y2, &r);

    Point P(xp, yp), A(x1, y1), B(x2, y2);

```

```

Vector V = (B - A).ort() * r / (B - A).mod();

Point X[2];
int cnt = 0;

Point H1 = P + (B - A).ort() * cross(P - A, B - A) / (B - A).mod2() + V;
double d1 = abs(r + cross(P - A, B - A) / (B - A).mod());

if (d1 - EPS <= r) {
    double k = sqrt(abs(r * r - d1 * d1));

    X[cnt++] = Point(H1 + (B - A).unit() * k);

    if (k > EPS) X[cnt++] = Point(H1 - (B - A).unit() * k);
}

Point H2 = P + (B - A).ort() * cross(P - A, B - A) / (B - A).mod2() - V;
double d2 = abs(r - cross(P - A, B - A) / (B - A).mod());

if (d2 - EPS <= r) {
    double k = sqrt(abs(r * r - d2 * d2));

    X[cnt++] = Point(H2 + (B - A).unit() * k);

    if (k > EPS) X[cnt++] = Point(H2 - (B - A).unit() * k);
}

sort(X, X + cnt);

if (cnt == 0)
    printf("[]\n");
else if (cnt == 1)
    printf("(%.6lf,%.6lf)\n", X[0].x, X[0].y);
else if (cnt == 2)
    printf("(%.6lf,%.6lf), (%.6lf,%.6lf)\n", X[0].x, X[0].y, X[1].x, X[1].y);
}

void CircleTangentToTwoLinesWithRadius() {
    int x1, y1, x2, y2, x3, y3, x4, y4, r;
    scanf("%d %d %d %d %d %d %d %d %d", &x1, &y1, &x2, &y2, &x3, &y3, &x4, &y4,
        &r);

    Point A1(x1, y1), B1(x2, y2), A2(x3, y3), B2(x4, y4);

    Vector V1 = (B1 - A1).ort() * r / (B1 - A1).mod();
    Vector V2 = (B2 - A2).ort() * r / (B2 - A2).mod();

    Point X[4];
    X[0] = lineIntersection(A1 + V1, B1 + V1, A2 + V2, B2 + V2);
    X[1] = lineIntersection(A1 + V1, B1 + V1, A2 - V2, B2 - V2);
    X[2] = lineIntersection(A1 - V1, B1 - V1, A2 + V2, B2 + V2);
    X[3] = lineIntersection(A1 - V1, B1 - V1, A2 - V2, B2 - V2);

```

```

    sort(X, X + 4);
    printf("(%.6lf,%.6lf), (%.6lf,%.6lf), (%.6lf,%.6lf), (%.6lf,%.6lf)\n", X[0].x,
        X[0].y, X[1].x, X[1].y, X[2].x, X[2].y, X[3].x, X[3].y);
}

void CircleTangentToTwoDisjointCirclesWithRadius() {
    int x1, y1, r1, x2, y2, r2, r;
    scanf("%d %d %d %d %d %d %d", &x1, &y1, &r1, &x2, &y2, &r2, &r);

    Point A(x1, y1), B(x2, y2);

    r1 += r;
    r2 += r;

    double d = dist(A, B);

    if (d > r1 + r2 || d < max(r1, r2) - min(r1, r2))
        printf("[]\n");
    else {
        double a = (r1 * r1 - r2 * r2 + d * d) / (2.0 * d);
        double b = d - a;
        double c = sqrt(abs(r1 * r1 - a * a));

        Vector V = (B - A).unit();
        Point H = A + V * a;

        Point P1 = H + V.ort() * c;
        Point P2 = H - V.ort() * c;

        if (P2 < P1) swap(P1, P2);

        if (P1 == P2)
            printf("(%.6lf,%.6lf)\n", P1.x, P1.y);
        else
            printf("(%.6lf,%.6lf), (%.6lf,%.6lf)\n", P1.x, P1.y, P2.x, P2.y);
    }
}

```

4 Graphs

4.1 Articulation Points

```

#define SZ 100
bool M[SZ][SZ];
int N, colour[SZ], dfsNum[SZ], num, pos[SZ], leastAncestor[SZ], parent[SZ];

int dfs(int u) {

```

```

int ans = 0, cont = 0, v;

stack<int> S;
S.push(u);

while (!S.empty()) {
    v = S.top();
    if (colour[v] == 0) {
        colour[v] = 1;
        dfsNum[v] = num++;
        leastAncestor[v] = num;
    }

    for (; pos[v] < N; ++pos[v]) {
        if (M[v][pos[v]] && pos[v] != parent[v]) {
            if (colour[pos[v]] == 0) {
                parent[pos[v]] = v;
                S.push(pos[v]);
                if (v == u) ++cont;
                break;
            } else
                leastAncestor[v] < ? = dfsNum[pos[v]];
        }
    }

    if (pos[v] == N) {
        colour[v] = 2;
        S.pop();

        if (v != u) leastAncestor[parent[v]] < ? = leastAncestor[v];
    }

    if (cont > 1) {
        ++ans;
        printf("%d\n", u);
    }

    for (int i = 0; i < N; ++i) {
        if (i == u) continue;
        for (int j = 0; j < N; j++)
            if (M[i][j] && parent[j] == i && leastAncestor[j] >= dfsNum[i]) {
                printf("%d\n", i);
                ++ans;
                break;
            }
    }

    return ans;
}

void Articulation_points() {
    memset(colour, 0, sizeof(colour));

```

```

memset(pos, 0, sizeof(pos));
memset(parent, -1, sizeof(parent));
num = 0;

int total = 0;
for (int i = 0; i < N; ++i)
    if (colour[i] == 0) total += dfs(i);

printf("# Articulation Points : %d\n", total);
}

```

4.2 Bridges

```

#define SZ 100
bool M[SZ][SZ];
int N, colour[SZ], dfsNum[SZ], num, pos[SZ], leastAncestor[SZ], parent[SZ];

void dfs(int u) {
    int v;
    stack<int> S;
    S.push(u);

    while (!S.empty()) {
        v = S.top();
        if (colour[v] == 0) {
            colour[v] = 1;
            dfsNum[v] = num++;
            leastAncestor[v] = num;
        }

        for (; pos[v] < N; ++pos[v]) {
            if (M[v][pos[v]] && pos[v] != parent[v]) {
                if (colour[pos[v]] == 0) {
                    parent[pos[v]] = v;
                    S.push(pos[v]);
                    break;
                } else
                    leastAncestor[v] < ? = dfsNum[pos[v]];
            }
        }

        if (pos[v] == N) {
            colour[v] = 2;
            S.pop();

            if (v != u) leastAncestor[parent[v]] < ? = leastAncestor[v];
        }
    }
}

```

```

void Bridge_detection() {
    memset(colour, 0, sizeof(colour));
    memset(pos, 0, sizeof(pos));
    memset(parent, -1, sizeof(parent));
    num = 0;

    int ans = 0;

    for (int i = 0; i < N; i++)
        if (colour[i] == 0) dfs(i);

    for (int i = 0; i < N; i++)
        for (int j = 0; j < N; j++)
            if (parent[j] == i && leastAncestor[j] > dfsNum[i]) {
                printf("%d - %d\n", i, j);
                ++ans;
            }

    printf("%d bridges\n", ans);
}

```

4.3 Disjoint Sets

```

struct UnionFind {
    vector<int> pset, set_size;
    int disjointSetsSize;

    void initSet(int N) {
        pset.assign(N, 0);
        set_size.assign(N, 1);
        disjointSetsSize = N;
        for (int i = 0; i < N; i++) pset[i] = i;
    }

    int findSet(int i) { return (pset[i] == i) ? i : (pset[i] = findSet(pset[i])); }

    bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }

    void unionSet(int i, int j) {
        if (!isSameSet(i, j)) {
            set_size[findSet(j)] += set_size[findSet(i)];
            pset[findSet(i)] = findSet(j);
            disjointSetsSize--;
        }
    }

    int numDisjointSets() { return disjointSetsSize; }
}

```

```

int sizeOfSet(int i) { return set_size[findSet(i)]; }
};

```

4.4 Erdos Gallai

```

// Receives a sorted degree sequence (non ascending)
bool isGraphicSequence(const vector<int> &seq) // O(n lg n)
{
    vector<int> sum;
    int n = seq.size();

    if (n == 1 && seq[0] != 0) return false;

    sum.reserve(n + 1);
    sum.push_back(0);
    for (int i = 0; i < n; ++i) sum.push_back(sum[i] + seq[i]);
    if ((sum[n] & 1) == 1) return false;

    for (long long k = 1; k <= n - 1 && seq[k - 1] >= k; ++k) {
        int j = distance(seq.begin(), upper_bound(seq.begin() + k, seq.end(), k,
                                                    greater<int>())) +
            1;
        long long left = sum[k];
        long long right = k * (k - 1) + (j - k - 1) * k + (sum[n] - sum[j - 1]);

        if (left > right) return false;
    }

    return true;
}

```

4.5 Heavy Light Decomposition

```

#include <bits/stdc++.h>
#define pb push_back
#define sz size
#define all(X) (X).begin(), (X).end()
#define for_each(it, X) \
    for (__typeof((X).begin()) it = (X).begin(); it != (X).end(); it++)

using namespace std;

typedef long long int lld;
typedef pair<int, int> pii;

```

```

const int MaxN = 1 << 20;

int N, M, Level[MaxN], Parent[MaxN], Size[MaxN], Chain[MaxN];
vector<int> E[MaxN];

void DFS(int Curr, int Prev) {
    Parent[Curr] = Prev;
    Size[Curr] = 1;

    for_each(it, E[Curr]) if (*it != Prev) Level[*it] = Level[Curr] + 1,
        DFS(*it, Curr),
        Size[Curr] += Size[*it];
}

void HLD(int Curr, int Prev, int Color) {
    Chain[Curr] = Color;

    int idx = -1;
    for_each(it, E[Curr]) if (*it != Prev && (idx == -1 || Size[*it] > Size[idx]))
        idx = *it;

    if (idx != -1) HLD(idx, Curr, Color);
    for_each(it, E[Curr]) if (*it != Prev && *it != idx) HLD(*it, Curr, *it);
}

inline int LCA(int idx, int idy) {
    while (Chain[idx] != Chain[idy])
        if (Level[Chain[idx]] < Level[Chain[idy]])
            idy = Parent[Chain[idy]];
        else
            idx = Parent[Chain[idx]];
    return Level[idx] < Level[idy] ? idx : idy;
}

int main(void) {
    cin.sync_with_stdio(0);
    cout.sync_with_stdio(0);

    cin >> N >> M;
    for (int i = 0; i < N - 1; i++) {
        int idx, idy;
        cin >> idx >> idy;
        idx--;
        idy--;

        E[idx].pb(idy);
        E[idy].pb(idx);
    }

    DFS(0, -1);
    HLD(0, -1, 0);

    for (int i = 0; i < M; i++) {

```

```

        int idx, idy;
        cin >> idx >> idy;
        idx--;
        idy--;

        cout << LCA(idx, idy) + 1 << endl;
    }

    return 0;
}

```

4.6 Max Cardinality Bipartite Matching Iterative

```

struct MCBM {
    // n = # of left elements, m = # of right elements
    int n, m;
    // adj list for left elements
    // left elements are [0..n-1], right elements are [0..m-1]
    vector<vector<int>> lst;

    bool find_match(int s, vector<int>& lema, vector<int>& rima) {
        vector<int> from(n, -1);
        queue<int> q;
        int where, match, next;
        bool found = false;

        q.push(s), from[s] = s;
        while (!found && !q.empty()) {
            where = q.front();
            q.pop();
            for (int i = 0; i < (int)lst[where].size(); ++i) {
                match = lst[where][i];
                next = rima[match];
                if (where != next) {
                    if (next == -1) {
                        found = true;
                        break;
                    }
                    if (from[next] == -1) q.push(next), from[next] = where;
                }
            }
        }

        if (found) {
            while (from[where] != where) {
                next = lema[where];
                lema[where] = match, rima[match] = where;
                where = from[where], match = next;
            }
        }
    }
}

```

```

        lema[where] = match, rima[match] = where;
    }

    return found;
}

int maximum_matching() // O(V*E)
{
    int ans = 0;
    vector<int> lema(n, -1), rima(m, -1);
    for (int i = 0; i < n; ++i) {
        ans += find_match(i, lema, rima);
    }
    return ans;
}
};

```

4.7 Max Cardinality Bipartite Matching Recursive

```

typedef vector<int> vi;
vector<vi> lst; // adj list: left-nodes links
vi rima, visited; // rima = right nodes' (left-)match
int n, m; // n = # of left nodes, m = # of right nodes

bool find_match(int where) {
    if (where == -1) return 1;
    for (int i = 0; i < (int)lst[where].size(); i++) {
        int match = lst[where][i];
        if (!visited[match]) {
            visited[match] = 1;
            if (find_match(rima[match])) {
                rima[match] = where;
                return 1;
            }
        }
    }
    return 0;
}

int maximum_matching() // O(V*E)
{
    int ans = 0;

    visited.resize(m), rima.assign(m, -1);
    for (int i = 0; i < n; ++i) {
        fill(visited.begin(), visited.end(), 0);
        ans += find_match(i);
    }
}

```

```

    return ans;
}

```

4.8 Max Flow With Min Cost

```

struct McMaxFlow {
    struct MfEdge { int v, cap, cpu, backid; };
    struct FlowResult { int flow, cost; };
    vector<vector<int>> g; // integers represent edges' ids
    vector<MfEdge> edges; // edges.size() should always be even
    int n, s, t; // n = # vertices, s = src vertex, t = sink vertex

    // Directed Edge u -> v with capacity 'cap' and cost per unit 'cpu'
    void add_edge(int u, int v, int cap, int cpu) {
        int eid = edges.size();
        g[u].push_back(eid);
        g[v].push_back(eid + 1);
        edges.push_back(MfEdge{v, cap, cpu, eid + 1});
        edges.push_back(MfEdge{u, 0, -cpu, eid});
    }

    FlowResult find_path() {
        const int inf = int(1e9 + 7);
        vector<int> from(n, -1), used_edge(n, -1);

        vector<int> dist(n, inf);
        queue<int> q; vector<bool> queued(n, false);
        dist[s] = 0; q.push(s); queued[s] = true;

        while (!q.empty()) {
            const int u = q.front(); q.pop();
            queued[u] = false;

            for (int eid : g[u]) {
                int v = edges[eid].v;
                int cand_dist = dist[u] + edges[eid].cpu;
                if (edges[eid].cap > 0 && cand_dist < dist[v]) {
                    dist[v] = cand_dist;
                    from[v] = u; used_edge[v] = eid;
                    if (!queued[v]) { q.push(v); queued[v] = true; }
                }
            }
        }

        int f = 0, fcost = 0;
        if (from[t] != -1) {
            f = inf;
            for (int v = t; from[v] > -1; v = from[v]) {
                f = min(edges[used_edge[v]].cap, f);
            }
        }
    }
};

```



```

        fcost += edges[used_edge[v]].cpu;
    }
    for (int v = t; from[v] > -1; v = from[v]) {
        int backid = edges[used_edge[v]].backid;
        edges[used_edge[v]].cap -= f;
        edges[backid].cap += f;
    }
    fcost *= f;
}

return (FlowResult){f, fcost};
}

FlowResult get() {
    FlowResult res = {0, 0};
    while (true) {
        FlowResult fr = find_path();
        if (fr.flow == 0) break;
        res.flow += fr.flow;
        res.cost += fr.cost;
    }
    return res;
}
};

```

4.9 Max Flow

```

struct MfEdge {
    int v, cap;
    int backid; // id to the back edge
};

struct MaxFlow {
    vector<vector<int>> g; // integers represent edges' ids
    vector<MfEdge> edges; // edges.size() should always be even
    int n, s, t; // n = # vertices, s = src vertex, t = sink vertex

    int find_path() {
        const int inf = int(1e9 + 7);
        vector<int> from(n, -1), used_edge(n, -1);

        vector<int> visited(n, -1); queue<int> q;
        q.push(s); visited[s] = true;
        while (!visited[t] && !q.empty()) {
            int u = q.front();
            q.pop();
            for (int eid : g[u]) {
                int v = edges[eid].v;
                if (edges[eid].cap > 0 && !visited[v]) {

```

```

                    from[v] = u, used_edge[v] = eid;
                    q.push(v); visited[v] = true;
                    if (v == t) break;
                }
            }
        }

        int f = inf;
        if (from[t] != -1) {
            for (int v = t; from[v] > -1; v = from[v]) {
                f = min(edges[used_edge[v]].cap, f);
            }
            for (int v = t; from[v] > -1; v = from[v]) {
                int backid = edges[used_edge[v]].backid;
                edges[used_edge[v]].cap -= f;
                edges[backid].cap += f;
            }
        }
        return (f == inf ? 0 : f);
    }

    int get() {
        int mf = 0, d;
        while ((d = find_path())) mf += d;
        return mf;
    }
};

```

4.10 Strongly Connected Components

```

vector<vector<int>> g, gt;
stack<int> S;
int n;
vi scc;

void scc_dfs(const vector<vector<int>> &g, int u, bool addToStack = false) {
    for (int i = 0; i < (int)g[u].size(); ++i) {
        int v = g[u][i];
        if (scc[v] == inf) {
            scc[v] = scc[u];
            scc_dfs(g, v, addToStack);
        }
    }
    if (addToStack) S.push(u);
}

int kosaraju() {
    const int inf = int(1e9 + 7);
    int ans = 0;

```

```
scc.assign(n, inf);
for (int u = 0; u < n; ++u) {
    if (scc[u] != inf) continue;
    scc[u] = true;
    scc_dfs(g, u, true);
}
scc.assign(n, inf);
while (!S.empty()) {
    int u = S.top();
    S.pop();
    if (scc[u] != inf) continue;
    scc[u] = ans++;
    scc_dfs(g, u);
}

return ans;
}
```

4.11 Tree Center

```
#define MAX_SIZE 50000

vector<int> L[MAX_SIZE];

bool visited[MAX_SIZE];
int V, prev[MAX_SIZE], Q[MAX_SIZE], tail;

int most_distant(int s) {
    fill(visited, visited + V, false);
    visited[s] = true;
    Q[0] = s;
    tail = 1;
    prev[s] = -1;

    int ans = s;

    for (int k = 0; k < V; ++k) {
        int aux = Q[k];
        ans = aux;

        for (int i = L[aux].size() - 1; i >= 0; --i) {
            int v = L[aux][i];
            if (visited[v]) continue;
            visited[v] = true;
            Q[tail] = v;
            ++tail;
            prev[v] = aux;
        }
    }
}
```

```
}

return ans;
}

void get_center() {
    int s = most_distant(0);
    int e = most_distant(s);
    int v = e, L = 0;

    while (v != -1) {
        Q[L] = v;
        v = prev[v];
        ++L;
    }

    if (L & 1)
        printf("%d\n", 1 + Q[L / 2]);
    else
        printf("%d %d\n", 1 + min(Q[L / 2 - 1], Q[L / 2]),
            1 + max(Q[L / 2 - 1], Q[L / 2]));
}
```

5 Java

5.1 Fast Input Output Template

```
import java.io.*;
import java.math.*;
import java.util.*;
import java.lang.*;

public class Main {
    public static void main(String[] args) {
        InputReader in = new InputReader(System.in);
        OutputWriter out = new OutputWriter(System.out);
        // Do your thing
        out.close();
    }
}

class InputReader {
    private InputStream stream;
    private byte[] buf = new byte[1024];
    private int curChar;
    private int numChars;
    private SpaceCharFilter filter;
```

```

public InputReader(InputStream stream) {
    this.stream = stream;
}

public int read() {
    if (numChars == -1) {
        throw new InputMismatchException();
    }

    if (curChar >= numChars) {
        curChar = 0;
        try {
            numChars = stream.read(buf);
        } catch (IOException e) {
            throw new InputMismatchException();
        }
        if (numChars <= 0) {
            return -1;
        }
    }

    return buf[curChar++];
}

public int readInt() {
    int c = read();
    while (isSpaceChar(c)) {
        c = read();
    }

    int sgn = 1;
    if (c == '-') {
        sgn = -1;
        c = read();
    }

    int res = 0;
    do {
        if (c < '0' || c > '9') {
            throw new InputMismatchException();
        }
        res *= 10;
        res += c - '0';
        c = read();
    } while (!isSpaceChar(c));

    return res * sgn;
}

public String readString() {
    int c = read();
    while (isSpaceChar(c)) {

```

```

        c = read();
    }

    StringBuilder res = new StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isSpaceChar(c));
    return res.toString();
}

public boolean isSpaceChar(int c) {
    if (filter != null) {
        return filter.isSpaceChar(c);
    }
    return c == ' ' || c == '\n' || c == '\r' || c == '\t' || c == -1;
}

public String next() {
    return readString();
}

public interface SpaceCharFilter {
    public boolean isSpaceChar(int ch);
}

class OutputWriter {
    private final PrintWriter writer;

    public OutputWriter(OutputStream outputStream) {
        writer = new PrintWriter(
            new BufferedWriter(new OutputStreamWriter(outputStream))
        );
    }

    public OutputWriter(Writer writer) {
        this.writer = new PrintWriter(writer);
    }

    public void print(Object... objects) {
        for (int i = 0; i < objects.length; i++) {
            if (i != 0) {
                writer.print(' ');
            }
            writer.print(objects[i]);
        }
    }

    public void printLine(Object... objects) {
        print(objects);
        writer.println();
    }
}

```

```

public void close() {
    writer.close();
}

public void flush() {
    writer.flush();
}
}

class IOUtils {
    public static int[] readIntArray(InputReader in, int size) {
        int[] array = new int[size];
        for (int i = 0; i < size; i++) {
            array[i] = in.readInt();
        }
        return array;
    }
}

```

6 Math

6.1 Big Integer

```

string trim_zeros(const string& a) {
    size_t idx = 0;
    while (a[idx] == '0' && idx < a.size()) idx++;
    if (idx == a.size()) idx--;

    return a.substr(idx);
}

string big_sub(const string& n1, const string& n2) {
    string a = trim_zeros(n1);
    string b = trim_zeros(n2);

    bool minus = false;
    if (esMayor(b, a)) {
        swap(a, b);
        minus = true;
    }

    int i, j, d = (a.length() - b.length());
    for (i = b.length() - 1; i >= 0; i--) {
        if (a[i + d] >= b[i])
            a[i + d] -= b[i] - '0';
        else {

```

```

            j = -1;
            while (a[i + d + j] == '0') {
                a[i + d + j] = '9';
                j--;
            }
            a[i + d + j]--;

            a[i + d] += 10 - b[i] + '0';
        }
    }

    return (minus ? "-" : "") + trim_zeros(a);
}

string big_add(const string& a, const string& b) {
    int LA = a.size(), LB = b.size(), L = max(LA, LB), carry = 0;

    string x = string(L, '0');

    while (L-- > 0) {
        LA--;
        LB--;

        if (LA >= 0) carry += a[LA] - '0';
        if (LB >= 0) carry += b[LB] - '0';

        if (carry < 10)
            x[L] = '0' + carry, carry = 0;
        else
            x[L] = '0' + carry - 10, carry = 1;
    }

    if (carry) x = '1' + x;
    return x;
}

string big_mult(string a, string b) {
    if (a == "0" || b == "0")
        return "0";
    else if (a.size() == 1) {
        int m = a[0] - '0';

        string ans = string(b.size(), '0');

        int lleva = 0;

        for (int i = b.size() - 1; i >= 0; i--) {
            int d = (b[i] - '0') * m + lleva;
            lleva = d / 10;
            ans[i] += d % 10;
        }
        if (lleva) ans = (char)(lleva + '0') + ans;
        return ans;
    }
}

```

```

} else if (b.size() == 1)
    return big_mult(b, a);
else {
    string ans = "0";
    string ceros = "";
    for (int i = a.size() - 1; i >= 0; i--) {
        string s = big_mult(string(1, a[i]), b) + ceros;
        ceros += "0";
        ans = big_add(ans, s);
    }
    return ans;
}
}

```

6.2 Chinese Remainer Theorem

```

// rem y mod tienen el mismo numero de elementos
long long chinese_remainder(vector<int> rem, vector<int> mod) {
    long long ans = rem[0], m = mod[0];
    int n = rem.size();

    for (int i = 1; i < n; ++i) {
        int a = modular_inverse(m, mod[i]);
        int b = modular_inverse(mod[i], m);
        ans = (ans * b * mod[i] + rem[i] * a * m) % (m * mod[i]);
        m *= mod[i];
    }

    return ans;
}

```

6.3 Combinations

```

long long comb(int n, int m) {
    if (m > n - m) m = n - m;

    long long C = 1;
    // C^{n}_{i} -> C^{n}_{i+1}
    for (int i = 0; i < m; ++i) C = C * (n - i) / (1 + i);
    return C;
}

// Cuando n y m son grandes y se pide comb(n, m) % MOD,
// donde MOD es un numero primo, se puede usar el Teorema de Lucas.

```

```

#define MOD 3571
int C[MOD][MOD];

void FillLucasTable() {
    memset(C, 0, sizeof(C));

    for (int i = 0; i < MOD; ++i) C[i][0] = 1;
    for (int i = 1; i < MOD; ++i) C[i][i] = 1;
    for (int i = 2; i < MOD; ++i)
        for (int j = 1; j < i; ++j) C[i][j] = (C[i - 1][j] + C[i - 1][j - 1]) % MOD;
}

int comb(int n, int k) {
    long long ans = 1;

    while (n != 0) {
        int ni = n % MOD, ki = k % MOD;
        n /= MOD;
        k /= MOD;
        ans = (ans * C[ni][ki]) % MOD;
    }

    return (int)ans;
}

```

6.4 Deterministic Miller Rabin

```

/*
** Deterministic Miller-Rabin
** if n < 3,825,123,056,546,413,051, it is enough to test
** a = 2, 3, 5, 7, 11, 13, 17, 19, and 23.
*/
#include <bits/stdc++.h>
using namespace std;
typedef unsigned long long ll;

vector<ll> mr_values({2, 3, 5, 7, 11, 13, 17, 19, 23});

ll mulmod(ll a, ll b, ll n) {
    ll erg = 0;
    ll r = 0;
    while (b > 0) {
        // unsigned long long gives enough room for base 10 operations
        ll x = ((a % n) * (b % 10)) % n;
        for (ll i = 0; i < r; i++) x = (x * 10) % n;
        erg = (erg + x) % n;
        r++;
        b /= 10;
    }
}

```

```

    return erg;
}

ll fastexp(ll a, ll b, ll n) {
    if (b == 0) return 1;
    if (b == 1) return a % n;
    ll res = 1;
    while (b > 0) {
        if (b % 2 == 1) res = mulmod(a, res, n);
        a = mulmod(a, a, n);
        b /= 2;
    }
    return res;
}

bool mrtest(ll n) {
    if (n == 1) return false;
    ll d = n - 1;
    ll s = 0;
    while (d % 2 == 0) {
        s++;
        d /= 2;
    }
    for (ll j = 0; j < (ll)mr_values.size(); j++) {
        if (mr_values[j] > n - 1) continue;
        ll ad = fastexp(mr_values[j], d, n);
        if (ad % n == 1) continue;
        bool notcomp = false;
        for (ll r = 0; r <= max(0ull, s - 1); r++) {
            ll rr = fastexp(2, r, n);
            ll ard = fastexp(ad, rr, n);
            if (ard % n == n - 1) {
                notcomp = true;
                break;
            }
        }
        if (!notcomp) {
            return false;
        }
    }
    return true;
}

bool isprime(ll n) {
    if (n <= 1) return false;
    if (n == 2) return true;
    if (n % 2 == 0) return false;
    return mrtest(n);
}

```

6.5 Extended Gcd

```

// a*x + b*y = gcd(a,b)
int extGcd(int a, int b, int &x, int &y) {
    if (b == 0) {
        x = 1;
        y = 0;
        return a;
    }

    int g = extGcd(b, a % b, y, x);
    y -= a / b * x;
    return g;
}

// ASSUME: gcd(a, m) == 1
int modInv(int a, int m) {
    int x, y;
    extGcd(a, m, x, y);
    return (x % m + m) % m;
}

```

6.6 Factorial Prime Factors

```

vector<int> primes; // Filled with prime numbers <= n (at least)

void factorial_prime_factor(const int n, vector<int>& v) {
    v.clear();
    for (size_t i = 0; primes[i] <= n && i < primes.size(); i++) {
        const int& p = primes[i];
        double q = (n / (double)p);
        int d = int(q);

        while (q >= p) {
            q /= p;
            d += int(q);
        }

        v.push_back(d);
    }
}

```

6.7 Least Significant Bit Position

```
// http://supertech.csail.mit.edu/papers/debruijn.pdf
int lsbpos(unsigned int v) {
    static const int t[32] = {0, 1, 28, 2, 29, 14, 24, 3, 30, 22, 20,
                              15, 25, 17, 4, 8, 31, 27, 13, 23, 21, 19,
                              16, 7, 26, 12, 18, 6, 11, 5, 10, 9};
    return t[((unsigned int)((v & -v) * 0x077CB531U)) >> 27];
}
```

7 Strings

7.1 Knuth Morris Pratt

```
#define MAX_L 70
int f[MAX_L];

void prefixFunction(string P) {
    int n = P.size(), k = 0;
    f[0] = 0;

    for (int i = 1; i < n; ++i) {
        while (k > 0 && P[k] != P[i]) k = f[k - 1];
        if (P[k] == P[i]) ++k;
        f[i] = k;
    }
}

int KMP(string P, string T) {
    int n = P.size(), L = T.size(), k = 0, ans = 0;

    for (int i = 0; i < L; ++i) {
        while (k > 0 && P[k] != T[i]) k = f[k - 1];
        if (P[k] == T[i]) ++k;

        if (k == n) {
            ++ans;
            k = f[k - 1];
        }
    }

    return ans;
}
```

7.2 Minimum String Rotation

```
int minimumExpression(string s) {
    s = s + s;
    int len = s.size(), i = 0, j = 1, k = 0;
    while (i + k < len && j + k < len) {
        if (s[i + k] == s[j + k])
            k++;
        else if (s[i + k] > s[j + k]) {
            i = i + k + 1;
            if (i <= j) i = j + 1;
            k = 0;
        } else if (s[i + k] < s[j + k]) {
            j = j + k + 1;
            if (j <= i) j = i + 1;
            k = 0;
        }
    }
    return min(i, j);
}
```

7.3 Trie

```
#include <bits/stdc++.h>
using namespace std;

template <int alphabet_size>
struct TrieNode {
    int n_words, n_prefixes;
    int child[alphabet_size] = {0};

    TrieNode() : n_words(0), n_prefixes(0) { }
};

template <int alphabet_size>
struct Trie {
    static constexpr int npos = -1;
    using TNode = TrieNode<alphabet_size>;
    vector<TNode> nodes;

    Trie() { nodes.emplace_back(); }

    /*
    ** Maps the given char to an unsigned integer
    ** inside the range [0..alphabet_size)
    */
    int char_to_child(char c) {
        int result = c - '0';
        //assert(0 <= result && result < alphabet_size);
        return result;
    }
}
```

```

/*
** Adds the given word to the trie
*/
void add_word(const char *s) {
    int current = 0;

    for (int i = 0; s[i]; i++) {
        nodes[current].n_prefixes += 1;

        int next_child = char_to_child(s[i]);

        int next_node = nodes[current].child[next_child];
        if (next_node == 0) {
            next_node = nodes.size();
            nodes[current].child[next_child] = next_node;
            nodes.emplace_back();
        }
        current = next_node;
    }

    nodes[current].n_prefixes += 1;
    nodes[current].n_words += 1;
}

/*
** Traverses the trie, following the content of string 's'.
** Returns the node ID where the traversal stopped, or
** Trie::npos if it couldn't follow the whole string.
*/
int traverse(const char *s) {
    int current = 0;

    for (int i = 0; s[i]; i++) {
        int next_child = char_to_child(s[i]);

        int next_node = nodes[current].child[next_child];
        if (next_node == 0) {
            return Trie::npos;
        }

        current = next_node;
    }

    return current;
}

int count_prefixes(const char *s) {
    int node = traverse(s);
    int result = (node == Trie::npos ? 0 : nodes[node].n_prefixes);
    return result;
}

```

```

int count_words(const char *s) {
    int node = traverse(s);
    int result = (node == Trie::npos ? 0 : nodes[node].n_words);
    return result;
}
};

```

7.4 Z Function

```

/*
** Given a string S of length n, the Z Algorithm produces
** an array Z where Z[i] is the length of the longest substring
** starting from S[i] which is also a prefix of S, i.e. the
** maximum k such that S[j] = S[i + j] for all 0 ≤ j < k.
** Note that Z[i] = 0 means that S[0] != S[i].
*/
void z_func(const string &s) {
    const int length = s.size();
    int left = 0, right = 0;

    vi z(length);
    z[0] = 0;

    for (int i = 1; i < length; i++) {
        if (i > right) {
            int j;
            for (j = 0; i + j < length && s[i + j] == s[j]; j++)
                ;
            z[i] = j;
            left = i;
            right = i + j - 1;
        } else if (z[i - left] < right - i + 1)
            z[i] = z[i - left];
        else {
            int j;
            for (j = 1; right + j < length && s[right + j] == s[right - i + j]; j++)
                ;
            z[i] = right - i + j;
            left = i;
            right = right + j - 1;
        }
    }

    return z;
}

```