



TECHNICAL DATA SHEET

M ONE silicone spray

Product description

M ONE silicone spray is a grease-free protection, lubricant, release and care agent for plastics, wood, rubber and metals.

- Lubricates stain-free and invisibly, non-resinous lubricating film
- Good surface quality and high temperature resistance
- Good electrical resistance, water-repellent and anti-static
- Protects against oxidation and corrosion

Application instructions

M ONE silicone spray has a very wide range of applications. In paper and wood processing it prevents the build-up of adhesive residue on presses and guides. The treatment of cut strips, - edges and tools ensure easy, clean cutting. In the field of conveyor technology Prevents goods from sticking to conveyor belts, channels, slideways and slides.

- Rubber parts are cared for, do not become brittle, freeze or stick
- Plastic parts have a good shine and do not become brittle
- Makes stuck and squeaking parts work again

Processing instructions

Shake the can vigorously before use. From a distance of 20-30 cm onto the cleaned and degreased area to be treated Spray on surface and rub with a soft cloth.

M ONE
At Kapellenberg 11
97246 Eibelstadt
Tel: +49 9366 90710

info@m-one.net www.m-one.net

With this information we want to advise you to the best of our knowledge based on our experiments and experiences. However, we can provide a guarantee for the processing results in individual cases due to the large number of possible uses and the outside influence of storage and handling conditions. We do not accept the processing conditions of our products. Carry out your own experiments. Lightweight discoloration of sealants possible under UV radiation. Minor color variations between batches due to product technology. No guarantee is given for absolute color fidelity. Object-related use material from the same batch. Our technical and commercial advisory service is at your disposal available.

With the publication of this data sheet, all previous editions become invalid.

Issue: 07.24