



SAFETY DATA SHEET

This safety data sheet has been prepared in accordance with the following requirements:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

M-ONE UBS SPRAY
Replaces date 05-Aug-2025

Revised on Dec 15, 2025
Revision number 1.04

SECTION 1: Identification of the substance or mixture and of the company

1.1. Product identifier

Product name M-ONE UBS SPRAY

Other names

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Corrosion inhibitor aerosol

Uses of which will None known. discouraged

1.3. Details of the supplier providing the safety data sheet

Company name

M ONE
At Kapellenberg 11
97246 Eibelstadt
Tel: +49 9366 90710

Email address info@m-one.net

1.4. Emergency number

Deutschland GGIZ Erfurt's 24-hour emergency number: +49-361-730730

SECTION 2: Potential Hazards

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosols	Category 1 - (H222, H229)
Skin irritation	Category 2 - (H315)
Eye irritation	Category 2 - (H319)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

2.2. Marking elements

Contains xylene; ethylbenzene; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, < 2% aromatics



Signal word

Danger

SAFETY DATA SHEET

M-ONE UBS SPRAY

Replaces date 05-Aug-2025

Danger warnings

H222 - Extremely flammable aerosol.

Revised on Dec 15, 2025

Revision number 1.04

H229 - Container is pressurized: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

Safety instructions - Regulation (EC) §28, No. 1272/2008

P101 - If medical advice is required, have container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. Don't smoke

P211 - Do not spray on an open flame or other source of ignition

P251 - Do not puncture or burn, even after use

P260 - Do not breathe dust, smoke, gas, mist, vapor or aerosol

P264 - Wash skin thoroughly after use

P280 - Wear protective gloves, eye protection and face protection

P314 - Get medical advice/attention if you feel unwell

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Possibly

Remove existing contact lenses if possible. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P410 + P412 - Protect from direct sunlight. Do not expose to temperatures above 50°C/122°F

P501 - Dispose of contents/container to an approved waste disposal facility

Additional Information This product requires one when delivered to the general public tactile warning.

2.3. Other dangers

Formation of explosive/highly flammable mixtures is possible if there is insufficient ventilation or through use.

PBT & vPvB

The components of this formulation do not meet the criteria for classification as a PBT or vPvB substance.

Endocrine Disorder Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Designation	Weight% REACH registration serial number	EC no. (index-Nr.)	Classification according to Regulation (EC) Nr. 1272/2008 [CLP]	More specific concentration limit (SCL):	M factor	M factor (long term g)	Notice
Xylene 1330-20-7	10 - <20 01-2119488216-32-xxxx	215-535-7 (601-022-00-9)	Acute Tox. 4 (H312) Acute Tox. 4 (H332)	-	-	-	C
			Skin irritation. 2 (H315) Eye irritation. 2 (H319) STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 3 (H226)				
n-butane 106-97-8	5 - <10 01-2119474691-32-XXXX	203-448-7	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	C,U

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025

Revised on Dec 15, 2025
Revision number 1.04

			(601-004-00-0)					
Ethylbenzene 100-41-4	5 - <10	01-2119489370 -35-XXXX	202-849-4 (601-023-00-4)	Acute Tox. 4 (H332) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225)	-	-	-	-
hydrocarbons, C10-C13, n-Alkane, isoalkanes, Cycloalkanes, <2% aromatics RR-113412-9	1 - <5	01-2119457273 -39-XXXX	918-481-9	Asp. Tox. 1 (H304) (EUH066)	-	-	-	-
Isobutane 75- 28-5	1 - <5	01-2119485395 -27-XXXX	200-857-2 (601-004-00-0)	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	C,U

Substances marked with a number starting with ·RR· in the CAS field are substances for which no CAS number is used. We use an internal numbering system for this in our SDB software

Note C - Some organic substances can exist either in a well-defined isomeric form or as a mixture several isomers are placed on the market. In this case, the supplier must indicate on the identification label whether it is a specific isomer or a mixture of isomers.

Note U - When placed on the market, the gases must be classified as ·gases under pressure· in one of the groups of compressed gases, of liquefied gases, frozen gases or dissolved gases. The assignment to a group depends on the physical state in which the gas is packaged and must therefore be decided on a case-by-case basis. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols may not be classified as gases under pressure (see Annex I, Part 2, Section 2.3.2.1, Note 2).

For the wording of the H and EUH phrases see section 16

Estimation of acute toxicity

If LD50/LC50 data is not available or does not correspond to the classification category, the appropriate Conversion value from CLP Annex I, Table 3.1.2 used to calculate the Acute Toxicity Estimate (ATEmix) for classification of a mixture based on its components

Chemical Designation	EC no. (index-Nr.)	CAS no.	Oral LD 50 mg/kg	Dermal LD50 mg/kg	Inhale LC50 - 4 h - Dust/Fog - mg/l	Inhale LC50 - 4 h - Steam - mg/l	Inhale LC50 - 4 h - Gas - ppm
Xylene	215-535-7 (601-022-00-9)	1330-20-7	-	1990	-	11	-
n-butane	203-448-7 (601-004-00-0)	106-97-8	-	-	-	-	-
Ethylbenzene	202-849-4 (601-023-00-4)	100-41-4	3500	15400	4.99	17.6	-
hydrocarbons, C10-C13, n-Alkane, isoalkanes, cycloalkanes, <2% aromatics	918-481-9	RR-113412-9	5001	-	-	>5.001	-
Isobutane	200-857-2 (601-004-00-0)	75-28-5	-	-	-	-	-

This product does not contain substances of very high concern (SVHC) on the candidate list at a concentration of >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025

Revised on Dec 15, 2025
Revision number 1.04

SECTION 4: First aid measures

4.1 Description of first aid measures

General recommendation	This safety data sheet must be shown to the attending physician. Immediate medical treatment is required.
Inhale	Get some fresh air. Aspiration into the lungs can cause serious complications lead to lung damage. If breathing stops, administer artificial respiration. Medical Call in help. Avoid direct contact with skin. At Use protection against contact when performing mouth-to-mouth resuscitation. If you have difficulty breathing (trained personnel should) administer oxygen. Pulmonary edema may be delayed occur.
Eye contact	Rinse immediately thoroughly with plenty of water for at least 15 minutes, including under the skin eyelids. If possible, remove any contact lenses. Next rinse out. Keep eyes wide open while rinsing. Affected area don't rub. If irritation occurs and persists, consult a doctor.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. At If persistent irritation occurs, consult a doctor.
Swallowed	IF SWALLOWED, RISK OF ASPIRATION - CAN INTO LUNGS GET THERE AND CAUSE DAMAGE. DO NOT induce vomiting. If you vomit spontaneously, keep your head below your hips to prevent aspiration prevent. Rinse mouth. Never give water to an unconscious person. Immediately seek medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical staff are aware of the is informed about the substance(s) involved, takes measures to protect himself and a Spread of contamination is avoided. Wear personal protective clothing (see Section 8). Avoid direct contact with skin. At Use protection against contact when performing mouth-to-mouth resuscitation. Prescribed ones Use personal protective equipment. Contact with skin, eyes and clothing avoid.

4.2. Most important acute and delayed symptoms and effects

Symptoms	Difficulty breathing. Coughing and/or wheezing. Lightheadedness. May cause redness and cause watery eyes. Burning sensation.
Effects upon exposure	May cause damage to organs through prolonged or repeated exposure.

4.3. Indications of immediate medical attention or special treatment

Note to the doctor	Because of the risk of aspiration, no vomiting and no gastric lavage should be performed be carried out if the risk is not posed by the danger of further toxic substances is justified.
---------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing agent

Suitable extinguishing agents	Dry extinguishing agent. Carbon dioxide (CO ₂). Spray water.
Unsuitable extinguishing agents	Full water jet. ONLY EXTINGUISH A FIRE CAUSED BY LEAKING GAS IF LEAKAGE CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Special dangers arising from the risk of inflammation. Keep product and empty container away from heat and sources of ignition. Run out of substance in the event of fire, cool containers with water spray. Fire residue and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Gas cylinders can break in extreme heat. Handling Damaged pressure bottles should only be repaired by professionals. Containers may explode when heated.

Dangerous combustion products Carbon monoxide. Carbon dioxide (CO₂).

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025
5.3. Advice for firefighting ·

Revised on Dec 15, 2025
Revision number 1.04

Special protective equipment and fire crews must wear self-contained breathing apparatus and complete
Precautions for Wear emergency clothing. Use personal protective equipment.
Firefighting

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures ·

Personal Evacuate employees to safe areas. Mandatory personal
Precautions Use protective equipment. For more information, see Section 8. Touch
avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Keep people away from the spill/leak
send to the windward side. REMOVE all sources of ignition (no smoking, no
Sparks or flames in the immediate surrounding area). Measures against
meet electrostatic charges. Inhale from
Avoid dust/smoke/gas/mist/steam/aerosol.

Other information Ventilate the area. See safeguards listed in Sections 7 and 8.

emergency services Use personal protective equipment recommended in Section 8.

6.2. Environmental protection measures

Environmental protection measures See safeguards listed in Sections 7 and 8. If
gefahrlos möglich weitere Leckagen oder Verschütten vermeiden. Not in that
Allow access to sewers or waterways.

6.3. Methods and material for containment and cleaning ·

Methods for restraint Stop the leak if it is safe to do so. Can be used to reduce fumes
a vapor suppressing foam can be used. Spills over a wide area
Dam to catch runoff water. Not in drains, sewers, ditches and
allow water to enter. Flood with water to complete polymerization and
then scrape it off the floor.

Cleaning procedure Take measures against electrostatic charges. Contain. With inert,
absorbent material. Record and place in appropriately marked areas
Transfer container. Clean, spark-proof tool for collecting the
Use absorbed material.

Avoiding secondary hazards Remove all sources of ignition if safe to do so. Non-recyclable residues
are disposed of as chemical waste. Rinsing fluids containing organic solvents
Cleaned equipment is collected and disposed of as solvent waste.

6.4. Reference to other sections

Reference to other sections For more information, see Section 8. For more information, see
Section 13.

SECTION 7: Handling and storage

7.1. Protective measures for safe handling

Instructions for safe handling Use personal protective equipment. From heat, hot surfaces, sparks,
Keep away from open flames and other sources of ignition. Do not smoke. Not against
spray onto an open flame or other source of ignition. Measures to avoid one
electrostatic discharge (which can cause organic vapors to ignite)
company. Use spark-proof tools and explosion-proof equipment.
Only handle the product in a closed system or with sufficient suction
provide. Store in areas where a sprinkler system is installed.
Do not open or burn cans. Content is under pressure. In case of a break.
Avoid breathing vapors or mist. With good work hygiene and
Handle safety technology. Avoid contact with skin, eyes and clothing. At
Do not eat, drink or smoke. Take off contaminated clothing and put it in front of you
Wash before wearing.

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025

Revised on Dec 15, 2025
Revision number 1.04

General hygiene regulations

Do not eat, drink or smoke when using. Do not contaminated work clothing wear outside the workplace. Regular cleaning of equipment work area and clothing is recommended. Hands before breaks and immediately wash after handling the product. Suitable for work
Wear protective gloves and safety glasses/face protection. Contact with skin, eyes and avoid clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Protect from sunlight. From heat, sparks, flames and others
Keep sources of ignition away (i.e. pilot lights, electric motors and static electricity).
Store in correctly labeled containers. Not near combustibles
Store materials. Store in areas where a sprinkler system is installed
is. Store in accordance with specific national regulations. According to local
Store regulations. Store in a cool, dry area, away from
potential heat sources, open flames, direct sunlight or
other chemicals. Store under lock and key. Must not fall into the hands of
children reach. Store away from other materials. Only in
Keep/store original container. In a closed container on one
store in a dry place.

7.3. Specific end uses

Specific uses

Aerosol. Corrosion inhibitor.

Risk management measures (RMM)

The required information is contained in this safety data sheet.

Other information

Please note the technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Zu uberwachende Parameter

Exposure limits

Chemical name	European Union	Germany TRGS
Xylene 1330-20-7	TWA: 50 ppm; TWA: 221 mg/m3;	TWA-AGW; 50 ppm (2(II)); TWA-AGW; 220 mg/m3 (2(II));
	STEL: 100 ppm; STEL: 442 mg/m3; pSk	Sk
Propane 74-98-6	-	TWA-AGW; 1000 ppm (4(II)); TWA-AGW; 1800 mg/m3 (4(II));
n-butane 106-97-8	-	TWA-AGW; 1000 ppm (4(II)); TWA-AGW; 2400 mg/m3 (4(II));
Ethylbenzene 100-41-4	TWA: 100 ppm; TWA: 442 mg/m3; STEL: 200ppm; STEL: 884 mg/m3; pSk	TWA-AGW; 20 ppm (2(II)); TWA-AGW; 88 mg/m3 (2(II)); Sk
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, Cycloalkanes, <2% aromatics RR-113412-9	-	C9-C14 ALIPHATES Germany TRGS 900 300 mg/m3 -8 hrs Mw. steam. C10-C13 RCP TWA 1200 mg/m3 184 ppm Total hydrocarbons (ExxonMobil)
Isobutane 75-28-5	-	TWA-AGW; 1000 ppm (4(II)); TWA-AGW; 2400 mg/m3 (4(II));

Biological workplace limits

Chemical name	European Union	Germany TRGS
Xylene 1330-20-7	-	2000 mg/L (urine - Methylhippuric(tolur-)acid (all isomers) end of exposure or shift)

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025

Revised on Dec 15, 2025
Revision number 1.04

Ethylbenzol 100-41-4	-	250 mg/g creatinine (urine - mandelic acid plus Phenylglyoxylic acid end of exposure or shift)
----------------------	---	--

Derived exposure level without impairment. No information is available (DNEL)

Estimated No-effect concentration (PNEC) No information is available.

8.2. Limiting and monitoring exposure

Technical Control devices Ensure adequate ventilation, especially in enclosed spaces. vapors / Aerosols must be safely extracted directly at the point of origin.

Personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must be the norm Correspond to DIN EN 166.
Hand protection	Wear suitable protective gloves. Thickness of gloves > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough times for the specified glove materials are in generally greater than 480 minutes. Ensure that the breakthrough time of the Glove material is not exceeded. Information from the supplier Use breakthrough time for the specific gloves.
Recommendations	Gloves must comply with the EN 374 standard
Skin and body protection	Personal protective clothing suitable to protect against contact with skin wear.
Respiratory protection	Ensure adequate ventilation when spraying. In case of insufficient ventilation Put on breathing apparatus.
Recommended filter type:	Filter for organic gases and vapors according to EN 14387. Respiratory mask according to EN 140 Wear with filter type A or better.

Limitation and monitoring of No information is available.

Environmental exposure

SECTION 9: Physical and chemical properties

9.1. Information on the basic physical and chemical properties

Physical condition	liquid
Appearance	Aerosol
color	Black
smell	Solvent.

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025

Revised on Dec 15, 2025
Revision number 1.04

<u>property</u>	<u>Values</u>	<u>Remarks · Method</u>
Melting point / freezing point	No data available	None known
Start of boiling point and boiling range	.	Not applicable, aerosol
Inflammability	No data available	None known
Flammability limit in the Luft		None known
Upper flammability or Explosion limit	No data available	
Lower flammability or Explosion limit	No data available	
Flash point	No data available	Not applicable, aerosol
Auto-ignition temperature	No data available	None known
Decomposition temperature pH		None known
Value pH (as aqueous solution)	No data available	Not applicable. Insoluble in water.
Viscosity, kinematic	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water.	None known
solubility(ies)	No data available	None known
distribution coefficient	No data available	None known
Vapor pressure	No data available	hPa
Relative density bulk density	No data available	None known
density	No data available	
Relative vapor density	0.90 - 1.1 g/cm ³	
Particle properties	No data available	None known
particle size	No information is available	
Particle size distribution	No information is available	

9.2. Other information

Solids content (%) No information is available

Volatile organic compound content approximately 488.8 g/L

9.2.1. Information on physical hazard classes Not applicable

9.2.2. Other security features

No information is available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information is available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

sensitivity to mechanical impact sensitivity versus Yes.
static discharge

None.

10.3. Possibility of dangerous reactions

Possibility of dangerous Reactions Heating leads to an increase in pressure and the risk of bursting.

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025
10.4. Conditions to avoid

Revised on Dec 15, 2025
Revision number 1.04

Conditions to avoid	Heat, sparks and flames. From open flames, hot surfaces and Keep ignition sources away. Extreme temperatures and direct sunlight.
---------------------	--

10.5. Incompatible materials

Incompatible materials	Strong acids. Strong alkalis. Strong oxidizing agents. Incompatible with oxidizing agents.
------------------------	---

10.6. Dangerous decomposition products

Hazardous decomposition products None known under normal conditions of use. Stable at the recommended
Storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes according to Regulation (EC) No. 1272/2008

Information on likely routes of exposure

Product information

Inhale	Intentional misuse through concentration and inhalation of the ingredients can occur be harmful or fatal. Specific experimental data for the substance or mixture are not available. Aspiration into the lungs can cause serious lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. Can become one Cause irritation of the respiratory tract.
Eye contact	Based on the available data, the classification criteria are not met. Specific Test data for the substance or mixture are not available. May cause irritation cause. Causes serious eye irritation. (based on components). Can Cause redness, itching and pain.
Skin contact	Repeated exposure may cause dry or cracked skin. Specific Test data for the substance or mixture are not available. Caused Skin irritation. (based on components).
Swallowed	Specific test data for the substance or mixture are not available. At There is a risk of aspiration if swallowed. May cause lung damage if swallowed cause. Aspiration can cause pulmonary edema and pneumonitis. Can can be fatal if swallowed and enters the respiratory tract. May be swallowed gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological properties

Symptoms	Difficulty breathing. Coughing and/or wheezing. Lightheadedness. Redness. May cause redness and cause watery eyes.
----------	---

Acute toxicity

Toxicity index

The following ATE values were calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	13,211.30 mg/kg
ATEmix (Inhale from gas)	>20000 ppm
ATEmix (Inhale from dust/fog)	89.20 mg/L
ATEmix (Inhale from steaming)	73.00 mg/L

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025

Revised on Dec 15, 2025
Revision number 1.04

Information about the components

Chemical Designation	LD50 orally	LD50 dermal	LC50 Inhale
Xylene	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	4 hours = 5000 ppm (Rattus) 4 hours
n-butane	-	-	=658 g/m3 (Rattus) 4 hours
Ethylbenzene	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.6 mg/L (Rattus) 4 hours
hydrocarbons, C10-C13, n-Alkane, isoalkanes, Cycloalkanes, <2% aromatics	DL50 >5000 mg/kg (Rattus)	DL50 >2000 mg/kg (Oryctolagus cuniculus)	LC50 (8h) >5000 mg/m3 advice - Vapors
Isobutane	-	-	=658 mg/L (Rattus) 4 hours

Delayed and immediate effects as well as chronic effects after short or long duration

Exposure

Corrosion/irritation to skin

Classification is based on the data available for the ingredients. Caused Skin irritation.

Heaviness

Classification is based on the data available for the ingredients. Causes seriousness

Eye damage/eye irritation Eye irritation.

Respiratory sensitization or the skin

Based on the available data, the classification criteria are not met.

Germ cell mutagenicity

Based on the available data, the classification criteria are not met.

Chemical name	European Union
Xylene	Muta. 1B
Ethylbenzene	Muta. 1B

Carcinogenicity

Based on the available data, the classification criteria are not met.

Chemical name	European Union
Xylene	Carc. 1B
Ethylbenzene	Carc. 1B

Reproductive toxicity

Based on the available data, the classification criteria are not met.

STOT - single exposure

Based on the available data, the classification criteria are not met.

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025
STOT - repeated exposure
Danger of aspiration

Revised on Dec 15, 2025
Revision number 1.04

May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

11.2. Information about other hazards

11.2.1. Endocrine disrupting properties

Endocrine disruptive properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information is available.

SECTION 12: Ecological information

12.1. toxicity

Ecotoxicity Based on the available data, the classification criteria are not met.

Chemical Designation	Algae/water replenishment	Fish	Toxicity opposite microorganisms	Crustaceans	M factor	M factor (long term)
Xylene 1330-20-7	EC50: =11mg/L (72h, Pseudokirchneriella subcapitata)	2.661 - 4.093 mg/L (Oncorhynchus mykiss static)	-	EC50 48h = 3.82 mg/L (Daphnia magna)		
Ethylbenzene 100-41-4	EC50 72h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)		
hydrocarbons, C10-C13, n-Alkane, isoalkanes, Cycloalkanes, <2% Aromatics RR-113412-9	LEO (72h) =1000 mg/L Algae (Pseudokirchneriella subcapitata)	LLO (96h) =1000 mg/L (Oncorhynchus mykiss)	-	LEO (48h) =1000 mg/L (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information is available.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, < 2% aromatics (RR-113412-9)			
Method	Exposure time	Value	Results
OECD test no. 301F: Lightweight biodegradability: Manometric respiration test (TG 301 F)	28 days		80% Slightly organic degradable

12.3. Bioaccumulative potential

Bioaccumulation

Information about the components

Chemical name	distribution coefficient
Xylene	3.15
n-butane	2.31
Ethylbenzene	3.6
Isobutane	2.8

12.4. Mobility in the ground

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025
Mobility in the ground

No information is available.

Revised on Dec 15, 2025
Revision number 1.04

12.5. Results of the PBT and vPvB assessment

Results of the PBT and vPvB rating Based on the available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment results
Xylene	No PBT/vPvB
n-butane	No PBT/vPvB
Ethylbenzene	No PBT/vPvB
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, < 2% aromatics	No PBT/vPvB
Isobutane	No PBT/vPvB

12.6. Endocrine disruptive properties Endocrine disruptive properties

Environmental endocrine disruption Based on available data, the classification criteria are not met.

12.7. Other adverse effects Other adverse effects

Other adverse effects No information is available.
PMT or vPvM properties Based on the available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment processes

Waste from residues/not products used Dispose of contents/containers in accordance with local, regional, national and comply with international regulations. Must not be released into the environment.
Dispose of in accordance with local regulations. Waste in accordance with environmental regulations dispose.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Containers do not cutting, piercing, or welding.

European waste catalogue 16 05 04* gases containing dangerous substances in pressure vessels (including halons)
15 01 04 Metal packaging

Other information Waste keys must be specified by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number UN1950

14.2 Proper UN shipping name COMPRESSED GAS PACKINGS

14.3 Transport hazard classes 2

Markings 2.1

14.4 Packaging group Not regulated

Description UN1950, COMPRESSED GAS PACKINGS, 2, (D)

14.5 Environmental Hazards No

14.6 Special precautions for the user

Special regulations 190, 327, 344, 625

Classification code 5F

Tunnel restriction code (D)

Limited Quantity (LQ) 1 L

IMDG

14.1 UN number or ID number UN1950

14.2 Proper COMPRESSED GAS PACKINGS

SAFETY DATA SHEET

M-ONE UBS SPRAY

Replaces date 05-Aug-2025

UN shipping name

Revised on Dec 15, 2025

Revision number 1.04

14.3 Transport hazard classes 2.1

14.4 Packaging group

Not regulated

Description

UN1950, COMPRESSED GAS PACKINGS, 2.1

14.5 Marine pollutant

NP

14.6 Special precautions for the user · special regulations

63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ)

Lake SP277

EmS no.

F-D, S-U

14.7 Transport in bulk

dem sea route according to IMO-instruments

Transport in bulk in accordance with Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950

14.2 Proper

AEROSOLS, FLAMMABLE

UN shipping name

14.3 Transport hazard classes

2.1

14.4 Packaging group

Not regulated

Description

UN1950, AEROSOLS, FLAMMABLE, 2.1

14.5 Environmental Hazards

No

14.6 Special precautions for the user ·

Special regulations

A145, A167, A802

Limited Quantity (LQ)

30kg G

ERG code

10L

SECTION 15: Legislation

15.1. Safety, health and environmental regulations/legislation specific to the substance or the mixture

European Union

Directive on the Registration, Evaluation and Authorization of Chemicals (REACH) (EC 1907/2006)

SVHC: Substance of very high concern for approval:

This product does not contain substances of very high concern (SVHC) on the candidate list at a concentration of $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII Restrictions on Use

This product does not contain any restricted substances (Regulation (EC)(No. 1907/2006, (REACH), appendix. XVII).

Substance that is subject to approval requirements according to REACH, Annex XIV

This product does not contain any substances that are subject to authorization (Regulation (EC)(No. 1907/2006, (REACH), Annex XIV)

Requirements for issuing export licenses

This product does not contain any substances specified in Regulation (EC) No. 649/2012 of the European Parliament and the Council on the export and import of dangerous chemicals are above the threshold that requires labeling of Regulation (EC) No. 1272/2008. Therefore, this product is not subject to prior consent requirements Notification.

Category for dangerous substances according to the Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Regulation on ozone-depleting substances (EC) No. 2024/590

Not applicable.

SAFETY DATA SHEET

M-ONE UBS SPRAY
Replaces date 05-Aug-2025
Persistent organic pollutants
Not applicable

Revised on Dec 15, 2025
Revision number 1.04

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on
Marketing and use of explosives precursors Not applicable

Regulations on drug precursors (EC) No. 111/2005 (export) and 273/2004 (domestic trade) This
Product does not contain any substances that are listed as drug precursors.

National regulations

Deutschland
Industrial Safety Ordinance (BetrSichV, Germany)
Not a flammable liquid according to BetrSichV

Water hazard class (WGK) clearly hazardous to water (WGK 2)

Storage class according to TRGS 510 Storage class 2B: Aerosols

Swiss VOC (%) 48.9

15.2. Chemical safety assessment

Chemical safety assessments have been carried out for substances > 10 t/a by the respective REACH registrants; for that
No chemical safety assessment has been carried out on this mixture

SECTION 16: Other information

Key or legend for abbreviations and acronyms used in the safety data sheet

Full text of all hazard and/or precautionary statements referenced in Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking
H220 - Extremely flammable gas
H225 - Highly flammable liquid and vapor
H226 - Flammable liquid and vapor
H280 - Contains gas under pressure; can explode if heated
H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

Notes on the identification, classification and labeling of substances

Note C - Some organic substances can exist either in a well-defined isomeric form or as a mixture
several isomers are placed on the market. In this case, the supplier must indicate on the identification label whether
it is a specific isomer or a mixture of isomers
Note U - When placed on the market, the gases must be classified as 'gases under pressure' in one of the groups of compressed gases,
of liquefied gases, frozen gases or dissolved gases. The assignment to a group
depends on the physical state in which the gas is packaged and must therefore be decided on a case-by-case basis.
The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.).
Aerosols may not be classified as gases under pressure (see Annex I Part 2 Section 2.3.2.1 Note 2)

SVHC: Substance of very high concern for approval:
PBT: Persistent, bioaccumulative and toxic (PBT) substances
vPvB: Very persistent and very bioaccumulative (vPvB) substances STOT
RE: Specific Target Organ Toxicity - Repeated Exposure

SAFETY DATA SHEET

M-ONE UBS SPRAY

Replaces date 05-Aug-2025

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalog

Revised on Dec 15, 2025

Revision number 1.04

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IATA:

International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG:

Sea transport

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time weighted average)	STEL	STEL (Short Term Exposure Limit, value for short-term exposure)
AGW	Occupational limit value	BGW	Biological limit
limit	Maximum limit	Sk*	Skin naming

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapors	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Corrosion/irritation to skin	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitization	Calculation method
Skin sensitization	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Danger of aspiration	Calculation method
Ozone	Calculation method
Flammable aerosol	Based on test data

Authoritative literature references and sources for the data used to prepare the safety data sheet

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Risk Assessment Committee (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

US Environmental Protection Agency

Guideline values for acute exposure (Acute Exposure Guideline Level(s), AEGL(s))

International Unified Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health, cf. Federal Institute for Occupational Safety and Health)

International Organization for Economic Cooperation and Development (International Organization for Economic

Co-operation and Development, OECD) publications on the environment, health and safety

International Organization for Economic Cooperation and Development (International Organization for Economic

Co-operation and Development (OECD) program for high-volume chemicals

International Organization for Economic Cooperation and Development (International Organization for Economic

Co-operation and Development, OECD) Screening Information Data Set

Manufactured by Product safety

Revised on 15-Dec-2025

Note on revision SDS sections updated 2

Training Notes No information is available

Further information No information is available

SAFETY DATA SHEET

M-ONE UBS SPRAY

Replaces date 05-Aug-2025

Safety data sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878 and Regulation (EC) No. 1272/2008

Revised on Dec 15, 2025

Revision number 1.04

version

Disclaimer

The information provided in this safety data sheet is as of the date of publication accurate to the best of our knowledge. The information is for guidance only for safe handling, Use, processing, storage, transport, disposal and in the event of spillage are determined and apply not as a guarantee and quality specifications. This information refers only to the explicit specified material and may when used with other materials or other processes for such Material is not valid unless specified in the text.

End of the safety data sheet