



PREMIUM SILIKON

Acetoxy silicone for building, glazing and sanitary joints



PRODUCT DESCRIPTION

M ONE PREMIUM SILIKON is a versatile acetoxy silicone sealant, which cures under influence of humidity to form a durable elastic rubber. The product is excellent UV and weather resistant.

KEY BENEFITS

- Versatile sealant
- Mold resistant- Good resistant to UV, water and weather

APPLICATIONS

M ONE PREMIUM SILIKON has been especially developed for connection joints in buildings, glazing systems (1), kitchens and bathrooms.

Remark (1):

Compatibility with edge seals of insulation glass cannot be guaranteed, as the compositions of sealant for the edges of insulation glass can be different or changed by the producer of insulation glass. Advices concerning the compatibility of glazing sealants to the edge seals of insulation glass are based on experience and therefore not guaranteed.

DIRECTION FOR USE

A joint with the correct dimensions is able to absorb movements between building materials. The joint depth should always be in the correct relationship of the joint width. A general rule is the ratio of joint depth to the width of the joint with a joint width till 10 mm is 1:1, with a minimum of 5 mm in width and depth. For joints wider than 10 mm, the depth is the width divided by 3 plus 6 mm. For more information see the Technical Bulletin Joint Dimensions in the Knowledge Base on our website www.denbraven.com.

TECHNICAL SPECIFICATIONS

100% Modulus	DIN 53504 S2	0,28 N/mm ²
Application Temperature		+5°C till +40°C
Base		Silicone
Application Rate	@ Ø3 mm/6,3 bar	900 g/min
Curing Time	@ +23°C/50% RH	2 mm/24 hours
Density	ISO 1183-1	0.97 g/ml
Elongation At Break	DIN 53504 S2	410%
Frost Resistance		till -15°C
Shore A Hardness	DIN 53505	11
Skin Formation	+23°C/50% (DBTM 16)	10-12 minutes
Temperature Resistance		-40°C till +120°C

Tensile Strength	DIN 53504 S2	0.75 N/mm ²
Viscosity		75

These are typical values

LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates.
- Not suitable for applications on concrete, marble, lead, copper and galvanized steel.

SURFACE PREPARATIONS AND FINISHING

Application temperature: +5°C to +40°C (environment and substrate).

Surfaces must be dry, clean and solid. Clean surfaces with Cleaner. M ONE PREMIUM SILIKON adheres perfectly without the use of a primer to most non porous substrates. Strong porous surfaces to be pre-treated with Primer Universal. Always test adhesion prior to application. Use Finisher to smooth the joint.

PAINTABILITY

M ONE PREMIUM SILIKON is not paintable. It is recommended to cover the edges of the joint with masking tape in order to prevent that surfaces which remain to be painted will be contaminated with silicone.

CLEANING

Uncured material and tools can be cleaned by using Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Wipes.

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life up to 18 months from production date, stored in a dry place.

CERTIFICATIONS

- A+ French VOC Regulation
- EN 15651-2: G-CC
- EN 15651-3: S S1
- EN 15651-1: F-EXT-INT-CC

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

M ONE warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of M ONE. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without

M ONE written consent. The technical information in this document serves as an indication and is non-exhaustive. M ONE is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. M ONE reserves the right to amend the wording of this document. M ONE cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.