
When Should LLMs Trust Retrieval?

Bayes-Optimal Knowledge Arbitration under Conflict

Anonymous Authors

Abstract

A retrieval-augmented LLM has to arbitrate three voices that often disagree: a parametric prior fixed at training, a retrieved passage, and the model’s own chain of thought. Production systems use hand-tuned rules for this; the choice silently fixes hallucination rate and calibration on every slice where the sources disagree, and no principled account has existed. We provide one in three theorems and two inference-time interventions that fall out of a single free-energy functional. **(CT1)** Inside the log-linear family the Bayes-optimal combiner is the reliability-weighted geometric mixture $\hat{p}_{w^*} \propto p_\theta^{1-w^*} p_{\text{ctx}}^{w^*}$ with $w^* = \mathbb{E}[r \mid q, c]$. It is the unique Gibbs minimizer of an arbitration–tempering free energy and the unique combiner under four classical axioms; CAD, AdaCAD, CoCoA, Astute, Self-RAG, and JuICE all collapse to special cases, and the rule carries a TV-perturbation envelope on regret. **(CT2)** The chain of thought reads as an endogenous generalized-Bayes update on the same functional, converging to a Berk–Nash fixed point inside an η -linear sandwich whose safe learning rate shrinks under conflict. **(CT3)** When the post-trace distribution overshoots, the Brier improvement under η -tempering is closed-form, $\Delta\text{Brier}(\eta^*) = (1-\eta^*)^2 V_{\text{post}} + O((1-\eta^*)^3)$, giving safe-Bayes an operational reading of when ordinary temperature scaling is justified. BAYESARBITER beats the strongest heuristic by +0.083 in regret on 23/25 cells (e-value 2806); powered $n=210$ head-to-heads against AdaCAD, CoCoA, Astute RAG, and Self-RAG land at +0.064/ +0.043/ +0.032/ +0.022, every CI strictly above zero (AdaCAD CI [0.060, 0.068]). The spectral diagnostic predicts trace decay $\text{TV}(p_t, p_K)$ within ± 0.07 across 12 cells over 3 families ($r=0.997$). A matched-base DPO-vs-GRPO contrast at 8B isolates a +0.344 ECE gap as RL-induced; on the RLCR-trained 8B worst cell, stacking η -tempering moves accuracy from 0.063 to 0.531, ECE from 0.904 to 0.431, and Brier from 0.886 to 0.415. Both interventions ship as a single inference-time line over a standard decoder, with no retraining.

1 Introduction

A 2023-trained language model knows Elon Musk runs Twitter. But a 2024 article retrieved by RAG names Linda Yaccarino as CEO of X. How is the model supposed to choose?

Such conflict is the rule, not the exception, in retrieval-augmented systems. The model carries a parametric prior $p_\theta(y \mid q)$ from training, conditions on a retrieved context $p_{\text{ctx}}(y \mid q, c)$, and, if it produces a chain of thought, listens to itself across K reasoning steps before answering. Any of those voices can be wrong, and they often disagree. Whatever rule the system uses to arbitrate fires on every query and silently fixes hallucination rate, calibration on conflict slices, and worst-case behavior under poisoned or stale retrieval.

The rule is silent in deployment. It picks a source and ships the answer; the conflict never surfaces, and the user has no signal that a choice was made. Arbitration is the chokepoint where training-cutoff lag and retrieval drift collapse into a single decision per query. A medical assistant trained before a label change either reads the updated dose off the chart or quietly defaults to the older one. Both




Figure 1: The BAYESARBITER pipeline. Three inputs (q , c , trace $z_{1:K}$) produce three distributions (p_{θ} , p_{ctx} , $p(\cdot | \text{trace})$). A reliability plug-in $\hat{w}(c) = \hat{\mathbb{E}}[r | s(q, c)]$ drives the geometric mixture (Section 3.1); the post-trace distribution is η -tempered with closed-form Brier improvement (Theorem 4).

choices ship; only one is right. The same scenario plays out on legal precedent, financial disclosures, and any domain where the world updates faster than the next pretraining run.

Today that rule is set by hand. Production RAG systems trust retrieval unconditionally, trust the parametric model unconditionally, or interpolate with tuned thresholds and learned controllers [3, 40, 73]. Decoder-level methods like Context-Aware Decoding [59] and its variants AdaCAD [67] and CoCoA [30] sharpen the heuristic but stay heuristic. The calibration literature on reasoning models has split into camps that look mutually contradictory: longer chain-of-thought helps calibration on standard QA [74] and hurts it on harder or misspecified tasks [14, 22].

None of these approaches is derived from a posterior over how reliable the context actually is. CAD and AdaCAD weight the context-conditional against the prior with fixed or first-order-corrected exponents the authors do not interpret as a Bayes-optimal action; CoCoA averages reliability proxies without a consistency guarantee. Survey work [72] flags that fixed trust in either source is suboptimal and stops there. The calibration tension shares this root cause: no theory tells the practitioner which regime they are in, so the same chain-of-thought scaling argument supports both “reasoning helps calibration” and “reasoning hurts calibration” depending on which subset of the literature is consulted.

We give a principled account. BAYESARBITER (Figure 1) treats arbitration as parameter estimation. The latent variable is context reliability $r \in [0, 1]$, with prior $\pi(r)$ informed by observable signals such as BM25, entity popularity, and semantic entropy. Four classical axioms pin the unique combiner to the geometric mixture $p_{\theta}^{1-w^*} p_{ctx}^{w^*}$ with $w^* = \mathbb{E}[r | q, c]$. CAD, AdaCAD, and CoCoA fall out as approximations of this rule. For the chain of thought, the trace itself reads as endogenous generalized-Bayes evidence, and the local convergence rate at the fixed point ties an empirically observable spectral diagnostic on logged trajectories to the per-cell saturation slope. When the post-trace distribution overshoots, inference-time tempering (η -Gibbs at readout) reverses it, with a closed-form Brier improvement. Both interventions ship at inference time over a standard RAG decoder.

BAYESARBITER clears zero against 7 of 10 named baselines on the 25-cell spotlight, including a +0.083 advantage over the heuristic-adaptive primary on 23/25 cells (e-value 2806, CI [0.037, 0.111]); the four tightest competitors (AdaCAD, CoCoA, Astute RAG, Self-RAG) clear zero on the powered $n=210$ matched design at +0.064/ +0.043/ +0.032/ +0.022, AdaCAD’s CI [0.060, 0.068] the tightest of the four. The trajectory diagnostic predicts trace decay within ± 0.07 across 12 cells over three model families ($r=0.997$). On the load-bearing RLCR-trained 8B worst cell (ConflictBank, $K=1024$), η -tempering moves accuracy from 0.063 to 0.531, ECE from 0.904 to 0.431, and Brier from 0.886 to 0.415; on a standalone R1-14B cell at the same benchmark, η -tempering alone drops Brier from 0.903 to 0.505. A matched-base RL contrast at a fixed Llama-3.1-8B base separates conflict-slice ECE by +0.344 between DPO and GRPO; the Llama lineage and a cross-family Phi-3 replication reproduce the direction.

Our contribution is three theorems on a single free-energy functional $\mathcal{F}$, two inference-time interventions, and a unification of the existing decoder literature.

CT1, Bayes-optimal arbitration (Theorem 1). The geometric mixture $p \propto p_{\theta}^{1-w} p_{ctx}^w p_K^{\eta}$ with $w^* = \mathbb{E}[r | s]$ is the unique Gibbs minimizer of $\mathcal{F}[p] = \mathbb{E}_p[E_{w,\eta}] - H[p]$ and the unique combiner under four classical axioms. CAD, AdaCAD, CoCoA, Astute, Self-RAG, and JuICE all collapse to special cases on this exponent axis (Section 3.1). A four-channel TV-perturbation envelope absorbs model error, signal noise, finite-sample variance, and adversarial poisoning into one regret inequality.

Table 1: Results indexed by theorem. Each row is a body claim, organized by which CT it tests; pointer in App. G.1.

Theorem	Test	Result	App.
CT1	75-cell spotlight + powered $n=210$ vs. AdaCAD/CoCoA/Astute/Self-RAG	Spotlight clears 0 on 7/10 baselines; powered +0.064/ +0.043/ +0.032/ +0.022 adds AdaCAD plus the three remaining adaptives	H.2
CT1	Boundary $w_0 \in \{0, 1\}$ + synthetic $\sqrt{n}$ -audit	Collapses ~ 2 orders; $R^2=0.998$ at $n=2048$	H.9
CT1 (env.)	Poisoned-context, reliability-noise, multi-doc envelopes	Within predicted bounds across 3 panels	I.1
CT2	$\hat{\rho}^*$ predicts $\text{TV}(p_t, p_K)$ on 12 cells / 3 families	± 0.07 MAE, $r=0.997$; held-out ± 0.08	E.4
CT3	Matched SFT/DPO/GRPO, Llama lineage + Phi-3, Mistral, Gemma	Llama-8B +0.344; DeepSeek-70B +0.388; DeepSeek-8B +0.053; Phi-3 +0.207 / +0.003 / +0.209; Mistral-7B SFT +0.164; Gemma-2-9B SFT +0.103	H.1.9
CT3 (η)	η -tempering; RLCR+ η stack at 8B	RLCR+ η : Acc 0.063 $\rightarrow$ 0.531, ECE 0.904 $\rightarrow$ 0.431, Brier 0.886 $\rightarrow$ 0.415; pooled +0.043 Brier	H.1.8
Frontier	GPT-4o-mini / Claude / Gemini via top- k logprobs	+0.055 to +0.060 regret advantage	L.1
Held-out	ClashEval + RAMDocs replication	Both predicted directions confirmed on held-out splits	H.19

CT2, trajectory envelope on $\mathcal{F}$ (Theorem 3). The chain-of-thought iterate converges to a Berk–Nash fixed point at geometric rate ρ^* inside an η -linear sandwich, with phase boundary $\eta_c = 1/D^*$. The rate is observable: $\hat{\rho}^*$ from logged trajectories predicts $\text{TV}(p_t, p_K)$ decay to within ± 0.07 .

CT3, closed-form η -tempering (Theorem 4). $\Delta\text{Brier}(\eta^*) = (1-\eta^*)^2 V_{\text{post}} + O((1-\eta^*)^3)$. Calibrated temperature scaling [21] acquires a safe-Bayes derivation [7, 20] that identifies when $\eta^* < 1$ is the right call.

Extensions in App. H.18: K -hop multiplicative composition (Theorem E.19) and causal doubly-robust identification of w^* (Theorem E.20).

Arbitration was the last hand-tuned step in retrieval-augmented LLM pipelines, and a single functional now gives the optimal combiner, the trajectory envelope, and the closed-form deployment scalar in one place. Six published decoders collapse to special cases on the exponent axis of that functional, and the two interventions ship as one inference-time line over a standard RAG decoder. On the worst conflict cell observed (RLCR-trained 8B), η -tempering raises accuracy from 6.3% to 53.1% and Brier from 0.886 to 0.415 without a gradient step. The matched-base GRPO-vs-DPO contrast at +0.344 ECE, replicated across five families, is the first causal evidence that a specific post-training recipe induces context-overtrust.

2 Related Work

The conflict framing originates with Longpre et al. [39]; surveys carve sub-types [71, 72], and benchmarks span synthetic counter-memory [61], real Wikipedia contradictions [24], temporal drift [41], and popularity stratification [40]. Adaptive RAG variants threshold on popularity, learn when to retrieve [3, 27], correct retrieval errors [73], or debate documents [66, 68]. None derives the trust schedule from a posterior over reliability; survey work flags fixed-trust as suboptimal but stops short of the optimum, which we identify as $w^* = \mathbb{E}[r | s]$ (Section 3.1).

At the decoder level, CAD [59], AdaCAD [67], CoCoA [30], NWCAD [29], JuICE [11], and contrastive decoding [37] reweight contextual logits with hand-crafted signals. Each sits at a fixed point on the same exponent axis as our minimizer (Section 3.1); none is interpreted by its authors as Bayes-optimal arbitration, and none carries a perturbation envelope or a closed-form readout-time correction.

The reasoning-time calibration literature reads as mutually contradictory: Kadavath et al. [28], Yoon et al. [74] report calibrated reasoning on standard QA, while Bereket and Leskovec [5], Damani et al. [14], Halawi et al. [22], Lacombe et al. [34], Sun et al. [62], Welch et al. [69] document overthinking, implicit answer-conditioning, and RL-induced overconfidence on knowledge-intensive tasks. The split has one root cause: no theory tells the practitioner whether the cell sits below or above the safe-Bayes learning rate. Section 3.2 reconciles the two camps and Section 3.2 gives the dimensional threshold $\eta_c = 1/D^*$. RLHF [10, 48], DPO [52], and GRPO [58] shape the post-trained distribution

differently [49]; our matched-base contrast at fixed Llama-3.1-8B base isolates the recipe-level calibration effect from confounders. Weight-editing [43, 44] is an orthogonal complement.

On the opinion-pool axiomatics side, McConway [42] and Genest and Zidek [19] characterize geometric pooling under marginalization and external Bayesianity, both of which pin w to a constant. Section 3.1 relaxes EB to log-likelihood-ratio invariance, which permits context-dependent w , exactly what RAG arbitration needs. We transport classical results to the LLM CoT setting without reproving them: Berk’s KL-projection concentration [6], Kleijn–van der Vaart [31], Bissiri–Holmes–Walker generalized Bayes [7], Grünwald–van Ommen safe-Bayes [20], and endogenous-evidence Berk–Nash dynamics [17, 18]; the spectral diagnostic in CT2 is the first observable rate in this line.

3 Setup and Theory

A query q with retrieved context c has a true answer $y^* \in \mathcal{Y}$ drawn from $\mathbb{P}^*$, where $\mathcal{Y}$ is the (closed) candidate set. The LLM exposes the closed-book softmax $p_\theta(y | q)$ and the context-conditioned softmax $p_{\text{ctx}}(y | q, c)$, with top-1 modes $y_{\text{par}} := \arg \max_y p_\theta$ and $y_{\text{ctx}} := \arg \max_y p_{\text{ctx}}$. Latent reliability $r := \mathbb{P}(y^* = y_{\text{ctx}} | q, c) \in [0, 1]$ has prior $\pi(r)$ informed by observable signals $s(q, c)$ (BM25, popularity, semantic entropy [33], contradiction type). The decision maker chooses $\hat{p} \in \Delta(\mathcal{Y})$; risk is $R(\hat{p}) = \mathbb{E}_{q,c,y^*}[S(\hat{p}, y^*)]$ for a strictly proper scoring rule S (log loss and Brier). **Assumptions** (App. A.1, A.2): (A1) $y^* \perp c | (q, r)$; (A2) the conditional answer model is log-linear. All theorems operate under (A1)–(A2).

Three theorems sit on the same free-energy functional $\mathcal{F}$ on $\Delta(\mathcal{Y})$: **CT1** (Gibbs minimizer + perturbation envelope), **CT2** (η -linear sandwich on chain-of-thought convergence), **CT3** (closed-form Brier improvement under η -tempering). Variational free energy [26, 65] and the geometric opinion pool [19, 23, 42] are classical; the contribution is the specific energy whose Gibbs minimizer reads $w^* = \mathbb{E}[r | s]$ and unifies arbitration, trace-tempering, and perturbation response inside one functional.

3.1 CT1 Bayes-optimal arbitration and perturbation envelope

Let $E_{w,\eta}(y) := -(1-w) \log p_\theta(y | q) - w \log p_{\text{ctx}}(y | q, c) - \eta \log p_K(y | q, c, \text{trace})$ and $\mathcal{F}[p; w, \eta] := \mathbb{E}_p[E_{w,\eta}] - H[p]$.

Theorem 1 (CT1: Free-energy characterization). *The unique Gibbs minimizer of $\mathcal{F}$ on $\Delta^\circ(\mathcal{Y})$ is*

$$p_{w,\eta}^*(y) \propto p_\theta(y)^{1-w} p_{\text{ctx}}(y)^w p_K(y)^\eta, \quad (1)$$

and under (A1)–(A2), the choice $w^* = \mathbb{E}[r | s]$ is Bayes-optimal for log loss.

Corollary (Section 3.1, App. C.1). CAD, AdaCAD, CoCoA, Astute RAG, Self-RAG, and JuICE collapse to fixed points on the exponent axis of (1); every alternative is strictly suboptimal away from $w^* = \mathbb{E}[r | s]$.

What is new. CT1 supplies the first principled answer to which arbitration rule a RAG stack should use, and it does so by subsuming the existing decoder literature under one Bayes-optimal target. Six independently-published methods now share a common origin and a common improvement direction, $\hat{w} \rightarrow \mathbb{E}[r | s]$.

Theorem 2 (CT1’: Perturbation envelope). *With $\sigma_r^2 := \mathbb{E}[\text{Var}(r | s)]$, V the log-LR variance under p^* , V_{max} its sup, L_w the plug-in Lipschitz constant, k the top- k effective support, the geometric-mixture regret under TV- ε model and TV- δ signal perturbation obeys*

$$R_{\varepsilon,\delta}(\hat{p}_{\hat{w}}) - R_0(\hat{p}^*) \leq \underbrace{\frac{1}{2}\sigma_r^2 V}_{\text{intrinsic}} + \underbrace{4\varepsilon \log k}_{\text{model TV}} + \underbrace{2L_w \delta V_{\text{max}}}_{\text{signal TV}} + \underbrace{O(n^{-1/2})}_{\text{finite-}n}. \quad (2)$$

The intrinsic and signal-TV terms admit matching $\Omega(\sigma_r^2 V)$ and $\Omega(\delta V_{\text{max}})$ Le Cam lower bounds (Section 3.1); the model-TV term is Pinsker-tight in $\log k$.

What is new. The four perturbation channels (model error, signal noise, finite-sample variance, adversarial poisoning) have to date been studied separately or under restrictive sub-cases. CT1’ collapses them into one inequality with three of the four bounds matched up to constants, giving the practitioner one expression to read off worst-case regret under any combination of perturbations.

3.2 CT2 trajectory envelope on $\mathcal{F}$

The chain-of-thought trace $z_{1:K}$ induces a generalized-Bayes update [7] that equals mirror descent on $\mathcal{F}$ with $D_\Phi = \text{KL}$ (Lemma E.19):

$$p_{t+1}(y \mid q, c) \propto p_t(y \mid q, c) \exp(-\eta \ell_t(y; q, c, z_t)), \quad z_t \sim \mu(\cdot \mid p_t, q, c). \quad (3)$$

With $D^* := \sup_y |\log(p_{\text{ctx}}/p_\theta)|$ the conflict diameter, $\rho^* := \rho(I - \eta \nabla^2 \mathcal{F}[p^*])$ the linearized spectral radius, and the *stable-answer subset* the slice with argmax-invariant CoT rollouts:

Theorem 3 (CT2: Trajectory envelope). *On the stable-answer subset, the iterate (3) converges to a hyperbolic Berk–Nash fixed point p^* [17, 18] at geometric rate ρ^* satisfying*

$$\underbrace{1 - \frac{C_\pi \eta}{D^{*2} |\mathcal{Y}|}}_{\text{lower}} \leq \rho^* \leq \underbrace{1 - c' \eta \text{Var}_{p^*}(s_t)}_{\text{upper}}, \quad (4)$$

both sides η -linear, with phase boundary $\eta_c = 1/D^$ separating contractive from overshoot regimes; consequently $\text{TV}(p_t, p^*) \leq C \rho^{*t}$ for $t \geq T_0$.*

Corollary (Section 3.2, App. E.1). For $\eta < \eta_c$ the iterate is contractive; for $\eta > \eta_c$ it overshoots and V_{post} stays bounded away from zero, the regime CT3 corrects.

The rate is observable: a ridge-LS estimate $\hat{\rho}^*$ on consecutive trace distributions predicts $\text{TV}(p_t, p_K)$ decay within ± 0.07 across 12 cells over 3 model families (pooled $r = 0.997$, held-out ± 0.08 ; Table E.7).

What is new. $\hat{\rho}^*$ is the first observable spectral diagnostic in the misspecified-Bayes line of work. It ties trajectory-side dynamics to a per-cell scalar a practitioner can compute from logged traces alone, without re-running the model. The dimensional threshold $\eta_c = 1/D^*$ converts the “reasoning helps vs. hurts calibration” debate into a falsifiable phase boundary.

3.3 CT3 closed-form η -tempering at readout

Theorem 4 (CT3: Closed-form Brier improvement under η -tempering). *Let $\hat{p}_\eta \propto p_K^\eta$ and assume the cell is non-degenerate ($p_K(y^*) \neq 1/|\mathcal{Y}|$). The Brier improvement at the Brier-optimal $\eta^* \in [0, 1]$ is*

$$\Delta \text{Brier}(\eta^*) = (1 - \eta^*)^2 V_{\text{post}} + O((1 - \eta^*)^3), \quad (5)$$

where $V_{\text{post}} := \text{Var}_{p_K}[\mathbf{1}\{Y = y^\}]$.*

Corollary (Section 3.3, App. F.1). The Murphy split has $\langle \nabla_\eta \text{REL}, \nabla_\eta \text{RES} \rangle_{\text{Brier}} = 0$ at η^* , so REL and RES decompose orthogonally.

As a procedure this is calibrated temperature scaling [21]; safe-Bayes [7, 20] tells the practitioner when $\eta^* < 1$ via CT2’s safe-rate descent.

What is new. The closed form converts a widely-used empirical recipe (temperature scaling) into a quantity the practitioner can predict from the post-trace variance alone. Combined with CT2’s safe-rate condition, the result answers when $\eta^* < 1$ is the right call without requiring a held-out sweep, which is the unresolved question in the calibration literature on long chain-of-thought.

Two extensions live in App. H.18: K -hop multiplicative composition (Theorem E.19) and doubly-robust causal identification of w^* (Theorem E.20).

4 Experiments

Three theorems, three things to falsify. CT1 says one specific arbitration rule is optimal and the rest of the literature lives on its exponent axis. CT2 says the chain-of-thought decay rate is something you can read off a logged trajectory. CT3 says the readout-time fix has a closed-form payoff. We put each one in front of every comparator we could find and watch where it bends. The headline: BAYESARBITER is the only Gibbs minimizer of the underlying free energy, and the six published decoders that sit alongside it on that axis (Table 2) lose by margins the theory predicts. On the worst cell we observed, an RLCR-trained 8B that flips into post-trace collapse, η -tempering pulls accuracy from 6.3% back to 53.1% without retraining the model.

What we ran, in one breath: 12 conflict and open-QA benchmarks, 13 model checkpoints from 7B to 70B across seven families plus three frontier APIs, 15 baselines, 3 seeds. The CT1/CT2 spotlight is a $5 \times 5 \times 4$ matrix; CT3 runs a five-benchmark size-scaling sweep; the matched-base contrast is a shared LoRA inventory with per-family overrides. Inference for everyone: paired bootstrap (10,000 resamples, seed 42), one-sided sign tests, fixed- λ e-values [53, 56]. The full inventory (per-matrix configurations, training defaults, family overrides, evaluation runner, compute footprint) lives in App. G.3; prompts and decoding hyperparameters in App. G.2.

4.1 CT1 arbitration rule and perturbation envelope

Table 2: Six published decoders sit on the CT1 exponent axis. Each row shows the geometric exponent w chosen, its theory status against the Bayes optimum $w^* = \mathbb{E}[r | s]$, and mean regret on the 25-cell conflict spotlight (lower is better; oracle 0). Only BayesArbiter is the Gibbs minimizer of $\mathcal{F}$; every other method is a fixed point or first-order approximation on the same axis.

Method	Reliability weight	Theory status	Regret↓
Always parametric	$w = 0$ (fixed)	CT1 boundary; minimax-suboptimal	+5.242
Always context	$w = 1$ (fixed)	CT1 boundary; minimax-suboptimal	+7.994
Fixed 50/50	$w = 0.5$ (fixed)	class-III suboptimal	+0.404
CAD [59]	$w = 2$ (analytic cont.)	over-amplification of $\log p_{\text{ctx}}/p_\theta$	−0.079
AdaCAD [67]	Laplace of $\mathbb{E}[r c]$	first-order approx., Beta prior	−0.106
CoCoA [30]	averaged proxies	no consistency guarantee for $\mathbb{E}[r s]$	−0.128
BayesArbiter (CT1)	$w^* = \mathbb{E}[r s]$	Gibbs minimizer of $\mathcal{F}$	−0.172

BAYESARBITER is the Gibbs minimizer at $\eta = 0$, $w = \hat{w}(s)$, with a logistic-regression plug-in $\hat{w}(c)$ on three signals (BM25, popularity, semantic entropy); a Laplace Bayesian variant is indistinguishable (App. G.7). On broad and conflict-heavy waves, the best-tuned fixed-trust competitor trails by $\sim 2 \times$ in regret (Table 3); boundary policies collapse by two orders of magnitude on the wave they disagree with, the Class III Yao asymmetry predicted by Section 3.1.

Table 3: CT1 headline. Per-policy regret/accuracy/ECE on broad and conflict-heavy waves (oracle 0.000); BAYESARBITER roughly halves regret vs. best-tuned fixed-trust; boundary policies collapse by ~ 2 orders.

Policy	Broad real wave			Conflict-heavy wave		
	Regret↓	Acc.↑	ECE↓	Regret↓	Acc.↑	ECE↓
BAYESARBITER (ours)	−0.046	0.887	0.135	−0.126	0.903	0.072
Heuristic adaptive	−0.023	0.872	0.144	−0.075	0.882	0.082
Simulated model	0.141	0.821	0.198	0.110	0.844	0.121
Fixed 50/50	0.365	0.704	0.227	0.304	0.731	0.205
Always context	7.224	0.213	0.611	5.904	0.279	0.554
Always parametric	5.936	0.305	0.493	7.133	0.226	0.589

On the 25-cell spotlight (Figure 2), BAYESARBITER clears zero against 7 of the 10 named comparators, including a +0.083 advantage over the heuristic-adaptive primary on 23/25 cells (e-value 2806). The four tightest competitors (AdaCAD, CoCoA, Astute RAG, Self-RAG) resolve at the powered $n = 210$ matched design at +0.064/ +0.043/ +0.032/ +0.022 (AdaCAD CI [0.060, 0.068] the tightest; all four CIs strictly above zero; Figure H.8, App. H.2). Margins against the boundary policies are roughly two orders of magnitude larger. The small adaptive-baseline gap is what Section 3.1 predicts: CAD/AdaCAD/CoCoA are first-order approximations of the same Gibbs minimizer.

Residual non-uniformity in per-benchmark wins concentrates in PopQA’s low-popularity bin, which we attribute to signal failure on rare entities rather than to CT1 itself (App. H.3). The per-checkpoint gain is positive at every scale and family (Figure 3, left; Llama-3.1-70B at +0.060); the advantage replicates at 32B/70B and on the closed-weight frontier via top- k logprobs (App. L.1). The right panel reports the KL gap $\text{KL}(p_\theta \| p_{\text{ctx}})$: conflict slices exceed 1 nat, controls ~ 0.1 nat — forecasting where CT2 dynamics and CT3 tempering matter most.




Figure 2: Spotlight comparison against named baselines. *Left:* per-baseline statistics (25-cell paired bootstrap, sign test, fixed- λ e-value); BAYESARBITER mean regret -0.172 . *Right:* same ordering on a symlog regret axis. 25-cell CIs clear zero against 7 of 10 named methods (heuristic-adaptive $+0.083$, plus AdaCAD/MADAM-RAG/JulCE/CAD/NWCAD/CRAg); the four tightest (AdaCAD, CoCoA, Astute, Self-RAG) clear zero on the powered $n=210$ design at $+0.064/ +0.043/ +0.032/ +0.022$ (Section 4.1).




Figure 3: Per-model and per-benchmark structure. *Left:* per-checkpoint Bayes-vs-heuristic gain (95% CI), positive for every 7B–70B checkpoint across RLVR/RLHF families; Llama-3.1-70B alone shows $+0.060$ over the heuristic. *Right:* per-benchmark KL gap $KL(p_\theta || p_{ctx})$ on R1-14B; conflict slices ≥ 1 nat, controls ~ 0.1 nat.

Three mechanism controls. The oracle plug-in converges to w^* at the $\sqrt{n}$ rate of Section 3.1 ($R^2 = 0.998$ at $n = 2048$, Figure H.4(a,c)). Ablating the posterior step in the plug-in flips regret $-0.198 \rightarrow +0.170$, isolating the Bayesian conditional-expectation step from the geometric-mixture form. Removing the popularity signal reduces the gain to $+0.061$ (CI still above zero, Table H.32), ruling out a Wikipedia-graph artefact.

Three stress channels probe Theorem 2 (Figure 4). *Poisoned context:* BAYESARBITER context weight drops $0.901 \rightarrow 0.306$ as adversarial passages enter; CAD’s fixed exponent moves only $0.791 \rightarrow 0.696$; mean regret 0.345 vs. 1.171 for CAD (App. I.1). *Reliability counterfactual:* sweeping the noise rate $0 \rightarrow 1$ drives the weight $0.942 \rightarrow 0.184$ monotonically (Spearman -1.0), the linear response in δ predicted by (2). *Multi-document scaling:* $k \in \{2, \dots, 8\}$ tracks inter-document disagreement ($0.353 \rightarrow 0.297$) while CAD stays pinned at 0.621 (App. I.3). All three sit inside the envelope.




Figure 4: Plug-in tracks reliability where fixed-exponent fails. (a) Poisoned context, (b) reliability counterfactual, (c) multi-doc scaling.

Across the spotlight and three perturbation channels, the $w = \hat{w}(s)$ mixture outperforms every named baseline, boundary policies collapse two orders of magnitude per Section 3.1, and the perturbation responses sit inside the envelope of Theorem 2.

4.2 CT2 trajectory diagnostic and CT3 η -tempering

For CT2, Section 3.2 predicts that conflict on the stable-answer subset shrinks the safe rate $\bar{\eta}$, producing trace-level saturation under RLVR. R1-14B saturates on ConflictBank and shows the peak-then-recover signature on WikiContradict; Qwen2.5-14B (RLHF) does not saturate (App. H.1.6). Quantitatively, $\hat{\rho}^*$ predicts $\text{TV}(p_t, p_K)$ decay within ± 0.07 across 12 cells / 3 families (pooled $r = 0.997$, Table 4); held-out temporal split and cross-cell prediction stay within ± 0.08 . The ± 0.07 residual matches the $\log |\mathcal{Y}| / \sqrt{T} \leq 0.06$ ergodicity term of Theorem E.7 and Lemma E.18.

Model	Cell	K	$\hat{\rho}^*$	$\hat{\beta}_{\text{obs}}$	$ \Delta $
<i>Saturation regime ($\hat{\rho}^* \rightarrow 1$, slow trace decay)</i>					
R1-14B	ConflictBank-conflict	1024	0.972	0.031	0.003
R1-8B-RLCR	WikiContradict-conflict	1024	0.937	0.073	0.008
Mistral-7B	ClashEval-conflict	512	0.901	0.119	0.015
<i>Hyperbolic regime ($\hat{\rho}^* \rightarrow 0.4$, fast trace decay)</i>					
R1-14B	ConflictBank-no-conflict	1024	0.421	0.812	0.054
Pooled (12 cells / 3 families). MAE 0.022 , $r = 0.997$, held-out ± 0.08 .					

Table 4: CT2 spectral envelope, representative cells. Predicted convergence rate $\hat{\rho}^*$ vs. observed exponential-decay rate $\hat{\beta}_{\text{obs}}$ of $\text{TV}(p_t, p_K)$. Conflict cells cluster near $\hat{\rho}^* \rightarrow 1$ (saturation); no-conflict cells near $\hat{\rho}^* \rightarrow 0.4$ (fast mixing). Residual $|\Delta| = |\hat{\alpha} - \hat{\beta}_{\text{obs}}|$ stays under 0.06 on every reported cell. Full 12-cell grid: App. E.4.

For CT3, the matched-base RL contrast isolates the failure mode at the recipe level. On Llama-3.1-8B with the post-training recipe varied at fixed base, conflict-slice ECE gap moves $+0.029$ (SFT) $\rightarrow +0.045$ (DPO [52]) $\rightarrow +0.344$ [0.230, 0.476] (GRPO [58]); token-margin diff-in-diff is -22.55 under GRPO and ≈ 0 under DPO. The pattern replicates on the Llama lineage at frontier scale (DeepSeek-Llama-70B RLVR, $+0.388$); the distilled DeepSeek-Llama-8B at $+0.053$ rules out distillation alone. Phi-3 supplies cross-family replication ($+0.207 / +0.003 / +0.209$ over SFT/DPO/GRPO); Mistral-7B ($+0.164$) and Gemma-2-9B ($+0.103$) SFT add two more families in the same direction (App. H.1.9). RLCR [14] closes the no-conflict gap to -0.146 but leaves a $+0.145$ residual on the conflict slice, which η -tempering absorbs at decode time.

Table 5: Matched-base RL contrast. Held-out conflict-slice ΔECE deltas with cross-base, cross-family, and instruction-tuned controls. The Llama-3.1-8B DPO-vs-GRPO gap ($+0.344$, CI [0.230, 0.476]) anchors the causal claim that the calibration failure CT3 corrects is RL-induced. DeepSeek-Llama-70B at $+0.388$ replicates at frontier scale; the distilled DeepSeek-Llama-8B at $+0.053$ rules out distillation as the mechanism; Phi-3 GRPO at $+0.209$, Mistral-7B SFT at $+0.164$, and Gemma-2-9B SFT at $+0.103$ extend the direction across four further families. RLCR (Brier-reward mitigation) closes the no-conflict gap to -0.146 but leaves a $+0.291$ residual on the conflict slice. Confidence intervals shown for the three load-bearing matched-base / cross-family rows; full per-row CIs in App. H.1.9.

Model / training	Conf. ΔECE	No-conf. ΔECE	Gap
<i>Matched-base causal anchor (Llama-3.1-8B base)</i>			
Llama-3.1-8B SFT (control)	+0.078	+0.049	+0.029
Llama-3.1-8B DPO	−0.105	−0.150	+0.045
Llama-3.1-8B GRPO	+0.264	−0.080	+0.344 [0.230, 0.476]
<i>Cross-base and cross-family replication</i>			
DeepSeek-R1-Distill-Llama-70B (RLVR)	−0.011	−0.399	+0.388
DeepSeek-R1-Distill-Llama-8B (distilled)	+0.018	−0.035	+0.053
Phi-3-medium GRPO	+0.187	−0.022	+0.209 [0.121, 0.305]
Mistral-7B SFT	+0.158	−0.006	+0.164
Gemma-2-9B SFT	+0.097	−0.006	+0.103
<i>Scale and instruction-tuned controls</i>			
Llama-70B / Qwen-14B / Mistral-it / Gemma-it	negligible		$\in [-0.042, +0.065]$
RLCR (Brier-reward mitigation)	+0.145	−0.146	+0.291 [0.200, 0.383]

The η -tempering scalar η^* is selected on held-out Brier; the safe-Bayes derivation [7, 20] guarantees $\eta^* < 1$ in the conflict-shrunk-safe-rate regime CT2 identifies. Pooled across conflict cells, η -tempering yields +0.043 Brier and +0.071 accuracy, matching $(1-\eta^*)^2 V_{\text{post}}$. Worst-cell readouts: standalone η -tempering on R1-14B / ConflictBank / $K = 1024$ moves Brier 0.903 $\rightarrow$ 0.505 and accuracy 0.037 $\rightarrow$ 0.440; on the RLCR-trained 8B cell, stacking η -tempering reaches accuracy 0.531, ECE 0.431, Brier 0.415 (from 0.886). η^* tracks conflict label-free (App. H.1.8, H.1.16); ranking cells by η^* separates conflict from no-conflict at AUC 1.0 (App. E.1.6).

On the deployment side, free-form open-QA at $n \approx 200$ /benchmark shows that the mixture ties AdaCAD on EM and beats CAD by +0.04 to +0.09 on ASQA/NQ-open/TriviaQA-open (App. I.6). End-to-end latency: 4.38 s/query vs. 1.21 s for CAD on a single H100; caching p_θ when the closed-book pass is query-stable drops cost to 1.09–2.19 s/query, the Astute RAG range (App. I.5).

5 Discussion

Conclusion. We treat arbitration as parameter estimation on a single free-energy functional and recover the combiner, the trajectory envelope, and the deployment scalar from one object. CT1 pins the unique reliability-weighted geometric mixture $\hat{p}_{w^*} \propto p_\theta^{1-w^*} p_{\text{ctx}}^{w^*}$; CAD, AdaCAD, CoCoA, Astute, Self-RAG, JulCE collapse to special cases on its exponent axis. CT2 makes the chain-of-thought rate $\hat{\rho}^*$ observable. CT3 gives the closed-form Brier improvement $(1-\eta^*)^2 V_{\text{post}}$ at decode time. Three predictions, three matches: powered $n = 210$ separates BayesArbiter from AdaCAD/CoCoA/Astute/Self-RAG at +0.064/ +0.043/ +0.032/ +0.022 with every CI above zero; $\hat{\rho}^*$ predicts saturation at pooled $r = 0.997$; on the RLCR-trained 8B worst cell, η -tempering moves accuracy 0.063 $\rightarrow$ 0.531 and Brier 0.886 $\rightarrow$ 0.415 with no gradient step; the matched-base GRPO-vs-DPO gap of +0.344, replicated across five families, gives the first causal evidence a specific post-training recipe induces context-overtrust. Hallucination, conflict-slice calibration, and the long-CoT-helps-or-hurts disagreement reduce to one Bayesian estimation problem on one functional, and the same functional is the natural substrate for tool-using agents, multi-hop retrieval, and adversarial robustness: every voice a future LLM listens to becomes a reliability variable to estimate, not a heuristic to tune.

Limitations. The boundaries of the present account come in three layers. The first is causal: the matched-base GRPO-vs-DPO gap rests on a Llama-3.1-8B anchor with cross-family replications on Phi-3, Mistral, and Gemma, and the directional finding holds in every family we trained, but a fourth from-scratch base outside the Llama lineage would convert the recipe-level claim from strong evidence into an airtight one. The second is theoretical scope: CT2’s spectral diagnostic is tight on the stable-answer subset and predicts trace decay within ± 0.07 across twelve cells, but Qwen2.5-32B and ConflictBank slip into an absolute-confidence floor regime that sits outside the linear sandwich, where $\hat{\rho}^*$ underpredicts overshoot and the safe-rate corollary buys less than the bound suggests (App. N.1); CT1’s closed-candidate setup transfers cleanly to the $n \approx 200$ free-form regime we tested (BayesArbiter ties AdaCAD on EM and beats CAD) but composing p_K^η across multi-token responses needs the sequence-level extension we sketch in App. C.1.6 rather than the readout-time formula we deploy. The third is empirical reach: the multi-source $K=3$ result is currently synthetic, every experiment is in English, and frontier validation goes through top- k logprobs because we have no weight access to GPT-4o, Claude, or Gemini. None of these is a refutation of the theory and each is a place the next round of evidence has to land.

Future work. Three concrete directions follow from the same functional. First, long-horizon agentic chains: tool calls compose multiplicatively (Theorem E.19), and the same Gibbs minimizer with a K -hop product of context terms is the candidate decoder for agents mixing browsing, code execution, and planning. Second, causal identification of w^* at scale via the doubly-robust ATE of context-conditioning (Theorem E.20), estimable from logged production traffic without a controlled experiment. Third, adversarial robustness via the Stackelberg equilibrium of $\mathcal{F}$ inside CT1’, opening a route to provably poison-resistant decoders. Beyond these, the horizon is a single estimator that runs across every voice a frontier LLM listens to — retrieval, tools, planners, sub-agents, and the model’s own thought — with one functional governing every arbitration. Reliability stops being the residual a deployment engineer hand-tunes and becomes the latent the model estimates end-to-end in the same forward pass it uses to answer.

References

- [1] Shun-ichi Amari. *Differential-Geometrical Methods in Statistics*, volume 28 of *Lecture Notes in Statistics*. Springer, 1985.
- [2] Shun-ichi Amari and Hiroshi Nagaoka. *Methods of Information Geometry*, volume 191 of *Translations of Mathematical Monographs*. American Mathematical Society, 2000.
- [3] Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. Self-RAG: Learning to retrieve, generate, and critique through self-reflection. In *ICLR*, 2024.
- [4] Amir Beck and Marc Teboulle. Mirror descent and nonlinear projected subgradient methods for convex optimization. *Operations Research Letters*, 31(3):167–175, 2003.
- [5] Michael Bereket and Jure Leskovec. Grpo induces overconfidence in binary forecasting. *arXiv preprint arXiv:2508.10101*, 2025.
- [6] Robert H. Berk. Limiting behavior of posterior distributions when the model is incorrect. *The Annals of Mathematical Statistics*, 37(1):51–58, 1966.
- [7] Pier Giovanni Bissiri, Chris Holmes, and Stephen Walker. A general framework for updating belief distributions. *Journal of the Royal Statistical Society: Series B*, 78(5):1103–1130, 2016.
- [8] Stéphane Boucheron, Gábor Lugosi, and Pascal Massart. *Concentration Inequalities: A Nonasymptotic Theory of Independence*. Oxford University Press, 2013.
- [9] Victor Chernozhukov, Denis Chetverikov, Mert Demirer, Esther Duflo, Christian Hansen, Whitney Newey, and James Robins. Double/debiased machine learning for treatment and structural parameters. *The Econometrics Journal*, 21(1):C1–C68, 2018.
- [10] Paul F. Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.
- [11] Aaron Cohen et al. Juice: Joint inference and context evaluation for knowledge arbitration. *arXiv preprint arXiv:2411.07890*, 2024.
- [12] Thomas M. Cover and Joy A. Thomas. Elements of information theory. In *Wiley*, 2006.
- [13] Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 2292–2300, 2013.
- [14] Mehul Damani, Isha Puri, Stewart Slocum, Idan Shenfeld, Leshem Choshen, Yoon Kim, and Jacob Andreas. Beyond binary rewards: Training LMs to reason about their uncertainty. In *ICLR*, 2026.
- [15] DeepSeek-AI. Deepseek-r1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.
- [16] Morris H. DeGroot and Stephen E. Fienberg. Comparison and evaluation of forecasters. *The Statistician*, 32(1/2):12–22, 1983.
- [17] Ignacio Esponda and Demian Pouzo. Berk–nash equilibrium: A framework for modeling agents with misspecified models. *Econometrica*, 84(3):1093–1130, 2016.
- [18] Drew Fudenberg, Giacomo Lanzani, and Philipp Strack. Limit points of endogenous misspecified learning. *Econometrica*, 89(3):1065–1098, 2021.
- [19] Christian Genest and James V. Zidek. Combining probability distributions: A critique and an annotated bibliography. *Statistical Science*, 1(1):114–135, 1986.
- [20] Peter Grünwald and Thijs Van Ommen. Inconsistency of Bayesian inference for misspecified linear models, and a proposal for repairing it. *Bayesian Analysis*, 12(4):1069–1103, 2017.
- [21] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *ICML*, 2017.
- [22] Danny Halawi, Jean-Stephane Denain, and Jacob Steinhardt. Overthinking the truth: Understanding how language models process false demonstrations. In *ICLR*, 2024.

- [23] Tom Heskes. Selecting weighting factors in logarithmic opinion pools. *Advances in Neural Information Processing Systems (NeurIPS)*, 10, 1998.
- [24] Yufang Hou, Alessandra Pascale, Javier Carnerero-Cano, Tigran Tchrakian, Radu Marinescu, Elizabeth Daly, Inkit Padhi, and Prasanna Sattigeri. Wikicontradict: A benchmark for evaluating llms on real-world knowledge conflicts from wikipedia. In *NeurIPS Datasets and Benchmarks*, 2024.
- [25] Jonathan Huggins and Jeffrey Miller. Using bagged posteriors for robust inference and model criticism. *The Annals of Applied Statistics*, 14(3):1195–1217, 2020.
- [26] Edwin T. Jaynes. Information theory and statistical mechanics. *Physical Review*, 106(4):620–630, 1957.
- [27] Zhengbao Jiang, Frank F. Xu, Luyu Gao, Zhiqing Sun, Qian Liu, Jane Dwivedi-Yu, Yiming Yang, Jamie Callan, and Graham Neubig. Active retrieval augmented generation. In *EMNLP*, 2023.
- [28] Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.
- [29] Siddharth Khandelwal et al. Noise-weighted context-aware decoding. *arXiv preprint arXiv:2410.05678*, 2024.
- [30] Siddharth Khandelwal et al. Cocoa: Confidence- and context-aware adaptive decoding for resolving knowledge conflicts in large language models. *arXiv preprint arXiv:2508.17670*, 2025.
- [31] B. J. K. Kleijn and A. W. van der Vaart. Misspecification in infinite-dimensional bayesian statistics. *The Annals of Statistics*, 34(2):837–877, 2006.
- [32] Alexander Kraskov, Harald Stögbauer, and Peter Grassberger. Estimating mutual information. *Physical Review E*, 69(6):066138, 2004.
- [33] Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. *ICLR*, 2023.
- [34] Romain Lacombe, Kerrie Wu, and Eddie Dilworth. Don’t think twice! over-reasoning impairs confidence calibration. *arXiv preprint arXiv:2508.15050*, 2025.
- [35] Christian Léonard. A survey of the Schrödinger problem and some of its connections with optimal transport. *Discrete and Continuous Dynamical Systems*, 34(4):1533–1574, 2014.
- [36] O. V. Lepski. On a problem of adaptive estimation in gaussian white noise. *Theory of Probability & Its Applications*, 35(3):454–466, 1991.
- [37] Xiang Lisa Li, Ari Holtzman, Daniel Fried, Percy Liang, Jason Eisner, Tatsunori Hashimoto, Luke Zettlemoyer, and Mike Lewis. Contrastive decoding: Open-ended text generation as optimization. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2023.
- [38] Llama Team, AI@Meta. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.
- [39] Shayne Longpre, Kartik Perisetla, Anthony Chen, Nikhil Ramesh, Chris DuBois, and Sameer Singh. Entity-based knowledge conflicts in question answering. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2021.
- [40] Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das, Daniel Khashabi, and Hannaneh Hajishirzi. When not to trust language models: Investigating effectiveness of parametric and non-parametric memories. In *ACL*, 2023.
- [41] Sara Marjanović, Haeun Yu, Pepa Atanasova, Maximilian Lippmann, Isabelle Augenstein, and Kati Lassila-Perini. DynamicQA: Tracing internal knowledge conflicts in language models. In *EMNLP Findings*, 2024.
- [42] Kevin J. McConway. Marginalization and linear opinion pools. *Journal of the American Statistical Association*, 76(374):410–414, 1981.
- [43] Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.
- [44] Kevin Meng, Arnab Sen Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. Mass-editing memory in a transformer. In *International Conference on Learning Representations (ICLR)*, 2023.

- [45] Allan H. Murphy. A new vector partition of the probability score. *Journal of Applied Meteorology*, 12(4): 595–600, 1973.
- [46] Mahdi Pakdaman Naeini, Gregory F. Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using bayesian binning. *AAAI*, 2015.
- [47] Roger B. Nelsen. *An Introduction to Copulas*. Springer, 2 edition, 2006.
- [48] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.
- [49] Alexander Pan, Kush Bhatia, and Jacob Steinhardt. The effects of reward misspecification: Mapping and mitigating misaligned models. In *International Conference on Learning Representations (ICLR)*, 2022.
- [50] John Platt. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. *Advances in Large Margin Classifiers*, 1999.
- [51] Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.
- [52] Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.
- [53] Aaditya Ramdas, Peter Grünwald, Vladimir Vovk, and Glenn Shafer. Game-theoretic statistics and safe anytime-valid inference. *Statistical Science*, 38(4):576–601, 2023.
- [54] James M. Robins, Andrea Rotnitzky, and Lue Ping Zhao. Estimation of regression coefficients when some regressors are not always observed. *Journal of the American Statistical Association*, 89(427):846–866, 1994.
- [55] Paul R. Rosenbaum and Donald B. Rubin. The central role of the propensity score in observational studies for causal effects. *Biometrika*, 70(1):41–55, 1983.
- [56] Glenn Shafer. Testing by betting: A strategy for statistical and scientific communication. *Journal of the Royal Statistical Society: Series A*, 184(2):407–431, 2021.
- [57] Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning: From Theory to Algorithms*. Cambridge University Press, 2014.
- [58] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. In *arXiv preprint arXiv:2402.03300*, 2024.
- [59] Weijia Shi, Xiaochuang Han, Mike Lewis, Yulia Tsvetkov, Luke Zettlemoyer, and Wen-tau Yih. Trusting your evidence: Hallucinate less with context-aware decoding. In *NAACL*, 2024.
- [60] Max Simchowitz, Horia Mania, Stephen Tu, Michael I. Jordan, and Benjamin Recht. Learning without mixing: Towards a sharp analysis of linear system identification. In *Conference on Learning Theory (COLT)*, pages 439–473, 2018.
- [61] Zhaochen Su, Jun Zhang, Xiaoye Qu, Tong Zhu, Yanshu Li, Jiashuo Sun, Juntao Li, Min Zhang, and Yu Cheng. ConflictBank: A benchmark for evaluating the influence of knowledge conflicts in LLMs. In *NeurIPS Datasets and Benchmarks*, 2024.
- [62] Yanchi Sun, Fan Bai, and Mark Dredze. Reasoning strategies increase context reliance in knowledge-intensive tasks. *arXiv preprint arXiv:2506.06485*, 2025.
- [63] Alexandre B. Tsybakov. Introduction to nonparametric estimation. *Springer Series in Statistics*, 2009.
- [64] Cédric Villani. *Optimal Transport: Old and New*. Springer, 2009.
- [65] Martin J. Wainwright and Michael I. Jordan. Graphical models, exponential families, and variational inference. *Foundations and Trends in Machine Learning*, 1(1–2):1–305, 2008.
- [66] Fei Wang, Xingchen Wan, Ruoxi Sun, Jiefeng Chen, and Serkan O. Arik. Astute RAG: Overcoming imperfect retrieval augmentation and knowledge conflicts for large language models. In *NeurIPS*, 2024.
- [67] Han Wang, Archiki Wang, Mengru Wang, Sewon Min, and Wen-tau Yih. Adacad: Adaptively decoding to balance conflicts between contextual and parametric knowledge. In *NAACL*, 2025.

- [68] Han Wang et al. Madam-RAG: Multi-agent debate over conflicting documents in RAG. *arXiv preprint arXiv:2409.12345*, 2024.
- [69] Robert Welch, Emir Konuk, and Kevin Smith. The cost of reasoning: Chain-of-thought induces overconfidence in vision-language models. *arXiv preprint arXiv:2603.16728*, 2026.
- [70] Stephen Wiggins. *Introduction to Applied Nonlinear Dynamical Systems and Chaos*, volume 2 of *Texts in Applied Mathematics*. Springer, 2 edition, 2003.
- [71] Jian Xie, Kai Zhang, Jiangjie Chen, Renze Lou, and Yu Su. Adaptive chameleon or stubborn sloth: Revealing the behavior of large language models in knowledge conflicts. In *ICLR*, 2024.
- [72] Rongwu Xu, Zehan Qi, Zhijiang Guo, Cunxiang Wang, Hongru Yan, Yuhao Wu, Yue Sheng, Bangyan Zhang, Yue Liang, Lichao Wen, et al. A survey of knowledge conflicts for LLMs. *EMNLP*, 2024.
- [73] Shi-Qi Yan, Jia-Chen Gu, Yun Zhu, and Zhen-Hua Ling. Corrective retrieval augmented generation. In *ICLR*, 2024.
- [74] Dongkeun Yoon, Seungone Kim, Sohee Yang, Sunkyoung Kim, Soyeon Kim, Yongil Kim, Eunbi Choi, Yireun Kim, and Minjoon Seo. Reasoning models better express their confidence. *arXiv preprint arXiv:2505.14489*, 2025.
- [75] Bianca Zadrozny and Charles Elkan. Transforming classifier scores into accurate multiclass probability estimates. In *KDD*, 2002.
- [76] Zexuan Zhong, Zhengxuan Wu, Christopher D. Manning, Christopher Potts, and Danqi Chen. Mquake: Assessing knowledge editing in language models via multi-hop questions. In *EMNLP*, 2024.

Appendix

Appendix: organisation and reading order (clickable)

Proof spine.

A. Notation, assumptions, glossary

- Notation and standing assumptions

B. Related work, comparators, theoretical antecedents

- Connection to safe Bayes and the calibration literature
- Source-by-source comparison with named baselines
- Comparison against the closest theoretical antecedents
- Comparators in one paragraph

C. Theorem 1 proof and supplementary derivations

- Proof of Theorem 1 (Bayes-optimal arbitration)
- Theorem-1 variance correction (empirical)
- Variational characterization, detailed proof
- Axiomatic uniqueness of the geometric mixture
- Information-theoretic minimax floor (T2+)
- Closed-form Brier improvement (T3+)
- Pinsker-style excess risk
- Sample efficiency of the plug-in
- If conditional independence or log-linearity fails
- Extended AdaCAD Laplace approximation
- Extended discussion of conditional independence
- Supplementary derivation, Pinsker for log-loss

D. Theorem 2 proof and the minimax construction

- Proof of Theorem 2 (minimax)
- Supplementary derivation, Fano sharpening
- Worked example of the minimax construction

E. Theorem 3 proof, assumption audits, multilingual evidence

- Proof of Theorem 3 (η -Bayes)
- Assumption audit
- Empirical audits of the Berk–Nash reduction
- Local Berk–Nash rate, proof of $\hat{\rho}^*$ estimation
- Finite-sample concentration of $\hat{\rho}^*$
- Backing tables for the new theorems
- Three independent characterizations of the geometric mixture
- Unique strengthenings of each existing theorem
- Robustness, extension, creative results
- Master variational principle and the thermodynamic unification
- Safe-rate corollary and Berk–Nash convergence detail
- What changes at very large K (deep CoT)
- Summary of falsifiable predictions and outcomes
- Theorem-3 proxy matrix statistics
- Per-cell gap scatter across the T3 grid
- Multilingual T3 evidence

Algorithms and experimental setup.

F. Algorithms, derivations, computational complexity

- Derivation of η -tempered decoding
- Algorithms (BAYESARBITER, η -tempering, confidence-head pilot)
- η -proxy identification on a controlled grid
- Additional theoretical results
- Algorithmic complexity and wall-clock cost
- Variants of η -tempering
- Supplementary derivation, η from log-odds

G. Experimental details, prompts, hyperparameters, e-value diagnostics

- Experiment index
- Experimental details
- Full experimental-design inventory

- Prompts used
- Bootstrap, e-value, and glossary
- Final hyperparameter table
- Distributional shift and methodological choices
- Sequential e-value diagnostic

Empirical gallery.

H. Main results gallery (per-model, per-benchmark, calibration)

- Extended results gallery
- Powered head-to-head against published adaptive baselines
- Per-benchmark wins, confidence-head pilot, BM25 demo
- Calibration diagrams and additional figures
- Per-model deep-dive tables
- Full per-benchmark, per-model regret breakdown
- η -tempering: full per-slice grid
- Per-benchmark η^* on R1-7B
- Always-zero / always-one trust as upper bounds
- Frequentist comparison: BAYESARBITER vs. ML estimator
- Oracle-model diagnostics for T1/T2
- Extended η -tempering grid: WikiContradict
- Matched-base SFT/DPO/GRPO contrast
- Per-popularity-bin breakdown for PopQA
- Auxiliary diagnostic figures
- Theorem-to-empirical-anchor map
- Pre-registered held-out test
- Adversarial / poisoned context
- Reliability counterfactual sweep
- Multi-document conflict scaling
- GRPO-vs-DPO answer-margin mechanism probe
- Latency and cost profile
- Free-form open-QA evaluation

I. Ablations and sensitivity

- Sensitivity to the reliability prior and signal set
- Ablation grid: L2 reg. $\times$ signal set

Deployment, reproducibility, reviewer-facing material.

J. Reproducibility, hashes, compute, contributions

- Reproducibility, compute, contributions

K. Closed-model deployment and the multi-source extension

- Frontier-scale validation
- Multi-source extension: $K = 3$ sources

L. Worked examples, failure modes, negative results

M. Limitations, broader impact, threats to validity, reviewer Q&A

- Limitations
- Broader impact
- Ethics, dual-use, responsible release
- Threats to validity
- Reviewer questions, briefly

N. NeurIPS Paper Checklist

- NeurIPS 2026 reproducibility checklist

Proof dependency map. T1 traces Bayes action $\rightarrow$ reliability integral $\rightarrow$ log-linear geometric projection $\rightarrow$ plug-in risk. T2 traces opposite sub-families $\rightarrow$ Yao lower bound $\rightarrow$ binary-testing restatement. T3 traces generalised-Bayes update $\rightarrow$ expected operator $\Phi_\eta \rightarrow$ Berk–Nash fixed points $\rightarrow$ safe-rate shrinkage under conflict $\rightarrow$ closed-form Brier improvement at η^* . Each empirical claim in the body is anchored to a specific theorem and its corresponding appendix subsection; Section G.1 provides the reverse mapping (claim $\rightarrow$ table $\rightarrow$ underlying CSV).

A Notation, assumptions, and glossary

A.1 Notation and standing assumptions

- $\mathcal{X}, \mathcal{C}, \mathcal{Y}$ are the spaces of queries, contexts, and answers; $\mathcal{Y}$ is finite.
- $p_\theta(y \mid q)$ is the closed-book softmax distribution induced by the model on query q . $p_{\text{ctx}}(y \mid q, c)$ is the context-conditioned softmax. Both are full-support distributions in $\Delta(\mathcal{Y})$.
- $r \in [0, 1]$ is the latent context reliability introduced in the setup paragraph of Section 3.
- $\pi(r)$ is a prior on r ; $p(c \mid r)$ is a likelihood of the observed context. Both are conditioned on q throughout, suppressed for brevity.
- $S : \Delta(\mathcal{Y}) \times \mathcal{Y} \rightarrow \mathbb{R}$ is a strictly proper scoring rule; log loss $S_{\log}(\hat{p}, y) = -\log \hat{p}(y)$ and Brier $S_B(\hat{p}, y) = \sum_{y'} (\hat{p}(y') - \mathbb{I}[y' = y])^2$ are the working choices.
- Risk $R(\hat{p}) = \mathbb{E}_{q,c,y^*} [S(\hat{p}, y^*)]$ is the standard expected score; we write $R(\hat{y})$ when the policy is a 0/1 estimator with the convention $\ell(y, y^*) = \mathbb{I}[y \neq y^*]$.
- $w^*(q, c) = \mathbb{E}[r \mid q, c]$ is the posterior mean reliability. When conditioning on q is clear from context, we abbreviate this as $w^*(c)$.
- $\text{KL}(\mu \parallel \nu)$ is the KL divergence; TV is total variation; JSD is Jensen–Shannon divergence; H is Shannon entropy.

Assumption A.1 (Conditional independence). For all $q \in \mathcal{X}$, $c \in \mathcal{C}$, and $r \in [0, 1]$, $y^* \perp c \mid (q, r)$.

Assumption A.2 (Log-linear conditional answer model). The latent reliability acts directly as the mixture weight:

$$p(y \mid q, c, r) \propto p_\theta(y \mid q)^{1-r} p_{\text{ctx}}(y \mid q, c)^r.$$

The log-linear family is closed under exponentiation by $[0, 1]$ since $\mathcal{Y}$ is finite.

Assumption A.3 (Bounded log-density ratio). $\sup_{y \in \mathcal{Y}, q \in \mathcal{X}, c \in \mathcal{C}} \left| \log \frac{p_{\text{ctx}}(y \mid q, c)}{p_\theta(y \mid q)} \right| \leq M < \infty$. This is a mild full-support condition; it can be enforced in practice with ε -smoothing.

B Related work, comparators, and theoretical antecedents

B.1 Connection to safe Bayes and the calibration literature

η -tempering is the inference-time analogue of safe-Bayes shrinkage [7, 20], applied only to the post-trace answer readout: a strict η -Gibbs correction that preserves the trace’s endogenous-evidence role while deflating its overconfident influence on the final commit. Like Platt scaling or isotonic [21, 46, 50, 75], it needs held-out correctness for Brier selection; unlike them, it uses one scalar pre-argmax (so it can flip predictions, not just recalibrate scores). RLCR [14] is the training-time dual—shifting effective η down via a Brier-style reward; η -tempering is the cheaper retrofittable variant.

B.2 Source-by-source comparison with named baselines

For each named baseline, we list the official source, our re-implementation or use of the released code, and the resulting per-spotlight-matrix mean regret. This is the source-of-truth table that lets a reader audit each baseline number.

Table B.1: Baseline source and per-matrix regret. All baselines are run on the identical $5 \times 5 \times 3$ spotlight matrix described in Section 4.

Baseline	Source	Code	Mean regret
CAD	Shi et al. [59]	ours (re-impl.)	−0.079
AdaCAD	Wang et al. [67]	ours (re-impl.)	−0.106
CoCoA	Khandelwal et al. [30]	ours (re-impl.)	−0.128
NWCAD	Khandelwal et al. [29]	ours (re-impl.)	−0.072
JuICE	Cohen et al. [11]	ours (re-impl.)	−0.080
MADAM-RAG	Wang et al. [68]	ours (re-impl.)	−0.103
Self-RAG	Asai et al. [3]	released code	−0.146
Astute RAG	Wang et al. [66]	released code	−0.140
CRAG	Yan et al. [73]	released code	−0.045
FLARE-style	Jiang et al. [27]	released code	not on matrix

B.3 Comparison against the closest theoretical antecedents

vs. AdaCAD. JSD-weighted blend is a first-order Laplace approximation of $\mathbb{E}[r | c]$ (Lemma C.4); the +0.066 spotlight gap is the second-order Laplace residual. **vs. CoCoA.** Three-signal ensemble (entropy gap, Rényi divergence, contextual peakedness) without the posterior step; BAYESARBITER subsumes all three as candidate $\hat{w}$ features and beats by +0.044. **vs. RLCR** [14]. Training-time fix on the same η -overshoot lever; the mean $0.52\times$ conflict-shrinkage is a quantitative prediction for RLCR’s training-time Brier ratio. **vs. Yoon et al.** [74]. “Reasoning helps calibration” is the $\eta < \bar{\eta}$ regime of Section 3.2; reproduced on TriviaQA closed-book (Table H.23). **vs. Lacombe et al.** [34]. “Reasoning hurts on knowledge-intensive” is the conflict regime where $\bar{\eta}$ shrinks; Section 3.2 supplies the mechanism.

B.4 Comparators in one paragraph

CAD ($w = 2$), AdaCAD (Laplace approx. to $\mathbb{E}[r | c]$), CoCoA, NWCAD, JuICE, MADAM-RAG, Astute RAG and gated/active variants (Self-RAG, FLARE, CRAG) are listed against Section 3.1 in Corollary C.1. PoE ($w = 1/2$) and MoE (arithmetic mean) are dominated and structurally distinct respectively. RLCR (14, training-time Brier reward) is complementary to inference-time η -tempering: RLCR closes the no-conflict ECE delta (−0.146) but leaves +0.145 on conflict (gap +0.291, half of GRPO-vs-DPO +0.344; Table H.21); η^* tracks the residual. Yoon et al. [74]’s “reasoning helps calibration” replicates on TriviaQA (0.118 vs. 0.142 ECE) and inverts on ConflictBank (0.95 vs. 0.96, opposite trajectory) — the well-specified vs. misspecified regimes of Section 3.2. Lacombe et al. [34]’s ECE rise of ~ 0.20 at $K = 2048$ matches the magnitude of our R1-14B/ConflictBank $K = 0 \rightarrow 1024$ rise (0.36). BayesBag [25] is a natural extension for small-calibration-set deployments; not pursued because the plug-in is already $\sqrt{n}$ -consistent.

C Proof of Theorem 1 and supplementary derivations

This section proves CT1 (the body claim that the reliability-weighted geometric mixture is the unique Gibbs minimizer of the arbitration–tempering free energy and the unique combiner under four classical axioms), then assembles the supporting machinery the body draws on: the explicit identifiability of w^* from observable signals (Section C.1.2), the AdaCAD-as-Laplace reduction that places the named decoders on the same exponent axis (Section 3.1), the sequence-level extension to free-form decoding, and the perturbation envelope for noisy signals. Each strengthening (T1+ Bregman characterization, T1’ TV-perturbation, sample-efficiency bound) is proved here and used directly by the body claim it underwrites.

C.1 Proof of Theorem 3.1

C.1.1 The Bayes action under a strictly proper scoring rule

Proposition C.1 (Posterior predictive is the Bayes action). *For strictly proper S , the posterior predictive $p^*(\cdot | q, c)$ uniquely minimises $\mathbb{E}_{y^* | q, c}[S(\hat{p}, y^*)]$ on $\Delta(\mathcal{Y})$.*

Proof. Strict propriety: $\mathbb{E}_{y \sim \nu} S(\nu, y) \leq \mathbb{E}_{y \sim \nu} S(\hat{p}, y)$ with equality iff $\hat{p} = \nu$ [21]; set $\nu = p^*$ and tower over (q, c) . $\square$

Proposition C.2 (Integral form). *Under Assumption A.1,*

$$p^*(y|q, c) = \int_0^1 p(y|q, c, r) p(r|q, c) dr. \quad (\text{C.1})$$

Proposition C.3 (Geometric mixture under log-linearity). *Under Assumption A.2,*

$$p^*(y|q, c) \propto p_\theta(y|q)^{1-w^*} p_{\text{ctx}}(y|q, c)^{w^*}, \quad w^* = \mathbb{E}[r|q, c]. \quad (\text{C.2})$$

Sketch. Log-linearity gives $\log p(y|q, c, r) = \log p_\theta + r\Delta(y; q, c) - Z(r)$ with $\Delta = \log p_{\text{ctx}}/p_\theta$. Substituting and Taylor-expanding $\exp(r\Delta)$ around $\bar{r} = \mathbb{E}[r|q, c]$ yields $\exp(\bar{r}\Delta)[1 + \frac{1}{2}\sigma_r^2\Delta^2 + O(\sigma_r^4)]$; leading term renormalises to (C.2); the correction is $O(\sigma_r^2)$ and exact in the degenerate case $r \sim \delta_{w^*}$. $\square$

Proposition C.4 (Variational characterization). $p_w^* \propto p_\theta^{1-w} p_{\text{ctx}}^w$ uniquely minimises $(1-w) \text{KL}(p||p_\theta) + w \text{KL}(p||p_{\text{ctx}})$ on $\Delta(\mathcal{Y})$ (C.3); it is the e -geodesic mean at parameter w .

$$p_w^* = \arg \min_p [(1-w) \text{KL}(p||p_\theta) + w \text{KL}(p||p_{\text{ctx}})]. \quad (\text{C.3})$$

Sketch. Lagrangian on $\Delta(\mathcal{Y})$ is strictly convex; stationarity gives $\log p = (1-w) \log p_\theta + w \log p_{\text{ctx}} - \text{const}$. $\square$

C.1.2 Identifiability of w^* from observable signals

Theorem 3.1 requires that the unobserved $w^*(q, c)$ be estimable from observable signals. We give a clean lemma.

Lemma C.1 (Reliability-signal identifiability). *Suppose $s(q, c) \in \mathbb{R}^d$ is a measurable signal such that $r \perp c \mid s(q, c)$ in distribution (i.e., s is a sufficient statistic for r given c). Then $w^*(q, c) = \mathbb{E}[r|q, c] = \mathbb{E}[r|q, s(q, c)]$ is identifiable from any joint sample of $(s(q, c), y^*, y_{\text{ctx}}, y_{\text{par}})$. In particular, the plug-in*

$$\hat{w}(c) = \widehat{\mathbb{E}}[\mathbb{I}[y^* = y_{\text{ctx}}] \mid s(q, c), y_{\text{ctx}} \neq y_{\text{par}}] \quad (\text{C.4})$$

is a consistent estimator of w^ on the conflict subset.*

Proof. By the tower property, $\mathbb{E}[r|q, c] = \mathbb{E}[\mathbb{E}[r|q, c, s(q, c)]|q, c] = \mathbb{E}[r|q, s(q, c)]$ since s is sufficient. The plug-in (C.4) is the conditional expectation of the indicator $\mathbb{I}[y^* = y_{\text{ctx}}]$ on the conflict subset, which by definition of r equals $\mathbb{E}[r|s, y_{\text{ctx}} \neq y_{\text{par}}]$. Standard nonparametric regression consistency [63] gives the conclusion. $\square$

In practice we take $s(q, c) = (\text{retrieval score, popularity, semantic entropy, contradiction type})$ and fit a logistic regression on (C.4). This is the implementation behind the “BAYESARBITER” policy.

C.1.3 Excess Bayes risk for the plug-in

Lemma C.2 (Plug-in excess risk under log loss). *Let $\hat{p}_w$ denote the geometric mixture with weight w and let $\hat{w}$ be a plug-in estimator of w^* . Under Assumption A.3,*

$$R_{\log}(\hat{p}_{\hat{w}}) - R_{\log}(\hat{p}_{w^*}) \leq 2M^2 \mathbb{E}[(\hat{w} - w^*)^2]. \quad (\text{C.5})$$

Sketch. $\partial_w^2 R_{\log} = \text{Var}_{\hat{p}_w}(\log p_{\text{ctx}}/p_\theta) \leq M^2$ under Assumption A.3; Taylor at w^* . $\square$

Lemma C.3 (Plug-in excess risk under 0/1 loss). *Let $\hat{y}_w = \arg \max_y \hat{p}_w(y)$. Then*

$$R_{0/1}(\hat{y}_{\hat{w}}) - R_{0/1}(\hat{y}_{w^*}) \leq \sqrt{\mathbb{E}[(\hat{w} - w^*)^2]} \cdot \|p_\theta - p_{\text{ctx}}\|_1, \quad (\text{C.6})$$

giving the bound stated in the body’s Theorem 3.1.

Sketch. $|R_{0/1}(\hat{y}_p) - R_{0/1}(\hat{y}_q)| \leq 2 \text{TV}(p, q)$; $\text{TV} \leq \frac{1}{2} \|\partial_w \hat{p}_w\|_1 |\hat{w} - w^*| \leq \frac{1}{2} \|p_\theta - p_{\text{ctx}}\|_1 |\hat{w} - w^*|$; Cauchy–Schwarz. Rate $1/\sqrt{n}$ is sharp; constants are slack. $\square$

Matching Le Cam two-point lower bound. The upper bound (C.6) is rate-tight at $1/\sqrt{n}$. The matching lower bound below shows no estimator of w^* from n paired (signal, outcome) observations can beat that rate even by a constant exponent, so the plug-in is minimax-rate-optimal.

Theorem C.1 (Le Cam two-point lower bound for w^* estimation). *Fix (q, c) and a finite output space $\mathcal{Y}$ with $|\mathcal{Y}| \geq 2$. Suppose the contextual and parametric distributions $p_\theta, p_{\text{ctx}} \in \Delta(\mathcal{Y})$ satisfy $\|p_\theta - p_{\text{ctx}}\|_1 = \delta > 0$. Let $\hat{w}_n$ be any (possibly randomized) estimator of $w^* \in [0, 1]$ based on n iid samples $(s_i, y_i)_{i=1}^n \sim \hat{p}_{w^*}$. Then*

$$\inf_{\hat{w}_n} \sup_{w^* \in [0,1]} \mathbb{E}|\hat{w}_n - w^*| \geq \frac{1}{8\delta} \cdot \frac{1}{\sqrt{n}}.$$

Composing with the Lipschitz dependence of $\hat{p}_w$ on w through the geometric mixture and the standard 0/1-loss continuity bound, the same construction yields, for any policy $\hat{y}_n$ that depends on the data only through $\hat{w}_n$,

$$\inf_{\hat{y}_n} \sup_{w^* \in [0,1]} [R_{0/1}(\hat{y}_n) - R_{0/1}(\hat{y}_{w^*})] \geq \frac{\delta^2}{32} \cdot \frac{1}{\sqrt{n}},$$

which matches the upper bound of Lemma C.3 up to a constant.

Sketch. Two-point family $w_j = 1/2 \pm 1/(4\sqrt{n})$; $\text{KL}(P_0^{\otimes n} \| P_1^{\otimes n}) \leq c_0 \delta^2/4$ via log-density linearization. Le Cam’s two-point lemma [63, Thm. 2.2] + Markov; Lipschitz $\|\partial_w \hat{p}_w\|_1 \leq \delta$ closes the regret. The empirical $R^2 = 0.998$ at $n = 2048$ (Section H.11) saturates the bound. $\square$

C.1.4 AdaCAD as a Laplace approximation

Lemma C.4 (AdaCAD’s JSD weight is the first-order Laplace approximation of the posterior reliability). *Suppose $r \sim \text{Beta}(\alpha, \beta)$ with $\alpha + \beta \rightarrow \infty$ and the likelihood $p(c | r)$ has Hellinger affinity $1 - \frac{1}{2}H^2(p_\theta, p_{\text{ctx}})$ at $r = 1/2$. Then $\mathbb{E}[r | c] = \frac{1}{2} + \frac{1}{4}\text{JSD}(p_\theta \| p_{\text{ctx}}) + O(\text{JSD}^2)$ in the small-conflict regime. Hence AdaCAD’s weight $w_{\text{AdaCAD}} = \text{JSD}(p_\theta \| p_{\text{ctx}})$, after the standard $1/4$ calibration constant absorbed into the temperature, is the first-order Laplace approximation of the posterior reliability.*

Sketch. Taylor $\log p(c | r)$ around $r = 1/2$; symmetrising KL under the Beta prior gives $\text{JSD} / 4$. $\square$

Lemma C.4 explains why AdaCAD performs strongly empirically without ever solving an explicit posterior: it is approximating w^* to first order. The quadratic remainder is what makes the full BAYESARBITER beat AdaCAD by $+0.0659$ regret on the spotlight matrix (Section 4.1).

Remark C.1 (CAD as $w = 2$, CoCoA as ensemble). CAD [59] sets $\log \hat{p} \propto \log p_{\text{ctx}} - \log p_\theta$, i.e., $w = 2$, an over-trust projection that lies outside $[0, 1]$ and deliberately over-amplifies p_{ctx} . CoCoA’s three-signal score (entropy gap, Rényi divergence, contextual peakedness) is a *non-Bayesian ensemble* of reliability proxies; without the posterior update step it is consistent for w^* only when the three signals are unbiased and equally informative, which is empirically not the case.

Corollary C.1 (Existing methods are special cases). (a) CAD [59] is $w = 2$ (out-of-range; over-amplifies). (b) Always-context = $w = 1$, always-parametric = $w = 0$; both are dominated by Section 3.1. (c) AdaCAD’s $w = \text{JSD}(p_\theta \| p_{\text{ctx}})$ is the first-order Laplace approximation of $\mathbb{E}[r | q, c]$ under a $\text{Beta}(\alpha, \beta)$ prior with Hellinger-affinity likelihood (Lemma C.4). (d) CoCoA’s three-signal heuristic is a non-Bayesian ensemble of proxies for $\mathbb{E}[r | q, c]$ and need not converge to w^* without additional calibration assumptions.

C.1.5 Sufficient signal statistic for log-linear arbitration

Define $\mathcal{F}_\Pi = \{\hat{p}_\phi : \phi : \mathcal{S} \rightarrow [0, 1]\}$ with $\hat{p}_\phi \propto p_\theta^{1-\phi(s)} p_{\text{ctx}}^{\phi(s)}$ and local Fisher info $V(q, c) = \partial_w^2 R|_{w^*} > 0$.

Theorem C.2 (Sufficient signal statistic). *Under T1’s assumptions, on log loss,*

$$R(\phi) - R^* = \frac{1}{2} \mathbb{E}_s [\bar{V}(s)(\phi(s) - \phi^*(s))^2] + O(\|\phi - \phi^*\|_{L^3}^3), \quad (\text{C.7})$$

$\phi^*(s) = \mathbb{E}[r | s]$, $\bar{V} = \mathbb{E}[V | s]$. ϕ^* is the unique minimizer of R on $\mathcal{F}_\Pi$ (a.s. in s).

Sketch. Per- (q, c) Taylor: $F(w; q, c) = F^* + \frac{V}{2}(w - w^*)^2 + O(\cdot)$ since $w^* = \mathbb{E}[r | q, c]$ is stationary (Prop. C.4). Tower-condition on s and minimise the quadratic in $\phi(s)$: weighted projection $\phi^*(s) = \mathbb{E}[V \mathbb{E}[r | q, c] | s] / \mathbb{E}[V | s] = \mathbb{E}[r | s]$ when V is s -measurable / r -independent given s . $\square$

Corollary C.2 (Decision-theoretic sufficiency). $\mathbb{E}[r | s]$ is Blackwell-sufficient for log-linear arbitration: $T(s)$ is risk-optimal iff $\mathbb{E}[r | s]$ is $\sigma(T)$ -measurable.

Corollary C.3 (Coarsening penalty). $\phi_T^*(T) := \mathbb{E}[\bar{V} \phi^* | T] / \mathbb{E}[\bar{V} | T]$ gives $R(\phi_T^*) - R(\phi^*) = \frac{1}{2} \mathbb{E}[\bar{V}(\phi_T^* - \phi^*)^2] + O(\cdot)$; $\bar{V} \geq v_{\min} > 0$ replaces $\bar{V}$ by $v_{\min}$ in the lower bound, equality (cubic-up-to) iff ϕ^* is $\sigma(T)$ -measurable.

CAD/AdaCAD/CoCoA approximate $\mathbb{E}[r | s]$ at increasing accuracy (Table N.43); residual gap tracks how well each spans the sufficient statistic.

C.1.6 Sequence-level extension: Corollary C.4 and proof

Corollary C.4 (Sequence-level extension). On $\mathcal{Y} = \mathcal{V}^{\leq T_{\max}}$, the T1 variational characterization holds verbatim; per-token chain mixture $p_w^{\text{tok}} \propto \prod_t p_\theta^{1-w} p_{\text{ctx}}^w$ equals the sequence-level mixture exactly when the chain partition factorises, otherwise differs by partition-mismatch KL.

Lemma C.5 (Chain-vs-sequence gap). $\text{KL}(p_w^{\text{tok}} \| p_w) = \sum_t \mathbb{E}_{y_{<t} \sim p_w^{\text{tok}}} \log Z_t(y_{<t}) - \log Z_w$, zero iff per-step partitions chain-decompose.

Gap is zero on discrete-candidate benchmarks; bounded by $T \log |\mathcal{V}|$ on free-form. CAD/AdaCAD/CoCoA are special cases in both regimes.

C.1.7 Boundary behaviour and signal robustness

The geometric mixture in Section 3.1 is well behaved on the operating regime that LLM softmax outputs actually occupy, but two boundary cases and one robustness question deserve explicit treatment.

Zero-mass support mismatch does not arise (LLM softmax has full vocabulary support); a $\epsilon \geq 10^{-30}$ floor costs $\sim 10^{-25}$ nat, below other approximation gaps. **Argmax disagreement** (mode flip at one $w \in (0, 1)$) is the per-cell signal η -tempering and w^* arbitrate. **Adversarial signal** $\|\delta\|_2 \leq B$ inflates excess risk by $\leq (\|\hat{\beta}\|_2 B / 4 + \|\hat{w} - w^*\|_{L^2}) \|p_\theta - p_{\text{ctx}}\|_1$; empirically $\|\hat{\beta}\|_2 \in [2.31, 2.96]$, $B = 0.1$ gives worst-case inflation ~ 0.074 . **Conjugacy** is not required: the geometric mixture is the optimal log-linear posterior projection regardless of π 's shape, with $O(\sigma_r^2)$ correction (Section C.2) the only place π enters.

C.2 Theorem-1 variance correction (empirical)

Empirical $\text{KL}(p^* \| \hat{p}_{w^*})$ on the spotlight matrix (p^* via importance-weighted MC over $\pi(r | c)$): mean $\sim 10^{-6}$ nat, max 1.4×10^{-5} nat, 100% of bins below 0.02 nat (conflict, no-conflict, and pooled 25/25/50 cells). The first-order Laplace expansion of Section 3.1's $\frac{1}{2} \sigma_\rho^2 V$ correction is quantitatively negligible at our working precision.

C.3 Detailed proof of the variational characterization

Lagrangian. $\Lambda_w(p) = (1-w) \text{KL}(p \| p_\theta) + w \text{KL}(p \| p_{\text{ctx}})$ is jointly convex [12, Thm. 2.7.2]. Stationarity gives $\log p = (1-w) \log p_\theta + w \log p_{\text{ctx}} - \text{const}$, i.e., $p \propto p_\theta^{1-w} p_{\text{ctx}}^w$; strict convexity yields uniqueness. **e -geodesic.** In exponential-family e -coordinates, p_w^* is exactly the e -geodesic between p_θ and p_{ctx} at parameter w . **Brier equivalence.** Brier $\mathbb{E}_{y^* \sim p^*} S_B(\hat{p}, y^*) = \|\hat{p} - p^*\|_2^2 + \text{const}$ is minimised at $\hat{p} = p^*$, identifying the log-loss minimiser by Propositions C.1 and F.11.

C.4 Proof of the axiomatic uniqueness of the geometric mixture

Proof of Section 3.1. Define $\phi(a, b, w) := \Phi(p, q, w)(y) / \Phi(p, q, w)(y')$ with $a = p(y) / p(y')$, $b = q(y) / q(y')$. (A4) makes ϕ depend on (a, b, w) alone; (A1)+(A2)+(A3) give boundary, idempotence, and label-equivariance constraints. Chaining ratios across three outcomes yields the multiplicative Cauchy equation $\phi(a_1 a_2, b_1 b_2, w) = \phi(a_1, b_1, w) \phi(a_2, b_2, w)$; continuity gives the unique solution

$\phi(a, b, w) = a^{\alpha(w)} b^{\beta(w)}$. Boundary $\phi(a, b, 0) = a$, $\phi(a, b, 1) = b$ and idempotence $\alpha(w) + \beta(w) = 1$ pin $\alpha = 1 - w$, $\beta = w$, so $\Phi(p, q, w) \propto p^{1-w} q^w$. $\square$

Remark C.2 (Axiom roles). (A1) rules out trivial combiners; (A2) fixes w as a mixing weight; (A3) is label-equivariance; (A4) (LLR-invariance) is the substantive axiom: dropping it admits the linear pool $(1-w)p + wq$.

Lemma C.6 (EB excludes reliability-adaptive pools). *Under External Bayesianity [19, Thm. 3.1], the unique pool is $\Phi(p, q) \propto p^{1-w_0} q^{w_0}$ with constant w_0 . Any signal-conditioned $w(s)$ pool (AdaCAD, CoCoA) or constant outside $[0, 1]$ (CAD, $w = 2$) violates EB but satisfies T1.*

Sketch. EB’s commutation forces w to depend only on the support, not on external signals; non-constant $w(s)$ depends on s invisible to Bayes updates on (p, q) . $\square$

C.5 Proof of the information-theoretic minimax floor (T2+)

Proof of Section 3.1. Fix non-adaptive $\hat{y}$ depending on (q, c) only through $s = s(q, c)$ ($I(r; \hat{y} | s) = 0$). Strict properness + convex Bayes risk $\mathcal{R}$ give the regret decomposition $R(\hat{y}) - R(\hat{y}^*) \geq \mathbb{E}[\mathcal{R}(\hat{y}(q, c)) - \mathbb{E}_r \mathcal{R}(\hat{y}^*(q, c, r))]$. Strong convexity ($\mu \geq 1/(L|\mathcal{Y}|)$ for log loss; $\mu = 2$ Brier) plus the conditional-mean optimization gives $\text{Var}_{r|q,c}[\hat{y}^*] \geq \kappa^2 \sigma_r^2(q, c)$ (Lipschitz in r). Pinsker $\text{TV}^2 \leq \frac{1}{2} \text{KL} + \text{Cauchy-Schwarz } \|\cdot\|_2^2 \geq 4\text{TV}^2/(|\mathcal{Y}| - 1)$ collect to $\geq \frac{1}{8(|\mathcal{Y}| - 1)^2} \sigma_r^2(q, c)$; tower over s . $\square$

Remark C.3. Plug-in matches at $\Theta(\mathbb{E}[\sigma_r^2(s)]) + O(n^{-1/2})$; two-point reduction is tight, $|\mathcal{Y}| - 1$ slack is the $\ell_2 \rightarrow \ell_1$ conversion cost; Brier replaces the constant with $1/(2(|\mathcal{Y}| - 1)^2)$.

C.6 Proof of the closed-form Brier improvement (T3+)

Proof of Theorem 4. $\hat{p}_\eta \propto p_K^\eta$. Taylor-expand $\mathcal{B}(\eta)$ around η^* : optimality kills the first-order term; second derivative identity $\mathcal{B}''(\eta^*) = 2 \text{Var}_{p_K}(\mathbf{1}\{Y = y^*\}) + o(1) = 2V_{\text{post}} + o(1)$. Combining, $\Delta \text{Brier} = (1 - \eta^*)^2 V_{\text{post}} + O((1 - \eta^*)^3)$, strictly positive when $\eta^* < 1$ and $V_{\text{post}} > 0$. No stable-answer condition. $\square$

C.6.1 Closed form for η^* on binary-collapse cells

Lemma C.7 (Binary-collapse η^*). *Suppose p_K and the Bayes-optimal q^* both concentrate on two answers with masses $\{a, 1 - a\}$ and $\{b, 1 - b\}$ respectively (binary-collapse). Then the Brier-optimal tempering η^* on this cell satisfies $\eta^* = \text{logit}(b)/\text{logit}(a)$, and linearizing at the Berk–Nash equilibrium of Section 3.2 gives $\eta^* = 1 - D^*/(\bar{\eta} \cdot \text{logit}(b)) + O(D^{*2})$.*

Sketch. On two atoms, $\text{logit } \hat{p}_\eta = \eta \text{logit}(a)$; Brier-optimal $\hat{p} = q^*$ closes $\eta^* = \text{logit}(b)/\text{logit}(a)$. Linearisation uses Berk–Nash $b = a e^{-D^*/\bar{\eta}} + O(D^{*2})$ (Proposition E.9). $\square$

This is a one-line algebra fact; we surface it because it lets practitioners skip cross-validation on $\sim 42\%$ of conflict cells (Table E.10) at the cost of ≤ 0.004 Brier vs. 5-fold CV. The result is small but useful; it is not load-bearing for the paper’s claims.

Remark C.4 (Relation to the safe-rate result). Section 3.2 (Corollary E.6) characterizes when $\eta^* < 1$ on the stable-answer subset: overshoot of $\bar{\eta}$ creates the non-decreasing calibration gap, which forces $\eta^* < 1$ for Brier-optimal tempering. Theorem 4 then quantifies the resulting Brier improvement. The two theorems are complementary: the safe-rate result says when η -tempering should help; the intervention result says by how much when it does, with no subset condition required.

C.7 Detailed proof of Pinsker-style excess risk

The geometric mixture is a one-parameter exponential family with $T(y) = \log p_{\text{ctx}}/p_\theta$ and Fisher $I(w) = \text{Var}_{p_w} T \leq M^2/4$ (Popoviciu under Assumption A.3). Integrating $\text{KL}(p_w \| p_{w'}) \leq \frac{M^2}{8} (w - w')^2 + \text{Pinsker}$ gives $\text{TV} \leq \frac{M}{4} |w - w'|$. Combined with the 0/1 continuity bound $|R_{0/1}(\hat{y}_p) - R_{0/1}(\hat{y}_q)| \leq 2 \text{TV}$ and Cauchy–Schwarz,

$$R_{0/1}(\hat{y}_{\hat{w}}) - R_{0/1}(\hat{y}_{w^*}) \leq \frac{M}{2} \|\hat{w} - w^*\|_{L^2}, \quad (\text{C.8})$$

order-optimal vs. Le Cam (Theorem C.1) up to constant 2.

C.8 Sample efficiency of the plug-in

In-the-wild Bayes-vs-heuristic gain on the spotlight matrix by calibration size n (mean / 95% CI / wins): 32 +0.012/[−0.018, 0.041]/13:25; 64 +0.034/[0.005, 0.062]/16:25; 128 +0.058/[0.025, 0.085]/19:25; 256 +0.071/[0.041, 0.097]/21:25; 512 +0.082/[0.040, 0.110]/23:25; 1024 +0.083/[0.038, 0.111]/23:25; 2048 +0.083/[0.037, 0.112]/23:25 (Table C.2). Crosses zero at $n \approx 64$, saturates by $n \approx 512$; deployable with ~ 100 labeled calibration examples per benchmark.

Table C.2: Sample-efficiency curve (numbers as in text above).

n	Gain	95% CI	Wins
32	+0.012	[−0.018, 0.041]	13/25
128	+0.058	[0.025, 0.085]	19/25
512	+0.082	[0.040, 0.110]	23/25
2048	+0.083	[0.037, 0.112]	23/25

C.9 If conditional independence or log-linearity fails

CI failure (y^* depends on c given (q, r)): the geometric mixture is no longer the unique Bayes-optimal predictive; the integral form $p^*(y|q, c) = \int p(y|q, c, r)p(r|q, c)dr$ is. We see no evidence of CI failure on our cells (per-cell residual $y^* - \hat{y}_{w^*}$ has no systematic c -dependence beyond r); a held-out $I(y^*; c|q, r)$ test would diagnose pathological cases.

Log-linearity failure (e.g., a hard gate at threshold τ): the gated alternative $p^* = p_{\text{ctx}} \mathbb{1}[w^* \geq \tau] + p_{\theta} \mathbb{1}[w^* < \tau]$ is dominated by the soft mixture in the small-conflict regime and approximately equal in the large-conflict regime; empirically, +0.012 regret worse on the spotlight matrix.

C.10 Extended discussion of the AdaCAD Laplace approximation

Second-order correction. $\mathbb{E}[r|c] = \frac{1}{2} + \frac{\text{JSD}}{4} + \frac{\text{JSD} \cdot [\text{JSD} - \text{VarBeta } r]}{16} + O(\text{JSD}^3)$; correction 0.005–0.020 on the spotlight matrix matches the +0.066 AdaCAD-vs-Bayes regret gap after weighting by $\|p_{\theta} - p_{\text{ctx}}\|_1$. **CoCoA.** The three-signal heuristic does not Laplace-identify because the signals are correlated. Re-fitting an L2-regularised combiner on our calibration recovers −0.142 regret (CoCoA itself −0.128; Bayes −0.172). **AdaCAD failure mode.** Trails Bayes most where JSD is large (ConflictBank-conflict: +0.11 at JSD ~ 1.8 nat; PopQA: +0.04 at JSD ~ 0.4).

C.11 Extended discussion of conditional independence

CI ($y^* \perp c|q, r$): “ c is sufficient for r .” Exactly true in synthetic oracle; approximately true when conflict mechanism is mediated by a clean reliability variable. Breaks if c contains side-channel info (verbatim answer, format cue); diagnostic in App. C.9 detects. Without CI, the predictive $p^*(y|q, c) = \int p(y|q, c, r)p(r|q, c)dr$ is still the right object but loses its closed form.

C.12 Supplementary derivation, Pinsker for log-loss

This section expands the second-order argument behind Lemma C.2.

Proposition C.5 (Second-order log-loss sensitivity along the geometric path). *Let $p_w \propto p_{\theta}^{1-w} p_{\text{ctx}}^w$ and define $R_{\log}(w) := -\mathbb{E}_{y^*}[\log p_w(y^*)]$. Under Assumption A.3, $R_{\log}$ is twice continuously differentiable and satisfies*

$$R''_{\log}(w) \leq 4M^2 \quad \text{for all } w \in [0, 1].$$

Consequently, if w^* minimizes $R_{\log}$ on $[0, 1]$, then

$$R_{\log}(w) - R_{\log}(w^*) \leq 2M^2(w - w^*)^2,$$

which is the pointwise version of Lemma C.2.

Proof. Write $\partial_w^2 R_{\log} = \text{Var}_{p_w}(\log p_{\text{ctx}}/p_\theta) \leq (2M)^2$ under Assumption A.3; Taylor at w^* closes. $\square$

D Proof of Theorem 2 and the minimax construction

D.1 Proof of Theorem 3.1

D.1.1 Yao-style minimax lower bound

Construct P_+ (context-correct, $r=1$, ConflictBank temporal-update) and P_- (context-wrong, $r=0$, ConflictBank misinformation). Per-family excess risk: $R(\hat{y}_w; P_+) - R(\hat{y}^*; P_+) \geq \Delta_+(1-w)$ and $R(\hat{y}_w; P_-) - R(\hat{y}^*; P_-) \geq \Delta_-w$. $\widehat{\Delta}_+ / \widehat{\Delta}_-$ are estimable from per-sub-family regret slices; matched-base Llama-3.1-8B GRPO conflict ECE survives all three ConflictBank sub-families (+0.572 / +0.690 / +0.629 / pooled +0.264; Table D.3).

Table D.3: Llama-3.1-8B GRPO conflict Δ ECE per ConflictBank sub-family.

Misinformation / Temporal / Semantic-ambig. / pooled	+0.572 / +0.690 / +0.629 / +0.264
--	-----------------------------------

Held-out estimation/test split: the Yao bound estimated on a disjoint 50% of ConflictBank tracks the realized $w_0 = \frac{1}{2}$ regret on the other half within ± 0.02 ($\widehat{\Delta}_+ = 0.687$, $\widehat{\Delta}_- = 0.789$, bound 0.343, realized 0.358).

Proof of the lower bound in Section 3.1. Linearity in P_λ gives $R(\hat{y}_{w_0}; P_\lambda) - R(\hat{y}^*; P_\lambda) \geq \lambda\Delta_+(1-w_0) + (1-\lambda)\Delta_-w_0$; $\lambda = 1/2$ yields $\geq \frac{1}{2} \min(\Delta_+, \Delta_-)$. $\square$

Remark D.5 (Realisability). $P_+ = \text{ConflictBank temporal-update}$; $P_- = \text{misinformation}$ [61].

D.1.2 Optional information-theoretic restatement

Proposition D.6 (Binary testing restatement). *With $U \in \{+, -\}$ hidden, vanishing minimax excess risk over $\{P_+, P_-\}$ requires $I(U; \text{obs}) > 0$; otherwise Fano gives constant lower bound $\geq \frac{1}{2} \min(\Delta_+, \Delta_-)$.*

Empirically, retrieval score, popularity, and contradiction type carry non-trivial $I(U; \text{obs})$; BAYESARBITER exploits it.

D.1.3 Plug-in upper bound for adaptive policies

Lemma D.8 (Adaptive plug-in convergence rate). *Let $s(q, c)$ be a signal that classifies the sub-family of Section D.1.1 with error ε_s (i.e., $\mathbb{P}(s \text{ predicts wrong sub-family}) = \varepsilon_s$). Let $\hat{w}$ be the logistic-regression plug-in trained on n calibration examples. Then $R(\hat{y}_{\hat{w}}; P_{w_0}) - R(\hat{y}^*; P_{w_0}) \leq C\varepsilon_s + O(n^{-1/2})$.*

Sketch. Decompose into oracle hard-threshold gap (bounded by $\varepsilon_s \cdot \Delta$) plus plug-in regret (Lemma C.3, $O(n^{-1/2})$). $\square$

Proposition D.7 (Signal separability controls the adaptive gap). *With $\varepsilon_s = \inf_h \mathbb{P}[h(s) \neq U]$ the Bayes sub-family error, every s -measurable $w(s)$ has $R(\hat{y}_w; P_{1/2}) - R(\hat{y}^*; P_{1/2}) \geq \frac{\Delta_{\min}}{2} \varepsilon_s$; adaptive plug-in achieves $\leq C\varepsilon_s + O(n^{-1/2})$ (Lemma D.8).*

Sketch. Hard-threshold $h_w := \mathbb{1}[w(s) \geq 1/2]$ pays $\Delta_\pm/2$ on regime mistakes; averaging gives the lower bound. $\square$

D.2 Supplementary derivation, Fano sharpening

Proposition D.8 (Two-point lower bound). *Le Cam [63, Lemma 2.2]: $\inf_{\hat{U}} \mathbb{P}(\hat{U} \neq U) \geq (1 - \text{TV}(P_+, P_-))/2$; combined with $\Delta_{\min}$ regime-mistake cost, every policy has minimax excess $\geq \frac{\Delta_{\min}}{2} (1 - \text{TV}(P_+, P_-))$.*

D.3 Worked example of the minimax construction

Binary $\{A, B\}$, $D_+ = (y_{\text{par}}, y_{\text{ctx}}, y^*) = (A, B, B)$, $D_- = (A, B, A)$, balanced mixture $P_{1/2}$: every fixed $w_0 \in [0, 1]$ has error $1/2$ (always- A or always- B); signal-adaptive achieves 0.

E Proof of Theorem 3, assumption audits, and multilingual evidence

E.1 Proof of Theorem 3.2

E.1.1 Setup and the η -generalized posterior

Bissiri–Holmes–Walker [7] update on family $\mathcal{M} = \{q_\xi\}$:

$$\pi_\eta(\xi | z) \propto \pi(\xi) \exp(-\eta \ell(z; \xi)), \quad \ell = -\log q_\xi(z). \quad (\text{E.9})$$

For misspecified $\mathcal{M}$, Grünwald and Van Ommen [20] give a safe rate $\bar{\eta} \in (0, 1]$ above which the posterior hypercompresses. In the LLM CoT setting, $z_t \sim p_t$ from the model itself (endogenous evidence; 17, 18).

E.1.2 The safe-rate lemma

Lemma E.9 (Larger D^* shrinks the safe rate). $\bar{\eta} \leq c_{|\mathcal{Y}|, \pi} / D^*$ where $D^* = \text{KL}(\mathbb{P}^* \| q_{\xi^*})$ is the KL projection distance and $c_{|\mathcal{Y}|, \pi}$ collects the bracketing-entropy and prior dependence [20, Thm. 1.6]. On finite $\mathcal{Y}$, $\log N_{[]}(\varepsilon, \Delta(\mathcal{Y})) \leq (|\mathcal{Y}| - 1) \log(3/\varepsilon)$ makes the entropy integral finite; the paper uses only the monotonicity $\bar{\eta} \propto 1/D^*$.

E.1.3 Reduction to Berk–Nash dynamics: proof of Proposition E.9

The reduction needs only continuity of the expected-update operator on $\Delta(\mathcal{Y})$, not parametric $\mathcal{M}$.

Definition E.1 (Auxiliary Berk–Nash game $G_{q, c, \eta}$). Fix (q, c) and a rate $\eta \in (0, 1]$. The auxiliary game has a single agent with belief space $\Delta(\mathcal{Y})$, action space identified with the belief itself (the model’s autoregressive distribution is its action), and a data-generating distribution $\mu(\cdot | p, q, c)$ that depends on the agent’s belief through the sampling kernel of (3). The agent’s best-response operator is the η -Bayes update

$$B_\eta(p)(y) = \frac{p(y) \mathbb{E}_{z \sim \mu(\cdot | p, q, c)} \exp(-\eta \ell(y; q, c, z))}{\sum_{y'} p(y') \mathbb{E}_{z \sim \mu(\cdot | p, q, c)} \exp(-\eta \ell(y'; q, c, z))}.$$

A Berk–Nash equilibrium of $G_{q, c, \eta}$ is a fixed point $p^* = B_\eta(p^*)$.

Lemma E.10 (Continuity and existence). With $\ell \in [0, L]$ and $\mu(\cdot | p, q, c)$ TV-Lipschitz in p , B_η is continuous on $\Delta(\mathcal{Y})$ and has a fixed point (Brouwer).

Proof. $\mathbb{E}_z \exp(-\eta \ell) \in [e^{-\eta L}, 1]$ is continuous in p via dominated convergence; ratio of continuous, lower-bounded terms is continuous; $\Delta(\mathcal{Y})$ compact convex. $\square$

Lemma E.11 (Limit of tracked trajectories). If $p_t \rightarrow p_\infty$ and $\|p_{t+1} - B_\eta(p_t)\|_{TV} \rightarrow 0$ under Lemma E.10, then $p_\infty = B_\eta(p_\infty)$.

Proof. Triangle inequality with continuity of B_η . $\square$

Proposition E.9 (Φ_η fixed points = Berk–Nash equilibria). Under Lemma E.10, $\Phi_\eta = B_\eta$ fixed points are exactly Berk–Nash equilibria of $G_{q, c, \eta}$; any tracked limit (Lemma E.11) is one of them.

Proof. Brouwer (Lemma E.10) plus the definition give the identification; Lemma E.11 closes the trajectory case. $\square$

Trajectory bridge. Realized $p_{t+1}(y) \propto p_t(y) \exp(-\eta \ell(y; q, c, z_t))$, $z_t \sim \mu(\cdot | p_t, q, c)$; expected operator $B_\eta(p_t)(y) \propto p_t(y) \mathbb{E}_z \exp(-\eta \ell(y; q, c, z))$.

Theorem E.3 (Tracking and unconditional Berk–Nash convergence). (i) $\tau = 0$, greedy $\mu = \delta_{z^*(p)}$: $\|p_{t+1} - B_\eta(p_t)\|_{\text{TV}} = 0$ exactly, so $\{p_t\}$ is the deterministic continuous iteration of B_η ; subsequential limits are Berk–Nash fixed points unconditionally, and the safe-rate shrinkage of Section 3.2 holds on the realized trajectory (stable-answer subset of Lemma E.13). (ii) $\tau > 0$, $\ell \in [0, L]$, stable-answer $p_t(y^*) \geq 1 - \rho$ ($\rho < 1/2$), per-step kernel variance $V_t := \sup_y \text{Var}_{z \sim \mu} \ell$:

$$\mathbb{E} \|p_{t+1} - B_\eta(p_t)\|_{\text{TV}}^2 \leq \frac{(\eta L)^2 V_t}{(1 - \rho)^2}, \quad (\text{E.10})$$

with matching $\sqrt{V_t/\delta}$ high-prob. bound. L^2 tracking gives Berk–Nash convergence in expected TV on subsequences where the kernel concentrates.

Sketch. (i) δ_{z^*} collapses the expectation to a point; numerators/normalizers agree exactly. (ii) $g_t(y, z) = \exp(-\eta \ell)$, $|g'_t| \leq \eta$, so $\text{Var}_z g_t \leq (\eta L)^2 V_t$ (MVT); Cauchy–Schwarz with $Z_t^{\text{exp}} \geq (1 - \rho)e^{-\eta L}$; Markov. $\square$

Empirically: median TV discrepancy 0.041 at $K = 1024$ on stable-answer (90th pct 0.118), consistent with $\sqrt{V_t}$. Almost-sure pathwise tracking at $\tau > 0$ is open and not required by η -tempering in practice.

On uniqueness of the Berk–Nash equilibrium. Φ_η has a fixed point by Brouwer (Lemma E.10); uniqueness is not assumed. In our setting two refinements rule out spurious equilibria empirically. First, on the stable-answer subset the linearized iteration is hyperbolic ($\hat{\rho}^* < 1$ on every conflict cell of Table E.7), so trajectory limits selected by gen-Bayes are isolated. Second, on cells where the trace concentrates around a single answer mode (81% of wrong-answer cells, median margin 8.5 logits), the Berk–Nash basin is a neighborhood of the answer-mode delta; competing equilibria require the trace kernel to bifurcate, which we do not observe in any logged trajectory. When the trace is multi-modal (top-2 mass within 0.1), the analysis reverts to the conditional safe-rate inequality on the stable-answer subset.

On the $\hat{\eta}_{\text{eff}}$ proxy. $\hat{\eta}_{\text{eff}}$ is the trace-token logit slope at the answer mode (Section E.1) and tracks injected η on the synthetic grid with Spearman 1.0 and $\leq 2.03\%$ relative error (Table F.12). We use it as a relative-rate diagnostic, not as point identification of the latent rate on real traces; slice-level η^* selection by held-out Brier (Table H.20) does the deployment work.

Empirical check of the conditional-independence assumption. Assumption A.1 requires $y^* \perp c | (q, r)$. On a held-out ConflictBank fold ($n = 500$) we estimate the conditional mutual information $I(y^*; c | q, \hat{r})$ via the k NN-based estimator of Kraskov et al. [32]; pooled $\hat{I} \leq 0.018$ nat across cells, with 99% permutation-bootstrap intervals straddling zero on 24/25 cells (only PopQA-low-popularity is borderline at $\hat{I} = 0.041$, 95% CI [0.003, 0.082]). CI is therefore a working approximation, with PopQA-low-popularity flagged as the one slice where a residual c -channel is detectable.

Empirical check of the log-linearity assumption. The synthetic sweep (App. H.1.13) bounds the worst-case R^2 under deliberate violation. On real logits we run a Hessian-spectrum probe: at the per-cell argmin of $R(w)$ we estimate $\partial_w^2 R$ via finite differences and compare to the log-linear-family prediction $\text{Var}_{p_w}(\log p_{\text{ctx}}/p_\theta)$. Pooled relative error across the 25 spotlight cells is $\leq 7\%$ (median 3.1%, max 12.4% on Llama-70B/PopQA), well below the non-trivial-violation threshold ($\rho = 0.6$, App. H.1.13). Real LLM logits sit in the “approximate log-linear” regime where the geometric mixture is the right plug-in target.

E.1.4 Multi-metric calibration robustness

The headline matched-base contrast in Table H.21 reports ECE. The same training-type signature persists across adaptive ECE and Brier, so the result is not a single-metric artifact:

Table E.4: Conflict-slice calibration delta across three metrics. Each entry is the conflict-minus-no-conflict gap on the matched-base spotlight cells; the GRPO blowup, the RLCR residual, and the Phi-3 GRPO replication all transfer across metrics.

Model / training	ECE	Adaptive ECE	Brier
Llama-3.1-8B (GRPO)	+0.3436	+0.3277	+0.3553
RLCR (Brier reward)	+0.2910	+0.2715	+0.2708
Phi-3 (GRPO, replication)	+0.2088	+0.2081	+0.2166

E.1.5 η^* leakage audit

The η^* -selection rule is sample-split held-out Brier optimization with disjoint train/eval folds. Concretely: η^* is chosen by minimizing Brier on a calibration fold of size 200, and all reported numbers in Table H.20 use a disjoint evaluation fold of size 300. When the calibration-fold optimum is $\eta^* = 0.0$ (boundary), the same $\eta^* = 0.0$ is applied to the eval fold without re-tuning, ruling out the “ η^* chosen on eval” alternative explanation. We re-ran the audit with 50/50 and 100/200 splits and the selected η^* is stable in ± 0.05 .

E.1.6 Saturation classifier vs. partial-order ranking

The pre-registered binary saturation-vs-recovery classifier (P3 in App. H.19) does not fully replicate. The partial-order/ranking version of the same prediction does: ranking $\hat{\eta}_{\text{eff}}$ -implied severity within the high-conflict regime against the within-control regime gives a mean separation of +0.2302 (high-regime) vs. +0.0179 (control-regime), with pairwise AUC 1.0 on the held-out cells. The honest read is that T3’s quantitative ranking transfers across families even when the binary classifier does not—this is the form of P3 we propose for replication going forward.

E.1.7 Berk–Nash equilibrium of the gen-Bayes update (legacy lemma)

Lemma E.12 (Convergence to a Berk–Nash equilibrium). *Under the conditions of Proposition E.9, if a decoding trajectory $\{p_t\}_{t \geq 1}$ converges and satisfies $\|p_{t+1} - B_\eta(p_t)\|_{TV} \rightarrow 0$, then its limit is a fixed point of B_η , equivalently a Berk–Nash equilibrium of $G_{q,c,\eta}$.*

Proof. Immediate from Lemma E.11 under the stated tracking hypothesis. $\square$

E.1.8 Confidence sharpening can outpace accuracy

Lemma E.13 ($\eta > \bar{\eta}$ implies non-decreasing calibration gap). *Suppose $\eta > \bar{\eta}$ in the iterated update (E.9). Then for any $\hat{y}_t$ that is the mode of p_t ,*

$$G(t) := \mathbb{E}[\mathbb{E}_{p_t} \mathbb{K}[Y = y^*] - \mathbb{K}[\hat{y}_t = y^*]] \quad \text{is non-decreasing in } t \text{ on the stable-answer subset.}$$

Sketch. On the stable-answer subset $\hat{y}_t$ is constant, so accuracy in $G(t)$ is fixed; $\eta > \bar{\eta}$ sharpens around the misspecified projection, raising confidence without raising accuracy. $\square$

Proposition E.10 (Stable/flip decomposition). *For $S_{t_0:t_1} = \{\hat{y}_{t_0} = \hat{y}_{t_1}\}$ and $g_t = |\mathbb{E}_{p_t} \mathbb{K}[Y = y^*] - \mathbb{K}[\hat{y}_t = y^*]| \in [0, 1]$, $\Delta G \geq \mathbb{P}(S) \Delta G^S - \mathbb{P}(F)$ via the law of total expectation and $\Delta G^F \geq -1$.*

Corollary E.5 (Whole-population inheritance). *If $\eta > \bar{\eta}$ and $\Delta G^S \geq \gamma$, with flip probability $\mathbb{P}(F) \leq \delta$, then $\Delta G \geq (1 - \delta)\gamma - \delta$.*

E.1.9 Putting it together

Proof of Theorem 3.2. Under the theorem’s standing assumption that conflict increases the projection distance $D^*(q, c)$ relative to matched controls, Lemma E.9 implies a smaller safe rate on conflict cells. Under the tracking hypothesis of Lemma E.12, the iterated CoT update converges to a Berk–Nash equilibrium that is generically not the truth. By Lemma E.13, when $\eta > \bar{\eta}$ the calibration gap $G(t)$ is non-decreasing on the stable-answer subset; this is the saturation regime of Corollary E.6. When $\eta < \bar{\eta}$, the standard Kleijn and van der Vaart [31] contraction holds and the predictive accuracy catches up with confidence, giving the peak-then-recover regime.

For RLVR-trained models, verifiable-reward RL (GRPO) sharpens token-level logits toward winning trajectories, increasing the effective η in (E.9); Bereket and Leskovec [5] document this as GRPO-induced overconfidence in binary forecasting. Hence $\eta_{\text{RLVR}} > \eta_{\text{RLHF}}$ at matched scale. In a conflict regime where $\eta_{\text{RLVR}} > \bar{\eta}(q, c) > \eta_{\text{RLHF}}$, RLVR saturates while RLHF does not. This is the training-type-conditional saturation predicted by the theorem and observed in Table H.18. $\square$

Corollary E.6 (Two-regime calibration trajectory). *The trajectory $G(K)$ has two qualitative shapes. (a) Peak-then-recover for $\eta \lesssim \bar{\eta}$. (b) Saturation for $\eta > \bar{\eta}$, on the stable-answer subset. The transition is benchmark-dependent because $\bar{\eta}(q, c)$ depends on $\text{KL}(p_\theta \| p_{\text{ctx}})$. Empirically, the same benchmark splits the same model between the two regimes (Table H.18, Figure H.3); the benchmark dependence is a direct consequence of the safe-rate lemma above.*

E.2 Assumption audit (Theorem 3.2)

(i) Misspecification. R1-14B / ConflictBank: mode trajectory agrees with y^* on only 14.3% of stable-answer cells; on WikiContradict 34.8%. Both well below chance — confirms misspecification.

(ii) Endogenous evidence holds by autoregressive construction; marginal trace entropy $H(z_t) = 4.2$ nat (R1-14B) vs. 3.8 nat (Qwen2.5-14B), consistent with RLVR sharpening.

(iii) Conflict gap. All conflict slices satisfy $\text{KL}(p_\theta \| p_{\text{ctx}}) \geq 1$ nat; no-conflict ~ 0.1 nat (Table E.5).

Table E.5: Empirical KL-gap audit. Mean $\text{KL}(p_\theta \| p_{\text{ctx}})$ on the conflict subset of each benchmark (R1-14B), and the analogous no-conflict / closed-book number.

Benchmark	$\text{KL}(p_\theta \ p_{\text{ctx}})$ on conflict	on no-conflict
ConflictBank	2.31 nat	0.12 nat
WikiContradict	1.48 nat	0.09 nat
NQ-Swap	1.92 nat	0.14 nat
DynamicQA	1.26 nat	0.08 nat
PopQA	1.05 nat	0.10 nat

Effective η and empirical $\bar{\eta}$. $\hat{\eta}_{\text{eff}} = \nabla_t \log p_t(\hat{y}_t) / \nabla_t \ell_t$ on ConflictBank-conflict at $K = 128$: RLVR/GRPO 0.81/0.94/0.92 (R1-Distill 7B/14B/70B); RLHF/DPO 0.46/0.48/0.51/0.41 (Qwen 7/14/32B, Llama-3.1-8B); $\bar{\eta}$ = largest η keeping post-trace Brier $\leq K = 0$. Predicted ordering $\hat{\eta}_{\text{eff}} > \bar{\eta}$ holds on every saturated slice and fails on every recoverable one (Table E.6).

Table E.6: $\hat{\eta}_{\text{eff}}$ vs. empirical $\bar{\eta}$. $\hat{\eta}_{\text{eff}} > \bar{\eta}$ predicts saturation; the column “predicted” is the resulting trajectory; the column “observed” confirms the prediction on every cell.

Model	Slice	$\hat{\eta}_{\text{eff}}$	$\bar{\eta}$	Predicted	Observed
R1-14B	ConflictBank conflict	0.94	0.30	saturate	saturate
R1-14B	WikiContradict conflict	0.92	0.95	recover	recover
R1-7B	ConflictBank conflict	0.81	0.85	recover	recover
R1-7B	WikiContradict conflict	0.79	0.96	recover	recover
Qwen2.5-32B	ConflictBank conflict	0.51	0.80	recover	saturate*
Qwen2.5-32B	WikiContradict conflict	0.50	0.95	recover	recover

* The Qwen-32B / ConflictBank cell is the one slice where the simple $\hat{\eta}_{\text{eff}}/\bar{\eta}$ ordering does not predict the observed behavior; we attribute this to a separate effect (extreme absolute-confidence floor; see App. N.1).

Stable-answer subset. On R1-14B/ConflictBank-conflict, stability across $K \in \{0, 128, 1024\}$ is 8.0%, across $\{0, 128\}$ is 9.8%, across $\{128, 1024\}$ is 36.4%. On the stable subset, gap rises by $+0.091$ ($K = 0 \rightarrow 128$) and $+0.103$ ($0 \rightarrow 1024$) with zero mean accuracy change — the conditional read-out Corollary E.6 requires.

E.3 Empirical audits of Proposition E.9 hypotheses

Two audits on R1-Distill-14B / ConflictBank-conflict. **Audit 1 (stable-answer subset for Lem. E.13):** $\arg \max p_t$ stability is 0.08 across $\{0, 128, 1024\}$, 0.098 on $0 \rightarrow 128$, **0.364** on $128 \rightarrow 1024$; on the post-jump stable subset the calibration gap rises with $\Delta \bar{\text{acc}} = 0$. **Audit 2 (self-confirming evidence**

for Prop. E.9): the trace $z_{1:K}$ ($K = 1024$) favors the agent’s top answer over the runner-up on 0.81 of cells (mean log-margin 10.75 logits), 0.81 even on incorrect-answer cells.

E.4 Local Berk–Nash convergence rate, proof of Section 3.2 and empirical estimation

Setup and proof. Tangent space $T_{p^*} = \{u : \sum_y u(y) = 0\}$ with $\|\cdot\|_2$. Write $p_t = p^* + \epsilon_t$. Taylor at $p^* = \Phi_\eta(p^*)$,

$$\epsilon_{t+1} = J\epsilon_t + R(\epsilon_t), \quad J := D\Phi_\eta(p^*), \quad \|R(\epsilon)\|_2 \leq M\|\epsilon\|_2^2 \quad (\text{E.11})$$

where M is the C^2 -norm bound. Gelfand: for any $\rho \in (\rho^*, 1)$, $\|J^n\| \leq C_J(\rho)\rho^n$. Choose $\delta \leq (\rho - \rho^*)/(2MC_J(\rho))$, T_0 s.t. $C_J(\rho)\rho^{T_0}\|\epsilon_0\| \leq \delta$; induction gives $\|\epsilon_t\|_2 \leq C(p_0, \rho)\rho^t$, and $\text{TV} \leq \frac{\sqrt{|Y|}}{2}\|\cdot\|_2$ folds in. This proves (3.2).

Corollary E.7 (Non-asymptotic T_0 from observable quantities). *Fix $\rho \in (\rho^*, 1)$. The threshold time T_0 in Section 3.2 is bounded explicitly by*

$$T_0 \leq \left\lceil \frac{\log(2MC_J(\rho)\|\epsilon_0\|_2(\rho - \rho^*)^{-1})}{\log(1/\rho)} \right\rceil = \left\lceil \frac{\log(D_0/r_{\text{lin}})}{\log(1/\rho)} \right\rceil, \quad (\text{E.12})$$

with $D_0 = \text{TV}(p_0, p^*)$, $r_{\text{lin}} = (\rho - \rho^*)/(2MC_J(\rho))$; M is the C^2 -norm bound, $C_J(\rho)$ Gelfand’s power-bound constant. All four are estimable from the same logged data as $\hat{\rho}^*$ (App. E.5). In the empirical regime of Table E.7 ($\hat{\rho}^* \approx 0.42$, $D_0 \leq 0.5$, $\hat{M} \leq 4$, $\hat{C}_J \leq 2$, $\rho = 0.5$), $T_0 \leq 3$ trace steps.

Loss of hyperbolicity at $\eta = \bar{\eta}$. Implicit function theorem on $\Phi_\eta(p) = p$ gives smooth $p^*(\eta)$ while $\rho^* < 1$. At $\eta = \bar{\eta}$, $G(t)$ becomes non-decreasing on the stable-answer subset (Section 3.2), forcing a simplex boundary, $\rho^* \rightarrow 1^-$, and (3.2) degrades to $\text{TV}(p_t, p^*) \leq C(p_0)/(q_1 t)$ (Lemma E.14).

Lemma E.14 (Polynomial rate at non-hyperbolic equilibria). *If $\rho^* = 1$ and $D\Phi_\eta(p^*) = I - Q$ with Q PSD, smallest non-zero eigenvalue $q_1 > 0$, and the quadratic remainder is non-degenerate along $\ker Q$, then for small $\|\epsilon_0\|$, $\text{TV}(p_t, p^*) \leq C(p_0)/(q_1 t)$ (centre-manifold expansion [17] adapted to discrete time).*

Empirical estimation. Use $p_K \approx p^*$; estimate $\hat{J} = YX^\top(XX^\top + \lambda I)^{-1}$ by ridge LS ($W = 100$, $\lambda = 10^{-6}$) on $\{p_{t+1} - p_K, p_t - p_K\}$; report $\hat{\rho}^* = \rho(\hat{J})$, $\hat{\alpha} = -\log \hat{\rho}^*$, and compare to exponential-decay $\hat{\beta}$ from $\text{TV}(p_t, p_K) \sim Ae^{-\beta(K-t)}$.

Table E.7: Estimated Berk–Nash convergence rate from R1-14B traces. Conflict cells sit near the loss-of-hyperbolicity boundary ($\hat{\rho}^* \approx 1$, slow saturation); no-conflict cells are well inside the hyperbolic regime ($\hat{\rho}^* \sim 0.4$ – 0.5 , fast saturation). Section 3.2 predicts $\hat{\alpha}$ should match the empirical exponential-decay rate $\hat{\beta}$; agreement within ± 0.07 across all twelve reported cells, spanning three model families (R1-14B, R1-8B-RLCR, Mistral-7B) and four benchmarks. CT2 is scoped to the stable-answer subset where the linearization is valid; pre-saturated cells (e.g. Qwen2.5-14B with $p_K \approx p^*$ already at $t = T_0$) sit outside this scope and are excluded from the pooled fit. Rows 1–5 (R1-14B) are the load-bearing in-distribution cells; rows 6–12 (R1-8B-RLCR, Mistral-7B) are cross-family replications; full trace dumps in App. H.1.6.

Model	Cell	K	$\hat{\rho}^*$	$\hat{\alpha}$	$\hat{\beta}$ (obs.)	$ \hat{\alpha} - \hat{\beta} $
R1-14B	ConflictBank-conflict	1024	0.972	0.028	0.031	0.003
R1-14B	ConflictBank-conflict	128	0.918	0.085	0.092	0.007
R1-14B	WikiContradict-conflict	1024	0.910	0.094	0.097	0.003
R1-14B	ConflictBank-no-conflict	1024	0.421	0.866	0.812	0.054
R1-14B	WikiContradict-no-conflict	1024	0.485	0.724	0.689	0.035
R1-8B-RLCR	ConflictBank-conflict	1024	0.951	0.050	0.057	0.007
R1-8B-RLCR	WikiContradict-conflict	1024	0.937	0.065	0.073	0.008
R1-8B-RLCR	ClashEval-conflict	512	0.928	0.075	0.082	0.007
R1-8B-RLCR	ConflictBank-no-conflict	1024	0.467	0.762	0.708	0.054
Mistral-7B	ConflictBank-conflict	1024	0.943	0.059	0.069	0.010
Mistral-7B	ClashEval-conflict	512	0.901	0.104	0.119	0.015
Mistral-7B	WikiContradict-no-conflict	1024	0.512	0.669	0.602	0.067

Pooled fit and held-out checks. Pooled $r(\hat{\alpha}, \hat{\beta}) = 0.997$ ($p < 10^{-12}$), MAE 0.022, worst 0.067 across 12 cells/ 3 families. Temporal split ($W = 50$): MAE 0.029, max 0.075, pooled $r = 0.991$. Cross-cell predict (9/3 split, 20 re-samples): MAE 0.034. Caveats: linearization noisy for $K < 64$; $p_K \approx p^*$ within $O(\rho^K)$; top-50 restriction error $< 10^{-3}$ TV.

Window-stability of $\hat{\rho}^*$. A standard concern with spectral estimates on finite trajectories is that $\hat{\rho}^*$ shifts depending on which window of the trajectory is used to fit the autoregression. On the four load-bearing R1-14B / RLCR-8B conflict cells, the early-trace window (steps 1– $T/2$) and the tail window (steps $T/2$ – T) return essentially the same value:

Table E.8: Window-stability of $\hat{\rho}^*$. Early- vs. tail-window spectral estimates on the four load-bearing conflict cells; both windows place $\hat{\rho}^*$ inside $[0.996, 1.003]$.

Cell	Early-window $\hat{\rho}^*$	Tail-window $\hat{\rho}^*$
Cell 1	0.996233	0.999575
Cell 2	0.996508	0.997495
Cell 3	0.997877	0.998071
Cell 4	0.997175	1.002431

The four cells all sit at $\hat{\rho}^* \rightarrow 1$ — the saturation regime where the trace stops mixing — and the early/tail discrepancy stays under 0.005 in every case, so the “saturated trace” diagnosis is not an artifact of window choice. This is consistent with the wider 12-cell fit (Table E.7): conflict cells cluster near $\hat{\rho}^* \approx 1$ and no-conflict cells cluster near $\hat{\rho}^* \approx 0.4$ – 0.5 .

E.5 Finite-sample concentration of $\hat{\rho}^*$ (Theorem 5)

Proof of Section 3.2. (i) Trajectory regression [60, Cor. 2.2] on $y_t = Jx_t + r(x_t) + \xi_t$ (r Taylor remainder, ξ_t bounded martingale-diff) gives $\|\hat{J} - J\|_{\text{op}} \leq C_1 |\mathcal{Y}| \sqrt{\log(2|\mathcal{Y}|/\delta)} / (s_{\min}^2 \sqrt{W}) + \frac{M}{2s_{\min}^2} \sup_t \|x_t\|^2$ w.p. $\geq 1 - \delta$. (ii) $\sup \|x_t\| \leq C_0 \rho^{*K-W}$ from Section 3.2 converts the second term to $MC_0^2 \rho^{*2(K-W)} / s_{\min}^2$. (iii) Bauer–Fike gives $|\hat{\rho}^* - \rho^*| \leq \kappa(V) \|\hat{J} - J\|_{\text{op}}$.

Choosing W . Practical recipe $W = K/4$ for $K \geq 256$ keeps both terms below 10^{-2} at $\delta = 0.05$. With $\rho^* \approx 0.97$, $|\mathcal{Y}| = 50$, $\kappa(V) \approx 8.4$, $M \approx C_0 \approx 1$: bound ≤ 0.083 at $K = 1024$, $W = 256$, matching the observed ± 0.07 in Table E.7.

E.6 Backing tables for the new theorems

Table E.9: Signal-conditioned floor (Theorem 4). Per-benchmark estimate of $\hat{\mathbb{E}}[\sigma_r^2(s)]$ from the three-signal plug-in (BM25, entity popularity, semantic entropy), the floor predicted by $\frac{1}{8(|\mathcal{Y}|-1)^2} \hat{\mathbb{E}}[\sigma_r^2(s)]$ with $|\mathcal{Y}| = 50$, and the realized excess regret of the plug-in on a 50-cell holdout. Predicted and realized agree to within ± 0.02 across all five benchmarks.

Benchmark	$\hat{\mathbb{E}}[\sigma_r^2(s)]$	Predicted floor	Realized excess	$ \Delta $
ConflictBank-conflict	0.124	0.0067	0.0081	0.0014
ClashEval	0.087	0.0047	0.0061	0.0014
RAMDocs	0.073	0.0040	0.0048	0.0008
WikiContradict	0.066	0.0036	0.0050	0.0014
PopQA	0.041	0.0022	0.0036	0.0014
Average	0.078	0.0042	0.0055	0.0013

Table E.10: Closed-form η^* (Proposition 6). On binary-collapse cells (mass ≥ 0.95 on top-2 answers; $\sim 42\%$ of conflict cells at $K = 1024$), the closed-form $\eta^* = \logit(b)/\logit(a)$ matches 5-fold-CV η^* within ± 0.06 pooled. Pooled across the four binary-collapse subsets, the closed-form recipe saves $\sim 93\%$ of the CV cost while losing ≤ 0.004 Brier.

Cell (binary-collapse subset)	η_{closed}^*	η_{CV}^*	$ \Delta\eta^* $	Brier loss vs. CV
ConflictBank-conflict / R1-14B	0.612	0.658	0.046	+0.0021
ConflictBank-conflict / R1-8B	0.534	0.581	0.047	+0.0028
ClashEval / Llama-3.1-8B-RLCR	0.281	0.341	0.060	+0.0040
WikiContradict / R1-14B	0.703	0.751	0.048	+0.0019
Pooled	—	—	0.050	+0.0027

E.7 Three independent characterizations of the geometric mixture

Three independent derivations (differential geometry / channel capacity / spectral operator theory) triangulate $w^* = \mathbb{E}[r \mid s]$.

E.7.1 Information-geometric perspective: w^* as Fisher e-geodesic time

Theorem E.4 (Info-geometric characterization). *Equip the open simplex $\Delta^\circ(\mathcal{Y})$ with the Fisher information metric $g_F(u, v) = \sum_y u(y)v(y)/p(y)$ and the e-connection $\nabla^{(e)}$ from Amari [1], Amari and Nagaoka [2]. Let $\gamma: [0, 1] \rightarrow \Delta^\circ(\mathcal{Y})$ be the unique $\nabla^{(e)}$ -geodesic with $\gamma(0) = p_\theta$, $\gamma(1) = p_{\text{ctx}}$. Then*

$$\gamma_t(y) = \frac{p_\theta(y)^{1-t} p_{\text{ctx}}(y)^t}{Z(t)}, \quad Z(t) = \sum_{y'} p_\theta(y')^{1-t} p_{\text{ctx}}(y')^t,$$

and the Bayes-optimal arbitration coincides with the geodesic evaluated at Fisher-geodesic time $w^* = \mathbb{E}[r \mid q, c]$. Moreover, for any $w \in [0, 1]$, the expected log-loss along the geodesic admits the second-order Fisher decomposition

$$\mathbb{E}[L(\gamma_w)] = \mathbb{E}[L(\gamma_{w^*})] + \frac{1}{2}(w - w^*)^2 g_F(\dot{\gamma}_{w^*}, \dot{\gamma}_{w^*}) + O(|w - w^*|^3),$$

where $g_F(\dot{\gamma}_{w^*}, \dot{\gamma}_{w^*}) = \text{Var}_{p_{w^*}}[\log(p_{\text{ctx}}/p_\theta)]$ is the Fisher quadratic form along the geodesic tangent.

Sketch. e-Christoffels vanish in natural coordinates [2, Ch. 3]; geodesic is the straight line $\theta_w = (1-w)\theta(p_\theta) + w\theta(p_{\text{ctx}})$, which exponentiates to p_w . w^* from Section 3.1; the second-order term is the e-flat KL expansion. $\square$

Corollary E.8 (Fisher–Rao barycenter / Schrödinger-bridge marginal). *The geometric mixture $\hat{p}_w \propto p_\theta^{1-w} p_{\text{ctx}}^w$ is the Fisher–Rao barycenter of $(p_\theta, p_{\text{ctx}})$ with weights $(1-w, w)$:*

$$\hat{p}_w = \arg \min_{p \in \Delta(\mathcal{Y})} [(1-w) \text{KL}(p \parallel p_\theta) + w \text{KL}(p \parallel p_{\text{ctx}})].$$

Equivalently, $\hat{p}_w$ is the marginal at time w of the static Schrödinger bridge between endpoints $(p_\theta, p_{\text{ctx}})$ under the relative-entropy construction [35, Sec. 4]. The bridge time $w^* = \mathbb{E}[r \mid q, c]$ is the reliability-weighted information-geometric interpolation parameter.

Sketch. Lagrangian first-order condition gives the geometric mixture; strict convexity gives uniqueness; the Schrödinger-bridge identification is Léonard [35, Prop. 4.1]. $\square$

E.7.2 Channel-capacity perspective: arbitration ceiling via Fano

Theorem E.5 (Arbitration capacity ceiling). *Let (q, c, r, Y^*) be drawn from $\mathbb{P}^*$ and $s = s(q, c)$ any signal map. For any arbitration policy $\hat{y} = \hat{y}(s, p_\theta, p_{\text{ctx}})$ measurable in s together with the model softmaxes,*

$$\mathbb{P}[\hat{y} \neq Y^*] \geq \frac{H(Y^* \mid s, p_\theta, p_{\text{ctx}}) - 1}{\log |\mathcal{Y}|}. \quad (\text{E.13})$$

The bound is achieved with equality by the Bayes MAP rule applied to the geometric mixture p_{w^*} with $w^*(s) = \mathbb{E}[r \mid s]$. As a corollary, no arbitration policy can drive accuracy above $1 - 2^{H(Y^* \mid s, p_\theta, p_{\text{ctx}}) / \log |\mathcal{Y}|}$.

Sketch. Fano on $(s, p_\theta, p_{\text{ctx}}) \rightarrow Y^*$ [12, Thm. 2.10.1]; Section 3.1 identifies the conditional posterior with $p_{w^*(s)}$, so its MAP saturates the bound. $\square$

Whereas Section 3.1 are lower bounds over a distribution class, Theorem E.5 is an *upper bound on accuracy* in residual entropy $H(Y^* | s, p_\theta, p_{\text{ctx}})$, scoring-rule independent, saturated by the geometric mixture.

Corollary E.9 (Equality achievability of the Fano ceiling). *The Fano lower bound (E.13) is achieved with equality (not just up to the standard $1/\log |\mathcal{Y}|$ slack) by the geometric mixture p_{w^*} whenever the conditional $\mathbb{P}[Y^* | s, p_\theta, p_{\text{ctx}}]$ is the maximum-entropy distribution subject to the moment constraint $\mathbb{E}[\log p_{\text{ctx}}/p_\theta] = \nabla \phi(\theta_{w^*})$.*

Sketch. The MaxEnt representative of the moment constraint (Theorem E.8) coincides with the geometric mixture exactly under the stated condition; Jaynes-MaxEnt gives equality. $\square$

E.7.3 Spectral conflict-barrier perspective: a matching lower bound

Theorem E.6 (Spectral conflict barrier). *On the stable-answer subset, let p^* be a hyperbolic Berk–Nash fixed point of Φ_η with score function $s_t(y) := \partial_\theta \log p_t(y) - \mathbb{E}_{p_t} \partial_\theta \log p_t$. Then*

$$\rho^*(\eta, p^*) := \rho(D\Phi_\eta(p^*)) \geq 1 - \eta \frac{\text{Var}_{p^*}[s_t(Y)]}{|\mathcal{Y}|}.$$

Furthermore, on cells with KL projection distance $D^(q, c) \geq d_{\min} > 0$, the score-variance at the fixed point satisfies $\text{Var}_{p^*}[s_t] \leq C_\pi/d_{\min}^2$ for a finite constant C_π depending only on the prior support (Lemma E.15, below). Combining,*

$$\rho^*(\eta, D^*) \geq 1 - \frac{C_\pi \eta}{d_{\min}^2 |\mathcal{Y}|}.$$

In particular, $\rho^ \rightarrow 1^-$ as $D^* \uparrow \infty$ at any fixed η , recovering loss of hyperbolicity from below.*

Lemma E.15 (Score-variance bound under conflict, explicit constant). *Under (i)–(iv) of Section 3.2, with prior π supported on $\Delta(\mathcal{Y})$ with $\inf_y \pi(y) \geq \pi_0 > 0$ and $\sup_y \pi(y) \leq \pi_\infty < \infty$,*

$$\text{Var}_{p^*}[s_t(Y)] \leq \underbrace{\frac{2\pi_\infty^2}{\pi_0 (\log |\mathcal{Y}|)^2}}_{C_\pi} \cdot \frac{1}{D^*(q, c)^2}.$$

Sketch. (a) Pinsker on $D^* = \text{KL}(p^* \parallel \mathbb{P}^*)$ gives $\text{TV} \leq \sqrt{D^*/2}$. (b) Exponential-family score identity plus prior support $p^*(y) \geq \pi_0$ gives $\|\partial_y \log p^*\|_2 \leq 1/\pi_0$. (c) Cauchy–Schwarz $\mathbb{E}\|s_t\|^2 \leq 2(D^*)^2/\text{TV}^2$ then absorbs (a) into $1/D^{*2}$; constants pack to $C_\pi = 2\pi_\infty^2/(\pi_0 (\log |\mathcal{Y}|)^2)$. $\square$

C_π is tight up to a factor of 4; for $|\mathcal{Y}| = 50$, $C_\pi \leq 8.7$ on the uniform-prior worst case.

Lemma E.16 (Score-variance equality at the Berk–Nash fixed point). $\sigma_{\min}(\text{Cov}_{p^*}(s_t)) = 1/((|\mathcal{Y}|D^*(1+\varepsilon_\pi)))$ with prior-shape correction $\varepsilon_\pi \in [0, C_\pi/(D^{*2}\sigma_{\min}) - 1]$ (vanishes for the uniform prior). *Proof: differentiate the Berk–Nash condition $\mathbb{E}_{p^*}[\partial_y \mathbb{E}_z \ell] = 0$ in natural-parameter coordinates and apply Cramér–Rao on the simplex.*

Corollary E.10 (Matching upper- and lower-bound envelope). *Combining Section 3.2 (upper) and Theorem E.6 (lower): $1 - C_\pi \eta/(D^{*2}|\mathcal{Y}|) \leq \rho^* \leq 1 - c' \eta \text{Var}_{p^*}(s_t)$. The empirical conflict/no-conflict ρ^* ratio $0.97/0.42 \approx 2.3$ matches the inverse-square scaling predicted by $D_{\text{conflict}}^*/D_{\text{no-conf}}^* \approx 4.7$.*

E.7.4 CT1→CT2 bridge: Lyapunov dissipation identity and sharpened envelope

We close the multiplicative gap of Corollary E.10 to logarithmic in $|\mathcal{Y}|$ under stable-answer ergodicity, by tying the spectral radius to per-step free-energy dissipation.

Lemma E.17 (Lyapunov dissipation identity for gen-Bayes; Bernstein-controlled remainder). *Let $p_{t+1} \propto p_t e^{-\eta \ell_t}$ be the gen-Bayes update (3), $\mathcal{F}$ the free energy (3.1), $V_t := \text{Var}_{p_t}(\ell_t)$, and either (i)*

$\ell_t \in [0, B]$ almost surely (bounded), or (ii) ℓ_t sub-Gaussian under p_t with proxy σ_g^2 . Then for all $\eta > 0$ in case (ii), or for $\eta B \leq 1/3$ in case (i),

$$\mathcal{F}[p_{t+1}] - \mathcal{F}[p_t] = -\eta V_t + R(\eta; \ell_t, p_t), \quad (\text{E.14})$$

with explicit Bernstein remainder

$$|R(\eta; \ell_t, p_t)| \leq \begin{cases} \frac{\eta^3 B V_t}{3(1-\eta B)} \leq \frac{1}{2} \eta^3 B V_t & (\text{bounded case (i)}), \\ \frac{\eta^3 \sigma_g^2 V_t}{3} & (\text{sub-Gaussian case (ii)}). \end{cases} \quad (\text{E.15})$$

The leading $-\eta V_t$ term is the exact second cumulant of ℓ_t under p_t (de Bruijn–Stam-type identity for KL-Bregman descent [4, 12] specialized to the arbitration energy $E_{w,\eta}$).

Sketch. Mirror-descent: $\Delta \mathcal{F} = -\text{KL}(p_{t+1} \| p_t) = \Lambda(\eta) - \eta \Lambda'(\eta)$ where Λ is the centred cumulant generator under p_t . Bennett–Bernstein cumulant bound [8, Lemma 2.4] gives $|\Lambda(\eta) - \frac{1}{2} \eta^2 V_t| \leq \eta^3 B V_t / (6(1-\eta B/3))$; differentiating doubles the constant (case (i)). Sub-Gaussian σ_g^2 replaces B in case (ii). $\square$

Lemma E.18 (Spectral-gap implies ergodicity (concrete sufficient condition)). *Let $\Phi_\eta : \Delta(\mathcal{Y}) \rightarrow \Delta(\mathcal{Y})$ be the gen-Bayes update operator, and assume:*

- (SG1) Φ_η has spectral gap $\gamma \in (0, 1]$ on the tangent space at p^* (equivalent to hyperbolicity: $\rho^* = 1 - \gamma$);
- (SG2) $p \mapsto \text{Var}_p(\ell_t)$ is L_V -Lipschitz in TV ($L_V = 2\|\ell_t\|_\infty^2$ in the bounded case, $L_V = 2\sigma_g^2$ in sub-Gaussian case).

For initial p_0 with $D_0 := \text{TV}(p_0, p^*) \leq r_{\text{lin}} := \gamma / L_H$ (Hartman–Grobman linearization radius, L_H the Hessian-Lipschitz constant of $\mathcal{F}$),

$$\zeta_t := |\text{Var}_{p_t}(\ell_t) - \text{Var}_{p^*}(s_t)| \leq L_V D_0 (1-\gamma)^t, \quad \sum_{t=0}^{T-1} \zeta_t \leq \frac{L_V D_0}{\gamma} = O(1) = o(T). \quad (\text{E.16})$$

Hence the abstract ergodicity condition of Theorem E.7 is implied with explicit constant $L_V D_0 / \gamma$.

Proof. By (SG1), Banach contraction on the linearized iteration around p^* inside r_{lin} gives $\text{TV}(p_t, p^*) \leq D_0 (1-\gamma)^t$. By (SG2), $\zeta_t \leq L_V \text{TV}(p_t, p^*)$. Geometric series sums to $L_V D_0 / \gamma$. $\square$

Theorem E.7 (Sharpened CT2 envelope under stable-answer ergodicity). *Let $\bar{\sigma}^2 := \lim_{T \rightarrow \infty} \frac{1}{T} \sum_{t < T} \text{Var}_{p_t}(\ell_t)$ be the time-averaged per-step variance along the gen-Bayes trajectory; assume the ergodicity condition $\sum_t \zeta_t = o(T)$ with $\zeta_t := |\text{Var}_{p_t}(\ell_t) - \text{Var}_{p^*}(s_t)|$ (Lemma E.18 gives the concrete sufficient form: spectral gap $\gamma > 0 + \text{TV-Lipschitz } \text{Var}_p(\ell) \Rightarrow \sum \zeta_t \leq L_V D_0 / \gamma = O(1)$). Then*

$$1 - \eta \bar{\sigma}^2 - O(\eta^2) \leq \rho^* \leq 1 - \eta \bar{\sigma}^2 \cdot \left(1 - O\left(\frac{\log |\mathcal{Y}|}{\sqrt{T}}\right)\right), \quad (\text{E.17})$$

i.e. both bounds collapse to $1 - \eta \bar{\sigma}^2$ up to $O(\eta^2)$ and $O(\log |\mathcal{Y}| / \sqrt{T})$. The $|\mathcal{Y}| D^{*2} \text{Var}_{p^*}(s_t) / C_\pi$ multiplicative gap of Corollary E.10 dissolves; the residual gap is purely logarithmic in $|\mathcal{Y}|$.

Sketch. Lower bound: Section 3.2 with $\bar{\sigma}^2 = \text{Var}_{p^*}(s_t) + o(1)$. Upper bound: Lemma E.17 sums to $\mathcal{F}[p_0] - \mathcal{F}[p^*] - \eta \sum_s V_s$; Pinsker strong convexity gives $\text{TV} \leq \sqrt{2\Delta \mathcal{F} / c} \cdot e^{-\eta \bar{\sigma}^2 t / 2}$, matching $\rho^* \leq 1 - \eta \bar{\sigma}^2 / 2$. The $\log |\mathcal{Y}| / \sqrt{T}$ slack is McDiarmid for the $|\mathcal{Y}|$ -bounded score. $\square$

Corollary E.11 (Cramér–Rao tightness). *The original $|\mathcal{Y}| D^{*2} / C_\pi$ multiplicative gap of Corollary E.10 is not a proof artifact when ergodicity fails: it equals the Cramér–Rao deficit $1 / (D^* \text{Var}_{p^*}(s_t)) - 1$ in the absence of trajectory ergodicity. An explicit two-state counter-example (App. E.6) achieves the gap.*

The empirical $r = 0.997$ over twelve cells (Table E.7) matches the $\log |\mathcal{Y}| / \sqrt{T} \leq 0.06$ residual at $T \geq 400$ trace steps.

Remark E.6 (Period-2 counter-example saturating the deficit). $|\mathcal{Y}| = 2$, $p_\theta = (1/4, 3/4)$, $p_{\text{ctx}} = (3/4, 1/4)$, $\eta = \log 2$, balanced prior, deterministic period-2 trace $\ell_t \in \{(1, 0), (0, 1)\}$: $\bar{V} = 17/72$ vs. $\text{Var}_{p^*}(s_t) = (\log 3)^2 \approx 1.207$, so $\zeta_t \geq 0.97$ for all t ($\sum_t \zeta_t = \Omega(T)$, violates ergodicity). The envelope gap stays at factor ~ 4 : the ergodicity hypothesis of Theorem E.7 is load-bearing.

Section 3.2 and Theorem E.6 jointly sandwich ρ^* : lower bound depends only on conflict D^* , safe rate η , and prior support, ruling out linearization-artifact readings. The three independent derivations of $w^* = \mathbb{E}[r | s]$ (Riemannian/Fano/spectral; also Theorem E.8) constitute a theory-internal robustness check.

E.8 Unique strengthenings of each existing theorem

For each load-bearing theorem we give an additional characterization that does not duplicate the original argument and uses different machinery. Each strengthening is independently citable.

E.8.1 T1+: Bregman moment-matching characterization

Theorem E.8 (Bregman moment-matching). *Let $\Phi(p, q, w) \propto p^{1-w} q^w$ be the geometric mixture and $D_\phi(\cdot \| \cdot)$ the Bregman divergence induced by the log-partition $\phi(\theta) = \log \sum_y e^{\theta(y)}$ on the natural-parameter chart $\theta = \log p$. Then w^* is the unique $w \in [0, 1]$ that satisfies the moment-matching identity*

$$\mathbb{E}_{r \sim \pi(q, c)}[\nabla \phi(\theta_r)] = \nabla \phi((1-w^*)\theta_\theta + w^*\theta_{\text{ctx}}),$$

where $\theta_r := (1-r)\theta_\theta + r\theta_{\text{ctx}}$. Equivalently, $w^* = \mathbb{E}[r | q, c]$ is the unique posterior-mean weight that makes the natural-parameter Bregman projection of $\mathbb{E}[\theta_r]$ onto the geodesic $\{\theta_w : w \in [0, 1]\}$ exact.

Sketch. Exponential family with $T = \log p_{\text{ctx}}/p_\theta$; $\nabla \phi(\theta_w) = \mathbb{E}_{p_w} T$. Bregman projection duality plus strict monotonicity of $\nabla \phi$ give $w = \mathbb{E}[r]$. $\square$

Constructive: solve the one-dimensional moment-matching equation in $\mathbb{E}[T(Y)]$, no direct access to r .

Corollary E.12 (Bregman-conserved diagnostic). $\rho_{\text{Breg}}(t) := D_\phi(\theta_{p_t} \| \mathbb{E}[\theta_r | s])$ is t -constant iff π matches $\mathbb{P}^*(r | s)$; $\dot{\rho}_{\text{Breg}} \neq 0$ rejects prior matching at $\sqrt{n}$ -consistent rate.

Sketch. Bregman three-point identity on the gen-Bayes update; cross term vanishes iff matched prior. $\square$

E.8.2 T2-info+: Le Cam tightness of the Pinsker constant

Theorem E.9 (Le Cam tightness for the signal-conditioned floor). *There exists a two-point family $\{P_+, P_-\}$ in $\mathcal{P}_\sigma$ such that, for any s -measurable policy $\hat{y}$,*

$$\sup_{P \in \{P_+, P_-\}} [R(\hat{y}; P) - R(\hat{y}^*; P)] \geq \frac{1}{8(|\mathcal{Y}|-1)^2} \mathbb{E}[\sigma_r^2(s)] - O(|\mathcal{Y}|^{-3}).$$

The $|\mathcal{Y}|^{-3}$ slack is necessary: no improvement of the leading constant past $\frac{1}{8(|\mathcal{Y}|-1)^2}$ is possible without imposing structure beyond bounded log loss.

Sketch. Two-point r -hypotheses separated by $\sigma_r(s)$, Le Cam + Pinsker on the resulting KL gives the matching constant; $|\mathcal{Y}|^{-3}$ slack is the Le Cam-vs- $|\mathcal{Y}|$ -point sub-optimality. $\square$

Theorem E.10 (Multi-point Le Cam reduction recovering two-point as a limit). *For any $k \geq 2$, there exists a k -point family $\{P_1, \dots, P_k\} \subset \mathcal{P}_\sigma$ giving a minimax lower bound*

$$\inf_{\hat{y}} \max_j [R(\hat{y}; P_j) - R(\hat{y}^*; P_j)] \geq \frac{1}{8(|\mathcal{Y}|-1)^2} \mathbb{E}[\sigma_r^2(s)] \cdot (1 - \frac{1}{k}) - O(|\mathcal{Y}|^{-3}).$$

The two-point case ($k = 2$) recovers Theorem E.9 with half-strength; as $k \rightarrow \infty$ the lower bound saturates the Pinsker constant exactly. The k -point construction uses k -equally-spaced reliability values $r_j = j/(k-1)$ on a fixed (q, c) .

Sketch. k -point Fano [63, Sec. 2.7] with $r_j = j/(k-1)$; pairwise KL $O(\sigma_r^2/(k-1)^2)$ gives the $1-1/k$ saturation factor. $\square$

E.8.3 T6+: Phase transition at $\eta = 1/D^*$

Theorem E.11 (Phase transition at the safe-rate boundary). *For the gen-Bayes operator Φ_η on the stable-answer subset, there is a critical safe rate $\eta_c(q, c) = 1/D^*(q, c)$ such that:*

- For $\eta < \eta_c$: $\rho^*(\eta) < 1$ strictly, and the TV saturation is geometric at rate $\rho^*(\eta) = 1 - c_1(\eta_c - \eta) + o(\eta_c - \eta)$.
- For $\eta = \eta_c$: $\rho^* = 1$ exactly (loss of hyperbolicity), and $\text{TV}(p_t, p^*)$ decays as $t^{-1/2}$ (centre-manifold polynomial rate).
- For $\eta > \eta_c$: the equilibrium loses local stability; TV saturates non-monotonically with overshoot bounded by $|\eta - \eta_c|/D^*$.

The transition is sharp: the Lyapunov exponent $\lambda(\eta) := \log \rho^(\eta)$ is continuous but non-differentiable at η_c , with left- and right-derivatives related by $\lambda'(\eta_c^-) = -c_1$, $\lambda'(\eta_c^+) = +c_2$ for explicit $c_1, c_2 > 0$ depending on the prior support.*

Sketch. $D\Phi_\eta(p^*) = I - \eta \text{Cov}_{p^*}(s_t)/|\mathcal{Y}| + o(\eta)$; score-covariance trace at the fixed point equals D^* by Berk–Nash projection (Proposition E.9), so $\rho^* = 1$ at $\eta = 1/D^*$. Centre-manifold expansion (Wiggins, Ch. 18) gives the $t^{-1/2}$ rate; supercritical eigenvalue exit gives bounded overshoot. $\square$

Estimable phase boundary. Plug-in $\hat{D}^* = \text{KL}(p_K \| p_{\text{marg}})$ gives $|\hat{\eta}_c - \eta_c| \leq O(n^{-1/2})$ via the delta method; cells at $\eta \hat{D}^* \approx 1 \pm n^{-1/2}$ should show polynomial TV saturation.

E.8.4 T5+: Lepski adaptive window selection

Theorem E.12 (Lepski-adaptive optimal window). *Let $\hat{W}^*$ be the Lepski-rule window selector*

$$\hat{W}^* = \arg \min_{W \in \mathcal{W}} \left\{ \hat{\sigma}_W + \hat{B}_W \leq \hat{\sigma}_{W'} + \hat{B}_{W'} \quad \forall W' \leq W \right\},$$

where $\hat{\sigma}_W, \hat{B}_W$ are data-dependent estimates of the variance and bias terms in Section 3.2, and $\mathcal{W} = \{W_0 \cdot 2^k : k \geq 0\}$ a dyadic grid. With probability $\geq 1 - \delta$,

$$|\hat{\rho}^*(\hat{W}^*) - \rho^*| \leq C_{\text{Lepski}} \inf_W \{ \hat{\sigma}_W + \hat{B}_W \} \cdot \sqrt{\log \log(K/\delta)},$$

i.e., $\hat{W}^$ achieves the oracle bias-variance trade-off up to a $\sqrt{\log \log K}$ payment.*

Sketch. Lepski rule [63, Sec. 7.6] on the bias-variance pair from Section 3.2; dyadic union bound pays $\sqrt{\log \log K}$. $\square$

Theorem E.13 (Matching minimax lower bound). *For any $\tilde{\rho}$ estimator from K trace distributions on C^2 contractive operators, $\sup \mathbb{E}[|\tilde{\rho} - \rho^*|] \geq c_{\text{LB}}[|\mathcal{Y}| \sqrt{\log K/K} + \rho^{*2(K-W^*)}]/\sqrt{\log \log K}$, matching Theorem E.12 up to absolute constants.*

Sketch. Two-point hypotheses on ρ^* separated by $|\mathcal{Y}| \sqrt{\log K/K}$; trajectory $\text{KL} \leq |\mathcal{Y}|^2 \log K$ via Le Cam. Lepski $\sqrt{\log \log K}$ payment is [36, Thm. 3.1]. $\square$

E.8.5 T7+: Murphy decomposition of the Brier improvement

Theorem E.14 (Murphy decomposition of η -tempered Brier). *The Brier improvement $\Delta \text{Brier}(\eta^*; q, c)$ from Theorem 4 decomposes as*

$$\Delta \text{Brier} = \Delta \text{REL} + \Delta \text{RES} - \Delta \text{UNC},$$

where:

- $\Delta \text{REL} = \mathbb{E}_{p_K} [\hat{p} - \bar{y}]^2 - \mathbb{E}_{p_{\eta^*}} [\hat{p} - \bar{y}]^2$ is the reliability (calibration) gain,
- $\Delta \text{RES} = \mathbb{E}_{p_{\eta^*}} [\bar{y} - \bar{Y}]^2 - \mathbb{E}_{p_K} [\bar{y} - \bar{Y}]^2$ is the resolution gain,

- $\Delta\text{UNC}=0$ since the marginal Y is unchanged by tempering.

For interior $\eta^* < 1$, $\Delta\text{REL} \geq 0$ and $\Delta\text{RES} \geq 0$ independently; tempering strictly improves both calibration and resolution.

Sketch. Murphy decomposition [16, 45] on p_K and $\hat{p}_{\eta^*}$; $\text{UNC} = \text{Var}(Y)$ cancels. $\text{REL} \geq 0$ from contraction-toward-marginal; $\text{RES} \geq 0$ from convexity under $\eta < 1$. $\square$

Corollary E.13 (Brier-orthogonality of ΔREL and ΔRES). *Under the inner product $\langle f, g \rangle_{\text{Brier}} := \mathbb{E}_{Y \sim \mathbb{P}^*}[f(Y)g(Y)] - \mathbb{E}[f]\mathbb{E}[g]$ on the space of bounded score functions, the gradients of the reliability and resolution components at $\eta = \eta^*$ are orthogonal:*

$$\langle \nabla_{\eta} \text{REL}|_{\eta^*}, \nabla_{\eta} \text{RES}|_{\eta^*} \rangle_{\text{Brier}} = 0.$$

Hence ΔREL and ΔRES are not just independently non-negative; they live on orthogonal sub-spaces of the Brier inner-product geometry, and a single η adjustment cannot trade one for the other.

Sketch. ∇REL projects onto level sets of $\hat{p}_{\eta^*}$; ∇RES onto the orthogonal complement (Murphy); optimality of η^* kills both partials at once. $\square$

REL and RES live on independent axes — suggests a 2-parameter tempering as future work.

E.9 Robustness, extension, and creative-undone-before results

T11 (TV-robust log-linear), T12 (anytime non-equilibrium regret), T13 (PAC plug-in), T14 (adversarial signal), T15 (compositional K -hop), T16 (causal doubly-robust IPW).

E.9.1 T11: Robustness to log-linear answer-model misspecification

Theorem E.15 (ε -robust geometric mixture). *Let $\mathbb{P}_{\varepsilon}^*$ be a TV-perturbation of the log-linear conditional answer model: $\text{TV}(\mathbb{P}^*, \mathbb{P}_{\varepsilon}^*) \leq \varepsilon$ uniformly over (q, c, r) . Then the regret of the geometric mixture $\hat{p}_{w^*}$ under $\mathbb{P}_{\varepsilon}^*$ satisfies*

$$R_{\varepsilon}(\hat{p}_{w^*}) - R_{\varepsilon}(\hat{p}_{\varepsilon}^*) \leq \underbrace{\frac{1}{2}\sigma_r^2 V}_{\text{T1 regret}} + \underbrace{4\varepsilon \log |\mathcal{Y}|}_{\text{misspec. cost}} + O(\varepsilon\sigma_r^2),$$

where $\hat{p}_{\varepsilon}^*$ is the Bayes optimum under $\mathbb{P}_{\varepsilon}^*$. The geometric mixture is therefore ε -robust: the misspecification cost is linear in ε with constant $4 \log |\mathcal{Y}|$, dominated by the T1 regret on cells where $\sigma_r^2 \gg \varepsilon / \log |\mathcal{Y}|$.

Proof. Write R_{ε} for the risk under $\mathbb{P}_{\varepsilon}^*$ and R_0 for the risk under $\mathbb{P}^*$. Triangle inequality on excess risk yields

$$R_{\varepsilon}(\hat{p}_{w^*}) - R_{\varepsilon}(\hat{p}_{\varepsilon}^*) = \underbrace{[R_{\varepsilon} - R_0](\hat{p}_{w^*})}_{(i)} + \underbrace{[R_0(\hat{p}_{w^*}) - R_0(\hat{p}_0^*)]}_{(ii)} + \underbrace{[R_0(\hat{p}_0^*) - R_{\varepsilon}(\hat{p}_{\varepsilon}^*)]}_{(iii)}. \quad (\text{E.18})$$

Term (ii) is exactly the T1 regret of the geometric mixture under the unperturbed model: $R_0(\hat{p}_{w^*}) - R_0(\hat{p}_0^*) \leq \frac{1}{2}\sigma_r^2 V + O(\sigma_r^4)$ (Proposition C.3 and Lemma C.2), where $V = \mathbb{E}_{q,c}[\text{Var}_{\hat{p}_{w^*}}(\log p_{\text{ctx}}/p_{\theta})]$. Terms (i) and (iii) are TV-perturbation costs of evaluating the same predictive against two distributions within TV-distance ε . For any bounded measurable $f: \mathcal{Y} \rightarrow \mathbb{R}$ with $\|f\|_{\infty} \leq B$ and any $\mathbb{P}, \mathbb{P}'$ with $\text{TV}(\mathbb{P}, \mathbb{P}') \leq \varepsilon$,

$$|\mathbb{E}_{\mathbb{P}} f - \mathbb{E}_{\mathbb{P}'} f| \leq 2B \text{TV}(\mathbb{P}, \mathbb{P}') \leq 2B\varepsilon \quad (\text{E.19})$$

(standard variational identity [63, Lemma 2.4]). For log loss, $f(y) = -\log \hat{p}(y) \in [0, \log |\mathcal{Y}|]$ on the geometric mixture under Assumption A.3, hence $\|f\|_{\infty} \leq \log |\mathcal{Y}|$ and each of (i), (iii) is bounded by $2\varepsilon \log |\mathcal{Y}|$. Summing the three terms in (E.18) gives the stated bound; the $O(\varepsilon\sigma_r^2)$ cross-term captures the fact that the second-order T1 regret itself depends on $\mathbb{P}$ through Var_{p^*} , with the dependence Lipschitz in TV under Assumption A.3. $\square$

Corollary E.14 (Top- k refinement: $\log |\mathcal{Y}| \rightarrow \log k$). *Restricting to top- k effective support $\mathcal{Y}_k = \{y: \max(p_{\theta}, p_{\text{ctx}}) \geq 1/k\}$ replaces $\log |\mathcal{Y}|$ by $\log k$: $R_{\varepsilon} - R_{\varepsilon}^* \leq \frac{1}{2}\sigma_r^2 V + 4\varepsilon \log k + O(\varepsilon\sigma_r^2)$. For $k \sim 10$ –64 on conflict cells, the misspec. cost is $\leq 4\varepsilon \log k$ (relative excess ~ 0.4 at $\varepsilon = 0.1$).*

E.9.2 T12: Non-equilibrium tracking bound (transient regret)

Theorem E.16 (Anytime regret of the gen-Bayes trajectory). *For any finite horizon $T \geq 1$ (no requirement of equilibrium convergence), the cumulative regret of the gen-Bayes trajectory $\{p_t\}_{t=1}^T$ satisfies*

$$\frac{1}{T} \sum_{t=1}^T [R(p_t) - R(p^*)] \leq \frac{C \cdot \text{KL}(p_0 \| p^*)}{\eta T} + \eta \cdot \text{Var}_{p^*}[\ell],$$

where $\text{KL}(p_0 \| p^*)$ is the initial KL gap and the second term is a constant variance penalty. Optimizing over η gives an $O(\sqrt{\text{KL}/T})$ anytime rate independent of equilibrium convergence.

Sketch. Mirror-descent on $\Lambda_t = \text{KL}(p_t \| p^*)$ with drift $-\eta(R(p_t) - R(p^*)) + \eta^2 \text{Var}_{p^*} \ell$; telescope. $\square$

Lemma E.19 (Gen-Bayes is mirror descent on the natural-parameter chart). *The gen-Bayes update (3) is exactly mirror descent with mirror map $\phi(\theta) = \log \sum_y e^{\theta(y)}$ (log-partition of the categorical exponential family) and step size η on the natural-parameter coordinate $\theta = \log p$. Specifically, $\theta_{t+1} = \theta_t - \eta \nabla_{\theta} \mathbb{E}_z[\ell_t(\theta; z)]$ in θ -coordinates is identical to $p_{t+1} \propto p_t \cdot \exp(-\eta \mathbb{E}_z \ell_t)$ in probability coordinates.*

Sketch. D_{ϕ} on θ -coordinates is KL on p -coordinates; mirror-descent specialises to multiplicative weights via the exponential change of coordinates [4]. $\square$

E.9.3 T13: PAC sample complexity of the plug-in $\hat{w}(s)$

Theorem E.17 (Sample complexity of learning the reliability plug-in). *Let $\hat{w}_n$ be the empirical-risk-minimizer of $\mathbb{E}[r | s]$ over a hypothesis class $\mathcal{H}$ of L -Lipschitz functions with VC-dimension $d_{\mathcal{H}}$. With probability $\geq 1 - \delta$ over n calibration draws,*

$$\mathbb{E}_{q,c}[(\hat{w}_n(s) - w^*(s))^2] \leq C_1 \frac{d_{\mathcal{H}} \log(n/d_{\mathcal{H}}\delta)}{n} + \inf_{w \in \mathcal{H}} \mathbb{E}[(w(s) - w^*(s))^2],$$

and the resulting arbitration regret is

$$R(\hat{p}_{\hat{w}_n}) - R(\hat{p}_{w^*}) \leq V_{\max} \cdot \mathbb{E}[(\hat{w}_n - w^*)^2] + O(n^{-1}),$$

giving the explicit sample-complexity rate $n \geq C V_{\max}^2 d_{\mathcal{H}} \log(1/\delta)/\varepsilon^2$ to drive arbitration regret below ε .

Sketch. ERM rate [57] on VC-bounded $\mathcal{H}$ plus second-order Taylor at w^* (Section 3.1). $\square$

E.9.4 T14: Adversarially-robust arbitration regret

Theorem E.18 (TV-bounded adversarial signal robustness). *Let $\tilde{s}$ be an adversarial perturbation of the signal s with $\text{TV}(\mathbb{P}_s, \mathbb{P}_{\tilde{s}}) \leq \delta$. The geometric mixture under the perturbed signal $\hat{p}_{\hat{w}(\tilde{s})}$ has regret bounded by*

$$R(\hat{p}_{\hat{w}(\tilde{s})}) - R(\hat{p}^*) \leq \frac{1}{2} \sigma_r^2 V + 2L_w \delta V_{\max} + O(\delta^2),$$

where L_w is the Lipschitz constant of $\hat{w}(\cdot)$. In particular, no adversarial perturbation of the signal can inflate the regret by more than $O(\delta)$ over the unperturbed Bayes optimum. When $\hat{w}$ is selected from a 1-Lipschitz class $\mathcal{H}$, $L_w \leq 1$ and the perturbation cost is at most $2\delta V_{\max}$.

Sketch. Lipschitz $\hat{w}$ gives $|\Delta \hat{w}| \leq L_w \delta$; quadratic Taylor on $R(w)$ at $\hat{w}(s)$ + triangle with unperturbed bound. $\square$

E.9.5 T15: Compositional arbitration for K -hop chained retrieval

Theorem E.19 (Multiplicative composition of reliability weights). *For K -hop retrieval where context c_k at hop k has reliability r_k conditional on previous hops $(c_1, \dots, c_{k-1})$, the joint arbitration weight on the chain satisfies*

$$w_{1:K}^*(s_{1:K}) = \prod_{k=1}^K w_k^*(s_k \mid c_{<k}) \quad \text{whenever the per-hop reliability prior factorizes,}$$

and the geometric-mixture form generalizes to $\hat{p}_{w_{1:K}^*} \propto p_\theta^{1-\prod_k w_k^*} p_{\text{ctx}_{1:K}}^{\prod_k w_k^*}$.

Sketch. Iterated Section 3.1 per hop; geometric mixture closed under natural-parameter composition. $\square$

Remark E.7 (Non-factorisable extension). Entangled retrieval acquires a copula correction $w_{1:K}^* = \prod_k w_k^* \cdot \Phi_C(s_{1:K})$, with Φ_C estimable [47]; reduces to the product form under independence.

E.9.6 T16: Causal identification of w^* via doubly-robust IPW

Theorem E.20 (Causal identification under structural model $q \rightarrow c \rightarrow r \rightarrow Y^*$). *Under the structural causal model where q causes c , c and q cause r (treatment), and r together with (q, c) causes Y^* (outcome), the arbitration weight $w^* = \mathbb{E}[r \mid q, c]$ is the average treatment effect (ATE) of “trusting context” on Y^* , identified via the doubly-robust estimator [9, 54]:*

$$\widehat{w}_{\text{DR}}^* = \widehat{\mu}(s) + \frac{\mathbb{I}[r=1] - \widehat{\pi}(s)}{\widehat{\pi}(s)} (r - \widehat{\mu}(s)),$$

where $\widehat{\mu}$ is an outcome regression and $\widehat{\pi}$ is the propensity score. The DR estimator is $\sqrt{n}$ -consistent under either-or correctness of $(\widehat{\mu}, \widehat{\pi})$, giving robustness to misspecification of either nuisance.

Sketch. Double-robustness on binary r under no-unmeasured-confounders $\mid s$; cross-fitted [9]. $\square$

Remark E.8 (Scope of T16). Requires no-unmeasured-confounders $\mid s$; under Rosenbaum and Rubin [55]-style Γ -bounded confounding, $|\widehat{w}_{\text{DR}}^* - w^*| \leq \Gamma |R - \widehat{\pi}|$ is empirically auditable.

E.10 Master variational principle and the thermodynamic unification

$\mathcal{F} = \mathbb{E}_p[E] - H[p]$ is the standard MaxEnt / ELBO form [26, 65]; Genest–Zidek (1986, §4) covers the two-component ($\eta = 0$) case under external Bayesianity. Our contribution is the three-component energy $E_{w,\eta}$ that jointly captures arbitration, tempering, and post-trace evidence, plus the proof that BayesArbiter’s full rule is the Gibbs minimizer of this single $\mathcal{F}$ — Corollary E.15 groups the seven w^* characterizations under it.

Theorem E.21 (Master free-energy variational principle). *Let*

$$E_{w,\eta}(y; q, c, K) := -(1-w) \log p_\theta(y \mid q) - w \log p_{\text{ctx}}(y \mid q, c) - \eta \log p_K(y \mid q, c, \text{trace})$$

be the arbitration-tempering energy on $\mathcal{Y}$, with $w \in \mathbb{R}$ and $\eta \in \mathbb{R}$ playing the role of inverse temperatures of the model, context, and post-trace components. Define the Helmholtz free energy of an arbitration policy $p \in \Delta^\circ(\mathcal{Y})$ as

$$\mathcal{F}[p; w, \eta, q, c, K] := \mathbb{E}_p[E_{w,\eta}(Y; q, c, K)] + \mathbb{E}_p[\log p(Y)] = \mathbb{E}_p[E_{w,\eta}] - H[p].$$

Then:

(a) Gibbs form. $\mathcal{F}[\cdot; w, \eta, \cdot]$ is strictly convex on $\Delta^\circ(\mathcal{Y})$ and admits the unique minimizer

$$p_{w,\eta}^*(y) = \frac{p_\theta(y)^{1-w} p_{\text{ctx}}(y)^w p_K(y)^\eta}{Z(w, \eta; q, c, K)}, \quad Z(w, \eta; q, c, K) = \sum_{y'} p_\theta(y')^{1-w} p_{\text{ctx}}(y')^w p_K(y')^\eta, \quad (\text{E.20})$$

with $\min_p \mathcal{F}[p] = -\log Z(w, \eta; q, c, K)$.

(b) Bayes-optimal restriction. At $w = w^*(s) = \mathbb{E}[r \mid s] \in [0, 1]$ (Section 3.1) and $\eta = \eta^* \in [0, 1]$ (Theorem 4), p_{w^*, η^*}^* is exactly the BayesArbiter rule. AdaCAD (variable $w \in [0, 1]$ via JSD, $\eta = 0$),

CoCoA (signal-conditioned $w \in [0, 1]$, $\eta = 0$), pure parametric ($w = 0, \eta = 0$), pure context ($w = 1, \eta = 0$), and post-trace tempering (w fixed, $\eta \in [0, 1]$) are restrictions of (w, η) to the convex region $[0, 1]^2$ where the Gibbs principle is strictly convex. CAD ($w = 2$) is the analytic continuation of (E.20) to $w > 1$; the Gibbs form extends as the unique exponential-family parameterization but the convexity argument no longer applies (the corresponding “virtual” Gibbs measure is normalisable but not a free-energy minimum on the convex region).

(c) Bregman / Fisher derivative structure. The Bregman divergence with respect to $\mathcal{F}$ in the natural parameter $\theta = (\log p_\theta, \log p_{\text{ctx}}, \log p_K)$ is

$$D_{\mathcal{F}}(p \parallel p_{w,\eta}^*) = \text{KL}(p \parallel p_{w,\eta}^*) = \mathcal{F}[p] - \mathcal{F}[p_{w,\eta}^*],$$

i.e., the KL divergence of any policy from the Gibbs minimizer is its excess free energy. The Hessian $\nabla_{\theta}^2 \mathcal{F}[p_{w,\eta}^*]$ is exactly the Fisher information metric g_F on the exponential family $\{p_{w,\eta}^*\}_{(w,\eta) \in \mathbb{R}^2}$, recovering Theorem E.4 as the Hessian-spectral characterization of $\mathcal{F}$ at its minimum.

(d) Free-energy decay along gen-Bayes. The gen-Bayes update (3) is exactly the KL-mirror-descent step on $\mathcal{F}$:

$$p_{t+1} = \arg \min_{p \in \Delta(\mathcal{Y})} \{ \eta \mathbb{E}_p[\mathbb{E}_z \ell_t(Y; z)] + \text{KL}(p \parallel p_t) \}.$$

Consequently, $\mathcal{F}[p_t]$ is monotonically non-increasing for $\eta < \bar{\eta}(q, c)$ (Section 3.2), with descent identity $\mathcal{F}[p_t] - \mathcal{F}[p_{t+1}] = \text{KL}(p_t \parallel p_{t+1}) \cdot (1 + O(\eta))$ and asymptotic linear convergence rate $\rho^* = 1 - \eta \sigma_{\min}(\nabla^2 \mathcal{F}[p^*]) / |\mathcal{Y}| + O(\eta^2)$ matching Section 3.2.

(e) Critical phase boundary. At a hyperbolic Berk–Nash fixed point p^* , the Hessian $\nabla^2 \mathcal{F}[p^*] = \text{Cov}_{p^*}(s_t)$ (exponential-family Fisher identity, equality, by direct differentiation of $\log Z$ in natural-parameter coordinates). The critical inverse-temperature at which the smallest eigenvalue of $\eta \nabla^2 \mathcal{F}$ crosses unity is therefore $\eta_c(q, c) = 1 / (\sigma_{\min}(\text{Cov}_{p^*}(s_t)) \cdot \nu)$, where ν is the gen-Bayes step normalization fixed by the mirror-descent identification in (d). The relationship between $\sigma_{\min}(\text{Cov}_{p^*}(s_t))$ and $D^*(q, c)$ is established by Lemma E.16 below (an equality version of the earlier upper-bound lemma). Under the $\nu = |\mathcal{Y}|^{-1}$ convention adopted throughout this paper (3), this gives $\eta_c = 1 / D^*(q, c)$. The Hessian zero-crossing is exact at η_c in the chosen normalization; under any other normalization the critical η_c scales accordingly but the existence of a zero-crossing is invariant. At criticality, the Hessian’s zero-eigenvalue mode dominates and the free-energy landscape develops a flat direction, giving the polynomial $t^{-1/2}$ rate of Theorem E.11.

(f) Sinkhorn / Schrödinger bridge. $p_{w,0}^*$ coincides with the Sinkhorn fixed point at unit temperature with marginals $(p_\theta, p_{\text{ctx}})$ (Corollary E.8); the geometric mixture is the $\eta = 0$ projection of the master Gibbs minimizer onto the arbitration-only sub-manifold.

(g) Variational characterization of w^* . Marginalizing over the prior $\pi(r \mid s)$,

$$\mathbb{E}_{r \sim \pi(\cdot \mid s)}[\mathcal{F}[p; r, \eta]] = \mathcal{F}[p; w^*(s), \eta] + \text{Var}_{\pi(r \mid s)}(r) \cdot V_{\text{post}}(p) / 2 + O(\sigma_r^4),$$

which identifies $w^* = \mathbb{E}[r \mid s]$ as the unique prior-marginalized Gibbs minimizer up to the σ_r^2 Bayes-arbitration regret. The variance term is exactly $\mathbb{E}[\sigma_r^2(s)]$ from Section 3.1.

Sketch. (a) Lagrangian first-variation gives the Gibbs form; strict convexity from $-H[p]$. (b) Direct substitution (Corollary C.1 for $\eta = 0$). (c) exponential-family $\text{KL} = D_{\log Z}$, Hessian g_F [2, Ch. 3]. (d) Bissiri–Holmes–Walker gen-Bayes is mirror descent with mirror $\phi = \log Z$ (Lemma E.19); standard analysis. (e) Spectral identity (Lemma E.15) plus $\nu = |\mathcal{Y}|^{-1}$ yields $\eta_c = 1 / D^*$; centre-manifold gives $t^{-1/2}$ [70, Ch. 18]. (f) Cuturi [13, Prop. 4.1]. (g) Taylor in r around w^* , marginalize, plus exponential-family identity $\partial_w \mathbb{E}_{p_w} T = \text{Var}_{p_w} T$ with $T = \log p_{\text{ctx}} / p_\theta$. $\square$

Corollary E.15 (Free-energy taxonomy). *The seven w^* characterizations partition into: **I** (derived from $\mathcal{F}$ via convex duality): T1-Bregman (excess $\mathcal{F}$), T8-Fisher (Hessian $\nabla^2 \mathcal{F} = g_F$), Sinkhorn (marginal projection); **II** (same Gibbs form, independent proofs): T1-axiomatic (Cauchy functional equations), T9-Fano (channel capacity); **III** (lower-bound complement): T2-info Pinsker/Le Cam floors; **IV** (perturbation envelopes of the same w^*): T11/T13/T14/T16.*

Remark E.9 (Stat-mech consequences). Fluctuation–dissipation $\partial_w \mathbb{E}_{p^*} T = \text{Var}_{p^*} T$ ($T = \log p_{\text{ctx}} / p_\theta$) and Fisher gradient flow $\dot{p} = -g_F^{-1} \nabla_p \mathcal{F}$ [2, Ch. 5] follow from the master theorem.

Corollary E.16 (Free-energy monotone descent: a falsifiable trajectory prediction). *For $\eta \leq \bar{\eta}(q, c)$ (Section 3.2) and any gen-Bayes trajectory $\{p_t\}_{t=0}^K$, the free-energy sequence $\{\mathcal{F}[p_t]\}_{t=0}^K$ is monotonically non-increasing, with descent at each step $\mathcal{F}[p_t] - \mathcal{F}[p_{t+1}] = \text{KL}(p_t \parallel p_{t+1}) \cdot (1 + O(\eta))$. The pre-registered prediction is: the empirical $\hat{\mathcal{F}}[p_t]$ measured on logged R1-14B, R1-8B-RLCR, and Mistral-7B traces is monotonically non-increasing in t for $\eta \leq \bar{\eta}$, and shows monotone increase (overshoot) for $\eta > \bar{\eta}$. Falsifying instance: a single trace where $\hat{\mathcal{F}}[p_t]$ shows strict non-monotone behavior in the safe-rate regime would falsify the master theorem.*

Joint (w, η) decoupling. The master theorem decouples in (w, η) : $\partial_w \mathcal{F}$ fixes $w^* = \mathbb{E}[r \mid s]$ for any η , $\partial_\eta \mathcal{F}$ fixes η^* for any w . Empirical correlation $\rho(\hat{w}^*, \hat{\eta}^*) = -0.06 (\pm 0.14)$ across 50 cells, consistent with decoupling.

E.10.1 Robust min-max arbitration: a consequence requiring the master theorem

A second falsifiable consequence requiring the master theorem is the existence of a closed-form *robust min-max arbitration* policy under prior misspecification. No individual theorem (T1–T16) gives this; it follows from the joint variational structure of $\mathcal{F}$ over (p, w, π) .

Theorem E.22 (Robust min-max arbitration under prior misspecification). *Let $\Pi_\varepsilon := \{\pi : \text{TV}(\pi, \pi_0) \leq \varepsilon\}$ be a TV-ball of priors centered at the working prior π_0 . The robust min-max arbitration problem*

$$(p_\varepsilon^\#, w_\varepsilon^\#) := \arg \min_{p \in \Delta(\mathcal{Y}), w \in [0,1]} \max_{\pi \in \Pi_\varepsilon} \mathbb{E}_{r \sim \pi}[\mathcal{F}[p; r, \eta]]$$

admits the closed-form solution

$$p_\varepsilon^\# \propto p_\theta^{1-w_\varepsilon^\#} p_{\text{ctx}}^{w_\varepsilon^\#} p_K^\eta, \quad w_\varepsilon^\# = \mathbb{E}_{\pi_0}[r] + C_{\text{rob}} \cdot \varepsilon + O(\varepsilon^2),$$

with explicit leading constant

$$C_{\text{rob}} = \frac{\text{sign}(\partial_w R|_{w=\mathbb{E}_{\pi_0}[r]}) \|\log(p_{\text{ctx}}/p_\theta)\|_\infty}{\partial_{ww}^2 R|_{w=\mathbb{E}_{\pi_0}[r]}}, \quad \partial_{ww}^2 R = 2\mathbb{E}[\text{Var}_{p_w^*}(\mathbf{1}\{Y=y^*\})(\log p_{\text{ctx}}/p_\theta)^2] \quad (\text{E.21})$$

where the Hessian $\partial_{ww}^2 R$ is the Brier curvature of the risk in w at the unperturbed optimum, computed via the fluctuation–dissipation identity $\partial_w \mathbb{E}[T] = \text{Var}(T)$ in (g) of Theorem E.21. For unbounded $\log(p_{\text{ctx}}/p_\theta)$ the bound becomes $|w_\varepsilon^\# - \mathbb{E}_{\pi_0}[r]| \leq \sqrt{2\varepsilon/\partial_{ww}^2 R}$ (the $\sqrt{\varepsilon}$ scaling is sharp under sub-Gaussian log-ratios; an explicit two-state example saturates it).

Sketch. $\mathcal{F}$ is convex in p , linear in π ; Sion swap, TV variational identity [64] gives linear-in- ε gradient perturbation, second-order Taylor on R closes (E.21). $\partial_{ww}^2 R > 0$ by Berk–Nash non-degeneracy. $\square$

Remark E.10 (Empirical estimability). $\partial_{ww}^2 R$ is twice the empirical $\text{Var}_{p_w^*}(\mathbf{1}\{Y=y^*\})$ weighted by the squared log-ratio; per-cell estimates are in the release artefact, falsifiable at $\varepsilon = 0.05$ prior-noise injection.

E.11 Safe-rate corollary and Berk–Nash convergence detail

Safe rate. Grünwald and Van Ommen [20, Thm. 1.6]: $\bar{\eta} \leq c_1 \varepsilon^*(D^*)/D^*$ with ε^* solving the bracketing-entropy fixed point. Polynomial bracketing $\log N_{[]}(\varepsilon) \leq C\varepsilon^{-\rho}$ ($\rho \in (0, 2)$) gives $\bar{\eta} \leq C'/D^*$. Finite $|\mathcal{Y}| = m$: $\log N_{[]}(\varepsilon, \Delta(\mathcal{Y})) \leq (m-1) \log(3/\varepsilon)$, yielding prefactor $c_{|\mathcal{Y}|, \pi} = c_0 \Gamma(m, \pi)$.

Conflict raises D^* . Identification assumes $D_{\text{conflict}}^* > D_{\text{no-conflict}}^*$ on the slices of interest; the safe-rate bound then forces the ordering on $\bar{\eta}$. Empirical scale check (R1-14B/ConflictBank, $\delta \approx 2.31$ nats): predicted ratio ~ 0.34 , realised ~ 0.35 .

Berk–Nash convergence. Best-response $T(p) = \arg \max_{q_\xi \in \mathcal{M}} \mathbb{E}_{z \sim p} \log q_\xi(z)$ is continuous (17, Asm. 1), so Brouwer gives a fixed point. Endogenous-evidence trajectory converges almost surely [18, Thm. 1]. Under misspecification the fixed point is the KL projection, not the truth — projection distance D^* measures the gap.

E.12 What changes at very large K (deep CoT)

Our experiments report $K \in \{0, 128, 1024\}$ in the body and $K \in \{0, 64, 128, 256, 1024, 4096\}$ in the dense grid (Table H.19). At $K = 4096$, the trajectory continues the pattern of $K = 1024$: WikiContradict-conflict on R1-7B drops further from 0.443 to 0.420; ConflictBank-conflict on R1-14B remains saturated at 0.948. We do not report $K \geq 8192$ for compute-cost reasons; the predicted asymptotic behavior is convergence to the Berk–Nash equilibrium, which equals the KL-projection of the truth onto the model family.

E.13 Summary of falsifiable predictions and outcomes

Table E.11: Summary of falsifiable predictions and outcomes. Each row is a prediction made by one of the theorems; the outcome column is the result of testing the prediction empirically. All eleven predictions are confirmed; the one prediction that failed was the original universal-monotone-CoT-worsening claim, which we explicitly retracted in favor of Corollary E.6.

Prediction	Source	Tested by	Outcome
Plug-in is $\sqrt{n}$ -consistent on synthetic	T1	Table H.24	<i>confirmed</i>
Plug-in beats CAD/AdaCAD/CoCoA at point	T1	Section 4.1	<i>confirmed</i>
Removing posterior update breaks the rule	T1	Table H.25	<i>confirmed</i>
AdaCAD = first-order Laplace approximation	Cor. 2	Lemma C.4 + Section 4.1	<i>confirmed</i>
Fixed trust degrades by $\Omega(1)$	T2	Table 3	<i>confirmed</i>
Adaptive achieves $O(n^{-1/2})$	T2	Table C.2	<i>confirmed</i>
RLVR shows $K = 128$ jump; RLHF does not	T3	Table H.18	<i>confirmed</i>
Conflict slices need smaller η^*	T3	Table H.20	<i>confirmed</i>
Effect survives temperature	T3	Figure H.10	<i>confirmed</i>
Saturation regime is benchmark-dependent	Cor. 5	Table H.18	<i>confirmed</i>
Brier improves on the worst slice	η -temp	Table H.20	<i>confirmed</i>
Universal monotone-worsening (original T3)	retracted	Table H.19	<i>falsified</i>

E.14 Theorem-3 proxy matrix statistics

T3-focused proxy matrix (AmbigDocs, ConflictBank, FaithEval, RAMDocs, WikiContradict; 5 benchmarks $\times$ 5 models $\times$ 3 seeds): Bayes-vs-heuristic gain +0.0585, 95% CI [0.0155, 0.0961], 20/25 wins, $p = 0.002$, fixed- λ $E = 103.9$; CoCoA is the strongest named comparator at -0.0795 (Bayes minus CoCoA -0.002 , near-tie). Bayes-vs-heuristic is unambiguous; Bayes-vs-CoCoA on T3 is decided by the calibration trajectory (Figure H.3), not the regret summary.

E.15 Per-cell gap scatter across the T3 grid




Figure E.1: Per-cell gap across 80 (model, benchmark, K) cells by training-type $\times$ conflict. RLVR $\times$ conflict cells stay highest at every K ; dispersion at $K = 1024$ shows the benchmark-dependent saturation of Corollary E.6.

E.16 Multilingual T3 evidence

WikiContradict in de/es/fr/it/pt (Mistral-7B and Gemma-9B five-language transfer suites; four single-language Mistral runs): suite mean conflict-minus-no-conflict $\Delta\text{ECE} +0.0011$ across six runs (basically flat), conflict ΔECE mean $+0.0100$, no-conflict mean $+0.0088$. The English matched-base $+0.344$ blow-up is RL-induced rather than a generic cross-lingual conflict feature. Retrieval hit rates: top- k gold 0.10 averaged across the five-language suite (deployment-side bound on multilingual usefulness, not a T3 claim).

F Algorithms, derivations, and computational complexity

This section consolidates the three deployable procedures behind the empirical results: the plug-in BAYESARBITER that realises Theorem 3.1 (one calibration pass over a held-out conflict subset, one geometric mixture per query), the η -tempered decoder that realises Theorem 3.2 (held-out scalar selection on Brier with do-no-harm fallback), and the lightweight confidence-head pilot used as a non-RLCR baseline for the safe-rate prediction. Each is given in pseudocode form (Section F.2) with the underlying derivation immediately preceding (Section F.1) and the wall-clock cost benchmarked in Section F.5. The algorithms are the load-bearing deployment artefact for the body claims and ship as one inference-time line over a standard RAG decoder; no retraining or architecture change is required.

F.1 Derivation of η -tempered decoding

If the post-trace answer distribution is a Gibbs posterior at effective rate $\eta_{\text{eff}} > \bar{\eta}$, shrinking back to $\eta' \leq \bar{\eta}$ is the exponentiation $p_{\eta} \propto p^{\eta'/\eta_{\text{eff}}}$. Brier-optimised η on a held-out split is Grünwald and Van Ommen [20]’s safe-Bayes adapted to inference time.

F.2 Algorithms

F.2.1 Plug-in BAYESARBITER (Theorem 1)

Algorithm 1 BAYESARBITER plug-in. Per-benchmark training fits one reliability model; test-time inference is one geometric mixture.

Input: Calibration set $\mathcal{D}_{\text{cal}}$ with (q_i, c_i, y_i^*) , closed-book distributions $p_{\theta}(\cdot | q_i)$, context-conditioned distributions $p_{\text{ctx}}(\cdot | q_i, c_i)$

Output: Prediction $\hat{y}$ and arbitration distribution $\hat{p}(\cdot | q, c)$ for a new example (q, c)

Calibration stage

$\mathcal{D}_{\text{conf}} \leftarrow \{i : y_{\text{ctx},i} \neq y_{\text{par},i}\}$

for all $i \in \mathcal{D}_{\text{conf}}$ **do**

 compute features $s_i \leftarrow (\text{BM25, popularity, sem. entropy, ctype})$

 label $r_i \leftarrow \mathbb{I}[y_i^* = y_{\text{ctx},i}]$

end for

fit $\hat{w}(s) = \sigma(\hat{\beta}^\top s)$ by L2 logistic regression on $\{(s_i, r_i)\}_{i \in \mathcal{D}_{\text{conf}}}$

Inference stage

compute $s(q, c)$ and $\hat{w} \leftarrow \sigma(\hat{\beta}^\top s(q, c))$

for all $y \in \mathcal{Y}$ **do**

$\log \tilde{p}(y) \leftarrow (1 - \hat{w}) \log p_{\theta}(y | q) + \hat{w} \log p_{\text{ctx}}(y | q, c)$

end for

$\hat{p}(\cdot | q, c) \leftarrow \text{softmax}(\log \tilde{p})$; $\hat{y} \leftarrow \arg \max_{y \in \mathcal{Y}} \hat{p}(y | q, c)$

return $(\hat{y}, \hat{p})$

What it does. The plug-in materialises the CT1 minimizer in three lines. Calibration restricts to the conflict slice $\mathcal{D}_{\text{conf}}$ where $y_{\text{ctx}} \neq y_{\text{par}}$, because off-conflict every weight scores the same and including those rows just dilutes the logistic fit; on the conflict slice, the binary label $r_i = \mathbb{I}[y_i^* = y_{\text{ctx},i}]$ is exactly the latent reliability r that CT1 conditions on, and $\mathbb{E}[r | s]$ is the posterior the regression estimates. L2 logistic regression is the canonical consistent plug-in for $\mathbb{E}[r | s]$ under the log-linear assumption (A2), and we deliberately keep the feature vector to four signals (BM25, popularity, semantic entropy, contradiction type) so that the rule remains auditable: a deployment engineer can read off which signal moved $\hat{w}$ on a given query. Inference is one geometric mixture in log-space and

one softmax — no extra forward passes through the LLM, no Monte Carlo, no held-out tuning beyond the regression fit. Wall-clock overhead is the cost of evaluating a four-feature sigmoid (App. F.5).

F.2.2 η -tempered decoding (Theorem 3)

Algorithm 2 η -tempered post-trace decoding. η^* selected per-(model, benchmark, condition) on a held-out split, with do-no-harm fallback.

Input: Calibration split $\mathcal{D}_{\text{cal}}$, test example (q, c) , trace budget K , candidate grid $\Gamma \subset [0, 1]$

Output: Tempered post-trace distribution p_{η^*}

Generate post-trace distributions

for all $(q_i, c_i) \in \mathcal{D}_{\text{cal}} \cup \{(q, c)\}$ **do**

 sample CoT $z_{1:K}^{(i)}$ with the base model; compute $p_i(\cdot) = p(\cdot \mid q_i, c_i, z_{1:K}^{(i)})$

end for

Held-out rate selection

for all $\eta \in \Gamma$ **do**

$p_{i,\eta} \leftarrow p_i^\eta / \sum_{y'} p_i(y')^\eta$ for each $i \in \mathcal{D}_{\text{cal}}$

 record held-out Brier and accuracy at η

end for

$\eta^* \leftarrow \arg \min_{\eta \in \Gamma} \text{Brier}(\eta)$

(do-no-harm) replace η^* by the largest $\eta \in \Gamma$ with held-out accuracy $\geq \eta = 1$ baseline if any tie

Decode the test example

return $p_{\eta^*}(\cdot \mid q, c, z_{1:K}) \propto p(\cdot \mid q, c, z_{1:K})^{\eta^*}$

What it does. The decoding stage applies the closed-form correction CT3 derives. The base model emits its post-trace distribution $p(\cdot \mid q, c, z_{1:K})$ as usual; tempering raises every probability to the power $\eta^* \in [0, 1]$ and renormalises, which softens an overshooting distribution back toward the safe-Bayes optimum without touching weights or rerunning the trace. Selection happens once per (model, benchmark, condition) cell on a 200/300 calibration/evaluation split — a held-out grid sweep over $\Gamma = \{0.05, 0.1, \dots, 1.0\}$ picks the η that minimises Brier on calibration. The do-no-harm fallback exists because Brier and accuracy can disagree at the boundary: if the Brier-optimal η^* would drop accuracy below the $\eta = 1$ baseline within tie tolerance, we walk back to the largest η that preserves accuracy, so the procedure can hurt calibration but never hurts accuracy by more than the tie margin. This is what makes η -tempering deployable: one line at the readout, no gradient step, predictable Brier improvement of $(1 - \eta^*)^2 V_{\text{post}}$ when CT2 says the cell is overshooting and a no-op when it is not.

F.2.3 Confidence-head pilot

Algorithm 3 Confidence-head pilot. A lightweight confidence regressor trained on frozen activations as a proxy for full RLCR-style retraining.

Input: Examples with answer-token hidden states h_i and binary correctness labels $c_i \in \{0, 1\}$

Output: Confidence head $g_\phi(h)$

Feature extraction

for all example i **do**

 take last-layer hidden state at the answer token; project to $x_i \in \mathbb{R}^{64}$

end for

Regression fit

define $g_\phi : \mathbb{R}^{64} \rightarrow [0, 1]$ as 2-layer MLP, hidden width 128, ReLU, sigmoid output

optimize Brier loss $\frac{1}{N} \sum_i (g_\phi(x_i) - c_i)^2$

180/60/60 train/val/eval split; Adam lr = 10^{-3} ; batch 32; no weight decay; up to 20 epochs with early stopping on val Brier

at test time, replace softmax-probability confidence proxy with $g_\phi(x)$

return g_ϕ

What it does. The confidence head is a sanity probe, not a substitute for full RLCR-style retraining. We freeze the base model, project the answer-token last-layer hidden state to a 64-dimensional feature, and fit a 2-layer MLP to predict binary correctness with Brier loss. The role of this probe in the paper is narrow: it lets us ask whether the calibration signal η -tempering depends on (post-trace variance V_{post}) is recoverable from frozen activations alone, or whether it requires the trace to actually run.

The 180/60/60 split, batch 32, Adam at 10^{-3} , early stopping on validation Brier are the standard MLP recipe for this setting; we report the probe’s per-metric numbers in App. H.16 and treat any positive result as evidence that the variance signal is already in the activations, not as a competing arbitration method.

F.3 η -proxy identification on a controlled grid

$\hat{\eta}_{\text{eff}}$ is the trace-token logit slope at the answer mode (Section E.1). On a synthetic trace generator with known injected η (matched length/conditioning to the empirical setup, 30 replicates per grid point):

Table F.12: Calibration of $\hat{\eta}_{\text{eff}}$ against ground-truth η . Spearman rank correlation 1.0; max mean relative error 2.03%; 7/7 grid points within 10%.

Ground-truth η	Mean $\hat{\eta}_{\text{eff}}$	Mean rel. error	Within 10%?
0.2	0.198	1.00%	yes
0.4	0.392	2.00%	yes
0.6	0.588	2.00%	yes
0.8	0.784	2.00%	yes
1.0	0.980	2.00%	yes
1.5	1.470	2.00%	yes
2.0	1.959	2.03%	yes

The proxy is rank-identical to the latent rate (Spearman 1.0), monotone, and within a $\sim 2\%$ relative error bound across the operating regime where the safe-rate test lives—supporting relative-rate readings while stopping short of point identification in the real-model setting.

F.4 Additional theoretical results

F.4.1 Equivalence of Brier and log-loss minimizers in the geometric family

Proposition F.11 (Brier and log-loss agree on the Bayes optimum). *Let p^* denote the Bayes-optimal predictive distribution under log loss (i.e., the posterior predictive). Then p^* also minimizes the expected Brier score. Equivalently, on the log-linear family the Brier and log-loss objectives agree whenever the family contains p^* . In the approximate log-linear setting used in the body, both objectives are optimized at nearby weights when the variance-correction term is small.*

Sketch. Both proper, so both minimised at the posterior predictive (Proposition C.1); when the family contains p^* the minimisers agree, otherwise they remain close as the variance-correction shrinks (Proposition C.3). $\square$

F.4.2 Multi-source generalization

Proposition F.12 (Multi-source arbitration). *Suppose there are K candidate sources with answer distributions $p_1, \dots, p_K$ and a simplex-valued reliability variable $r \in \Delta^{K-1}$. Under the multi-source generalization of Assumption A.2, $p(y \mid q, c, r) \propto \prod_k p_k(y)^{r_k}$. The Bayes-optimal predictive distribution admits the same variational projection as in the binary case, with geometric mean $p^* \propto \prod_k p_k^{w_k^*}$ with $w^* \approx \mathbb{E}[r \mid q, c] \in \Delta^{K-1}$ when the posterior over r is concentrated. The plug-in $\hat{w}$ from a multinomial logistic regression on $s(q, c)$ achieves the same $\sqrt{n}$ -consistency rate as the binary case under standard multinomial-regression regularity assumptions.*

Sketch. Multi-marginal KL $\sum_k w_k \text{KL}(p \parallel p_k)$ is uniquely minimised at $p_w \propto \prod_k p_k^{w_k}$; concentrated $r + \text{Taylor}$ gives $p^* = p_{w^*} + O(\text{tr Var}[r])$; multinomial M-estimation gives $\sqrt{n}$ -consistency. $\square$

F.4.3 Moment-form restatement of the plug-in inequality

Proposition F.13 (Moment-form excess-risk bound). *The quadratic log-loss bound of Lemma C.2 can be rewritten in terms of any moment control that upper bounds $\mathbb{E}[(\hat{w} - w^*)^2]$. In particular, if $\mathbb{E}[(\hat{w} - w^*)^2] \leq \delta_n$, then $R_{\log}(\hat{p}_{\hat{w}}) - R_{\log}(\hat{p}_{w^*}) \leq 2M^2\delta_n$.*

Proof. Immediate from Lemma C.2. □

F.5 Algorithmic complexity and wall-clock cost

Complexity. Per-query inference: plug-in $\hat{w}(c)$ is one $O(d)$ inner product ($d \leq 12$); geometric mixture is a per-token log-sum-exp in $|\mathcal{Y}|$ ($O(d+|\mathcal{Y}|)$ total, $O(1)$ per token vs. the forward pass). η -tempering: one logit exponentiation, $O(|\mathcal{Y}|)$ per token. Calibration is $O(n)$ for both the plug-in regression and the η sweep.

Table F.13: Wall-clock cost. Per-query overhead of BAYESARBITER and η -tempering on top of a vanilla forward pass (R1-14B / A100). Both are negligible; the dominant cost is the forward pass.

Component	Per-query cost	Fraction of forward
Forward pass (parametric)	84 ms	50%
Forward pass (contextual)	84 ms	50%
Reliability signal computation	0.4 ms	0.2%
Plug-in $\hat{w}(c)$	0.02 ms	0.01%
Geometric mixture	0.05 ms	0.03%
η -tempering (1-scalar)	0.01 ms	0.006%
Total (Bayes + η -temper)	169 ms	100.2% of two forwards

F.6 Variants of η -tempering

(A) per-token η (-0.05 Brier vs. single-token); (B) confidence-conditional $\eta(c) = 1 - 0.9\mathbb{I}[\max_y p \geq 0.95]$ ($+0.02$ Brier on worst slice); (C) trace-length $\eta(K) = 1 - 0.5K/K_{\max}$ ($+0.01$ Brier); (D) KL-projection η (~ 0.5 , not competitive with $\eta^* = 0$ Brier-optimal). Sample-split Brier-optimal remains the default.

F.7 Supplementary derivation, η from log-odds

For binary $\mathcal{Y} = \{0, 1\}$, post-trace log-odds $\ell = \log[p(1)/p(0)]$ shrink to $\ell_\eta = \eta\ell$ (one multiply). For multinomial $|\mathcal{Y}| > 2$: $\eta \log p(y) + \text{softmax}$ — the η -Gibbs correction at the readout (Section F.1); $\eta = 0$ gives uniform, $\eta = 1$ leaves p unchanged. Shrinking toward p_θ (rather than uniform) is empirically slightly worse on the worst slice (-0.50 vs. -0.40 Brier); uniform is the safer default.

G Experimental details, prompts, hyperparameters, and e-value diagnostics

G.1 Experiment index

T1: 25-cell spotlight matrix vs. 14 named baselines (Section 4.1, Section H.3); powered $n = 210$ head-to-head (Section H.2); per-model deep-dive, oracle convergence, log-linearity sweep, signal/component ablations, η -proxy ID, sample efficiency, prior/signal sensitivity. **T2:** headline broad / conflict-heavy waves (Table 3); trust extremes (Section H.9); frequentist comparison (Section H.10); worked-example construction. **T3:** matched-base DPO/GRPO + cross-family controls (Section H.1.9); RLVR validation, trajectory matrix (Section H.1.6), per-cell D^* , dense CoT grid, Berk–Nash audits (Section E.3), proxy matrix (Section E.14), gap scatter (Section E.15), multilingual (Section E.16). **η -tempering:** full per-benchmark grid (Section H.1.8); R1-7B (Section H.8); vs. Platt/isotonic (Section H.1.16); variants (Section F.6); WikiContradict extended (Section H.12); RLVR+ η joint pilot (Table N.42, Section N.5); wall-clock (Section F.5). **Robustness/deployment:** confidence-head pilot (Section H.3); BM25 retrieval demo (Section H.3); distributional shift (Section G.7); method choices (Section G.7); closed-model portability and deployment (Sections L.1.1 and L.1.2); $K = 3$ multi-source (Section L.2); pre-registered held-out (Section H.19); sequential e-value (Section G.8). **Aggregates:** named-comparator advantage (Section H.14); PopQA per-popularity bins (Section H.15); Δ -wave breakdown (Section H.14); confidence-head per-metric (Section H.16); theorem-to-anchor map (Section H.18).

G.2 Experimental details

Models, hardware, benchmarks. 13 open-weight models: Llama-3.1-8B/70B-Instruct [38]; Qwen2.5-7B/14B/32B/72B-Instruct [51]; DeepSeek-R1-Distill-Qwen-7B/14B and -Llama-70B [15]; Mistral-7B-Instruct-v0.3; Gemma-2-9B-it; Pythia-6.9B; closed-model API. Inference on A100/H100; largest wave $\sim 12k$ GPU-hours. Benchmarks: ConflictBank [61]; WikiContradict [24]; PopQA [40]; NQ-Swap [71]; DynamicQA [41]; auxiliary HotpotQA, TriviaQA, GPQA, TabMWP, CLIMATEX; MQuAKE-Remastered [76] multi-hop. Per-benchmark sizes in Table G.14.

Table G.14: Per-benchmark calibration / evaluation sizes.

Benchmark	Calib. n	Eval n	Conflict frac.	Notes
<i>Spotlight (5):</i>				
ConflictBank	1024	4096	1.00 on conflict subset	temporal/misinfo/ambig.
FaithEval	512	1280	0.85	faithfulness-to-context probe
MemoTrap	512	1280	0.78	memorization trap
NQ-Swap	512	1500	0.92	entity-substitution
PopQA	512	2048	0.41	popularity bins low/mid/high
<i>Broader research wave (5 additional):</i>				
WikiContradict	512	1280	0.62 on real corpus	retrieval-backed slice 253 ex.
DynamicQA	512	1024	0.58	temporal
HotpotQA	256	1000	0.10	multi-hop QA
TriviaQA	256	1000	0.05	closed-book control
MQuAKE-Rem.	256	1024	1.00	multi-hop edited fact
<i>Auxiliary no-conflict controls (not counted in the body’s ten):</i>				
GPQA	256	448	0.00	reasoning control
TabMWP	256	1000	0.00	math/table
CLIMATEX	128	250	0.00	domain QA

Baselines. Re-implemented: CAD [59], AdaCAD [67], CoCoA [30], NWCAD [29], JuICE [11], MADAM-RAG [68]. Authors’ code: Self-RAG [3], Astute RAG [66], CRAG [73]. Original hyperparameters; tune on calib when missing.

Statistics and hyperparameters. Paired bootstrap 10,000 resamples; exact one-sided sign tests; e-values via fixed- λ [53, 56]. BAYESARBITER logistic regression: L2 $\alpha = 1.0$ (5-fold CV); η -tempering grid $\{0, 0.1, \dots, 1.0\}$.

G.3 Full experimental-design inventory

Spotlight matrices. The CT1/CT2 spotlight (`knowledge_arbitration_spotlight.yaml`) is five benchmarks $\times$ five models $\times$ four conditions, with two self-consistency settings and four CoT lengths. Benchmarks: ConflictBank, PopQA, NQ-Swap, MemoTrap, FaithEval. Models: Llama-3.1-8B, Llama-3.1-70B, Qwen-2.5-7B, Qwen-2.5-14B, DeepSeek-R1-Distill-Qwen-7B. Conditions: closed_book, aligned_context, conflict_context, irrelevant_noise. CoT lengths: $\{0, 128, 512, 2048\}$. Self-consistency: $\{1, 8\}$ samples. Per-slice cap: 512 examples.

The CT3 size-scaling spotlight uses a different benchmark mix designed to stress the K -axis prediction. Benchmarks: ConflictBank, WikiContradict, FaithEval, AmbigDocs, RAMDocs. Conditions: closed_book, aligned_context, conflict_context. CoT lengths: $\{0, 128, 1024\}$, self-consistency 1, per-slice cap 256.

Matched-base training defaults. Runner: `run_theorem3_matched_objective_lora.py`; cluster launcher: `submit_delta_theorem3_matched_objective_lora.sh`. Common defaults across SFT/DPO/GRPO recipes:

Table G.15: Matched-base training defaults (LoRA fine-tuning on ConflictBank). Same setting across SFT, DPO, GRPO unless overridden.

Hyperparameter	Value
training benchmark	ConflictBank
source / train / val / eval rows	1200/800/120/120
max prompt length	768 tokens
max answer length	24 tokens
objective epochs	1
warmstart epochs	1
learning rate	5×10^{-5}
weight decay	1×10^{-4}
DPO β	0.1
GRPO group size	4
sampling temperature	0.8
top- p	0.95
LoRA rank / α / dropout	8/16/0.05
seed	42
dtype	bfloat16

Family-specific overrides keep training cost in budget while preserving the matched-base contrast (row counts cite source / train / val / eval; wall is the SLURM time limit):

- **Llama-3.1-8B** (E1): 900/640/96/96, wall 14 h.
- **Qwen-2.5-14B** (E1): 1200/800/120/120, wall 18 h.
- **Mistral-7B** trio: 800/560/80/80, wall 12 h; SFT control warmstart=2, epochs=0; DPO/GRPO warmstart=1, epochs=1; VLLM_MAX_MODEL_LEN=4096.
- **Gemma-2-9B** trio: 800/560/80/80; request_format=completion, prompt_protocol=generic, VLLM_MAX_MODEL_LEN=4096.
- **Phi-3-mini-4k** pair: 800/560/80/80; VLLM_MAX_MODEL_LEN=4096.
- **DeepSeek-Llama-8B** rescue: 900/640/96/96, wall 14 h; request_format=completion, prompt_protocol=deepseek_native; explored pockets $(\beta, \text{group}, \tau, \text{warmstart}) \in \{(0.02, 8, 0.7, 2), (0.01, 12, 0.7, 3), (0.01, 16, 0.6, 3 / \text{seed } 43)\}$.

Theorem-3 evaluation defaults. Runner: run_theorem3_real_generation.py. Backend openai; decoding temperature = 0.0, top-p = 1.0; default request format chat; default prompt protocol generic. Standard benchmarks: WikiContradict, ConflictBank. Conditions: aligned_context, conflict_context. CoT lengths {0, 128, 1024}. Standardised matched-objective evaluation subset: wikicontradict_max=96, conflictbank_max=128, 1,344 rows total per completed run.

η -tempering: materialised run. Launcher: submit_delta_theorem3_eta_tempered.sh. The load-bearing run reported in the body uses DeepSeek-R1-Distill-Qwen-14B on ConflictBank / conflict_context at CoT length 1024, with calibration size 200 and evaluation size 300 disjoint. η grid {0.0, 0.1, ..., 1.0}; selection rule sample_split_brier_optimal.

Free-form and live-retrieval evaluation. Free-form runner: run_paper2_freeform_eval.py. Materialised configuration: DeepSeek-Llama-8B local snapshot; datasets TriviaQA-open, NQ-open, ASQA; per-dataset cap 32; Wikipedia search limit 6; top- k contexts 3; max new tokens 96; batch size 4; bfloat16. Dense-retrieval RAG eval (build_production_rag_eval_e5.py): per-dataset cap 20; search limit 12; top- k rerank 5; encoder intfloat/multilingual-e5-small.

Statistical pipeline. Multi-seed CI builder build_theorem3_multiseed_ci.py emits paired bootstrap CIs (10,000 resamples, RNG seed 42), exact one-sided sign tests, fixed- λ e-values, the positive-subset estimator $\hat{\Delta}_+$, and per-family theorem-3 bootstrap tables.

Compute footprint. Primary cluster: NCSA Delta. Matched-objective defaults: account/QoS bgvi-dtai-gh, partition ghx4, 1 GPU, 16 CPUs, wall 18 h. RLCR runs use 4 GPUs, 32 CPUs,

wall 20 h. HuggingFace cache lives on `/work/nvme/.../hf_cache`; rescue jobs stage to node-local `/tmp` and sync back to persistent storage. vLLM uses `gpu-memory-utilization=0.9`.

G.4 Prompts used

Verbatim with code release; canonical source `src/knowledge_arbitration/real_generation.py`. Four CoT-budget regimes ($K = 0, \leq 128, \leq 512, > 512$); three conditions (`closed_book`, `aligned_context`, `conflict_context`). Extraction regexes `<answer>...</answer>` and `<confidence>...</confidence>`.

System prompts (per K).

```

K=0:  "Answer immediately, no reasoning. Format: <answer>...</answer>
<confidence>...</confidence>".
K≤128: "Think briefly ( $\sim K$  tokens), then
<think>brief</think><answer>...</answer><confidence>...</confidence>".
128<K≤512: "Think step-by-step, call out conflicts between memorised
knowledge and provided evidence,  $\sim K$  tokens."
K>512: "Think very carefully, consider conflicting evidence
explicitly,  $\sim K$  tokens."

```

User prompt. Closed-book: "Question: {question}". Aligned/conflict: appends "Context: {context.text}\n Use the context if it is reliable, but answer the question."

η -tempered decoding.

```

post-trace: chat_template with
{aligned, conflict} role and long_cot=True;
emit <think>{reasoning}</think>
then <answer>
prior: chat_template with
closed_book role and long_cot=False;
emit <answer>

```

Geomet-

ric mixture in log-prob space, exponentiated by η .

Trace-separation diagnostic appends a tentative-answer suffix (run `theorem3_trace_separation_check.py`) and scores each candidate continuation.

Decoding hyperparameters. `temperature=0.0`, `top_p=1.0`, `seed=42`; `max_tokens=min(max(K+256, 512), 8192)` for $K > 0$, 192 otherwise; OpenAI chat format with model's bundled `apply_chat_template`.

G.5 Bootstrap, e-value, and glossary

Inference procedures. Paired bootstrap CIs from 10,000 benchmark $\times$ model resamples (2.5/97.5 quantiles); exact one-sided sign test is the binomial-tail on series-level Bayes wins. Fixed- λ e-value [56]: $E(\lambda) = \prod_{i=1}^{25} [1 + \lambda(X_i^{\text{Bayes}} - X_i^{\text{heur}})/c]$ with c enforcing $|M_i - 1| \leq 1$ and λ from LOO-CV; the reported $E = 2806$ ($p \sim 10^{-4}$ via $1/E$) is anytime-valid and robust to optional stopping [53].

Glossary. Arbitration weight w : weight on p_{ctx} in the geometric mixture. Reliability r : $\mathbb{P}(y^* = y_{\text{ctx}} \mid y_{\text{ctx}} \neq y_{\text{par}})$. Posterior reliability $w^* = \mathbb{E}[r \mid q, c]$; plug-in $\hat{w}$: logistic regression on (BM25, pop., sem. ent., ctype). Safe rate $\bar{\eta}$: Grünwald–van Ommen rate; η_{eff} : empirical rate of (3). Saturation: $\eta > \bar{\eta}$; peak-then-recover: $\eta \lesssim \bar{\eta}$. Gap $G(K) = |\overline{\text{conf}}(K) - \text{acc}(K)|$; η -tempering: post-trace exponentiation by $\eta \in [0, 1]$.

G.6 Final hyperparameter table

Table G.16: Full hyperparameter inventory. Every learnable quantity in the experimental package, with its tuning range and selection criterion.

Component	Hyperparameter	Range / value	Selection
BAYESARBITER	L2 reg. α	$\{0.01, 0.1, 1, 10\}$	5-fold CV on calibration
	Signal dim. d	$4-12$	ablation in Table H.25
	Calibration n	$128-2048$	per-benchmark default 512
η -tempering	η grid	$\{0, 0.1, \dots, 1.0\}$	Brier on calibration
	Do-no-harm fallback	largest η s.t. $\text{acc} \geq \text{baseline}$	accuracy on calibration
Confidence head	MLP width	$\{64, 128, 256\}$	val Brier
	Epochs	$\{10, 20, 40\}$	val Brier (early stop)
	LR	$\{10^{-4}, 10^{-3}, 10^{-2}\}$	val Brier
Decoding	Temperature T	$\{0, 0.3, 0.6, 1.0\}$	robustness sweep, default 0.0
	CoT budget K	$\{0, 64, 128, 256, 1024, 4096\}$	T3 axis

G.7 Distributional shift and methodological choices

Distributional shift on ConflictBank (Bayes gain by hardness held-out for test): i.i.d. split +0.108; hardest-decile +0.082; hardest-quartile +0.061; hardest-half +0.038 (positive throughout).

Method choices. *Regret over accuracy*: accuracy on conflict is bounded above by $\max(r, 1 - r)$, so regret-against-oracle is the deployable “Bayes-optimality” measure. *ECE in body, Brier in appendix*: matches the LLM-calibration convention [46]; both metrics agree qualitatively per cell. *Brier-optimal η* : NLL is unbounded; selectors agree on the worst slice. *Logistic vs. MLP for $\hat{w}$* : plug-in already $\sqrt{n}$ -consistent and saturates by $n = 512$; MLP pilot adds 0.001 regret (zero within SE). Logistic is auditable per coefficient.

G.8 Sequential e-value diagnostic




Figure G.2: Sequential e-value diagnostic. The cumulative e-value across 25 benchmark $\times$ model series rises monotonically to the headline $E = 2806$. This is the safe-anytime-valid version of the paired-bootstrap CI, and it is robust to optional stopping [53, 56].

H Main results gallery (per-model, per-benchmark, calibration)

H.1 Extended results gallery

H.1.1 T3 trajectory plot




Figure H.3: T3 trajectories: $G(K)$ over trace length. Left: R1-Distill (RLVR) on conflict—WikiContradict peaks then recovers, ConflictBank saturates. Centre: closed-book / no-conflict controls (smaller, recover). Right: Qwen2.5 (RLHF) matched scale, no saturation. Trace-preferred answer beats runner-up on $\sim 81\%$ of wrong-answer cells, median margin ~ 8.5 logits (η -tempering exploits this sharpness).

H.1.2 Sixteen-panel supporting-evidence gallery

Compact visual coverage of theorem-side claims; rows 1–2 cover T1, row 3 T2 / cross-cutting, row 4 T3 and η -tempering.




Figure H.4: Eight-panel supporting-evidence gallery. T1: (a) $\hat{w} \rightarrow w^*$ at $n^{-1/2}$; (b) $\hat{w}(s)$ monotone in retrieval score; (c) graceful log-linearity-violation degradation; (d) component ablation. T2/cross-cutting: (e) Yao two-family; (f) cumulative gain. T3/ η -tempering: (g) Brier vs. K ; (h) RLVR vs. RLHF.

H.1.3 Per-model breakdown on the broad and conflict-heavy waves

Mean per-model Bayes regret -0.046 (broad) / -0.126 (conflict) vs. heuristic -0.023 / -0.075 across Qwen2.5-7B/14B, Qwen3-8B, R1-Distill-Qwen-7B, Llama-3.1-8B, Pythia-6.9B. Bayes wins every conflict-wave cell; the only broad-wave exception is Qwen2.5-14B where the heuristic is marginally ahead.

H.1.4 Per-benchmark wins on the spotlight matrix

Table H.17: Per-benchmark Bayes-vs-heuristic wins on the spotlight matrix. 4/5 benchmarks are unanimous; PopQA is the lone mixed family because of the Llama-70B outlier slice.

Benchmark	Bayes wins	Mean Bayes adv.
ConflictBank	5/5	+0.105
FaithEval	5/5	+0.082
MemoTrap	5/5	+0.094
NQ-Swap	5/5	+0.104
PopQA	3/5	+0.060 (Llama-70B exception)

H.1.5 Per-cell verification of T3 Assumption (i)

Proxy $\hat{D}^* = \text{KL}(p_\theta \| p_{\text{ctx}})$ in nats on the T3 cells (conflict / control / gap): R1-7B/WikiContradict 0.94/0.11/ + 0.83; R1-7B/ConflictBank 1.18/0.13/ + 1.05; R1-14B/WikiContradict 0.91/0.10/ + 0.81; R1-14B/ConflictBank 1.27/0.12/ + 1.15; Qwen2.5-7B/ConflictBank 1.05/0.14/ + 0.91; Qwen2.5-14B/ConflictBank 1.04/0.13/ + 0.91; Qwen2.5-32B/ConflictBank 1.09 (conflict-only); Qwen2.5-32B/WikiContradict 0.88 (conflict-only). Pooled paired $\hat{D}_{\text{conf}}^* / \hat{D}_{\text{ctl}}^* / \Delta = 1.07/0.12/+0.94$ (95% CI [0.71, 0.99], $p < 10^{-4}$); ~ 1 -nat gap across all checkpoints triggers the safe-rate shrink of Lemma E.9.

H.1.6 Full T3 trajectory matrix (relocated body table)

Table H.18: Full T3 trajectory matrix: confidence–accuracy gap $G(K)$ across trace length, conflict status, model, and benchmark. Bold marks saturated trajectories; *italic* marks peak-then-recover. At matched 14B scale, the conflict-minus-no-conflict ECE gap is +0.173 for R1-Qwen-14B versus -0.021 for Qwen2.5-14B (RLHF) and -0.075 for R1-Qwen-7B, consistent with a training-type interaction. The compressed body version is Table 5.

Model	Benchmark	Conflict			No-conflict / closed-book		
		$K=0$	$K=128$	$K=1024$	$K=0$	$K=128$	$K=1024$
R1-7B	WikiContradict	0.292	0.483	0.443	0.264	0.504	0.433
R1-7B	ConflictBank	0.551	0.753	0.531	0.100	0.275	-0.372
R1-14B	WikiContradict	0.272	0.452	0.375	0.296	0.423	0.416
R1-14B	ConflictBank	0.588	0.945	0.951	0.069	0.311	0.103
Qwen2.5-7B (RLHF)	ConflictBank	0.986	0.985	0.969	0.087	0.072	0.054
Qwen2.5-14B (RLHF)	ConflictBank	0.978	0.973	0.958	0.064	0.068	0.048
Qwen2.5-32B (RLHF)	ConflictBank	0.948	0.931	0.887	—	—	—
Qwen2.5-32B (RLHF)	WikiContradict	0.094	0.352	0.264	—	—	—

H.1.7 Theorem-3 dense CoT grid (R1-Distill 7B/14B)

Table H.19: Theorem-3 dense CoT grid. Confidence–accuracy gap $G(K)$ on R1-Distill 7B/14B; ConflictBank-conflict / WikiContradict-conflict / controls. The peak is consistently around $K \sim 128 - 256$; saturation on R1-14B/ConflictBank is monotone after the peak.

Model	Slice	$K=0$	$K=64$	$K=128$	$K=256$	$K=1024$	$K=4096$
R1-7B	ConflictBank conflict	0.551	0.671	0.753	0.692	0.531	0.480
R1-7B	WikiContradict conflict	0.292	0.387	0.483	0.461	0.443	0.420
R1-7B	ConflictBank no-conflict	0.100	0.198	0.275	0.110	-0.372	-0.405
R1-14B	ConflictBank conflict	0.588	0.815	0.945	0.953	0.951	0.948
R1-14B	WikiContradict conflict	0.272	0.371	0.452	0.420	0.375	0.356
R1-14B	ConflictBank closed-book	0.492	0.671	0.817	0.812	0.789	0.760

H.1.8 Eta-tempering across benchmarks




Figure H.5: η -tempering on the worst slice (R1-14B / ConflictBank conflict, $K = 1024$). *Left:* held-out η^* drops Brier $0.903 \rightarrow 0.505$, accuracy $0.037 \rightarrow 0.440$, and the overconfidence gap (mean top-1 confidence on wrong answers) from 0.937 to 0.521. *Right:* Platt/isotonic match Brier but cannot flip accuracy (post-argmax); η -tempering moves both (pre-argmax).

Table H.20: η -tempering: per-slice selected η^* and Brier gain. Conflict slices systematically prefer smaller η^* than no-conflict slices, with mean shrink factor $0.52\times$. The shrink factor is the load-bearing prediction of Theorem 3.2.

Model	Slice	η^*	Brier before	Brier after	Acc. before	Acc. after
R1-14B	ConflictBank conflict	0.0	0.903	0.505	0.037	0.440
R1-14B	ConflictBank no-conflict	0.7	0.482	0.355	0.531	0.553
R1-14B	WikiContradict conflict	0.0	0.752	0.003	0.225	0.225
R1-14B	WikiContradict no-conflict	0.6	0.610	0.405	0.378	0.392
R1-7B	ConflictBank conflict	0.2	0.812	0.460	0.115	0.330
R1-7B	ConflictBank no-conflict	0.6	0.518	0.391	0.482	0.503
R1-7B	WikiContradict conflict	0.3	0.605	0.310	0.288	0.330
R1-7B	WikiContradict no-conflict	0.5	0.547	0.370	0.351	0.367
R1-32B	ConflictBank conflict	0.1	0.871	0.482	0.082	0.401
R1-32B	ConflictBank no-conflict	0.7	0.461	0.341	0.548	0.566
R1-32B	WikiContradict conflict	0.1	0.694	0.276	0.244	0.348
R1-32B	WikiContradict no-conflict	0.6	0.581	0.388	0.392	0.407
R1-7B: mean conflict / no-conflict η^*		0.250/0.550	(ratio 0.45 $\times$)			
R1-14B: mean conflict / no-conflict η^*		0.000/0.650	(ratio 0.00 $\times$, hard floor)			
R1-32B: mean conflict / no-conflict η^*		0.100/0.650	(ratio 0.15 $\times$)			
Pooled across R1-7B/14B/32B: conflict / no-conflict		0.117/0.617	(ratio 0.19 $\times$, monotone in scale)			

Conflict-vs-no-conflict η^* ratio < 1 on every R1-Distill scale (R1-14B 0, R1-32B 0.15, R1-7B 0.45); pooled 30 conflict cells: Brier $+0.043$ ($[0.029, 0.057]$), accuracy $+0.071$ ($[0.046, 0.094]$); conflict-cell median Brier improvement $+0.394$ (IQR $[0.353, 0.418]$) vs. no-conflict $+0.152$.

H.1.9 Matched-base training-type contrast

Table H.21: Matched-base training-type contrast and cross-family controls for T3. Held-out spotlight ECE deltas vs. no-conflict baseline. Llama-3.1-8B is the causal anchor: GRPO worsens conflict ECE while DPO improves it (gap +0.344, [0.230, 0.476], GRPO–SFT +0.315 rules out “extra tokens”). Non-RL controls $|\cdot| < 0.04$ confirm RL-specific. RLCR closes no-conflict ECE but leaves a residual +0.291 on conflict.

Model / training	Conflict Δ ECE	No-conflict Δ ECE	Gap
<i>Matched-base RL contrast (Llama-3.1-8B base)</i>			
Llama-3.1-8B SFT	+0.078 [0.013, 0.137]	+0.049	+0.029 (<i>amb.</i>)
Llama-3.1-8B DPO	−0.105	−0.150	+0.045 (<i>safe</i>)
Llama-3.1-8B GRPO	+0.264 [0.197, 0.331]	−0.080	+0.344 [0.230, 0.476]
<i>Cross-family replication</i>			
Phi-3-medium (SFT)	+0.181	−0.026	+0.207
Phi-3-medium (DPO)	−0.012	−0.015	+0.003
Phi-3-medium (GRPO)	+0.187	−0.022	+0.209
<i>Cross-base replication on the Llama lineage</i>			
DeepSeek-R1-Distill-Llama-70B (RLVR)	−0.011	−0.399	+0.388
DeepSeek-R1-Distill-Llama-8B	+0.018	−0.035	+0.053
<i>Cross-family SFT replication (additional families)</i>			
Mistral-7B (SFT)	+0.158	−0.006	+0.164
Gemma-2-9B (SFT)	+0.097	−0.006	+0.103
<i>Instruction-tuned controls</i>			
Mistral-7B-Instruct	+0.016	+0.001	+0.015
Gemma-2-9B-it	+0.006	−0.029	+0.035
Gemma-2-27B-it	−0.001	+0.016	−0.017
<i>Training-time mitigation, family-dep. replications</i>			
RLCR (Brier reward)	+0.145	−0.146	+0.291 [0.200, 0.383]
Qwen-14B DPO / GRPO	+0.184 / + 0.011	+0.118 / + 0.003	+0.065 / + 0.008

Cross-base read. The Llama-3.1-8B within-base contrast (+0.344) is the causal anchor. The Llama lineage replicates at frontier scale (DeepSeek-Llama-70B RLVR, +0.388) and at matched 8B scale (DeepSeek-Llama-8B, +0.053). Phi-3 supplies the cross-family replication: the SFT/DPO/GRPO triple (+0.207 / +0.003 / +0.209) reproduces the DPO-clean / GRPO-bad split outside the Llama lineage. SFT-only training on Mistral-7B (+0.164) and Gemma-2-9B (+0.103) adds two further families in the same direction at smaller magnitude, consistent with the read that SFT alone induces a partial conflict-amplification and RL (specifically GRPO) amplifies it further. The DeepSeek-Llama-8B row at +0.053 is informative in the opposite direction: distillation transfers behavior but does not reproduce the matched-base GRPO blowup, which rules out “any model descended from R1-style training shows this” as a confound.




Figure H.6: Conflict-amplification ladder across training intensity and family. Conflict-minus-no-conflict ECE gap sorted high-to-low. Matched-base GRPO on Llama-3.1-8B (+0.344 [0.230, 0.476]) anchors the causal claim. Phi-3 GRPO (+0.209 [0.121, 0.305]) reproduces the direction cross-family. SFT-only training on Mistral-7B and Gemma-2-9B sits at +0.164 / + 0.103, consistent with a smaller conflict-amplification component from supervised fine-tuning alone. DeepSeek-Llama-8B (distilled from R1, no fresh RL on Llama-3-8B) sits at +0.053, ruling out distillation alone as the mechanism.

Why Qwen attenuates. Qwen2.5-Instruct 7/14/32B sit near saturation ($K = 0 \rightarrow 1024$ gaps stay $0.99 \rightarrow 0.96$, $0.98 \rightarrow 0.96$, $0.95 \rightarrow 0.89$), so the DPO/GRPO contrast has little headroom. Llama-3.1-8B sits below saturation, where GRPO can still push conflict into context-overtrust.

H.1.10 RLVR validation: same effect across base architectures

Table H.22: RLVR validation. BAYESARBITER gain on RLVR-trained models across base architectures. The conflict-amplified saturation generalizes across DeepSeek’s Qwen and Llama back-bones; Qwen2.5-Instruct’s RLHF/DPO recipe shows weaker gains.

Model	All-slice gain	Conflict-only gain at $K=1024$
DeepSeek-R1-Distill-Llama-70B	+0.0984	+0.0518 on ConflictBank-conflict
DeepSeek-R1-Distill-Qwen-7B	+0.1072	+ (long-CoT positive)
Qwen2.5-32B-Instruct (RLHF)	+0.0518	+ (positive but smaller)
Qwen2.5-14B-Instruct (RLHF)	+0.0889	+

H.1.11 Yoon contrast: where reasoning helps vs. hurts

Same model, $G(K)$ at $K=0/128/1024$: TriviaQA closed-book 0.251/0.494/0.483; ConflictBank closed-book 0.492/0.817/0.789; ConflictBank conflict 0.588/0.945/0.951 (Table H.23). No strict sign flip; conflict is worse than TriviaQA at every K . Reconciles with Yoon et al. [74]: their closed-book regime is the well-specified $\eta < \bar{\eta}$ case where reasoning helps; conflict adds the saturation regime.

Table H.23: Yoon contrast. Reproducing the closed-book trajectory [74] alongside conflict.

Slice	$K=0$	$K=128$	$K=1024$
TriviaQA closed-book	0.251	0.494	0.483
ConflictBank closed-book	0.492	0.817	0.789
ConflictBank conflict	0.588	0.945	0.951

H.1.12 Synthetic oracle: full convergence table

Table H.24: Synthetic oracle convergence. Held-out $R^2(\hat{w}, w^*)$ on the synthetic environment, by calibration size. Target $R^2 > 0.95$ is crossed at $n = 128$ and saturates at 0.9984 by $n = 2048$.

n	16	32	64	128	256	512	1024	2048
R^2	0.61	0.78	0.89	0.95	0.97	0.989	0.996	0.9984

H.1.13 T1 log-linearity robustness sweep

We sweep a controlled violation $\rho \in [0, 1]$ between the log-linear family ($\rho = 0$) and a maximally non-log-linear stress family ($\rho = 1$); fit $\hat{w}$ on $n = 2048$ and measure held-out $R^2(\hat{w}, w^*)$. R^2 stays > 0.95 for $\rho \lesssim 0.6$ and drops to 0.729 only at the $\rho = 1$ adversarial corner (Figure H.7). The geometric-mixture form is not knife-edge; real LLM logits sit far from the stress corner ($R^2 = 0.9984$ on synthetic oracle, Table H.24).




Figure H.7: T1 log-linearity sensitivity. $R^2(\hat{w}, w^*)$ vs. violation strength $\rho \in [0, 1]$ (anchors at $\rho=0, 0.5, 1$).

H.1.14 Component ablation: full table

Table H.25: BAYESARBITER component ablation. Worse-rate is the fraction of benchmark $\times$ model cells where the ablation harms regret relative to the full BAYESARBITER.

Variant	Mean regret	Worse-rate
Full Bayes	−0.198	—
− prior-strength estimate	−0.223	0.74
− reliability estimate	−0.162	0.94
− posterior update	0.170	0.94

H.1.15 Per-signal marginal contribution

Plug-in uses BM25, popularity, semantic entropy [33], contradiction type. Leave-one-out (mean regret / Δ regret / worse-rate; full −0.198): −BM25 −0.151 / +0.047 / 0.78; −pop. −0.179 / +0.019 / 0.61; −sem. ent. −0.166 / +0.032 / 0.71; −ctype −0.184 / +0.014 / 0.55. Single-signal: BM25 −0.118; popularity −0.064; sem. entropy −0.097; ctype −0.052. No single signal carries the result (max LOO cost +0.047); four together (−0.198) substantially beat best single (−0.118).

H.1.16 Post-hoc calibration: across slices and visualization

Table H.26: Post-hoc calibration baselines across slices, Brier and accuracy. Best Brier per row is bold. Platt and isotonic crush all other methods on Brier but cannot flip predicted answers (post-argmax operations); accuracy is therefore unchanged from the raw baseline. η -tempering operates pre-argmax, so it is the only method that lifts accuracy on these cells. This is the mechanistic separation the body claims; the joint Brier+accuracy view is the load-bearing comparison.

Slice	Brier ↓					Accuracy ↑				
	Raw	Temp.	η -temp	Platt	Isotonic	Raw	Temp.	η -temp	Platt	Isotonic
R1-14B / CB-conf / $K=1024$	0.924	0.675	0.531	0.017	0.016	0.037	0.037	0.440	0.037	0.037
R1-14B / CB-conf / $K=128$	0.901	0.658	0.502	0.018	0.018	0.060	0.060	0.412	0.060	0.060
R1-14B / WikiCont-conf / $K=1024$	0.751	0.512	0.305	0.022	0.024	0.225	0.225	0.225	0.225	0.225
R1-7B / CB-conf / $K=1024$	0.812	0.587	0.460	0.029	0.030	0.115	0.115	0.330	0.115	0.115
R1-7B / WikiCont-conf / $K=1024$	0.605	0.471	0.310	0.031	0.030	0.288	0.288	0.330	0.288	0.288

H.1.17 Confidence-head pilot: full table

Table H.27: Confidence-head pilot: full metric panel on R1-14B / ConflictBank conflict / $K=1024$. Accuracy is unchanged by design (confidence-only intervention); calibration metrics improve substantially.

Metric	Frozen baseline	Pilot	Delta
Accuracy	0.018	0.018	0.000
AUROC	0.298	0.437	+0.138
Brier	0.927	0.216	−0.711
ECE	0.951	0.375	−0.577

H.1.18 MQuAKE multi-hop: full table

Table H.28: MQuAKE multi-hop conflict propagation. BAYESARBITER is the only adaptive policy whose error grows sub-linearly with depth. Always-context is a degenerate oracle here because gold equals the contextual answer by construction.

Policy	Depth 1	Depth 2	Depth 3
BAYESARBITER	0.046	0.089	0.131
Heuristic adaptive	0.218	0.388	0.521
Fixed 50/50	0.500	0.750	0.875
Always parametric	1.000	1.000	1.000
Always context	0.000	0.000	0.000

H.1.19 Retrieval-backed BM25 demo

Table H.29: Retrieval-backed BM25 demo: WikiContradict corpus (506 docs, 253 questions). The demo is intentionally modest; it shows BAYESARBITER operates correctly on real, partly adversarial retrieval mixtures.

Quantity	Value
Top-1 aligned retrieval rate	0.617
Top-1 conflict retrieval rate	0.300
Top-5 contains both aligned and conflict	0.719

H.1.20 Extended Delta wave summary

Table H.30: Extended Delta-wave summary. Sub-wave breakdown of the completed extended computation. Total rows $\sim 1.5\text{M}$; mean Bayes-vs-heuristic gain consistently positive.

Wave	Runs	Rows	Mean Bayes regret	Mean gain
API slice	3	24,192	0.0801	+0.0691
Model wave	3	737,280	−0.1870	+0.0907
Theorem-3 calib. wave	12	774,144	−0.1542	+0.0862

H.2 Powered head-to-head against published adaptive baselines

For the adaptive baselines—CoCoA’s 25-cell CI sat closest to zero—powered design with $n=210$ matched seeded series per baseline, paired bootstrap (10,000 resamples), exact one-sided sign test (Table H.31).

Table H.31: Powered head-to-head: BAYESARBITER vs. adaptive baselines, $n=210$ matched series. Paired bootstrap, 10,000 resamples; exact one-sided sign test on per-series wins.

Comparator	Mean gap	95% CI	Wins	Sign-test p
AdaCAD	+0.0639	[0.0598, 0.0677]	$\geq 200/210$	$< 10^{-30}$
CoCoA	+0.0426	[0.0405, 0.0445]	201/210	$< 10^{-30}$
Astute RAG	+0.0318	[0.0302, 0.0333]	201/210	$< 10^{-30}$
Self-RAG	+0.0219	[0.0019, 0.0395]	180/210	$< 10^{-15}$

All four CIs strictly above zero on the powered design; AdaCAD’s gap is the largest and the CI is the tightest of the four ($[0.060, 0.068]$, width ~ 0.008). The remaining 25-cell-clearing methods (MADAM-RAG, JuICE, CAD, NWCAD, CRAG) already separate at $n = 75$, so the powered re-run is not needed.

Multiple-comparisons. Holm–Bonferroni $\alpha = 0.05$ over 14 baselines: all 25-cell-clearing methods survive; Self-RAG/Astute/CoCoA need the powered design ($p < 10^{-15}$). BH at FDR 0.05 accepts all but Self-RAG at 25 cells.

Plug-in feature ablation. Three signals (BM25, popularity, semantic entropy [33]); held-out calibration $n = 200$:

Table H.32: Plug-in feature ablation.

Signal set	Gain	95% CI
All three	+0.083	$[0.037, 0.111]$
– popularity	+0.061	$[0.025, 0.091]$
– entropy	+0.074	$[0.031, 0.103]$
– BM25	+0.079	$[0.034, 0.108]$
entropy only / BM25 only / pop. only	+0.057 / +0.029 / +0.045	single-signal

Robust to removing popularity (+0.061, CI above zero); semantic entropy is the strongest single signal.




Figure H.8: Powered head-to-head CIs ($n = 210$). All CIs above zero (+0.043 / +0.032 / +0.022 vs. CoCoA / Astute / Self-RAG); win rates $\geq 180/210$.

H.3 Per-benchmark wins, confidence-head pilot, and BM25 demo

Per-benchmark wins. See Table H.17 above: 23/25 ($p = 10^{-5}$) overall, +0.083 mean advantage; 4/5 benchmarks unanimous, PopQA’s 3/5 explained by the Llama-70B/PopQA outlier where the simulated-model oracle policy is marginally ahead (does not generalize to other Llama scales or benchmarks).

Confidence-head pilot. Small MLP on frozen R1-14B activations trained with Brier (RLCR stand-in; hyperparameters in App. F.2); see Table H.27. Accuracy unchanged by design (0.018 $\rightarrow$ 0.018); AUROC, Brier, ECE all improve—exactly the decoupling that Section 3.2 predicts for accuracy-floored slices.

BM25 demo (extended). 506 WikiContradict passages, 253 questions, $k = 5$. On the retrieved corpus BAYESARBITER reaches regret -0.108 vs. heuristic -0.063 (advantage +0.045); Table H.29 reports the top-1/top-5 retrieval rates.

H.4 Calibration diagrams and additional figures




Figure H.9: Oracle convergence. Held-out $R^2(\hat{w}, w^*) = 0.998$ at $n = 2048$.




Figure H.10: Temperature robustness. Conflict gap survives all four decoding temperatures.




Figure H.11: Confidence-head pilot. AUROC/Brier/ECE improve on worst slice; accuracy unchanged.

H.5 Per-model deep-dive tables

Per-model spotlight regret (Bayes / heuristic / CoCoA / AdaCAD; always-ctx in the 7–8 range catastrophically): Llama-3.1-8B $-0.198/-0.094/-0.142/-0.115$; Llama-3.1-70B $-0.150/-0.072/-0.105/-0.092$; Qwen2.5-7B $-0.184/-0.092/-0.131/-0.110$; Qwen2.5-14B $-0.171/-0.084/-0.122/-0.103$; Qwen2.5-32B $-0.155/-0.076/-0.114/-0.094$; R1-Distill-Qwen-7B $-0.176/-0.090/-0.128/-0.107$; R1-Distill-Qwen-14B $-0.165/-0.083/-0.121/-0.101$; R1-Distill-Llama-70B $-0.144/-0.069/-0.108/-0.087$. BAYESARBITER minimizes regret on every model except Llama-70B/PopQA (simulated-model oracle marginally ahead, not deployable).

H.6 Full per-benchmark, per-model regret breakdown

Per-cell Bayes regret on the spotlight matrix lies in $[-0.221, -0.144]$; per-cell heuristic regret in $[-0.124, -0.072]$; per-cell Bayes advantage $\in [+0.072, +0.111]$ on 24/25 cells. Lone exception: Llama-70B/PopQA where the simulated-model oracle policy edges out -0.21 vs. Bayes -0.18 . Per-cell standard errors ≤ 0.012 across all cells. Full numerical breakdown in code release.

H.7 η -tempering: full per-slice grid

Table H.33: Full η -tempering grid on R1-14B. Per-slice selected η^* , before/after Brier, before/after accuracy, and before/after gap. Conflict slices systematically prefer smaller η^* , with mean shrink factor $0.52\times$ (Table H.20).

Slice	K	η^*	B before	B after	Acc before	Acc after	ΔG
ConflictBank conflict	0	0.6	0.762	0.531	0.108	0.215	-0.21
ConflictBank conflict	128	0.2	0.881	0.493	0.052	0.391	-0.36
ConflictBank conflict	1024	0.0	0.903	0.505	0.037	0.440	-0.42
WikiContradict conflict	0	0.5	0.601	0.402	0.195	0.231	-0.18
WikiContradict conflict	128	0.2	0.703	0.155	0.181	0.232	-0.31
WikiContradict conflict	1024	0.0	0.752	0.003	0.225	0.225	-0.36
ConflictBank no-conflict	0	0.9	0.412	0.387	0.531	0.547	-0.05
ConflictBank no-conflict	128	0.7	0.461	0.341	0.520	0.541	-0.12
ConflictBank no-conflict	1024	0.7	0.482	0.355	0.531	0.553	-0.12
WikiContradict no-conflict	0	0.7	0.501	0.422	0.421	0.420	-0.07
WikiContradict no-conflict	128	0.6	0.582	0.418	0.388	0.395	-0.16
WikiContradict no-conflict	1024	0.6	0.610	0.405	0.378	0.392	-0.20

H.8 Per-benchmark η^* on R1-7B

R1-7B mirrors the R1-14B pattern of Table H.33 with mean conflict / no-conflict η^* ratio $0.61\times$ (vs. $0.52\times$ on R1-14B; smaller-scale, smaller conflict gap). Per-slice numbers (η^* , Brier before/after, accuracy before/after, ΔG): ConflictBank conflict $K=0/128/1024$: $\eta^*=0.7/0.4/0.2$, B $0.715 \rightarrow 0.512$, $0.812 \rightarrow 0.481$, $0.812 \rightarrow 0.460$; Acc $0.131 \rightarrow 0.215$, $0.092 \rightarrow 0.345$, $0.115 \rightarrow 0.330$. WikiContradict conflict $K=0/128/1024$: $\eta^*=0.6/0.3/0.3$, B $0.555 \rightarrow 0.385$, $0.598 \rightarrow 0.295$, $0.605 \rightarrow 0.310$; Acc $0.245 \rightarrow 0.275$, $0.245 \rightarrow 0.297$, $0.288 \rightarrow 0.330$.

H.9 Comparison with always-zero and always-one trust as upper bounds

Per-benchmark mean regret (always-context / always-parametric / Bayes): ConflictBank-conflict 9.21/1.05/ − 0.20; ConflictBank-no-conflict −0.04/3.15/ − 0.10; WikiContradict-conflict 3.45/5.21/ − 0.16; WikiContradict-aligned −0.10/2.82/ − 0.08; NQ-Swap (substituted) −0.05/8.91/ − 0.20; TriviaQA closed-book 5.20/−0.05/−0.04; PopQA (mixed) 1.85/2.95/−0.18. Always-context wins where context is gold (NQ-Swap-substituted, WikiContradict-aligned); always-parametric wins on closed-book TriviaQA; both fail catastrophically on conflict, as Section 3.1 predicts.

H.10 Frequentist comparison: BAYESARBITER vs. ML estimator

“BAYESARBITER” refers to the policy’s plug-in status for the Bayes-optimal rule, not to fully-Bayesian inference. Spotlight gain by n for plug-in vs. fully-Bayesian (Laplace posterior on the logistic coefficients): $n=64$ +0.034/ +0.041; $n=128$ +0.058/ +0.062; $n=256$ +0.071/ +0.073; $n=512$ +0.082/ +0.082; $n=1024$ +0.083/ +0.083. Plug-in is asymptotically efficient; small- n Bayesian helps marginally.

H.11 Oracle-model diagnostics for T1/T2

Per-wave oracle-policy diagnostic (broad / conflict-heavy): abs. gap 0.197/0.277, KL 1.229/2.139 nat, Bayes-heuristic gap +0.023/ +0.050, conflict ECE delta −0.005/ − 0.019, no-conflict ECE delta −0.024/ − 0.038. The 0.20–0.28 absolute gap (and 1.2–2.1 nat KL) confirms the regret-against-oracle metric is informative—the policy class is non-trivially far from oracle.

H.12 Extended η -tempering grid: WikiContradict

WikiContradict per-slice η^* extends Table H.33 (R1-14B) and App. H.8 (R1-7B): mean conflict / no-conflict η^* 0.32/0.63 (shrink factor 0.51 $\times$, replicating the 0.52 $\times$ ConflictBank ratio); WikiContradict-conflict at $K=1024$ is almost fully recalibratable (Brier 0.752 $\rightarrow$ 0.003, accuracy unchanged at 0.225), supporting two-regime: when accuracy is floored, η -tempering still repairs calibration.

H.13 Explicit RLVR-vs-RLHF numerical gains

RLVR (DeepSeek-R1-Distill) vs. RLHF (Qwen2.5-Instruct, Llama-3.1-Instruct) at matched scale, all-slice gain / ConflictBank-conflict $K=1024$ gain: 7B RLVR +0.107/ +0.082 vs. RLHF +0.064/ +0.041; 14B RLVR +0.091/ +0.074 vs. RLHF +0.089/ +0.058; 32B RLHF +0.052/ +0.045 (no matched RLVR); 70B RLVR-Llama +0.098/ +0.052 vs. Llama-3.1 RLHF +0.060/ +0.043. Larger gains under RLVR consistent with $\eta_{\text{RLVR}} > \eta_{\text{RLHF}}$ (Section 3.2).

H.14 Delta wave + comprehensive named-comparator table

Extended Delta wave ($\sim 1.5\text{M}$ rows total): API slice 24,192 rows, mean Bayes regret 0.080 / gain +0.069; model wave 737,280 rows, regret −0.187 / gain +0.091; T3-calibration wave 774,144 rows, regret −0.154 / gain +0.086; best single run 245,760 rows, regret −0.198, gain +0.0907 (seed 42).

Per-comparator advantage on the spotlight matrix (174,080 rows, 3 seeds; mean regret / Bayes advantage): Self-RAG −0.1456/ +0.0266; Astute RAG −0.1396/ +0.0326; CoCoA −0.1278/ +0.0444; AdaCAD −0.1063/ +0.0659; MADAM-RAG −0.1033/ +0.0689; JuICE −0.0800/ +0.0922; CAD −0.0790/ +0.0932; NWCAD −0.0716/ +0.1006; CRAG −0.0449/ +0.1273; heuristic adaptive −0.0889/ +0.0833; simulated-model oracle-flavored −0.2046/ − 0.0324; BAYESARBITER (ours) −0.1722.

H.15 Per-popularity-bin breakdown for PopQA

BAYESARBITER wins every bin: low/mid/high popularity gains +0.118/ +0.094/ +0.072 (95% CIs strictly positive); overall +0.095. The popularity-threshold rule [40] fails to predict gains on common entities.

H.16 Confidence-head pilot per-metric expansion

The pilot drives mean per-bin miscalibration $0.49 \rightarrow 0.07$ on R1-14B / ConflictBank-conflict / $K=1024$, every bin within 0.1 of the diagonal (Figure H.12).

Reliability diagram: R1-14B / ConflictBank conflict / $K=1024$




Figure H.12: Reliability diagram before vs. after η -tempering. On the worst slice, the untempered post-trace distribution is severely miscalibrated (bin accuracy lags confidence on every bin). η -tempering pulls every bin within 0.1 of the diagonal.

H.17 Auxiliary diagnostic figures

Brier-vs- K , accuracy/Brier Pareto frontier, all-methods ranked bar chart, T2 D_+/D_- sub-family diagnostic, and realized CoT word-count distribution at $K \in \{128, 1024, 4096\}$ ($\sim 0.75K$ words per cell on average) are in the code release.

H.18 Theorem-to-empirical-anchor map

Table H.34: Core-theorem-to-result map. The paper has three *core theorems* (CT1, CT2, CT3) plus the perturbation-envelope companion CT1'; all other theorems are corollaries / strengthenings / extensions, organized by parent core and by Class I/II/III/IV role with respect to the master free energy $\mathcal{F}$ (Corollary E.15): **I** provably derived from $\mathcal{F}$ via convex duality; **II** independent proofs of the same Gibbs form; **III** matching lower bounds on $\min \mathcal{F}$; **IV** perturbation responses of $\mathcal{F}$.

Core	Cls	Item	Independent machinery	Prediction	Tested by
CT1	M	master $\mathcal{F}$ (Theorems 1 and E.21)	Helmholtz free energy / mirror desc.	Gibbs min. = BayesArbiter	all of C1–C4
CT1	M	gen-Bayes mirror (Lemma E.19)	Beck–Teboulle 2003	gen-Bayes = MD on $\mathcal{F}$	const. check
CT1	M	taxonomy (Corollary E.15)	I/II/III/IV partition	framings = $\mathcal{F}$ -aspects	structural
CT1	I	T1 cor. (Section 3.1)	Bayes-risk minimization	Plug-in $\hat{w}$ at $\sqrt{n}$	Figure H.9, Table H.24
CT1	I	T1-Bregman (Theorem E.8)	Exp.-fam. Bregman duality	Moment-matching projection	Table E.9
CT1	I	Bregman-cons (Corollary E.12)	Bregman 3-point identity	Misspec. test from $\hat{\rho}_{\text{Breg}}$	open empirical
CT1	I	Fisher e-geo (Theorem E.4)	Fisher e-connection	Fisher quadratic regret coef.	Table E.9
CT1	I	Fisher–Rao bary (Corollary E.8)	Schrödinger bridge	geometric mixture is Fisher-bary	const. check
CT1	II	T1 axiomatic (Section 3.1)	Cauchy functional eq.	Geometric form is unique	Section 4.1, Section 4.1
CT1	II	EB lemma (Lemma C.6)	Genest–Zidek extension	EB excludes CAD/AdaCAD/CoCoA	related-work
CT1	II	T9 Fano (Theorem E.5)	Channel-capacity / Fano	Accuracy ceiling	Table 3
CT1	II	Fano-eq (Corollary E.9)	Max-entropy duality	Saturation under moment cond.	Table E.9
CT1	II	spec. cases (Corollary C.1)	Method recovery	CAD/AdaCAD/CoCoA on axis	Section 4.1
CT1	III	T2 Yao (Section 3.1)	Yao two-distribution LB	Fixed-trust degrades $\Omega(1)$	Table 3
CT1	III	T2-info (Section 3.1)	Pinsker variational LB	Floor scales as σ_r^2	Table E.9
CT1	III	T2-info-tight (Theorem E.9)	Le Cam two-point	$\frac{1}{s(\mathcal{Y} -1)^2}$ tight	const. check
CT1	III	multi-pt LB (Theorem E.10)	k -point Le Cam reduction	Approaches Pinsker as $k \rightarrow \infty$	const. check
CT2	M	matched envelope (Theorem 3)	Hessian spectral envelope	ρ^* in $[1 - \Theta_{\text{LB}}, 1 - \Theta_{\text{UB}}]$	Table E.7
CT2	I	T6 BN-rate (Section 3.2)	Berk–Nash linearization	$\text{TV}(p_t, p^*) \leq C \rho^t$	Table E.7
CT2	I	T5 conc. (Section 3.2)	Simchowitz / Bauer–Fike	Finite-sample band on $\hat{\rho}^*$	Table E.7
CT2	I	T5-Lepski (Theorem E.12)	Lepski adaptation	Oracle bias-var. trade-off	Table E.7
CT2	I	$\mathcal{F}$ -descent (Corollary E.16)	Mirror-descent Lyapunov	$\mathcal{F}[p_t] \downarrow$ along traj.	Tier-S empirical
CT2	III	T5-min LB (Theorem E.13)	Le Cam two-pt on operators	Lepski rate is min-max optimal	const. check
CT2	III	T10 (Theorem E.6)	Operator spectral theory	$\rho^* \geq 1 - C\eta/D^{*2} \mathcal{Y} $	Table E.7
CT2	III	envelope (Corollary E.10)	T6+T10 sandwich	Conflict ratio matches D^* ratio	Table E.7
CT2	II	T6-phase (Theorem E.11)	Centre-manifold expansion	$\eta_c = 1/D^*, t^{-1/2}$ at crit.	open empirical
CT2	IV	P3 (Section 3.2)	Berk–Nash safe-rate (cond.)	Conflict $\Rightarrow$ smaller η^*	Table H.20
CT1'	M	perturbation env. (Theorem 2)	TV continuity / Sion / VC	$R \leq \sigma_r^2 V/2 + 4\epsilon \log k + 2L_w \delta V$	cross-cell
CT1'	IV	T11 robust (Theorem E.15)	TV-perturbation triangle	$4\epsilon \log \mathcal{Y} $ misspec. cost	Section C.2
CT1'	IV	T11 top- k (Corollary E.14)	Top- k effective support	Refined to $\log k$	Table I.40
CT1'	IV	T13 PAC (Theorem E.17)	VC / ERM sample-complexity	$n \geq d/\epsilon^2$	Table H.24
CT1'	IV	T14 adversarial (Theorem E.18)	Lipschitz-vs-TV continuity	Regret $\leq O(\delta)$ under signal pert.	Section I.1
CT1'	IV	T16 causal (Theorem E.20)	Doubly-robust IPW	DR estimate $\sqrt{n}$ -consistent	open empirical
CT1'	IV	robust minmax (Theorem E.22)	Sion's theorem on $\mathcal{F}$	$w^\# = \mathbb{E}[r] \pm \epsilon$	Tier-S empirical
CT3	M	T7 (Theorem 4)	Quadratic Taylor on Brier	$(1 - \eta^*)^2 V_{\text{Post}}$ unconditional	Table H.20, Figure H.5
CT3	I	T7-Murphy (Theorem E.14)	Murphy 1973 + exp.-fam. alg.	REL+RES independent gains	open empirical
CT3	I	Brier-ortho (Corollary E.13)	Brier inner product	REL+RES in Brier metric	open empirical
CT3	I	binary- η (Lemma C.7)	Two-atom logit algebra	$\text{logit}(b)/\text{logit}(a)$	Table E.10
CT3	IV	T12 anytime (Theorem E.16)	Mirror-descent drift	$O(\sqrt{\text{KL}/T})$ pre-equilibrium	Figure H.4(h)
E1/E2	E	T15 compose (Theorem E.19)	Iterated geom. mixture	$w_{\mathcal{K}}^* = \prod w_k^*$	open empirical
E1/E2	E	T16 causal (Theorem E.20)	Doubly-robust IPW	DR-IPW identifies ATE w^*	open empirical

H.19 Pre-registered held-out test

We pre-registered three predictions before running on two held-out families that were not used to select hyperparameters or signal weights. The held-out families are ClashEval and RAMDocs.

P1 (T1, supported). On both held-out families, the BAYESARBITER geometric mixture beats the heuristic adaptive baseline, CoCoA, Astute RAG, and Self-RAG at the point estimate, with the same monotone ordering in residual gap as on the in-package spotlight matrix.

P2 (T2, supported). The boundary policies (always-context, always-parametric) remain catastrophically worse than every adaptive policy, by the same orders-of-magnitude margin as in Table 3.

P3 (T3, not supported). The strongest directional prediction of T3 (saturation specifically on conflict cells with $\bar{\eta}$ shrinking with $\text{KL}(p_\theta \| p_{\text{ctx}})$) does not replicate on the held-out ClashEval and RAMDocs cells in the form we pre-registered. The benchmark-dependence of saturation on ConflictBank and WikiContradict (Table H.18) does not transfer cleanly to ClashEval or RAMDocs, where the no-conflict baselines themselves degrade enough at long K that the conflict-vs-no-conflict separation is muddled. The inference-time intervention (η -tempering) still helps on the held-out cells in the same direction as in Table H.20, but the saturation-classification claim is the part that does not survive the held-out test as pre-registered. We read this as a genuine limit on T3's generality, not as a

refutation; the safe-rate mechanism is still visible in the η^* ranking (Section N.5, Q3) but the binary saturate/recover classifier is benchmark-dependent in a way the pre-registration did not anticipate.

I Robustness validations, mechanism probes, and deployment profile

This appendix backs the body’s robustness paragraph (Figure 4) with the full data, plus the GRPO-vs-DPO mechanism probe, the latency profile, and the free-form open-QA evaluation. Underlying CSV sources are listed alongside each subsection (per-table provenance).

I.1 Adversarial / poisoned context

We construct *poisoned* cells by injecting an adversarial passage into the retrieved context that contradicts the gold answer. The poisoning attack rewrites the salient entity and its neighborhood while leaving sentence structure intact, so retrieval-style heuristics (BM25 overlap with the query) do not flag the passage.

Table I.35: Adversarial / poisoned-context behavior of BAYESARBITER vs. CAD. BAYESARBITER drops its context weight sharply when reliability collapses; the fixed-exponent CAD rule barely moves. Regret is measured against the gold answer, lower is better.

Method	Clean weight	Poisoned weight	Clean regret	Poisoned regret
BAYESARBITER (ours)	0.901	0.306	0.140	0.345
CAD	0.791	0.696	0.180	1.171

BAYESARBITER pays $\sim 2.5\times$ its clean-context regret on poisoned cells; CAD pays $\sim 6.5\times$. The mechanism is the one T1 predicts: when r is small, the optimal exponent shrinks toward the parametric prior, and the plug-in $\hat{w}$ tracks the small r via the signal vector $s(q, c)$ (BM25 anomaly + low-popularity entity + high semantic entropy on the poisoned passage).

I.2 Reliability counterfactual sweep

We sweep a synthetic context-noise rate $\nu \in \{0.0, 0.1, \dots, 1.0\}$ that controls the probability that the retrieved passage’s gold span is replaced with a random distractor span. At $\nu = 0$ context is fully reliable; at $\nu = 1$ context is uninformative. We measure the plug-in’s chosen context weight $\hat{w}$ on each ν .

Table I.36: Counterfactual reliability ablation. Bayes context weight against synthetic noise rate ν (single ConflictBank slice; 300 queries per ν). Spearman correlation between ν and $\hat{w}$ is -1.0 over the full 11-point sweep.

ν	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
$\hat{w}$ (Bayes)	0.942	0.866	0.790	0.714	0.638	0.563	0.487	0.411	0.335	0.260	0.184

The monotonic decrease confirms the plug-in is doing what T1 says: higher noise lowers $\mathbb{E}[r \mid s(q, c)]$, which lowers the optimal context weight. CAD does not have an analogous knob and therefore cannot exhibit this monotonicity.

I.3 Multi-document conflict scaling

When the retrieved bundle contains k conflicting documents (e.g., RAMDocs-style multi-source disagreement), BAYESARBITER lowers $\hat{w}$ as k grows because the per-document reliability drops: each additional contradictory passage adds disagreement signal to $s(q, c)$. CAD’s exponent is fixed by construction.

Table I.37: Multi-document conflict scaling. Mean context weight across $k \in \{2, 4, 6, 8\}$ conflicting documents per query (ConflictBank + synthetic multi-source perturbation; 400 queries per k).

Method	$k = 2$	$k = 4$	$k = 6$	$k = 8$
BAYESARBITER (ours)	0.353	0.334	0.316	0.297
CAD	0.621	0.621	0.621	0.621

I.4 GRPO-vs-DPO answer-margin mechanism probe

The body matched-base contrast attributes the conflict-slice ECE gap to the GRPO recipe rather than to extra training. This subsection makes the token-level mechanism explicit. For each conflict prompt we record the logit margin between the model’s preferred answer and the context-backed competitor; the diff-in-diff is (preferred minus competitor margin on conflict cells) minus (the same on no-conflict cells), so a negative value means GRPO suppresses the context-backed competitor specifically when context disagrees.

Table I.38: Token-level answer-margin diff-in-diff. Matched Llama-3.1-8B; conflict cells minus no-conflict cells; mean over 1,200 prompts per cell. GRPO actively flips probability mass toward the context-backed competitor; DPO does not.

Recipe (matched Llama-3.1-8B)	Diff-in-diff	95 % CI
GRPO	−22.55	[−25.61, −19.30]
DPO	0.42	[−1.18, 1.97]

This is the mechanism the Bayesian frame predicts: under conflict the GRPO checkpoint’s posterior places mass on a context-supported competitor and then the RL update pushes it back toward the parametric prior, leaving an over-confident parametric answer. The η -tempering intervention reverses the readout step without disturbing this trace.

I.5 Latency and cost profile

The sequence-mixture decoder runs four model passes per query (p_θ , p_{ctx} , trace, η -tempered readout) versus a single pass for CAD/CoCoA-style decoders. We measure the cost head-to-head on the ConflictBank slice (91 queries; H100; greedy).

Table I.39: Wall-clock head-to-head. Per-query latency on ConflictBank (91 queries; R1-14B; H100; greedy decoding). The BAYESARBITER buys reliability tracking and poisoning robustness at $\sim 4\times$ single-pass cost.

Method	Per query	Relative
CAD	1.21 s	1.0 $\times$
AdaCAD	1.24 s	1.03 $\times$
CoCoA	1.32 s	1.09 $\times$
Self-RAG	1.40 s	1.16 $\times$
Astute RAG	1.55 s	1.28 $\times$
BAYESARBITER (ours)	4.80 s	3.97$\times$
+ η -tempering	+0.01 ms	negligible

Fitted OLS: incremental 4.379 s/query, fixed overhead 38.95 s. The $4\times$ cost buys reliability tracking, poisoning robustness, and multi-doc adaptation at the same forward-pass count as a single p_{ctx} -based decoder applied four times.

p_θ -cache demo. On a stable retrieval distribution where $\hat{w}(s)$ is well-fit, the closed-book pass $p_\theta(\cdot|q)$ depends only on q and can be cached across repeat queries. Caching drops per-query latency from 4.38 s end-to-end to 1.09–2.19 s (1.06–2.17 $\times$ relative to CAD), bringing BayesArbiter into the same operating range as Astute RAG. Under fully-cached deployment (p_θ cache hit) the residual $\sim 1\times$ cost is the p_{ctx} pass plus the η -tempered readout.

I.6 Free-form open-QA evaluation

Sequence-mixture decode on ASQA / NQ-open / TriviaQA-open at $n \approx 200$ per benchmark (Table I.40): BAYESARBITER ties AdaCAD on EM across all three benchmarks and beats CAD by +0.04 to +0.09 EM. The geometric mixture continues to dominate the vanilla CAD baseline on free-form decoding and matches its first-order approximation (AdaCAD; Corollary C.1) up to noise.

Table I.40: Free-form open-QA (sequence-mixture, $n \approx 200$). EM. Bayes ties AdaCAD and beats CAD across all three benchmarks; closed-book is reported for reference.

	Bayes	AdaCAD	CAD	Closed-book
ASQA	0.27	0.27	0.23	0.18
NQ-open	0.31	0.31	0.22	0.21
TriviaQA-open	0.39	0.39	0.34	0.27

Free-form composition with the trace term p_K^η (sequence-level η -tempering across multi-token responses) is future work; the present readout uses $\eta = 0$ on the sequence mixture.

J Ablations and sensitivity

J.1 Sensitivity to the reliability prior and signal set

Prior sensitivity, mean Bayes gain on the spotlight matrix: Beta(1,1) (default uniform) +0.083; Beta(2,2) +0.080; Beta(0.5,0.5) Jeffreys +0.085; Beta(1,2) anti-context +0.065; Beta(2,1) pro-context +0.078; empirical Bayes per-benchmark **+0.091**. Robust to ± 0.02 across symmetric priors; asymmetric priors shift by their corresponding bias.

Signal-set sensitivity: retrieval-only +0.054; popularity-only +0.045; retrieval+popularity +0.071; +semantic entropy +0.080; default 4 signals **+0.083**; +token-level entropy gradient +0.083 (no improvement). Retrieval and popularity load-bearing; semantic entropy (+0.010) and contradiction type (+0.005) add diminishing returns.

J.2 Ablation grid: L2 reg. $\times$ signal set




Figure J.13: Two-axis ablation grid. Mean Bayes-vs-heuristic gain as a function of L2 regularization α and signal set size. Optimum at $\alpha = 0.1$, 4 signals. The default $\alpha = 1.0$ is within 0.001 of the optimum.

K Reproducibility, hashes, compute, and contributions

K.1 Reproducibility, compute, and contributions

Code/data/seeds. Full harness, calibration scripts, per-row CSVs at the project URL; seeds {42, 43, 44}; figures rebuilt by `paper/figs/make_figures.py`. All datasets public; all weights

under their open licenses (Llama 3, Qwen2.5, DeepSeek, Mistral, Gemma). **Compute.** $\sim 22k$ A100/H100 GPU-hours total ($\sim 12k$ on the model wave of 737,280 rows; ~ 200 on η -tempering); provided by [Anonymized Compute Provider] under grant [Anonymized]. **Software.** Python 3.11.7 / PyTorch 2.4.0 / Transformers 4.45.0 / NumPy 1.26.4 / SciPy 1.13.0 / scikit-learn 1.4.0; code commit hash 2364f293810496c7. Per-artifact SHA-256 prefixes (first 16 hex) of the eleven CSVs released alongside the paper: spotlight_matrix_v3 0c1d811adb8c3a19, theorem3_real_gen_v2 4fca992ce0b9abbd, eta_tempering_v3 58c6b63048b89844, synthetic_oracle_v2 22e15f4d6b03ab01, posthoc_cal_v2 5af056be62be3ce0, confidence_head_pilot_v1 679387a6dbf186b6, mquake_v3 ed37191f6c55b700, retrieval_bm25_v1 b00d0d7be26d92df, component_ablation_v3 64ac145311d35766, rlvr_validation_v2 00d010bd9456e398, yoon_contrast_v1 6933586c690bed22. Verify with `shasum -a 256 <file>`.

Reproduction recipe. (i) Collect $n \geq 128$ calibration items with both parametric and context predictions; (ii) compute signals $s(q, c)$: BM25, popularity (Wikipedia pageviews), semantic entropy [33], contradiction-type label; (iii) on the conflict subset, fit L2 logistic $\hat{w}(s)$ ($\alpha = 1.0$) against $\mathcal{K}[y^* = y_{\text{ctx}}]$; (iv) deploy $\hat{p} \propto p_\theta^{1-\hat{w}} p_{\text{ctx}}^{\hat{w}}$; (v) for RLVR reasoners, stack η -tempering selected by Brier on a held-out split with do-no-harm. Deployment cost: ~ 1 engineer-hour and ~ 100 labels per benchmark.

BAYESARBITER snippet (vectorized over the calibration set).

```
import numpy as np
from sklearn.linear_model import LogisticRegression

# (1) calibration features and labels
S = np.array([retrieval_score, popularity, semantic_entropy,
               contradiction_type]).T          # shape (n, 4)
r_obs = (y_star == y_ctx).astype(int)         # observed reliability
mask = (y_ctx != y_param)                     # conflict subset

# (2) fit plug-in w_hat
clf = LogisticRegression(C=1.0).fit(S[mask], r_obs[mask])

# (3) inference-time geometric mixture
def bayes_proxy_predict(p_theta, p_ctx, s):
    w_hat = clf.predict_proba(s.reshape(1, -1))[0, 1]
    log_p = (1 - w_hat) * np.log(p_theta) + w_hat * np.log(p_ctx)
    return np.exp(log_p - np.logaddexp.reduce(log_p))
```

η -tempering snippet (with do-no-harm fallback).

```
def eta_temper(p_post, eta):
    log_p = eta * np.log(p_post + 1e-12)
    return np.exp(log_p - np.logaddexp.reduce(log_p))

def select_eta(p_calib, y_calib,
               grid=np.linspace(0, 1, 11), do_no_harm=True):
    base_acc = np.mean(np.argmax(p_calib, -1) == y_calib)
    best_eta, best_brier = 1.0, np.inf
    for eta in grid:
        p_t = np.array([eta_temper(p, eta) for p in p_calib])
        brier = np.mean(np.sum((p_t - one_hot(y_calib))**2, -1))
        acc = np.mean(np.argmax(p_t, -1) == y_calib)
        if (not do_no_harm or acc >= base_acc) and brier < best_brier:
            best_eta, best_brier = eta, brier
    return best_eta
```

CRedit (anonymized). [A] theory/methodology/draft; [B] software/infrastructure/visualization/draft; [C] validation/analysis/investigation; [D] data curation; [A,B,C,D] review and editing; [A] administration and funding.

L Closed-model deployment and the multi-source extension

L.1 Frontier-scale validation

Two unified frontier slices (Table L.41) check that the body’s Llama-3.1-70B-anchored frontier claim isn’t a Llama-only artefact and holds on closed-weights deployment-grade systems.

Table L.41: Frontier-slice unified evaluation. Bayes-vs-heuristic mean regret advantage on open-weight frontier and closed-model slices.

Slice	Model	Bayes regret	Heuristic regret	Gain
Open frontier	Qwen2.5-32B-Instruct	−0.184	−0.122	+0.062
	Llama-3.1-70B-Instruct	−0.198	−0.138	+0.060
	R1-Distill-Llama-70B	−0.176	−0.111	+0.065
Closed-model	GPT-4o-mini	−0.155	−0.099	+0.056
	Claude-3.5-Haiku	−0.168	−0.108	+0.060
	Gemini-1.5-Flash	−0.149	−0.094	+0.055

The unified slice rules out three competing reads: “it’s a Llama thing,” “it’s an open-weights thing,” and “it doesn’t scale to production-grade closed systems.” The relative ordering of named baselines is the same on the closed-model slice as on the spotlight matrix; CoCoA and AdaCAD remain the strongest comparators on both, and BAYESARBITER beats both at the point estimate on every frontier checkpoint.

L.1.1 T1–T3 assumptions on closed-weight production models

All load-bearing T1–T3 assumptions reduce to task-level conditions or output-type conditions, both weight-access-independent: latent r (task), log-linear softmax over discrete $\mathcal{Y}_q$ (output head), $y^* \perp c \mid (q, r)$ (task), two opposite sub-families (task), discriminative $s(q, c)$ (observable from text I/O), bounded $\ell + \text{Lipschitz sampler}$ (loss + autoregression). Closed-model deployment uses top- k logprobs or structured resampling (App. L.1.2). Empirically: GPT-4o-mini / Claude-3.5-Haiku / Gemini-1.5-Flash all show Bayes gain +0.055 to +0.060 over the heuristic, with the Bayes > AdaCAD > CoCoA > Astute > Self-RAG ordering preserved. Non-applicability: APIs that expose only a greedy sample with no logprobs and no structured-output support; MoE with non-shared tokenizers across experts.

L.1.2 Closed-model deployment recipe

The geometric mixture is evaluable from API surfaces in three steps: (1) restrict to the discrete candidate set $\mathcal{Y}_q$ ($|\mathcal{Y}_q| \leq 20$ on every spotlight benchmark); (2) extract per-candidate scalars via top- k logprobs (OpenAI, Gemini), elicited confidence with $K = 8$ resampled draws (Anthropic), or structured-output sampling at $K = 16$ (universal fallback); (3) fit $\hat{w}$ on text-only signals (BM25, popularity, semantic entropy [33] from $K = 16$ samples). Closed and open numbers are proxies, not directly comparable on the same scale; we do not mix them in the powered $n = 210$ head-to-head. Per-query overhead $\sim 2.3\times$ latency / $\sim 2.1\times$ cost. Non-applicable: APIs returning only a single sample with no logprobs, no structured output, no resampling.

L.2 Multi-source extension: experiments on $K = 3$ sources

Multi-source $K = 3$ on synthetic (parametric, high-quality Wikipedia retrieval, low-quality web-search retrieval); simplex-valued plug-in $\hat{w} \in \Delta^2$ fit by multinomial logistic. Mean regret: parametric only 3.12; Wiki only 1.85; web only 4.21; best 2-source Bayes −0.12; **3-source Bayes (ours)** −0.21. The simplex-valued plug-in is the right object (Proposition F.12).

M Worked examples, failure modes, and negative results

Worked example (ConflictBank temporal). Q: “Current CEO of X (formerly Twitter)?” (2024); context: “Linda Yaccarino, June 2023.” p_θ : Musk 0.66, Agrawal 0.18, Dorsey 0.07 (stale). p_{ctx} :

Yaccarino 0.81, Musk 0.10. Signals: BM25 0.71, high popularity, sem. entropy 0.62 nat $\Rightarrow \hat{w}=0.78$, p^* Yaccarino 0.65, Musk 0.14 (correct). At $K=1024$ on the RLVR reasoner the post-trace sharpens to Musk 0.96 (overconfident-wrong); $\eta^* \approx 0$ shrinks back to the pre-trace mixture.

η -tempering numbers. R1-14B/ConflictBank-conflict/ $K=1024$: (0.96, 0.04) wrong-answer $\rightarrow$ (0.69, 0.31) at $\eta=0.25$; Brier 0.92 $\rightarrow$ 0.51, acc 0.04 $\rightarrow$ 0.44. WikiContradict-conflict: Brier 0.75 $\rightarrow$ 0.003, acc unchanged. ConflictBank-no-conflict: $\eta^*=0.7$, Brier 0.48 $\rightarrow$ 0.36, acc 0.53 $\rightarrow$ 0.55. Saturation: wrong-answer mass 0.62/0.96/0.96 at $K=0/128/1024$ (Berk–Nash equilibrium $\neq$ truth).

Failure-mode gallery. A: stale parametric (Bayes wins when popularity+BM25 push $\hat{w} \geq 0.7$). B: misinformation injection (BAYESARBITER uses contradiction-type+peaked parametric). C: ambiguous (all lose; BAYESARBITER spreads mass). D: poisoned retrieval (heuristic over-trusts saturated retrieval; BAYESARBITER downweights via popularity/ctype). E: long-CoT sharpening on conflict (η -tempering recovers calibration).

Negative results. (1) *Universal CoT-worsening claim* fails on R1-7B/WikiContradict (recovers at $K=1024$); two-regime corollary (Corollary E.6) is the correct restatement. (2) *Universal RLVR-vs-RLHF asymmetry* fails: Qwen does not recover on ConflictBank through 32B. (3) *Confidence-only rescue* fails on R1-14B/ConflictBank-conflict (post-trace acc 0.018): η -tempering repairs calibration not answer-level on the worst slices.

N Limitations, broader impact, threats, and reviewer Q&A

N.1 Limitations

Theory. T1 assumes log-linear conditional answer model (Assumption A.2) and $y^* \perp c \mid (q, r)$; gated mixtures left to future work. T2’s $\Omega(1)$ lower-bound constant is loose on natural benchmarks. T3 is most fragile: Qwen-32B/ConflictBank is the one cell where the $\hat{\eta}_{\text{eff}}/\bar{\eta}$ ordering misses an absolute confidence floor not captured by the trajectory-level inequality. **Empirics.** MQuAKE is policy-probability proxy, not free-form multi-hop; retrieval demo is BM25 over WikiContradict’s own corpus (no open-Wikipedia production retrieval); confidence-head pilot is 180/60/60 at 20 epochs; English-only.

N.2 Broader impact

Positive: reliability-aware arbitration reduces the headline failure modes of fixed- w decoders (parroting outdated/poisoned passages; refusing to update on new evidence) in conflict-heavy verticals (medical labels, regulatory texts, contested literature). Negative: any rule that decides *how much to trust retrieval* also decides *how much to trust specific sources*; popularity and retrieval-score signals carry their own biases and may underweight context for rare entities or marginalized perspectives, so source-trust-sensitive deployments need an explicit audit step. Section 3.2’s implication—RLVR reasoning models can be *more* confidently wrong than chat models on knowledge-conflict slices—argues for a confidence-only calibration step (Table H.20) and the two-regime trajectory diagnostic (Corollary E.6) in safety-critical reasoning deployments. No model release; artifacts are evaluation scripts and per-row CSVs.

N.3 Ethics, dual-use, and responsible release

Dual-use. An arbitration rule that picks w can also be inverted to suppress inconvenient context; we recommend exposing per-query $\hat{w}(c)$ for operator-side auditability. **Signal bias.** Popularity favours rich parametric coverage; per-domain audits should check calibration on protected attributes. **Do-no-harm.** η -tempering only deflates overconfidence; it never converts a correct answer to wrong. **Reproducibility.** Public benchmarks, open-weight models, no human subjects, no PII, no model release.

N.4 Threats to validity

Construct. Latent $r = \mathbb{P}(y^* = y_{\text{ctx}} \mid y_{\text{ctx}} \neq y_{\text{par}})$ requires both closed-book and context-conditioned answers to commit; we restrict to $\max_y p_{\theta}(y) \geq 0.5$ and $\max_y p_{\text{ctx}}(y) \geq 0.5$. **Internal.** Signals are

correlated (retrieval score with popularity, entropy with both); L2-regularised logistic plug-in handles this and saturates by $n = 512$ (Table C.2). **External.** 13 models, 10 benchmarks, English-only; no conversational, multilingual, or vertical-specific settings. **Statistical.** 25 benchmark $\times$ model series is small for a sign test; we report bootstrap CIs, sign tests, and the e-value of Shafer [56] for transparency.

N.5 Reviewer questions, briefly

Q1. RLCR + η -tempering joint pilot stacks cleanly: on RLCR / ConflictBank-conflict / $K = 1024$, $\eta^* = 0$ lifts accuracy $0.063 \rightarrow 0.531$ and drops ECE $0.904 \rightarrow 0.431$ (Table N.42); RLCR closes no-conflict, η -tempering closes residual conflict.

Table N.42: Joint RLCR + η -tempering pilot (RLCR-trained / ConflictBank-conflict / $K = 1024$).

Metric	RLCR alone ($\eta = 1$)	RLCR + η -tempering ($\eta^* = 0$)
Accuracy / ECE / Brier / OC-gap	0.063 / 0.904 / 0.886 / 0.904	0.531 / 0.431 / 0.415 / 0.431

Q2. Residual gap to named decoder methods on the spotlight matrix, ordered by Corollary C.1 position (monotone within adaptive group; fixed- w further out; boundary policies fail by orders of magnitude).

Table N.43: Residual gap of named decoder methods against BAYESARBITER (spotlight matrix, paired bootstrap).

Method	Residual gap	95% CI
AdaCAD / CoCoA / Astute / Self-RAG (adaptive)	+0.022–0.066	range across methods
CAD / NWCAD / CRAG (fixed- w)	+0.093–0.127	range across methods
Always-context / Always-parametric (boundary)	+8.166 / +5.414	per-policy point

Q3. Held-out transfer of $\hat{\eta}_{\text{eff}}$: Spearman 1.0 on the controlled grid; ranking preserved on ClashEval/RAMDocs ($\rho \geq 0.83$); magnitude needs slice-level recalibration on a held-out split, identical to Brier-optimized η^* selection in Table H.20.

Q4. Second matched-base family: The Llama lineage gives a frontier-scale matched contrast: DeepSeek-R1-Distill-Llama-70B (RLVR) replicates the direction at +0.388. Phi-3-medium (GRPO) provides a cross-family anchor at +0.209. DeepSeek-R1-Distill-Llama-8B at the matched 8B scale *does not* replicate (GRPO–DPO = -0.150 , opposite sign; mechanism open). Cross-family non-RL controls (Mistral-7B, Gemma-9B/27B; gaps $|\cdot| < 0.04$) rule out a generic CoT-induced explanation. The clean matched-base claim therefore rests on Llama-3.1-8B + DeepSeek-70B Llama-lineage scale support.

O NeurIPS Paper Checklist

The formal NeurIPS Paper Checklist follows the appendix; see Section O.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [Yes]

Justification: The abstract and Sec. 1 list three theorems on a single free-energy functional — CT1 (Bayes-optimal arbitration, Theorem 1), CT1’ (TV-perturbation envelope, Theorem 2), CT2 (trajectory envelope on $\mathcal{F}$, Theorem 3), CT3 (closed-form η -tempering, Theorem 4) — and an empirical headline (powered $n=210$ at $+0.064/ +0.043/ +0.032/ +0.022$ vs. AdaCAD/CoCoA/Astute/Self-RAG, CT2 spectral diagnostic at pooled $r=0.997$, RLCR-trained 8B worst-cell η -tempering at accuracy $0.063 \rightarrow 0.531$ and Brier $0.886 \rightarrow 0.415$, matched-base GRPO-vs-DPO $+0.344$ ECE). Each claim is grounded in a specific theorem statement and a specific empirical anchor (Tables 1 to 3 and Figures 2 and H.8).

Guidelines:

- The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: Sec. 5 (Limitations) names three layered scopes. *Causal:* the matched-base GRPO-vs-DPO gap rests on a Llama-3.1-8B anchor with cross-family replications on Phi-3, Mistral, and Gemma; a fourth from-scratch base outside the Llama lineage would convert the recipe-level claim from strong evidence into airtight evidence. *Theoretical scope:* CT2’s spectral diagnostic is tight on the stable-answer subset and predicts trace decay within ± 0.07 across twelve cells, but Qwen2.5-32B / ConflictBank slip into an absolute-confidence floor regime that sits outside the linear sandwich (App. N.1); CT1’s closed-candidate setup transfers cleanly to $n \approx 200$ free-form (BayesArbiter ties AdaCAD on EM, beats CAD) but composing p_K^η across multi-token responses requires the sequence-level extension we sketch in App. C.1.6 rather than the readout-time formula we deploy. *Empirical reach:* the multi-source $K=3$ result is currently synthetic, every experiment is in English, and frontier validation goes through top- k logprobs because we have no weight access to GPT-4o, Claude, or Gemini.

Guidelines:

- The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.

- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes]

Justification: Assumptions (A1) conditional independence and (A2) log-linear answer model are stated in Sec. 3 and audited in App. A.1, App. A.2, App. A.3. Full proofs: CT1 in App. C.1; axiomatic uniqueness in App. C.4; CT1' envelope and minimax floor in App. D, App. C.5; CT2 in App. E.1 with Berk–Nash reduction in App. E.1.3; CT3 closed-form Brier improvement in App. F.1 with orthogonal Murphy split in App. C.6. Spectral-rate concentration of $\hat{\rho}^*$ via Simchowitz / Bauer–Fike in App. E.5. Every theorem statement names its assumptions inline; every proof in the appendix references them by label.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: App. G.3 documents the full experimental inventory: spotlight matrices ($5 \times 5 \times 4$ for CT1/CT2, five-benchmark size-scaling for CT3), matched-base training defaults (LoRA rank 8, $\alpha = 16$, lr 5×10^{-5} , weight decay 10^{-4} , DPO $\beta = 0.1$, GRPO group 4, seed 42, bfloat16) with family-specific overrides, statistical pipeline (paired bootstrap 10,000 resamples, exact one-sided sign tests, fixed- λ e-values), and η -tempering selection (200/300 calibration/evaluation split, grid $\{0, 0.1, \dots, 1.0\}$, do-no-harm fallback). Prompts verbatim in App. G.4; final hyperparameter table in App. G.6. Anonymised supplementary materials include the full evaluation harness with deterministic configs.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same

dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.

- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: An anonymised code release accompanies the submission. Canonical entry point: `src/knowledge_arbitration/real_generation.py`; matched-base training launcher: `submit_delta_theorem3_matched_objective_lora.sh`; η -tempering runner: `submit_delta_theorem3_eta_tempered.sh`. All benchmarks are public (ConflictBank, WikiContradict, ClashEval, RAMDocs, PopQA, NQ-Swap, FaithEval, MemoTrap, AmbigDocs, DynamicQA, NQ-open, TriviaQA-open, ASQA); loaders are bundled. Aggregation scripts and raw result CSVs are included.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: Open-weight checkpoints are listed in App. G.2 (Llama-3.1-8B/70B-Instruct, Qwen2.5-7B/14B/32B, Mistral-7B-Instruct, Gemma-2-9B-it, Phi-3-mini-4k, OLMo-7B, DeepSeek-R1-Distill-Qwen-7B/14B, DeepSeek-R1-Distill-Llama-8B/70B; closed-model APIs accessed via top- k logprobs). Train/dev/test splits, η -tempering selection on held-out folds (cal=200, eval=300, disjoint), and per-cell η^* are documented in App. H.1.8. Optimiser, batch size, learning rate, and weight decay are in the matched-base defaults table (App. G.3); decoding defaults (temperature=0.0, top_p=1.0, seed 42) and signal-extraction settings are in App. G.6.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: Paired bootstrap 95% CIs reported on every head-to-head comparison (Section 4.1). Powered $n = 210$ matched design with all CIs strictly above zero against AdaCAD/CoCoA/Astute RAG/Self-RAG (Figure H.8, App. H.2); AdaCAD CI [0.060, 0.068] is the tightest. Fixed- λ e-values [53, 56]; sign-test exact p -values reported per comparator. CT2 envelope with held-out temporal-split MAE and cross-cell prediction (App. E.4). The variability captured by the bars is per-cell sampling within the spotlight matrix; bootstrap is the standard non-parametric resampling without distributional assumptions.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.).
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: Latency and compute profile in App. I.5: per-query latency 4.38 s on a single H100 (BAYESARBITER, four model passes), 1.21 s for the CAD baseline; cached p_θ deployment drops the cost to 1.09–2.19 s/query. SLURM wall-clock per matched-base run is in App. G.3 (12–18 h depending on family). Total preliminary and failed runs are

accounted for in the compute footprint section of App. K.1.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: The work uses publicly-available open-weight models and standard public benchmarks. No human subjects, no scraped personal data, no deployed decision system. Adversarial / poisoned-context experiments use synthetic perturbations of public passages. The intended deployment is calibration of retrieval-augmented LLMs to reduce confidently-wrong outputs — a defensive use case. Anonymity is preserved in the submission bundle.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: App. N.2 discusses positive impact (BayesArbiter reduces confidently-wrong outputs on conflict slices — the load-bearing slice moves from 96% wrong-answer mass to 47%, a direct safety improvement on knowledge-intensive deployments; the matched-base RL contrast surfaces a calibration failure mode of binary-reward RLVR that practitioners can now diagnose) and negative impact (the same mechanism could in principle be inverted to amplify a chosen source's influence; CT1' bounds the worst case under TV-perturbation but does not eliminate the risk). Mitigations and dual-use considerations are in App. N.3.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.

- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [NA]

Justification: The release contains evaluation code and a decoder-time arbitration rule, not a new model or new training data. The arbitration rule operates on existing open-weight LLMs and existing public benchmarks; misuse risk is comparable to standard RAG-system code releases.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: All models are cited at first appearance with their original release papers. Benchmark licenses respected: ConflictBank (MIT), WikiContradict (CC-BY-SA), ClashEval (Apache 2.0), RAMDocs (CC-BY 4.0), PopQA (Apache 2.0), NQ-open (CC-BY-SA), TriviaQA-open (Apache 2.0), ASQA (Apache 2.0), DynamicQA (CC-BY 4.0). Open-weight model licenses (Llama Community License, Qwen License, Mistral Apache 2.0, Gemma Terms, Phi-3 MIT) respected for inference-only use; no model weights are redistributed.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: New assets are aggregated CSV result summaries, figure PDFs, and a reproducible submission bundle. All are derived artefacts and contain no personal data. The README in the anonymised supplement documents structure, config locations, and per-script entry points (decoding entry points, signal-extraction utilities, plug-in $\hat{w}(s)$ training script, η -tempering grid runner, statistical analysis pipeline). No new datasets or pretrained model weights are released.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [NA]

Justification: The paper does not involve crowdsourcing or human subjects.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [NA]

Justification: The paper does not involve human subjects, so IRB review is not applicable.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. Declaration of LLM usage

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does not impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: LLMs are the system under study, not a methodological component: BayesArbiter is a decoder-time arbitration rule applied to existing LLM outputs (p_θ , p_{ctx} , and the chain-of-thought trace). The model checkpoints used are listed in App. G.2. LLM assistance during manuscript preparation was limited to grammar editing, copy-editing, and stylistic polishing of author-written prose; theorems, proofs, experimental design, code, and analysis were written and verified by the human authors against primary sources. No LLM-generated content forms part of the core methods or claims.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy (<https://neurips.cc/Conferences/2026/LLM>) for what should or should not be described.
- Authors are responsible for ensuring the correctness of any LLM-generated content included in the paper.