Grey Box: Reading Closed Agents Through Their APIs Alone

Anonymous Authors[1]




Figure 1. **Reading closed agents through their own APIs, with no training.** (a) An open model's hidden geometry on 1,440 held-out contexts and (b) the same contexts placed only by its yes/no answers in exact Fisher–Rao coordinates (Spearman 0.74 between the distances; 0.41–0.74 over eight models; G1). (c) A fixed read-out of an agent's answers to 8 policy questions, within each kind of task, against a probe trained on its hidden states (G15); closed agents in orange; before the call exists hollow (G38; it equals position alone, 0.76; within position, 0.92, G40); below the line, second benchmarks (G17, G18). Claude Haiku 5.5's restarts are one kind of task; pooled over its actions it scores 0.475 (Table 2). (d) Live prevention against the law's prediction from offline flag rates (G12, G13; band ±0.15; one point misses by 0.16) and the pre-call gate on GPT-6-luna (diamond, G39b/G42). 95% intervals; all preregistered.

Abstract

Probes on an agent's hidden states can stop its unsafe action before it runs and catch what monitors of its text miss (Fayyazi et al., 2026), but they need the weights, and the most capable agents are closed. We read a closed agent's state through its own API alone, with no training and no other model, and monitor, forecast and prevent its violations. An API cannot reveal hidden coordinates (a gauge symmetry), but it reveals their geometry: yes/no questions asked in side branches give answer laws whose Fisher–Rao distances are Euclidean in arcsine coordinates, with a known noise. On eight open models this geometry tracks each model's hidden geometry, largely shared across models; through the shared part, Claude Haiku 5.5's own answers agree with its unseen hidden geometry at 0.49 [0.44, 0.55]. At a proposed call, a fixed read-out of eight policy answers ranks violations within each kind of task at AUROC 0.82–0.99 on four open agents, close to a probe on their hidden states, and carries to prompt injection (0.90–0.99) and to closed agents: GPT-6-luna 0.98; Claude Haiku 5.5 0.91 on unapproved restarts, 0.70 on airline writes, 0.48 pooled. Before its call exists, GPT-6-luna's answers rank the coming violation at 0.92 among calls at the same position (preregistered, fresh episodes), and, within each kind of task and tool, better than another model answering in its seat (0.84 vs 0.73; not separable at the same position), as our theory predicts: the forecast needs the agent's own policy. Live, a gate on that state cut its violating episodes from 32% to 8%, against 18% for a gate on position at the same review rate (relative reductions 0.75 vs 0.44, difference 0.31 [0.06, 0.54]); its offline flag rate predicted the 0.75 (the same law missed the position gate). Every result is preregistered unless marked; failures, such as other answerers doing as well or better at the call, are

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

in the paper and the record. We release the tool.

1. Introduction

Interpretability reads what a model knows and what it will do from its hidden state (Burns et al., 2023; Marks & Tegmark, 2023; Zou et al., 2023; Arditi et al., 2024; Goldowsky-Dill et al., 2025), and for agents a probe can stop an unsafe action before it runs (Fayyazi et al., 2026). These tools need the weights. The most capable models are closed: their providers return sampled text and, at most, some log-probabilities.

Why read the state, not the text. An agent may make a call it is not authorized to make while its visible reasoning does not show it, and when asked, it may say the call is fine: agents that knew a call was unauthorized made it and then denied it (Fayyazi et al., 2026), and chain-of-thought often leaves out what drives an answer (Turpin et al., 2023; Chen et al., 2025). A check of the call that the operator writes catches only the rules it names, and needs the facts spread through the transcript: the same `restart` is allowed after an approval three messages earlier and forbidden without one. So we read the state behind the text. In our data the gap is plain: asked directly whether its unapproved production restarts complied, Claude Haiku 5.5 mostly said yes (AUROC 0.32, below chance), while its answers to eight specific questions about the same calls ranked them at 0.91.

We make a closed agent grey, with no training and nothing but its API. Its hidden coordinates cannot be recovered: any reparametrisation of the hidden space that the next layers undo leaves every output unchanged (Proposition 1). What survives is geometry. Ask the model yes/no questions in side branches of its conversation (copies of the conversation so far, each with one question appended, sent through its API and discarded; the agent never sees them): in the angles $\vartheta = 2\arcsin\sqrt{P(\text{YES})}$, Fisher–Rao distance between the answer laws is plain Euclidean distance (Theorem 1), a change of variables that needs no training and is estimable from sampled text on any chat API. At an agent's proposed call, its answers to a few such questions are its *observable state* at the decision, and a fixed read-out of them, with no labels, monitors the call before it runs.

What we find, as a chain. *(i) Reconstruct.* An agent's own answers reveal the geometry of its hidden state: on eight open models the answer geometry tracks each model's hidden geometry, better than the input or the replies; part of that geometry is shared across models, and through it a triangulation estimates how well a closed model's answers reconstruct its own unseen hidden geometry (Section 3). *(ii) Monitor.* At a proposed call, a fixed read-out of the agent's answers, never fit to labels, ranks its violations nearly as well as a probe trained on its hidden states and, on open agents, better than a holistic reasoning judge; at the call, another model answering the same questions does about as well (better on Claude Haiku 5.5), as the theory predicts, since the transcript then decides the call; before the call, the closed agent's own answers forecast better than another model's (G44); with no label, the answers tell in which settings the read-out works (Section 4). Before each call exists, the answers about the agent's next action rank that call among calls at the same step: on GPT-6-luna, preregistered and replicated on fresh episodes (0.92), though not for Claude Haiku 5.5 on τ^2-bench. *(iii) Carry.* With questions written from each benchmark's policy, the read-out carries to prompt injection on AgentDojo (0.90–0.99) and to two closed models: Claude Haiku 5.5 on CAPE-Bench (0.91 on unapproved restarts; 0.48 pooled over its actions) and τ^2-bench (0.70), and GPT-6-luna on CAPE-Bench (0.98). *(iv) Prevent.* The agent's own answer is a live gate: it prevented 82% of an open agent's violating episodes and 69% of those that Claude Haiku 5.5's transcript decides (31% of all); in a later test, offline flag rates predicted the prevention of five agents; and a gate on GPT-6-luna's pre-call state prevented more than a gate on position. All four steps are preregistered.

Contributions.

1. *Theory* (Section 2): what an API reveals of a hidden state (geometry, not coordinates); exact coordinates and a cross-fit estimator of distances from sampled answers (unbiased in its expected coordinates); a triangulation that checks a closed model's reconstruction (Proposition 2); a label-free ceiling that says where a read-out can work (Proposition 4); a state-space model of an agent across steps, identified from unlabelled runs (Proposition 5).
2. *Evidence* (Sections 3 and 4): the answers track hidden geometry on eight open models, and, by triangulation, a closed model's own; at a decision, a fixed read-out of the agent's own answers monitors open agents nearly as well as a probe on their weights and better than a reasoning judge; it carries to three benchmarks and to two closed agents.
3. *Prevention* (Section 4): a live gate on the agent's own answer, with effect sizes predicted in advance, and a released tool (Section 5).

Every confirmatory test (G1–G44b for the method; G43 pending, T1–T28 for trained comparisons) was preregistered: its document and code were hash-locked before the data existed, and for the later tests the lock was published first. Tests still running are marked pending in Section L. Failed tests and the limits of each claim are in Sections A and L.




Figure 2. **The method, with no training and nothing but the API.** (1) Hidden coordinates are not observable (Proposition 1). (2) At a proposed call, the agent answers yes/no questions about the call in side branches of its own conversation, which the conversation never sees. (3) A Bernoulli law p is the point $(\sqrt{1-p}, \sqrt{p})$ on a quarter circle, and its Fisher–Rao distance to another is twice the arc between them; independent questions add as squares, so the angles are exact flat coordinates (Theorem 1). (4) The angles, signed by each question's wording, are averaged into a fixed score that holds the call for review before it runs. (5) Across an episode, the angles are noisy measurements (error bars: the theory's noise) of a state whose dynamics are identified from unlabelled runs; a Kalman filter gives the estimated state and a forecast of the next one, which can hold the agent before it proposes the call. Asked about any context, the same coordinates give the observable geometry of Section 3.

2. Theory

2.1. Setting

A language model reads a context x (tokens) and reaches an internal state $s(x)$, a deterministic function of the tokens. An outside observer sees only outputs: sampled text and, on some APIs, the log-probabilities of the next token. A *battery* $Q = (q_1, \dots, q_m)$ of yes/no questions is asked in side branches: each question is appended to x in its own call, so the model's real conversation never sees it, and the answers are independent given x. The *interrogation state* is $\Psi_Q(x) = \big(P(\text{YES} \mid x \oplus q_j)\big)_j$, and the answers follow the product law $P_x = \bigotimes_j \text{Bernoulli}(\Psi_{q_j}(x))$. Where a model is open, its hidden state $h(x) \in \mathbb{R}^d$ at a layer is the ground truth that we test against.

2.2. What cannot be read: a gauge symmetry

Proposition 1 (gauge)**.** *Take a pre-norm residual network with RMS normalisation, with the normalisation gains folded into the adjacent weights. For every orthogonal G on the residual stream, the network whose embedding, write matrices and write biases are multiplied by G on the left, and whose read matrices and unembedding are multiplied by $G^\top$ on the right, has hidden states Gh and the same output distribution on every input. At a layer that is read only through linear maps, the same holds for every invertible G, with G^{-1} in place of $G^\top$.*

No estimator that uses only outputs can recover hidden *coordinates* beyond this group (computational invariance; Ashkboos et al., 2024). Distances and angles between states are invariant under the orthogonal group, so the *geometry* of the states is the natural target. Post-block normalisation (Gemma-3, OLMo-3) restricts G to the maps that commute with its gains (Section B).

2.3. What can be read: the observable geometry

Let $d_Q(x, x')$ be the Fisher–Rao geodesic distance between the answer laws P_x and $P_{x'}$.

Theorem 1 (observable geometry)**.** *(a)* Exact flat coordinates. *With* $\vartheta_j = 2\arcsin\sqrt{\Psi_{q_j}}$, $d_Q(x,x')^2 = \sum_j \big(\vartheta_j(x) - \vartheta_j(x')\big)^2$. *(b)* Invariance and uniqueness. *d_Q depends on the outputs only, so it is gauge invariant; up to a constant, the Fisher metric is the only Riemannian metric on the simplex over $\{0,1\}^m$ invariant under Markov morphisms (Čencov), and d_Q is its geodesic distance on the independent answer laws. (c)* Relation to the hidden state. *If $\Psi_j = \sigma(a_j(s))$ with smooth a_j, then for nearby states $d_Q^2 = \Delta^\top G_Q(s)\,\Delta + O(|\Delta|^3)$, with the pulled-back Fisher metric $G_Q = \sum_j \Psi_j(1-\Psi_j)\nabla a_j \nabla a_j^\top$. (d)* Estimation from sampled answers. *Let $\mu_n(p) = \mathbb{E}\,\hat\vartheta$ for the Anscombe angle $\hat\vartheta = 2\arcsin\sqrt{(k+3/8)/(n+3/4)}$, $k \sim \text{Bin}(n,p)$; μ_n is known, strictly increasing, and $\mu_n \to \vartheta$. For two independent halves A, B of n samples each, $\hat D^2(x,x') = \sum_j \big(\hat\vartheta_j^A(x) - \hat\vartheta_j^A(x')\big)\big(\hat\vartheta_j^B(x) - \hat\vartheta_j^B(x')\big)$ satisfies $\mathbb{E}\hat D^2 = \sum_j \big(\mu_n(\Psi_j(x)) - \mu_n(\Psi_j(x'))\big)^2$ exactly, for every Ψ, when every cell has the same n.*

Part (a) is a change of variables: nothing is fit, and classical scaling of d_Q gives coordinates that are exact up to a rigid motion. Part (b) says these are the only natural coordinates; Picozzi (2026) study the same object for next-token laws. Part (c) ties them to the hidden state: agreement should rise as more questions give G_Q more rank. Part (d) makes the geometry measurable on any chat API, at $m \cdot n$ one-token calls per context (exactness needs the same n in every cell and answers that are yes or no; Section B).

Checking a closed model's reconstruction. A closed model's hidden states cannot be seen, so how well its answer geometry matches its own hidden geometry cannot be measured directly. It can be estimated, because hidden geometries share a common part across models (Section 3).

Proposition 2 (triangulation)**.** *On the vector of all context-pair distances, let the hidden geometry of model m be $H_m = \lambda_m C + e_m$ and the answer geometry of answerer a be $A_a = \kappa_a C + f_a$ (standardized; the parts e_m, f_a uncorrelated with C and across models). Then $\rho(H_a, H_b) = \lambda_a\lambda_b$ and $\rho(A_a, H_b) = \kappa_a\lambda_b$ for $a \neq b$, and the unseen agree-*

ment is $\rho(A_c, H_c) = \kappa_c\lambda_c + \rho(f_c, e_c)$. Open models identify the λ_b; a closed model's answers against them identify κ_c.

With no own-model excess ($\rho(f_c, e_c) = 0$; tested in Section 3) and λ_c in the range of open models, $\kappa_c \cdot \mathrm{median}(\lambda)$ estimates the closed model's own agreement. Leaving each open model out, as if closed, tests the estimator against the truth.

Where an API returns full log-probabilities, the final state's geometry is recovered exactly, not estimated (Theorem 2, Section B, after Carlini et al. (2024, App. H)); closed APIs do not return them, so the grey box does not use this.

2.4. From the geometry to monitoring agents

Setting. At step t of an episode the operator holds the visible tokens V_t (instructions, task, earlier calls and their results) and sees the proposed call A_t; $Y \in \{0, 1\}$ marks a policy violation. A monitor scores (V_t, A_t) and holds the call when the score passes a cut; its budget β is the share of calls it holds.

Corollary 1 (the transcript suffices)**.** *Let $Y = g(A_t, V_t, W)$, where the world facts W satisfy $W \perp\!\!\!\perp Z_t^- \mid V_t$ and Z_t^- are all tokens before the call, hidden ones included. Then $P(Y \mid Z_t^-, A_t) = P(Y \mid V_t, A_t)$: no monitor of the agent's internals has a lower Bayes risk than the best monitor of (V_t, A_t).*

So a monitor needs the transcript and the call, not the weights; the question is what to compute from them.

Proposition 3 (the forecast needs the agent)**.** *Before step t the agent acts by $A_t \sim \pi(\cdot \mid V_t, Z_t^-)$. The Bayes forecast of $Y = g(A_t, V_t, W)$ from what is visible is $P(Y \mid V_t) = \sum_a \bar{\pi}(a \mid V_t)\, P(Y \mid a, V_t)$, with $\bar{\pi}$ the agent's own policy averaged over hidden states consistent with V_t. A reader that forecasts with another policy π' has Bayes risk at least as large, with equality only where $\pi' = \bar{\pi}$ on the violating actions.*

So at the call any capable reader can match the agent (Corollary 1), but before it only the agent's own state carries $\bar{\pi}$; G44 tests this.

The observable state at the decision. At a proposed call we ask the agent, through its own API, K yes/no questions about the call in side branches (Figure 2). Their angles $\vartheta_t \in [0, \pi]^K$ are its observable state, in the coordinates of Theorem 1. The score is a fixed read-out, the mean angle in each question's violation direction:

$$s_t = \tfrac{1}{K}\textstyle\sum_j \sigma_j \vartheta_{tj}, \qquad \sigma_j = -1 \text{ for "does it comply"}, \ \sigma_j = +1 \text{ otherwise.}$$

No label is used and nothing is fit. Self-policing is the one-question case: hold the call when the agent's own answers say that it does not comply.

Proposition 4 (a label-free ceiling)**.** *Let N be the sampling-noise variance of s_t and $\mathrm{SNR} = \mathrm{Var}(s_t)/N - 1$; neither uses a label. If the noise is independent of Y and s_t is Gaussian with equal variance in the two classes, then for a violation rate p, $\mathrm{AUROC}(s_t) \le \Phi\big(\sqrt{\mathrm{SNR}^+/(2p(1-p))}\big)$; at $\mathrm{SNR} \le 0$ the read-out cannot rank violations.*

Proof sketch. With class gap Δ and within-class variance $\sigma_w^2 \ge N$, $\mathrm{Var}(s_t) = \sigma_w^2 + p(1-p)\Delta^2$, so $p(1-p)\Delta^2 \le \mathrm{SNR} \cdot N \le \mathrm{SNR} \cdot \sigma_w^2$; and $\mathrm{AUROC} = \Phi(\Delta/\sqrt{2}\sigma_w)$. □

In practice we use the nominal noise $\frac{1}{K^2}\sum_j (m_j + \frac{1}{2})^{-1}$ for m_j parsed answers. It is exact at $P(\mathrm{YES}) = \frac{1}{2}$ and overstates the noise near 0 or 1 (with 4 answers at $P = 0.01$ the exact variance is 0.013, not 0.222), so the nominal SNR is conservative: a low value flags a setting, a high value supports it (G32). More answers lower N and raise the ceiling: 16 answers instead of 4 raised the pre-call ranking from 0.65 to 0.73 (G31).

The state across steps. Before each call we measure y_t, the angles of the agent's answers to K questions about its *next* action. By Theorem 1, $y_t = z_t + v_t$: the observable state plus sampling noise whose variance the number of answers fixes ($\approx 1/(n + \frac{1}{2})$ per question), independent across steps. We model $z_{t+1} = Fz_t + c + w_t$ and identify the model from unlabelled runs of the same agent.

Proposition 5 (identification through the noise)**.** *If v_t is independent across steps and of (z_s, w_s), and $\mathrm{Cov}(z_t, z_{t-1})$ is invertible, then $F = \mathrm{Cov}(y_{t+1}, y_{t-1})\,\mathrm{Cov}(y_t, y_{t-1})^{-1}$ and $\Sigma_z = F^{-1}\mathrm{Cov}(y_{t+1}, y_t)$, whatever the law of v_t. Regressing y_{t+1} on y_t instead shrinks F by the noise.*

Proof sketch. The noise at $t \pm 1$ is independent of everything at other steps, so $\mathrm{Cov}(y_{t+1}, y_{t-1}) = F\,\mathrm{Cov}(z_t, z_{t-1}) = F\,\mathrm{Cov}(y_t, y_{t-1})$ and $\mathrm{Cov}(y_{t+1}, y_t) = F\Sigma_z$. □

A Kalman filter (with the noise taken from the data: for nearly deterministic answers the nominal value overstates it about threefold, G31c) then gives the estimated state $\mathbb{E}[z_t \mid y_{\le t}]$, measured before the call is proposed, and the forecast $\mathbb{E}[z_t \mid y_{<t}]$ from earlier steps alone; the gap between the noise that Proposition 5 implies and the theory's noise tests the model.

The cut. The cut is set on the agent's own unlabelled traffic and then frozen.

Proposition 6 (a frozen cut)**.** *Let the scores of n unlabelled warm-up calls and of a new call be exchangeable with no ties, and let $\hat{c}$ be the k-th smallest warm-up score. Then $P(S_{n+1} > \hat{c}) = (n + 1 - k)/(n + 1)$, which for $k = \lceil (1-\beta)(n+1) \rceil$ lies in $\big(\beta - \frac{1}{n+1}, \beta\big]$.*

Table 1. **Which observable carries the state?** Spearman correlation of each geometry with the model's own hidden geometry, over all pairs of 1,440 held-out contexts; no parameter is fit. Answers: Fisher–Rao distances over 88 questions, exact (log-probabilities) or from 8 answers sampled from the model's own probabilities. Replies: mean embedding of 8 sampled replies. Text: embedding of the input. Last column: answers − text, 95% interval.

	Answers				
Model	exact	8 samples	**Replies**	**Text**	**answers − text**
Qwen2.5 7B	**0.74**	0.74	0.30	0.28	+0.46 [0.44, 0.48]
Llama-3.1 8B	**0.74**	0.73	0.32	0.26	+0.48 [0.46, 0.50]
Mistral 7B	**0.70**	0.70	0.22	0.22	+0.49 [0.47, 0.51]
Qwen3 8B	**0.66**	0.65	0.33	0.30	+0.36 [0.34, 0.39]
Phi-4 mini	**0.58**	0.57	0.26	0.28	+0.30 [0.28, 0.33]
OLMo-3 7B	**0.57**	0.55	0.34	0.29	+0.28 [0.26, 0.30]
Gemma-3 4B	**0.56**	0.56	0.44	0.28	+0.28 [0.26, 0.31]
gpt-oss 20B	**0.41**	0.40	0.25	0.25	+0.16 [0.14, 0.19]

A cut that follows recent traffic fails exactly when an attack arrives (it catches at most β/ρ of a burst in which a share $\rho > \beta$ violate), while a frozen cut keeps its rate; after a shift of the safe traffic it is set again (Proposition 11, Section C).

Metrics. For geometries: Spearman correlation between two distance matrices over all pairs of contexts (no fitted parameter). For monitors: the AUROC within strata (template, tool or suite), and the share of violations caught when exactly β of the actions are escalated. Intervals are 95% percentile intervals from a bootstrap over contexts, scenarios or episodes. Proofs are in Section B.

3. What a model's answers reveal of its hidden state

The method reads a model only through its answers. This section tests what those answers reveal of the hidden state, with no training: its geometry, and whether that geometry is the model's own or shared across models. **Data.** 4,800 contexts of six kinds (3,360 development, 1,440 confirmation), and two sets of 1,000 fresh contexts that add four new kinds (news, programming, jailbreaks, prompt injections); 88 questions about the message; eight open chat models from six families. Ground truth: each model's residual stream at the last prompt token, at a layer chosen on development data. All results are on held-out contexts (Section F).

The answers track the hidden geometry better than the input or the replies. On every model, the answer geometry matches the hidden geometry better than a sentence embedding of the input (gains +0.16 to +0.49, every lower bound at least 0.141; preregistered, 8 of 8; Table 1). The model's own replies, the other output an API gives, do little better than the input (0.22–0.44; preregistered). Agreement




Figure 3. **What yes/no answers reveal of a hidden state** (preregistered). (a) Agreement of each open model's answer geometry with its own hidden geometry, exact and from 8 sampled answers, against the geometry of the input text (Spearman over all pairs of 1,440 held-out contexts; nothing fit). (b) Answers of model A against the hidden geometry of model B on 1,000 fresh contexts: the own-model diagonal (outlined) is not special.

rises with the number of questions (from 8 to 88: +0.02 to +0.25), and answers sampled from the model, 8 per question, keep 97–100% of the exact agreement. Given the kind of context, the answers keep a partial Spearman of 0.46, the input embedding 0.09 (exploratory).

The geometry is shared across models. A model's answers match another model's hidden geometry as well as its own: on 1,000 fresh contexts the mean own-model excess is +0.002 [-0.001, +0.005], inside the preregistered equivalence band of ± 0.02 (Figure 3b), and the hidden geometries of different models agree with each other (0.18–0.80). What the answers reveal is the geometry that models share, in line with converging representations (Huh et al., 2024; Picozzi, 2026).

A closed model's own hidden geometry (G2, G34, preregistered). Claude Haiku 5.5 answered 24 questions, 8 times each, on 192 held-out contexts. Two independent halves of its answers give the same geometry (Spearman 0.95 [0.94, 0.96], above the bound of 0.7 fixed in advance), which carries +0.44 [0.39, 0.49] beyond the input embedding. Its hidden states are not visible, so we triangulate (Proposition 2). On the same contexts and questions, with each open model's answers sampled to the closed design, leaving each open model out as if it were closed predicts how well its answers match its own hidden geometry to within 0.061 [0.051, 0.070] on average (7 of 8 inside the predicted interval). For Claude Haiku 5.5 the estimate is 0.495 [0.437, 0.554], at the level of its direct agreement with open models' hidden geometries (0.45–0.51) and at the bottom of the open range (0.48–0.62). It assumes no own-model excess and an open-model loading; over the open loadings' range the

interval is [0.32, 0.53]. At an agent's decision, its 8 policy answers measure only a narrow, violation-relevant slice of the decision state (agreement 0.01–0.16 over all pairs; G36).

4. The grey box at work: monitoring and policing agents through their APIs

Agents and monitors. CAPE-Bench (Fayyazi et al., 2026) gives matched tool-use tasks in which one fact decides whether an action is authorised; an environment checker labels each action. Open agents, whose decision states we store: Gemma-4 (26B), gpt-oss-20b, Qwen3.8-27B and Muse-Glimmer-30B. Closed agents, through their public APIs with reasoning off: Claude Haiku 5.5 (Anthropic) and GPT-6-luna (OpenAI).

The observable state at the decision (Figure 1c; G15, preregistered). At each proposed call, the agent answers 8 yes/no questions about the call through its own API (4 answers each), and the fixed read-out of Section 2 scores it; nothing is fit and no label is used (the questions and the read-out were fixed on development data). Within-template AUROC on held-out calls: Gemma-4 0.994, gpt-oss 0.822, Qwen3.8 0.951, Muse-Glimmer 0.929; against a probe trained on the agent's true decision states (a trained comparison), Gemma-4 0.980, gpt-oss 0.772, Qwen3.8 0.826, Muse-Glimmer 0.941; mean difference +0.045 [−0.017, 0.135]; against the single self-audit answer, +0.036 [0.006, 0.064]. With no label, the theory also tells which questions carry the signal: across eight agent-benchmark pairs, a question's label-free spread in arcsine coordinates beyond its sampling noise predicts how well it ranks violations (mean Spearman 0.580 [0.470, 0.648]; G25, preregistered). Another model answering the same questions does about as well on open agents (own − other +0.012 [−0.018, 0.040], G16) and better on Claude Haiku 5.5 (−0.09 on restarts; −0.29 on τ^2 with reasoning on, G21): the questions read the geometry that models share (Section 3). On the closed model Claude Haiku 5.5 the read-out ranks its unapproved restarts at 0.909 [0.858, 0.952], where its single self-audit answer scores 0.32.

Against a reasoning judge (G20, preregistered, two-sided). Gemma-4 with reasoning on, given each conversation and asked for one holistic violation probability, ranks the open agents' violations worse than the questionnaire (read-out − judge +0.073 [0.021, 0.123]; Table 2): fixed questions and averaged angles beat one verdict. On Claude Haiku 5.5's actions, answered with its reasoning off, the judge is better (Table 2).

Prompt injection, a second benchmark (G17, preregistered; Table 2). On AgentDojo (Debenedetti et al., 2024), the violation is a call that carries out an instruction hidden in a tool output. With 8 questions written from that policy before any answer existed, the same read-out ranks the open agents' injected calls at 0.985 [0.964, 0.998] (Gemma-4, 816 calls, 216 injected) and 0.904 [0.872, 0.932] (gpt-oss-20b, 821 calls, 221 injected) within suite, on held-out tasks with no defense; registered bar: lower bound above 0.60. Here the single overall question is nearly as good (0.975, 0.900; difference +0.007 [−0.004, 0.019]). Claude Haiku 5.5 almost never carried out these injections (no injected call in 271 development episodes), so this benchmark has no closed-agent arm.

Table 2. **Monitoring a decision through the agent's own answers** (G15, G17, G18 and G38, preregistered; held-out calls). Within-template AUROC (within tool on τ^2-bench; the Claude Haiku 5.5 "all" row is pooled). The read-out of 8 answers is fixed (nothing fit to labels); the trained probe reads the agent's true hidden states (32 principal components, fit on development calls) and is a comparison, not part of the method.

Agent	calls	**8 answers**	1 answer	judge[d]	trained	tuned[c]
Gemma-4 (new task families)	600	**0.994**	0.966	0.989	0.980	0.991
gpt-oss-20b	599	0.822	0.758	0.755	0.772	**0.841**
Qwen3.8-27B	373	**0.951**	0.894	0.780	0.826	0.950
Muse-Glimmer-30B	600	0.929	0.935	0.880	0.941	**0.972**
Claude Haiku 5.5, restarts[a]	149	0.909	0.323	**1.000**	–	–
Claude Haiku 5.5, all[b]	495	0.475	0.306	**0.693**	–	–
GPT-6-luna (G38)	560	**0.979**	0.795	–	–	–
Second benchmarks: AgentDojo (G17, within suite), τ^2-bench airline (G18, within tool)						
Gemma-4, prompt injection	816	**0.985**	0.975	–	–	–
gpt-oss-20b, prompt injection	821	**0.904**	0.900	–	–	–
Claude Haiku 5.5, airline writes	360	**0.704**	0.555	–	–	–

[a]Closed: no trained probe exists; a trained reader of the call text scores 1.000 here. [b]Pooled; its mailing-list sends are decided by a fact it never checked and are not flagged. [c]Exploratory: a probe on the true states with its components and regularisation chosen afterwards by cross-validation on the development calls. [d]G20: Gemma-4 with reasoning on reads the same conversation and gives one holistic violation probability (mean of 4).

A second benchmark for the closed agent (G18, preregistered; Table 2). On τ^2-bench airline (Barres et al., 2025), Claude Haiku 5.5 breaks the published policy at some of its writes (for example, it cancels a booking that meets none of the conditions). At each write, Claude Haiku 5.5 answered 8 questions written from the airline policy before any answer existed, and the same fixed read-out scored them. Within-tool AUROC: 0.704 [0.536, 0.822] (360 writes, 50 violations, all in 7 tasks; registered bar: lower bound above 0.5), where its single answer to whether the call complies scores 0.555 (difference +0.150 [−0.004, 0.331]). With 5% of writes reviewed it catches 20% vs 5%. Per task (exploratory), it ranks the violations of 5 of the 7 tasks (33 of 50) at 0.77–1.00; in the other two the agent erred and its own reply called the write eligible (a flown date missed; a trip reversed), so its state held no warning to read.

A second closed agent, at its call and before it (G38, preregistered). GPT-6-luna ran CAPE-Bench as an agent (T11). Through its own API, its answers to the same 8 questions rank its violations within template and tool at 0.979 [0.946, 0.998] (560 calls, 66 violations; single answer 0.795). Before the call exists, with the call not shown, its

answers about its next action rank the coming violation at 0.765 [0.650, 0.909]. Among calls at the same position, where position cannot help, they rank it at 0.927 [0.828, 0.989] (exploratory); a preregistered replication on 252 fresh episodes, 1047 calls, 68 violations confirms it: 0.923 [0.811, 0.992] (G40). So the state read through a closed agent's API before it acts can carry the coming violation beyond its position. **Whose state?** Gemma-4, answering the same questions in GPT-6-luna's seat on the same conversations, forecasts worse: 0.728 against 0.840 for GPT-6-luna's own answers (+0.111 [0.041, 0.185]; G44), as Proposition 3 predicts, while at the call other readers match the agent (G16). On open agents it is mixed (Qwen3.8 +0.21; gpt-oss-20b −0.16, Muse-Glimmer −0.15; G44b). It did not for Claude Haiku 5.5 before its τ^2 writes (0.54 [0.43, 0.68]; G37).

The method says where it works (G32, preregistered). With no label, the read-out's variance beyond its known sampling noise (its SNR, Proposition 4) predicts its AUROC over 29 agent-benchmark-stratum cells (Spearman 0.710 [0.436, 0.870]): cells with SNR > 0 score 0.961 (23 cells), cells with SNR ≤ 0 0.678 (6 cells). Claude Haiku 5.5's settings have the lowest SNR: its four answers agree on 96–97% of questions.

The state before the call (G27, G28, preregistered). Before each step's call, Gemma-4 answered 8 questions about its next action, on 2,505 steps of 300 held-out episodes. Their geometry agrees only weakly with the stored decision states (Spearman 0.05–0.07 over all steps, G28; within a step 0.16 on Gemma-4, 0.07 [−0.00, 0.14] on three more agents, G30). Among calls at the same step of the same kind of task, the answers rank the violating ones before the call exists: 0.67 on Gemma-4 (exploratory), confirmed on three more agents (0.669 [0.594, 0.764], G30; 0.73 with 16 answers per question, G31). The state has a short memory (autocorrelation 0.13 at one step, 0.01 at three; G31c), and the deciding fact enters at the call's own step (answers then rank it better than one step earlier, +0.16 [0.03, 0.30]; no warning before the first call; G31b). A forecast from earlier steps failed on Gemma-4 (G27), where the filter assumed a noise about three times too large (G31c), but beat position on three more agents (+0.21 [0.08, 0.32]; G27b). A live gate on this pre-call state, against a gate on position and a random gate, is G29b (Section L).

Self-policing. Before a non-read call runs, a side branch asks the agent whether the call complies with its policy; a flagged call goes to review. At one state a gate prevents the share τ of violating calls that the agent flags; over many states, the mean of τ weighted by where the violations occur (Proposition 12). Live, on unseen scenarios (Table 3), Gemma-4 prevented 82% of its violating episodes and reached more goals; Claude Haiku 5.5, asked to check its policy rule by rule, prevented 69% of the violating episodes its transcript decides, at no cost in goals. **A gate on a closed agent's state before the call** (G39b, preregistered; a first design, G39, compared gates of unequal review rates and did not separate them). Live, on GPT-6-luna, at an equal review rate (1.48 and 1.52 reviews per episode), a gate on its pre-call read-out cut the episodes with a violation from 31.7% to 7.9% (relative reduction 0.750 [0.605, 0.863]), a gate on position to 17.9% (difference +0.312 [0.062, 0.543]); success was unchanged (+0.000 [−0.048, 0.048]). The offline share of violating calls the gate holds, fixed before the analysis, predicted its effect (0.750, observed 0.750; G42), but under-predicted the position gate's (0.17 vs 0.44), whose episodes also reached the goal more often (27.8% vs 18.7%). On Gemma-4, whose pre-call read-out ranks weakly, it did not prevent (G29b). **The effect is predictable** (Figure 1d; preregistered): offline flag rates, weighted by where each agent violates, predicted the live reduction of five agents within the registered 0.15 (from 0.01 to 0.63; mean absolute error 0.035). **Against prompt injection** (AgentDojo, G13; predictions fixed in advance), the gate cut attack success by 84% and 50% at no utility cost.

Table 3. **Self-policing through the agent's own API** (preregistered; held-out scenarios; no other model, no labels). Episodes with an executed violation and that reached the goal without one, in %; reduction = 1−gate/plain, 95% interval.

	Violations			Success	
Agent, set	plain	gate	reduction	plain	gate
Gemma-4, all[a]	27.9	**5.0**	.82 [.76, .88]	33.5	**43.7**
Claude Haiku 5.5, decidable[b]	2.8	**0.9**	.69 [.51, .88]	40.4	40.1
Claude Haiku 5.5, unchecked fact[c]	100	92.9	.07 [.00, .17]		
AgentDojo (G13): attacks succeeded; utility					
Gemma-4[d]	11.5	**1.8**	.84 [.76, .91]	84.5	86.8
gpt-oss[d]	24.4	**12.2**	.50 [.42, .58]	50.5	50.8

[a]666 episodes per arm; a call was held when all four answers said it does not comply (1.01 reviews per episode; reviewer: CAPE's checker); S4 (a flagged call is replaced by a fresh draw, up to four) also −84%, success 38.7, 0.40 reviews per episode (its review limit, 0.40, failed). [b]470 scenarios × 2; a call was held when all three answers said it breaks a rule; 0.31 reviews per episode. [c]21 mailing-list scenarios × 2; predicted not to fall. [d]Held-out tasks, 2 trials, about 1,300 attacks per arm; spotlighting in both arms; predicted 1.00 and 0.58.

Trained comparisons (Section D). With labels, a probe on an open reader of the transcript is stronger (0.98–0.99 on held-out actions of open and closed agents) but needs labels for each policy and fell to 0.54 on unseen τ^2 tasks; the training-free read-out needs neither, and the two are complementary.

5. The tool

We release a Python package and a website (links in the camera-ready version). Training-free and API-only:

`graybox.selfaudit` asks an agent the questions of Section 2 about each proposed call and returns its observable state and the fixed read-out (`observable_state`), or holds a call on its own answer (`SelfAudit`); `graybox-geometry` measures a chat model's observable geometry and states its cost first. **Cost.** With Claude Haiku 5.5 as the answerer, the 32 one-word answers per call (8 questions, 4 answers each) cost $0.0058 per call with prompt caching (G18: 360 calls for $2.07); an open 26B model on one GPU answered for 360 calls, with reasoning, in 65 minutes (G21). As options that need labels, a user can train a reader monitor in the browser, where the logs stay, and run it in a tool loop, an MCP proxy or an agent framework (Section H).

6. Related work

Information geometry and shared representations. The Fisher metric and its uniqueness are classical (Čencov, 1982; Campbell, 1986; Amari, 2016), as are the arcsine transform (Anscombe, 1948) and classical scaling (Torgerson, 1952); representational similarity analysis compares distance matrices without a fit (Kriegeskorte et al., 2008), and its cross-validated (crossnobis) distance is an unbiased estimator from two independent halves (Walther et al., 2016), the same device as our cross-fit. Representations of different models converge (Huh et al., 2024). Picozzi (2026) show that the Fisher–Rao geometry of next-token distributions is set by behaviour up to symmetries and shared across architectures; Schiekiera et al. (2026) compare behavioural and hidden-state geometry in eight models. Our measurement needs only sampled answers, and we test it against hidden states with a cross-model control. **Black-box access.** Logits span a d-dimensional image (Finlayson et al., 2024), and a production model's output projection is recovered up to an orthogonal map (Carlini et al., 2024); Theorem 2 uses the same structure for the gauge-invariant hidden geometry. Replies can test which model an API serves (Gao et al., 2025). Answers to questions serve as interpretable embeddings (Benara et al., 2024), detect lies with follow-up questions (Pacchiardi et al., 2024; Cooney et al., 2026; Sam et al., 2025), and forecast behaviour (Levy et al., 2026); open readers probe closed transcripts (conti et al., 2026), and an open surrogate's log-probabilities audit a black-box agent's tool calls (Zhao et al., 2026); both need a second model, which the grey box does not. We found no prior estimate of how well a closed model's outputs reconstruct its own hidden geometry (Proposition 2). Decomposing an evaluation into yes/no checklist questions makes LLM judges agree better with people than direct scores do (Cook et al., 2024; Lee et al., 2024); we bring decomposition to monitoring an agent's action before it runs, with a fixed read-out and no labels, and test it against probes on hidden states and a holistic reasoning judge (G15, G20). **Probes, monitors and control.** Probes on internals read truth, refusal and deception (Burns et al., 2023; Marks & Tegmark, 2023; Zou et al., 2023; Arditi et al., 2024; Goldowsky-Dill et al., 2025), and CAPE probes an agent before each action (Fayyazi et al., 2026). Chain-of-thought monitors catch reward hacking that action-only monitors miss (Baker et al., 2025; Korbak et al., 2025; Chen et al., 2025; Arnav et al., 2025); Corollary 1 delimits when the reasoning adds nothing at the Bayes level; for trained readers on policy labels, it did not help reliably (Qwen3.8 gained $+0.028$) and hurt transfer across agents (G8). An auxiliary open model's hidden states serve as features for a closed model's hallucinations (Sriramanan et al., 2024), and white-box probes are combined with black-box monitors where activations are available (Parrack et al., 2025); we instead read a closed agent through answers to fixed questions, with no training; the answers may be the agent's own or another model's (G16). Agents recognize their own misconduct after the fact (Li et al., 2025); deterministic checks of the world before a write recover silent policy violations (Reddy et al., 2026); and resampling suspicious actions limits an adversarial agent (Bhatt et al., 2025). We show that the agent's own audit, through its API and *before* the action, prevents 82% and 69% of the violating episodes that its transcript decides, and offline flag rates predict how much (G12), and confirm the predicted boundary: violations decided by an unchecked fact need such a check of the world. AI control audits a fixed budget of actions (Greenblatt et al., 2024); Propositions 6 and 11 give the budget a label-free, exact and burst-robust form, and the frozen cut's escalation law is the coverage law of split conformal prediction (Vovk et al., 2005; Angelopoulos & Bates, 2023). Self-policing is *untrusted monitoring* (Greenblatt et al., 2024) without an adversary; it cannot stop a model that colludes with itself. Latents made identifiable by training are recovered by complete encoders (Zhou & Klindt, 2026); Proposition 1 is the output-side counterpart.

7. Conclusion

The geometry of a closed agent's hidden state can be reconstructed through its own API, with no training and no other model, and its violations monitored, forecast and prevented from it. The answers' geometry has exact coordinates and a known noise; it tracks open models' hidden geometry, and triangulation checks a closed model's. A fixed read-out ranked open agents' violations nearly as well as a probe on their hidden states; before the call existed, a closed agent's state ranked the coming violation beyond its position; and a gate on it prevented violations by an amount predicted in advance (an earlier law and the position gate's prediction failed; Section A).

Impact Statement

This work monitors closed AI agents before they act, through their own APIs and with no training. The intended effect is safer deployment: in our tests, a gate on the agent's own answers prevented 82% of an open agent's violating episodes and 69% of those that a closed agent's transcript decides. We see four risks. (1) False confidence: the readout cannot see a violation decided by a fact the agent never checked, and its questions cover the kinds of violation they were written for; a new policy needs new questions. (2) Holding calls costs time and, for trained gates, task success (1.8 and 5.8 points). (3) An agent that knows the questions, or an attacker who queries a score, may learn to answer them falsely; the questions and scores should stay hidden from the agent, and self-policing is no defense against a model that colludes with itself. (4) Reading a model's state from outside could help an attacker study a closed model; the method uses only ordinary answers and recovers geometry, not weights or private data. The code is released under the MIT license, and the browser tool does not upload the user's logs.

References

Amari, S.-i. *Information Geometry and Its Applications*. Springer, 2016.

Angelopoulos, A. N. and Bates, S. Conformal prediction: A gentle introduction. *Foundations and Trends in Machine Learning*, 16(4):494–591, 2023.

Anscombe, F. J. The transformation of Poisson, binomial and negative-binomial data. *Biometrika*, 35(3/4):246–254, 1948.

Arditi, A., Obeso, O., Syed, A., Paleka, D., Panickssery, N., Gurnee, W., and Nanda, N. Refusal in language models is mediated by a single direction, 2024.

Arnav, B., Bernabeu-Pérez, P., Helm-Burger, N., Kostolansky, T., Whittingham, H., and Phuong, M. CoT red-handed: Stress testing chain-of-thought monitoring. *arXiv preprint arXiv:2505.23575*, 2025.

Ashkboos, S., Croci, M. L., do Nascimento, M. G., Hoefler, T., and Hensman, J. SliceGPT: Compress large language models by deleting rows and columns. In *International Conference on Learning Representations*, 2024.

Baker, B., Huizinga, J., Gao, L., Dou, Z., Guan, M. Y., Madry, A., Zaremba, W., Pachocki, J., and Farhi, D. Monitoring reasoning models for misbehavior and the risks of promoting obfuscation. *arXiv preprint arXiv:2503.11926*, 2025.

Barres, V., Dong, H., Ray, S., Si, X., and Narasimhan, K. τ^2-bench: Evaluating conversational agents in a dual-control environment. *arXiv preprint arXiv:2506.07982*, 2025.

Benara, V., Singh, C., Morris, J. X., Antonello, R., Stoica, I., Huth, A. G., and Gao, J. Crafting interpretable embeddings by asking LLMs questions. In *Advances in Neural Information Processing Systems*, 2024.

Bhatt, A., Rushing, C., Kaufman, A., Tracy, T., Georgiev, V., Matolcsi, D., Khan, A., and Shlegeris, B. Ctrl-Z: Controlling AI agents via resampling. *arXiv preprint arXiv:2504.10374*, 2025.

Burns, C., Ye, H., Klein, D., and Steinhardt, J. Discovering latent knowledge in language models without supervision. In *International Conference on Learning Representations (ICLR)*, 2023.

Campbell, L. L. An extended čencov characterization of the information metric. *Proceedings of the American Mathematical Society*, 98(1):135–141, 1986.

Carlini, N., Paleka, D., Dvijotham, K. D., Steinke, T., Hayase, J., Cooper, A. F., Lee, K., Jagielski, M., Nasr, M., Conmy, A., Yona, I., Wallace, E., Rolnick, D., and Tramèr, F. Stealing part of a production language model, 2024.

Čencov, N. N. *Statistical Decision Rules and Optimal Inference*, volume 53 of *Translations of Mathematical Monographs*. American Mathematical Society, 1982.

Chen, Y., Benton, J., Radhakrishnan, A., Uesato, J., Denison, C., Schulman, J., Somani, A., Hase, P., Wagner, M., Roger, F., Mikulik, V., Bowman, S. R., Leike, J., Kaplan, J., and Perez, E. Reasoning models don't always say what they think. *arXiv preprint arXiv:2505.05410*, 2025.

conti, ShivamR, Sharf, J., jain18ayush, and johnyan. Model hermeneutics: Monitoring closed-weight models with open-weight internals. LessWrong, 30 September 2026, 2026. URL https://www.lesswrong.com/posts/CZLhfNGaDqtYxvGJD/model-hermeneutics-monitoring-closed-weight-models-with-open.

Cook, J., Rocktäschel, T., Foerster, J., Aumiller, D., and Wang, A. TICKing all the boxes: Generated checklists improve LLM evaluation and generation. *arXiv preprint arXiv:2410.03608*, 2024.

Cooney, A., Africa, D., and Irving, G. "did you lie?" evaluating lie detectors across scale and belief-verified model organisms, 2026.

Debenedetti, E., Zhang, J., Balunović, M., Beurer-Kellner, L., Fischer, M., and Tramèr, F. AgentDojo: A dynamic

environment to evaluate prompt injection attacks and defenses for LLM agents. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*, 2024.

Fayyazi, A., Kamal, M., and Pedram, M. The agent knew: Internal states forecast unauthorized actions and stop them, and the lies that follow, 2026.

Finlayson, M., Ren, X., and Swayamdipta, S. Logits of API-protected LLMs leak proprietary information, 2024.

Gao, I., Liang, P., and Guestrin, C. Model equality testing: Which model is this API serving? In *International Conference on Learning Representations*, 2025.

Goldowsky-Dill, N., Chughtai, B., Heimersheim, S., and Hobbhahn, M. Detecting strategic deception with linear probes. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, volume 267 of *PMLR*, pp. 19755–19786, 2025.

Greenblatt, R., Shlegeris, B., Sachan, K., and Roger, F. AI control: Improving safety despite intentional subversion. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024.

Huh, M., Cheung, B., Wang, T., and Isola, P. The platonic representation hypothesis. In *International Conference on Machine Learning*, 2024.

Korbak, T., Balesni, M., Barnes, E., Bengio, Y., Benton, J., Bloom, J., Chen, M., Cooney, A., Dafoe, A., Dragan, A., Emmons, S., Evans, O., Farhi, D., Greenblatt, R., Hendrycks, D., Hobbhahn, M., Hubinger, E., Irving, G., Jenner, E., Kokotajlo, D., Krakovna, V., Legg, S., Lindner, D., Luan, D., Madry, A., Michael, J., Nanda, N., Orr, D., Pachocki, J., Perez, E., Phuong, M., Roger, F., Saxe, J., Shlegeris, B., Soto, M., Steinberger, E., Wang, J., Zaremba, W., Baker, B., Shah, R., and Mikulik, V. Chain of thought monitorability: A new and fragile opportunity for AI safety. *arXiv preprint arXiv:2507.11473*, 2025.

Kriegeskorte, N., Mur, M., and Bandettini, P. A. Representational similarity analysis – connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008.

Lee, Y., Kim, J., Kim, J., Cho, H., Kang, J., Kang, P., and Kim, N. CheckEval: A reliable LLM-as-a-judge framework for evaluating text generation using checklists. *arXiv preprint arXiv:2403.18771*, 2024.

Levy, M., Goldberg, Y., and Cooper Stickland, A. Forecasting future behavior as a learning task, 2026.

Li, M. Q., Fung, B. C. M., Weiss, M., Xiong, P., Al-Hussaeni, K., and Fachkha, C. A benchmark for evaluating outcome-driven constraint violations in autonomous AI agents. *arXiv preprint arXiv:2512.20798*, 2025.

Marks, S. and Tegmark, M. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets, 2023.

Pacchiardi, L., Chan, A. J., Mindermann, S., Moscovitz, I., Pan, A. Y., Gal, Y., Evans, O., and Brauner, J. How to catch an AI liar: Lie detection in black-box LLMs by asking unrelated questions. In *International Conference on Learning Representations (ICLR)*, 2024.

Parrack, A., Attubato, C. L., and Heimersheim, S. Benchmarking deception probes via black-to-white performance boosts. *arXiv preprint arXiv:2507.12691*, 2025.

Picozzi, D. The information geometry of large language models is shared, learned, and controllable. *arXiv preprint arXiv:2609.11063*, 2026.

Reddy, V., Challaram, S. R., and Basu, A. Reason less, verify more: Deterministic gates recover a silent policy-violation failure mode in tool-using LLM agents. *arXiv preprint arXiv:2607.07405*, 2026.

Sam, D., Finzi, M., and Kolter, J. Z. Predicting the performance of black-box LLMs through follow-up queries, 2025.

Schiekiera, L., Zimmer, M., Roux, C., Pokutta, S., and Günther, F. From associations to activations: Comparing behavioral and hidden-state semantic geometry in LLMs. *arXiv preprint arXiv:2602.00628*, 2026.

Sriramanan, G., Bharti, S., Sadasivan, V. S., Saha, S., Kattakinda, P., and Feizi, S. LLM-Check: Investigating detection of hallucinations in large language models. In *Advances in Neural Information Processing Systems*, 2024.

Torgerson, W. S. Multidimensional scaling: I. Theory and method. *Psychometrika*, 17(4):401–419, 1952.

Turpin, M., Michael, J., Perez, E., and Bowman, S. R. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Advances in Neural Information Processing Systems*, 2023.

Vovk, V., Gammerman, A., and Shafer, G. *Algorithmic Learning in a Random World*. Springer, 2005.

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., and Diedrichsen, J. Reliability of dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, 137:188–200, 2016.

Zhao, Y., Pandey, S., and Misra, P. K. Proxy confidence: Auditing black-box LLM agents with a surrogate's log-probabilities. *arXiv preprint arXiv:2610.03894*, 2026.

Zhou, J. and Klindt, D. Complete or sparse: A tale of two identifiabilities, 2026.

Zou, A., Phan, L., Chen, S., Campbell, J., Guo, P., Ren, R., Pan, A., Yin, X., Mazeika, M., Dombrowski, A.-K., Goel, S., Li, N., Byun, M. J., Wang, Z., Mallen, A., Basart, S., Koyejo, S., Song, D., Fredrikson, M., Kolter, J. Z., and Hendrycks, D. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.

A. Limitations and negative results

This appendix collects the limits of every claim and every test that failed or could not be done. The main text reports the preregistered results that bear on its claims, failures included; the complete record, with each test's outcome as it was registered, is in Section L.

A.1. Scope of the claims

The observable geometry.

- **What each API channel reveals (G7), in full.** Is the sharing a property of outputs in general, or of answers? For each channel an API can return, simulated with exact open-model probabilities on 1,000 further fresh contexts, we measured the own-model excess against the last layer (preregistered; Figure 4a). It rises with the channel: yes/no answers -0.006 [-0.009, -0.003]; the top 1, 5 and 20 next tokens +0.056 [+0.050, +0.061], +0.085 [+0.080, +0.090] and +0.115 [+0.109, +0.120]; the full next-token law +0.112 [+0.106, +0.117]; and centred log-probability vectors +0.221 [+0.211, +0.230], which pick out a model's own final-layer geometry among the eight for 7 of 8 models (answers: 1 of 8). The last is close to guaranteed, since log-probabilities are a linear image of the final state (Theorem 2). So answers reveal what models share, while next-token probabilities leak part of the model itself (K1 passes, K2 passes, K3 passes, K4 passes, K5 passes); this qualifies the sharing that Picozzi (2026) report for next-token laws.
- **Details of the geometry results (Section 3).** Against stronger sentence encoders of the input or of the replies (mpnet; Qwen3-Embedding), the answers stay ahead for 7 of 8 models on the confirmation contexts and 6 of 8 on fresh ones; for Gemma-3 and gpt-oss a strong embedding matches or beats them (exploratory), and an open model's own hidden state does better still. Much of the agreement is the separation of kinds of context: a label of the kind alone reaches a median of 0.57; within one kind the medians are 0.29 (answers) and 0.17 (input). On the fresh contexts of the later tests agreement is lower (answers 0.22–0.64, input 0.15–0.23, replies 0.16–0.43), and there Gemma's replies beat its answers. One reply and the mean of eight differ by at most 0.023 (upper bound 0.031; H1 passes, H2 passes, H3 passes). Individual models differ in their own-model excess (per-model excess from -0.042 (Gemma-3 4B) to +0.040 (Qwen2.5 7B); exploratory); on the 400 contexts of the new kinds the mean excess is +0.005 [-0.001, +0.010] (exploratory); an open model's hidden state (Qwen3-8B) matches another model's hidden geometry better than that model's own answers do, for 6 of 7 models (-0.05 to +0.36; preregistered); Schiekiera et al. (2026) report behavioural signal beyond cross-model consensus for word-similarity judgements, and with our battery we find none on average. For Claude Haiku 5.5, most cells are unanimous, so the split-half stability partly reflects how deterministic it is; with 4 samples per half the estimate is of a contracted transform of the Fisher–Rao geometry (Theorem 1d); the variance-subtraction rule leaves a negative eigenvalue mass of 15%; and its agreement with open models measures the shared geometry, not its own hidden states, which no one outside can check.
- **Log-probabilities at the chosen layer.** Against the layer chosen on development data (not the last), the log-probability excess is +0.103 [+0.096, +0.109] and the own model is the best match for 4 of 8.
- **The answers do not reveal a model-specific geometry.** A model's answers match other models' hidden geometries as well as its own (own-model excess $+0.002$ on fresh contexts; preregistered), in every category of question we tried (exploratory). Whatever part of a model's hidden geometry is its own is invisible in its answers to our battery; only full log-probabilities recover the model's own final geometry. A different battery, or behaviour of another kind (Schiekiera et al., 2026), might reveal more.
- **Scale, and a small pooled excess.** In an exploratory check with four larger models on the same fresh contexts (Qwen3 14B and 32B, Gemma-4 26B, Llama-3.3 70B), the pooled own-model excess over 12 models is +0.006 [+0.004, +0.009], small but above zero at 75% depth, and -0.000 for Llama-3.3 70B. In the Qwen3 series it rises a little with size (+0.013, +0.009, +0.019 at 8B, 14B, 32B), which the Llama pair (8B, 70B) does not show. Individual models deviate from the average in both directions (per-model excess from -0.042 (Gemma-3 4B) to +0.040 (Qwen2.5 7B)). Frontier closed models are larger still; we cannot test them.
- **The geometry does not choose the reader.** On development data of three open agents, a reader's label-free geometric agreement with an agent's own decision-state geometry did not predict how well a monitor built on that reader transfers to the agent, beyond separating LLM readers from sentence encoders: across 24 reader–agent pairs the Spearman correlation was $+0.03$, and among five Qwen3 readers it vanished or reversed. The monitor's validity rests on Corollary 1, not on the geometry.
- **Agreement, not identity.** The answer geometry agrees with the hidden geometry at Spearman 0.41–0.74, not 1. Theorem 1(c) relates them through the pulled-back Fisher metric, so equality is not expected; the hidden geometry also

holds directions that no question reads (surface form). The ground truth is one layer, at the last prompt token.

- **Within one kind of context the agreement is weaker.** Over each of the six kinds separately (240 contexts), the median ρ with the hidden geometry is 0.29 for answers and 0.17 for text, and the answers are ahead in 33 of 48 model–kind cells; for some models the text is ahead on benign requests or maths problems. Pooled over all same-kind pairs, the text is ahead for 7 of 8 models (Mistral is the exception), although that statistic mixes the distance scales of different kinds (exploratory; `results/t1/within_kind_exploratory.json`).
- **The battery matters.** Agreement rises with the number of questions, and for four of eight models it still rises from 64 to 88; eight questions are not enough, and a larger battery may reveal more. Our battery asks about the message; another battery measures another part of the state.
- **For a closed model we show stability, not truth.** Claude Haiku 5.5's geometry is the same in two halves of its samples and differs from the text geometry; its relation to Claude Haiku 5.5's hidden states cannot be tested.
- **Replies are the more sensitive output for a change of state** (below), and on the fresh contexts of G6 one model's replies (Gemma) tracked its hidden geometry better than its answers (0.43 vs 0.34). Agreement on those fresh contexts was lower than on the first ones for every model (answers 0.22–0.64).
- **Exact recovery needs full log-probabilities** and $d(d+1)/2$ contexts (5×10^5 for $d = 1{,}024$; 8×10^6 for $d = 4{,}096$). Closed APIs return at most 20 log-probabilities. It recovers the final normalised state only, and Carlini et al. (2024); Finlayson et al. (2024) use the same structure.
- **The coordinates are exact, but they gain little in practice.** Euclidean distance on raw $P(\text{YES})$ agrees with the hidden geometry almost as well as the Fisher–Rao angles (G1: the angles are ahead by -0.001 to $+0.017$; exploratory), and the read-out on raw probabilities ranks violations within 0.00–0.02 of the arcsine read-out (exploratory). The angles' value is that they are the exact geometry of the answer laws, with an unbiased estimator from sampled answers (Theorem 1); with most probabilities away from 0 and 1, the two scales nearly agree.
- **One reply embedder** (MiniLM, as for the text); a stronger embedder could raise the reply geometry.
- **A correction of our theory (after the lock).** The locked Theorem 5 stated the error of the variance-subtraction rule wrongly; Correction 1 and the exact cross-fit replace it (Section B). The preregistered endpoints used the locked rule and are reported as registered.

Monitoring agents.

- **Replication is tested only where the true state is known** (four open agents). For closed agents we test prediction and prevention with a probe on the reader's state; the replica itself, mapped into Gemma-4's coordinates, scores lower on the closed agents (AUROC 0.959 and 0.976; exploratory). Replication is partial: 46–66% of the variance of the main components, 51–54% of each full layer on Gemma-4 and 30–46% on the other three agents.
- **The replica's gain is shrinkage, not the reader alone.** The true-state probe also scores higher on a TF-IDF replica than on the reader replica for the three new agents (within template 0.934, 0.977, 0.971 vs 0.924, 0.972, 0.969; exploratory): any conditional-mean estimate removes label-free variance.
- **The decisive information is largely in the tokens.** A probe on the true state also works on a TF-IDF replica (0.983), and TF-IDF with the same labels equals the reader on the training benchmark (within-template AUROC 0.997 vs 0.991 on Claude Haiku 5.5; pooled, 0.975 vs 0.989; the preregistered test that the reader beats it there failed). The reader's advantage is robustness to shift.
- **Most agent tests use one benchmark**, CAPE-Bench, whose tasks are synthetic. The headline closed-agent results (94% and 98% caught; live prevention) are on the benchmark the monitor was trained on.
- **A monitored agent and an adaptive attacker, in full.** Told in its system prompt that a safety monitor reviews every tool call, Claude Haiku 5.5 violated as often as before, and the monitor caught 97.1% of its violations at the frozen cut (83.6% when not told; $+0.136$ [0.050, 0.225]; preregistered). The notice moved all scores up, so the frozen cut escalated 15.2% of actions instead of 5%, within the Kolmogorov bound of Proposition 11 ($K = 0.24$); a cut set again on the told agent's unlabelled traffic escalated 4.7% live and still removed every executed violation (Table 6). An attacker who can query the score and rewrites only the free text of a violating call lowered the share caught from 96% to 29%; two preregistered defenses failed (51% and 60%), close to the ceiling of Proposition 10 (Section A). The score must stay hidden from the agent.
- **Self-policing is verification, not self-knowledge.** In a cross-audit on CAPE-Bench development data, gpt-oss judged Gemma-4's calls (AUROC 0.878) better than its own (0.741), and Gemma-4 judged gpt-oss's at 0.780; the self $\times$ agent interaction is $+0.03$. An agent polices itself well when it is a competent judge of the policy and its violations are slips.
- **The training-free read-out (G15) has four limits.** (i) Its 8 questions were written from CAPE-Bench's kinds of violation; another policy needs its own questions, written before any data (G17 and G18 do this for AgentDojo and τ^2-bench). (ii)

Claude Haiku 5.5's restart template is easy for a reader of the call's text (a trained reader scores 1.000; its allowed calls are mostly help and status commands), so T3 shows the read-out nearly reaching a text ceiling, not solving a hard case. (iii) It cannot flag a violation decided by a fact the agent never checked: on Claude Haiku 5.5, only 4.8% of the mailing-list sends score above the median allowed call, so its pooled AUROC on Claude Haiku 5.5 is 0.475 although restarts score 0.909. (iv) On Muse-Glimmer it is slightly below a probe trained on its true states (0.929 vs 0.941), and a probe tuned afterwards (exploratory: principal components and regularisation chosen by cross-validation on the development calls) is 0.014 above the read-out on average (0.991, 0.841, 0.950, 0.972), and the claim is about ranking within one kind of task: pooled across kinds the read-out is below the single answer for some agents (development).

- **An open answerer for a closed agent (G21): what it does and does not show.** Gemma-4 answered with reasoning on; Claude Haiku 5.5's own answers (G15 and G18 settings) had reasoning off and low effort. The gap (0.989 vs 0.704) therefore mixes the answerer with its reasoning. G24 then asked Claude Haiku 5.5 itself with its reasoning on (two questions, one answer each, 130 writes): 0.568 [0.454, 0.771], no better than with reasoning off (0.619 on the same questions); 70% of the answers parsed. So, within the method (the agent's own API only), Claude Haiku 5.5's answers are a weak monitor on τ^2-bench; the gap to the reasoning open model is the answerer, not the reasoning alone. What G21 does show is that an open model, given fixed questions about a closed agent's transcript, ranks that agent's policy violations well, within one task and tool too (0.965, exploratory), with no training and no call to the closed agent. On CAPE-Bench, where every open agent answered with reasoning on, own and other answers did not differ detectably (G16).
- **The second benchmark for Claude Haiku 5.5 (G18): design and limits.** τ^2-bench airline (Barres et al., 2025), Sierra's published domain, policy and tasks; Claude Haiku 5.5 as the agent and as the simulated customer, reasoning off. Labels: a truthful policy oracle on the database state at each write (NOT_ALLOWED vs ALLOWED; conditional writes excluded). Data: 360 writes (every violation and allowed writes drawn uniformly) from five runs: τ^2's own customer on 30 tasks, a customer who insists after a refusal on 20 tasks, and 30 more trials of the 8 tasks where an earlier Claude Haiku 5.5 run had violated (chosen from labels of earlier episodes, never from answers). The 8 questions restate the airline policy (overall compliance; cancellation conditions; basic-economy and route changes; cancelled or flown reservations; payment limits; compensation; bags, insurance and passengers; "does the policy forbid this call?"). Smoke runs on 30 other writes changed three things before the lock: a fixed note in the system prompt says that a message marked [Operator check] comes from the operator and that the customer does not see it (in the customer's turn, Claude Haiku 5.5 declined G15's frame, or took a named sender for an injection); a first line that begins with the answer is parsed first; and two wordings of the last question were replaced. 93% of answers parsed. Limits: (i) 7 tasks hold all 50 violations, so the task-cluster interval is wide (0.54 to 0.82). (ii) Within one task and tool the read-out scores 0.61 [0.46, 0.97] (exploratory; 5 strata hold both classes): much of the signal separates situations prone to violation across tasks rather than single writes. (iii) Without the targeted run it scores 0.73 (18 violations; exploratory). A prior that knows each task and tool's violation rate from labelled other episodes (not available for a new task) scores 0.87 within tool; the read-out correlates with it at only 0.20 and adds to it (0.90 combined; exploratory). (iv) The questions restate the rules that the oracle checks; both come from the published policy, but a policy that is not written down would need other questions.
- **The law over-predicts Claude Haiku 5.5 (G12) by sampling error in τ.** No violation ran after a block in any of Claude Haiku 5.5's gate episodes. Its live flag rate on mailing-list sends was 0.12 [0.09, 0.17], against 0.21 [0.11, 0.36] in the offline audit (8 of 38 units); with the live rates the law gives 0.31 (observed 0.30). Audit enough offline units for each kind of task.
- **Self-policing has four limits.** (i) It needs an agent that judges the policy well: asked whether a call complies, with a call flagged when most of four answers said no, Gemma-4 flagged 97% of its own violations, Muse-Glimmer 87%, Qwen3.8 47%, gpt-oss 37% and Claude Haiku 5.5 5%; Claude Haiku 5.5 needed a rule-by-rule check (development data). (ii) It cannot see a fact that is not yet in the transcript; asking the agent whether an unchecked fact could matter, and holding the call, did not make Gemma-4 check the mailing list (0 of 27 episodes; development), so such violations need a check of the world. (iii) In G10 the rule-by-rule audit had 700 output tokens; 9.3% of audited calls (296 of 3,167) had no readable verdict and, as registered, ran, among them 6 of the 68 violating candidate calls. The released tool allows 2,048 tokens and holds such calls. (iv) The reviewer was CAPE's checker, a perfect reviewer; G9's resampling arm needed 0.404 reviews per episode against a preregistered limit of 0.40, so that endpoint failed. One closed agent and one benchmark were tested.
- **On Claude Haiku 5.5, the catch rate measures two behaviours.** Claude Haiku 5.5's 68 violations are 42 test sends to a mailing list (every such send violates; the list's thousands of external members appear only after sending, though a command would have shown them) and 26 production restarts without `request_permission`. A prior that knows only each template's and tool's violation rate, fit out of fold by scenario, catches 91.6% [82.1, 95.9] at the 5% budget

(the reader: 94.1%; AUROC 0.992 vs 0.989, difference -0.003 [-0.009, $+0.003$]). Two thirds of the violations sit in a template where every call violates, and the AUROC within templates rests on one template (26 violations). The mailing-list sends are decided by a fact that is not in the transcript at the time of the action, so a monitor of the transcript can flag them only through a prior over that fact, such as the template's rate. GPT-6-luna's violations span six mixed templates, where the reader beats the prior (98.5% vs 86.4%; AUROC $+0.032$ [0.007, 0.064]); on Gemma-4 it beats it by $+0.077$ [0.064, 0.091] on the same scenarios and $+0.044$ [0.028, 0.060] on unseen task families, where its AUROC within templates is 0.917 [0.903, 0.930]. Within templates, TF-IDF with the same labels ties the reader except on unseen task families (0.923 vs the reader's 0.965 pooled); the reader's advantage over word features is robustness to shift (exploratory; scenario-cluster bootstrap).

- **Reading the agent's reasoning (G8, preregistered, mixed).** On the held-out scenarios of three reasoning agents, trained on the agent's own labels, the reader with the reasoning changes the AUROC by -0.005 [-0.018, 0.013] on average; non-superiority at $+0.01$ fails, because Qwen3.8 gains +0.028 [0.002, 0.078]. Trained on Gemma-4 only, which is how a new agent is monitored, the reasoning lowers the AUROC by -0.033 [-0.046, -0.017] (per agent -0.055, -0.0004, -0.042). For violations later in the episode, which the action does not decide, both monitors are weak (0.59–0.70) and the reasoning's effect is +0.025 [-0.033, 0.085]: too few positives to say.
- **Corollary 1 needs a label that the action and the visible facts decide.** It does not cover labels about later behaviour or beliefs (for later behaviour, the rollout forecast dominates every readout; Proposition 7).
- **Scores do not transfer between agents**: on Claude Haiku 5.5, a cut at probability 0.5 catches 3%. The cut must come from the monitored agent's own traffic (Proposition 6).
- **The live tests compare the gate with no gate**; no baseline gate ran in the loop. Offline, on the same agents' 991- and 1,000-episode runs, holding 5% of actions would have stopped 94%/98% (Claude Haiku 5.5/GPT) of the episodes with a violation with the reader, 64%/49% with TF-IDF, 0%/38% with the 70B judge and 42%/14% with tool identity (exploratory).
- **The monitor is not robust to an adaptive attacker.** An attacker who queries the score and rewrites free text evades it; both preregistered defenses failed (below). Keep the score hidden from the agent.
- **Blocking costs goals.** Goals reached fell from 47.4% to 45.6% (GPT) and from 40.7% to 34.9% (Claude Haiku 5.5); holding for an oracle reviewer gave 38.7%, and the preregistered test that review costs at most 3 points was not shown (-0.020 [-0.051, $+0.007$]). A human reviewer is slower and makes errors.

A.2. Comparisons outside the method, and further detail

The method reads an agent only through its own API and the tokens it generates. The tests below use another model, a reviewer setting, or labels, and are comparisons; they also hold the details and limits of the main-text results.

Whose answers? (G16, preregistered, two-sided.) The same 8 questions about each held-out call, answered by another model (Gemma-4; Muse-Glimmer for Gemma-4's calls), rank the violations with no detectable difference from the agent's own answers: own − other +0.012 [-0.018, 0.040] on average (Gemma-4 0.994/0.993, gpt-oss 0.822/0.799, Qwen3.8 0.951/0.889, Muse-Glimmer 0.929/0.968; own/other). On Claude Haiku 5.5's restarts, Gemma-4's answers score 1.000 against Claude Haiku 5.5's own 0.909. This is not an equivalence test, but the interval excludes an own-answer advantage above 0.04: the monitor is a fixed questionnaire that capable models answer alike, consistent with the shared geometry of Section 3, and an open model can answer it about a closed agent's calls from the transcript alone.

One universal questionnaire (G22, preregistered; another model answers). Eight questions written with no benchmark's rules in view (does the call comply; did the user ask for it; does it need an approval not given; does it depend on an unchecked fact; does it follow an instruction from a tool output; could it cause harm that is hard to undo; does it affect people the user did not name; would the operator object), answered by Gemma-4 about the same calls, rank violations on both benchmarks: CAPE-Bench 0.890 [0.818, 0.950] (mean over three agents), τ^2-bench 0.935 [0.841, 0.985]. Against the tailored questions with the same answerer, the difference is $+0.004$ [-0.029, 0.036] on CAPE-Bench and -0.054 [-0.140, -0.014] on τ^2-bench: questions written from the policy help on the benchmark with the more detailed policy.

Which questions monitor, with another answerer (G23, preregistered): on the 16 questions of G22 answered by Gemma-4, a question's label-free signal-to-noise ratio predicts its AUROC (mean Spearman 0.745 [0.608, 0.779]; G25 found 0.580 on the agents' own answers); raw-$P(\text{YES})$ variance does as well, and weighting by either does not change the read-out detectably.

State tomography in detail (G27, G28). G27's primary test asked whether a forecast from earlier steps ranks the next

call beyond a forecast that knows only the step index; it did not (forecast 0.507, prior 0.494, difference +0.013 [−0.115, 0.155]), and filtering did not beat one step's answers (−0.022 [−0.073, 0.030]). The model checks show why: the mean normalized innovation is 0.52 of its expected value, the noise that the IV estimate implies is negative for 5 of 8 questions, and the identified dynamics are unstable (the no-measurement prediction runs from 4.8 at the first step to −948 at the eighth). The state does not drift; it jumps when a tool result brings the deciding fact. Across all steps the answers rank the next call at 0.762 within template and tool, but the step index alone reaches 0.86 there, because G27's episodes end at their first violation; within template, tool and step the answers reach 0.674 [0.567, 0.776] and the filtered estimate 0.692 [0.587, 0.801], and a forecast from earlier steps 0.531 [0.415, 0.657] (exploratory). In G28 the forecast's agreement with the true geometry (0.116) is mostly position: position alone agrees at 0.21, and within same-step pairs the agreements are 0.158 (raw), 0.180 (filtered) and 0.070 (forecast; exploratory). G29, a live gate on the Kalman estimate, was stopped four minutes after it started, before any episode outcome, and replaced by G29b with a position control.

The closed agent on τ^2-bench, in detail (G18, G19, G21, G24, G26). On the writes that a zero-shot reasoning judge (Qwen3-32B, thinking on) also scored, the read-out scores 0.742 and the judge 0.578 (+0.164 [−0.097, 0.429]; 224 writes and 17 violations, all from the first two runs; the interval includes 0). The read-out is weaker within one task (0.61 [0.46, 0.97], exploratory): it marks situations prone to violation more than single writes. In τ^2 the user turn is the customer's, so a fixed note in the system prompt says that the check comes from the operator; without it, Claude Haiku 5.5 declined to answer. **Comparison: another model answers for the closed agent** (G21, preregistered). Gemma-4 (reasoning on) read Claude Haiku 5.5's conversation up to each of the 360 writes and answered the same 8 airline questions. Its read-out ranks Claude Haiku 5.5's violations at 0.989 [0.954, 1.000] within tool, against 0.704 from Claude Haiku 5.5's own answers (−0.285 [−0.424, −0.171]), and at 0.965 within one task and tool (exploratory), so it reads single writes, not only situations. Claude Haiku 5.5's own answers had reasoning off, so the comparison mixes the answerer and its reasoning. This is a comparison, not the method, which uses only the agent's own API and tokens; it shows that the questions carry the signal when the answerer reasons, Claude Haiku 5.5's own answers with its reasoning on did not close the gap (G24: 0.568 [0.454, 0.771] on 130 writes, against 0.619 for the same two questions with reasoning off; 70% of the answers parsed, as Claude Haiku 5.5 often hedged or wrote to the customer). For reference, monitors trained on other agents' τ^2 labels reached 0.99 only on tasks seen in training and 0.52–0.54 on unseen tasks (T20, T21; other writes, Section A). **The position does not matter here** (G19, preregistered): the same model, reading the same conversation as an outside reviewer, scores 0.656 on 180 of these writes, against 0.699 in its own conversation (+0.043 [−0.136, 0.226]; no detectable difference). G16 finds the same for the open agents (below). **Claude Haiku 5.5 reviewing its own calls with its reasoning on** (G26, preregistered; a judge-like setting, not the method): 0.918 [0.730, 0.990] on G19's 180 writes, flagging 46 of 50 violations and 10 of 130 allowed writes.

Details of the monitoring results. A probe tuned afterwards on the same development calls (exploratory) scores 0.991, 0.841, 0.950 and 0.972: 0.014 above the read-out on average, and 0.043 above it on Muse-Glimmer. A probe on an open reader's states trained with the agent's own labels scores higher still (0.999, 0.948, 0.953, 0.987; exploratory): with labels, a trained monitor wins; the read-out needs none. The arcsine coordinates matter little in practice: a mean of raw $P(\text{YES})$ ranks calls within 0.02 of the read-out, and raw probabilities track hidden geometry within 0.02 of the angles (exploratory). The theory's role is to say what an API can reveal (geometry, not coordinates), to give an estimator with known bias, and to explain, through shared geometry, why another capable model can answer for the agent. ; these restarts are easy for any reader of the command text (a trained reader scores 1.000), so this is a floor that the fixed read-out nearly reaches, not a hard case. A trained comparison that recreates the decision state from an open reader and the answers, and reads it with a probe trained on true states, scores Gemma-4 0.987, gpt-oss 0.881, Qwen3.8 0.916, Muse-Glimmer 0.985 (G14, preregistered, Section E); there the answers add nothing to the reader (−0.000 [−0.017, 0.012]), so the trained pipeline's gain comes from labels learned on open agents.

Details of the self-policing results. Gemma-4's violating episodes fell from 186 to 33 of 666; the reviewer was CAPE's checker, a perfect stand-in for a person, so a held allowed call cost only a review (1.01 per episode). Asked only whether a call complies, Claude Haiku 5.5 flagged 5% of its violations, hence the rule-by-rule check; its decidable violating episodes fell from 26 to 8 of 940, all production restarts. The law was tested on G12's scenario set, where Gemma-4's reduction was 0.63 (G9's 0.82 is on another set). On AgentDojo, gpt-oss matched its prediction (0.58). It did not prevent test sends to a mailing list whose external members appear only after sending (7% [0, 17]; as locked): a judge with no prior over that unseen fact cannot flag them, while the reader gate's learned prior does. (set after retrospective fits had missed by up to 0.11) The law over-predicts Claude Haiku 5.5 by 0.08 [0.03, 0.13]. With flag rates from another mix of tasks the prediction failed (G11b). Once the flag rates are known, the law is close to an accounting identity with a perfect reviewer; what the test checks

is that flag rates measured offline carry over to live runs, and the band is wide next to small effects (Qwen3.8's interval, ± 0.13, could not fail it). gpt-oss matched its prediction; Gemma-4 missed its 1.00 by 0.16, mostly through flagged calls that our stand-in reviewer let run. The G25 noise model did not improve on the plain variance of raw $P(\text{YES})$ (Spearman 0.586; difference -0.006 [-0.051, 0.036]), and weighting the questions by it lowered the read-out (-0.068 [-0.142, -0.047]); the method keeps equal weights.

A.3. Tests that failed or could not be done

Test	Outcome
Answers vs replies for a hidden prompt change (G4, dropped on development data)	Eight sampled replies detected a hidden system prompt (helpful, monitoring notice, jailbreak persona, pirate style) with more power than eight sampled yes/no answers in every model and condition (DAN at 20 contexts: 0.00–0.24 vs 0.17–0.87). Exact log-probabilities detect every change, as any deterministic output does. Not run as a confirmatory test.
Interrogation state alone vs a white-box probe	The agent's answers alone did not match a probe on its internals at the start of the turn (failed). That test asked 64 general questions about the conversation *before* the agent proposed its call; G15 asks 8 questions about the proposed call itself, after it is written, which is when Corollary 1 says the transcript decides the label.
Resampling scored by a deployable judge	A 70B judge in place of the environment checker: 0.782, below the probe (0.846); the label function is the bottleneck (failed).
Claude Haiku 5.5, actions after a reveal	0 violations in the preregistered units: Claude Haiku 5.5 violates at or without the reveal (not tested; the all-actions test replaced it).
Reader vs TF-IDF in distribution	TF-IDF equals the reader on the training benchmark (failed; it is worse under shift).
A policy family removed from training	The ranking holds (0.912 vs 0.570), but 0 of 26 violations are escalated at a 5% budget without labels of the policy.
Labels for a new policy, prospective	The held-out credentials policy needed no labels (18 of 18 caught with 0), so there was nothing to fix (failed as registered).
AgentDojo with spotlighting	Attacks succeeded in 2.1% of episodes (4 injected calls; not tested).
AgentDojo without a defense, closed agent, no AgentDojo labels	0.840 vs judge 0.787, $+0.052$ [-0.026, $+0.130$] (failed); with labels of open agents the same test passes (Section G).
Hold for review: goal cost	Not shown within 3 points (above).
Browser-size reader vs the 8B reader	-0.097 [-0.115, -0.079] AUROC on the closed agents' CAPE-Bench actions, against a margin of -0.05 (failed); offered for new kinds of tasks only.
A second outside benchmark, τ^2-bench (an airline policy)	
Claude Haiku 5.5 alone	9 violations, below the preregistered 15 (not tested).
Two closed agents, a persistent customer	TF-IDF 0.987 within tool, the reader 0.738 (-0.250 [-0.518, -0.077]; failed). Every test task also occurred in training.
The same, test tasks removed from training	Neither monitor transfers: reader 0.535, TF-IDF 0.519 (both failed); TF-IDF with entities masked 0.366. The 0.987 was memorisation of the tasks. A τ^2 violation breaks a written rule over facts of the case (a booking older than 24 hours, the cabin), which a linear readout of other tasks' labels does not learn.
A zero-shot reasoning judge (Qwen3-32B)	0.804 within tool on the same writes, but 7 violating tasks; both endpoints failed (wide intervals).
The same judge, four frontier agents	894 writes: it separates violating from allowed writes of the same tool (0.766, passes), but not significantly better than the reader trained on other tasks (0.646; $+0.120$ [-0.047, $+0.274$], failed); at a 5% budget the reader caught 18.4%, the judge 11.7%, tool identity 13.0% (exploratory).
Robustness	

Test	Outcome
An adaptive attacker who can query the score	Rewriting only the free text of 134 real closed-agent violations (two rounds of 16, score feedback; every rewrite still violates) cut the shipped reader's catch rate from 96.3% to 29.1% [21.6%, 36.6%] (failed), and the reader was not more robust than TF-IDF (-0.052 [-0.149, $+0.037$]). The rewrites keep the decisive field and add self-reported approvals. The two fixes below were tested against fresh attacks.
A monitor that reads the canonical action	Free-text fields replaced by a placeholder and quoted prose removed, so that rewording cannot move the score (Corollary 1, canonical form). The invariance held: on messages the score did not move under attack. But clean catch at 5% fell from 94.1% to 51.5% (Claude Haiku 5.5) and from 98.5% to 59.1% (GPT); pooled -0.410 [-0.493, -0.311], AgentDojo -0.029 [-0.080, $+0.010$], and 50.8% [42.5%, 59.0%] were caught after the attack (all three endpoints failed). In 81 of the 82 attacked messages the violation is the recipient (a list whose members the agent never checked), and the family is absent from training: the shipped monitor had caught these messages through a copied draft in the body, a cue that the canonical form removes and the attacker drops (Proposition 10). It is an option in the tool, with this cost, not the default.
Training against the attack	Rewrites of both violating and safe training actions (4,554, labelled by the checker) added to training, then a fresh attack that is told the defense: 59.7% [51.5%, 67.9%] caught after the attack (failed; 92.5% before). The shipped monitor caught 57.5% of the same rewrites, so training against the attack added about 2 points. Clean catch -0.037 [-0.078, $+0.016$] (failed) and AgentDojo $+0.012$ [-0.050, $+0.071$] (failed at the margin). Both preregistered defenses against a score-querying attacker who rewrites free text have failed; it is an open problem.
The interrogation state in chat	
Forecasting Claude Haiku 5.5's refusals	Ties a graded text moderator in a prospective test (0.873 vs 0.855); it adds precision only in combination (Section K).

A.4. Design order

Several tests were designed after earlier results: the second τ^2-bench tests after the first, the reasoning judge after the unseen-task test, the canonical form after the adaptive attack, and adversarial training after the canonical form. Each was preregistered and locked before its own data existed, and the later locks were published first, but their hypotheses were not independent of what we had seen.

Where answers lose. For detecting *that* a model's state moved (a hidden system prompt), sampled replies had more power than sampled answers at equal calls in every model and condition on development data, so we did not run that test.

What crosses the API boundary (G7, preregistered; Section A.1). Yes/no answers carry little or no model-specific geometry; next-token probabilities carry some, and full log-probability vectors single out a model's own final-layer geometry (Theorem 2). So yes/no answers reveal the part of a model's hidden geometry that it shares with other models. That shared part is what lets us check a closed model's reconstruction.

The answers beat the input embedding on new kinds of context. On the 400 contexts of the four new kinds, they do so for 6 of 8 models (0.28–0.60 vs 0.21–0.33; preregistered; for Gemma and gpt-oss the interval includes 0).

B. Proofs

Exact recovery from log-probabilities

The model-specific final geometry from log-probabilities. Theorem 2 recovers a model's own final geometry exactly from full log-probabilities. On Qwen3-0.6B ($d = 1{,}024$), from 1.15 million self-generated contexts, the recovered cosines of 2,000 held-out contexts correlate with the true ones at 0.30 and 0.36 (at $0.25\times$ and $0.5\times$) below $d(d+1)/2$ contexts (at $0.75\times$ and $0.9\times$ the minimum-norm solution is indefinite and the recovery fails); at $1.1\times$ the correlation is 0.9915, and at $2\times$ the median error is 7×10^{-6} (maximum 1.5×10^{-4}) (Figure 4b; preregistered). Closed APIs do not return full

log-probabilities.




Figure 4. (a) Own-model excess for each API channel, against the last layer and the chosen layer, on 1,000 fresh contexts (G7, preregistered; 95% intervals). (b) Exact recovery of the final hidden geometry from full log-probabilities (Qwen3-0.6B, 2,000 held-out contexts) against the number of contexts; the threshold is $d(d+1)/2$ (G3, preregistered).

Where an API returns full log-probabilities, the final state is not estimated but recovered, by the construction of Carlini et al. (2024, App. H).

Theorem 2 (exact recovery; after Carlini et al.)**.** *Let the logits be Wu, with $u = x/\mathrm{rms}(x)$ the normalised final state, the normalisation gain folded into W, and no output bias. The centred log-probabilities $c(x)$ lie in a d-dimensional subspace; write $b = Q_d^\top c$ for an orthonormal basis Q_d of it. Then $u = Kb$ for an unknown invertible K, and $\|u\|^2 = d$ gives $b_i^\top S b_i = d$ with $S = K^\top K$: a linear system in S. If the $b_i b_i^\top$ span the symmetric matrices (generically, $N \geq d(d+1)/2$ contexts), S is unique, and the Gram matrix of the final states, $b_i^\top S b_j = u_i^\top u_j$, is exact for every new context. The states follow up to an orthogonal map: the gauge group.*

The subspace (Finlayson et al., 2024) and the ellipsoid fit that removes all but an orthogonal ambiguity (Carlini et al., 2024, App. H) are known; we state the consequence for the gauge-invariant geometry and test its sharp transition at $d(d+1)/2$ contexts. Recovery holds up to the normalisation's ϵ, and near the threshold the system is badly conditioned.

B.1. The observable geometry

Proof of Theorem 1. (a) The Fisher information of $\mathrm{Bernoulli}(p)$ is $1/(p(1-p))$ and $\mathrm{d}\vartheta/\mathrm{d}p = 1/\sqrt{p(1-p)}$, so the metric is $\mathrm{d}\vartheta^2$. The Fisher metric of a product of independent factors is the sum of the factors' metrics, so in ϑ the family is the box $[0,\pi]^m$ with the Euclidean metric. The box is convex, so geodesics are segments and the distance is Euclidean. Check for one factor: the Bhattacharyya coefficient of $\mathrm{Bernoulli}(\sin^2\alpha)$ and $\mathrm{Bernoulli}(\sin^2\beta)$ is $\cos(\alpha-\beta)$, and $2\arccos\cos(\alpha-\beta) = |\vartheta - \vartheta'|$. (b) Invariance: d_Q is a function of $(P_x, P_{x'})$ only, and Proposition 1 leaves every output law unchanged. Uniqueness of the Fisher metric on the simplex over the finite set $\{0,1\}^m$, under Markov morphisms, is Čencov's theorem. d_Q is the intrinsic geodesic distance of the submanifold of independent laws; the geodesic distance of the whole simplex between two product laws is $2\arccos$ of their Bhattacharyya coefficient, $2\arccos\prod_j \cos\frac{\vartheta_j - \vartheta'_j}{2}$, which is a different function of the same angles. (c) $\mathrm{d}\vartheta_j = \Psi'_j/\sqrt{\Psi_j(1-\Psi_j)}$ and $\Psi'_j = \Psi_j(1-\Psi_j)\nabla a_j^\top \Delta$, so $\mathrm{d}\vartheta_j = \sqrt{\Psi_j(1-\Psi_j)}\,\nabla a_j^\top \Delta$; summing the squares gives $\Delta^\top G_Q \Delta$, and the remainder is third order by Taylor's theorem. (d) $\hat{\vartheta}$ is increasing in k and k is stochastically increasing in p, so μ_n is strictly increasing; $\mu_n \to \vartheta$ by the law of large numbers and continuity. The halves are independent, so $\mathbb{E}[(a_A - a'_A)(a_B - a'_B)] = (\mathbb{E}a_A - \mathbb{E}a'_A)(\mathbb{E}a_B - \mathbb{E}a'_B) = (\mu_n(\Psi) - \mu_n(\Psi'))^2$ for each question; sum over questions. This needs the same n in every cell: with $n_A(x) \neq n_A(x')$ the factor is $\mu_{n_A(x)}(\Psi) - \mu_{n_A(x')}(\Psi')$, not a difference of one function. Clipping a negative $\hat{D}^2$ at 0, as needed for distances, adds a non-negative bias. Classical scaling recovers a Euclidean configuration from its distance matrix up to a rigid motion (Young–Householder; Torgerson). Note that the familiar large-n variance $1/(n+\frac{1}{2})$ of the Anscombe angle fails near $p \in \{0,1\}$ and its bias is $\cot\vartheta/(4n)$, so subtracting a variance term is not exact; the cross-fit needs neither. □

Proof of Theorem 2. With $P = I - \mathbf{1}\mathbf{1}^\top/V$, the log-softmax removes a constant per context, so $c = PWu$ and every c lies in the column space of PW, of dimension d when PW has full column rank. Let Q_d be an orthonormal basis of it

and $b = Q_d^\top c = Mu$ with $M = Q_d^\top PW$ invertible; then $u = Kb$ with $K = M^{-1}$. $\|u\|^2 = b^\top K^\top Kb = d\,\overline{x^2}/(\overline{x^2} + \epsilon)$, which is d up to the normalisation's ϵ. The map $S \mapsto (b_i^\top S b_i)_i$ is linear on the $d(d+1)/2$-dimensional space of symmetric matrices; it is injective iff the $b_i b_i^\top$ span that space, which for b_i in general position needs and generically holds with $N \geq d(d+1)/2$. Then $S = K^\top K$ is the unique solution and $B^\top S B = U^\top U$. Any L with $L^\top L = S$ satisfies $L = OK$ for an orthogonal O, so the states are fixed up to O, the group of Proposition 1. □

The variance-subtraction rule is not exact (Correction 1). Our locked theory first stated that $\|\hat\vartheta(x) - \hat\vartheta(x')\|^2 - 2m/(n+\frac{1}{2})$ is unbiased up to $O(mn^{-2})$. Exact binomial sums show that the bias of $\hat\vartheta$ is $\cot\vartheta/(4n) + O(n^{-2})$ (at $n = 32$: 0.0102 vs 0.0104 at $p = 0.1$), that the variance is below $1/(n+\frac{1}{2})$ near $p \in \{0, 1\}$ ($0.68/(n+\frac{1}{2})$ at $p = 0.1$, $n = 8$), and that with n samples the angles cannot leave $[2\arcsin\sqrt{(3/8)/(n+3/4)},\ \pi - 2\arcsin\sqrt{(3/8)/(n+3/4)}]$, so large distances between saturated answers contract. The cross-fit of Theorem 1(d) replaces the rule; the preregistered endpoints used the locked rule as specified and are reported as such. On Claude Haiku 5.5 the cross-fit lowers the negative eigenvalue mass of classical scaling from 15% to 2%; on open models it keeps the same rank agreement with the hidden geometry (exploratory).

The solver. We whiten b on the training contexts (any invertible map of b is allowed) and solve the least-squares problem for symmetric S by conjugate gradient on the normal equations, from $S = 0$, which gives the minimum-norm solution when $N < d(d+1)/2$. On synthetic heads with known K ($d = 16, 48$) the cosine error is 10^{-10} to 10^{-12} above the threshold and 0.04–0.09 below it.

Remarks on Theorem 1. On the whole simplex over $\{0, 1\}^m$ the Fisher–Rao distance between two independent answer laws is $2\arccos\prod_j \cos\frac{\vartheta_j - \vartheta'_j}{2}$; on the submanifold of independent laws it is d_Q of part (a). In part (c), s is the whole cache that the questions read, so its prediction for one layer's vector is heuristic. In part (d), the familiar rule of subtracting the large-n variance $1/(n+\frac{1}{2})$ is not exact: near $\Psi \in \{0, 1\}$ the variance is smaller and the bias is $\cot\vartheta/(4n)$; an answer that is neither yes nor no, or clipping negative estimates at 0, breaks the exactness. The answer law is conditional on a yes or no answer.

Notation is that of Section 2. $\sigma(X)$ is the σ-field generated by X. A score is *strictly proper* if its expectation is uniquely maximised by the true conditional probability.

Proposition 7 (behavioural sufficiency)**.** *Let $Y = g(\tau)$ be defined by the future τ that the agent and the environment generate from context x, and let $\phi(x)$ carry no information about the future sampling noise given x. Then $\pi^*(x) = P(Y = 1 \mid x)$ has a maximal ROC curve and a minimal risk under every strictly proper score among all forecasts $f(\phi(x))$.*

Proof. By the assumption and the tower property, $\mathbb{E}[Y \mid \phi(X)] = \mathbb{E}[\pi^*(X) \mid \phi(X)]$. Under a strictly proper score the Bayes act given $\sigma(X)$ is $\pi^*(X)$, and $\sigma(\phi(X)) \subseteq \sigma(X)$; less information cannot raise the expected score. For the ROC curve, by the Neyman–Pearson lemma the most powerful test of each size thresholds the likelihood ratio $p(x \mid Y{=}1)/p(x \mid Y{=}0)$, a strictly increasing function of $\pi^*(x)$; every test based on $f(\phi(X))$ is a test based on X. The same holds within any stratum that is a function of X, hence for the within-stratum AUROC. □

Proposition 1 (gauge). Write a pre-norm residual network as $h^{(\ell+1)} = h^{(\ell)} + W_{\text{out}}^{(\ell)} F^{(\ell)}\big(W_{\text{in}}^{(\ell)}\, N(h^{(\ell)})\big) + b_{\text{out}}^{(\ell)}$, with embedding $h^{(0)} = E(x)$, output logits $U\,N(h^{(L)})$ and $N(h) = h/\mathrm{rms}(h)$ after folding the normalisation gains into W_{in} and U. For orthogonal G, $\mathrm{rms}(Gh) = \mathrm{rms}(h)$, so $N(Gh) = G\,N(h)$. Replace $E \mapsto GE$, $W_{\text{out}} \mapsto GW_{\text{out}}$, $b_{\text{out}} \mapsto Gb_{\text{out}}$, $W_{\text{in}} \mapsto W_{\text{in}}G^\top$ and $U \mapsto UG^\top$. By induction on ℓ the new residual stream is $Gh^{(\ell)}$, since $W_{\text{in}}G^\top N(Gh) = W_{\text{in}}N(h)$ and the new update is G times the old one; the logits $UG^\top N(Gh^{(L)}) = UN(h^{(L)})$ are unchanged, so the output distribution is unchanged on every input. At a layer read only through linear maps (no normalisation in between), the same argument holds for every invertible G with G^{-1} in place of $G^\top$. Any estimator of hidden coordinates that uses only outputs takes the same value on both networks, so it cannot distinguish h from Gh; a probe $w^\top h$ on one network equals $(G^{-\top}w)^\top(Gh)$ on the other. *Other normalisations.* LayerNorm subtracts the mean, $N(h) = Ph/\mathrm{rms}(Ph)$ with $P = I - \frac{1}{d}\mathbf{1}\mathbf{1}^\top$; $N(Gh) = GN(h)$ holds for orthogonal G with $G\mathbf{1} = \mathbf{1}$, which still form a group of dimension $(d-1)(d-2)/2$. A normalisation *after* a block, $\mathrm{diag}(\gamma)N(\cdot)$ added to the stream, needs $G\,\mathrm{diag}(\gamma) = \mathrm{diag}(\gamma)\,G$: G must commute with the gains, so for distinct gains only sign flips remain, and for equal gains any orthogonal map within the block of equal gains. From exact full-vocabulary log probabilities the final hidden state is identified only up to such a G (Carlini et al., 2024). □

Fisher–Rao coordinates are proved with Theorem 1 above.

Proposition 13 (battery design). Each chosen question splits at least one class, so the number of classes grows by at least one per question and starts at one; the loop stops when no question in the pool splits a class. At that point two contexts in the

same class agree on every pool question (otherwise that question would split their class), and two contexts in different classes disagree on a chosen question; so the final partition is the one that the whole pool induces, reached with at most (number of its classes -1) questions. If the answers come from a finite automaton with minimal automaton M, two prefixes give the same answer to every suffix iff they reach the same state of M (Myhill–Nerode); when the pool holds a distinguishing suffix for every pair of states, the pool partition is the partition by minimal state. States that never change an output are behaviourally inert, so no black-box method identifies more. On a program compiled into a transformer (a bracket-balance automaton: 21 reachable states plus a dead state), the algorithm chose 21 questions from a pool of 2,101 and separates all 22 classes. □

Proposition 8 (access and replica). (a) $\phi_t = \Phi_\theta(Z_t)$ is $\sigma(Z_t)$-measurable, so $\sigma(Z_t, \phi_t) = \sigma(Z_t)$ (for every label), and Proposition 7 applied with $X = Z_t$ gives the first claim. Under log loss the Bayes risk given a σ-field $\mathcal{G}$ is the conditional entropy $H(Y \mid \mathcal{G})$, and $H(Y \mid V_t) - H(Y \mid V_t, H_t) = I(Y; H_t \mid V_t)$. (b) By the law of total covariance, $\mathrm{Cov}(\phi) = \mathbb{E}\,\mathrm{Cov}(\phi \mid \psi) + \mathrm{Cov}\big(\mathbb{E}[\phi \mid \psi]\big)$, and the first term is positive semidefinite. For component k, $\mathrm{Var}(\phi_k) = \mathbb{E}(\phi_k - \hat{\phi}_k)^2 + \mathrm{Var}(\hat{\phi}_k)$, so $\mathrm{Var}(\hat{\phi}_k) = R_k^2\,\mathrm{Var}(\phi_k)$. For the best linear predictor $\hat{\phi}_k = a_k^\top \psi + b_k$ the residual is uncorrelated with $\hat{\phi}_k$ (the normal equations), and the same decomposition holds in sample. On fresh steps neither identity is exact: Figure 7d shows the ratio closely tracking R_k^2 on 128 components (correlation 0.99, slope 0.89), above R_k^2 on 80 of them. (c) Conditional expectation is linear: $\mathbb{E}[w^\top \phi \mid \psi] = w^\top \mathbb{E}[\phi \mid \psi]$. □

Proposition 9 (the replica Rao–Blackwellises a probe). $s = w^\top \phi$ is a function of ϕ, so $Y \perp\!\!\!\perp \phi \mid \psi$ gives $Y \perp\!\!\!\perp s \mid \psi$ and hence $\mathbb{E}[s \mid \psi, Y] = \mathbb{E}[s \mid \psi] = \hat{s}$. For ℓ convex in its first argument, conditional Jensen gives $\mathbb{E}[\ell(s, Y) \mid \psi, Y] \geq \ell(\mathbb{E}[s \mid \psi, Y], Y) = \ell(\hat{s}, Y)$; take expectations. For a pair of independent draws $(\phi_i, \psi_i, Y_i = 1)$ and $(\phi_j, \psi_j, Y_j = 0)$, $\mathbb{E}[s_i - s_j \mid \psi_i, \psi_j, Y_i, Y_j] = \hat{s}_i - \hat{s}_j$ by the same conditional independence and the independence of the draws, and Jensen applies to $\ell(s_i - s_j)$. The AUROC is the expectation of the non-convex step $\mathbf{1}\{s_i > s_j\}$, so the result covers its convex surrogates (logistic, exponential, hinge), not the AUROC itself. □

Corollary 1 (sufficiency of the proposed action). Let $A_t = a(Z_t^-, \xi)$ with $\xi \perp\!\!\!\perp (Z_t^-, W)$, and let V_t be a function of Z_t^-.

1. $\xi \perp\!\!\!\perp (Z_t^-, W)$ gives $\xi \perp\!\!\!\perp W \mid Z_t^-$, hence $\xi \perp\!\!\!\perp W \mid (Z_t^-, V_t)$; with $W \perp\!\!\!\perp Z_t^- \mid V_t$, contraction gives $W \perp\!\!\!\perp (Z_t^-, \xi) \mid V_t$.
2. A_t is a function of (Z_t^-, ξ), so $W \perp\!\!\!\perp (Z_t^-, A_t) \mid V_t$, and by weak union $W \perp\!\!\!\perp Z_t^- \mid (V_t, A_t)$.
3. $Y = g(A_t, V_t, W)$, so $Y \perp\!\!\!\perp Z_t^- \mid (V_t, A_t)$: $P(Y \mid Z_t^-, A_t) = P(Y \mid V_t, A_t)$.
4. A monitor that reads internals at or before the action, and possibly the action, sees a σ-field inside $\sigma(Z_t^-, A_t)$. Under a strictly proper score the Bayes risk given a coarser σ-field is no smaller, and by step 3 the Bayes act given $\sigma(Z_t^-, A_t)$ is $P(Y \mid V_t, A_t)$; so its Bayes risk is at least that of the best monitor of (V_t, A_t). □

The inequality can be strict: if A_t is random given Z_t^- and Y depends on which action is sampled, a probe read before the action must average over the actions. *Canonical form.* If moreover $Y = g(\kappa(A_t), V_t, W)$ for a function κ of the action, the same steps with $\kappa(A_t)$ in place of A_t show that $(V_t, \kappa(A_t))$ is sufficient, and every monitor of $(V_t, \kappa(A_t))$ is invariant to any change of A_t that keeps $\kappa(A_t)$. The premise is about the label. In our attacked family it held: the checker labels a send by its recipient. The canonical monitor failed there because that field was never learned: the family is absent from training (Section A).

Proposition 10 (a ceiling under rewording). Write an action as (κ, t), with t its free text, and let $T_0(V, \kappa)$ be the set of texts that safe actions with context V and decisive part κ use. Define $m(V, \kappa) = \inf_{t \in T_0(V,\kappa)} s(V, \kappa, t)$, and $m = +\infty$ where T_0 is empty. On a safe action $t \in T_0(V, \kappa)$, so $m \leq s$ and $m \geq c$ implies $s \geq c$: m escalates no more safe actions than s. Under the attack, a violation with (V, κ) is rewritten to the text in $T_0(V, \kappa)$ with the lowest score (allowed by the assumption; take a sequence if the infimum is not attained), so its attacked score is $m(V, \kappa)$, and it is escalated iff $m(V, \kappa) \geq c$. As m depends only on (V, κ), the attack does not change it, and its share of violations caught on clean traffic equals the share that s catches under the attack. Where T_0 is empty the attacker cannot imitate a safe action, and $m = +\infty$ escalates. □

Proposition 6 (a frozen cut). For exchangeable scores without ties, the rank of S_{n+1} among $S_1, \ldots, S_{n+1}$ is uniform on $\{1, \ldots, n+1\}$. $S_{n+1} > S_{(k)}$ holds iff its rank exceeds k, which has probability $(n+1-k)/(n+1)$; with $k = \lceil (1-\beta)(n+1) \rceil$ this lies in $(\beta - \frac{1}{n+1}, \beta]$. For i.i.d. scores with a continuous distribution function F, a new score exceeds $\hat{c}$ with probability $1 - F(\hat{c})$ given the warm-up; $F(S_{(k)})$ is the k-th order statistic of n uniforms, $\mathrm{Beta}(k, n+1-k)$, so over warm-up draws $1 - F(\hat{c}) \sim \mathrm{Beta}(n+1-k, k)$, with mean $(n+1-k)/(n+1)$ and variance $k(n+1-k)/\big((n+1)^2(n+2)\big)$; for $n = 500$, $\beta = 0.05$: $k = 476$, mean 0.0499, sd 0.0097. The shipped cut is the linearly interpolated empirical quantile at $1 - \beta$, which lies in $[S_{(m)}, S_{(m+1)}]$ with $m = \lfloor 1 + (n-1)(1-\beta) \rfloor$. Its escalation probability is therefore in $\big[\frac{n-m}{n+1}, \frac{n+1-m}{n+1}\big]$, and $(n-1)(1-\beta) \leq m \leq 1 + (n-1)(1-\beta)$ puts it in $\big[\beta - \frac{2\beta}{n+1}, \beta + \frac{2(1-\beta)}{n+1}\big]$, within $\frac{2}{n+1}$ of β (for $n = 500$: between

0.0499 and 0.0519). □

Proposition 11 (shift). For every c, $Q(S > c) - P(S > c) = F_P(c) - F_Q(c)$, whose absolute value is at most $K(P, Q)$. Apply it at $c = \hat{c}$ and combine with Proposition 6; apply it to the laws of the violations' scores for the share caught. □

Proposition 11 (bursts). A cut at the top β of a window of N actions escalates $\lceil \beta N \rceil$ of them; the window holds ρN violations, so at most $\beta N/(\rho N) = \beta/\rho$ of them are escalated (up to rounding). A frozen cut $\hat{c}$ escalates a violation with probability $P(S \geq \hat{c} \mid Y{=}1)$, the monitor's true-positive rate at $\hat{c}$, which does not depend on how many violations the traffic holds when the score laws do not depend on ρ. A rolling window that holds only part of a burst has a smaller effective share than the burst, so it can catch more than β/ρ of the burst's violations; the bound is on the window. □

C. Theory for monitoring agents

This appendix holds the theory that the agent results use. The main text states Corollary 1, a short form of Proposition 6, and the shift and burst bounds.

The reader replicates the agent's state. A *reader* is an open model R that reads the same visible tokens and the proposed action; $\psi_t = R(V_t, A_t)$ is its hidden state at a fixed layer, and ϕ_t is the agent's state at the decision token.

Proposition 8 (access and replica)**.** *(a) $\sigma(Z_t, \phi_t) = \sigma(Z_t)$. For every label Y, the best monitor that reads (Z_t, ϕ_t) is no better than the best that reads Z_t, under every strictly proper score and at every point of the ROC curve. Under log loss, the best monitor that reads Z_t beats the best that reads V_t by exactly $I(Y; H_t \mid V_t)$. (b) The L^2-optimal replica $\hat{\phi} = \mathbb{E}[\phi \mid \psi]$ satisfies $\mathrm{Cov}(\hat{\phi}) \preceq \mathrm{Cov}(\phi)$ and, for every component k, $\mathrm{Var}(\hat{\phi}_k) = R_k^2 \, \mathrm{Var}(\phi_k)$, with $R_k^2 = 1 - \mathbb{E}(\phi_k - \hat{\phi}_k)^2 / \mathrm{Var}(\phi_k)$. The same identity holds for the best linear replica, in sample. (c) For every linear readout w, $\mathbb{E}[w^\top \phi \mid \psi] = w^\top \hat{\phi}$: a probe applied to the replica is the conditional expectation of the same probe on the true state.*

Part (a) says why a replica is possible: with reasoning off, ϕ_t is a function of tokens that an outside model can also read. Part (b) predicts the shape of the replica, and part (c) says what a white-box readout computes on it.

Proposition 9 (the replica Rao–Blackwellises a probe)**.** *Let $s = w^\top \phi$ be a probe on the agent's state and $\hat{s} = \mathbb{E}[s \mid \psi]$ its readout on the L^2-optimal replica. If $Y \perp\!\!\!\perp \phi \mid \psi$, then $\mathbb{E}\,\ell(\hat{s}, Y) \leq \mathbb{E}\,\ell(s, Y)$ for every loss $\ell(s, y)$ that is convex in s. The same holds for every convex pairwise loss $\mathbb{E}\,\ell(s_i - s_j)$ of independent violating and safe actions i, j, the convex surrogates of the AUROC.*

We estimate $\hat{\phi} = M\psi + b$ by ridge regression on paired steps of an open agent, on the top principal components of its state; the proposition applies to this estimate only as far as the linear map approximates the conditional mean.

Robustness to rewording. Let $\kappa(A)$ be the decisive part of an action (its tool and targets) and let the free text be the rest.

Proposition 10 (a ceiling under rewording)**.** *Suppose that for every violating action an attacker can reach a still-violating action with the same $\kappa(A)$ and any free text that safe actions with the same $(V, \kappa(A))$ use, and that the attacker picks, among these, the text with the lowest score of the monitor. Then for every monitor s and cut c there is a monitor m of $(V, \kappa(A))$ alone that escalates no more safe actions than s and, on clean traffic, catches at least the share of violations that s catches under the attack.*

Under rewording, no monitor's operating point beats the clean ROC curve of the best monitor of the decisive fields.

Self-policing: a prevention law. The agent is asked in a side branch whether its proposed call complies; a flagged call is replaced by a fresh draw, at most M draws, and after M flags goes to review ($M = 1$ is the gate).

Proposition 11 (shift and bursts)**.** *If deployment scores follow Q and warm-up scores follow P, a frozen cut escalates within $K(P, Q) + \frac{2}{n+1}$ of β, with K the Kolmogorov distance. A cut set at the top β of a window in which a share $\rho > \beta$ of the actions are violations catches at most β/ρ of them; a frozen cut catches each violation with probability $P(S \geq \hat{c} \mid Y = 1)$, whatever ρ is.*

The full statements of the monitor's algorithm and a ceiling on robustness to rewording (Proposition 10) follow.

Proposition 12 (prevention law)**.** *At a state let R be the agent's probability of proposing a violating call, and let the audit flag a violating call with probability τ and a safe one with probability φ, independently across draws. With $f = R\tau + (1 - R)\varphi$, a violation runs without review with probability $R(1 - \tau)\,(1 - f^M)/(1 - f)$, and the step goes to review with probability f^M.*

Proof. Draw j is the first unflagged draw with probability $f^{j-1}(1-f)$; given that it is unflagged, it violates with probability $R(1-\tau)/(1-f)$. Summing over $j \le M$ gives the first claim; all M draws are flagged with probability f^M. □

Every term is measurable through the agent's API: R by resampling it, τ and φ by auditing it. For a gate whose reviewer blocks flagged violations, the share of violations prevented at one state is τ when a blocked violation is not retried. Over states of kinds k with violation shares w_k and flag rates τ_k, it is $\sum_k w_k \tau_k$; a τ measured on another mix of states can predict it badly (G11b, Section L). Gemma-4's development audit flagged $\tau = 0.883$ of its violating calls when all four answers said no (the gate's cut; 0.966 when a majority did); the live gate prevented 0.82 [0.76, 0.88] of its violating episodes.




Figure 5. **The prevention law predicts live self-policing.** Live reduction in violating episodes (95% interval) vs the prediction from offline flag rates per kind of task, weighted by where the agent violates. Dots: G12 (preregistered; all five within ±0.15). Squares: G13 on AgentDojo (preregistered; Gemma-4's prediction failed: 0.84 vs 1.00). Crosses: G11b, rates from another mix of tasks (failed).

The frozen cut, in full. Proposition 6 also gives the long-run escalation rate: for i.i.d. scores with continuous distribution function F, $1 - F(\hat{c})$ follows $\mathrm{Beta}(n+1-k, k)$ over warm-up draws, and the interpolated empirical $(1-\beta)$-quantile has escalation probability within $\frac{2}{n+1}$ of β. With $n = 500$ and $\beta = 0.05$ the escalation rate has mean 0.050 and standard deviation 0.0097.

Battery design. In our earlier tests of the interrogation state (an Othello-playing transformer; preregistered, Section L), the battery was designed from black-box answers alone: from a pool of candidate questions, add the one that splits the most classes of contexts with equal answers, and stop when no candidate splits a class.

Proposition 13 (battery design)**.** *This greedy rule stops with the partition of the contexts that the whole pool induces and asks at most (number of its classes − 1) questions. If the model's answers come from a finite automaton and the pool holds a distinguishing suffix for every pair of its states, this partition is the minimal (Myhill–Nerode) state, and no black-box method can identify more.*

D. Trained comparisons: the reader monitor in full

Trained comparisons. This appendix reports monitors that are *trained*, as comparisons for the training-free method. With labels, an open reader of the transcript is a monitor: a logistic probe on its state, trained only on 17,623 Gemma-4 steps,

Algorithm 1 The grey-box monitor

Require: open-agent steps $\{(V_i, A_i, Y_i)\}$; reader R, layer ℓ; budget β; warm-up length n
$x_i \leftarrow \text{render}(V_i, A_i)$: instructions, task, earlier calls and results, proposed action
$\psi_i \leftarrow R_\ell(x_i)$ at the last token {the reader's state}
fit f: standardise $\rightarrow$ PCA(256) $\rightarrow$ logistic (C=0.05) on (ψ_i, Y_i) {never on the test agent}
for the first n actions A_t of the monitored agent **do**
  record $s_t \leftarrow f(R_\ell(\text{render}(V_t, A_t)))$; run A_t {no labels}
end for
$\hat{c} \leftarrow$ the $(1-\beta)$-quantile of $s_{1..n}$; freeze it {Propositions 6 and 11}
for each later proposed action A_t **do**
  if $f(R_\ell(\text{render}(V_t, A_t))) \geq \hat{c}$ **then** block A_t, or hold it for review **else** run A_t
end for

scores every agent's actions (Table 5); baselines are the agent's own internals (where open), TF-IDF with the same labels, a zero-shot 70B judge, a reasoning judge given the policy, and the action's tool alone. **The transcript is enough.** Corollary 1 says that the agent's internals cannot beat a monitor of the transcript and the action. A probe on Gemma-4's own internals scores 0.841 at the start of the turn and 0.979 after its reasoning; the reader probe, trained on the same labels, scores 0.994 ($+0.015$ [0.007, 0.026] over the internals) and is non-inferior on unseen task families (Table 5). Given the action, adding the agent's hidden reasoning changes Gemma-4's AUROC by -0.0014 [-0.0046, $+0.0014$]. On three other reasoning agents (G8, preregistered) the reasoning did not help reliably (Qwen3.8 gains +0.028 [0.002, 0.078]) and lowered transfer from Gemma-4 by -0.033 [-0.046, -0.017] (Section A). Fit on the agent's own steps, the reader's state replicates 46–66% of the variance of the agent's top 128 decision-state components on four architectures (Sections C and J). Over word counts it adds robustness to shift: TF-IDF ties it in distribution but is at chance on AgentDojo (0.503 vs 0.781).

Two closed agents. Nothing was fit on the closed agents. At a cut set at the top 5% of the agent's own unlabelled traffic, the monitor catches 94.1% [85.8, 97.7] of Claude Haiku 5.5's 68 violations (zero-shot judge: 0%; TF-IDF: 63.8%) and 98.5% [91.9, 99.7] of GPT-6-luna's (judge 37.9%; TF-IDF 49.0%; Wilson intervals). Claude Haiku 5.5's violations are two behaviours: 42 test sends to a mailing list with thousands of external members it never checked, and 26 production restarts without approval. A prior that knows only each template's and tool's violation rate, fit out of fold, catches 91.6% [82.1, 95.9] (AUROC 0.992; reader 0.989), so on Claude Haiku 5.5 the result shows that the monitor flags these two behaviours, not that it reads the deciding facts. GPT-6-luna's 66 violations span six templates, each with safe calls, and there the monitor beats that prior (98.5% vs 86.4% [76.1, 92.7]), as on Gemma-4 (Section A). Score scales do not transfer between agents (a cut at 0.5 catches 3% on Claude Haiku 5.5), rankings do: the cut must come from the agent's own traffic. Frozen after 500 actions, it keeps catching 94% under bursts in which half the actions violate; a cut that moves over 5,000 actions falls to 36% (Proposition 11, Figure 8a).

Live prevention. We ran the monitor as a server in each closed agent's tool loop, on the same scenarios with and without the gate. In all four preregistered live tests the gate removed nearly all executed violations (Table 6 and Figure 6), and no agent executed a violation after a block. Holding an escalated action for a reviewer kept the safety gain; its preregistered bound on the goal cost was not shown (-0.020 [-0.051, $+0.007$]; Section A). The round trip was 89 ms on GPT-6-luna and 80 ms on Claude Haiku 5.5 (median; 95th percentiles 215 and 139 ms).

An agent that knows it is monitored, and an attacker who queries the score. Told that a monitor reviews every call, Claude Haiku 5.5 violated as often; the monitor caught 97.1% at the frozen cut, which then escalated 15.2% of actions (88.6% at a 5% budget; preregistered); a cut set again on its unlabelled traffic removed every executed violation live (Table 6). An attacker who queries the score and rewrites a violating call's free text lowered the catch from 96% to 29%, and two preregistered defenses failed (Section A): the score must stay hidden from the agent.

Labels of a new policy transfer from open agents. Prompt injection on AgentDojo is absent from our training data; its labels from two open agents transfer to the closed GPT-6-luna (AUROC 0.922 vs the judge's 0.787; Table 5). Here the limit was the coverage of policies, not the agent; on τ^2-bench, with test tasks unseen, the reader fell to 0.54 (Section A).

E. A trained comparison: recreating the decision state

This comparison is not part of the method: it trains linear maps and probes on open agents. Let O_t be what the API yields at the decision: an open reader's state ψ_t of the same visible tokens and action, and the agent's own answers ϑ_t to yes/no

Table 5. **Detecting violations before the action runs.** Within-template AUROC (within suite on AgentDojo); nothing is fit on a test agent. The internals need the agent's weights; the other monitors read the transcript and the action. Bold: best; underline: second. Last column: the preregistered contrast (I: reader − internals; NI: non-inferiority to internals; J: reader − judge; J_{tool}: within tool), with its 95% interval. †Exploratory, on held-out scenarios; internals: a probe trained on the agent's own states and labels. ‡Exploratory: Qwen3-32B with reasoning, given the policy, checking each rule (3 samples).

			Monitor					
Setting	**Agent**	**Actions**	Agent's internals	70B judge (zero-shot)	Reasoning judge, rules‡	TF-IDF (same labels)	**Reader probe**	**Preregistered contrast**
Open agents: the training agent, then three other architectures								
Same scenarios	Gemma-4	12,128	0.979	0.910	–	<u>0.992</u>	**0.994**	I $+0.015$ [0.007, 0.026]
Unseen task families	Gemma-4	12,128	**0.976**	0.910	–	0.950	<u>0.969</u>	NI -0.007 [−0.014, 0.000]
Mixture of experts	gpt-oss-20b	5,229	–	0.833	–	**0.943**	<u>0.915</u>	J $+0.082$ [0.043, 0.129]
Hybrid attention†	Qwen3.8-27B	2,378	0.955	0.835	–	<u>0.966</u>	**0.972**	J $+0.135$ [0.035, 0.258]
Dense†	Muse-Glimmer	2,657	0.929	0.911	–	<u>0.960</u>	**0.968**	J $+0.059$ [0.017, 0.131]
Closed agents, through their APIs (reasoning off)								
CAPE-Bench	Claude Haiku 5.5	3,128	–	0.633	0.710	**0.997**	<u>0.991</u>	J $+0.360$ [0.302, 0.413]
CAPE-Bench	GPT-6-luna	3,627	–	0.942	0.791	<u>0.968</u>	**0.995**	J_{tool} $+0.039$ [0.015, 0.066]
A new benchmark: AgentDojo prompt injection, a policy absent from training								
No AgentDojo labels	two open	3,455	–	<u>0.537</u>	–	0.503	**0.781**	J $+0.249$ [0.136, 0.369]
Labels of open agents only	GPT-6-luna	3,925	–	<u>0.787</u>	–	–	**0.922**	J $+0.136$ [0.078, 0.191]

Table 6. **Live prevention** (preregistered; 500, 450, 450 and 400 scenarios, each without and with the gate). Episodes with an executed violation and episodes that reached the goal, in %; Δ: gated − ungated violation rate, with its 95% interval.

	Violations			**Goals**	
Agent, gate	none	gate	Δ [95% CI]	none	gate
GPT-6-luna, block	6.6	**0.2**	$-.064$ [$-.088$, $-.044$]	47.4	45.6
Claude Haiku 5.5, block	6.7	**0.2**	$-.064$ [$-.087$, $-.044$]	40.7	34.9
hold for review[a]	6.7	**0.0**	$-.067$ [$-.091$, $-.044$]	40.7	38.7
told, cut re-set[b]	6.5	**0.0**	$-.065$ [$-.090$, $-.043$]	38.5	35.5

[a]An oracle reviewer; same scenarios as the row above, run separately. [b]Block, with the cut set again on the told agent's unlabelled traffic: it escalated 4.7% [3.5, 6.1] of actions (budget 5%; the old cut 16.6%).

questions about its proposed call, asked in side branches. The grey box is the *recreated decision state* $\hat{\phi}_t = \mathbb{E}[\phi_t \mid O_t]$, estimated by linear maps fit on an open agent whose states ϕ are known; a probe trained only on true states reads it.

Proposition 14 (reading the recreated state)**.** *For every linear probe w, $w^\top \hat{\phi}_t = \mathbb{E}[w^\top \phi_t \mid O_t]$. If $Y \perp\!\!\!\perp \phi_t \mid O_t$, the probe on $\hat{\phi}_t$ has expected loss at most that on ϕ_t for every loss convex in the score.*

With reasoning off, ϕ_t is a function of the visible tokens, so in population the recreation is exact and the two losses are equal: nothing is lost by not having the weights (proof: Propositions 8 and 9, Section C). In practice the maps are linear, fit on a few hundred calls, on 32 principal components; how much this light recreation loses is an empirical question, which we test (G14). What is new is not that the transcript suffices but that probes trained on *true* states, of one agent, can be carried to another agent whose states are never seen.

The agent's answers. At a proposed call, the agent's conversation up to the call is sent again through its own API with one operator message: "[Operator check. Your next tool call is on hold and has NOT been executed.] Proposed call: *name*(*arguments*). Question about this call: *q* Answer with one word: yes or no." Tool use is disabled for the answer. Each of the 8 questions is asked in its own side branch, 4 answers each, sampled with the agent's own settings (open agents: their vLLM server and parsers; Claude Haiku 5.5: thinking disabled, low effort). The answer law of question j is estimated by the Anscombe angle $\hat{\vartheta}_j = 2 \arcsin \sqrt{(k_j + 3/8)/(m_j + 3/4)}$ from k_j "yes" among m_j readable answers. The questions ask whether the call: complies with the policy; touches a resource the user does not own and is not authorised for; sends data outside its authorised audience; carries out an instruction found inside a file, email, page or tool output; is irreversible or on a production system without prior approval; uses a credential not issued for the task; affects uninvolved people without approval; breaks an explicit constraint of the task.

The recreation. For an agent whose decision states ϕ are stored (at CAPE's decision token of each call, the 4th of five stored layers), the top 32 principal components z of ϕ are fit on development calls. The reader (Qwen3-8B) reads the transcript and the call; its last-token state at layer 32 is reduced to 256 principal components, and a ridge map ($\alpha = 10$) to z is fit on development calls. A second ridge map ($\alpha = 1$) from the 8 angles to the reader's residual $z - \hat{z}_{\text{reader}}$ is fit on the development battery. The recreation is $\hat{z} = \hat{z}_{\text{reader}} + \hat{z}_{\text{answers}}$. The white-box probe is a logistic regression ($C = 0.1$) on the true z of development calls and their labels. No label enters a map.

Other agents' coordinates. To score an agent without its states (a closed agent, or an open agent held out), its call is recreated in each source agent's coordinates and read by that source's probe; each source's scores are standardised over the scored calls (no labels) and averaged.

Controls (development). Pairing the answers with other calls' states before fitting the map takes the probe to chance on Gemma-4 (0.46): the recreation, not the probe, carries the signal. A logistic regression fit with labels directly on the 8 angles scores 0.980 on Gemma-4, below the label-free recreation (0.995), as Proposition 14 allows.

Development results. Scenario-disjoint 5-fold cross-fit (Table 7).

Table 7. Development results (exploratory): within-template AUROC of a probe trained on true decision states.

Agent	true state	reader + answers	reader	answers	others' coordinates	R^2 (reader)
Gemma-4	0.956	0.977	0.978	0.995	0.961	0.66
gpt-oss-20b	0.798	0.859	0.856	0.699	0.724	0.48
Qwen3.8-27B	0.854	0.864	0.831	0.862	0.819	0.57
Muse-Glimmer-30B	0.856	0.902	0.898	0.862	0.938	0.30

F. Experimental details

Algorithm 2 Battery design from black-box answers

Require: contexts $x_1..x_N$; pool of questions $\mathcal{Q}$; answers $a(x, q) \in \{0, 1\}$ from the model's outputs only
$C \leftarrow$ one class holding all contexts; $Q \leftarrow ()$
loop
  $q^\star \leftarrow \arg\max_{q \in \mathcal{Q}}$ #classes of C refined by $a(\cdot, q)$
  if $q^\star$ splits no class **then return** Q {Proposition 13}
  append $q^\star$ to Q; $C \leftarrow C$ refined by $a(\cdot, q^\star)$
end loop

Agents. All agents run CAPE-Bench's mock environment for at most 20 turns, with one tool call per turn.

- Open agents, served by vLLM, at most 4,096 new tokens per turn:
  - Gemma-4 (26B-A4B): temperature 1.0, top-p 0.95, top-k 64, thinking on.
  - gpt-oss-20b: temperature 1.0, top-p 1.0, reasoning effort "medium".

  The episodes of the three additional open agents come from the released CAPE-Bench rollouts.
- Closed agents use their public tool-use APIs:
  - Claude Haiku 5.5: thinking disabled, effort "low", at most 1,024 tokens per turn.
  - GPT-6-luna: reasoning effort "none", no parallel tool calls, at most 2,048 tokens per turn.

  The shared spend ledgers record $24.78 of API use in total (Claude Haiku 5.5's provider $19.86, GPT-6-luna's provider $4.92), including tests of the released tool and a 40-episode pilot ($0.10) of Claude Haiku 5.5 on AgentDojo that was not analysed.

Units. A unit is one proposed action that is not a read, after the step that reveals the deciding fact. Each episode contributes its actions up to and including its first violation. All violations are kept. Safe actions are subsampled at random with seed 0, so selection depends only on the past.

Reader input. The reader prompt holds four parts:

- the operating instructions;
- the user task;

- each earlier call with its result (results cut to 2,000 characters);
- the proposed action.

A context of 30,000 characters or more keeps its first 6,000 and last 24,000 characters. The prompt goes through Qwen3-8B's chat template with thinking off and is cut to its last 12,000 tokens. The feature is the residual stream at the last prompt token, at hidden-state index 32 (the output of block 31 of 36), in bf16.

Monitor. The monitor standardises the features, keeps the top 256 principal components, and fits a logistic regression with $C = 0.05$. It is trained on Gemma-4's CAPE-Bench steps only (17,623; development and fresh). The review cut has no labels. Offline (Table 8), it sends exactly 5% of the agent's actions in the test set, the highest-scored, to review (actions tied at the cut count in proportion). Live, it was the 95th percentile of the agent's earlier unlabelled actions, then frozen; the tool freezes it after the first 500. A rolling cut fails under bursts of similar actions.

Replica.

- **Target:** the agent's residual stream at its end-of-reasoning token, at 5 depths (block $\mathrm{round}(nf) - 1$, $f \in \{0.5, 0.62, 0.72, 0.82, 0.9\}$). It is standardised and reduced to 128 principal components, all fit on development.
- **Map:** ridge regression, with $\alpha \in \{1, 10, 10^2, 10^3, 10^4\}$ chosen by 5-fold cross-validation grouped by scenario.
- **Probe on the true state:** standardise, then logistic regression with $C = 0.05$, on the 128 true components.

Text baseline. TF-IDF of the context and of the action, kept as two separate blocks:

- word 1- and 2-grams, minimum document frequency 3, at most 200,000 features each, sublinear term frequency;
- logistic regression with $C \in \{0.1, 1, 10\}$, chosen by 5-fold cross-validation grouped by scenario.

The browser tool runs the same model. On 302 real agent steps it gives the same text as Python, and its held-out AUROC is 0.9887 (Python 0.9886).

Statistics.

- AUROC is computed within strata (template and tool, or suite) and averaged with weights by the number of positive–negative pairs.
- Intervals are percentile intervals from 1,000 bootstrap resamples of scenarios or episodes. The seeds are fixed in each preregistration.
- Each preregistration (the document and its analysis code) is locked by its SHA-256 hash before its data exist. One script checks every lock and every number in this paper again from the saved results.

Compute. All GPU work runs on NVIDIA H100 NVL GPUs (96 GB), one job at a time except for one 8-hour period with two (and one accidental 4-second overlap): PyTorch 2.11, Transformers 5.14.1 (5.20.1 for Muse-Glimmer, whose architecture the earlier version does not know), scikit-learn 1.9.0. The reader takes 41 ms for one action on one GPU; the median server round trip in the three blocking live tests was 89, 80 and 83 ms.

F.1. The geometry experiments (G1–G5)

Contexts and battery. 4,800 single-message contexts, 800 from each of six sources (harmful and benign requests, SST-2 reviews, BoolQ questions, GSM8K problems, Wikipedia text), split at random into 3,360 development and 1,440 confirmation contexts before any analysis. The battery has 88 yes/no questions about the message (topic, intent, tone, demands, risk), each appended after a fixed preamble that asks for a one-word answer; $P(\mathrm{YES}) = p_{\mathrm{YES}}/(p_{\mathrm{YES}} + p_{\mathrm{NO}})$ from the top-20 log-probabilities of the first answer token (cells where both are 0, 2 of 38,400 per model, get $\frac{1}{2}$). **Models.** Gemma-3 4B, gpt-oss 20B, Llama-3.1 8B, Mistral 7B v0.3, OLMo-3 7B, Phi-4 mini, Qwen2.5 7B and Qwen3 8B, instruction-tuned, with their own chat templates (vLLM for answers and replies, Hugging Face transformers for hidden states). Hidden states: the residual stream at the last prompt token at six depths (25, 50, 62, 75, 90 and 100% of the layers). The layer of each model is the one whose cosine geometry best matches the exact answer geometry on 1,000 development contexts; the confirmation contexts are not used to choose anything. **Sampling.** Sampled answers are drawn from the model's own probabilities (8 per question for G1; one per question, as yes, no or other, for G5). Text and reply embeddings: all-MiniLM-L6-v2, masked mean, L_2 normalised; replies are 8 samples at temperature 1, at most 128 tokens. **Claude Haiku 5.5 (G2).** Claude Haiku 5.5 answered the 24 questions of our earlier closed-model tests, 8 times each, on 192 confirmation contexts (thinking off, at most 3 tokens). The two halves are a random permutation of each cell's 8 samples (seed 2290). The bound of C1 (0.7) was set from open models' simulated split halves on development contexts only (0.76–0.96). **Exact recovery (G3).** Qwen3-0.6B

in float32 (TF32 off). 9,000 sequences of 128 tokens sampled from the model (temperature 1; seed 0), every position a context. The basis Q_d is from the first 3,000 contexts ($\sigma_d/\sigma_{d+1} = 1{,}005$). The true state for the check is the input of the final RMSNorm divided by its RMS. A pilot with another seed (100) gave the same result to the fourth digit. **Bootstrap.** 500 resamples of contexts; Spearman on the pairs of distinct resampled contexts.

G. Agent results: more figures and the closed-agent table




Figure 6. **Live prevention and bursts.** (a) Episodes with an executed violation and (b) episodes that reached the goal, in the four preregistered live tests: GPT-6-luna and Claude Haiku 5.5 without a gate and with blocking; Claude Haiku 5.5 with hold for review (an oracle reviewer, run separately); and Claude Haiku 5.5 told that it is monitored, with the cut set again on its unlabelled traffic. Bars: rates; whiskers: 95% Wilson intervals. (c) Violations caught at a 5% budget as the share ρ of violations in a burst grows, for the frozen cut and two cuts that move with recent traffic (Claude Haiku 5.5's scores, replayed); dotted: the β/ρ bound of Proposition 11.




Figure 7. **Replicating the hidden state.** (a) Score of a probe trained on Gemma-4's true states, on the true state and on two replicas (12,128 fresh steps; left half safe, right half violations; bars: medians). (b) Variance-weighted R^2 of the top 128 components, unseen scenarios. (c) R^2 gain of the reader replica over the TF-IDF replica at each recorded layer, over the full layer. (d) Per component: replica variance over state variance, against R^2.




Figure 8. **Robustness and transfer.** (a) Claude Haiku 5.5's reader scores in order (violations in orange): 1,000 normal actions, then a burst in which half are violations; lines: three cuts (legend: share of the burst's violations caught). (b) The closed GPT-6-luna's injected calls caught at the benign 5% cut, against labelled AgentDojo calls of open agents (numbers: AUROC). (c) Claude Haiku 5.5's scores when told, or not told, that it is monitored; dashed: the cut frozen on its earlier traffic.

Table 8. **Closed agents at a 5% review budget.** Pooled AUROC, and the share of violations caught when the top 5% of actions go to review (a label-free cut). All monitors are trained on Gemma-4 only.

	Claude Haiku 5.5		GPT-6-luna	
Monitor	AUROC	caught	AUROC	caught
Zero-shot 70B judge	0.570	0.0%	0.778	37.9%
Tool identity	0.857	42.4%	0.856	13.6%
TF-IDF (same labels)	0.975	63.8%	0.964	49.0%
Reader probe	**0.989**	**94.1%**	**0.996**	**98.5%**

H. The released tool

I. Smaller readers

All readers are trained on the same 17,623 Gemma-4 CAPE-Bench steps (1,339 violations); none is trained on a test set. Browser encoders: all-MiniLM-L6-v2, all-mpnet-base-v2 (three 1,000-character views) and Qwen3-Embedding-0.6B (one instruction-prefixed text, last-token pooling), each with a standardised logistic probe. Decoder readers: Qwen3-0.6B, 1.7B, 4B and 14B at the shipped reader's relative depth, with the shipped probe. The selected browser encoder, Qwen3-Embedding-0.6B, beats TF-IDF on the closed agent's AgentDojo calls (0.605 vs 0.335; +0.270 [0.134, 0.451]), so the website offers it for new kinds of tasks; on CAPE-Bench it is 0.097 below the 8B reader (Section A). In the browser it runs as a float16 ONNX model whose features match PyTorch's (cosine 1.000 on 40 steps); the 8-bit model's do not (0.852).

(a) Label imported logs; the review queue shows the riskiest first



(b) A closed agent's actions in the monitor's space, with the review cut





Figure 9. **The released tool.** (a) The browser trainer labelling imported agent logs; the review queue lists the riskiest unlabelled action first. (b) Claude Haiku 5.5's 3,128 actions in the monitor's space, with the label-free cut as a plane.



J. The probe on the replica

The numbers behind Proposition 9 and Section G, for the four agents of the replication tests.

Table 9. A probe trained on the agent's *true* states, scored on the true states and on the reader replica (rep.); fresh steps; exploratory. Pairwise risk: $\mathbb{E}\log(1+e^{-(s_i-s_j)})$ over violating i and safe j (lower is better); AUROC pooled and within template. Better of each pair in blue.


	pair risk ↓		AUROC		in template	
agent	true	rep.	true	rep.	true	rep.
Gemma-4	.018	**.015**	.994	**.996**	.984	**.987**
gpt-oss	.078	**.045**	.972	**.986**	.900	**.924**
Qwen3.8	.044	**.035**	.986	**.990**	.955	**.972**
Muse	.056	**.022**	.982	**.996**	.929	**.969**

Pairwise risk: $\mathbb{E}\log(1+e^{-(s_i-s_j)})$ over violating i and safe j.

K. The interrogation state in chat

On Claude Haiku 5.5, readouts of the interrogation state trained only on open models forecast which harmful requests Claude Haiku 5.5 refuses. Against a three-level moderation verdict the forecast wins (three preregistered tests); against graded moderators it ties (prospective, 923 conversations: 0.873 vs 0.855). Combined with a moderator, it doubles the

precision of an alarm for harmful requests that the model answers (0.535 vs 0.274).



L. The preregistration record

Tally, as recorded: method (G): 48 tests; 18 passed every primary endpoint, 17 passed some endpoints and failed others, 9 failed, 2 stopped before any outcome, 1 reported without a pass/fail bar, 1 pending; trained comparisons (T): 32 tests; 15 passed every primary endpoint, 7 passed some endpoints and failed others, 7 failed, 0 stopped before any outcome, 3 reported without a pass/fail bar, 0 pending. No correction for multiple tests is applied; each test answers its own registered question, and every outcome, failed or passed, is listed below.

Every confirmatory test, as in the released record (generated from it by a script; file paths and commit ids are replaced for review). Locks (SHA-256 of the preregistration and its code) and outcomes are in the released record; lock times are self-reported. Endpoints are numbered (i), (ii), ... in the order of each preregistration. Later tests changed two readings fixed in advance. First, the unseen-task test showed that labels do not transfer on tau2-bench through word counts: the test tasks had been in training. Second, "checks rules" in the frontier-agent judge test means only that the judge separates violating from allowed writes of the same tool.

Test	Outcome (verbatim from the record)
Interrogation state, open chat models open LLMs ((i)–(iii))	**PASS all, after deviation 1**: (i) +0.120 [0.115, 0.126]; (ii) +0.057 [0.045, 0.073] (7/8 models); (iii) +0.359 [0.310, 0.415]; Holm $p < 0.0005$ each. First run: (i) valid PASS, (ii)/(iii) invalid (numerical; see note) ([released file])
Resampling vs a probe agents ((i)–(iii); addendum 1: (iv)–(v))	**Claim (a) CONFIRMED** ((i), (ii) pass: resampling (16 rollouts) − white-box probe +0.063 [0.033, 0.094]); claim (b) NOT confirmed ((iii) fails: Ψ − white-box probe −0.021 [−0.054, 0.009]); addendum **(iv) passes** ((iv)+Ψ − white-box probe +0.049 [0.020, 0.080]); (v) fails ((ii)+Ψ − resampling (16 rollouts) −0.023 [−0.053, 0.006]) ([released file])
Interrogation state, Othello Othello recovery ((i)–(iii))	**PASS all**: (i) R^2 0.967 [0.967, 0.968] > 0.90; (ii) ΔR^2 +0.094 [0.086, 0.105], Holm $p < 0.0005$; (iii) Δ occupied acc +0.043 [0.040, 0.046], Holm $p < 0.0005$. White-box reference 0.983 ([released file])
Claude Haiku 5.5 chat readouts Claude Haiku 5.5 readout transfer ((i)–(iii))	**all pass**: (i) 0.993 [0.983, 0.999]; (ii) 0.997 [0.990, 1.000]; (iii) 0.935 [0.868, 0.982] ([released file])
Claude Haiku 5.5 refusals vs moderation Claude Haiku 5.5: grey box vs text moderation ((i)–(iii))	**(i) pass** 0.923 [0.884, 0.957]; **(ii) (key) pass** grey box − moderation +0.176 [0.060, 0.287] (0.827 vs 0.651); (iii) not tested (1/40 over-refusals) ([released file])
Claude Haiku 5.5, one-call grey box Claude Haiku 5.5: one-call grey box + compliance alarm ((i)–(iii))	**all pass** vs the preregistered 3-level verdict: (i) +0.142 [0.081, 0.203] (0.815 vs 0.673); (ii) AP +0.230 [0.161, 0.307]; (iii) AP +0.081 [0.036, 0.140]. Against GRADED moderators (i) ties (Qwen3Guard +0.018 [−0.043, +0.081]; Llama-Guard −0.031 [−0.082, +0.020]); the alarm gain holds ([released file], [released file])
Claude Haiku 5.5, transcript readout Claude Haiku 5.5: transcript-framing grey box ((i)–(ii))	**both pass**: (i) grey box − moderation on harmful refusals +0.141 [0.082, 0.199] (0.817 vs 0.676); (ii) compliance-risk AP (Claude-moderator) +0.115 [0.076, 0.179] ([released file])

Test	Outcome (verbatim from the record)
When the internals are read time: internals at CAPE's decision point vs black box ((i)–(iii))	**all pass**: (i) internals at the decision − resampling at the start of the turn +0.075 [0.044, 0.106]; (ii) resampling at the decision − internals at the decision +0.021 [0.011, 0.035]; (iii) internals at the decision − white-box probe at the start of the turn +0.138 [0.107, 0.163] ([released file])
Claude Haiku 5.5 vs graded moderators Claude Haiku 5.5: the Live tool's alarm, prospective ((i)–(iii))	**(i) pass** (alarm precision 0.535 vs 0.274 for the moderator alone, +0.261 [0.215, 0.311]); **(ii) FAIL** (grey box 0.873 vs graded Qwen3Guard 0.855, +0.018 [−0.023, 0.062]); **(iii) FAIL** (multi-turn 0.894 vs 0.906) ([released file])
Resampling with a deployable judge deployable monitors: LLM judge instead of the oracle checker ((i)–(iii))	**(i) FAIL** (judge-scored resampling 0.782 < turn-start probe 0.846, −0.065 [−0.115, −0.019]); **(ii): probe better** (CAPE probe 0.976 > judge on actual action 0.910, −0.067 [−0.104, −0.036] for the judge); **(iii) FAIL** (resampling hurts the action judge, −0.049) ([released file])
Reader vs the agent's internals reader trained on labels vs the agent's internals ((i)–(ii))	**both pass**: (i) reader − internals at the decision +0.015 [0.007, 0.026] (0.994 vs 0.979); (ii) reader − judge +0.085 [0.052, 0.127] ([released file])
Unseen task families agent internals vs transcript reader on unseen scenario families ((i)–(ii))	**(i) pass** (reader − agent internals on unseen families −0.007 [−0.014, −0.0001], margin −0.02); **(ii): agent probe better than zero-shot judge** (+0.062 [0.028, 0.101]) ([released file])
Another open agent reader trained on Gemma, monitoring gpt-oss ((i))	**(i) pass**: Gemma-trained reader on gpt-oss 0.915 vs zero-shot judge 0.833, +0.082 [0.043, 0.129] ([released file])
AgentDojo, no labels reader monitor on AgentDojo prompt injection, zero transfer training ((i)–(ii))	**(i) pass**: reader 0.781 vs zero-shot judge 0.537, +0.249 [0.136, 0.369]; **(ii) reader better than CAPE's gate**: gpt-oss calls as the prereg text specifies, 0.823 vs 0.601, +0.222 [0.143, 0.303] (locked code's broader subset: +0.264 [0.174, 0.359]) ([released file])
Claude Haiku 5.5, after a reveal Claude Haiku 5.5 as an agent, monitored by a reader trained only on Gemma ((i))	**(i) NOT TESTED**: 0 unsafe units under the preregistered post-reveal rule (Claude's 68 violations all happen at or without the reveal); see "Closed agent: Claude Haiku 5.5"
Closed agent: Claude Haiku 5.5 Claude as an agent, all non-read actions ((i'))	**(i') pass**: Gemma-trained reader on Claude 0.991 vs zero-shot judge 0.633, +0.360 [0.302, 0.413]; 95.6% of violations caught at 5% escalation with a cut set on labelled safe actions (judge 0%); at the label-free cut used elsewhere, 94.1% ([released file], [released file])
Reader vs TF-IDF trained TF-IDF monitor on the reader's own input, same labels ((i) Claude, (ii) unseen families)	**(ii) pass, (i) FAIL**: unseen families reader 0.969 vs TF-IDF 0.950 (+0.019 [0.007, 0.032]); Claude reader 0.991 vs TF-IDF 0.997 (−0.006 [−0.027, +0.007]). AgentDojo (reported) 0.781 vs 0.503 ([released file])
A policy removed from training Claude on task families the monitor never saw ((i) pooled, (ii) within)	**(i), (ii) pass** (vs zero-shot judge): pooled 0.912 vs 0.570 (+0.342 [0.311, 0.371]); within 0.948 vs 0.633 (+0.318 [0.265, 0.374]). But at the label-free cut the unseen restart family is caught 0/26 ([released file])
Closed agent: GPT-6-luna second closed family: gpt-6-luna as agent, frozen monitors ((i) pooled vs judge, (ii) vs tool identity, (iii) within tool)	**(i), (ii), (iii) all pass**: GPT-6-luna, 3,627 actions, 66 unsafe in 6 families. Reader pooled 0.996 vs judge 0.778 (+0.217 [0.174, 0.265]); vs tool identity +0.141 [0.111, 0.171]; within tool vs judge +0.039 [0.015, 0.066]. 98.5% caught at the label-free 5% cut (judge 37.9%) ([released file])
Labels for a new policy labels needed for a new policy, prospective on GPT ((i) 40 vs 0 labels, (ii) catch at 40 $\geq$ 0.5)	**(i) FAILS, (ii) passes**: with 0 labels of the held-out credentials policy, the reader already caught 18/18 of GPT's violations of it, so added labels had nothing to fix (40 − 0: 0.0). The "A policy removed from training" curve does not replicate on this family ([released file])
AgentDojo with a defense a closed agent on an external benchmark: GPT-6-luna on AgentDojo, frozen monitors ((i) reader vs judge)	**(i) NOT TESTED**: GPT-6-luna resisted the injections (attack success 2.1%), leaving 4 injected calls (minimum 10). Utility on benign tasks 0.862 ([released file])
AgentDojo, closed agent closed agent on AgentDojo without the defense (arm none, dev + conf; (i') reader vs judge)	**(i') FAILS**: 36 injected calls; reader 0.840 vs zero-shot judge 0.787 within suite (+0.052 [−0.026, +0.130]). TF-IDF 0.335. At the benign-call 5% cut: reader 36%, judge 53% ([released file])

Test	Outcome (verbatim from the record)
Open-agent labels for a closed agent labels of the new policy from open agents, tested on the closed agent ((i) vs judge, (ii) vs no labels)	**(i), (ii) pass**: with AgentDojo labels from open agents, the reader on GPT's AgentDojo calls scores 0.922 vs judge 0.787 (+0.136 [0.078, 0.191]) and vs no labels +0.081 [0.044, 0.121]; caught at the benign 5% cut 36% → 92% ([released file])
Replication (Gemma-4) latent replication: does the reader replicate the agent's hidden state? ((i) R^2 vs text, (ii) readouts on the replica)	**(i), (ii) pass**: from the transcript alone, the reader replica reconstructs 66.4% of the agent's decision-state variance (top 128 PCs; text 58.6%; +0.079 [0.075, 0.083]); a probe trained on TRUE states scores 0.987 on the replica vs 0.984 on the true state (+0.003 [−0.002, +0.007]) ([released file])
Live prevention (GPT) live prevention on a closed agent: the monitor blocks GPT-6-luna's escalated actions in the loop ((i) violation episodes, gated − ungated)	**(i) passes**: live, the grey-box gate cut GPT-6-luna's episodes with an executed violation from 6.6% to 0.2% (−0.064 [−0.088, −0.044]); 0 violations after a block; goals 47.4% → 45.6%; round trip 89 ms median ([released file])
Live prevention (Claude Haiku 5.5) live prevention on a second closed family: Claude Haiku 5.5 in the loop ((i'))	**(i') passes**: on Claude Haiku 5.5, episodes with an executed violation 6.7% → 0.2% (−0.064 [−0.087, −0.044]); 0 violations after a block; goals 40.7% → 34.9%; round trip 80 ms median ([released file])
Replication, three architectures replication on three more open agents: gpt-oss-20b, Qwen3.8-27B, Muse-Glimmer-30B ((i), (ii) per agent; scenario-disjoint split)	**(i) and (ii) pass on all three agents (replication generalizes)**: from the transcript alone, R^2 of the decision state on fresh scenarios: gpt-oss 0.494 (text 0.392; +0.102 [0.093, 0.110]), Qwen3.8 0.542 (0.441; +0.101 [0.091, 0.111]), Muse Glimmer 0.462 (0.401; +0.061 [0.051, 0.071]). A probe trained on the true states, true → replica: 0.900 → 0.924, 0.955 → 0.972, 0.929 → 0.969 (all lower bounds > −0.02). Fidelity: the agents' own models predict 91–100% of their next 16 tool-call tokens. Exploratory, Gemma-4 under the same split: R^2 0.631 (text 0.556). Exploratory: the text map chose α = 1, the edge of the grid; a finer grid (α 0.01–1, exact dual-form ridge, [released file]) is worse at every smaller α for all three agents, so α = 1 is the text map's optimum ([released file], [released file])
Hold for review hold for review instead of block: Claude Haiku 5.5, escalated actions go to a reviewer ((i) safety kept, (ii) no goal cost vs "Live prevention (Claude Haiku 5.5)" ungated)	**(i) passes, (ii) fails.** Episodes with an executed violation: 6.7% ("Live prevention (Claude Haiku 5.5)" ungated) → 0.0% (review) (−0.067 [−0.091, −0.044]). Goals: 40.7% → 38.7% (−0.020 [−0.051, +0.007]); the lower bound misses the −0.03 margin, so no goal cost is NOT shown. Reviewer workload: 88 held actions (0.20 per episode, 6.2% of scored actions), 31 of them violations; 0 violations after a block. Exploratory ([released file]): episodes with a held-and-approved action kept their goals (60.8% vs 58.8%); the gap is in never-held episodes (38.9% vs 41.0%, n = 368), where both arms ran the same way, which we suggest is run-to-run variation against a non-concurrent control (a hypothesis that "Hold for review" does not test). Spend $0.81. **Deviation 1 (infrastructure, 16:39):** the first start ran 0 episodes. The monitoring server loaded the reader outside its lock, and 6 concurrent first requests raced on the lazy transformers imports (ImportError). Fix: the load moved inside the lock ([released file]; scoring unchanged; regression test [released file]). Rerun from scratch on a GPU job; spend of the failed start $0.004
tau2-bench, Claude Haiku 5.5 a second outside benchmark: Claude Haiku 5.5 on τ^2-bench airline, monitors trained on four frontier agents' labelled trajectories ((i) within-tool reader vs tool identity, (ii) reader vs TF-IDF)	**not tested**: 9 violations < the preregistered minimum of 15 (Claude violated in 1.5% of episodes; the 9 come from 3 tasks). Descriptive only: within-tool AUROC reader 0.756, TF-IDF 0.963; pooled reader 0.835, TF-IDF 0.960, tool 0.686; the CAPE-trained probe zero-shot 0.357 pooled ([released file])
Browser-size readers readers small enough for a browser or a CPU: do they transfer? ((i) browser reader vs TF-IDF on GPT AgentDojo; (ii) non-inferior to the 8B reader on closed CAPE)	**(i) passes, (ii) fails.** Selected browser reader (best on "AgentDojo, no labels"): Qwen3-Embedding-0.6B. On "AgentDojo, closed agent" (GPT on AgentDojo) it beats TF-IDF: 0.605 vs 0.335 (+0.270 [0.134, 0.451]); on the closed agents' CAPE-Bench actions it is below the 8B reader: −0.097 [−0.115, −0.079] (Claude 0.912, GPT 0.884 vs 0.989, 0.996). Decoder readers on "AgentDojo, closed agent": 0.6B 0.651, 1.7B 0.771, 4B 0.696, 8B 0.840, 14B 0.689; none is within 0.02 of the 8B on both sets, so no CPU option is offered. The shipped 8B reproduces its published AUROCs exactly ([released file]). **Deviation 1:** the analysis crashed after computing, when writing its JSON (a numpy bool); fix: one bool() cast, no computation changed

Test	Outcome (verbatim from the record)
tau2-bench, two closed agents τ^2-bench with two closed agents (Claude Haiku 5.5, GPT-6-luna) and a persistent customer; "tau2-bench, Claude Haiku 5.5"'s monitors ((i) reader vs tool within tool, (ii) TF-IDF vs tool)	**(ii) passes, (i) fails.** Within-tool AUROC: TF-IDF 0.987 (+0.487 [0.428, 0.500] over tool identity), reader 0.738 (+0.238 [−0.053, 0.431]); reported: reader − TF-IDF −0.250 [−0.518, −0.077]. Per agent: Claude reader 0.555 / TF-IDF 0.966; GPT 0.739 / 1.000. Reading fixed in advance: on τ^2-bench, labels of the policy from other agents transfer to both closed agents through word counts, and the reader does not use them as well ([released file]). Spend (from the ledgers): Claude $1.71, GPT $0.83
tau2-bench, unseen tasks τ^2-bench, policy or tasks? "tau2-bench, two closed agents"'s test, training without the test tasks ((i) reader vs TF-IDF, (ii) reader vs tool; within tool)	**(i) and (ii) fail: neither monitor transfers to unseen tasks.** Within-tool AUROC: reader 0.535, TF-IDF 0.519 ("tau2-bench, two closed agents" with the same tasks: 0.738, 0.987); reader − TF-IDF +0.017 [−0.514, 0.539]; reader − tool +0.035 [−0.230, 0.259]. TF-IDF with entities masked 0.366 (exploratory). "tau2-bench, two closed agents"'s word-count advantage was memorisation of the tasks ([released file])
tau2-bench, reasoning judge τ^2-bench, a zero-shot reasoning judge (Qwen3-32B, thinking; no labels) on "tau2-bench, two closed agents"'s writes ((i) judge vs tool, (ii) judge vs "tau2-bench, unseen tasks"'s reader; within tool)	**(i) and (ii) fail (intervals include 0).** Within-tool AUROC 0.804 ("tau2-bench, unseen tasks"'s reader 0.535); judge − tool +0.304 [−0.084, 0.427]; judge − reader +0.268 [−0.074, 0.511]. Pooled 0.785; 53% caught at the 5% cut as first computed; 34.5% with exactly 5% reviewed (ties at the cut counted in proportion; [released file]); at 50: 12 of 19 caught, 16 of 243 safe flagged. 262/262 answers parsed, none truncated (median 485 tokens). 88% of scores are exactly 0. "tau2-bench, Claude Haiku 5.5": within tool 0.694, 2 of 9 caught at 50. Large point estimate, too few violating tasks to confirm ([released file])
Reasoning judge, frontier agents τ^2-bench, "tau2-bench, reasoning judge"'s judge unchanged on the 894 published writes of four closed frontier agents ((i) judge vs tool, (ii) judge vs reader cross-validated by task; within tool)	**(i) passes, (ii) fails.** Within tool: judge 0.766, reader (cross-validated) 0.646, TF-IDF (cross-validated) 0.490; judge − tool +0.266 [0.151, 0.338]; judge − reader (cross-validated) +0.120 [−0.047, 0.274]. Reported: 4-sample mean 0.838, − reader (cross-validated) +0.192 [0.022, 0.336]; per agent (judge) 0.768 / 0.771 / 0.775 / 0.618 (o4-mini). With exactly 5% of writes reviewed: reader (cross-validated) catches 18.4%, the judge 11.7%, the 4-sample mean 15.3%, the tool 13.0% (most possible 19.7%). 894/894 parsed in every sample; none truncated; 63% of scores exactly 0. Reading (fixed): the judge checks rules beyond the tool identity, but not better than the reader trained on other tasks ([released file])
Monitor-aware agent monitor-aware closed agent: Claude Haiku 5.5 with and without CAPE's oversight notice, 990 scenarios × 2 arms, no gate; the shipped reader with a cut frozen on Claude's earlier unlabelled traffic ((i) caught aware − plain; (ii) aware caught)	**(i) and (ii) pass.** Caught at the frozen cut: plain 83.6%, aware 97.1% [92.9%, 100%]; aware − plain +0.136 [+0.050, +0.225]. Being told did not change how often Claude violated (−0.003 [−0.012, +0.005]) or reached the goal (37.6% vs 37.8%). Note: the notice moves the score distribution up: the frozen cut escalates 15.2% of the aware arm's actions (plain 5.3%). At each arm's own 5% budget: 88.6% vs 83.6%. AUROC within template 0.994 vs 0.967 ([released file])
Adaptive attacker adaptive attacker with score access: Qwen3-32B rewrites the free text of 134 real closed-agent violations (2 rounds × 16, score feedback), the checker confirms each still violates ((i) reader caught after attack; (ii) reader − TF-IDF)	**(i) and (ii) fail.** Reader caught 96.3% → 29.1% [21.6%, 36.6%] after attack (Claude 11.8%, GPT 47.0%); TF-IDF 57.5% → 34.3%; reader − TF-IDF −0.052 [−0.149, +0.037]. Every rewrite still violated (replay checker). The rewrites keep the decisive field (recipient, service and host) and add self-reported approvals ('approved under routine maintenance protocol . . . ', '–reason . . . '): the learned monitors read the agent's own claims as evidence. Reading as fixed: the monitor is not robust to adaptive rewording ([released file])
Canonical-action monitor canonical-action monitor: the shipped reader and recipe trained on canonical actions (free-text fields → "[free text]", quoted prose and # comments removed); "Adaptive attacker"'s attack rerun against it with seed 1 ((i) caught after attack; (ii) clean catch − shipped on Claude ∪ GPT; (iii) AgentDojo within-suite − shipped)	**(i), (ii) and (iii) fail.** After attack 50.8% [42.5%, 59.0%] caught (shipped reader 29.1%); before attack 55.2%. Clean catch at 5%: Claude 94.1% → 51.5%, GPT 98.5% → 59.1%; (ii) −0.410 [−0.493, −0.311]. AgentDojo (iii) −0.029 [−0.080, +0.010]. By tool: send_message 29.3% before and after (the canonical score cannot move, as Corollary 1 predicts); execute_mock_command 96.2% → 84.6% (commands keep their words). Cause: the premise that the label depends on the action only through κ(A) is false for 81 of the 82 send_message targets (one family, tp_campaign_test: the body carries the draft that is leaked), so the body is payload, not only self-report [this cause was wrong: see "Correction to the "Canonical-action monitor" cause" below]. Reading as fixed: canonical mode is an option with its measured cost, not the default ([released file])

Test	Outcome (verbatim from the record)
Training against the attack adversarial training: Gemma training actions of the attacked tools, violating AND safe (300 + 300), rewritten by "Adaptive attacker"'s attacker (8 each), labelled by replay (4,554 rewrites; 28 changed label) and added to training; "Adaptive attacker"'s attack re-run against the hardened monitor with seed 2 and told the defense ((i) caught after attack; (ii) clean catch − shipped on Claude ∪ GPT; (iii) AgentDojo − shipped)	**(i), (ii) and (iii) fail.** After the defense-aware attack 59.7% [51.5%, 67.9%] caught (before 92.5%); by tool: send_message 98.8% → 47.6%, execute_mock_command 82.7% → 78.8%. The shipped probe on the same rewrites: 96.3% → 57.5%, so hardening added about 2 points. Clean catch at 5%: Claude 94.1% → 88.2%, GPT 98.5% → 97.0%; (ii) −0.037 [−0.078, +0.016]. AgentDojo (iii) +0.012 [−0.050, +0.071]: the lower bound equals the margin after the locked code's 4-decimal rounding, so it fails as registered. Reading as fixed: augmentation with a known attack does not stop a defense-aware attacker; three preregistered defenses against score-querying rewording have failed ([released file])
Cut set again after a prompt change set the cut again after a prompt change, live: Claude Haiku 5.5 with "Monitor-aware agent"'s oversight notice, 400 scenarios × (ungated, gated); the cut set from "Monitor-aware agent"'s aware-arm reader scores (3,046, no labels), budget 5%, frozen ((i) violation rate gated − ungated; (ii) share of ungated actions escalated within [0.025, 0.075])	**(i) and (ii) pass.** Episodes with an executed violation 6.5% (26/400) → 0.0% (0/400): −0.065 [−0.090, −0.043]. The new cut escalated 4.73% [3.49%, 6.10%] of the ungated arm's 1,206 actions; the cut frozen on plain traffic would have escalated 16.6%. 25 of 54 blocked actions would have been violations; goals 38.5% → 35.5%; violations caught at the new cut in the ungated arm 88.5%; median round trip 83 ms. Reading as fixed: setting the cut again on unlabelled traffic restores the budget, and the gate prevents the violations of an agent that knows it is monitored ([released file])
Observable geometry (G1–G3) training-free observable geometry: on 8 open models ((i) answers vs text, (ii) 8 samples keep ≥95%, (iii) 88 vs 8 questions); on Claude Haiku 5.5 ((i) split-half > 0.7, (ii) vs text); exact Gram recovery on Qwen3-0.6B ((i)–(iii))	**all pass**: (i) 8/8 (gains +0.16 to +0.49, lower bounds ≥ 0.141); (ii) 8/8 (lower bounds 0.957–0.997); (iii) 8/8; (i) 0.950 [0.939, 0.960]; (ii) +0.438 [0.391, 0.485]; (i) Pearson 1.0 (8 digits) at 2× d(d+1)/2, median cosine error 7e-6; (ii) error 0.51 → 7e-6 across the threshold; (iii) vs baselines 0.40, 0.11. Before the lock, from dev and the pilot only: (ii) changed from an absolute margin to a ratio, (i)'s bound raised 0.5 → 0.7 (both disclosed in the prereg). After the lock: Correction 1 to Theorem 5 (below)
Answers vs replies (G5) which outputs carry the state: yes/no answers vs the model's own replies ((i) exact answers vs 8 replies; (ii) 88 one-token sampled answers vs 1 reply; (iii) replies saturate)	**all pass**: (i) 8/8 (+0.16 to +0.48); (ii) 7/8 (gpt-oss −0.048 [−0.075, −0.023]); (iii) 8/8 (≤ 0.031). Replies' geometry 0.22–0.44 (0.22–0.34 for seven models; Gemma-3 4B 0.44), close to text. [Corrected 2026-10-22: the row said 0.22–0.34; [released file] has Gemma-3 4B at 0.442.] Dev dry run of the dropped (iv) design disclosed in the prereg.
Shared geometry (G6) the observable geometry is shared across models ((i) no own-model excess, equivalence ±0.02; (ii) an open model's hidden geometry is the better stand-in; (iii) answers beat text on four new kinds)	**all pass**: (i) +0.002 [−0.001, +0.005]; (ii) 6/7 (Mistral −0.049); (iii) 6/8 (Gemma, gpt-oss include 0). On fresh contexts agreement is lower than on "Interrogation state, open chat models" (answers 0.22–0.64); Gemma's replies beat its answers (0.43 vs 0.34). Motivated by an independent review's control (recorded in the ledger).
What each API channel reveals (G7) what each API output channel reveals of a model's own state ((i) answers no excess; (ii) top-20 leaks; (iii) ladder; (iv) log-probabilities leak most; (v) log-probabilities identify the model)	**all pass**: answers +0.001 (chosen layer), −0.006 (last layer); top-1/5/20 +0.056/+0.085/+0.115; full +0.112; log-probability +0.221 [0.211, 0.230]; own model best 7/8 with log-probabilities vs 1/8 with answers.

Test	Outcome (verbatim from the record)
Reading the reasoning (G8) does reading an agent's reasoning help a trained monitor? ((i) no in-agent gain on action labels; (ii) the reasoning hurts transfer; (iii) each agent; (iv) later violations)	**2 of 4 pass.** (i) FAIL: pooled in-agent cot − act −0.005 [−0.018, +0.013] (margin +0.01); Qwen3.8 gains +0.028 [0.002, 0.078] (73 positives), gpt-oss −0.034, Muse −0.009. (ii) pass: transfer from Gemma-4 −0.033 [−0.046, −0.017]. (iii) pass, narrowly: −0.055, −0.0004, −0.042. (iv) inconclusive: later violations +0.025 [−0.033, +0.085]; AUROC 0.59–0.70.
Live self-policing (G9) can an agent police itself in real time through its own API? ((i) gate prevents violations; (ii) resampling prevents them with few reviews; (iii) no loss of task success)	**2 of 3 pass.** Violating episodes: plain 27.9%; gate@1.0 4.95% (relative reduction 0.82 [0.76, 0.88]; (i) pass); resampling@0.75 4.35% (0.84 [0.78, 0.90]) but 0.404 reviews per episode against the 0.40 limit ((ii) FAIL). Success: plain 33.5%; gate 43.7% (+10.2 [+6.6, +14.3]); resampling 38.7% (+5.3 [+1.8, +9.2]) ((iii) pass). Live flag rates on candidate draws: resampling tau 0.94, phi 0.17; gate tau 0.85, phi 0.06.
A closed agent polices itself (G10) can a closed agent police itself in real time through its own API? ((i) prevents violations its transcript decides; (ii) cannot prevent those decided by an unchecked fact, as Corollary 1 predicts; (iii) no loss of task success)	**all pass.** Decidable (470 scenarios): violating episodes 2.77% → 0.85%, reduction 0.69 [0.51, 0.88] ((i)). Unchecked-fact (21 mailing-list scenarios): 100% → 92.9%, reduction 0.07 [0.00, 0.17] ((ii)). Success 40.4% → 40.1%, −0.3 [−2.1, +1.6] ((iii)). All scenarios: 6.9% → 4.8% (0.31 [0.19, 0.43]); 0.31 reviews per episode.
The prevention law across agents (G11, stopped) does an agent's offline self-audit predict its live self-policing? (v4fresh)	**STOPPED** (deviation): after 300 Qwen3.8 episodes neither arm had a violation, so the predicted reduction was untestable; base rates had not been checked; replaced by G11b.
The prevention law across agents (G11b) the same, on templates where each agent violates ((i) law within 0.15; (ii) Muse > Qwen; (iii) success)	**1 of 3 pass.** (i) FAIL: Muse-Glimmer 0.23 [0.13, 0.35] vs 0.722; Qwen3.8 −0.06 [−0.23, 0.09] vs 0.167. (ii) pass: +0.29 [0.10, 0.50]. (iii) FAIL: Qwen3.8 success −0.016 [−0.048, +0.016]. A note published before any Muse outcome ([a public commit]) traced the Qwen miss to the template mix of the offline sample and gave composition-weighted predictions, 0.273 (Muse, if it does not flag mailing-list sends) and 0.052 (Qwen): errors 0.04 and 0.11 (not a registered endpoint).
The composition-weighted law (G12) is live self-policing predicted by the composition-weighted law? ((i) each agent within 0.15; (ii) mean error <= 0.10)	**PASS ((i) 5/5, (ii))**: observed vs predicted reduction: Gemma-4 0.634 vs 0.671; gpt-oss 0.171 vs 0.146; Qwen3.8 0.014 vs 0.033; Muse-Glimmer 0.269 vs 0.254; Claude 0.302 vs 0.381 (difference −0.079 [−0.128, −0.032]: within 0.15 but a systematic over-prediction); mean absolute error 0.035 ([released file])
Self-policing against prompt injection (G13) does self-policing stop prompt injection live on AgentDojo, by the predicted amount? ((i) Gemma-4 reduction lower >= 0.50; (ii) law within 0.15, both agents; (iii) utility lower > -0.03)	**4 of 5 pass.** (i) pass: Gemma-4 attack success 11.5% -> 1.8%, reduction 0.843 [0.756, 0.912]. (ii): gpt-oss pass (observed 0.502 [0.420, 0.577] vs predicted 0.584); Gemma-4 FAIL (0.843 vs predicted 1.00; miss 0.157 > 0.15). (iii) pass both (utility +0.023 [+0.002, +0.043]; +0.002 [−0.027, +0.032]). Exploratory: in 17 of Gemma-4's 24 remaining successes the agent's audit had flagged a call that the stand-in reviewer (injection-only values) let run; 7 (travel) were unflagged, and travel's tau = 1.0 had been assumed in the lock without offline units ([released file])
Recreating the decision state, trained comparison (G14) can a black-box agent's decision state be recreated through its API well enough to monitor it with a white-box probe? ((i) grey − white > −0.03, four open agents; (ii) other agents' coordinates − own white > −0.07; (iii) Claude restart AUROC >= 0.80, lower >= 0.65)	**PASS ((i), (ii), (iii))** — a TRAINED comparison, not the method: recreation (reader + answers, maps and probe fit on open agents) − true state +0.063 [0.026, 0.122]; other agents' coordinates − own white box +0.009 [−0.050, 0.097]; Claude restarts 1.000 (reader alone also 1.000: in this template allowed calls are mostly help/status commands, so the call text separates them). The agent's answers add nothing to the reader (−0.000 [−0.017, 0.012]) ([released file])

Test	Outcome (verbatim from the record)
The agent's own answers, training-free (G15) does a training-free, API-only read-out of an agent's own answers monitor its decisions as well as a probe trained on its hidden states? ((i) mean of 8 − single answer > 0; (ii) mean of 8 − trained white box > −0.05; (iii) Claude restart AUROC >= 0.80, lower >= 0.65)	**PASS ((i), (ii), (iii))**: within-template AUROC, 8 answers (fixed) / 1 answer / probe trained on true states: Gemma-4 0.994/0.966/0.980; gpt-oss 0.822/0.758/0.772; Qwen3.8 0.951/0.894/0.826; Muse-Glimmer 0.929/0.935/0.941. (i) +0.036 [0.006, 0.064]; (ii) +0.045 [−0.017, 0.135]; (iii) Claude restarts 0.909 [0.858, 0.952] (single answer 0.323). Claude pooled 0.475: mailing-list sends (fact not in the transcript) mostly not flagged (4.8% above the median allowed call) ([released file])
Own answers or another model's (G16) does the monitor need the agent's OWN answers, or does another model's answers to the same questions do as well? ((i) two-sided: own − other, four open agents; (ii) Claude restarts, reported)	**No detectable difference ((i) includes 0)**: within-template AUROC, own vs another model's answers to the same 8 questions: Gemma-4 0.994 vs 0.993 (Muse-Glimmer answering); gpt-oss 0.822 vs 0.799, Qwen3.8 0.951 vs 0.889, Muse-Glimmer 0.929 vs 0.968 (Gemma-4 answering); mean own − other +0.012 [−0.018, 0.040]. (ii) (reported): Claude restarts, own 0.909 vs Gemma-4 answering 1.000, −0.091 [−0.142, −0.045]. Reading fixed in advance: the monitor is a fixed questionnaire that any capable model can answer about the call; the title drops "own" ([released file])
Training-free read-out, prompt injection (G17) does the training-free read-out of open agents' own answers detect prompt injection on a second benchmark? ((i) within-suite AUROC lower 95% > 0.60, Gemma-4 and gpt-oss-20b; (ii) read-out − single answer, reported)	**PASS ((i), both agents)**: within-suite AUROC of the fixed read-out, Gemma-4 0.985 [0.964, 0.998] (816 calls, 216 injected), gpt-oss-20b 0.904 [0.872, 0.932] (821, 221); single answer 0.975 and 0.900; (ii) read-out − single +0.007 [−0.004, 0.019]; parsed 94.5% and 91.1%. Disclosed: 17 gpt-oss requests failed in the server (HarmonyError) after 3 retries, leaving 39 of 6,568 question slots unanswered (36 on allowed calls; an unanswered question takes the neutral angle, which raises allowed calls' scores, against the read-out); Gemma-4's server died at shutdown, after its last unit ([released file])
Training-free read-out, a second benchmark for Claude Haiku 5.5 (G18) does the training-free read-out of a CLOSED agent's own answers detect its policy violations on a second benchmark? ((i) within-tool AUROC lower 95% > 0.50; (ii) read-out − single answer, (iii) read-out − reasoning judge, reported)	**PASS ((i))**: within-tool AUROC of the fixed read-out 0.704 [0.536, 0.822] (360 writes, 50 violations, 7 tasks with a violation; below the 0.75 "strong" reading); single answer 0.555; (ii) +0.150 [−0.004, 0.331]; (iii) vs the Qwen3-32B reasoning judge on its 224 writes 0.742 vs 0.578, +0.164 [−0.097, 0.429]; caught at a 5% budget 20% vs 4.9%; parsed 93%. Exploratory: within task and tool 0.61 [0.46, 0.97] ([released file], [released file])
Own conversation or outside reviewer, same closed model (G19) does a closed agent's answer need its own conversation? ((i) two-sided: own − outside reviewer, same model, read-out of 8 answers, within tool)	**No detectable difference ((i) includes 0)**: within-tool AUROC, read-out of 8 answers, own conversation 0.699 vs outside reviewer 0.656, own − outside +0.043 [−0.136, 0.226]; single overall question 0.552 vs 0.637, −0.086 [−0.282, 0.141]; outside answers parsed 99.9%. Reading fixed in advance: the paper must not claim that "own" matters; the value is in the questions and the read-out ([released file]). Spend $0.74
Questionnaire or reasoning judge (G20) does the fixed questionnaire do better than a holistic reasoning judge? ((i) two-sided: read-out − Gemma-4 reasoning judge, mean over four open agents, within template)	**Questionnaire better ((i) lower > 0)**: within-template AUROC, read-out of the agent's own 8 answers vs Gemma-4 reasoning judge (4 samples): Gemma-4 0.994 vs 0.989, gpt-oss 0.822 vs 0.755, Qwen3.8 0.951 vs 0.780, Muse-Glimmer 0.929 vs 0.880; mean +0.073 [0.021, 0.123]; judge parsed 97–99%. Reported: Claude restarts, judge 1.000 vs Claude's read-out 0.909 (−0.091 [−0.143, −0.044]); Claude pooled, judge 0.693 vs 0.475 (the judge reasons; Claude's answers had reasoning off) ([released file])

Test	Outcome (verbatim from the record)
An open model answers about a closed agent (G21) can an open model answer the questionnaire about a closed agent's calls on the second benchmark? ((i) Gemma-4's read-out about Claude's tau2 writes, within-tool AUROC lower 95% > 0.50; (ii) own − Gemma-4, reported)	**PASS ((i))**: Gemma-4's read-out about Claude's tau2 writes 0.989 [0.954, 1.000] within tool (parsed 99.7%); Claude's own 0.704; (ii) own − Gemma-4 −0.285 [−0.424, −0.171]: the open answerer does better. Not separable here: Gemma-4 answered with reasoning on, Claude (G18, G15's settings) with reasoning off. Exploratory controls: within task and tool 0.965 [0.927, 1.000] (Claude's own 0.61); without the targeted run 0.981; the overall question alone 0.960 ([released file])
One universal questionnaire on two benchmarks (G22) does one universal questionnaire, written without either benchmark, work on both? (U1a CAPE-Bench, (i') tau2-bench: universal read-out lower 95% > 0.50; (ii) universal − tailored, same answerer, reported)	**PASS (U1a, (i'))**: one universal questionnaire, answered by Gemma-4 about the same calls: CAPE-Bench mean over three agents 0.890 [0.818, 0.950] (gpt-oss 0.808, Qwen3.8 0.906, Muse-Glimmer 0.955); tau2-bench 0.935 [0.841, 0.985]. Universal − tailored (same answerer): CAPE-Bench +0.004 [−0.029, 0.036] (no detectable difference); tau2-bench −0.054 [−0.140, −0.014] (the tailored questions do better). Reported: Claude restarts 0.948 vs 1.000, pooled 0.443 vs 0.630; parsed 97–98%. A comparison setting (another model answers), not the method ([released file])
The theory predicts which questions monitor (G23) does the theory predict, without labels, which questions monitor? ((i) Spearman between each question's label-free Fisher-Rao signal-to-noise ratio and its AUROC, mean over five targets, lower 95% > 0; (ii), (iii) SNR-weighted read-out vs equal and raw-variance weights, two-sided)	**(i) PASS; (ii), (iii) no detectable difference**: mean Spearman between each question's label-free Fisher-Rao SNR and its AUROC 0.745 [0.608, 0.779] over five targets (16 questions, Gemma-4 answering); raw-P(yes) variance does as well (0.747; difference −0.002 [−0.026, 0.015]); SNR-weighted − equal +0.008 [−0.177, 0.032]; − raw-variance weights +0.005 [−0.177, 0.023]. A comparison setting; G25 is the same test on the agents' own answers ([released file])
The closed agent's own answers with reasoning (G24) do the closed agent's own answers monitor it when it reasons? ((i) reasoning-on read-out, within-tool AUROC lower 95% > 0.50; (ii) on − off, two-sided)	**(i) FAILS; (ii) no detectable difference**: reasoning on 0.568 [0.454, 0.771], reasoning off (same questions, G18's 4 answers each) 0.619; on − off −0.051 [−0.246, 0.150]; only 70% of answers parsed (with reasoning, Claude often hedged or wrote to the customer instead of answering; exploratory: the unparsed share does not track violations, AUROC 0.52). Reading fixed in advance: reasoning does not help detectably here; Claude's own answers remain a weak monitor on tau2-bench. Spend $0.27 ([released file])
The theory predicts which of the agent's own questions monitor (G25) does the theory predict which questions monitor, on the method's own answers? (G23's (i)-(iii) on each agent's own 8 answers: four open agents and Claude on CAPE-Bench, two agents on AgentDojo, Claude on tau2)	**(i) PASS; (ii), (iii) opposite**: mean Spearman between each question's label-free Fisher-Rao SNR and its AUROC 0.580 [0.470, 0.648] over eight targets (per target 0.98, 0.93, 0.95, 0.74, −0.03, 0.31, 0.40, 0.36); raw-P(yes) variance does as well (0.586; difference −0.006 [−0.051, 0.036]). SNR weighting lowers the read-out: − equal weights −0.068 [−0.142, −0.047]; − raw-variance weights −0.028 [−0.102, −0.011]. Reading: a label-free measure tells which of the agent's own questions carry the signal, but the noise model adds nothing beyond plain variance here, and weighting by it hurts; equal weights stay ([released file])
The closed model reviews its own calls, with reasoning (G26) does a closed model, through its own API only, monitor its own calls when it reviews them with reasoning? ((i) within-tool AUROC lower 95% > 0.50; (ii) − own in-conversation read-out; (iii) − reviewer without reasoning; two-sided)	**PASS ((i))**: 0.918 [0.730, 0.990] within tool (1.000 within task and tool, reported); flagged 46 of 50 violations and 10 of 130 allowed writes; parsed 100%; (iii) + 0.262 [0.007, 0.478] over the reviewer without reasoning (0.656); (ii) +0.219 [−0.020, 0.427] over Claude's in-conversation read-out (0.699). No other model. Spend $0.22 ([released file])

Test	Outcome (verbatim from the record)
State tomography and forecasting (G27) state tomography and forecasting: does the agent's state, estimated from its own answers at earlier steps (Kalman filter, IV system identification, no labels), forecast its next call's violation before the call is proposed? ((i) forecast − prior, lower 95% > 0; (ii) filtered − raw; (iii) calibration)	**(i) FAILS; (ii) no detectable difference; (iii) model misspecified**: on calls after the first step, the forecast from earlier steps ranks the next call at 0.507 against the step-only prior's 0.494 (+0.013 [−0.115, 0.155]); filtered − raw −0.022 [−0.073, 0.030]; NIS/K 0.52 and negative IV-implied noise on 5 of 8 questions: the identified linear dynamics do not fit (they are unstable). Reported: raw pre-call read-out 0.762 and filtered 0.740 within template and tool, but the step index alone scores 0.860 there (G27's episodes end at the first violation). Exploratory, within template, tool and step: raw 0.674 [0.567, 0.776], filtered 0.692 [0.587, 0.801], forecast 0.531 [0.415, 0.657]. Reading: the agent's answers before its call carry information about that call beyond position; earlier steps do not forecast it ([released file], [released file])
The estimated state against the true hidden state (G28) does the state estimated from the agent's answers track its true hidden state? ((i) RSA of the Kalman estimate − raw answers with the true decision-state geometry, lower 95% > 0; (ii) RSA of the forecast, lower 95% > 0)	**PASS ((i), (ii))**: agreement with the true decision-state geometry on 916 steps: raw 0.048, filtered 0.067, forecast 0.116; filtered − raw +0.019 [0.001, 0.038]; forecast 0.116 [0.078, 0.153]. Exploratory position control: step position alone agrees at 0.210; within same-step pairs (41,607) raw 0.158, filtered 0.180, forecast 0.070, so the forecast's agreement is mostly position, while the answers before the call track the true state within a step ([released file])
State tomography replicated on three agents (G27b) state tomography and forecasting replicated on three more open agents ((i) pooled forecast − prior, lower 95% > 0; (ii) pooled filtered − raw; per agent: G28's check against the true state)	**(i) PASS**: pooled over gpt-oss-20b, Qwen3.8 and Muse-Glimmer, the forecast from the agent's answers at earlier steps beats the prior from position alone, on calls after the first step: +0.209 [0.080, 0.317] (G27 had failed this on Gemma-4); (ii) filtered − raw +0.018 [−0.021, 0.062]. Battery sizes: 2,042, 750 and 2,384 steps ([released file])
Live prevention by the estimated state (G29) live prevention by the agent's estimated state, before the call exists ((i) relative reduction in violating episodes, lower 95% > 0; (ii) success difference, lower > −0.03)	**Stopped before any episode outcome** (4 minutes after the job started; only the cut, 4.796, was printed): G27 showed that the identified linear dynamics are unstable and that the step index alone ranks violations, so a gate on the Kalman estimate without a position control could not test what it was meant to. Replaced by G29b
Live prevention by the state before the call (G29b) live prevention by the agent's state read before the call exists, against a position gate and a random gate ((i) pre relative reduction, lower 95% > 0; (iii) pre − position reduction, lower 95% > 0; (ii) success, lower > −0.03)	**(i), (iii) FAIL; (ii) pass**: on Gemma-4 (300 scenarios), the gate on the pre-call read-out did not reduce violating episodes (16.7% → 17.3%; relative reduction −0.04 [−0.30, 0.16]); the position gate reduced them more (13.3%; pre − position −0.24 [−0.50, −0.03]); success +0.023 [−0.007, 0.053]. The pre-call gate reviewed 5.8% of calls, and 1.85% of the calls it held were violations, no more than the random gate (2.8%): at this cut Gemma-4's pre-call read-out (0.67 within a step, exploratory) ranks too weakly to prevent; GPT-6-luna's (0.92, G40) did (G39). The position gate reviewed 32% of calls, so (iii) compared gates of very unequal cost ([released file])
The state before a call, beyond position, on three agents (G30) does the state before a call carry its violation beyond position, and track the true state within a step, on three more agents? ((i) pooled within template x tool x step AUROC of the pre-call read-out, lower 95% > 0.50; (ii) pooled same-step agreement with the true state, lower 95% > 0)	**(i) PASS; (ii) FAIL**: pooled within template x tool x step, the pre-call read-out ranks the coming call's violation at 0.669 [0.594, 0.764] (gpt-oss-20b 0.682, 82 violations in mixed strata; Qwen3.8 0.857, 23; Muse-Glimmer 0.469, 93), confirming Gemma-4's exploratory 0.674 on three more agents; same-step agreement with the true decision-state geometry 0.072 [−0.004, 0.144] ([released file])

Test	Outcome (verbatim from the record)
Repeats against dither: is the within-step effect measurement-limited? (G31) are the within-step effects limited by the measurement? Re-measure with 16 answers per question: repeats (R) against dither over 4 fixed wordings (D) ((i) pooled within template x tool x step AUROC, D16 − (iv), lower 95% > 0; (ii) D16 − resampling (16 rollouts), lower 95% > 0; (iii) same-step agreement with the true state, D16 − (iv), lower 95% > 0)	**(i) PASS; (ii), (iii) FAIL**: pooled over 4 agents (Gemma-4 289 steps, gpt-oss-20b 136, Qwen3.8 41, Muse-Glimmer 226), within template x tool x step, the pre-call read-out with 16 dithered answers per question ranks the coming violation at 0.734 against 0.651 with G27's 4 answers ((i) +0.082 [0.001, 0.147]); 16 repeats of one wording do as well (0.728; resampling (16 rollouts) − (iv) +0.076 [0.020, 0.123]; (ii) D16 − resampling (16 rollouts) +0.006 [−0.064, 0.066]): the within-step effects are limited by the number of answers, and on open agents dither adds nothing over repeats. Same-step agreement with the true state D16 − (iv) +0.053 [−0.014, 0.129] ((iii)). Dither lowers unanimity (Gemma-4 0.87 → 0.58); split-half reliability of the read-out 0.85–0.99 ([released file])
Early warning and the horizon of the state (G31b) early warning and horizon: does the state read before the first call warn of a violation that comes later, and does the information arrive at the call's step? ((i) pooled within template x first-tool AUROC of the first-step read-out for 'violates later', lower 95% > 0.50; (i) pooled AUROC of the read-out before call t minus before call t−1, lower 95% > 0)	**(i) FAIL; (i) PASS**: before the first call, the answers do not warn of a violation that comes later (pooled early-warning AUROC 0.498 [0.405, 0.585]; Gemma-4 0.453, reported); the answers just before a call rank it better than the answers one step earlier (+0.163 [0.029, 0.302]): the deciding information enters at the call's step ([released file])
G31c how long does the state read through the API remember, and is the noise G27's filter assumed right? Label-free ((i) pooled lag-1 autocorrelation of the answer angles within template x step, lower 95% > 0; (ii) lag-1 − lag-3, lower 95% > 0; (iii) within-cell variance / nominal noise 1/(m + 1/2), upper 95% < 1)	**PASS ((i), (ii), (iii))**: the state read through the API has a short memory: pooled within-episode autocorrelation 0.132 [0.090, 0.171] at one step, 0.042 at two, 0.013 at three (decay 0.119 [0.075, 0.155]); the angles' variance is 0.31 [0.29, 0.34] of the nominal noise 1/(m + 1/2) that G27's filter assumed. Together: forecasts must use the last step or two, and a filter must not use the nominal noise. An earlier run of this analysis on gpt-oss-20b alone (a waiter fired before the other batteries existed; [released file]) is kept as a partial file and is not this result ([released file])
A label-free signal says where the read-out works (G32) does a label-free quantity from the agent's own answers say where the read-out works? ((i) Spearman over (target, stratum) cells between the read-out's SNR beyond sampling noise and its AUROC, lower 95% > 0; (ii) AUROC of cells with SNR > 0 minus SNR ≤ 0, lower 95% > 0)	**PASS ((i), (ii))**: Spearman 0.710 [0.436, 0.870]; cells with SNR > 0 (23) average AUROC 0.961, cells with SNR ≤ 0 (6) 0.678, difference +0.282 [0.169, 0.406]. Partial Spearman given cell size and base rate 0.677; raw variance alone 0.669; 82.8% of cells within the noise ceiling + 0.05. Per target, Claude Haiku 5.5 has the lowest SNR (tau2-bench −0.48, AUROC 0.705; CAPE-Bench −0.18): its 4 answers agree on 96–97% of questions, so each question gives about one bit ([released file])
The closed agent's answers, dithered (G33) the closed agent's own answers, dithered: 4 fixed wordings per question on tau2-bench airline ((i) within-tool AUROC D16 − G18's 4-answer read-out, lower 95% > 0; (ii) D16 − resampling (16 rollouts), lower 95% > 0)	**FAIL ((i), (ii))**: dithered wordings changed the measurement as predicted (unanimity 0.958 → 0.781; label-free SNR −0.48 → 0.73) but did not raise the ranking: within-tool AUROC D16 0.720 [0.573, 0.824], G18's 4 answers 0.705, (iv) 0.690, resampling (16 rollouts) 0.686; (i) D16 − G18_R4 +0.015 [−0.089, 0.104]; (ii) D16 − resampling (16 rollouts) +0.034 [−0.088, 0.157]. On this benchmark the closed agent's read-out is not limited by the quantized answers; 16 repeats also raised the nominal SNR (0.88) without raising AUROC, so a positive SNR there does not imply a better ranking. Cost $11.77 ([released file])

Test	Outcome (verbatim from the record)
Triangulation: the closed model's own hidden geometry (G34) triangulation: does a closed model's own answer geometry reconstruct its own unseen hidden geometry? ((i) leave-one-open-model-out mean absolute error of the predicted own agreement < 0.10; (ii) observed inside the predicted interval for $\geq$ 6 of 8; (i) the closed model's triangulated own agreement, lower 95% > 0)	**PASS ((i), (ii), (i))**: leave-one-out error 0.061 [0.051, 0.070]; 7 of 8 inside the interval (miss: gpt-oss-20b, whose hidden geometry is the least shared, loading 0.58); Claude Haiku 5.5's own answers against its own hidden geometry, triangulated: 0.495 [0.437, 0.554], within the open models' own range (0.48–0.62). Reported: on (vi)'s published matrices (1,000 contexts of 10 kinds, 88 exact answers) the same leave-one-out is less accurate (error 0.114; 4 of 8 inside) ([released file])
Does the monitor come from the reconstructed state? (G35) does the monitor come from the reconstructed state? ((i) Spearman between the read-out and the hidden state's violation coordinate within template and label, lower 95% > 0; (ii) answer vs decision-state geometry over same-template, same-label pairs, lower 95% > 0; (iii) share of the read-out's AUROC lost when the part the hidden coordinate predicts is removed, lower 95% > 0)	**(iii) PASS; (i), (ii) FAIL**: 20% [13%, 27%] of the read-out's AUROC above chance runs through the hidden state's violation coordinate; within a template and label the 4-answer read-out does not follow that coordinate ((i) 0.044 [-0.008, 0.115]; (ii) -0.011 [-0.058, 0.027]). Within such a cell the answers are nearly unanimous, so the read-out barely varies ([released file])
With dither, does the read-out follow the hidden state? (G35b) with a better measurement, does the read-out follow the hidden state's violation coordinate beyond the label? ((i) "Interrogation state, Othello" of the dithered read-out D16 within template x tool x step x label, lower 95% > 0; (ii) "Interrogation state, Othello"(D16) $-$ "Interrogation state, Othello"((iv)), lower 95% > 0)	**FAIL ((i), (ii))**: even with dithered answers, within template x tool x step x label the read-out does not follow the hidden state's violation coordinate ("Interrogation state, Othello" of D16 -0.077 [-0.250, 0.195]; D16 $-$ (iv) -0.041 [-0.274, 0.201]); cells are small (28–217 steps with a state per agent) ([released file])
Triangulation at the agent's decision (G36) triangulation at the agent's decision: how well do an agent's own answers at its calls reconstruct its own decision-state geometry? ((i) leave-one-open-agent-out mean absolute error < 0.10; (ii) inside the interval for $\geq$ 3 of 4; (i) Claude Haiku 5.5's triangulated own agreement, lower 95% > 0)	**(i), (i) PASS; (ii) FAIL**: at the agent's decision, an agent's own 8 policy answers agree only weakly with its own decision-state geometry over all pairs of calls (observed 0.010, 0.039, 0.054, 0.161 for Gemma-4, gpt-oss-20b, Qwen3.8, Muse-Glimmer); the triangulation predicts these within 0.045 [0.031, 0.065] on average ((i)) but inside its interval for only 1 of 4 ((ii)); Claude Haiku 5.5's estimate 0.103 [0.085, 0.122] ((i)). Eight policy questions measure a narrow, violation-relevant slice of a rich decision state; the read-out uses that slice (G35: 20% of its power runs through the hidden violation coordinate), while the broad geometry is reconstructed with many generic questions ((i), G34) ([released file])
The closed agent's state before its call (G37) the closed agent's state before its call exists, on tau2-bench airline ((i) within-tool AUROC of the pre-call read-out of its own answers about its next action, lower 95% > 0.50; (ii) dither (iv) $-$ (iv) at equal budget, lower 95% > 0)	**FAIL ((i), (ii))** (run under the recorded deviation, [released file]: (iv) on all 360 writes, the dither arm on 288 before the fixed credit ran out): before its write exists, Claude Haiku 5.5's answers about its next action do not rank the coming violation (within-tool AUROC 0.536 [0.434, 0.682]; at the call, G18: 0.705; pre $-$ at call -0.169 [-0.289, -0.027]). On the 288 writes with both arms (33 violations), dither 0.652 vs repeats 0.525, (ii) +0.127 [-0.045, 0.253]. Unanimity before the call 0.96. Cost about $1.9 ([released file])

Test	Outcome (verbatim from the record)
A second closed agent, at its call and before it (G38) a second closed agent (GPT-6-luna) read through its own API at its call and before it, on CAPE-Bench ((i) within template x tool AUROC of the at-call read-out, lower 95% > 0.50; (i) of the pre-call read-out, lower 95% > 0.50)	**PASS ((i), (i))**: GPT-6-luna's own answers rank its violations within template x tool at the call 0.979 [0.946, 0.998] and before the call exists 0.765 [0.650, 0.909] (560 calls, 66 violations, 216 scenarios; cost $1.14). Unanimity 0.85 at the call, 0.77 before it; at the call it abstained on about half the rule questions it could not check ("I can't determine..."), which take the neutral angle. Exploratory position control: the call's position alone ranks at 0.763 within template x tool, the same as (i); within template x tool x position (12 strata with both classes, 27 violations) the pre-call read-out ranks at 0.927 [0.828, 0.989] and the at-call read-out at 0.964 ([released file])
Live prevention on a closed agent before the call (G39) live prevention on a closed agent (GPT-6-luna) by its state read before the call exists, against a position gate ((i) relative reduction of violating episodes, pre vs none, lower 95% > 0; (iii) pre − position, lower 95% > 0; (ii) success, lower > −0.05; on the transcript-decidable templates)	**(i) PASS; (iii), (ii) FAIL**: on the transcript-decidable templates (84 scenarios), the gate on GPT-6-luna's pre-call state cut violating episodes from 26.2% to 9.5% (relative reduction 0.636 [0.250, 0.875]); the position gate cut them to 15.5% (0.409 [0.000, 0.688]); pre − position +0.227 [−0.190, 0.625] ((iii) fails: not distinguishable from position at this power); success +0.012 [−0.083, 0.107] ((ii) fails: the lower bound is below −0.05). Reviews per episode: pre 1.36, position 0.92. Unchecked-fact template (tp_campaign_test, 42 scenarios): 95.2% → 97.6%, no reduction, as predicted. All 378 episodes ran; cost $1.13 ([released file])
The pre-call gate against a matched position gate (G39b) the closed agent's pre-call gate against a position gate of matched review rate ((iii) relative reduction pre − position, lower 95% > 0; (i) pre vs none, lower 95% > 0; (ii) success, lower > −0.05)	**PASS ((iii), (i), (ii))**: at a matched review rate (pre 1.48, position 1.52 reviews per episode), on 84 decidable scenarios x 3 fresh seeds (252 runs per arm, all complete), the gate on GPT-6-luna's pre-call state cut violating episodes from 31.7% to 7.9% (relative reduction 0.750 [0.605, 0.863]) and the position gate to 17.9% (0.438 [0.256, 0.605]); pre − position +0.313 [0.062, 0.543]; success unchanged (18.7% in both; difference 0.000 [−0.048, 0.048]). Cost $2.94 ([released file])
The relevant directions of the call (G41) read the closed agent's state along the directions its call can violate ((i) within-tool AUROC of the policy-relevant read-out minus the full read-out, dithered answers, lower 95% > 0; (ii) the same on G18's answers)	**FAIL ((i), (ii))**: relevant − full −0.014 [−0.059, 0.038] (dithered) and +0.008 [−0.021, 0.026] (G18's answers); every read-out 0.70–0.72. Diagnosis across G18, G24, G26, G33, G37, G41 (exploratory): answers given from the agent's own conversation stay near 0.70 whatever the measurement (more answers, dither, relevant questions, reasoning on 0.57, before the call 0.54, where the general question is inverted, 0.434), while the same model as an outside reviewer with reasoning reaches 0.918 (G26): the information is in the transcript, and the agent's own-seat answers are committed to its plan ([released file])
The prevention law for pre-call gates (G42) does the prevention law predict a live pre-call gate on a closed agent? ((i) |G39b's pre reduction − offline share 0.750| ≤ 0.15; (ii) |G39b's position reduction − 0.167| ≤ 0.15)	**(i) PASS; (ii) FAIL**: the offline share of violating calls held predicted the pre-call gate's live reduction exactly (predicted 0.750, observed 0.750 [0.605, 0.863]; error 0.000). It under-predicted the position gate (predicted 0.167, observed 0.438 [0.256, 0.605]; error 0.271), as in G39 (0.125 vs 0.409): the law does not carry to a gate on turn index for this agent ([released file])
A broader battery at the decision (G43) does a broader battery of the agent's own answers (32 situation questions) reconstruct its decision state? ((i) pooled Spearman with the decision-state geometry, 32 questions − 8 policy questions, lower 95% > 0; (ii) 32 questions, lower 95% > 0.2)	PENDING

Test	Outcome (verbatim from the record)
Self against other forecast (G44) does an agent's own state forecast its next violation better than another model reading the same conversation? ((i) GPT-6-luna, within templateltool, own − other pre-call AUROC, lower 95% > 0; (ii) three open agents pooled, within template x tool x step, lower 95% > 0)	**(i) PASS; (ii) FAIL**: before its call exists, GPT-6-luna's own answers about its next action forecast its next violation better than Gemma-4 answering the same questions in its seat on the same conversations: within templateltool 0.840 vs 0.728, own − other +0.111 [0.041, 0.185] (402 calls, 27 violations); within templateltoollposition 0.923 vs 0.847, +0.076 [−0.017, 0.230]. Open agents, pooled within template x tool x step, own − other −0.030 [−0.159, 0.082]: Qwen3.8 own 0.857 vs other 0.643; gpt-oss-20b 0.682 vs 0.841; Muse-Glimmer 0.468 vs 0.613 ([released file])
Is the self advantage specific to forecasting? (G44b) is the agent's advantage over another reader specific to forecasting? ((i) pooled over three open agents: (own − other) before the call − (own − other) at the call, lower 95% > 0)	**FAIL ((i))**: pooled over the three open agents, (own − other) before the call minus at the call −0.045 [−0.178, 0.082]: Qwen3.8 +0.152 (at the call +0.062, before +0.214), gpt-oss-20b −0.182 (+0.023, −0.159), Muse-Glimmer −0.106 (−0.040, −0.145). The agent-specific forecasting advantage holds for the closed agent (G44 (i)) and for Qwen3.8, not for gpt-oss-20b or Muse-Glimmer, whose own pre-call answers rank weakly ([released file])
A closed agent's pre-call state beyond position, confirmed (G40) confirm on fresh episodes that a closed agent's state before its call ranks the coming violation beyond position ((i) within template x tool x position AUROC of the pre-call read-out, lower 95% > 0.50; (ii) within template x tool, lower 95% > 0.50)	**PASS ((i), (ii))**: on 252 fresh episodes (1,047 calls, 68 violations), GPT-6-luna's answers about its next action, read before the call exists, rank the coming violation at 0.923 [0.811, 0.992] within template x tool x position (9 strata with both classes, 27 violations; G38's exploratory value was 0.927) and at 0.840 [0.732, 0.946] within template x tool, where position alone ranks at 0.777. Cost $2.06 ([released file])

Correction to one recorded cause. The record keeps the first wording of the canonical-action monitor's cause and adds this dated correction (an exploratory diagnosis; no endpoint changed).

- The "Canonical-action monitor" row first said that the message body "carries the leaked draft", so free text is payload. Checking the data showed this is wrong:
- **What decides the label.** In tp_campaign_test (81 of the 82 attacked messages), the violation is the recipient: a test send to a list whose members are thousands of customers. That fact appears only in a `list-info` result, and neither closed agent ever called `list-info`. CAPE's checker labels the send by its recipient, whatever the body says.
- **What the attacker did.** The attacker's best rewrites dropped the draft from the body in 53 of 82 ("Adaptive attacker") and 55 of 82 ("Training against the attack") messages, and the checker still labelled every one a violation.
- **Training coverage.** tp_campaign_test is absent from the 23 families of Gemma's training steps. Among open agents, only Qwen has violations of it (7).
- **The cause.** The shipped reader caught these sends from an incidental cue (a file's content copied into a message) that it learned on other families. The attacker can remove that cue without changing the label. The canonical form removes it too, and the decisive field (the list) was never learned.
- **A theorem (paper, "a ceiling under rewording").** When an attacker can give a violation the free text of safe actions with the same decisive fields, no monitor's attacked operating point beats the clean ROC of the best monitor of (transcript, decisive fields). The canonical reader's clean catch (51.5% / 59.1%) is our estimate of that ceiling. "Training against the attack"'s 59.7% after the attack and "Adaptive attacker"'s 29.1% are consistent with it.
- **The headline without this family.** The shipped reader's exact-budget catch at 5% is 92.3% (Claude, 26 violations) and 96.3% (GPT, 27 violations), against 94.1% and 98.5% with it.