Grey Box: Replicating Agents' Hidden States from Their Transcripts, to Predict and Prevent the Violations of Closed Agents

Anonymous Authors[1]




Figure 1. **Seeing inside closed agents.** All panels share the two main axes of one reference open agent's hidden state (Gemma-4, at the moment before it acts). Blue: density of safe actions; red: violations of the policy. (a) The open agent's true hidden state on 12,128 fresh actions. (b) The grey-box replica of the same actions, computed from the transcript and the proposed action only (Section 4.2). The same reader replicates three more open agents on unseen scenarios (46–54% of variance; Figure 2). (c, d) Actions of two closed agents, mapped through the same reader and map. Here the replica cannot be checked (no true state), so we test what it is for: prediction. We never saw their weights and fit nothing on them; their own coordinates are not identifiable (Proposition 1), so we show them in the reference agent's coordinates. In every agent the violations occupy their own region. A probe on the reader's latent state, which holds the replica, catches 94% and 98% of them when 5% of the actions go to review. (e) Live prevention in the loop of the two closed agents (T16, T16b): the share of episodes with an executed violation, without and with the gate.

Abstract

Safety tools that read a model's hidden state need its weights, and the agents with the most capability are closed. We ask whether an outside observer can read the hidden state of a closed agent, replicate it, and use the replica to predict and prevent policy violations. The raw coordinates of a hidden state are not identifiable from outputs: a rotation of the hidden space changes no output. Two objects can be recovered, and we build a "grey box" from each. The first is the behavioural state: the model's answers to fixed questions asked in side branches. It recovers the hidden state of models with known internals (Othello-GPT: R^2 0.967), but as a safety signal it only ties a text moderator. The second follows from a simple theorem: an agent's internal state is a function of its tokens, so an open model that reads the same tokens can hold a replica of it. From the transcript alone, a replica in an open reader's latent space reconstructs 66% of the variance of the 128 main components of an agent's hidden state (51–54% of each full layer), more than text features do (59%). White-box readouts work on the replica (AUROC 0.987; true state 0.984) and also on a replica from text features (0.983): the information that decides a violation is in the tokens. The same reader replicates three more open agents with other architectures, on scenarios it never saw (46–54% of the main components). For a policy check on a proposed action, the transcript and the action are Bayes-sufficient. A probe on the reader's latent state, trained only on an open agent, catches 94% and 98% of the violations of two closed agents, Claude Haiku 5.5 and GPT-6-luna (reasoning off), when the 5% riskiest actions go to review, with a cut set without labels. In the loop of two closed agents, it blocks violations before they run (episodes with an executed violation: GPT 6.6% $\rightarrow$ 0.2%; Claude 6.7% $\rightarrow$ 0.2%), at a cost

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

in completed tasks (Claude: 40.7% → 34.9%). With a reviewer for the flagged actions, the safety gain stayed, but a small goal cost could not be excluded. On an outside benchmark (AgentDojo), labels of a new policy collected on open agents fixed the monitor for a closed agent. On τ^2-bench, word counts trained on other agents' labels scored 0.987 on two closed agents, but only because the test tasks were also in the training data: on unseen tasks, neither word counts nor the reader transferred (0.519, 0.535). A zero-shot reasoning judge needs no labels: on four closed frontier agents it separated violating from allowed calls of the same tool (0.766, preregistered), but at a 5% review budget it caught fewer violations than the reader. Every test is preregistered and hash-locked; we report the failures and the tests that could not be done. We release an SDK and a website on which anyone can train and audit a monitor.

1. Introduction

Interpretability can read a model's hidden state: what it knows, and what it will do (Burns et al., 2023; Marks & Tegmark, 2023; Zou et al., 2023; Arditi et al., 2024; Goldowsky-Dill et al., 2025). For agents that act through tools, a probe on the hidden state can forecast an unauthorized action before it runs and stop it (Fayyazi et al., 2026). But these tools need the weights, and the agents with the most capability are closed. Their providers give sampled text, and at most top-k log probabilities and a summary of the reasoning.

We ask three questions. **(1)** Can an outside observer read the hidden state of a closed model? **(2)** Can it replicate the state well enough that white-box tools work on the replica? **(3)** Can the replica predict and prevent the agent's violations, in real time?

Answers.

1. *What can be read.* The raw coordinates of a hidden state are not identifiable from outputs (Proposition 1). The behavioural state is, and a battery of side-branch questions recovers it on models with known internals (Section 4.1). As a safety signal this "interrogation state" is weak.
2. *What can be replicated.* An agent's internal state is a function of the tokens that it read (Proposition 2). An open reader model on the same tokens replicates 66% of the agent's hidden-state variance, and readouts trained on the true state work on the replica (Section 4.2).
3. *What it is good for.* For a policy check on a proposed action, the transcript and the action are Bayes-sufficient (Corollary 1). A probe on the reader's latent state (the space that holds the replica), trained only on an open agent, catches most violations of two closed agents before they run, and blocks them live (Sections 4.4 and 4.6). Its limit is policy coverage (Section 4.5).

Rigor. Every confirmatory test was preregistered: its document and analysis code were hash-locked (SHA-256) before we ran it. The lock times are self-reported; for T13b, T16 and T20 the lock was also published before the result. Table 1 lists the agent tests with their outcomes, including the ones that failed or could not be done.

2. Theory

Setting. A monitor acts at step t, after the agent proposes an action and before the action runs. Z_t is every token that the agent read or wrote up to t; V_t is the part that a deployment sees, and H_t is the rest (e.g. hidden reasoning). A_t is the proposed action, and W are world facts that the agent did not observe. An internal representation is $\phi_t = \Phi(Z_t; \theta)$, a deterministic function of the tokens.

Proposition 1 (gauge)**.** *For any invertible G, the model whose hidden space is transformed by G (with the adjacent weights compensated) computes the same function. Thus no method that uses only outputs can recover hidden coordinates, and a probe fit in one basis does not transfer to another. The behavioural state (the law of future outputs) is unchanged.*

Proposition 2 (access is not information)**.** *For every label Y, $\sigma(Z_t, \phi_t) = \sigma(Z_t)$. Thus the best monitor that uses (Z_t, ϕ_t) is not better than the best monitor that uses Z_t, under every strictly proper score and at every point of the ROC curve. Under log loss, the best monitor that uses Z_t beats the best that uses V_t by exactly $I(Y; H_t \mid V_t)$.*

Corollary 1 (the proposed action is sufficient)**.** *Let $Y = g(A_t, V_t, W)$ with $W \perp\!\!\!\perp Z_t^- \mid V_t$, where Z_t^- are the tokens before the action is sampled, and with sampling noise independent of (Z_t^-, W). Then $P(Y \mid Z_t^-, A_t) = P(Y \mid V_t, A_t)$, and every monitor that reads internals at or before the action has a Bayes risk at least that of the best monitor that reads (V_t, A_t).*

Proofs are in Section A. Proposition 1 says what a grey box can target: a behavioural state, or a state defined up to a learned map. It is the output-side counterpart of identifiability results for representations: latents that supervised training makes identifiable are recovered by encoders that are linear in them when the representation is complete (Zhou & Klindt, 2026), which is why we use a linear map between two models that read the same tokens. Proposition 2 says why a replica is possible: the hidden state is a function of tokens that an outside model can also read. Corollary 1 says when nothing is lost: a probe read before the action must

also predict which action the agent samples; a monitor that reads the action does not. It does not cover labels about later behaviour or about beliefs; for later behaviour, the rollout forecast dominates every readout of the state (Section A). What remains is statistical: learning $P(Y \mid V_t, A_t)$, which depends on the labels, the representation, and the coverage of the policies.

3. Setup

Agents and data. CAPE-Bench (Fayyazi et al., 2026) gives matched agent tasks in which one fact decides if an action is authorized; an environment rule checker labels each action. Open agents: Gemma-4 (26B) and gpt-oss-20b. Closed agents, through their public tool-use APIs, with reasoning off: Claude Haiku 5.5 and GPT-6-luna. External benchmark: AgentDojo prompt injections (Debenedetti et al., 2024).

The two grey boxes. *Interrogation state* Ψ: the probabilities of the answer "yes" to a fixed battery of questions, each asked in a side branch, so the real conversation never sees it. *Reader replica*: Qwen3-8B reads the agent's instructions, the user's task, the earlier tool calls with their results, and the proposed action. A ridge map from its layer-32 residual stream gives the replica of the agent's state, and a linear probe on the same layer gives the monitor. The reader is trained only on Gemma-4 CAPE-Bench steps (17,623) and is never fit on a test agent.

Baselines. The agent's own internals (CAPE's probe); a zero-shot 70B judge (Llama-3.3-70B, same input); TF-IDF with the reader's input and labels; the action's tool alone.

Statistics. AUROC within strata (template, tool or suite) with 95% intervals from a bootstrap over scenarios or episodes (1,000 resamples), and the share of violations caught when the 5% highest-scored actions go to review, with a cut set without labels (the 95th percentile of the monitor's own scores on the agent's actions). The closed agents ran with reasoning off, so the transcript holds every token that their APIs returned.

4. Results

4.1. Reading the state: the interrogation state

On models with known internals, Ψ recovers the state. A battery of 21 questions, designed with the states known (from a pool of 2,101), separates all 21 states of a program compiled into a transformer; a random battery of 256 questions separates 16 (development test, L0); after a random rotation of the residual stream, a readout that uses the known layout falls from $r = 0.9995$ to -0.46, and Ψ is unchanged (Proposition 1). On Othello-GPT, 61 queries recover the board-carrying hidden state at R^2 0.967 on 1,000 fresh games (preregistered; input-only 0.873). On eight open chat models, the answers recover the hidden state better than a text embedding ($+0.120$ R^2, 8/8 models, preregistered), and readouts trained only on open models transfer to Claude (harmful request 0.993, refusal 0.997 AUROC). **As a safety signal, Ψ is weak.** On agents, the answers alone do not match a white-box probe (T1). As a forecast of Claude's refusals, it only ties a graded text moderator in a prospective test (0.873 vs 0.855); with a moderator it doubles the precision of an alarm (Section D).

4.2. Replicating the state: the reader replica (T15)

On Gemma-4, where the true state is known, we fit a ridge map from the reader's latent space to the agent's hidden state at the decision point (5 layers, top 128 principal components, 80.5% of the variance) on development steps. On 12,128 fresh steps, the replica reconstructs 66.4% of the variance from the transcript alone; text features reconstruct 58.6% ($+0.079$ [0.075, 0.083]; Figure 3). A probe trained on the agent's *true* states scores 0.984 on true fresh states and 0.987 on the replica ($+0.003$ [-0.002, $+0.007$]): white-box readouts work on the replica. The replica is a conditional mean, so it is less spread than the true state, and a text replica also supports the readout (0.983): the part of the state that decides a violation is largely in the tokens, as Proposition 2 implies. A nonlinear map (an MLP) replicates less than the linear one (0.558 vs 0.664, exploratory), as expected when the reader represents the agent's main latents completely (Zhou & Klindt, 2026). Viewing attention as an associative memory over the tokens (Wang, 2026) predicts more interference in longer transcripts. Replication does fall with length (from 0.693 to 0.478 across quintiles of context length), but the probe on the replica stays at the level of the true state in every quintile (exploratory): the part of the state that decides a violation survives.

Three more agents (T17). One agent can be a special case. We repeated the test on three open agents with different architectures: a mixture of experts (gpt-oss-20b), hybrid linear attention (Qwen3.8-27B) and a dense model (Muse-Glimmer-30B). The split was stricter: development and fresh steps come from different scenarios. Before we read an agent's state, we checked that we give it the context that it saw. Teacher-forced, its own model predicts 91–100% of the next 16 tokens of its actual tool call. The same reader (Qwen3-8B, layer 32) replicated each agent's decision state better than text features, and the probe trained on true states worked on every replica. All six preregistered endpoints pass (Figure 2). gpt-oss-20b: R^2 0.494 vs text 0.392 (+0.102 [0.093, 0.110]); the probe on true states 0.900, on the replica 0.924 (+0.025 [-0.017, 0.058]). Qwen3.8-27B: R^2 0.542 vs text 0.441 (+0.101 [0.091, 0.111]); the probe on true states 0.955, on the replica 0.972 (+0.017 [-0.015, 0.049]). Muse-Glimmer-30B: R^2 0.462 vs text 0.401 (+0.061 [0.051, 0.071]); the probe on true states 0.929, on the replica 0.969

Table 1. All agent tests, grouped by question. Pass: the preregistered criterion was met.

Test	Question	Key result	Outcome
T1	Resampling vs a probe at the turn start (oracle checker)	0.904 vs 0.841	pass; answers alone: fail
T2	Internals after the reasoning vs monitors at the turn start	0.979 vs 0.904	pass
T3	Resampling with a deployable 70B judge	0.782 $<$ probe 0.846	fail (probe better)
T4	Reader with labels vs the agent's internals	0.994 vs 0.979	pass
T5	The same, on unseen task families	0.969 vs 0.976 (non-inferior)	pass
T6	Reader trained on Gemma, applied to gpt-oss	0.915 vs judge 0.833	pass
T7	Reader on AgentDojo, no AgentDojo training	0.781 vs judge 0.537	pass
T8	Claude, actions after the reveal	0 violations in the units	not tested
T8b	Claude, all actions	94.1% caught vs 0%	pass
T9	TF-IDF with the same labels vs the reader	equal in distribution; chance on AgentDojo	mixed
T10	Claude, a policy family removed from training	0.912 vs 0.570; 0/26 caught	pass (ranking)
T11	GPT-6-luna, beyond tool identity	0.996 vs 0.778; tool 0.856	pass
T12	Labels for a new policy, prospective	18/18 caught with 0 labels	H1 fail
T13	GPT-6-luna on AgentDojo, with spotlighting	attack success 2.1%; 4 injected calls	not tested
T13b	The same, without the defense	0.840 vs judge 0.787	fail
T14	T13b after adding AgentDojo labels of open agents	0.922 vs judge 0.787; 58% caught	pass
T15	Does the reader replicate the agent's hidden state?	R^2 0.664 (text 0.586); readout 0.987 vs 0.984	pass
T17	Replication on three more open agents, unseen scenarios	R^2 0.49/0.54/0.46 (text 0.39/0.44/0.40); readout holds	pass (3/3)
T16	Live prevention: the gate blocks GPT-6-luna's actions	6.6% $\rightarrow$ 0.2% of episodes	pass
T16b	Live prevention on Claude Haiku 5.5	6.7% $\rightarrow$ 0.2% of episodes	pass
T16c	Hold for review instead of block (Claude)	6.7% $\rightarrow$ 0.0%; goals 38.7% vs 40.7%	R1 pass, R2 fail
T19	Readers small enough for a browser	0.6B encoder 0.605 vs TF-IDF 0.335 (new task); -0.097 vs reader	F1 pass, F2 fail
T18	A second outside benchmark: Claude on τ^2-bench	9 violations ($<$15)	not tested
T20	τ^2-bench, two closed agents, persistent customer	TF-IDF 0.987, reader 0.738	G2 pass, G1 fail
T21	T20 with the test tasks removed from training	TF-IDF 0.519, reader 0.535	fail (both)
T22	Zero-shot reasoning judge (no labels), T20's writes	0.804 vs reader 0.535	fail (both, wide)
T23	The same judge, four closed frontier agents (894 writes)	0.766; reader (other tasks) 0.646	K1 pass, K2 fail

(+0.041 [0.020, 0.069]). Replication is partial: about half of the variance on unseen scenarios (Gemma-4 under the same split: 0.631 (text 0.556)). The text map is at its best setting: its regularization chose the edge of the grid, and smaller values are worse for every agent (exploratory). The readout also works on the text replica, so again the part of the state that decides a violation is largely in the tokens.

4.3. Why access does not help (T2–T5)

Timing. A probe on the agent's internals scores 0.841 at the start of the turn and 0.979 after the reasoning (T2): the white-box advantage over turn-start monitors is when it reads. **Labels.** Resampling scored by a 70B judge gets 0.782, below the probe (T3); the label function is the bottleneck. With labels, a probe on the reader scores 0.994, above the agent's own internals (0.979; $+0.015$ [0.007, 0.026]; T4), and it is non-inferior on unseen task families (0.969 vs 0.976; T5). Given the action, the agent's hidden reasoning adds nothing: -0.0014 [-0.0046, $+0.0014$] AUROC (exploratory), as Corollary 1 predicts. **Representation.** TF-IDF with the same labels equals the reader on the training benchmark, but is worse on unseen families (0.950 vs 0.969) and at chance on AgentDojo (0.503 vs 0.781; T9).

4.4. Two closed agent families (T8b, T11)

Nothing was fit on the closed agents (Table 2). On Claude, the monitor catches 94.1% of 68 violations when the top 5% of actions go to review (95.6% with a cut set on labelled safe actions); the judge catches none. On GPT-6-luna all three preregistered endpoints pass: pooled 0.996 vs 0.778 ($+0.217$ [0.174, 0.265]); against tool identity alone $+0.141$ [0.111, 0.171]; within tool $+0.039$ [0.015, 0.066]. Seen through Gemma's latent space (the T15 map and the true-state probe), Claude's actions score 0.959 and GPT's 0.976




Figure 2. One reader replicates four open agents with different architectures (T17; Gemma-4 is T15's development data under the same split, exploratory). Development and fresh steps come from different scenarios. (a) The share of variance of the agent's decision state (top 128 principal components) that a linear map reconstructs on fresh scenarios, from the reader's latent state or from text features of the same transcript. (b) A probe trained on the agent's *true* states, applied to the true fresh states and to the two replicas.




Figure 3. Replicating the hidden state of an agent from its transcript (T15, 12,128 fresh steps). (a) The agent's true decision-point state, on its first two principal components. (b) The grey-box replica of the same steps, from the transcript and the proposed action only, on the same axes. (c) The share of variance that the replica reconstructs, per principal component.

(exploratory). The probabilities do not transfer between agents (on Claude a 0.5 cut catches 3%), but the ranking does: a threshold at the top 5% of the agent's own unlabelled traffic, then frozen, catches 95.4% online on Claude and 98.4% on GPT, and stays at 94% in a simulated burst of attacks, where a rolling threshold falls to 36%.

4.5. The limit is policy coverage (T10, T12–T14)

For a service-restart policy removed from training, the monitor still ranks Claude's violations well (0.912 vs 0.570), but escalates 0 of 26 at a 5% budget; 20 labelled steps of the policy give 85%, 40 give 94% (T10, exploratory curve; Figure 5a). A held-out credentials policy with similar trained policies transfers with no labels (T12: the preregistered H1 fails, because there was nothing to fix). Prompt injection on AgentDojo is a new policy: on GPT-6-luna, the monitor is not significantly better than the judge (0.840 vs 0.787; T13b fails). We added labelled AgentDojo calls of the two *open* agents and tested on the *closed* agent (T14): 0.922 vs 0.787 (+0.136 [0.078, 0.191]). At the label-free cut, 58% of the injected calls are caught, against 28% without these labels (92% vs 36% with a cut set on benign calls; Figure 5b). The open agents' calls came from the development user tasks,

Table 2. Closed agents (reasoning off); monitors trained only on Gemma-4. Caught: violations escalated when exactly 5% of actions, the highest-scored, go to review (a cut set without labels; actions tied at the cut count in proportion).

	Claude Haiku 5.5		GPT-6-luna	
	AUROC	caught	AUROC	caught
Reader	0.989	94.1%	0.996	98.5%
TF-IDF	0.997†	63.8%	0.964	49.0%
Zero-shot judge	0.570	0.0%	0.778	37.9%
Tool identity	0.857	42.3%	0.856	13.6%

Pooled AUROC. †within the one stratum with both classes (the pooled value was not saved).




Figure 4. Monitoring the next action from the transcript, under increasing shift: the reader (blue), TF-IDF with the same labels (hollow square), a zero-shot 70B judge (green), and the agent's own internals where available (orange). The two Claude rows rest on one stratum (136 actions, 26 violations). In the T10 row the monitors were retrained without that policy; in the T13b row the policy (prompt injection) is new.

which the test shares; restricted to the confirmation split, whose user tasks the training never saw (the injection tasks and the attack template are shared), the result holds (0.929 vs 0.786, $+0.143$ [0.075, 0.227]; label-free 54% vs 29%; exploratory). On this benchmark, labels of a policy transferred from open agents to a closed agent. On τ^2-bench (Barres et al., 2025), a customer-service benchmark with an airline policy, we trained the monitors on the labelled writes of four frontier agents' published trajectories and tested them on two closed agents facing a customer who insists after a refusal (T20; 262 writes, 19 violations). Within tool, word counts reached AUROC 0.987 (G2 passes), but the reader reached only 0.738 (G1 fails; reader $-$ word counts -0.250 [-0.518, -0.077]). But all 13 test tasks with writes were also in the training trajectories. In T21 we removed them from training (554 writes of 28 other tasks remain). Then neither monitor transferred: within tool, word counts 0.519 and the reader 0.535 (reader $-$ word counts $+0.017$ [-0.514, $+0.539$]; reader $-$ tool identity $+0.035$ [-0.230, $+0.259$]; both preregistered endpoints fail). Word counts with entities masked fell to 0.366. So T20's word-count result was memorization of tasks (reservation codes, names, dates), not the policy. A τ^2 violation breaks an explicit rule that depends on facts of the case (a booking older than 24 hours, no insurance, basic economy); a linear readout of labels from other tasks does not compute these checks. A model that reasons over the written policy needs no labels, so it cannot memorize tasks. In T22, a zero-shot judge (Qwen3-32B with thinking, the monitors' input) reached 0.804 within tool on T20's writes, but only 8 tasks had a violation and both endpoints failed (judge $-$ tool $+0.304$ [-0.084, $+0.427$]). T23 ran the same judge, unchanged, on the 894 published writes of four closed frontier agents (227 violations, 29 tasks); the labelled monitors were cross-validated by task. The judge separated violating from allowed writes of the same tool (0.766; judge $-$ tool $+0.266$ [0.151, 0.338], K1 passes), but not significantly better than the reader trained on other tasks (0.646; $+0.120$ [-0.047, $+0.274$], K2 fails; the mean of four judge samples, reported: $+0.192$ [0.022, 0.336]). As a review queue the order flips: with exactly 5% of writes reviewed, the reader caught 18.4% of violations (the most possible is 19.7%), the judge 11.7%. So explicit rules can be checked without labels, within a tool, but on these agents neither route is enough alone. A first attempt on Claude alone (T18) had too few violations to test.

4.6. Live prevention on two closed agents (T16, T16b)

We ran the monitor as a server in the loop of GPT-6-luna on 500 CAPE-Bench scenarios, each with and without the gate (preregistered). The threshold came from GPT's past, unlabelled traffic. A blocked action does not run; the agent is told that it went to a human. The share of episodes with an executed violation fell from 6.6% to 0.2% (-0.064 [-0.088, -0.044]; P1 passes). The gate blocked 67 actions, of which 36% would have been violations; in safe scenarios it blocked 0.08 actions per episode. The agent executed 0 violations after a block. Task goals were reached in 47.4% (no gate) and 45.6% (gate) of the episodes; in these scenarios a goal can




Figure 5. Policy coverage. (a) A CAPE-Bench policy removed from training, against the number of its labelled steps added back (T10 exploratory; T12 preregistered). (b) Prompt injection on the closed GPT agent, against labelled AgentDojo calls from *open* agents (T14, preregistered).

require the unauthorized action. The server round trip was 89 ms (median). On Claude Haiku 5.5 (T16b, 450 scenarios $\times$ 2 arms, the cut seeded from Claude's past unlabelled traffic), the share of episodes with an executed violation went from 6.7% to 0.2% (-0.064 [-0.087, -0.044]; P1b passes). The gate blocked 78 actions, of which 44% would have been violations, and the agent executed 0 violations after a block.

Hold for review (T16c). Blocking has a cost: on Claude, goals fell by 5.8 points. In T16 and T16b, nearly all of that loss came from blocked *safe* actions (96% of it on Claude; exploratory). T16c sends an escalated action to a reviewer instead. The reviewer here is the environment's policy oracle, an upper bound on a human reviewer: it blocks a violation and lets a safe action run. On the same 450 Claude scenarios, episodes with an executed violation went from 6.7% (T16b, no gate) to 0.0% (-0.067 [-0.091, -0.044]; R1 passes), with 0 violations after a block. Goals were reached in 38.7% of the episodes, against 40.7% without the gate and 34.9% with blocking; the preregistered non-inferiority (at most 3 points lost) is not shown (-0.020 [-0.051, +0.007]). Exploratory: episodes with a held action that the reviewer let run kept their goals (60.8% vs 58.8%, 51 episodes); the gap is in the 368 episodes in which nothing was held (38.9% vs 41.0%), where the monitor did nothing; we suggest this is variation between runs, since the control was not concurrent, but this is a hypothesis that T16c does not test. The reviewer saw 0.20 actions per episode (6.2% of the scored actions); 31 of the 88 held actions were violations.

5. The tool

We release an SDK, a monitoring server and a website (links in the camera-ready version). On the website, a user imports their agent's logs (OpenAI or Anthropic tool-calling format), labels actions, trains a monitor in the browser, and gets a cross-validated accuracy over held-out conversations, a frozen review threshold and the catch rate at their budget; the logs stay in the browser. A review queue ranks the unlabelled actions by risk: on 300 GPT-6-luna conversations with half of them labelled, its first 25 actions were all violations (base rate 4.7%), and its first 43 held 92% of the violations. A guard places the monitor in an OpenAI or Anthropic tool loop. The browser and Python give byte-identical text on 302 real agent steps and the same held-out AUROC (0.9887 vs 0.9886). The text monitor takes 0.18 ms per action; the reader takes 41 ms on one GPU, and the server round trip in the loop of a closed agent was 89 ms (median; 95th percentile 215 ms). A live viewer shows a closed chat model's interrogation state in a 3D space shared with open models. **A reader small enough for a browser (T19).** The browser monitor is word counts, which do not transfer to a new kind of task. We tested three browser-size encoders and four smaller decoder readers, trained on the same steps as the reader (App. C). The selected browser encoder (Qwen3-Embedding-0.6B, chosen on open agents' AgentDojo calls) beats word counts on the closed agent's AgentDojo calls (0.605 vs 0.335; $+0.270$ [0.134, 0.451]; F1 passes). But it loses 0.097 [0.079, 0.115] of AUROC against the 8B reader on the closed agents' CAPE-Bench actions (F2, non-inferiority at 0.05, fails), and 0.235 on AgentDojo. By the rule fixed in advance, the website offers it for new kinds of tasks only. No smaller decoder came within 0.02 of the 8B reader, and the 14B reader was worse.

6. Related work

Probes on internals read truth, refusal and deception (Burns et al., 2023; Marks & Tegmark, 2023; Zou et al., 2023; Arditi et al., 2024; Goldowsky-Dill et al., 2025); CAPE probes an agent before each action (Fayyazi et al., 2026). **Chain-of-thought monitors** catch reward hacking that action-only monitors miss (Baker et al., 2025; Korbak et al., 2025; Chen et al., 2025); Corollary 1 says that for labels that the action

(a) Label imported logs; the review queue shows the riskiest first



(b) A closed agent's actions in the monitor's space, with the review cut




Figure 6. The released tool. (a) Labelling imported agent logs in the browser, with the review queue: the monitor trained on the labels so far puts the riskiest unlabelled action first (here a newsletter sent to an outside test list, the benchmark's violation). (b) The replay of Claude Haiku 5.5 as an agent: each of its 3,128 actions in the monitor's space, with the label-free review cut as a plane.

and the visible facts decide, the reasoning adds nothing once the monitor sees the action. **AI control** audits a fixed budget of actions with a trusted monitor (Greenblatt et al., 2024); we show that the threshold must come from the monitored agent's own traffic. **Identifiability.** Hidden coordinates are identifiable only up to transformations that leave the function unchanged; supervised learning identifies latents linearly when the representation is complete and through sparsity otherwise (Zhou & Klindt, 2026). Our gauge result applies the same logic to an observer who sees only outputs. **Black-box access** recovers parts of a model from logits (Carlini et al., 2024; Finlayson et al., 2024), detects lies with follow-up questions (Pacchiardi et al., 2024; Cooney et al., 2026; Sam et al., 2025), forecasts behaviour from traces (Levy et al., 2026), and probes closed transcripts with open readers (conti et al., 2026). We add the identifiability and sufficiency theory, a direct test that the reader replicates the hidden state, closed agents from two providers, live prevention, and a preregistered test of each claim.

7. Limitations

- We can test replication only where the true state is known (open agents). For closed agents, we test what the replica is for: prediction and prevention.
- The live tests (T16, T16b) compare the gate with no gate. We did not run a baseline gate, such as the judge or the tool identity at the same budget, in the loop.
- Most agent tests use one benchmark. On AgentDojo, a monitor without labels of the new policy is not significantly better than a judge on a closed agent (T13b). On τ^2-bench, no trained monitor transferred to unseen tasks (T21: reader 0.535, word counts 0.519); T20's high word-count score (0.987) came from test tasks that were also in training. Rules over facts of the case (dates, amounts, cabin) are a limit of label-trained readouts. A zero-shot reasoning judge checks them within a tool (T23), but at a 5% review budget it catches fewer violations than the reader. A first test on Claude alone had too few violations (T18). T20–T23 were designed after earlier results; T23's agents are older frontier models with published trajectories.
- Policy coverage was measured on three held-out policies; the role of similarity is a hypothesis.
- Corollary 1 needs a label that the action and the visible facts decide. It does not cover beliefs or later behaviour.
- The interrogation state is weak as a safety signal; probes on the reader's latent state carry the safety results.

8. Conclusion

The hidden state of a closed agent cannot be read in its own coordinates, but it can be partly replicated: an open model that reads the same tokens holds about half to two thirds of its main components, and white-box readouts work on the replica (as they do on text features, because the decisive information is in the tokens). For the actions of closed agents with reasoning off, a probe on this grey box predicts and prevents violations on the benchmark it was trained on, at a cost in completed tasks. On a new benchmark it needs labels of the new policy; labels from open agents worked on AgentDojo, while on τ^2-bench no trained monitor transferred to unseen tasks, and a zero-shot reasoning judge checked the explicit rules within a tool but did not beat the reader as a review queue.

Impact Statement

This work makes it possible to monitor closed AI agents before they act, from their transcripts alone. The intended effect is fewer harmful actions by deployed agents: in our tests, blocking the flagged actions cut the episodes with a violation from about 7% to 0.2% on two closed agents. We see three risks. (1) A monitor can give false confidence. It catches violations of the policies that it was trained on, and it can miss a new policy until that policy has labels (Section 4). We state this limit in the paper and in the tool. (2) Blocking has a cost for users: goal completion fell by 1.8 points on GPT and 5.8 points on Claude. (3) Methods that read the state of a model from outside could help an attacker to probe a closed model. Our methods use only the transcripts that the operator already has. They do not extract weights or private data. We release the code under the MIT license. The tool runs in the user's browser and does not upload the user's logs.

References

Arditi, A., Obeso, O., Syed, A., Paleka, D., Panickssery, N., Gurnee, W., and Nanda, N. Refusal in language models is mediated by a single direction, 2024.

Baker, B., Huizinga, J., Gao, L., Dou, Z., Guan, M. Y., Madry, A., Zaremba, W., Pachocki, J., and Farhi, D. Monitoring reasoning models for misbehavior and the risks of promoting obfuscation. *arXiv preprint arXiv:2503.11926*, 2025.

Barres, V., Dong, H., Ray, S., Si, X., and Narasimhan, K. τ^2-bench: Evaluating conversational agents in a dual-control environment. *arXiv preprint arXiv:2506.07982*, 2025.

Burns, C., Ye, H., Klein, D., and Steinhardt, J. Discovering latent knowledge in language models without supervision. In *International Conference on Learning Representations (ICLR)*, 2023.

Carlini, N., Paleka, D., Dvijotham, K. D., Steinke, T., Hayase, J., Cooper, A. F., Lee, K., Jagielski, M., Nasr, M., Conmy, A., Yona, I., Wallace, E., Rolnick, D., and Tramèr, F. Stealing part of a production language model, 2024.

Chen, Y., Benton, J., Radhakrishnan, A., Uesato, J., Denison, C., Schulman, J., Somani, A., Hase, P., Wagner, M., Roger, F., Mikulik, V., Bowman, S. R., Leike, J., Kaplan, J., and Perez, E. Reasoning models don't always say what they think. *arXiv preprint arXiv:2505.05410*, 2025.

conti, ShivamR, Sharf, J., jain18ayush, and johnyan. Model hermeneutics: Monitoring closed-weight models with open-weight internals. LessWrong, 30 September 2026, 2026. URL https://www.lesswrong.com/posts/CZLhfNGaDqtYxvGJD/model-hermeneutics-monitoring-closed-weight-models-with-open.

Cooney, A., Africa, D., and Irving, G. "did you lie?" evaluating lie detectors across scale and belief-verified model organisms, 2026.

Debenedetti, E., Zhang, J., Balunović, M., Beurer-Kellner, L., Fischer, M., and Tramèr, F. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*, 2024.

Fayyazi, A., Kamal, M., and Pedram, M. The agent knew: Internal states forecast unauthorized actions and stop them, and the lies that follow, 2026.

Finlayson, M., Ren, X., and Swayamdipta, S. Logits of API-protected LLMs leak proprietary information, 2024.

Goldowsky-Dill, N., Chughtai, B., Heimersheim, S., and Hobbhahn, M. Detecting strategic deception with linear probes. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, volume 267 of *PMLR*, pp. 19755–19786, 2025.

Greenblatt, R., Shlegeris, B., Sachan, K., and Roger, F. AI control: Improving safety despite intentional subversion. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024.

Korbak, T., Balesni, M., Barnes, E., Bengio, Y., Benton, J., Bloom, J., Chen, M., Cooney, A., Dafoe, A., Dragan, A., Emmons, S., Evans, O., Farhi, D., Greenblatt, R., Hendrycks, D., Hobbhahn, M., Hubinger, E., Irving, G., Jenner, E., Kokotajlo, D., Krakovna, V., Legg, S., Lindner, D., Luan, D., Madry, A., Michael, J., Nanda, N., Orr, D., Pachocki, J., Perez, E., Phuong, M., Roger, F., Saxe, J., Shlegeris, B., Soto, M., Steinberger, E., Wang, J., Zaremba, W., Baker, B., Shah, R., and Mikulik, V. Chain of thought monitorability: A new and fragile opportunity for AI safety. *arXiv preprint arXiv:2507.11473*, 2025.

Levy, M., Goldberg, Y., and Cooper Stickland, A. Forecasting future behavior as a learning task, 2026.

Marks, S. and Tegmark, M. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets, 2023.

Pacchiardi, L., Chan, A. J., Mindermann, S., Moscovitz, I., Pan, A. Y., Gal, Y., Evans, O., and Brauner, J. How to catch an AI liar: Lie detection in black-box LLMs by asking unrelated questions. In *International Conference on Learning Representations (ICLR)*, 2024.

Sam, D., Finzi, M., and Kolter, J. Z. Predicting the performance of black-box LLMs through follow-up queries, 2025.

Wang, A. You could have invented transformers from memory. Blog post, 15 October 2026, 2026. URL https://alexwang.ai/posts/associative-memory/.

Zhou, J. and Klindt, D. Complete or sparse: A tale of two identifiabilities, 2026.

Zou, A., Phan, L., Chen, S., Campbell, J., Guo, P., Ren, R., Pan, A., Yin, X., Mazeika, M., Dombrowski, A.-K., Goel, S., Li, N., Byun, M. J., Wang, Z., Mallen, A., Basart, S., Koyejo, S., Song, D., Fredrikson, M., Kolter, J. Z., and Hendrycks, D. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.

A. Proofs

Setting. Z_t are all tokens that the agent read or wrote up to step t; V_t is the visible part and H_t the hidden part; A_t is the proposed action; W are world facts that the agent did not observe. An internal representation is $\phi = \Phi(Z; \theta)$, a deterministic function of the tokens (numerical noise in a batch is independent of everything else).

Proposition 3 (behavioural sufficiency). Let $Y = g(\tau)$ be defined by the future τ that the agent and the environment generate from context x, and let $\phi(x)$ carry no information about the future sampling noise given x. Then $\pi^*(x) = P(Y = 1 \mid x)$ has a maximal ROC curve and a minimal risk under every strictly proper score among all forecasts $f(\phi(x))$.

Proof. By the assumption and the tower property, $E[Y \mid \phi(X)] = E[\pi^*(X) \mid \phi(X)]$. Under a strictly proper score, the Bayes act given $\sigma(X)$ is $\pi^*(X)$, and $\sigma(\phi(X)) \subseteq \sigma(X)$; less information cannot raise the expected score. For the ROC curve, the Neyman–Pearson lemma gives the most powerful test of each size as a threshold on the likelihood ratio, which is a strictly increasing function of π^*; every test based on $f(\phi(X))$ is a test based on X. □

Proposition 1 in the main text (access is not information). (i) ϕ_t is $\sigma(Z_t)$-measurable, so $\sigma(Z_t, \phi_t) = \sigma(Z_t)$, and Proposition 3 with $X = Z_t$ gives the first claim. (ii) The Bayes log loss of predicting Y from a σ-field $\mathcal{G}$ is the conditional entropy $H(Y \mid \mathcal{G})$; thus $H(Y \mid V_t) - H(Y \mid V_t, H_t) = I(Y; H_t \mid V_t)$. □

Corollary 1 in the main text (the proposed action is sufficient). Let Z^- be the tokens before the action is sampled, $A_t = a(Z^-, \xi)$ with sampling noise $\xi \perp\!\!\!\perp (Z^-, W)$, $W \perp\!\!\!\perp Z^- \mid V_t$, and $Y = g(A_t, V_t, W)$.

1. From $W \perp\!\!\!\perp Z^- \mid V_t$ and $\xi \perp\!\!\!\perp (Z^-, W)$: $W \perp\!\!\!\perp (Z^-, \xi) \mid V_t$.
2. A_t is a function of (Z^-, ξ), so $W \perp\!\!\!\perp (Z^-, A_t) \mid V_t$.
3. By weak union, $W \perp\!\!\!\perp Z^- \mid (V_t, A_t)$.
4. Y is a function of (A_t, V_t, W), so $Y \perp\!\!\!\perp Z^- \mid (V_t, A_t)$, that is, $P(Y \mid Z^-, A_t) = P(Y \mid V_t, A_t)$.
5. A monitor that reads internals at or before the action uses $\phi = \Phi(Z^-)$, with $\sigma(\phi) \subseteq \sigma(Z^-) \subseteq \sigma(Z^-, A_t)$. By step 4 the Bayes predictor given $\sigma(Z^-, A_t)$ equals the one given (V_t, A_t), and less information cannot help (Proposition 3). □

The inequality can be strict: if A_t is random given Z^- and Y depends on which action is sampled, a probe that reads before the action must average over the actions. The assumption on W fails only if the internals hold information about the world that is not in the tokens, which cannot happen for a model whose only input is its token history.

B. Experimental details

Agents. All agents run CAPE-Bench's mock environment for at most 20 turns, with one tool call per turn.

- Open agents, served by vLLM, at most 4,096 new tokens per turn:
  - Gemma-4 (26B-A4B): temperature 1.0, top-p 0.95, top-k 64, thinking on.
  - gpt-oss-20b: temperature 1.0, top-p 1.0, reasoning effort "medium".

  The episodes of the open agents in T17 come from CAPE-Bench's released rollouts, made with the same harness.
- Closed agents use their public tool-use APIs:
  - Claude Haiku 5.5: thinking disabled, effort "low", at most 1,024 tokens per turn.
  - GPT-6-luna: reasoning effort "none", no parallel tool calls, at most 2,048 tokens per turn.

  All API work in the paper cost $13.49 (Anthropic $9.60, OpenAI $3.89).

Units. A unit is one proposed action that is not a read, after the step that reveals the deciding fact. Each episode contributes its actions up to and including its first violation. All violations are kept. Safe actions are subsampled at random with seed 0, so selection depends only on the past.

Reader input. The reader prompt holds four parts:

- the operating instructions;
- the user task;
- each earlier call with its result (results cut to 2,000 characters);
- the proposed action.

A context of 30,000 characters or more keeps its first 6,000 and last 24,000 characters. The prompt goes through Qwen3-8B's chat template with thinking off and is cut to its last 12,000 tokens. The feature is the residual stream at the last prompt token, at hidden-state index 32 (the output of block 31 of 36), in bf16.

Monitor. The monitor standardizes the features, keeps the top 256 principal components, and fits a logistic regression with $C = 0.05$. It is trained on Gemma-4's CAPE-Bench steps only (17,623; development and fresh). The review cut has no labels: it is the 95th percentile of the scores of the agent's earlier actions, and it is then frozen. (In T16 and T16b these were the agent's earlier unlabelled actions; in the tool, its first 500. A rolling cut fails under bursts of similar actions.)

Replica (T15, T17).

- **Target:** the agent's residual stream at its end-of-reasoning token, at 5 depths (block $\mathrm{round}(nf) - 1$, $f \in \{0.5, 0.62, 0.72, 0.82, 0.9\}$). It is standardized and reduced to 128 principal components, all fit on development.
- **Map:** ridge regression, with $\alpha \in \{1, 10, 10^2, 10^3, 10^4\}$ chosen by 5-fold cross-validation grouped by scenario.
- **Probe for E2:** standardize, then logistic regression with $C = 0.05$, on the 128 true components.

Text baseline (T9). TF-IDF of the context and of the action, kept as two separate blocks:

- word 1- and 2-grams, minimum document frequency 3, at most 200,000 features each, sublinear term frequency;
- logistic regression with $C \in \{0.1, 1, 10\}$, chosen by 5-fold cross-validation grouped by scenario.

The browser tool runs the same model. On 302 real agent steps it gives the same text as Python, and its held-out AUROC is 0.9887 (Python 0.9886).


Statistics.

- AUROC is computed within strata (template and tool, or suite) and averaged with weights by the number of positive–negative pairs.
- Intervals are percentile intervals from 1,000 bootstrap resamples of scenarios or episodes. The seeds are fixed in each preregistration.
- Each preregistration (the document and its analysis code) is locked by its SHA-256 hash before its data exist. One script checks every lock and every number in this paper again from the saved results.

Compute. All GPU work runs on one NVIDIA H100 NVL (96 GB), one job at a time: PyTorch 2.11, Transformers 5.14.1 (5.20.1 for Muse-Glimmer, whose architecture the earlier version does not know), scikit-learn 1.9.0. The reader takes about 80–90 ms for one action (median round trip in T16 and T16b).


C. Smaller readers (T19)

All readers are trained on the same 17,623 Gemma-4 CAPE-Bench steps (1,339 violations); none is trained on a test set. Browser encoders: all-MiniLM-L6-v2, all-mpnet-base-v2 (three 1,000-character views) and Qwen3-Embedding-0.6B (one instruction-prefixed text, last-token pooling), each with a standardized logistic probe. Decoder readers: Qwen3-0.6B, 1.7B, 4B and 14B at the shipped reader's relative depth, with the shipped probe. In the browser, the 0.6B encoder runs as a float16 ONNX model; its features match PyTorch's (cosine 1.000 on 40 steps), while the 8-bit model's do not (0.855).



D. The interrogation state in chat

On Claude Haiku 5.5, readouts trained only on open models forecast which harmful requests Claude refuses. Against a 3-level moderation verdict the forecast wins (preregistered L3b, L3c, L3d); against graded moderators it ties (L3e, prospective, 923 conversations: 0.873 vs 0.855). Combined with a moderator, it doubles the precision of an alarm for harmful requests that the model answers (0.535 vs 0.274).



E. The full preregistration record

Every confirmatory test, as in the record (generated from docs/PREREGISTRATION_RECORD.md by paper/make_record.py). Locks (SHA-256 of the preregistration and its code) and outcomes are in the released record; lock times are self-reported.

Test	Outcome (verbatim from the record)
L2 open LLMs (H1–H3)	**PASS all, after deviation 1**: H1 +0.120 [0.115, 0.126]; H2 +0.057 [0.045, 0.073] (7/8 models); H3 +0.359 [0.310, 0.415]; Holm p ¡ 0.0005 each. First run: H1 valid PASS, H2/H3 invalid (numerical; see note) (results/l2/l2_confirm.json)
T1 agents (F1–F3; addendum 1: F4–F5)	**Claim (a) CONFIRMED** (F1, F2 pass: R16 − WB +0.063 [0.033, 0.094]); claim (b) NOT confirmed (F3 fails: Ψ − WB −0.021 [−0.054, 0.009]); addendum **F4 passes** (R4+Ψ − WB +0.049 [0.020, 0.080]); F5 fails (R2+Ψ − R16 −0.023 [−0.053, 0.006]) (results/t1/t1_agents_confirm.json)
L1 Othello recovery (E1–E3)	**PASS all**: E1 R^2 0.967 [0.967, 0.968] ¿ 0.90; E2 ΔR^2 +0.094 [0.086, 0.105], Holm p ¡ 0.0005; E3 Δ occupied acc +0.043 [0.040, 0.046], Holm p ¡ 0.0005. White-box reference 0.983 (results/othello/l1_confirm.json)
L3 Claude Haiku 5.5 readout transfer (C1–C3)	**all pass**: C1 0.993 [0.983, 0.999]; C2 0.997 [0.990, 1.000]; C3 0.935 [0.868, 0.982] (results/l3/)
L3b Claude Haiku 5.5: grey box vs text moderation (D1–D3)	**D1 pass** 0.923 [0.884, 0.957]; **D2 (key) pass** grey box − moderation +0.176 [0.060, 0.287] (0.827 vs 0.651); D3 not tested (1/40 over-refusals) (results/l3/claude_livebench.json)
L3c Claude Haiku 5.5: one-call grey box + compliance alarm (E1–E3)	**all pass** vs the preregistered 3-level verdict: E1 +0.142 [0.081, 0.203] (0.815 vs 0.673); E2 AP +0.230 [0.161, 0.307]; E3 AP +0.081 [0.036, 0.140]. Against GRADED moderators E1 ties (Qwen3Guard +0.018 [−0.043, +0.081]; Llama-Guard −0.031 [−0.082, +0.020]); the alarm gain holds (results/l3/claude_batch.json, l3c_graded_reanalysis.json)
L3d Claude Haiku 5.5: transcript-framing grey box (F1–F2)	**both pass**: F1 grey box − moderation on harmful refusals +0.141 [0.082, 0.199] (0.817 vs 0.676); F2 compliance-risk AP (Claude-moderator) +0.115 [0.076, 0.179] (results/l3/claude_transcript.json)
T2 time: internals at CAPE's decision point vs black box (G1–G3)	**all pass**: G1 I_dec − R16_ts +0.075 [0.044, 0.106]; G2 R16_dec − I_dec +0.021 [0.011, 0.035]; G3 I_dec − WB_ts +0.138 [0.107, 0.163] (results/t1/t2_time.json)
L3e Claude Haiku 5.5: the Live tool's alarm, prospective (A1–A3)	**A1 pass** (alarm precision 0.535 vs 0.274 for the moderator alone, +0.261 [0.215, 0.311]); **A2 FAIL** (grey box 0.873 vs graded Qwen3Guard 0.855, +0.018 [−0.023, 0.062]); **A3 FAIL** (multi-turn 0.894 vs 0.906) (results/l3/l3e_tool.json)

Test	Outcome (verbatim from the record)
T3 deployable monitors: LLM judge instead of the oracle checker (K1–K3)	**K1 FAIL** (judge-scored resampling 0.782 ¡ turn-start probe 0.846, −0.065 [−0.115, −0.019]); **K2: probe better** (CAPE probe 0.976 ¿ judge on actual action 0.910, −0.067 [−0.104, −0.036] for the judge); **K3 FAIL** (resampling hurts the action judge, −0.049) (results/t1/t3_deployable.json)
T4 reader trained on labels vs the agent's internals (M1–M2)	**both pass**: M1 READER_act − I_dec +0.015 [0.007, 0.026] (0.994 vs 0.979); M2 READER_act − J_act +0.085 [0.052, 0.127] (results/t1/t4_reader.json)
T5 agent internals vs transcript reader on unseen scenario families (P1–P2)	**P1 pass** (reader − agent internals on unseen families −0.007 [−0.014, −0.0001], margin −0.02); **P2: agent probe better than zero-shot judge** (+0.062 [0.028, 0.101]) (results/t1/t5_family.json)
T6 reader trained on Gemma, monitoring gpt-oss (Q1)	**Q1 pass**: Gemma-trained reader on gpt-oss 0.915 vs zero-shot judge 0.833, +0.082 [0.043, 0.129] (results/t1/t6_cross_agent.json)
T7 reader monitor on AgentDojo prompt injection, zero transfer training (R1–R2)	**R1 pass**: reader 0.781 vs zero-shot judge 0.537, +0.249 [0.136, 0.369]; **R2 reader better than CAPE's gate**: gpt-oss calls as the prereg text specifies, 0.823 vs 0.601, +0.222 [0.143, 0.303] (locked code's broader subset: +0.264 [0.174, 0.359]) (results/t1/t7_agentdojo.json)
T8 Claude Haiku 5.5 as an agent, monitored by a reader trained only on Gemma (S1)	**S1 NOT TESTED**: 0 unsafe units under the preregistered post-reveal rule (Claude's 68 violations all happen at or without the reveal); see T8b
T8b Claude as an agent, all non-read actions (S1b)	**S1b pass**: Gemma-trained reader on Claude 0.991 vs zero-shot judge 0.633, +0.360 [0.302, 0.413]; 95.6% of violations caught at 5% escalation with a cut set on labelled safe actions (judge 0%); at the label-free cut used elsewhere, 94.1% (results/t1/t8b_claude_all_actions.json, label_free_cuts.json)
T9 trained TF-IDF monitor on the reader's own input, same labels (B1 Claude, B2 unseen families)	**B2 pass, B1 FAIL**: unseen families reader 0.969 vs TF-IDF 0.950 (+0.019 [0.007, 0.032]); Claude reader 0.991 vs TF-IDF 0.997 (−0.006 [−0.027, +0.007]). AgentDojo (reported) 0.781 vs 0.503 (results/t1/t9_text_baseline.json)
T10 Claude on task families the monitor never saw (C1 pooled, C2 within)	**C1, C2 pass** (vs zero-shot judge): pooled 0.912 vs 0.570 (+0.342 [0.311, 0.371]); within 0.948 vs 0.633 (+0.318 [0.265, 0.374]). But at the label-free cut the unseen restart family is caught 0/26 (results/t1/t10_claude_unseen_families.json)
T11 second closed family: gpt-6-luna as agent, frozen monitors (G1 pooled vs judge, G2 vs tool identity, G3 within tool)	**G1, G2, G3 all pass**: GPT-6-luna, 3,627 actions, 66 unsafe in 6 families. Reader pooled 0.996 vs judge 0.778 (+0.217 [0.174, 0.265]); vs tool identity +0.141 [0.111, 0.171]; within tool vs judge +0.039 [0.015, 0.066]. 98.5% caught at the label-free 5% cut (judge 37.9%) (results/t1/t11_gpt_agent.json)
T12 labels needed for a new policy, prospective on GPT (H1 40 vs 0 labels, H2 catch at 40 $\geq$ 0.5)	**H1 FAILS, H2 passes**: with 0 labels of the held-out credentials policy, the reader already caught 18/18 of GPT's violations of it, so added labels had nothing to fix (40 − 0: 0.0). The T10 curve does not replicate on this family (results/t1/t12_new_policy_labels.json)
T13 a closed agent on an external benchmark: GPT-6-luna on AgentDojo, frozen monitors (K1 reader vs judge)	**K1 NOT TESTED**: GPT-6-luna resisted the injections (attack success 2.1%), leaving 4 injected calls (minimum 10). Utility on benign tasks 0.862 (results/t1/t13_gpt_agentdojo.json)
T13b closed agent on AgentDojo without the defense (arm none, dev + conf; K1b reader vs judge)	**K1b FAILS**: 36 injected calls; reader 0.840 vs zero-shot judge 0.787 within suite (+0.052 [−0.026, +0.130]). TF-IDF 0.335. At the benign-call 5% cut: reader 36%, judge 53% (results/t1/t13b_gpt_agentdojo_none.json)
T14 labels of the new policy from open agents, tested on the closed agent (L1 vs judge, L2 vs no labels)	**L1, L2 pass**: with AgentDojo labels from open agents, the reader on GPT's AgentDojo calls scores 0.922 vs judge 0.787 (+0.136 [0.078, 0.191]) and vs no labels +0.081 [0.044, 0.121]; caught at the benign 5% cut 36% → 92% (results/t1/t14_agentdojo_labels.json)
T15 latent replication: does the reader replicate the agent's hidden state? (E1 R^2 vs text, E2 readouts on the replica)	**E1, E2 pass**: from the transcript alone, the reader replica reconstructs 66.4% of the agent's decision-state variance (top 128 PCs; text 58.6%; +0.079 [0.075, 0.083]); a probe trained on TRUE states scores 0.987 on the replica vs 0.984 on the true state (+0.003 [−0.002, +0.007]) (results/t1/t15_latent_replication.json)
T16 live prevention on a closed agent: the monitor blocks GPT-6-luna's escalated actions in the loop (P1 violation episodes, gated − ungated)	**P1 passes**: live, the grey-box gate cut GPT-6-luna's episodes with an executed violation from 6.6% to 0.2% (−0.064 [−0.088, −0.044]); 0 violations after a block; goals 47.4% → 45.6%; round trip 89 ms median (results/t1/t16_live_gate.json)
T16b live prevention on a second closed family: Claude Haiku 5.5 in the loop (P1b)	**P1b passes**: on Claude Haiku 5.5, episodes with an executed violation 6.7% → 0.2% (−0.064 [−0.087, −0.044]); 0 violations after a block; goals 40.7% → 34.9%; round trip 80 ms median (results/t1/t16b_claude_live_gate.json)

Test	Outcome (verbatim from the record)
T17 replication on three more open agents: gpt-oss-20b, Qwen3.8-27B, Muse-Glimmer-30B (E1, E2 per agent; scenario-disjoint split)	**E1 and E2 pass on all three agents (replication generalizes)**: from the transcript alone, R^2 of the decision state on fresh scenarios: gpt-oss 0.494 (text 0.392; +0.102 [0.093, 0.110]), Qwen3.8 0.542 (0.441; +0.101 [0.091, 0.111]), Muse Glimmer 0.462 (0.401; +0.061 [0.051, 0.072]). A probe trained on the true states, true → replica: 0.900 → 0.924, 0.955 → 0.972, 0.929 → 0.969 (all lower bounds ¿ −0.02). Fidelity: the agents' own models predict 91–100% of their next 16 tool-call tokens. Exploratory, Gemma-4 under the same split: R^2 0.631 (text 0.556). Exploratory: the text map chose α = 1, the edge of the grid; a finer grid (α 0.01–1, exact dual-form ridge, scripts/96b) is worse at every smaller α for all three agents, so α = 1 is the text map's optimum (results/t1/t17_replication_agents.json, t17_txt_alpha_exploratory.json)
T16c hold for review instead of block: Claude Haiku 5.5, escalated actions go to a reviewer (R1 safety kept, R2 no goal cost vs T16b ungated)	**R1 passes, R2 fails.** Episodes with an executed violation: 6.7% (T16b ungated) → 0.0% (review) (−0.067 [−0.091, −0.044]). Goals: 40.7% → 38.7% (−0.020 [−0.051, +0.007]); the lower bound misses the −0.03 margin, so no goal cost is NOT shown. Reviewer workload: 88 held actions (0.20 per episode, 6.2% of scored actions), 31 of them violations; 0 violations after a block. Exploratory (scripts/97b): episodes with a held-and-approved action kept their goals (60.8% vs 58.8%); the gap is in never-held episodes (38.9% vs 41.0%, n = 368), where both arms ran the same way, which we suggest is run-to-run variation against a non-concurrent control (a hypothesis that T16c does not test). Spend $0.81. **Deviation 1 (infrastructure, 16:39):** the first start ran 0 episodes. The monitoring server loaded the reader outside its lock, and 6 concurrent first requests raced on the lazy transformers imports (ImportError). Fix: the load moved inside the lock (src/graybox/monitor_server.py; scoring unchanged; regression test tests/test_sdk.py). Rerun from scratch on job 3928; spend of the failed start $0.004
T18 a second outside benchmark: Claude Haiku 5.5 on τ^2-bench airline, monitors trained on four frontier agents' labelled trajectories (H1 within-tool READER vs TOOL, H2 READER vs TXT)	**not tested**: 9 violations ¡ the preregistered minimum of 15 (Claude violated in 1.5% of episodes; the 9 come from 3 tasks). Descriptive only: within-tool AUROC reader 0.756, TF-IDF 0.963; pooled reader 0.835, TF-IDF 0.960, tool 0.686; the CAPE-trained probe zero-shot 0.357 pooled (results/t1/t18_tau2_claude.json)
T19 readers small enough for a browser or a CPU: do they transfer? (F1 browser reader vs TF-IDF on GPT AgentDojo; F2 non-inferior to the 8B reader on closed CAPE)	pending. **Deviation 1:** the analysis crashed after computing, when writing its JSON (a numpy bool); fix: one bool() cast, no computation changed
T20 τ^2-bench with two closed agents (Claude Haiku 5.5, GPT-6-luna) and a persistent customer; T18's monitors (G1 reader vs tool within tool, G2 TF-IDF vs tool)	**G2 passes, G1 fails.** Within-tool AUROC: TF-IDF 0.987 (+0.487 [0.428, 0.500] over tool identity), reader 0.738 (+0.238 [−0.053, 0.431]); reported: reader − TF-IDF −0.250 [−0.518, −0.077]. Per agent: Claude reader 0.555 / TF-IDF 0.966; GPT 0.739 / 1.000. Reading fixed in advance: on τ^2-bench, labels of the policy from other agents transfer to both closed agents through word counts, and the reader does not use them as well (results/t1/t20_tau2_two_closed.json). Spend (from the ledgers): Claude $1.71, GPT $0.83