Grey Box: what we are doing, and how

A plain-language guide to the project as of October 15, 2026, 9 pm PDT. Every number here is labelled confirmed or development-only.


1. The goal in one paragraph

Safety tools that look *inside* a model (at its hidden activations) need the model's weights. The most capable models, such as Claude, GPT and Gemini, are closed: we only see their text. Your CAPE paper showed that reading an agent's insides can forecast and prevent unauthorized actions. This project asks two questions. How much of a closed model's inside can we reconstruct from the outside? And for safety, do we even need the inside?

The short answer so far. Quite a lot of the inside can be reconstructed. For safety questions about what an agent will *do*, outside access turns out to be at least as good as inside access. The best monitor we found is fully black-box.

2. The core trick: ask the model about itself, in side branches

We cannot read a closed model's neurons. We can ask it questions. At any moment of a conversation, we copy the conversation and add one short yes/no question to the copy, for example “Is this request harmful?” or “Will you refuse?”. We read how likely the model is to say yes. We do this for a fixed list of questions (64 to 88). The list of yes-probabilities is a fingerprint of the model's current state. We call it the **grey box**, written Ψ (psi).



The real reply is never changed: the questions go into copies of the conversation.

Why not reconstruct the actual neurons? Because it is mathematically impossible from outputs alone. Rotating a model's internal coordinate system leaves every output exactly the same, the way a rotated map still shows the same city. So no outside method can tell the rotations apart. We proved this, and showed it on a real network: after a rotation, a white-box readout broke (its accuracy fell from 0.9995 to −0.46), while the grey box was unchanged. What *can* be recovered exactly is everything about the state that affects behaviour. That is what the questions measure.

3. How we check it really works: a ladder of models whose insides we know

You cannot check an estimate of a closed model's insides directly. So we check on models we can open, pretending they are closed, and compare with their true hidden states. Each rung is harder:


Rung	The “black box”	What we found	Status
L0	A program compiled into a transformer (like Handwired)	21 questions identify all 21 hidden states exactly	Exact
L1	Othello-GPT (a model that learned the board)	Its hidden state is recovered at R^2 0.967 from 61 questions per move	**Confirmed** (pre-registered, fresh games)
L1b	16 small models trained on random hidden-state worlds	The hidden state is decoded as well as with a probe inside the model	Development
L2	8 open chat models (Qwen, Llama, Gemma, Mistral, Phi, OLMo, gpt-oss)	Qwen3-8B: 88 answers recover R^2 0.90 of its hidden state and predict 70% of individual neurons well	Development; 6 of 8 models done; confirmation pending
L3	Closed models (Claude, GPT, Gemini)	Not run yet: needs your API key	Pending

R^2 is the fraction of the hidden state's variation we reconstruct (1.0 = all of it).

4. The safety part: forecasting an agent's unauthorized action

We use your CAPE-Bench agents (Gemma-4, 26B), right before each action. Three ways to forecast whether the next action breaks the rules:

- **Look inside** (white box): a probe on the agent's hidden state. Needs the weights.
- **Ask** (black box): the 64 side-branch questions.
- **Replay** (black box): let the agent take the same turn again several times and see how often it breaks the rules. No training needed.



Development data, 5,493 agent turns, scored on scenarios each monitor never saw. Red: black box. Blue: needs internals. Copper: black box, asking only.

What this says

- Replaying the turn beats every monitor that looks inside, including a 27B model's internals.
- **A probe on the hidden state is worth about 6 replays.** We measured the same exchange rate on Othello-GPT and on the 26B agent.
- **Ask + replay is the best monitor of all, and it is fully black-box.** Four replays plus the 64 answers beat the strongest inside-reading monitor by 0.058.
- This matches our theorem. For anything defined by what the model will *do*, its own behaviour is the best possible forecast. Looking inside can only approximate it.

A trap we found along the way

The usual way to build test sets for safety monitors picks the “safe” examples from episodes that never go wrong. That choice uses the future. With it, a simple text classifier looked better than the theoretical best forecaster. Once we picked examples using only the past, the order flipped back. This is a warning for how such monitors are evaluated, and we have the theorem that explains it.

5. How we keep it honest


- **Pre-registration.** Before testing on new data we write down the exact test and pass mark, and lock them with a cryptographic hash. The Othello test passed this way. The agent test and its addendum are locked and run tonight.

- **Fresh data.** Confirmation uses data never touched during development (new games, new agent episodes with unused seeds, a held-out 30% of chat prompts).
- **Hard baselines.** We compare against reading the text alone, and against another model answering the same questions (to separate the agent's own state from what anyone reading the transcript would say).
- **Failures recorded.** Bugs and weak results go into a dated ledger with their cause and fix. Example: an automatic refusal detector misread polite refusals, which we caught by reading replies and then replaced with a standard judge model.


What did not hold, stated plainly. We hoped asking the agent would beat a strong outside model reading the transcript with its internals. Against a 27B reader it is a tie, so we dropped that claim. The stronger replacement is ask + replay. On very long agent transcripts, the 64 answers recover only about a third of the hidden state's variation (R^2 0.31–0.40).

6. The 3D features you asked for: status


Feature	What it shows	Status
Othello 3D viewer	The estimated hidden path (from questions only) next to the true hidden path; the board read from outputs; a button that rotates the model's internal coordinates to show the white box breaking	**Done.** Published: claude.ai/artifact/3NhZL81aBgmV3UYuNXtiAX
Agent 3D view	A real 26B agent's turns placed in 3D from its own answers, with a “risk” axis. For each action: the black-box forecast, the white-box forecast, and 16 replays. Its true vs estimated hidden path.	**Done.** Published: claude.ai/artifact/LccS8wWzBe1L5zxkcydoQ6
Grey Box Live (the API tool)	Chat with any model through its API. After each message, its path moves in a 3D space shared by all models, with readouts for “harmful request”, “about to refuse” and “negative tone”, each showing how accurate it is on model families it was never trained on (0.91–1.00).	**Built and validated.** The API path matches offline measurements (correlation 0.9998). Running on your server (localhost:8765/live via an SSH tunnel).
Live session with a real open model	A recorded conversation with Qwen3-8B, including its TRUE hidden path next to the estimate	**Recording tonight** on the GPU; published as a page by morning
Live with closed models	The same view for Claude, GPT or Gemini	**Pending:** needs your API key, after tomorrow's confirmations



Agent 3D view (published). Left: every agent state, placed only from its own yes/no answers; red states came right before an unauthorized action. Right: an episode turn by turn, with the agent's answers. It said approval was still required, then acted anyway.



Othello 3D viewer (published). Copper: the hidden path estimated from outside. Ink: the true hidden path. Right: the board read from outputs, with wrong squares outlined.



Grey Box Live (on your server). Shown here against a test endpoint. The 3D space fills in once the shared frame is loaded; it is now built from 4 model families.

7. Where we are, and what “groundbreaking” still needs

Item	Status	When
Theory (rotation, identifiability, why replay beats probes, the test-set trap)	Written with proofs	Done
Othello recovery	Confirmed (pre-registered)	Done
Agent safety: replay and ask + replay vs white box	Strong on development data; confirmation locked	Results tomorrow afternoon
Second agent model (gpt-oss)	Queued	Tomorrow
8 open chat models + their confirmation	6 of 8 done	Tomorrow morning
Live tool with real models	Built; open-model recording tonight	Tomorrow morning
A closed frontier agent	**Needs your API key and a small budget**	After confirmations

The candidate headline. For safety questions about what an agent will do, black-box access loses nothing. Asking a closed agent and replaying its turn beats probes on its insides, and a probe is worth about six replays. **It becomes groundbreaking** if it (1) passes tomorrow's pre-registered test on new episodes, (2) holds on a second agent model, and (3) works on one real closed frontier agent. If any of these fails, we still have a strong paper: the theory, the confirmed Othello result, the test-set warning and the exchange rate.

What I need from you: after tomorrow's confirmations, an API key (set as an environment variable on the server, never pasted in chat) for one closed model, and a spending cap. Rough cost: tens of dollars on a cheap model tier, with prompt caching.