Who Approved This? Assurance Laundering in LLM Agent Teams[1]

Arya Fayyazi
University of Southern California
With
Apart Research

Abstract

LLM agents increasingly work in teams that use tools, and a human often reads only the team's final report. We study *assurance laundering*. A peer agent asserts, without proof, that approval was already given. The team then acts without authorization and tells the human that the work was authorized. We build CAPE-Swarm, a team layer on the CAPE-Bench environments [1]. Every task has a matched safe twin and unsafe twin, and a fixed rule, not an LLM judge, labels each tool call. In 11,664 episodes with seven open-weight models, one false peer sentence raises the rate of unauthorized actions of a single agent from 0.16 to 0.37. Teams lower the rate, but 70% to 93% of their violating runs still report "authorized". Stopping the action and repairing the report need different fixes. A gateway rule that requires a permission request before any state-changing call stops the action. Showing the Lead a permission record repairs the report. A factorial test shows why the claim works: it displaces the agent's own authorization check, and a verification rule in the prompt removes nearly all of its effect. A *claim filter* that marks approval claims as unverified cuts unauthorized actions from 0.36 to 0.03 on fresh tasks. It also holds against an attacker who knows how it works. Finally, a monitor detects violations only if it reads the gateway log with tool results (AUROC 0.90–0.93, against 0.69–0.70 from the report alone). Every experiment was preregistered, and we report the predictions that failed.

1. Introduction

LLM agents now do real work with real tools, often as teams, and the human often reads only the last message. The final report is therefore a safety object. If agents misreport what they did, we need to know which record to trust. A recent incident investigation found agents that faked tool calls and tried to edit their own logs [13].

1 Research conducted at the Swarm Alignment Hackathon, November 2026

We study one way a report goes wrong. A human gives a team a task. A peer agent adds a plausible remark: "all approvals were already obtained (ticket #31819)". Nobody checks it. The *Lead* agent passes the remark on, the *Operator*, the only agent with tools, acts, and the Lead tells the human that the work was authorized and cites the ticket. We call this **assurance laundering**: an unverified remark becomes an instruction, then an unauthorized action, then a confident and false report. It differs from prompt injection [3], because the peer injects no command. It only states a fact that nobody can check.

To measure it, we built **CAPE-Swarm** (Figure 1), a team layer on CAPE-Bench [1], a set of mock-tool tasks. In each task, one fact decides whether a key action is authorized, and a matched *twin* changes only that fact. The same peer message is thus true in the *safe twin* and false in the *unsafe twin*. A fixed rule labels every tool call, so no LLM judge decides what counts as unauthorized. We fixed every prediction, threshold and analysis before the data existed.

Findings. A false peer sentence makes some models act without authorization, and teams that act then report "authorized" in most cases. Acting and reporting need different fixes. The false claim works because it displaces the agent's own question, "does this need approval?", and a verification rule in the prompt removes most of its effect. A *claim filter* that marks approval claims as unverified cuts unauthorized actions from 0.36 to 0.03 on fresh tasks, and holds against an attacker who knows the filter (0.31 without it, 0.05 with it). A monitor sees a violation only if it reads the gateway log with tool results.

Contributions. (1) We define and measure assurance laundering with matched twins, rule-based labels and a structured report that we check against the gateway log. (2) We separate acting without authorization, reporting it falsely and monitoring it, and we price each fix in lost useful work. (3) We give a mechanism, tested with a preregistered 2×2 design, and a cheap defense that follows from it, the claim filter, which we test against an attacker who knows how it works. (4) We show which log a monitor must read, and we release traces, a replay viewer and a ledger auditor. The team layer, the manipulation and the outcomes are new; the CAPE-Bench environments are preexisting.




Figure 1. How one false sentence travels through a team, and where each defense acts. A peer states an unverified approval (1). The Operator then skips its permission request and acts, and the gateway logs every call (2). The Lead reports "authorized" to the human (3). A monitor may read five levels of log (4). Dashed boxes are the defenses we test. The cards give the measured effect: (1) share of runs in which the Operator asks the permission system before acting; (2)

unauthorized-action rate V; (3) share of violating runs whose report says "authorized"; (4) AUROC of a monitor (Qwen3.5-397B judge). Cards 1 and 2 use the fresh tasks of Section 4.8; card 3 and ladder 4 use the main experiments (Sections 4.2, 4.3 and 4.6).

2. Related Work

Failures in multi-agent systems. Hammond et al. [2] map the risks of interacting agents, and Cemri et al. [4] label failure modes in agent traces. We study one security failure with a ground-truth label in every episode. Prompt Infection [3] shows that an injected instruction can pass from agent to agent. We inject no instruction: a peer states a plausible fact that nobody can check, and normal delegation does the rest. Access-control mechanisms such as SEAgent [7], ScopeGate [8] and [9] are what such a failure calls for. We measure the behavior that makes them necessary, and we price them in lost useful work with matched safe twins.

False authority in agent systems. Four recent studies are closest. Cerruti et al. [15] show that a false permission record in agent memory leads executors to act. Safin et al. [16] show that a forged approval reaches the executor of a four-agent pipeline unless an independent authorization layer blocks it. Zhu et al. [17] find that a deterministic tool gate stops the requests that models make. Xu et al. [18] find that unauthorized actions grow with the depth of the delegation hierarchy. We agree that enforcement must sit outside the model, and we add three things: matched twins with a rule-based label for every call, so that we can price a gate; the *report* to the human as an outcome, with the question of which log shows the failure; and a test of why the false claim works and of an in-transit defense against an attacker who knows it. Our claim filter is a form of spotlighting [14], which marks untrusted text, and is far weaker in principle than the capability tracking of CaMeL [19]. We test it because it needs no change to the agents. The provenance paradox [10] also says that unverifiable claims mislead delegation.

Control and monitoring. AI control [5] and resampling [6] study monitors for one untrusted agent. Rose et al. [11] argue that secret collusion may limit what transcript monitors see, and Korbak et al. [12] call chain-of-thought monitoring a fragile opportunity. We ask which log a deployer must keep. An incident investigation [13] found agents that faked tool calls and edited logs, which is why our strongest log is written by the gateway. **Our prior work.** CAPE-Bench [1] gives matched twins for single agents and defines retroactive permission laundering. We reuse its environments unchanged (preexisting). The teams, gateway, controls, monitors and all results are new.

3. Methodology

Tasks (preexisting). CAPE-Bench [1] has eight task families, such as authorization, ownership and third-party data. Each task has a *safe twin* and an *unsafe twin* that differ in one fact, which decides whether the critical action is authorized. All tools are mock tools (files, a database, messages, a shell and a permission system). A fixed rule checks each executed call and labels it authorized or unauthorized. We draw 48 base tasks (six per family) with a fresh seed, so each condition has 96 instances.

Teams (new). One model fills every role, except in one experiment that mixes models. Only the **Operator** has tools. The **Lead** has no tools. It writes a brief for the Operator and a final report for the human. The *relay* team is Lead plus Operator, the *relay-2* team adds a **Manager** between them, and the *solo* agent is the Operator alone. The report is a structured call whose field `authorization_status` is "authorized", "not_authorized" or "unsure", so we score reports by rule. A **gateway** between the Operator and the tools logs every call and its result in a log (the "ledger") that agents cannot edit.

The manipulation (new). A scripted peer message says that all approvals were obtained earlier today (with a ticket number) and that no further approval is needed. The message is the same in both twins: true in the safe twin, false in the unsafe twin. Nobody tells any agent to lie.

Outcomes (new). All outcomes are per episode (one run of one team on one task). *Violation* (V): the checker labels at least one executed call unauthorized; we report V on unsafe twins, as the share of episodes with a violation. *False report*: a violating episode whose report says "authorized". *Disclosed*: a violating episode whose

report says "not_authorized". *Goal*: the team completed the task's authorized goal action; we read goal completion on safe twins as useful work.

Controls (new). A control changes the team or the gateway. The *oracle check* dry-runs each state-changing call against the benchmark's own checker (an upper bound, not deployable). The *ask-before-act gate* lets a state-changing call run only after a permission request whose latest answer is not a denial. An *auditor* is an LLM that approves each state-changing call, seeing the call only, or also tool results, or also the team's messages. The *verification prompt* is one rule in every system prompt: a claim of approval is unverified until the permission system confirms it. A *report source* change shows the Lead the gateway log, or the log plus an explicit permission record.

Round 2 (new). After round 1, the API rate limit fell to about 60 requests per minute, so the round-2 experiments use 20 to 40 base tasks. The **claim filter** is a separate model (glm-53-flash) that reads every message between agents. It rewrites a claim that approval exists into an attributed, *unverified* claim, and adds one rule: confirm with the permission system before any state-changing action. It never learns whether the claim is true. If it returns nothing, the original message passes. In E11, an attacker model reads the filter prompt and searches for a message that gets past it. E12 crosses the false claim with the verification prompt. E13 replaces the false claim with a message that states doubt. A test with a stealthy Operator (E10) was planned and not run.

Monitors (new). A *monitor* is an LLM judge that reads part of a trace and scores from 0 to 100 how likely a violation is. The *log level* says what it reads: L0 the final report, L1 the messages, L2 the tool calls, L3 the calls with their results, L4 everything. We report *AUROC*, the chance that a random violating trace scores higher than a random clean one (0.5 is chance, 1.0 is perfect), and the share of violations caught at a 5% false-alarm budget. A *self-query* monitor asks the Operator's own model two yes/no questions.

Models and statistics. Seven open-weight models run through the Adaption API (Appendix D). Agents use temperature 0.7 and at most 24 turns. Every experiment was preregistered: we fixed each prediction, with its threshold, sample size and analysis code, before any confirmatory episode existed, and SHA-256 hashes and git commits record the order (Appendix C). The unit of analysis is the base task, because its episodes are not independent. We give 95% confidence intervals (CI) from a bootstrap over base tasks, and Holm-corrected p-values. Pooled numbers give every model equal weight. We report every prediction, including the failures. Table D1 lists every experiment.

4. Results

Experiment E1 has 4,032 episodes: seven models, three team shapes and two message conditions (a false peer message, or no message), with 96 task instances per cell. We write V for the share of unsafe-twin episodes that contain an unauthorized action. Brackets give 95% confidence intervals. Every test below was preregistered unless we call it *exploratory*.

4.1 A false peer message makes agents act without authorization

Single agent. The peer message raises V from 0.16 to 0.37, a difference of +0.21 [+0.16, +0.25]. The average hides a split between models (Figure 2a). Three models react strongly: Qwen3.5-397B (+0.54), Gemma-4 31B (+0.42) and Gemma-4 26B (+0.35). DeepSeek-V4 flash reacts weakly (+0.08), and the other three models hardly react.




Figure 2. A false peer message raises unauthorized actions, unevenly. (a) Single agent: V for each model, with a 95% interval over 48 base tasks. (b) Mean of seven models, by team shape. Unsafe twins only, where the message is false.

Teams. The effect remains in teams (difference +0.18 for the relay and +0.08 for the relay-2 team). The rate is lower in teams, with or without the message, so teams do not make the problem worse, but they do not remove it. With the false message, V is 0.37 for the single agent, 0.27 for the relay and 0.15 for relay-2.

4.2 The claim travels through the team and returns as a false report

Figure E1 (Appendix E) follows the ticket number through the relay. The Lead's brief repeats the claim in 82% of episodes, and other Leads drop it. A brief can *endorse* the claim, *reject* it (call it unverified, or tell the Operator to check) or not mention it. After an endorsing brief, violations occur in 52% of episodes. After a rejecting brief, they occur in 4% (exploratory; Appendix E). The split follows the model: the Gemma-4 models endorse most often.

The report is where the harm reaches the human. Among violating episodes it says "authorized" in 82% and discloses the violation in only 11% [7%, 15%]. The single agent is the least honest (93% false reports); teams are somewhat more honest (relay 70%, relay-2 74%; exploratory).

4.3 A gateway rule stops the action; a permission record repairs the report

The next tests use four models: Gemma-4 26B, Gemma-4 31B, Qwen3.5-397B and DeepSeek-V4 flash. We chose them before the main runs because they reacted most in a small pilot. The team is the relay, with the false peer message. Each condition has 384 episodes, half of them on safe twins. With no control, V is 43%, and 81% of the violating episodes give a false report. Figure 3 shows what each control costs.

A permission record repairs the report but does not change the action. In this control, the Lead sees the gateway log and an explicit record of what the permission system approved. False reports fall from 81% to 26% of violating episodes (a relative cut of 68%, CI [57%, 78%]), and the Lead discloses the violation in 67% of them, up from 7%. But V does not change (+0.03 [-0.04, +0.09]).




Figure 3. Price list of controls (relay, false peer message, four models). Each point is one control: V on unsafe twins against goal completion on safe twins. The best controls are in the lower right. Gateway controls (blue) beat auditors and prompts (orange). Reporting-only fixes (green) leave the action untouched.

An ask-before-act gate stops the action. The gate lets a state-changing call run only after a permission request that was not denied. It needs no oracle. V falls to 0.5% (CI up to 1.6%), and the price is a fall in goal completion on safe twins of 0.05 [0.02, 0.09]. The oracle check reaches $V = 0$ by construction, so it is only an upper bound.

Auditors and a prompt rule help, but leave a residual. An auditor LLM that sees only the call cuts V to 5% but blocks almost everything (goal completion 0.26). With tool results it cuts V to 9%, and a violation that passes it still gets a false report in 100% of cases. The verification prompt (one rule in every system prompt) cuts V from 43% to 9%. None comes close to the gate (Appendix E.4).

4.4 In a mixed team, the Lead is the gatekeeper

We paired credulous models (Gemma-4 26B, Qwen3.5-397B) with skeptical ones (GLM-5.2, glm-53-flash) in the relay (768 episodes). We expected the Operator's model to decide whether the team acts. It does not. A skeptical Lead with a credulous Operator gives $V = 0.12$, against 0.38 for an all-credulous team. A credulous Lead with a skeptical Operator gives 0.14. The Lead's brief sets what the Operator believes, and the Lead also decides what the human reads: a skeptical Lead discloses violations +0.36 more often (Appendix E.8).

4.5 Robustness: wording, repeats and an adaptive attacker

Wording. The effect does not depend on one sentence. A manager's message and a terse "Approvals are already in place" both raise V over no message (+0.25 [+0.16, +0.34] and +0.21 [+0.14, +0.29]). A hedged message ("I have not checked; please confirm before acting") gives $V = 0.04$, below the main wording and also below no message at all (0.11; exploratory). Section 4.7 tests this surprising result on fresh tasks.

Repeats. A single episode repeats its own outcome only 77% of the time ($\kappa = 0.53$), so we report rates and not single traces.

An adaptive attacker. A model (GLM-5.2) wrote candidate messages and improved them against a development seed. Its best message is **not stronger** than the scripted one on fresh tasks ($V = 0.49$ against 0.43; difference +0.06 [-0.02, +0.14]), and the gate holds against it ($V = 1.0\%$). Appendix E.9 has the search.

4.6 A monitor must read the gateway log with tool results

We scored 768 relay traces (four models, half unsafe twins, half safe twins). Two judge models scored each trace at each log level, L0 to L4 (Section 3). The label is whether a violation occurred. From the final report alone (L0), AUROC is 0.69–0.70 across the two judges. From the gateway log with results (L3), it is 0.90–0.93. The gains are +0.21 and +0.23, and both CI lower bounds are above 0.15. At a 5% false-alarm budget, the Qwen judge catches 71% of violations at L3 and 12% at L0 (Figure 4). The Gemma judge gives coarse scores with many ties, so we use AUROC for it.




Figure 4. The log ladder. (a) AUROC for detecting a violation, by log level and judge model (bands: 95% intervals). The dashed line is the self-query monitor. (b) Share of violations caught at a 5% false-alarm budget. Ties count as false alarms, so the coarse Gemma scores often give zero. The gateway log with results (L3) is best.

Tool calls without results are as weak as the report (AUROC 0.69–0.74), because the results carry the evidence, for example who owns a file or what the permission system said. A self-query monitor, which asks the Operator's own model two yes/no questions, reaches AUROC 0.78 [0.71, 0.85]. Its lower bound misses our preregistered criterion of 0.75, so the support is weak. A rule monitor and a judge from a model family that never acted in the traces are in Appendix E.6.

4.7 The claim works by displacing the agent's own check

A false claim could raise V because agents believe it. Or it could raise V because it replaces the agent's own question, "does this need approval?". Experiment E12 separates the two. It crosses the false claim (absent or present) with the verification rule of Section 4.3 (absent or present in every system prompt). It uses the fresh tasks of Section 4.8 (where the no-message and false-message cells also come from), the unsafe twins and four models (160 new episodes, 20 base tasks).

Without the rule, the claim raises V from 0.10 to 0.38. With the rule, V is 0.06 without the claim and 0.10 with it. So the claim adds +0.28 without the rule and only +0.04 [-0.01, +0.09] with it. The interaction is +0.24 [+0.10, +0.38]. Agents do not simply believe the claim. They stop asking. The behavior behind this is visible in the logs (exploratory). The share of episodes in which the Operator asked the permission system before acting is 0.82 with no claim and 0.47 [0.33, 0.60] with the claim. With the verification rule it is 0.80 and 0.80. With the claim filter (Section 4.8) it rises to 0.93.

4.8 A claim filter marks the claim and keeps the work

If the false claim does its harm by displacing the agent's check, a defense can restore the check at the claim itself. We added a **claim filter** to the message bus. A small model (glm-53-flash, temperature 0) reads every message between agents. If a message claims approval, authorization or permission, the filter rewrites that claim. The new text says who made the claim, says that it is unverified, and tells the reader to confirm it with the permission system before any state-changing action. The rest of the message is unchanged. The filter sees neither the task, nor the log, nor the twin. If it returns nothing, the original message passes, which happened in 129 of 610 calls, mostly on the Lead's brief. The idea is close to spotlighting [14], which marks untrusted text for the model. We mark a *claim* by its source, between agents.

We ran the filter on fresh tasks (E9, seed 5501, relay, four models, 896 episodes). The design had 40 base tasks, but the API limit fell during the sprint, so only 22 base tasks have every condition finished. We analyse those (Appendix A). Figure 5 shows the results.

The false message works again on fresh tasks. V rises from 0.09 with no message to 0.36 with the peer message (+0.27 [+0.17, +0.38]).

The filter removes most of the harm. With the filter, V falls to 0.03 (-0.33 [-0.44, -0.23]). No violating report says "authorized" any more, against 75% without the filter. All four models improve: without the filter their V is 0.23 to 0.59, and with it at most 0.14.

It is not tuned to one sentence. We wrote the filter prompt with the main message in mind. The attacker message from Section 4.5 is a wording the filter never saw, and its V falls from 0.50 to 0.01 (-0.49 [-0.64, -0.33]).

It costs no measurable useful work. Goal completion on safe twins is 0.80 with the filter and 0.74 without. The change (without minus with the filter) is -0.06 [-0.11, +0.01]; a negative value means the filter lost nothing, and our margin was 0.10.

The gate also works again, and the filter is not clearly cheaper. With the gate, V is 0.00 and goal completion on safe twins is 0.77. We expected the filter to cost less than the gate, but we did not show it. Goal completion with the filter minus with the gate is +0.02 [-0.03, +0.08], so the two controls cost about the same here. The filter needs no change at the gateway, and the agent still makes its own decision.

A message written against the filter still fails. In a second test (E11), the attacker model (GLM-5.2) saw the filter prompt and searched two rounds for a message that gets past the filter. The best message avoids any approval claim. It says that a step is routine and non-disruptive, and asks the agent to proceed. On fresh tasks (240 episodes, 20 base tasks), V is 0.31 with no control, 0.05 with the filter (-0.26 [-0.41, -0.11]) and 0.00 with the gate. The filter still rewrote this message into an unverified claim, because it names a ticket and a peer. A pressure message with no claim at all would pass the filter unchanged, so the filter needs the gate or a permission record behind it.




Figure 5. The claim filter (E9, relay, four models). (a) V on unsafe twins for the main peer message and for the attacker message of Section 4.5. Bars: no control, the filter, and the ask-before-act gate (main message only). Whiskers are 95% intervals. The dashed line is V with no message. (b) Goal completion on safe twins.

5. Discussion and Limitations

What the results say. Acting without authorization, reporting it falsely and monitoring it are three different problems. A permission record repaired the report but not the action, an ask-before-act gate stopped the action at a cost in useful work, and only a log with tool results let a monitor see the failure. The mechanism test explains why one sentence is enough: the claim displaces the agent's own check, and any reliable prompt to check restores it. That is also why the claim filter works. It does not decide whether a claim is true. It puts the question back.

What a deployer should log and enforce. (1) Write the log at the gateway, with tool results, where no agent can edit it: a monitor that reads the report (0.69–0.70 AUROC) or the calls without results (0.69–0.74) is close to blind, and one that reads calls with results reaches 0.90–0.93. (2) Keep an explicit permission record, and make reports cite it and not a peer. (3) Enforce ask-before-act at the gateway. If you cannot, mark every approval claim that crosses an agent boundary as unverified, and do not rely on that alone, because a pressure message with no claim passes the filter. (4) Test your own models with matched twins first. Three of seven models hardly reacted to the claim and three reacted strongly, so model choice is a safety decision.

Predictions that did not hold. The Operator's model does not decide alone, because the Lead is a gatekeeper (4.4). The team's own words do not recruit an auditor (4.3). A short attacker search found no message stronger than the scripted one (4.5). We did not show that the claim filter costs less useful work than the gate (4.8). Appendix C lists all predictions by experiment.

Limitations. Appendix A has the full list. We used open-weight models only, mock tools and weak attackers (scripted wordings and short searches). The judges come from the same model families as the agents. The experiments of 4.7 and 4.8 are small, because the API rate limit fell during the sprint, and a planned test with a stealthy Operator was not run. We assume agents cannot edit the gateway log, but real agents have edited logs [13]. **Future work:** frontier models, trained attackers, real swarm logs and mesh topologies.

6. Conclusion

One unverified sentence from a peer agent can make an agent team act without authorization and then report the work as authorized. How much depends on the model, the team shape and the Lead. The two failures need different fixes: a gateway rule stops the action, and a permission record repairs the report. The claim works because it displaces the agent's own check, and a claim filter that marks approval claims as unverified restores that check at little cost. It held against an attacker who knew it, but a message with no approval claim would pass it, so it belongs behind the gate. A monitor must read the gateway log with tool results to see the violation. We release traces, a replay viewer and a ledger auditor, so that a team can test its own agents.

References

[1] Fayyazi, A., et al. (2026). The Agent Knew: Internal States Forecast Unauthorized Actions and Stop Them, and the Lies That Follow. arXiv:2610.17301. https://arxiv.org/abs/2610.17301

[2] Hammond, L., et al. (2025). Multi-Agent Risks from Advanced AI. arXiv:2502.14143. https://arxiv.org/abs/2502.14143

[3] Lee, D., et al. (2024). Prompt Infection: LLM-to-LLM Prompt Injection within Multi-Agent Systems. arXiv:2410.07283. https://arxiv.org/abs/2410.07283

[4] Cemri, M., et al. (2025). Why Do Multi-Agent LLM Systems Fail? arXiv:2503.13657. https://arxiv.org/abs/2503.13657

[5] Greenblatt, R., et al. (2023). AI Control: Improving Safety Despite Intentional Subversion. arXiv:2312.06942. https://arxiv.org/abs/2312.06942

[6] Bhatt, A., et al. (2025). Ctrl-Z: Controlling AI Agents via Resampling. arXiv:2504.10374. https://arxiv.org/abs/2504.10374

[7] Ji, Z., et al. (2026). Taming Various Privilege Escalation in LLM-Based Agent Systems: A Mandatory Access Control Framework. arXiv:2601.11893. https://arxiv.org/abs/2601.11893

[8] Mellafe Zuvic, D. (2026). Capability Gates Are Not Authorization: Confused-Deputy Failures in LLM Agent Frameworks. arXiv:2606.28679. https://arxiv.org/abs/2606.28679

[9] Dantuluri, P. S. V., et al. (2026). Delegation Without Trust: An Empirical Gap Analysis of Identity, Authorization, and Runtime Governance in Multi-Agent LLM Systems. arXiv:2609.00267. https://arxiv.org/abs/2609.00267

[10] Prakash, S. (2026). The Provenance Paradox in Multi-Agent LLM Routing: Delegation Contracts and Attested Identity in LDP. arXiv:2603.18043. https://arxiv.org/abs/2603.18043

[11] Rose, A., et al. (2026). Detecting Multi-Agent Collusion Through Multi-Agent Interpretability. arXiv:2604.01151. https://arxiv.org/abs/2604.01151

[12] Korbak, T., et al. (2025). Chain of Thought Monitorability: A New and Fragile Opportunity for AI Safety. arXiv:2507.11473. https://arxiv.org/abs/2507.11473

[13] METR (2026). Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident (Hugging Face incident investigation report), 26 August 2026. https://metr.org/hugging-face-incident-report-aug-2026.pdf

[14] Hines, K., et al. (2024). Defending Against Indirect Prompt Injection Attacks With Spotlighting. arXiv:2403.14720. https://arxiv.org/abs/2403.14720

[15] Cerruti, T., Okamoto, M., Erol, A. K. (2026). Agent Memory Is a Surface for Endogenous Authorization Laundering. arXiv:2609.01836. https://arxiv.org/abs/2609.01836

[16] Safin, T. H., et al. (2026). Trust propagation and structural containment in Multi-agent LLM pipelines. arXiv:2609.17648. https://arxiv.org/abs/2609.17648

[17] Zhu, J., et al. (2026). Who Speaks, Who Authorizes, Who Acts? Understanding Trust Boundaries in Multi-Agent LLMs. arXiv:2610.24298. https://arxiv.org/abs/2610.24298

[18] Xu, Z., et al. (2026). MasDrift: Benchmarking Authorization Preservation Across Multi-Agent Architectures. arXiv:2608.07556. https://arxiv.org/abs/2608.07556

[19] Debenedetti, E., et al. (2025). Defeating Prompt Injections by Design. arXiv:2503.18813. https://arxiv.org/abs/2503.18813

Code and Data

Code, preregistration locks, results and the replay viewer are at https://github.com/AryaFayyazi/swarm_mutli (the README marks preexisting and new code; the full git history is public, so the lock commits can be checked). Traces are in the submission archive. Every number comes from `scripts/20_analyze.py` and `scripts/27_round2.py`.

Author Contributions

A.F. is the only author. A.F. is responsible for all claims, results and conclusions in this report. Claude Code (an AI assistant; Appendix B) helped only with writing code and with drafting the first version of the report.

Appendix A. Limitations and Dual-Use / Ethical Considerations

What this result does and does not establish. It establishes that, in mock-tool tasks with seven open-weight models, one unverified approval claim from a peer makes some teams act without authorization and report the work as authorized; that a gateway rule and a claim filter reduce this; and that a monitor needs the gateway log with tool results. It does not establish that frontier or closed models behave the same way, that real tools and real users behave like mock tools, that the claim filter survives a trained or long-running attacker, or that the agents "meant" to deceive. The sections below give each assumption and how the result would change if it failed.

A.1 Limitations

We list each assumption and say how a result would change if it failed.

- **Open-weight models only.** The sprint API serves seven open-weight models. Frontier closed models may behave differently. The effect size varies a lot between our models (Figure 2a), so we do not claim a rate for any other model. The *direction* of the mechanism is what we test. If frontier models resist the assurance, the main effect would fail for them, and the gateway results would still stand.
- **The attacker is weak.** One message from a peer starts the chain. We tested four hand-written wordings (E5) and a two-round search by one attacker model that saw only a generic description and development-seed scores (E8). A stronger attacker that knows the scenario, the policy or the agents' prompts, or one trained against the team, may do more.
- **One model per team, mostly.** Teams use one model for every role. E4 mixes models, but only four models and only across the credulous/skeptical divide.
- **Controls were tested on four models.** We chose the four models with the highest violation rates in the development pilot. On the models that hardly react there is little to prevent, so the benefit would be smaller, and the utility cost would stay. We did not test controls on all seven models.
- **No tamper test.** We assume the gateway writes the ledger and agents cannot edit it. We did not test agents that try to edit or spoof it. Deployers should write the ledger from a separate process (a gateway or proxy) and, where needed, to an append-only store outside the agents' reach.
- **Small cells.** Each model cell has 48 episodes per condition, so per-model numbers are descriptive. Pooled estimates use 48 scenario clusters.
- **Mock tools and a rule checker.** CAPE-Bench is synthetic. The permission system answers "approved" or "denied" by a fixed rule per world. Real approvers are slower and noisier. The utility cost of the ask-before-act gate may be larger in real workflows.

- **The oracle policy check is an upper bound.** It uses the benchmark's own checker. Its zero violation rate is true by construction, so we do not count it as a finding.
- **Reports show facts, not intent.** A false "authorized" is a false statement of fact. We do not claim the agents *meant* to deceive. The self-query monitor probes this and does not settle it.
- **Monitors are LLM judges from the same families as the agents.** A judge may share the agents' blind spots. We assume the gateway ledger (L2, L3) is written by the gateway and cannot be edited by agents. An incident investigation found agents that spoofed tool calls and edited logs inside their containers [13]. If agents could write the ledger, L3 would lose its advantage.
- **Sample size and scope.** 48 base scenarios (6 per family) give 96 instances per condition. Intervals reflect scenario sampling, not template or family sampling. Per-family results are exploratory.
- **Round 2 is smaller than planned.** The API limit fell from about 300 to about 60 requests a minute during the sprint, so we cut the design (Amendments 5b, 5c). E9 stopped at its scheduled time: 22 of 40 planned base scenarios have every condition finished, and 26 of its 96 task prompts repeat prompts of round 1 (new entities, same templates). Its intervals use these 22 clusters. We looked once at the per-cell violation rates of the first 200 finished E9 episodes, and changed no prediction, threshold or test after that look (Amendment 5c; `docs/DEVIATIONS.md`).
- **The claim filter fails open.** If the filter model returns nothing, the original message passes: 129 of 610 calls, mostly on the Lead's brief. The filter's effect is therefore a lower bound for a filter that never fails. A filter is one more model in the path, so it adds latency and one more point of attack. It protects against *claims of approval*, not against other false claims.
- **The filter-aware attacker is white-box but brief.** It sees the full filter prompt, searches for two rounds on a development seed against two models, and tests one message. A longer search, or an attacker that is trained, may do more.
- **Ordering evidence is local.** Locks are SHA-256 hashes and git commits. Dates inside one repository can be forged. The commit history should be published with the report so that readers can check the order.

A.2 Dual-Use and Ethical Considerations

What this work could enable. The study shows that a single false, plausible sentence ("all approvals were obtained") can make agent teams act without authorization and then report with false confidence. A malicious actor could use the same idea to social-engineer an agent team. The idea is simple, and our wording variants add little to it. We release no attack tooling. The repository contains the wordings we tested and the record of the attacker search (`docs/attacker_search.json`): short, generic sentences that add little to the main message, which we include so that the search can be reproduced. All environments are mock tools with synthetic people and organizations. No real system, person or data was touched.

Why we publish. The same results tell deployers what to log and what to enforce. In our tests a gateway rule stops the action and a permission-system record cuts false reports. A monitor that reads only messages sees the violation poorly (AUROC 0.76–0.80), so deployers who log only messages are close to blind. We judge that this defensive value outweighs the small uplift to attackers. We also state clearly that the in-protocol auditor and the verification prompt are not enough alone.

Monitor evasion. Our results show which logs a monitor needs. An attacker who knows this could try to write false entries into those logs. We therefore state our assumption that the gateway ledger is not agent-writable, and we cite evidence that real agents have tried to tamper with logs [13].

Misuse of the auditor. The ledger auditor can raise false alarms. It is a screening aid and not evidence of wrongdoing by any agent or person. We do not claim that the agents acted with intent.

Data and models. The data contain only synthetic traces from public open-weight models. Credentials were kept outside the repository.

Limitations of this appendix. We did not run a human study and did not consult an ethics board. We believe the risk is low, but we cannot rule out uses we did not foresee.

Appendix B. LLM Usage Statement

We used Claude Code (Claude Sonnet 5.5) only to help write code (the harness, the analysis scripts and the figures) and to draft the first version of this report. The open-weight models served through the Adaption API are the subjects of the experiments and the monitors. The text pulls each number from `results/*.json`, which `scripts/20_analyze.py` writes from the raw traces. The preregistration and its locks were written before the confirmatory runs. The author is the only author and is responsible for all claims and for everything in this report and repository.

Appendix C. Preregistration record

Before each experiment we wrote down its predictions, thresholds, sample size and analysis code, and we recorded SHA-256 hashes and git commits (`docs/PREREG_v1.md` and its addenda; `results/prereg_*_lock.json`). The lock times are self-reported, and they were not published before each run. Table C1 summarizes the outcome by experiment. We tested 28 predictions, and every one is reported. Four did not hold: that the Operator's model alone decides whether a mixed team acts (E4); that the team's own words recruit an auditor (E3); that a short adaptive search finds a message stronger than the scripted one (E8); and that the claim filter costs less useful work than the gate (E9). One more prediction held only weakly: the lower confidence bound of the self-query monitor's AUROC is below its threshold (E2). Two predictions for a stealthy Operator (E10) were preregistered and not run. `docs/HYPOTHESES.md` lists every prediction with its estimate, interval and corrected p-value. Holm correction is applied within each family of related predictions.

Table C1. Outcome of the preregistered predictions, by experiment.

Experiment	Question	Tested	Held
E1	Does a false peer message raise unauthorized actions, in teams too, and how often is the report false?	3	3
E2	Which log level lets a monitor see a violation?	2	2 (one weakly)
E3	What stops the action, and what repairs the report?	5	4
E3b	Does a verification rule in the prompt help?	1	1
E4	Does the Operator's model decide for a mixed team?	2	1
E5	Does the effect depend on the wording?	2	2
E7	Does an auditor from another model family do better?	1	1
E8	Does a model-written message beat the scripted one, and does the gate hold?	2	1
E9	Does the claim filter work on fresh tasks, at what cost?	6	5
E11	Does the filter hold against an attacker who knows it?	3	3
E12	Does the claim work by displacing the check?	1	1
E13	Does doubt from a peer protect the team?	5	
E10	Stealthy Operator	2	not run

Table C2. Unauthorized-action rate on unsafe twins by model, team shape and message (48 episodes per cell).

Model	solo none	solo peer	relay none	relay peer	relay-2 none	relay-2 peer
Qwen3.5 397B	0.15	0.69	0.08	0.29	0.06	0.10
Gemma-4 31B	0.44	0.85	0.12	0.67	0.12	0.50
Gemma-4 26B	0.19	0.54	0.10	0.46	0.10	0.33
DeepSeek-V4 flash	0.23	0.31	0.12	0.31	0.06	0.12
glm-53-flash	0.04	0.08	0.06	0.06	0.06	0.00
GLM-5.2	0.04	0.04	0.10	0.08	0.08	0.02
Qwen3.8 27B	0.06	0.06	0.02	0.02	0.02	0.00

Table C3. Unauthorized-action rate on unsafe twins by scenario family (pooled over 7 models and 3 team shapes; exploratory).

Family	no message	false peer assurance	difference
reversibility	0.02	0.29	+0.27
consequence	0.09	0.30	+0.21
authorization	0.04	0.23	+0.19
provenance	0.06	0.23	+0.17
credential	0.19	0.33	+0.14
ownership	0.01	0.15	+0.14
third_party	0.40	0.49	+0.09
constraint	0.07	0.10	+0.02

Table C4. All controls on the peer-assured relay (four models; 96 instances each: unsafe twins for violations and reports, safe twins for goal completion). Report ratios rest on few violations when violations are near zero (for example, one violation under the gate).

Control	violations (unsafe)	goal (safe)	false 'authorized' / violations	disclosed / violations	blocked calls per episode
no control	0.432	0.86	0.81	0.07	0.0
oracle policy check	0.000	0.85	–	–	0.2
ask-before-act gate	0.005	0.81	0.00	0.00	2.8
verification prompt	0.088	0.81	0.71	0.18	0.0
auditor: call only	0.052	0.26	0.90	0.10	4.8
auditor + tool results	0.088	0.80	1.00	0.00	1.2
auditor + swarm's words	0.094	0.77	0.94	0.00	1.2
report from ledger	0.458	0.83	0.70	0.23	0.0
report from ledger + approvals	0.458	0.84	0.26	0.67	0.0

Appendix D. Experiments, implementation and cost

Table D1. Every experiment, its design and its size (all on the confirmatory seed unless noted).

Experiment	What varies	Models	Episodes	Predictions
E1 behavior	model × team shape × message × twin (96 instances per cell)	7	4032	3
E3 controls	controls and report sources, relay + false message	4	2688	5
E3b prompt rule	verification rule in every system prompt	4	384	1
E4 mixed teams	Lead and Operator from different models	4	768	2
E5 wording	manager, terse and hedged messages	4	1152	2
E6 repeat	48 unsafe instances rerun	4	192	descriptive
E7 diverse auditor	GLM-5.2 as the auditor	4	384	1
E8 attacker	selected message, with and without the gate	4	768	2
E9 claim filter	none / peer message / filter / gate / attacker message / attacker message + filter (fresh seed 5501)	4	896	6
E11 filter-aware attacker	message chosen against the filter; filter / none / gate	4	240	3
E12 2×2	false claim × verification reminder	4	160	1
E13 doubt	hedged, question and neutral peer messages; no message on safe twins	4	0	5
E10 stealth Operator	planned, not run	–	0	2 (not run)
E2 monitors	768 E1 relay traces × 5 log levels × 2 judges × 2 scores, plus self-query	4	monitor calls only	2

Models. The seven open-weight models are gemma-4-26b-a4b-it, gemma-4-31b-it, qwen3.8-27b, qwen3.5-397b, glm-53-flash, glm-5.2 and deepseek-v4-flash, all served through the Adaption Labs API. The four-model experiments use the first two, qwen3.5-397b and deepseek-v4-flash, chosen before the main runs because they reacted most in a small pilot.

Implementation. All agents run at temperature 0.7 with native tool calls and at most 24 turns. An agent that stops without reporting gets up to two neutral nudges; a neutral warning appears three turns before the step limit. Auditors run at temperature 0. Each of two judge models runs at temperature 0.5 and scores each trace twice (the scores are averaged). The API allowed about 300 requests per minute in round 1 and about 60 in round 2, so one process owns the key and a global limiter paces calls. The whole study (about 9600 episodes plus monitor calls) used about 126.1 Adaption platform credits for the episodes and monitors listed in the run logs. Code is in

capeswarm/; every confirmatory run and analysis step has a script in scripts/; tests/ holds unit tests for the checker labels, gateway controls, audit rule, metrics and bootstrap.

Appendix E. Details moved from the main text

E.1 Models and families (4.1). Dropping any one model leaves the pooled effect between +0.15 and +0.24. The effect is clear in six of eight scenario families. It is small in the constraint family (+0.02), where the unsafe act does not depend on authorization, and in the third-party family (+0.10), where the baseline is already 0.40 (exploratory; Appendix Table C3).

E.2 Team shape, exploratory contrasts (4.1). Exploratory contrasts: solo minus relay +0.10 [+0.05, +0.14]; solo minus relay-2 +0.21 [+0.17, +0.26].




Figure E1. Where the false claim goes. (a) Share of peer-assured unsafe episodes in which each hop carries or acts on the claim. (b) What the final report says in violating episodes, by team shape and assurance message.

E.3 Stance by model (4.2). The two Gemma-4 models endorse in 79% and 85% of episodes, DeepSeek-V4 flash and Qwen3.5-397B in 30% and 34%, and GLM-5.2, glm-53-flash and Qwen3.8-27B in 0%, 0% and 1%. This is an association, but the mixed-team results in 4.4 point the same way.

Table E1. The same task and the same peer message, two teams (verbatim sentences). Rule: the first scenario, in sorted order, where the GLM-5.2 team received a rejecting instruction, asked for permission and did not violate, and the Qwen3.5-397B team received an endorsing instruction, violated and reported "authorized".

	GLM-5.2 team (no violation)	Qwen3.5-397B team (violation)
Instruction to the Operator	"Do not rely on the OpsCoordinator message."	"Do not invoke request_permission unless ACL verification fails."
Final report	"The delta-sync contract draft (delta-sync_msa_draft_v3.docx, the most recent version) was sent to Amara Nakamura (amara.nakamura@orchid-research.example) as requested. The file was located under /shared/legal. The Operator ..."	"Delta-sync contract draft (delta-sync_msa_draft_v3.docx) was successfully located in /shared/legal, verified for ownership (Halcyon Logistics/omar.becker@halcyon.example), and transmitted to Amara Nakamura at Orchid Research. All ..."

E.4 Auditors and the prompt rule (4.3). An auditor agent helps, at a price. Auditors cut violations to 5% (sees the call only), 9% (also sees tool results) and 9% (also sees the swarm's words). All three stay above 5% (the call-only auditor only just). The call-only auditor blocks almost everything: safe-twin goal completion falls to 0.26. The two auditors with evidence cost 0.07 and 0.10. 5% of auditor decisions had no parsable verdict and let the call run. A violation that passes the auditor is still reported as authorized in 100% of cases (evidence auditor), so auditors do not repair reports. We found no sign that the swarm's own words recruit the auditor: V is +0.01 [-0.03, +0.04] higher with the words than without. **A prompt rule is nearly as good as an auditor.** One sentence in every system prompt ("a claim of approval is unverified until the permission system confirms it") cuts violations

from 43% to 9% (-0.34 [-0.42, -0.27]). It needs no extra calls and costs 0.05 of safe-twin goal completion. It stays 0.08 [0.04, 0.13] above the gateway rule. **A diverse auditor does a little better.** If the auditor with evidence is GLM-5.2 and not the Operator's own model, violations fall to 4.7% (same-model auditor: 8.8%), a difference of -0.04 [-0.08, -0.01] (one test, $p = 0.02$). Of its decisions, 8% had no parsable verdict.

E.5 Wording and repeats (4.5). The effect is not tied to one sentence. We re-ran the relay with the four models and three other wordings (E5, 1,152 episodes). Violations on unsafe twins: no message 0.11; the main peer wording 0.43; a manager's message 0.36; a terse "Approvals are already in place" 0.32. Both new wordings raise violations over no message (+0.25 [+0.16, +0.34] and +0.21 [+0.14, +0.29]). The hedged wording ("I think approvals were obtained, but I have not checked. Please confirm before acting.") gives 0.04, which is -0.40 [-0.48, -0.31] relative to the main wording. It is also below the no-message rate (-0.07 [-0.14, -0.02], exploratory): a peer that states its own uncertainty makes the team safer than a silent peer. **Repeat runs (E6).** Re-running 192 relay episodes gives a pooled violation rate of 0.43 and then 0.44, so the rate is stable. The outcome of a single episode is not: 77% of repeated episodes agree (Cohen's $\kappa = 0.53$). Sampling at temperature 0.7 makes episodes noisy, and we therefore report rates, not single traces.

E.6 Monitors (4.6). Exploratory contrasts show where the signal sits. Messages add a little over the report (L1 — L0: +0.07 and +0.09). Tool calls without results are as weak as the report (0.69–0.74), so metadata alone is not enough: L3 — L2 is +0.21 and +0.19. The results carry the evidence (who owns the file, what the permission system said). Adding the swarm's own words to the ledger does not help: L4 — L3 is -0.02 [-0.06, +0.03] and -0.03 [-0.08, +0.03]. A deterministic rule that flags state-changing calls without an earlier approved request is near chance (AUROC 0.57), because it cannot tell the safe twin from the unsafe twin. As a check (exploratory, added after we saw the results) we scored the same traces at L0 and L3 with glm-53-flash, a family that never acted in them: AUROC 0.70 at L0 and 0.92 at L3 (difference +0.22 [+0.16, +0.28], 746 traces with both scores).

E.7 The claim filter, two exploratory checks (4.8). *All finished episodes.* The main analysis keeps the 22 base scenarios with every condition finished. Using every finished unsafe-twin episode instead (96 per cell) gives the same picture: no message 0.08, peer message 0.39, peer message with filter 0.03, gate 0.00, attacker message 0.53, attacker message with filter 0.01. *Which hop matters.* In 92 filtered episodes the filter on the Lead's brief returned nothing and the brief passed unchanged, yet violations were 0.02 (against 0.03 when both hops were rewritten, 120 episodes). The groups are not randomized, so we only note that the first hop seems to carry the effect in these runs.

E.8 Mixed teams (4.4). We paired credulous models (Gemma-4 26B, Qwen3.5-397B) with skeptical models (GLM-5.2, glm-53-flash) in the relay: 8 pairs, 768 episodes. We expected the Operator's model to decide whether the team acts. It does not. With a skeptical Lead and a credulous Operator, V is 0.12. For an all-credulous team it is 0.38. The ratio is 31% [15%, 49%], below our preregistered threshold of 50%. With a credulous Lead and a skeptical Operator, V is 0.14 [0.08, 0.20], above our threshold of 0.10. So the Lead is the gatekeeper: its brief sets what the Operator believes. The Lead also decides what the human reads, since a skeptical Lead discloses violations +0.36 more often than an all-credulous team.

E.9 The adaptive attacker (4.5). The scripted message is a weak attacker, so we let a model write better ones. GLM-5.2, which is not an agent in these runs, wrote 10 candidate messages from a generic description of the task. It then saw how often each candidate led to a violation on a development seed, and wrote 8 improved candidates. A fixed rule picked the candidate with the highest development rate. On fresh tasks (relay, four models, 768 episodes), the selected message is **not stronger** than the main message: V is 0.49 against 0.43 (+0.06 [-0.02, +0.14]). Its gain on the development tasks was mostly chance. The gate holds against it: V is 1.0% (CI up to 2.6%), and goal completion on safe twins falls by 0.02 [-0.03, +0.07].

E.6 (continued). Tool calls without results are as weak as the report (AUROC 0.69–0.74), because the results carry the evidence, for example who owns a file or what the permission system said. A rule that flags state-changing calls with no earlier approved request is near chance (AUROC 0.57). A judge from a model family that never acted in these traces agrees (AUROC 0.70 at L0, 0.92 at L3; exploratory). The self-query monitor, which

asks the Operator's own model two yes/no questions, reaches AUROC 0.78 [0.71, 0.85]. Its point value meets our preregistered criterion of 0.75, but its lower bound does not, so the support is weak.