

# RELAYSPEC: RETARGETING FROZEN SPECULATIVE DRAFTERS WITH SMALL-DATA LINEAR INTERFACES

**Anonymous authors**

Paper under double-blind review

## ABSTRACT

Feature-conditioned speculative drafters depend on the hidden states of the model used to train them. Reusing such a drafter with a larger target can therefore require running its source model alongside that target. RelaySpec replaces this dependency with a learned linear interface while keeping the target and drafter frozen. Across DFlash and EAGLE-3 drafters retargeted from Qwen3-4B to 8B and 14B, the original 4,096-record fits achieve 2.35–5.11 times autoregressive throughput on MATH-500. Separate EAGLE-3 measurements reduce peak allocated memory by 7.63–7.80 GiB relative to source reuse. Controlled scaling studies show that the interface can be learned from substantially fewer records: frozen 512-example maps retain 97.5% (DFlash) and 98.9% (EAGLE-3) of their 2,048-example maps’ throughput on 256 held-out GSM8K questions with 8B targets. Both confidence intervals exceed 95% retention, although tight accuracy noninferiority remains unresolved. The simple dense map has the highest mapper throughput in the completed 8B long-output capacity comparisons. Wider MLPs and longer fitting do not consistently improve decoding. Under matched warm-training budgets, feature regression outperforms the tested connector-CE and LoRA alternatives. These results identify a low-cost reuse regime and its limits, including task-dependent slowdowns relative to source reuse, optimization sensitivity and finite-precision output differences.

## 1 INTRODUCTION

A developer may have a DFlash drafter trained for Qwen3-4B but want to serve Qwen3-8B or Qwen3-14B. The new target can check its proposals, but supplies different hidden states. This creates a deployment choice: train a new target-specific drafter, or reuse the existing drafter while paying for its source model to provide compatible features. RelaySpec addresses deployments that seek to reuse this training investment with limited additional fitting work. It learns a replacement for the source conditioning path, allowing the new target to supply the drafter’s input. The practical goal is faster generation than plain AR while retaining much of a native target-specific drafter’s throughput.

Speculative decoding accelerates autoregressive (AR) generation by checking several proposed tokens in one target pass (Leviathan et al., 2023). DFlash and EAGLE-3 improve proposals using features computed inside a language model (Chen et al., 2026; Li et al., 2025). We call the model that provided these features during drafter training the *source*. The *target* is the model whose token choices govern deployment. Running the source alongside a new target supplies compatible features, but also retains its transformer computation and memory.

RelaySpec runs the source and new target on shared text during fitting. It learns a linear map from the target’s hidden states to the context that the source supplies to the drafter. At inference, the target already computes these states when checking proposals. Applying the map supplies the next drafting input without another source-transformer pass. The existing target verifier still decides which tokens to commit.

Only the map is trained. The target, drafter, inherited embedding and vocabulary projection stay fixed. The practical value is retaining an existing drafter’s training investment when upgrading the verifier, while eliminating the source transformer from each generation cycle. A small interface is useful only

if it preserves enough proposal quality to make that removal worthwhile. Our experiments test this directly.

Our contribution has three parts. First, we identify and replace the source-conditioning boundary in two released drafter families, obtaining 2.35–5.11 times AR throughput on MATH-500 and separately saving 7.63–7.80 GiB of allocated memory. Second, frozen-checkpoint confirmation shows that 512 fitting examples retain 97.5% and 98.9% of the 2,048-example maps’ speed. Third, we test whether simplicity sacrifices performance: matched linear/MLP capacity sweeps, longer fits, regularization and measured-budget CE/LoRA comparisons make the dense linear interface a strong empirical choice. It achieves the highest mapper throughput in the completed 8B long-output capacity comparisons, and feature regression wins every tested adaptation budget. The insight is that a frozen drafter’s useful prediction behavior can survive a cheap change of conditioning interface. Increasing the expressiveness or training work of that interface need not improve decoding. Domain-composition and 14B experiments identify the limits of this result rather than assuming it holds for every workload.




Figure 1: MATH-500 throughput relative to plain AR, measured within each paired run. RelaySpec reuses the 4B drafter. The native control uses a drafter released for the evaluated target. Whiskers show RelaySpec’s 95% paired intervals. Native controls show the three evaluated releases. Each runtime uses one request per GPU.

## 2 RELATED WORK AND POSITIONING

**Retargeting an inherited drafter.** DFlash and EAGLE-3 condition their proposals on target features (Chen et al., 2026; Li et al., 2025), tying an inherited drafter to its training interface. TriSpec already supports adapter-only finetuning into a fixed EAGLE-family drafter, mapping proxy features to the expected feature space (Jiang et al., 2026). Adapter-only tuning is therefore not our novelty claim. TriSpec uses a proxy to approve some tokens without full-target verification. RelaySpec instead removes the source transformer from generation, retargets its inherited drafter to a larger verifier, and retains target-controlled acceptance. Our contribution is this deployment setting and its measured data, capacity and source-removal behavior across two drafting families.

**Target-independent drafting and dynamic steering.** PARD adapts an autoregressive draft model for parallel token prediction and reuses it across a target family (An et al., 2026). Thus reuse across targets is established prior work. Its target-independent drafter offers zero additional target-specific fitting at deployment. RelaySpec instead makes a small target-specific investment to reuse a feature-conditioned checkpoint and exploit the new target’s internal states.  $SD^2$  is a closer alignment alternative: it computes steering from verifier states and injects it into a pretrained drafter (Berdoz et al., 2026). Our fitted input map replaces source conditioning, whereas  $SD^2$  learns steering within the drafter. The experiments include its public frozen-drafter configuration and PARD’s released checkpoint, with their own matched AR controls (Appendix D). These comparisons expose practical alternatives without attributing differences in runtime or inherited models to the alignment mechanism alone.

**Distillation and drafter adaptation.** OmniDraft uses online hybrid distillation and an n-gram cache to address cross-vocabulary deployment (Ramakrishnan et al., 2025). RelaySpec studies offline fitting with a shared vocabulary, so it does not replace heterogeneous-vocabulary verification (Timor et al., 2025a). RepSpec changes draft training through structural re-parameterization (Huo et al., 2026). VSD optimizes sequence acceptance, and the Draft-OPD preprint studies on-policy teacher feedback (Zou et al., 2026; Lei et al., 2026). These approaches improve a drafter’s learned prediction behavior. RelaySpec holds that behavior fixed and regresses its input context. Our connector-CE and rank-32 LoRA experiments test whether updating token prediction is a better use of the same measured warm-training budget. Feature fitting wins every tested budget comparison (Table 4), which supports this inexpensive adaptation recipe without ruling out other distillation objectives or longer full-drafter training.

**Frozen interfaces and the meaning of feature alignment.** Adapters, low-rank updates and model stitching already adapt or connect frozen networks (Houlsby et al., 2019; Hu et al., 2022; Bansal et al., 2021). A linear connector alone is therefore not the novelty. The contribution is locating an existing speculative decoder’s source-conditioning boundary, learning its replacement while preserving the target and drafter, and establishing the data, capacity and deployment consequences. Successful stitching need not imply equivalent information (Smith et al., 2025). We consequently test decoded speed and quality, equal-capacity linear and nonlinear maps, saved fitting trajectories and frozen-checkpoint confirmation. The observed gaps between training error, validation error and decoding speed are central findings rather than evidence that representation similarity is sufficient.

**Proposal structure and execution are separate axes.** Medusa changes prediction heads, EAGLE-2 and OPT-Tree allocate draft trees, and SpecInfer organizes tree verification (Cai et al., 2024; Li et al., 2024b; Wang et al., 2025; Miao et al., 2024). Self-speculative methods reuse parts of the target itself (Zhang et al., 2024; Elhoushi et al., 2024), while speculative speculative decoding overlaps drafting and verification (Kumar et al., 2026). RelaySpec changes who supplies the drafter’s input, not these execution policies. Its measured advantage is amortizing an inherited drafter with little fitting data and lower source-conditioning cost. We establish this on two drafter families and two target sizes, then identify when extra mapper capacity, optimization or broader training data helps and when it does not.

### 3 PRELIMINARIES

#### 3.1 DRAFTING AND TARGET VERIFICATION

An autoregressive model generates one token at a time. Blockwise and speculative methods propose several tokens, then check them in a target pass (Stern et al., 2018; Xia et al., 2023; Leviathan et al., 2023). In greedy decoding, the verifier commits the longest matching prefix and a target-selected next token. RelaySpec preserves this decoder and changes the features supplied to its drafter.

#### 3.2 THROUGHPUT AND ACCEPTED PROGRESS

Our primary metric is end-to-end output throughput: total generated tokens divided by total request time, including prompt processing. Let  $T_A$ ,  $T_R$  and  $T_N$  denote this throughput for plain AR, RelaySpec and the native target-specific drafter. We report

$$\text{AR speedup} = T_R/T_A, \quad \text{native throughput retained} = 100 T_R/T_N \%. \quad (1)$$

Throughput includes prompt processing. We also report summed AR time relative to summed relay time because output lengths can differ. Accepted progress counts tokens advanced per verification cycle, including the target-supplied token. Removing source computation saves cycle time but can reduce accepted progress. Appendix E specifies this tradeoff and the position-wise acceptance convention.

## 4 METHOD

### 4.1 FIT THE INPUT CONSUMED BY THE FROZEN DRAFTER

We run the source and new target on the same text and collect hidden states after five selected transformer blocks. Concatenating these states gives the target vector  $h_t$  and source vector  $s_t$  at position  $t$ . The drafter’s frozen projection  $F$  converts source features to its input width. We learn a bias-free matrix  $W$  that supplies this input from  $h_t$ . Figure 2 separates fitting from generation.




Figure 2: Fit once, then reuse the frozen drafter. The source and target process identical text during fitting. Only the map is updated. During generation, target features from committed positions feed the next draft.

DFlash consumes normalized projected features, while EAGLE-3 consumes the raw projection. Let  $N_{\text{in}}$  be fixed RMS normalization (Zhang & Sennrich, 2019) and  $N_{\text{out}}$  the released output normalization. Teacher and mapped contexts are

$$\begin{aligned} \text{DFlash: } c_t &= N_{\text{out}}(Fs_t), & \hat{c}_t &= N_{\text{out}}(WN_{\text{in}}(h_t)), \\ \text{EAGLE-3: } c_t &= Fs_t, & \hat{c}_t &= Wh_t. \end{aligned} \quad (2)$$

We fit  $W$  by minimizing the squared context error relative to the teacher’s squared magnitude. For a record with  $n$  token positions,

$$\mathcal{L}(W) = \frac{1}{n} \sum_{t=1}^n \frac{\|\hat{c}_t - c_t\|_2^2}{\max(\|c_t\|_2^2, \epsilon)}. \quad (3)$$

We average token losses within records and records across workers, with  $\epsilon$  the smallest positive normal FP32 value. Teacher-magnitude normalization prevents larger vectors from dominating. The normalized DFlash objective differs from raw linear least squares. The original fits use 4,096 math problem-and-solution conversations, capped at 192 tokens. Supervision is the source context vector. Only  $W$  is updated, with 52.43M/65.54M weights for 8B/14B targets. Appendix A gives dimensions, layers and fitting settings.

### 4.2 DRAFT WITH THE NEW TARGET’S FEATURES

The target caches prompt states, and the map supplies the frozen drafter’s context. The target verifies proposals in parallel, commits the matching prefix plus its next token, and crops the cache to the committed prefix. Mapped states feed the next cycle (Figure 6).

The standard greedy equivalence argument requires block verification to return the same token choices as single-token evaluation of each identical prefix (Leviathan et al., 2023). Finite-precision implementations can change those choices. We therefore measure task accuracy and token agreement separately from throughput. The map itself never supplies the scores used for target verification.

## 5 EXPERIMENTS

### 5.1 EXPERIMENTAL SETUP

**Models and runtime.** We retarget the released Qwen3-4B DFlash and DeepSpec EAGLE-3 drafters to Qwen3-8B and Qwen3-14B (Yang et al., 2025; DeepSeek-AI, 2026). DFlash uses block length 16. EAGLE-3 uses the supported chain procedure with seven draft positions. Native controls use released target-specific drafters within the same implementation and proposal setting. The main AR comparisons use four NVIDIA L40S GPUs, with one sequential request per worker. Historical block-size and isolated-memory studies use RTX 6000 Ada GPUs. We compare methods within runs on the same hardware. Serving systems such as vLLM and SGLang also optimize cache use and request execution (Kwon et al., 2023; Zheng et al., 2024). We measure one request per worker. Table 6 gives the full protocol.

**Workloads and data use.** We evaluate math, code and conversation workloads because speculative speed varies across tasks (Xia et al., 2024; Abramovich et al., 2026). MATH-500 supplies 500 questions (Lightman et al., 2024). The breadth suite contains 128 GSM8K questions, 164 HumanEval tasks, 378 MBPP tasks and 80 two-turn MT-Bench conversations (Hendrycks et al., 2021; Cobbe et al., 2021; Chen et al., 2021; Austin et al., 2021; Zheng et al., 2023). The 32-question development set informed interface and loss choices. Historical evaluations retain this exposure history. Fitting and evaluation problem texts have zero normalized exact matches. Appendix H quantifies related templates using token overlap. All completed workload cells in each reported suite are included.

**Controlled scaling protocol.** The original 4,096-record checkpoints remain fixed for the broad workload results. A fixed-1,024-update sweep varies distinct records from 64 to 4,096. A separate NuminaMath study uses nested 16–32,768-record sets, 1,024 feature-validation records and 8,192 batch-four updates per fit. Frozen feature caches are shared across matched linear and MLP fits. The longer-output capacity comparisons use 128 exposed MATH questions and a 2,048-token cap. The 14B capacity and adaptation screens use sixteen exposed questions and a 256-token cap. These studies have separate checkpoints and are not pooled with the broad evaluation.

**Quality and pairing.** We score the same math outputs used for the AR timing comparison with the pinned Qwen math scorer. Historical code comparisons use EvalPlus base and expanded tests (Liu et al., 2023). MT-Bench measures two-turn generation time, with each method conditioning its second turn on its own first answer. Its bootstrap unit is the conversation. Other confidence intervals resample matched requests and condition on the fitted checkpoint. Model loading and external task scoring sit outside the request timer.

### 5.2 ACCELERATION OVER PLAIN AUTOREGRESSIVE DECODING

Table 1 reports absolute end-to-end throughput and AR-relative speed. DFlash RelaySpec reaches 186.49 tokens/s at 8B and 116.88 at 14B, compared with AR at 37.37 and 22.88. EAGLE-3 RelaySpec reaches 84.92 and 59.18 tokens/s, compared with 36.15 and 22.88 for AR. The resulting throughput ratios are 4.99, 5.11, 2.35 and 2.59. Each paired interval is above one.

Table 1: MATH-500 end-to-end tokens/s, including prompt processing. Progress R is mean recorded relay progress per cycle. Ratios and intervals use the AR arm of that same run. Native-drafter comparisons are in Table 8.

| Drafter | Target | AR tok/s | Source tok/s | Relay tok/s | Relay / AR [95% CI] | Progress R |
|---------|--------|----------|--------------|-------------|---------------------|------------|
| DFlash  | 8B     | 37.37    | 121.81       | 186.49      | 4.99 [4.88, 5.10]   | 6.98       |
| DFlash  | 14B    | 22.88    | 92.15        | 116.88      | 5.11 [4.98, 5.23]   | 6.49       |
| EAGLE-3 | 8B     | 36.15    | 66.44        | 84.92       | 2.35 [2.32, 2.38]   | 4.33       |
| EAGLE-3 | 14B    | 22.88    | 53.96        | 59.18       | 2.59 [2.55, 2.63]   | 4.01       |

DFlash uses parallel proposals and the EAGLE-3 path drafts sequentially. These released-model comparisons also use different library versions, so cross-family speed does not isolate architecture.

### 5.3 NATIVE RETENTION AND SOURCE REMOVAL

RelaySpec retains 90.3% of native DFlash-8B throughput, reaching 186.49 versus 206.58 tokens/s. EAGLE-3 retains 90.2% at 8B and 89.1% at 14B (Table 8). These compare released drafters, not matched original training costs. Retained progress is lower than retained throughput because per-cycle work also differs: DFlash-8B advances 6.98 tokens per relay cycle versus 7.89 for native drafting.

Against source reuse, the relay’s throughput ratios are 1.531 and 1.268 for DFlash, and 1.278 and 1.097 for EAGLE-3, at 8B and 14B respectively. This comparison holds the inherited drafter fixed. Source computation is removed from each cycle, while retained target states supply the context at the scale tested in Section 5.7.

### 5.4 MATH ACCURACY AND OUTPUT AGREEMENT

Table 2 scores the exact outputs timed in Table 1. Observed AR-to-relay accuracy differences range from  $-0.2$  to  $+0.8$  percentage points, and each paired interval includes zero. These measured outcomes support the accuracy comparison without treating token equality as a substitute for task quality.

Table 2: MATH-500 accuracy in percent. Difference is RelaySpec minus AR in percentage points. Token matches count identical full output sequences.

| Drafter | Target | AR score | Relay score | Difference [95% CI] | Token matches |
|---------|--------|----------|-------------|---------------------|---------------|
| DFlash  | 8B     | 75.8     | 76.6        | +0.8 [-1.4, +3.0]   | 117/500       |
| DFlash  | 14B    | 79.2     | 79.2        | +0.0 [-2.2, +2.0]   | 113/500       |
| EAGLE-3 | 8B     | 75.8     | 75.6        | -0.2 [-2.4, +2.0]   | 135/500       |
| EAGLE-3 | 14B    | 79.2     | 79.4        | +0.2 [-1.8, +2.2]   | 106/500       |

In BF16, AR and block verification can select different tokens on an identical prefix. Traces of eight selected DFlash early-divergence prompts show changes in the leading target scores shared by native drafting, source reuse and RelaySpec. This diagnostic is separate from the timed runs. We report measured quality and agreement rather than claiming bitwise identity from the verifier’s mathematical contract.

### 5.5 SPEED ACROSS WORKLOADS

Figure 3 and Table 9 report the completed DFlash AR-paired breadth suite. RelaySpec is 1.85–3.69 times faster than AR across these eight cells. Code gains at 14B remain substantial relative to AR even where source reuse is faster than the relay. The useful comparison depends on the deployment choice: AR measures the acceleration obtained, while source reuse measures the benefit of removing its source.




Figure 3: DFlash RelaySpec throughput relative to AR across workloads. Whiskers are paired 95% intervals. Chat intervals resample whole two-turn conversations. Full absolute values are in Table 9.

## 5.6 FITTING WORK AND DEPLOYMENT MEMORY

The selected maps have 52.43–65.54M weights. Fitting takes 85.6–118.5 seconds on four RTX 6000 Ada GPUs after model loading, including feature computation and optimization. Loading, export and deployment initialization are separate costs (Appendix I).

Separate EAGLE-3 processes measure memory after removing source layers. Peak allocated memory falls from 25.56 to 17.76 GiB at 8B and from 37.56 to 29.94 GiB at 14B. These are savings of 7.80 and 7.63 GiB. Source token embeddings and vocabulary projections required by a drafter remain part of deployment. The claim concerns the removed source transformer, not every tensor inherited from the source.

## 5.7 ABLATION STUDIES

### 5.7.1 HOW MUCH DATA AND MAPPER CAPACITY ARE NEEDED?

We separate distinct training examples from optimization work. With 8,192 batch-four updates held fixed, the NuminaMath sweep spans 16 to 32,768 distinct records. DFlash-8B throughput rises from 96.9 tokens/s at 16 examples to 192.8 at 512, then ranges from 196.9 to 198.4 at 2,048–32,768 (Figure 4). Thus 16 examples already give  $2.58\times$  AR throughput, and 512 retain 97.2% of the observed best. All eleven mappers score 105/128. These are single-seed development results, not a universal minimum-data threshold. Appendix C retains the separate historical MATH-only study.




Figure 4: DFlash-8B data scaling on 128 development questions, with NuminaMath training and 8,192 updates per fit. All dataset sizes are measured with shared controls in one campaign. Paired 95% request intervals exclude fitting-seed variation and selection uncertainty.

The NuminaMath capacity study crosses 512/2,048 examples with dense, factored linear and GELU MLP maps over seven widths, using 8,192 updates per cell. This holds parameter count equal between each factored map and MLP. Validation error decreases with capacity and then flattens (Figure 5). The measured 128-question, 2,048-token decoding comparison gives dense  $N = 512$  193.68 tokens/s versus 198.09 for dense  $N = 2048$ , retaining 97.78% [97.09, 98.47]%. Linear-1024 at  $N = 512$  retains 95.00% [94.14, 95.85]% with 23.59M parameters instead of 52.43M. The latter interval crosses the 95% boundary. These are development comparisons with fixed fitting seeds.

EAGLE-3 repeats the dense data-count contrast on the same development questions, retaining 98.28% [97.59, 99.01]%. Its matched MLP remains slower than dense. Table 25 retains all eight maps.

**Confirmation with frozen checkpoints.** Before generating confirmation outputs, we fix the dense checkpoints and analysis criteria, then evaluate 256 GSM8K questions excluded from the recorded development history (Table 3). Both families exceed the predeclared 95% speed-retention threshold. The two data sizes have identical per-question correctness within each family. Relative to AR, conservative accuracy-difference intervals are  $[-3.07, 3.07]$  points for DFlash and  $[-1.63, 3.14]$  for EAGLE-3. Neither establishes the one-point noninferiority margin.

Table 3: Frozen small-data confirmation on 256 GSM8K questions. Retention is a percentage relative to the 2,048-example mapper in the same family, with paired 95% intervals. Outputs are capped at 2,048 tokens.

| Family  | Examples | Tokens/s | Retention (95% CI) | Correct | At cap |
|---------|----------|----------|--------------------|---------|--------|
| DFlash  | 512      | 157.8    | 97.5 [96.9,98.1]   | 236/256 | 0      |
| DFlash  | 2,048    | 161.9    | 100 (reference)    | 236/256 | 0      |
| EAGLE-3 | 512      | 100.0    | 98.9 [98.1,99.7]   | 238/256 | 0      |
| EAGLE-3 | 2,048    | 101.1    | 100 (reference)    | 238/256 | 0      |




Figure 5: Complete primary capacity study at 8,192 updates per cell. Markers compare validation interface error, with one fitting seed. The curves do not establish decoding speed or answer quality.

**Better feature fitting need not mean faster decoding.** The 94.37M-parameter MLP-4096 at  $N = 2048$  reaches 190.15 tokens/s, below dense. Extending the width-512 MLP from 8,192 to 32,768 updates on the same 2,048 records raises throughput only from 154.39 to 157.68. All tested mappers score 105/128 at this cap, versus AR’s 104/128, which does not establish a one-percentage-point noninferiority margin. The regularization study finds no matched endpoint benefit from its L2 settings and only small weight-decay gains in feature validation. The dense linear map has the highest mapper throughput in both completed 8B long-output capacity comparisons. Thus its simplicity is supported by measured alternatives, including equal-capacity nonlinear maps, rather than assumed from parameter count. All outcomes remain in the appendix.

**Replication and workload dependence.** The complete 14B grids repeat the small-data/capacity comparison in both drafter families. DFlash’s wide MLP fits its training features better than dense but has worse validation error and lower capped decoding throughput. EAGLE-3 shows late degradation in both dense 512-example seeds and a transient wide-linear loss spike. These results delimit the shared optimization recipe rather than prove a disadvantage of a function class (Appendix C.6). On the 8B capped long-output development set, dense  $N = 512$  retains 97.4–97.9% of dense  $N = 2048$  throughput across MATH difficulty groups. Very long inputs have too few examples for a reliable generalization claim.

**Training composition changes the speed tradeoff.** Replacing half of 2,048 math records with general instructions reduces dense general-domain feature error by 32.9% but raises math error by 10.2%. Code and chat throughput improve by 2.9% and 4.9%, while MATH throughput falls 1.2%. A second seed repeats this pattern. Matched arms generate identical tokens on all 160 development requests. The smaller maps show larger math/chat tradeoffs (Appendix F).

### 5.7.2 FEATURE FITTING WINS THE MATCHED ADAPTATION COMPARISONS

Feature regression achieves the highest throughput at every tested warm budget (Table 4). The comparison fixes 512 training records, charges CE and LoRA for their initial mapper, and gives each



an equal three-rate development screen. Across all three budgets, CE retains 73.2–76.6% and the two LoRA fits retain 79.4–82.7% of feature throughput. Every paired 95% interval lies below parity. This supports feature regression as the best tested adaptation under these budgets. The sixteen-question, 256-token screen does not establish full-answer quality or the ranking of other objectives. Cache preparation and export remain separate costs (Appendix C.7).

Table 4: Decoding tokens/s after matched warm-training budgets, using one common DFlash-8B runtime and the same 512 records. Columns are nominal training seconds. Bold marks the best tested adaptation in each column. All twelve fits and paired intervals appear in Table 29.

| Adaptation    | 22.9 s        | 91.4 s        | 365.6 s       |
|---------------|---------------|---------------|---------------|
| Feature MSE   | <b>145.05</b> | <b>144.80</b> | <b>144.55</b> |
| Connector CE  | 111.04        | 109.60        | 105.79        |
| LoRA32 (1729) | 119.30        | 115.02        | 118.49        |
| LoRA32 (1730) | 119.52        | 115.49        | 119.55        |

**Public-runtime baselines.** Table 5 places the completed public baselines beside RelaySpec. The relay has the highest measured throughput, but the separate runtime controls prevent an algorithm-only ranking. Table 31 distinguishes their adaptation mechanisms.

Table 5: Public-runtime comparison on 128 MATH development questions, 2,048-token cap. Correct counts are out of 128, with each system’s AR in parentheses. Precision, attention and libraries differ, so speedups use own-runtime AR. Settings and paired quality uncertainty appear in Appendix D.

| System                           | Tok/s  | Own AR tok/s | Speedup [95% CI]  | Correct (AR) |
|----------------------------------|--------|--------------|-------------------|--------------|
| RelaySpec ( $N = 512$ )          | 193.68 | 37.72        | 5.14 [4.90, 5.37] | 105 (104)    |
| PARD                             | 105.63 | 31.67        | 3.34 [3.22, 3.45] | 105 (103)    |
| SD <sup>2</sup> (frozen drafter) | 19.92  | 12.48        | 1.60 [1.56, 1.63] | 103 (103)    |

## 6 CONCLUSION

RelaySpec makes an existing feature-conditioned drafter useful with a larger verifier by learning one replacement input map. Its value is the combination of retained drafting behavior, removed source-transformer cost and little additional fitting data. Dense linear mapping is a competitive choice after testing nonlinear capacity, longer optimization, regularization and token-prediction adaptation. The experiments support a practical strategy: first fit the inherited interface cheaply, then spend additional adaptation work only when measured decoding warrants it. Mixed-domain fitting further shows that data composition can improve code/chat speed while trading away math performance.

These conclusions concern shared-vocabulary Qwen3 models, greedy decoding and one request per worker. Code workloads can favor source reuse, and EAGLE-3 optimization depends on the recipe. Frozen GSM8K confirmation supports speed retention but not tight accuracy noninferiority. Development exposure, possible shared math templates and limited fitting seeds restrict generalization. The 14B capacity and adaptation screens remain capped comparisons, and public-runtime baselines do not isolate an algorithm-only ranking.

## AI USE STATEMENT

Generative AI assisted with implementation, code review, literature search, analysis and manuscript editing. Numerical tables and plots are generated from recorded artifacts with checked method, request and scorer identity. Scientific interpretation and submission decisions remain the authors’ responsibility.

## REPRODUCIBILITY STATEMENT

The appendix specifies model identifiers, feature layers, fitting settings, measurement boundaries, complete workload results and data checks. The accompanying implementation includes configurations, request records, scorer provenance and scripts that regenerate the reported assets.

## REFERENCES

- Talor Abramovich, Maor Ashkenazi, Izzy Putterman, Benjamin Chislett, Tiya Mitra, Bitu Darvish Rouhani, Ran Zilberstein, and Yonatan Geifman. SPEED-Bench: A unified and diverse benchmark for speculative decoding. In *43rd International Conference on Machine Learning*, 2026. URL <https://arxiv.org/abs/2604.09557>. Accepted paper.
- Zihao An, Huajun Bai, Ziqiong Liu, Dong Li, and Emad Barsoum. PARD: Accelerating LLM inference with low-cost PARallel draft model adaptation. In *International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=XbOyv7iVGL>.
- Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*, 2021. URL <https://arxiv.org/abs/2108.07732>.
- Yamini Bansal, Preetum Nakkiran, and Boaz Barak. Revisiting model stitching to compare neural representations. In *Advances in Neural Information Processing Systems 34*, 2021. URL <https://papers.nips.cc/paper/2021/hash/01ded4259d101feb739b06c399e9cd9c-Abstract.html>.
- Frédéric Berdoz, Peer Rheinboldt, and Roger Wattenhofer. Steering pretrained drafters during speculative decoding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pp. 30067–30075, 2026. doi: 10.1609/aaai.v40i36.40255. URL <https://ojs.aaai.org/index.php/AAAI/article/view/40255>.
- Tianle Cai, Yuhong Li, Zhengyang Geng, Hongwu Peng, Jason D. Lee, Deming Chen, and Tri Dao. Medusa: Simple LLM inference acceleration framework with multiple decoding heads. In *Proceedings of the 41st International Conference on Machine Learning*, 2024. URL <https://proceedings.mlr.press/v235/cai24b.html>.
- Jian Chen, Yesheng Liang, and Zhijian Liu. DFlash: Block diffusion for flash speculative decoding. In *43rd International Conference on Machine Learning*, 2026. URL <https://arxiv.org/abs/2602.06036>. Accepted paper.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021. URL <https://arxiv.org/abs/2107.03374>.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021. URL <https://arxiv.org/abs/2110.14168>.
- DeepSeek-AI. DeepSpec: A full-stack codebase for training and evaluating speculative decoding draft models. Official open-source software, 2026. URL <https://github.com/deepseek-ai/DeepSpec>.
- Mostafa Elhoushi, Akshat Shrivastava, Diana Liskovich, Basil Hosmer, Bram Wasti, Liangzhen Lai, Anas Mahmoud, Bilge Acun, Saurabh Agarwal, Ahmed Roman, Ahmed Aly, Beidi Chen, and Carole-Jean Wu. LayerSkip: Enabling Early Exit Inference and Self-Speculative Decoding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024. URL <https://aclanthology.org/2024.acl-long.681/>.

- Yichao Fu, Peter Bailis, Ion Stoica, and Hao Zhang. Break the Sequential Dependency of LLM Inference Using Lookahead Decoding. In *Proceedings of the 41st International Conference on Machine Learning*, 2024. URL <https://proceedings.mlr.press/v235/fu24a.html>.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *Advances in Neural Information Processing Systems 34, Datasets and Benchmarks Track*, 2021. URL <https://openreview.net/forum?id=7Bywt2mQsCe>.
- Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin De Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-Efficient Transfer Learning for NLP. In *Proceedings of the 36th International Conference on Machine Learning*, 2019. URL <https://proceedings.mlr.press/v97/houlsby19a.html>.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-Rank Adaptation of Large Language Models. In *International Conference on Learning Representations*, 2022. URL <https://www.microsoft.com/en-us/research/publication/lora-low-rank-adaptation-of-large-language-models/>.
- Shijing Hu, Jingyang Li, Xingyu Xie, Zhihui Lu, Kim-Chuan Toh, and Pan Zhou. GRIFFIN: Effective token alignment for faster speculative decoding. In *Advances in Neural Information Processing Systems*, 2025. URL [https://proceedings.neurips.cc/paper\\_files/paper/2025/hash/b6e67ae290635d0874c4cb43ba2a2cfb-Abstract-Conference.html](https://proceedings.neurips.cc/paper_files/paper/2025/hash/b6e67ae290635d0874c4cb43ba2a2cfb-Abstract-Conference.html).
- Feiye Huo, Jianchao Tan, Jiahao Liu, Zixu Jiang, Jiacheng Li, Jingang Wang, Xunliang Cai, and Shengli Sun. RepSpec: Structural re-parameterized draft model training for speculative decoding. In *International Conference on Learning Representations*, 2026. URL [https://proceedings.iclr.cc/paper\\_files/paper/2026/hash/d70ea003729b440b89a2f958a5554c1f-Abstract-Conference.html](https://proceedings.iclr.cc/paper_files/paper/2026/hash/d70ea003729b440b89a2f958a5554c1f-Abstract-Conference.html).
- Haoyun Jiang, Junqi He, Feng Hong, Xinlong Yang, Jianwei Zhang, Zheng Li, Zhengyang Zhuge, Zhiyong Chen, Bo Han, Junyang Lin, and Jiangchao Yao. TriSpec: Ternary speculative decoding via lightweight proxy verification. *arXiv preprint arXiv:2601.23180*, 2026. doi: 10.48550/arXiv.2601.23180. URL <https://arxiv.org/abs/2601.23180>.
- Tanishq Kumar, Tri Dao, and Avner May. Speculative speculative decoding. In *International Conference on Learning Representations*, 2026. URL [https://proceedings.iclr.cc/paper\\_files/paper/2026/hash/1b96f01343ff10150e6719eb163e1536-Abstract-Conference.html](https://proceedings.iclr.cc/paper_files/paper/2026/hash/1b96f01343ff10150e6719eb163e1536-Abstract-Conference.html).
- Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient Memory Management for Large Language Model Serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, 2023. URL <https://doi.org/10.1145/3600006.3613165>.
- Haodi Lei, Yafu Li, Haoran Zhang, Shunkai Zhang, Qianjia Cheng, Xiaoye Qu, Ganqu Cui, Bowen Zhou, Ning Ding, Yun Luo, and Yu Cheng. Draft-OPD: On-policy distillation for speculative draft models. *arXiv preprint arXiv:2605.29343*, 2026. URL <https://arxiv.org/abs/2605.29343>.
- Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 19274–19286, 2023. URL <https://proceedings.mlr.press/v202/leviathan23a.html>.
- Yuhui Li, Fangyun Wei, Chao Zhang, and Hongyang Zhang. EAGLE: Speculative Sampling Requires Rethinking Feature Uncertainty. In *Proceedings of the 41st International Conference on Machine Learning*, 2024a. URL <https://proceedings.mlr.press/v235/li24bt.html>.

- Yuhui Li, Fangyun Wei, Chao Zhang, and Hongyang Zhang. EAGLE-2: Faster Inference of Language Models with Dynamic Draft Trees. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 2024b. URL <https://aclanthology.org/2024.emnlp-main.422/>.
- Yuhui Li, Fangyun Wei, Chao Zhang, and Hongyang Zhang. EAGLE-3: Scaling up inference acceleration of large language models via training-time test. In *Advances in Neural Information Processing Systems* 38, 2025. URL [https://proceedings.neurips.cc/paper\\_files/paper/2025/hash/c7b5a35ea98b62512a869c19ea7b03cb-Abstract-Conference.html](https://proceedings.neurips.cc/paper_files/paper/2025/hash/c7b5a35ea98b62512a869c19ea7b03cb-Abstract-Conference.html).
- Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let’s verify step by step. In *International Conference on Learning Representations*, 2024. URL [https://proceedings.iclr.cc/paper\\_files/paper/2024/hash/aca97732e30bcf1303bc22ac3924fd16-Abstract-Conference.html](https://proceedings.iclr.cc/paper_files/paper/2024/hash/aca97732e30bcf1303bc22ac3924fd16-Abstract-Conference.html).
- Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. Is your code generated by ChatGPT really correct? rigorous evaluation of large language models for code generation. In *Advances in Neural Information Processing Systems* 36, 2023. URL [https://proceedings.neurips.cc/paper\\_files/paper/2023/hash/43e9d647ccd3e4b7b5baab53f0368686-Abstract-Conference.html](https://proceedings.neurips.cc/paper_files/paper/2023/hash/43e9d647ccd3e4b7b5baab53f0368686-Abstract-Conference.html).
- Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL <https://arxiv.org/abs/1711.05101>.
- Xupeng Miao, Gabriele Oliaro, Zhihao Zhang, Xinhao Cheng, Zeyu Wang, Zhengxin Zhang, Rae Ying Yee Wong, Alan Zhu, Lijie Yang, Xiaoxiang Shi, Chunan Shi, Zhuoming Chen, Daiyaan Arfeen, Reyna Abhyankar, and Zhihao Jia. SpecInfer: Accelerating Large Language Model Serving with Tree-based Speculative Inference and Verification. In *Proceedings of the 29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 3*, 2024. URL <https://arxiv.org/abs/2305.09781>.
- Ramchalam Kinattinkara Ramakrishnan, Zhaocong Yuan, Shaojie Zhuo, Chen Feng, Yicheng Lin, Chenzheng Su, and Xiaopeng Zhang. OmniDraft: A cross-vocabulary, online adaptive drafter for on-device speculative decoding. In *Advances in Neural Information Processing Systems*, 2025. URL [https://proceedings.neurips.cc/paper\\_files/paper/2025/hash/3c2fe1417eed1c6ff9acf169617981ea-Abstract-Conference.html](https://proceedings.neurips.cc/paper_files/paper/2025/hash/3c2fe1417eed1c6ff9acf169617981ea-Abstract-Conference.html).
- Damian Smith, Harvey Mannerling, and Antonia Marcu. Functional alignment can mislead: Examining model stitching. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 55972–55998, 2025. URL <https://proceedings.mlr.press/v267/smith25a.html>.
- Mitchell Stern, Noam Shazeer, and Jakob Uszkoreit. Blockwise Parallel Decoding for Deep Autoregressive Models. In *Advances in Neural Information Processing Systems* 31, 2018. URL <https://proceedings.neurips.cc/paper/2018/hash/c4127b9194fe8562c64dc0f5bf2c93bc-Abstract.html>.
- Nadav Timor, Jonathan Mamou, Daniel Korat, Moshe Berchansky, Gaurav Jain, Oren Pereg, Moshe Wasserblat, and David Harel. Accelerating LLM inference with lossless speculative decoding algorithms for heterogeneous vocabularies. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025a. URL <https://proceedings.mlr.press/v267/timor25a.html>.
- Nadav Timor, Jonathan Mamou, Daniel Korat, Moshe Berchansky, Oren Pereg, Moshe Wasserblat, Tomer Galanti, Michal Gordon-Kiwkowitz, and David Harel. Distributed speculative inference: Speculation parallelism for provably faster lossless language model inference. In *International Conference on Learning Representations*, 2025b. URL [https://proceedings.iclr.cc/paper\\_files/paper/2025/hash/b36554b97da741b1c48c9de05c73993e-Abstract-Conference.html](https://proceedings.iclr.cc/paper_files/paper/2025/hash/b36554b97da741b1c48c9de05c73993e-Abstract-Conference.html).

- Jikai Wang, Yi Su, Juntao Li, Qingrong Xia, Zi Ye, Xinyu Duan, Zhefeng Wang, and Min Zhang. OPT-Tree: Speculative Decoding with Adaptive Draft Tree Structure. *Transactions of the Association for Computational Linguistics*, 2025. URL <https://aclanthology.org/2025.tacl-1.8/>.
- Heming Xia, Tao Ge, Peiyi Wang, Si-Qing Chen, Furu Wei, and Zhifang Sui. Speculative Decoding: Exploiting Speculative Execution for Accelerating Seq2seq Generation. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023. URL <https://aclanthology.org/2023.findings-emnlp.257/>.
- Heming Xia, Zhe Yang, Qingxiu Dong, Peiyi Wang, Yongqi Li, Tao Ge, Tianyu Liu, Wenjie Li, and Zhifang Sui. Unlocking Efficiency in Large Language Model Inference: A Comprehensive Survey of Speculative Decoding. In *Findings of the Association for Computational Linguistics: ACL 2024*, 2024. URL <https://aclanthology.org/2024.findings-acl.456/>.
- An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025. URL <https://arxiv.org/abs/2505.09388>.
- Biao Zhang and Rico Sennrich. Root Mean Square Layer Normalization. In *Advances in Neural Information Processing Systems 32*, 2019. URL <https://proceedings.neurips.cc/paper/2019/hash/1e8a19426224ca89e83cef47f1e7f53b-Abstract.html>.
- Jun Zhang, Jue Wang, Huan Li, Lidan Shou, Ke Chen, Gang Chen, and Sharad Mehrotra. Draft & Verify: Lossless Large Language Model Acceleration via Self-Speculative Decoding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024. URL <https://aclanthology.org/2024.acl-long.607/>.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-Bench and chatbot arena. In *Advances in Neural Information Processing Systems 36, Datasets and Benchmarks Track*, 2023. URL [https://proceedings.neurips.cc/paper\\_files/paper/2023/hash/91f18a1287b398d378ef22505bf41832-Abstract-Datasets\\_and\\_Benchmarks.html](https://proceedings.neurips.cc/paper_files/paper/2023/hash/91f18a1287b398d378ef22505bf41832-Abstract-Datasets_and_Benchmarks.html).
- Lianmin Zheng, Liangsheng Yin, Zhiqiang Xie, Chuyue Sun, Jeff Huang, Cody Hao Yu, Shiyi Cao, Christos Kozyrakis, Ion Stoica, Joseph E. Gonzalez, Clark Barrett, and Ying Sheng. SGLang: Efficient Execution of Structured Language Model Programs. In *Advances in Neural Information Processing Systems 37*, 2024. URL [https://proceedings.neurips.cc/paper\\_files/paper/2024/hash/724be4472168f31balc9ac630f15dec8-Abstract-Conference.html](https://proceedings.neurips.cc/paper_files/paper/2024/hash/724be4472168f31balc9ac630f15dec8-Abstract-Conference.html).
- Xiandong Zou, Jianshu Li, Jing Huang, and Pan Zhou. Variational speculative decoding: Rethinking draft training from token likelihood to sequence acceptance. In *Proceedings of the 43rd International Conference on Machine Learning*, 2026. URL [https://ink.library.smu.edu.sg/sis\\_research/11190/](https://ink.library.smu.edu.sg/sis_research/11190/).

## APPENDIX

The appendix gives implementation details (Appendix A), complete workload results (Appendix B), fitting studies (Appendix C), acceptance measurements (Appendix E), data checks (Appendix H) and fitting-time and memory measurements (Appendix I).

### A IMPLEMENTATION AND MEASUREMENT DETAILS

Table 6: Evaluation protocol. Main fitting choices remain fixed across workloads. Full identifiers and runtime versions are in Appendix A.

| Component        | Setting                                                                                            |
|------------------|----------------------------------------------------------------------------------------------------|
| Primary baseline | Plain greedy AR with the same target, prompt and runtime                                           |
| Other controls   | Native target-specific drafter and optimized source reuse                                          |
| Generation       | BF16, SDPA attention, thinking disabled, maximum 2,048 new tokens                                  |
| Relay fitting    | 4,096 records, 192-token cap, 1,024 AdamW updates (Loshchilov & Hutter, 2019), four records/update |
| Optimizer        | Learning rate $6 \times 10^{-4}$ , zero weight decay, gradient clipping 1.0                        |
| Timing           | Synchronized request timer, warmup excluded, rotated method order                                  |
| Uncertainty      | 10,000 paired resamples, whole conversations for two-turn chat                                     |

**Released models.** The source is Qwen/Qwen3-4B. Targets are Qwen/Qwen3-8B and Qwen/Qwen3-14B. The source DFlash is z-lab/Qwen3-4B-DFlash-b16, and its native 8B control is z-lab/Qwen3-8B-DFlash-b16. EAGLE-3 uses DeepSpec’s eagle3\_qwen3\_4b\_ttt7, eagle3\_qwen3\_8b\_ttt7 and eagle3\_qwen3\_14b\_ttt7 releases. All model and upstream revisions are fixed in the accompanying configurations.

**Features and dimensions.** Layer indices count transformer blocks from zero. Source and Qwen3-8B states come from blocks [1, 9, 17, 25, 33]. Qwen3-14B states come from [1, 10, 19, 28, 37]. Joining five 4,096-wide states gives a 20,480-wide 8B input. Joining five 5,120-wide states gives a 25,600-wide 14B input. Both drafter interfaces have width 2,560. The matrix dimensions are therefore  $2,560 \times 20,480$  and  $2,560 \times 25,600$ . The DFlash input normalization has no trainable gain or bias. The released output normalization remains frozen.

**Training.** Four workers average record losses at each update. Seed 1729 fixes the selected fit. AdamW uses learning rate 0.0006, zero weight decay and gradient clipping at 1.0. Computation uses BF16, with the feature loss computed in FP32. Each of 1,024 updates processes four records, each capped at 192 rendered tokens. The same map remains fixed across tasks.

**Runtime and timing.** The main AR runs use Python 3.12.13 and PyTorch 2.9.1 with CUDA 12.8. DFlash uses Transformers 5.3.0. EAGLE-3 uses the pinned 5.10.2 overlay. Each worker owns a full target replica on one L40S GPU. Four workers process independent requests rather than splitting one model over GPUs. One warmup per method precedes measured requests. Method order rotates across requests. The synchronized timer includes prompt processing, drafting, verification, feature updates and runtime bookkeeping. The historical block and memory experiments use RTX 6000 Ada GPUs.




Figure 6: One generation cycle. RelaySpec changes the drafter’s context. The target retains control over committed tokens and the shared decoder retains responsibility for positions, stopping and cache updates.

**Stopping and conversation history.** Generation stops at the first end token or the output cap. Capped requests remain in both timing and quality aggregates. Each MT-Bench method uses its own first-turn output as second-turn context. Two turns form one resampling unit. The breadth run has 750 initial records and 830 timed requests after expanding 80 conversations to two turns.

**Aggregation.** Each method’s throughput is the sum of its output-token counts divided by the sum of its request times. Each of 10,000 resamples recomputes this ratio from matched requests, using bootstrap seed 1729. Confidence bounds are the central 95% of resampled estimates. The request-time ratio uses summed times alone. Table 7 reports both measurements and output lengths.

Table 7: Additional MATH-500 measurements. A is AR, S is source reuse and R is RelaySpec. Time ratio divides summed AR time by summed relay time.

| Drafter | Target | Mean tokens AR / R | Time ratio AR / R | Throughput R / S | Progress S / R |
|---------|--------|--------------------|-------------------|------------------|----------------|
| DFlash  | 8B     | 783.22 / 778.81    | 5.018             | 1.531            | 7.66 / 6.98    |
| DFlash  | 14B    | 777.66 / 772.33    | 5.143             | 1.268            | 7.44 / 6.49    |
| EAGLE-3 | 8B     | 783.22 / 767.79    | 2.397             | 1.278            | 5.15 / 4.33    |
| EAGLE-3 | 14B    | 777.66 / 766.20    | 2.625             | 1.097            | 5.07 / 4.01    |

## B COMPLETE WORKLOAD RESULTS

Table 8: Native throughput retained and mean recorded progress per cycle. N and R denote native drafting and RelaySpec. Progress includes the implementation’s target-supplied token.

| Drafter | Target | Native tok/s | Relay tok/s | Retained [95% CI]  | Progress N | Progress R |
|---------|--------|--------------|-------------|--------------------|------------|------------|
| DFlash  | 8B     | 206.58       | 186.49      | 90.3% [89.8, 90.8] | 7.89       | 6.98       |
| EAGLE-3 | 8B     | 94.12        | 84.92       | 90.2% [89.8, 90.7] | 5.40       | 4.33       |
| EAGLE-3 | 14B    | 66.39        | 59.18       | 89.1% [88.6, 89.7] | 5.28       | 4.01       |

Table 9: Complete DFlash breadth comparisons with paired AR. Ratios use end-to-end throughput. Every planned task and target cell is included.

| Target | Task      | Requests | AR tok/s | Relay tok/s | Relay / AR [95% CI] | Relay / source |
|--------|-----------|----------|----------|-------------|---------------------|----------------|
| 8B     | GSM8K     | 128      | 37.60    | 138.89      | 3.69 [3.59, 3.81]   | 1.456          |
| 8B     | HumanEval | 164      | 37.55    | 120.87      | 3.22 [3.14, 3.30]   | 1.244          |
| 8B     | MBPP      | 378      | 37.49    | 129.35      | 3.45 [3.36, 3.54]   | 1.320          |
| 8B     | MT-Bench  | 160      | 37.47    | 70.69       | 1.89 [1.76, 2.05]   | 1.387          |
| 14B    | GSM8K     | 128      | 26.80    | 96.98       | 3.62 [3.52, 3.72]   | 1.104          |
| 14B    | HumanEval | 164      | 26.73    | 77.54       | 2.90 [2.83, 2.98]   | 0.890          |
| 14B    | MBPP      | 378      | 26.72    | 83.82       | 3.14 [3.07, 3.21]   | 0.956          |
| 14B    | MT-Bench  | 160      | 26.55    | 49.26       | 1.85 [1.73, 2.01]   | 1.086          |

The earlier fixed-map source comparisons in Table 10 provide all four workloads for both drafter families on RTX 6000 Ada. They are a separate paired experiment with their own denominator. The EAGLE-3 14B code cells show the reduced margin when lower accepted progress outweighs source-removal savings. This operating range complements the AR acceleration measured in the main comparison.

Table 10: Historical paired source-reuse breadth measurements on RTX 6000 Ada. Ratios compare relay with source throughput within these runs. They are not normalized by an AR arm from another experiment.

| Drafter | Target | Task      | Requests | Source tok/s | Relay tok/s | Ratio [95% interval]    |
|---------|--------|-----------|----------|--------------|-------------|-------------------------|
| DFlash  | 8B     | GSM8K     | 128      | 116.87       | 166.39      | 1.4237 [1.4040, 1.4445] |
| DFlash  | 8B     | HumanEval | 164      | 118.84       | 145.00      | 1.2201 [1.2017, 1.2383] |
| DFlash  | 8B     | MBPP      | 378      | 117.77       | 151.55      | 1.2868 [1.2732, 1.3001] |
| DFlash  | 8B     | MT-Bench  | 160      | 60.85        | 81.62       | 1.3412 [1.3183, 1.3639] |
| DFlash  | 14B    | GSM8K     | 128      | 88.04        | 97.07       | 1.1025 [1.0836, 1.1214] |
| DFlash  | 14B    | HumanEval | 164      | 87.34        | 77.61       | 0.8886 [0.8741, 0.9038] |
| DFlash  | 14B    | MBPP      | 378      | 88.02        | 83.98       | 0.9541 [0.9416, 0.9663] |
| DFlash  | 14B    | MT-Bench  | 160      | 45.32        | 49.30       | 1.0877 [1.0653, 1.1083] |
| EAGLE-3 | 8B     | GSM8K     | 128      | 85.99        | 108.45      | 1.2613 [1.2437, 1.2789] |
| EAGLE-3 | 8B     | HumanEval | 164      | 71.75        | 81.10       | 1.1304 [1.1172, 1.1434] |
| EAGLE-3 | 8B     | MBPP      | 378      | 69.85        | 82.10       | 1.1753 [1.1656, 1.1850] |
| EAGLE-3 | 8B     | MT-Bench  | 160      | 42.27        | 49.45       | 1.1698 [1.1501, 1.1906] |
| EAGLE-3 | 14B    | GSM8K     | 128      | 67.81        | 73.41       | 1.0826 [1.0675, 1.0979] |
| EAGLE-3 | 14B    | HumanEval | 164      | 55.38        | 50.58       | 0.9132 [0.9011, 0.9255] |
| EAGLE-3 | 14B    | MBPP      | 378      | 54.55        | 50.49       | 0.9256 [0.9151, 0.9361] |
| EAGLE-3 | 14B    | MT-Bench  | 160      | 33.83        | 34.57       | 1.0221 [0.9999, 1.0449] |

Table 11: Task scores for the historical fixed-map breadth runs. Source reuse and RelaySpec share each reported score. Code columns are single-program pass percentages under base and expanded EvalPlus tests.

| Drafter | Target | GSM8K | HumanEval | HumanEval+ | MBPP  | MBPP+ |
|---------|--------|-------|-----------|------------|-------|-------|
| DFlash  | 8B     | 93.75 | 85.98     | 80.49      | 84.13 | 73.02 |
| DFlash  | 14B    | 94.53 | 89.02     | 83.54      | 88.36 | 75.13 |
| EAGLE-3 | 8B     | 92.97 | 87.20     | 82.32      | 83.07 | 71.96 |
| EAGLE-3 | 14B    | 94.53 | 90.24     | 85.98      | 88.89 | 74.87 |

Across these historical math/code comparisons, all 4,680 paired task outcomes agree between source reuse and RelaySpec. This count is four model/drafter pairs times  $500 + 128 + 164 + 378 = 1,170$  problems. Expanded code tests evaluate the same programs and do not add independent examples. For the current AR-paired DFlash GSM8K runs, the scorer gives 120/128 correct for all arms at 8B and 121/128 at 14B. Code scores above refer specifically to the historical outputs, preserving scorer/run identity.

**AR-paired EAGLE-3 code quality.** We additionally score the saved programs from the EAGLE-3 AR-paired breadth runs with official EvalPlus base and expanded tests. Table 12 compares one program per task against AR from the same run. At 8B, RelaySpec passes four fewer MBPP tasks under both suites. At 14B, it passes two more. HumanEval expanded-test totals match AR at both target sizes, although individual task outcomes differ. RelaySpec and source reuse have identical per-task outcomes in all eight cells. The paired intervals cover zero. This does not establish equality or noninferiority. These retrospective comparisons use one fitted map per setting and do not include fitting-seed uncertainty. Conversation quality remains unmeasured.



Table 12: EAGLE-3 AR-paired code quality. Counts are passed tasks. The intervals resample paired tasks. Expanded tests reuse the same programs and do not add independent samples.

| Target/task   | Suite | AR      | Relay   | $\Delta$ (pp) | Paired 95% interval |
|---------------|-------|---------|---------|---------------|---------------------|
| 8B HumanEval  | base  | 143/164 | 141/164 | -1.22         | $[-3.66, +1.22]$    |
| 8B HumanEval  | plus  | 133/164 | 133/164 | +0.00         | $[-3.05, +3.05]$    |
| 8B MBPP       | base  | 318/378 | 314/378 | -1.06         | $[-2.91, +0.79]$    |
| 8B MBPP       | plus  | 276/378 | 272/378 | -1.06         | $[-2.65, +0.53]$    |
| 14B HumanEval | base  | 143/164 | 143/164 | +0.00         | $[-2.44, +2.44]$    |
| 14B HumanEval | plus  | 134/164 | 134/164 | +0.00         | $[-2.44, +2.44]$    |
| 14B MBPP      | base  | 338/378 | 340/378 | +0.53         | $[-1.32, +2.38]$    |
| 14B MBPP      | plus  | 283/378 | 285/378 | +0.53         | $[-1.06, +2.12]$    |

## C FITTING AND INTERFACE STUDIES

Table 13: DFlash-8B block-size ablation on 64 questions, a 512-token cap and RTX 6000 Ada hardware. AR is measured in each run.

| Block | AR tok/s | Native draft tok/s | Relay tok/s | Relay / AR | Progress / cycle |
|-------|----------|--------------------|-------------|------------|------------------|
| 8     | 44.68    | 175.12             | 164.90      | 3.691      | 4.98             |
| 16    | 44.67    | 229.87             | 210.15      | 4.704      | 6.48             |
| 32    | 44.76    | 207.70             | 131.36      | 2.935      | 4.14             |

**Distinct records at fixed fitting work.** A separate controlled DFlash-8B study holds fitting at 1,024 updates and four records per update while varying distinct records from 64 to 4,096. Smaller sets repeat in the same ordered schedule. Table 14 reports end-to-end throughput on the same 128 development-exposed MATH questions. Of the measured settings, 512 is the smallest within 5% of the best observed mapper throughput. The 256-record setting retains 91.4% of that observed best. This is a descriptive, single-seed boundary, not a minimum across settings or a confirmed optimum. The 512–4,096 settings form an unresolved plateau. Selecting the reference from the same evaluations does not provide independent confirmation. Every relay scores 105/128, versus AR’s 104/128.

Table 14: Distinct-data study at 4,096 presentations for every row. Native retention uses each run’s paired native-drafter control. Best retention uses the observed best relay across these settings. All results condition on one fitting seed.

| Records | Tokens/s | $\times$ AR | Native retained | Best retained | Correct |
|---------|----------|-------------|-----------------|---------------|---------|
| 64      | 134.39   | 3.55        | 65.7%           | 72.8%         | 105/128 |
| 128     | 154.56   | 4.10        | 75.5%           | 83.7%         | 105/128 |
| 256     | 168.76   | 4.51        | 82.6%           | 91.4%         | 105/128 |
| 512     | 181.91   | 4.84        | 88.9%           | 98.5%         | 105/128 |
| 1,024   | 184.55   | 4.92        | 90.3%           | 99.9%         | 105/128 |
| 2,048   | 183.81   | 4.88        | 89.8%           | 99.5%         | 105/128 |
| 4,096   | 184.64   | 4.90        | 90.2%           | 100.0%        | 105/128 |

**Continuous optimization.** We also save checkpoints from one uninterrupted 4,096-record fit at 128, 256, 512, 1,024 and 2,048 updates. They have seen respectively 512, 1,024, 2,048, 4,096 and 4,096 distinct records. The final point therefore measures a second pass, not 8,192 distinct examples. End-to-end AR-relative throughput increases from 3.65 to 5.03 across this trajectory. All five checkpoints score 105/128. Unlike the earlier separately fitted budget configurations, these checkpoints share one optimization trajectory. Figure 7 separates this experiment from the fixed-work data study.




Figure 7: Historical MATH-only fitting study. Left: distinct-data scaling at 1,024 updates. Right: one continuous optimization trajectory. This uses a different training dataset and budget from Figure 4.

**Expanded NuminaMath data curve.** Table 15 reports all eleven completed sizes at 8,192 batch-four updates, spanning 2,048 epochs at 16 records to one epoch at 32,768. The same 1,024 feature-validation records are used throughout. Larger data marginally improves feature loss but does not improve measured decoding beyond the plateau. The 512-record mapper retains 97.2% of the observed best throughput, while the 256-record mapper retains 93.9%. These percentages are descriptive and conditional on the evaluated fitting seed and development questions.

Table 15: NuminaMath fitting at fixed 8,192 updates; 128 paired MATH questions with a 2,048-token output cap. All eleven mapper outputs score 105/128, versus AR’s 104/128.

| Records | Tokens/s | Speedup / AR | Correct / 128 |
|---------|----------|--------------|---------------|
| 16      | 96.87    | 2.58×        | 105           |
| 32      | 133.23   | 3.55×        | 105           |
| 64      | 157.74   | 4.20×        | 105           |
| 128     | 177.75   | 4.73×        | 105           |
| 256     | 186.36   | 4.96×        | 105           |
| 512     | 192.81   | 5.14×        | 105           |
| 2,048   | 196.93   | 5.25×        | 105           |
| 4,096   | 198.30   | 5.28×        | 105           |
| 8,192   | 197.98   | 5.27×        | 105           |
| 16,384  | 198.37   | 5.28×        | 105           |
| 32,768  | 197.94   | 5.27×        | 105           |

Table 16: Completed DFlash-8B fitting studies on the same 128-question set. Records count distinct fitting examples. Two passes over 4,096 records give 8,192 presentations. Source reuse is paired within each run.

| Fitting choice            | Records | Updates      | Relay tok/s | Relay / source [95% CI] | Score |
|---------------------------|---------|--------------|-------------|-------------------------|-------|
| 512 records               | 512     | 128          | 136.78      | 1.150 [1.118, 1.181]    | 82.03 |
| 1,024 records             | 1,024   | 256          | 162.04      | 1.372 [1.347, 1.397]    | 82.03 |
| 2,048 records             | 2,048   | 512          | 173.72      | 1.477 [1.458, 1.495]    | 82.03 |
| 4,096 records, two passes | 4,096   | 2,048        | 187.85      | 1.573 [1.558, 1.588]    | 82.03 |
| Ridge surrogate           | 4,096   | <i>solve</i> | 115.18      | 0.955 [0.927, 0.982]    | 82.03 |
| Nonlinear width 512       | 4,096   | 1,024        | 104.49      | 0.872 [0.841, 0.903]    | 82.03 |

The data-budget configurations use the same normalized linear interface and relative-error objective. The nonlinear map uses an intermediate width of 512 and about 11.8M parameters, compared with 52.4M for the dense 8B map. Its lower throughput is consistent with a less effective fitted interface, but the comparison also changes capacity. It does not isolate a disadvantage of nonlinear functions.

The ridge configuration solves a raw linear surrogate with ridge coefficient 1.0. Since the deployed DFlash interface includes output normalization, this is a different objective from Equation 3.

**Matched capacity on a separate fitting source.** We additionally fit 30 DFlash-8B configurations on nested sets of 512 and 2,048 NuminaMath-CoT records,<sup>1</sup> using a fixed 1,024-record fitting validation split. The source-stratified sets include `cn_k12`, `orca_math` and `synthetic_math` examples. Their lexical filter excludes exact normalized problem/solution matches and near matches at five-shingle Jaccard similarity at least 0.6 for texts with at least ten unique shingles. This filter does not establish semantic or template independence. These results use a separate fitting source from the historical MATH study above.

Each configuration receives 8,192 updates with four records per update: 64 passes at  $N = 512$  and 16 at  $N = 2048$ . Frozen features are cached once. Factored linear maps and bias-free two-layer GELU MLPs use widths 64, 128, 256, 512, 1,024, 2,048 and 4,096, giving matched parameter counts  $h(20,480 + 2,560)$ . The dense reference has 52.43M parameters. The rank of a linear function remains bounded by 2,560 even when its factorization width is larger. All cells share the data order, relative-interface objective, learning rate  $6 \times 10^{-4}$  and seed 1729.

Table 17: Validation relative interface MSE for the capacity study. Linear and MLP entries at the same width have equal parameter counts. The dense row supplies the single-linear-layer reference.

| Width | Params (M) | Linear, $N=512$ | MLP, $N=512$ | Linear, $N=2048$ | MLP, $N=2048$ |
|-------|------------|-----------------|--------------|------------------|---------------|
| 64    | 1.47       | 0.5732          | 0.5790       | 0.5692           | 0.5752        |
| 128   | 2.95       | 0.4761          | 0.4871       | 0.4690           | 0.4804        |
| 256   | 5.90       | 0.3760          | 0.3883       | 0.3648           | 0.3767        |
| 512   | 11.80      | 0.2862          | 0.3082       | 0.2685           | 0.2878        |
| 1024  | 23.59      | 0.2295          | 0.2579       | 0.2040           | 0.2224        |
| 2048  | 47.19      | 0.2133          | 0.2438       | 0.1847           | 0.1982        |
| 4096  | 94.37      | 0.2145          | 0.2501       | 0.1845           | 0.1936        |
| Dense | 52.43      | 0.2101          | —            | 0.1805           | —             |

At this optimization budget, wider factorizations approach the dense reference, while MLPs have higher validation error at every matched width. Increasing MLP width from 2,048 to 4,096 at  $N = 512$  lowers diagnostic training error from 0.1586 to 0.1278 but raises validation error from 0.2438 to 0.2501. At  $N = 2048$ , validation error instead decreases from 0.1982 to 0.1936. This interaction motivates checking regularization and convergence before attributing the ranking to function class.

**More epochs on fixed smaller datasets.** We continue the width-512 linear and MLP fits to 32,768 total updates, preserving Adam moments, random states and cyclic data position. A separate bounded pilot reproduced uninterrupted fitting bit for bit. Figure 8 shows late-training diagnostics on the same first 256 training records and all 1,024 validation records. The  $N = 2048$  MLP improves from 0.2878 to 0.2787 validation error between 8,192 and 32,768 updates. At  $N = 512$ , linear training error falls from 0.2443 to 0.2350 while validation error rises from 0.2862 to 0.2873. The latter is consistent with mild overfitting on this diagnostic split. These single-seed fitting trajectories require separate decoding and quality evaluation, including replication across targets and workloads.

<sup>1</sup>AI-MO/NuminaMath-CoT, revision 9d8d210c9f6a, training shard 0 of 5.




Figure 8: Late-training trajectories, starting at 2,048 updates. Dashed lines use the fixed training diagnostic subset. Solid lines use fitting validation. The horizontal axis counts updates, while the distinct datasets remain fixed at 512 or 2,048 records.

**Explicit regularization on fixed smaller datasets.** We complete 42 nonzero-penalty fits for the dense, width-512 factored linear and width-512 GELU MLP connectors at  $N \in \{512, 2048\}$ . Each fit uses 8,192 updates, the same 1,024 validation records and seed 1729. Explicit L2 coefficients are  $10^{-7}, 10^{-6}, 10^{-5}, 10^{-4}$ . Separate AdamW arms use decay  $10^{-4}, 10^{-3}, 10^{-2}$ . No tested L2 coefficient improves its matched zero-penalty endpoint. The largest AdamW improvement is a 0.17% relative decrease in validation error for the width-512 linear connector at  $N = 512$ . Neither MLP setting improves with either penalty family. Table 18 reports the best validation value within each penalty family, so these minima are development selections. Figure 9 retains all tested coefficients. This grid does not establish a decoding gain or a penalty effect across seeds, and it does not resolve regularization for the wider MLPs.

Table 18: Matched regularization endpoints. Lower relative interface MSE is better. Each nonzero minimum is selected from four L2 or three AdamW coefficients using the same fitting validation split.

| $N$  | Mapper              | No penalty | Best tested L2 | Best tested AdamW |
|------|---------------------|------------|----------------|-------------------|
| 512  | Dense               | 0.21008    | 0.21138        | 0.21011           |
| 512  | Factored linear 512 | 0.28617    | 0.28738        | 0.28570           |
| 512  | GELU MLP 512        | 0.30818    | 0.30827        | 0.30822           |
| 2048 | Dense               | 0.18055    | 0.18424        | 0.18055           |
| 2048 | Factored linear 512 | 0.26853    | 0.26970        | 0.26852           |
| 2048 | GELU MLP 512        | 0.28776    | 0.28864        | 0.28779           |




Figure 9: All 42 penalty endpoints relative to their matched zero-penalty validation error. Positive values indicate worse fitting validation. The two curves are separate objective-L2 and AdamW experiments.

Table 19: Matched EAGLE-3 8B normalization comparison on 32 development questions after 128 updates. Throughput ratios use source reuse.

| Input to linear map | Relative error | Throughput ratio [95% interval] | Progress retained |
|---------------------|----------------|---------------------------------|-------------------|
| Normalized features | 0.413          | 1.035 [1.003, 1.068]            | 69.0%             |
| Raw features        | 0.266          | 1.237 [1.213, 1.263]            | 82.6%             |

Table 20: DFlash objective comparison on 32 development questions. Candidates share fitting data, update count, normalization and optimizer. Each ratio uses the source-reuse arm of that candidate’s paired run.

| Target | Objective              | Throughput ratio [95% interval] | Token matches |
|--------|------------------------|---------------------------------|---------------|
| 8B     | Relative error         | 1.523 [1.488, 1.558]            | 32/32         |
| 8B     | Squared error + cosine | 1.509 [1.476, 1.545]            | 32/32         |
| 14B    | Relative error         | 1.265 [1.243, 1.289]            | 32/32         |
| 14B    | Squared error + cosine | 1.251 [1.229, 1.276]            | 32/32         |

Relative error weights a record’s feature mismatch by teacher magnitude. Squared error plus 0.1 times cosine distance combines coordinate error with directional agreement. Direct candidate-to-candidate throughput ratios are 1.0085 [1.0005, 1.0174] at 8B and 1.0114 [1.0046, 1.0177] at 14B. These are modest gains with one fewer mixing coefficient.

### C.1 EAGLE-3 FITTING REPLICATION

We repeat the fixed smaller-data fitting study with the EAGLE-3 source drafter and the 8B target. The grid contains dense, factored linear and GELU MLP connectors, with widths 128, 512 and 2048 for the latter two. Each primary fit uses 8,192 updates at  $N \in \{512, 2048\}$  and the same 1,024 fitting-validation records. Two additional seeds repeat the dense  $N = 2048$  setting. This experiment uses the EAGLE input convention without the DFlash input normalization. Error values are interpreted within each drafter family’s conditioning interface.

Table 21: EAGLE-3 fitting validation. End denotes the 8,192-update endpoint. Best denotes the minimum saved fitting-validation error, with its update count. These are development selections for seed 1729, not decoding results. M weights counts millions of trainable mapper parameters.

| Mapper      | M weights | $N = 512$ |         |        | $N = 2048$ |         |        |
|-------------|-----------|-----------|---------|--------|------------|---------|--------|
|             |           | End       | Best    | Update | End        | Best    | Update |
| Dense       | 52.43     | 0.24787   | 0.21666 | 1024   | 0.21203    | 0.21061 | 2048   |
| Linear 128  | 2.95      | 0.41980   | 0.41980 | 8192   | 0.41505    | 0.41505 | 8192   |
| Linear 512  | 11.80     | 0.28632   | 0.28505 | 2048   | 0.27188    | 0.27188 | 8192   |
| Linear 2048 | 47.19     | 0.23486   | 0.22877 | 2048   | 0.21132    | 0.21132 | 8192   |
| MLP 128     | 2.95      | 0.46554   | 0.46554 | 8192   | 0.45645    | 0.45645 | 8192   |
| MLP 512     | 11.80     | 0.31749   | 0.31749 | 8192   | 0.29577    | 0.29577 | 8192   |
| MLP 2048    | 47.19     | 0.28154   | 0.27124 | 2048   | 0.23196    | 0.22683 | 4096   |

The dense  $N = 512$  mapper reaches 0.21666 at 1,024 updates, then rises to 0.24787 at the final update. Its endpoint is worse than the width-2048 linear mapper, but its best saved validation value is better than that linear mapper’s 0.22877. At  $N = 2048$ , the dense and width-2048 linear minima are 0.21061 and 0.21132. Thus endpoint rankings alone can reflect different convergence trajectories. At every matched width in this grid, the MLP’s best saved validation error exceeds the linear mapper’s minimum. The three dense  $N = 2048$  endpoints range from 0.212034 to 0.212043. This narrow seed spread concerns one fitting setting. It does not establish seed stability for the other architectures or for decoding performance.




Figure 10: EAGLE-3 fitting-validation trajectories at fixed distinct-data counts. Additional updates can worsen validation, most visibly for the dense mapper at  $N = 512$ . The horizontal axis counts updates rather than new examples. The subsequent checkpoint comparison measures actual decoding.

## C.2 FEATURE-VALIDATION MINIMA AND DECODING

We compare each distinct saved feature-validation minimum with its 8,192-update endpoint in two declared decoding campaigns. Each uses 16 paired development questions, greedy decoding and a 256-token cap. Checkpoint selection precedes decoding. Table 22 includes every distinct early-versus-endpoint pair in these campaigns.

Table 22: Decoding throughput at the minimum feature-validation checkpoint relative to the same fit’s endpoint. Intervals resample paired requests 10,000 times. They are descriptive, without multiple-comparison adjustment, and do not measure variation across fitting seeds.

| Family  | Mapper      | $N$  | Learning rate | Selected update | Early / end [95% CI] |
|---------|-------------|------|---------------|-----------------|----------------------|
| DFlash  | Linear 4096 | 512  | 0.0006        | 4096            | 1.009 [0.981, 1.040] |
| DFlash  | MLP 4096    | 512  | 0.0006        | 4096            | 0.978 [0.961, 0.998] |
| DFlash  | Linear 4096 | 512  | 0.0002        | 4096            | 1.008 [0.985, 1.029] |
| DFlash  | Linear 4096 | 512  | 0.0018        | 4096            | 1.003 [0.978, 1.029] |
| DFlash  | MLP 4096    | 512  | 0.0002        | 2048            | 1.011 [0.986, 1.039] |
| DFlash  | MLP 4096    | 512  | 0.0018        | 4096            | 0.961 [0.939, 0.983] |
| EAGLE-3 | Dense       | 512  | 0.0006        | 1024            | 0.950 [0.924, 0.976] |
| EAGLE-3 | Linear 512  | 512  | 0.0006        | 2048            | 0.969 [0.948, 0.988] |
| EAGLE-3 | Linear 2048 | 512  | 0.0006        | 2048            | 0.964 [0.922, 1.003] |
| EAGLE-3 | MLP 2048    | 512  | 0.0006        | 2048            | 0.968 [0.942, 0.996] |
| EAGLE-3 | Dense       | 2048 | 0.0006        | 2048            | 0.980 [0.969, 0.992] |
| EAGLE-3 | MLP 2048    | 2048 | 0.0006        | 4096            | 1.019 [0.995, 1.046] |

Lower feature-validation loss does not consistently predict faster decoding. For EAGLE-3’s dense  $N = 512$  fit, the selected 1,024-update checkpoint retains 94.99% of endpoint throughput, with interval [92.39, 97.59]%. For the DFlash width-4096 MLP at  $N = 512$  and learning rate 0.0006, the selected 4,096-update checkpoint retains 97.77%, with interval [96.09, 99.76]%. Other intervals cross equal throughput. These results support treating feature regression as a surrogate and measuring decoding when selecting a connector. They do not establish full-answer quality or justify selection on untouched evaluation data.

Table 23: Observed throughput ranges across three fitting seeds in a separate 16-question, 256-token development campaign. Selected uses each fit’s minimum saved feature-validation checkpoint. These ranges describe the three measured fits and runtime variation, not confidence intervals.

| Mapper      | $N$  | Learning rate | Endpoint tok/s range | Selected tok/s range |
|-------------|------|---------------|----------------------|----------------------|
| Dense       | 512  | 0.0006        | 184.34–184.68        | 183.36–184.58        |
| Dense       | 2048 | 0.0006        | 186.11–189.22        | 186.11–189.22        |
| Linear 1024 | 512  | 0.0006        | 179.47–181.23        | 179.47–181.23        |
| Linear 4096 | 2048 | 0.0002        | 185.36–187.81        | 185.36–187.81        |
| MLP 4096    | 2048 | 0.0002        | 183.92–184.78        | 183.92–184.78        |
| MLP 4096    | 512  | 0.0002        | 174.53–177.30        | 175.57–177.56        |

All six settings in Table 23 use the same cached features and seeds 1729, 1730 and 1731. The dense  $N = 512$  endpoints span 184.34–184.68 tokens/s. The width-4096  $N = 2048$  MLP improves on its  $N = 512$  counterpart, while the dense connector remains competitive. These short development runs do not establish the minimum sufficient data count or distinguish small architecture gaps from runtime variation.

### C.3 LONGER DEVELOPMENT OUTPUTS FOR SMALL-DATA MAPPERS

We evaluate nine saved DFlash connectors on 128 paired MATH development questions with a 2,048-token cap, greedy decoding and the same source, target and native-drafter references. These exposed questions provide a larger development comparison than the 16-question, 256-token screen. They are separate from any untouched confirmation set. The continued width-512 fits reuse the same 2,048 distinct training examples.

Table 24: Capped development outcomes for small-data DFlash fitting. Throughput retention uses the dense  $N = 2048$ , 8,192-update connector. Intervals use 10,000 paired request bootstrap samples. Correct counts scored answers. Cap counts outputs reaching 2,048 tokens, which can include EOS exactly at the limit and are not exact truncation counts.

| Method         | $N$  | Updates | Tok/s  | Dense retained (%) [95% CI] | Correct | Cap |
|----------------|------|---------|--------|-----------------------------|---------|-----|
| AR             | –    | –       | 37.72  | 19.04 [18.23, 19.90]        | 104/128 | 11  |
| Native drafter | –    | –       | 204.57 | 103.27 [102.35, 104.17]     | 105/128 | 9   |
| Source reuse   | –    | –       | 120.96 | 61.06 [60.53, 61.59]        | 105/128 | 9   |
| Dense          | 512  | 8192    | 193.68 | 97.78 [97.09, 98.47]        | 105/128 | 9   |
| Dense          | 2048 | 8192    | 198.09 | 100.00 [100.00, 100.00]     | 105/128 | 9   |
| Linear 1024    | 512  | 8192    | 188.19 | 95.00 [94.14, 95.85]        | 105/128 | 9   |
| Linear 4096    | 2048 | 8192    | 196.25 | 99.07 [98.50, 99.60]        | 105/128 | 9   |
| MLP 4096       | 2048 | 8192    | 190.15 | 95.99 [95.30, 96.70]        | 105/128 | 9   |
| Linear 512     | 2048 | 8192    | 164.61 | 83.10 [81.81, 84.38]        | 105/128 | 9   |
| Linear 512     | 2048 | 32768   | 167.29 | 84.46 [83.15, 85.71]        | 105/128 | 9   |
| MLP 512        | 2048 | 8192    | 154.39 | 77.94 [76.50, 79.35]        | 105/128 | 9   |
| MLP 512        | 2048 | 32768   | 157.68 | 79.60 [78.07, 81.06]        | 105/128 | 9   |

Dense fitting on 512 examples retains 97.78% of the dense  $N = 2048$  throughput, with interval [97.09, 98.47]%. This establishes a lower-data performance point in this setting, but does not establish that 512 is minimal. The width-1024 linear mapper at  $N = 512$  retains 95.00%, with interval [94.14, 95.85]%, leaving its 95% boundary unresolved. The width-4096 linear mapper is slightly below the dense connector in this larger sample, so the earlier short-screen point ranking should not be interpreted as an established architecture advantage.

All nine connectors score 105 of 128 answers, compared with 104 for AR. Their paired accuracy-difference intervals are  $[-0.03125, 0.046875]$ . These intervals do not establish a one-percentage-point noninferiority margin. Nine connector outputs and eleven AR outputs reach the token cap. The observed scores therefore concern the configured capped evaluation, not uncapped answer quality. Longer width-512 fitting gives modest throughput increases while remaining below the wider or dense connectors. This comparison does not treat additional updates as additional data.

#### C.4 EAGLE-3 LONGER-OUTPUT CAPACITY COMPARISON

Two disjoint 64-question shards evaluate eight saved EAGLE-3 maps and three shared controls on the same 128 exposed MATH development questions. All 1,408 expected method/request pairs are present. The 2,048-token cap, fitting checkpoints, source revisions and pinned scorer remain fixed across shards. An eight-request pilot precedes this evaluation.

Table 25: EAGLE-3 with an 8B target on 128 exposed development questions. Dense retention uses the  $N = 2048$  endpoint. Intervals are paired 95% request-bootstrap intervals conditional on the fits. Cap counts all outputs reaching 2,048 tokens. It is not an exact truncation count.

| Method         | $N$  | Tokens/s | Dense retained (%) [95% CI] | Correct | Cap |
|----------------|------|----------|-----------------------------|---------|-----|
| AR             | –    | 36.32    | 38.19 [37.14, 39.25]        | 104/128 | 11  |
| Native drafter | –    | 94.89    | 99.78 [98.86, 100.80]       | 105/128 | 7   |
| Source reuse   | –    | 66.80    | 70.24 [69.69, 70.84]        | 105/128 | 7   |
| Dense          | 512  | 93.47    | 98.28 [97.59, 99.01]        | 105/128 | 7   |
| Dense          | 2048 | 95.10    | 100.00 [100.00, 100.00]     | 105/128 | 7   |
| Linear 2048    | 512  | 93.85    | 98.69 [98.08, 99.31]        | 105/128 | 7   |
| Linear 2048    | 2048 | 93.59    | 98.41 [97.76, 99.12]        | 105/128 | 7   |
| MLP 2048       | 512  | 84.67    | 89.03 [88.24, 89.87]        | 105/128 | 7   |
| MLP 2048       | 2048 | 89.25    | 93.85 [93.27, 94.46]        | 105/128 | 7   |
| Linear 512     | 2048 | 84.91    | 89.29 [88.54, 90.09]        | 105/128 | 7   |
| MLP 512        | 2048 | 79.76    | 83.87 [82.94, 84.84]        | 105/128 | 7   |



Dense  $N = 512$  retains 98.28% of dense  $N = 2048$  throughput. Linear-2048 at  $N = 512$  retains 98.69%, while the two MLP-2048 fits retain 89.03% and 93.85% at  $N = 512$  and  $N = 2048$ . The width-512 endpoints are slower. Every speculative method scores 105/128 with seven cap-length outputs. AR scores 104/128 with eleven. All speculative methods have identical per-question correctness in this sample, but the conservative paired 95% difference interval is still  $[-3.37, 3.37]$  percentage points. Against AR, dense  $N = 2048$  has four beneficial and three adverse correctness discordances. Equal or close scores therefore do not establish tight noninferiority or uncapped answer quality. The observed small-data retention replicates across the two drafter families under these development conditions, not across independent benchmark samples.

### C.5 INPUT-ONLY TASK COMPLEXITY

We stratify the same 128 development requests using the benchmark’s original difficulty levels and subjects, together with shared tokenized input length. Group definitions are fixed before computing subgroup outcomes. They do not use candidate success, generated output length or latency. This is a retrospective analysis of exposed development data, not a new confirmatory test. All twelve methods and all requests remain in the analysis.

Table 26: Throughput retained from dense  $N = 2048$  within each MATH difficulty group, in percent with descriptive paired 95% intervals. All fits use 8,192 updates except the continued width-512 fits, which use 32,768 updates on the same 2,048 examples. For fitted maps, unspecified  $N$  is 2,048. Intervals do not adjust for multiple subgroup comparisons or model selection.

| Setting                 | Levels 1–2 ( $n = 42$ ) | Level 3 ( $n = 21$ ) | Levels 4–5 ( $n = 65$ ) |
|-------------------------|-------------------------|----------------------|-------------------------|
| AR                      | 20.1 [18.6, 21.5]       | 19.0 [16.5, 22.1]    | 18.7 [17.8, 19.7]       |
| Native drafter          | 101.4 [99.1, 104.1]     | 104.2 [102.0, 106.6] | 103.7 [102.8, 104.6]    |
| Source reuse            | 60.6 [59.2, 61.8]       | 60.7 [59.2, 62.1]    | 61.3 [60.6, 61.9]       |
| Dense, $N = 512$        | 97.4 [96.1, 98.6]       | 97.9 [96.1, 100.2]   | 97.9 [97.0, 98.8]       |
| Dense, $N = 2048$       | 100.0 [100.0, 100.0]    | 100.0 [100.0, 100.0] | 100.0 [100.0, 100.0]    |
| Linear 1024, $N = 512$  | 94.5 [93.2, 95.9]       | 94.8 [93.4, 96.5]    | 95.2 [94.0, 96.4]       |
| Linear 4096, $N = 2048$ | 98.9 [97.9, 99.8]       | 100.0 [98.6, 101.5]  | 98.9 [98.2, 99.6]       |
| MLP 4096, $N = 2048$    | 95.5 [94.3, 96.6]       | 96.8 [94.9, 98.7]    | 96.0 [95.1, 96.9]       |
| Linear 512              | 82.6 [79.3, 85.7]       | 84.5 [81.6, 86.8]    | 83.0 [81.5, 84.5]       |
| Linear 512, continued   | 84.1 [80.6, 87.5]       | 86.2 [84.0, 88.2]    | 84.2 [82.7, 85.7]       |
| MLP 512                 | 76.5 [73.4, 79.5]       | 79.9 [76.8, 82.5]    | 78.0 [76.2, 79.7]       |
| MLP 512, continued      | 78.4 [74.6, 82.0]       | 79.8 [77.0, 82.0]    | 80.0 [78.1, 81.7]       |

Dense  $N = 512$  retains 97.4–97.9% of dense  $N = 2048$  throughput across the three difficulty groups. The width-1024 linear map stays near the 95% boundary, while MLP-4096 retains 95.4–96.8%. The smaller width-512 maps remain slower in every group. These results describe the tested capacities and workloads. They do not establish an optimal size across settings.

For levels 1–2, level 3 and levels 4–5, respectively, AR answers 38/42, 19/21 and 47/65 questions correctly. Every mapper answers 38/42, 18/21 and 49/65 correctly. All eleven AR cap hits occur in the highest difficulty group, as do eight of the nine mapper cap hits. Difficulty therefore coincides with changes in capped answer quality and output length. It is not a controlled intervention on decoding cost.

Input-length bins of at most 64, 65–128, 129–256 and more than 256 tokens contain 52, 57, 15 and 4 requests. In the final four-request group, dense  $N = 512$  retains 94.5% [91.3, 96.4]% and linear-1024 retains 90.8% [88.2, 94.4]% of dense  $N = 2048$  throughput. The small sample and multiple comparisons make this a signal for replication, not evidence of a causal length effect or a new tuning rule. All seven original subject strata, input assignments, method outcomes and conservative paired accuracy intervals are retained in the accompanying artifacts. No additional generation or fitting is used for this analysis.

## C.6 CAPACITY REPLICATION WITH A 14B TARGET

We repeat the fixed-data capacity comparison with Qwen3-14B for both DFlash and EAGLE-3. Each family has fourteen primary fits: dense, factored linear and GELU MLP widths 512, 1,024 and 4,096 at each of  $N = 512$  and  $N = 2048$ . Two additional dense fits use seed 1730. All receive 8,192 batch-four updates at learning rate  $6 \times 10^{-4}$ , with no L2 penalty or weight decay. Validation uses the same 1,024 records within each family. Training diagnostics use a 256-record prefix. The five target taps give 25,600 input dimensions and the output has 2,560 dimensions. Dense therefore has 65.54M parameters, versus 14.42M, 28.84M and 115.34M at the three matched factorized/MLP widths. Width 4,096 does not increase the maximum rank of a linear function beyond the output dimension.




Figure 11: DFlash with Qwen3-14B. Validation error across the saved training trajectory, with all capacities and both dense seeds retained. The decoding endpoint remains fixed at 8,192 updates.

Table 27: DFlash-14B fixed endpoints. Throughput retention uses dense  $N = 2048$ , seed 1729. Intervals are paired 95% request-bootstrap intervals on sixteen exposed questions capped at 256 output tokens. They exclude fitting-seed and selection uncertainty.

| Mapper            | $N$  | Params (M) | Train / val.  | Tokens/s | Retained (%)         |
|-------------------|------|------------|---------------|----------|----------------------|
| Dense             | 512  | 65.54      | 0.153 / 0.244 | 123.38   | 96.0 [92.3, 99.3]    |
| Dense (seed 1730) | 512  | 65.54      | 0.153 / 0.244 | 122.08   | 94.9 [91.5, 98.1]    |
| Linear 512        | 512  | 14.42      | 0.251 / 0.304 | 99.16    | 77.1 [72.6, 81.8]    |
| Linear 1024       | 512  | 28.84      | 0.180 / 0.258 | 117.39   | 91.3 [87.7, 95.1]    |
| Linear 4096       | 512  | 115.34     | 0.155 / 0.247 | 121.65   | 94.6 [91.4, 97.9]    |
| MLP 512           | 512  | 14.42      | 0.277 / 0.327 | 92.11    | 71.6 [68.1, 75.8]    |
| MLP 1024          | 512  | 28.84      | 0.208 / 0.283 | 109.02   | 84.8 [79.7, 90.3]    |
| MLP 4096          | 512  | 115.34     | 0.140 / 0.278 | 112.85   | 87.8 [83.5, 92.0]    |
| Dense             | 2048 | 65.54      | 0.188 / 0.204 | 128.58   | 100.0 [100.0, 100.0] |
| Dense (seed 1730) | 2048 | 65.54      | 0.188 / 0.204 | 129.55   | 100.8 [99.5, 102.1]  |
| Linear 512        | 2048 | 14.42      | 0.274 / 0.282 | 105.53   | 82.1 [76.9, 87.4]    |
| Linear 1024       | 2048 | 28.84      | 0.212 / 0.224 | 127.67   | 99.3 [96.5, 102.3]   |
| Linear 4096       | 2048 | 115.34     | 0.193 / 0.208 | 126.96   | 98.7 [96.5, 101.2]   |
| MLP 512           | 2048 | 14.42      | 0.292 / 0.300 | 96.46    | 75.0 [70.9, 79.2]    |
| MLP 1024          | 2048 | 28.84      | 0.227 / 0.241 | 121.21   | 94.3 [90.9, 98.1]    |
| MLP 4096          | 2048 | 115.34     | 0.174 / 0.215 | 122.32   | 95.1 [92.6, 98.2]    |

With DFlash, the wide MLP at  $N = 2048$  has lower training error than dense, but higher validation error and lower measured throughput. The width-1024 linear map nearly matches dense throughput with fewer parameters. These comparisons use fixed endpoints, not checkpoints chosen after inspecting decoding. Every method reaches the output cap on these sixteen questions, so the short scores do not establish full-answer quality. The runtime includes AR and source-reuse controls. No native 14B DFlash checkpoint is substituted from another target.




Figure 12: EAGLE-3 with Qwen3-14B under the same data-count and update budgets. The width-4096 linear trajectory retains its intermediate validation spike. Curves show optimization behavior, not a ranking of decoding performance or a selected stopping rule.

Table 28: EAGLE-3-14B fixed endpoints under its own runtime. Retention and intervals use the same within-family protocol as Table 27. Absolute throughput across the two tables is not an algorithm-only comparison.

| Mapper            | $N$  | Params (M) | Train / val.  | Tokens/s | Retained (%)         |
|-------------------|------|------------|---------------|----------|----------------------|
| Dense             | 512  | 65.54      | 0.234 / 0.341 | 62.24    | 94.4 [91.7, 97.2]    |
| Dense (seed 1730) | 512  | 65.54      | 0.238 / 0.345 | 63.32    | 96.1 [92.7, 99.5]    |
| Linear 512        | 512  | 14.42      | 0.256 / 0.308 | 56.92    | 86.4 [83.5, 89.4]    |
| Linear 1024       | 512  | 28.84      | 0.197 / 0.273 | 62.50    | 94.8 [91.9, 98.0]    |
| Linear 4096       | 512  | 115.34     | 0.226 / 0.301 | 60.90    | 92.4 [89.8, 95.1]    |
| MLP 512           | 512  | 14.42      | 0.302 / 0.349 | 53.15    | 80.6 [77.4, 84.1]    |
| MLP 1024          | 512  | 28.84      | 0.253 / 0.321 | 59.45    | 90.2 [87.3, 92.8]    |
| MLP 4096          | 512  | 115.34     | 0.224 / 0.315 | 52.64    | 79.9 [76.6, 83.5]    |
| Dense             | 2048 | 65.54      | 0.231 / 0.254 | 65.91    | 100.0 [100.0, 100.0] |
| Dense (seed 1730) | 2048 | 65.54      | 0.231 / 0.254 | 66.45    | 100.8 [99.3, 102.4]  |
| Linear 512        | 2048 | 14.42      | 0.279 / 0.287 | 58.92    | 89.4 [86.0, 92.7]    |
| Linear 1024       | 2048 | 28.84      | 0.236 / 0.249 | 63.41    | 96.2 [94.6, 97.8]    |
| Linear 4096       | 2048 | 115.34     | 0.216 / 0.228 | 65.61    | 99.5 [97.5, 101.9]   |
| MLP 512           | 2048 | 14.42      | 0.311 / 0.321 | 56.54    | 85.8 [82.2, 89.3]    |
| MLP 1024          | 2048 | 28.84      | 0.259 / 0.275 | 61.76    | 93.7 [90.5, 97.0]    |
| MLP 4096          | 2048 | 115.34     | 0.227 / 0.263 | 64.02    | 97.1 [94.9, 99.4]    |

EAGLE-3 differs from DFlash in its fitting dynamics. At  $N = 512$ , both dense seeds have their lowest saved validation error at 384 updates, followed by substantial increases. At  $N = 2048$ , the wide linear endpoint has lower validation error than dense, but nearly equal decoding throughput. Its intermediate spike also shows that the shared learning rate does not produce uniformly smooth training. These observations motivate matched learning-rate checks before attributing a difference to the mapper function class. Four lower-rate 16-update pilots passed numerical and decoding checks, but their proper 8,192-update fits were not executed within the experiment timebox. The pilots do not establish whether a lower rate resolves the degradation. Lower feature error alone does not establish a decoding gain. Full-answer quality, broader workloads and additional fitting seeds remain separate from this capped comparison.

### C.7 MATCHED WARM-TRAINING BUDGETS ON 512 EXAMPLES

We compare feature regression, connector cross-entropy (CE) and rank-32 drafter LoRA on the same 512-example pool. CE updates the connector while LoRA holds the initial connector fixed. Both use target-greedy teacher labels on the last 15 proposal positions. An equal three-rate development screen selects learning rate  $2 \times 10^{-5}$  for each adaptation family. Feature regression uses its declared rate  $6 \times 10^{-4}$ . The two LoRA seeds vary the update initialization and share the same initial mapper. They do not measure variation across initial mapper fits.

We measure 91.413 seconds of optimizer-update time for the 8,192-update feature baseline and declare budgets of 0.25, 1 and 4 times that cost. CE and LoRA begin with a 128-update mapper, whose measured 1.546 seconds of training counts toward each budget. Each worker stops after the first completed update reaching its remaining budget. Recorded overshoot is at most one update, ranging from 0.002 to 0.201 seconds across the twelve fits. The three four-GPU fitting jobs finish in 2m33s, 2m35s and 7m12s.

Table 29: Measured training costs and subsequent decoding in one common development campaign. Worker time includes model/cache setup, validation and export where performed, plus the measured initial mapper worker cost for CE and LoRA. It excludes Python startup and shared cache construction. Ratios compare against feature regression at the same warm budget.

| Budget | Objective     | Updates | Warm s | Worker s | Tok/s  | Feature ratio [95% CI] |
|--------|---------------|---------|--------|----------|--------|------------------------|
| 0.25×  | Feature MSE   | 2026    | 22.86  | 52.04    | 145.05 | 1.000 [1.000, 1.000]   |
| 0.25×  | Connector CE  | 106     | 22.94  | 91.89    | 111.04 | 0.766 [0.737, 0.791]   |
| 0.25×  | LoRA32 (1729) | 95      | 23.00  | 94.66    | 119.30 | 0.823 [0.786, 0.859]   |
| 0.25×  | LoRA32 (1730) | 94      | 22.86  | 95.20    | 119.52 | 0.824 [0.788, 0.860]   |
| 1×     | Feature MSE   | 8144    | 91.42  | 119.71   | 144.80 | 1.000 [1.000, 1.000]   |
| 1×     | Connector CE  | 474     | 91.58  | 161.04   | 109.60 | 0.757 [0.726, 0.786]   |
| 1×     | LoRA32 (1729) | 402     | 91.45  | 165.73   | 115.02 | 0.794 [0.757, 0.831]   |
| 1×     | LoRA32 (1730) | 407     | 91.50  | 164.61   | 115.49 | 0.798 [0.765, 0.830]   |
| 4×     | Feature MSE   | 32446   | 365.65 | 390.11   | 144.55 | 1.000 [1.000, 1.000]   |
| 4×     | Connector CE  | 1899    | 365.72 | 435.56   | 105.79 | 0.732 [0.699, 0.763]   |
| 4×     | LoRA32 (1729) | 1651    | 365.85 | 438.51   | 118.49 | 0.820 [0.786, 0.853]   |
| 4×     | LoRA32 (1730) | 1646    | 365.76 | 437.99   | 119.55 | 0.827 [0.793, 0.860]   |

Table 30: References measured within the same budget-decoding campaign. The initial mapper has 128 feature-regression updates. The 8,192-update reference is an existing saved checkpoint.

| Reference           | Tok/s  | Initial mapper ratio [95% CI] |
|---------------------|--------|-------------------------------|
| AR                  | 28.61  | 0.240 [0.207, 0.277]          |
| Native drafter      | 151.71 | 1.275 [1.205, 1.348]          |
| Source reuse        | 84.71  | 0.712 [0.684, 0.737]          |
| Initial mapper      | 119.01 | 1.000 [1.000, 1.000]          |
| Dense, 8192 updates | 145.82 | 1.225 [1.154, 1.302]          |

Feature regression reaches 145.05, 144.80 and 144.55 tokens/s at the three budgets. Relative to the quarter-budget fit, the 1-times and 4-times fits retain 99.83% [97.18, 102.53]% and 99.66% [97.35, 102.11]%, respectively. These intervals do not establish a benefit from longer fitting. Connector CE retains 73.2–76.6% of same-budget feature throughput, and the two LoRA seeds retain 79.4–82.7%. This result concerns the declared teacher-forced objective, initialization, rank and development-selected learning rates. It does not establish that other adaptation objectives or full drafter training fail.

Warm training is a marginal cost with cached features available. The historical full-cache extraction took 712.58 seconds and produced 292.8 GB. We reuse its first 512 training records and report the original construction cost separately. Dividing that cost by the record count would not measure a fresh 512-example extraction. The timed fits do not add training examples or repeat large-data scaling.

All seventeen methods decode the same sixteen exposed development questions with a 256-token cap. Tables 29 and 30 report descriptive paired request bootstrap intervals. They do not provide full-answer quality, untouched confirmation or corrections for selecting among multiple comparisons. Absolute throughput is interpreted within this common campaign and its deterministic training/runtime configuration.

## C.8 DRAFT LENGTH AND INTERFACE CHOICES

The block-size experiment directly compares AR, native DFlash and the relay at lengths 8, 16 and 32 on 64 fixed requests. Block 16 gives the highest relay throughput, 210.15 tokens/s (Table 13). Block 8 retains more source progress proportionally but advances fewer tokens per cycle. Block 32 adds verification width while reducing accepted progress for the released block-16 drafter. This supports keeping its trained block length instead of maximizing the relative gain over source reuse.

The EAGLE-3 normalization comparison holds parameter count, data and 128-update budget fixed. Raw target features reduce relative context error from 0.413 to 0.266 and increase the source-relative throughput ratio from 1.035 to 1.237. The raw interface consumes feature magnitude, which input normalization removes. This gives a concrete reason for preserving scale in the selected map.

Appendix C reports the DFlash objective, ridge and normalization comparisons with their distinct fitting recipes.

## D EXTERNAL BASELINES IN THEIR PUBLIC RUNTIMES

Table 31: Mechanism and evaluation scope of the closest alternatives. All rows inherit pretrained models. “No new fit” for PARD refers to retargeting its released checkpoint, not its original training cost. DFlash and EAGLE-3 are the inherited drafter families rather than independent competitors to RelaySpec’s interface replacement.

| Method                                | New-target adaptation                        | Use of target features            | Evidence here                                      |
|---------------------------------------|----------------------------------------------|-----------------------------------|----------------------------------------------------|
| RelaySpec                             | Fit input map, freeze drafter                | Replace source conditioning       | Two drafter families, 8B/14B targets               |
| PARD (An et al., 2026)                | No new fit for released drafter              | Target-independent proposals      | Public runtime, 128-question capped quality        |
| SD <sup>2</sup> (Berdoz et al., 2026) | Fit steering in tested frozen-drafter option | Inject steering within drafter    | Rate and epoch sweeps, 128-question capped quality |
| Connector CE                          | Fit input map with token CE                  | Same replacement interface        | Common-runtime matched warm budgets                |
| Drafter LoRA                          | Fit initial map, then LoRA with map frozen   | Adapt feature-conditioned drafter | Common-runtime matched warm budgets, two seeds     |

We evaluate SD<sup>2</sup>’s public frozen-drafter option and the released PARD parallel drafter on sixteen exposed MATH development requests with a 256-token cap. Each system has a correct cached AR control using its own target runtime and identical pretokenized inputs. These are short development comparisons. Below we separately evaluate capped answer quality. No untouched confirmation is included in these measurements.

SD<sup>2</sup> trains 402,665,472 steering parameters with merged guidance from target layers 3, 16 and 33 into all drafter layers. Inherited target and drafter weights remain frozen. Each of six objective/rate settings sees 512 distinct records once, using 128 batch-four updates and 95,835 non-padding supervised positions. Records are capped at 192 tokens. Training takes 47.0–48.6 seconds per fit. The initial TVD and KL settings also have exact fitting replicas, whose costs remain in the experiment record. This supervision differs from the feature-regression and last-15-position adaptation objectives in the preceding study.

Table 32: One-epoch SD<sup>2</sup> development comparison. Intervals resample paired requests 10,000 times and do not adjust for rate selection. Exact AR counts identical capped token sequences.

| Setting                 | Tok/s | AR ratio [95% CI]    | Independent ratio [95% CI] | Exact AR |
|-------------------------|-------|----------------------|----------------------------|----------|
| Matched AR              | 12.64 | 1.000 [1.000, 1.000] | 0.671 [0.622, 0.719]       | 16/16    |
| Independent drafter     | 18.83 | 1.490 [1.391, 1.607] | 1.000 [1.000, 1.000]       | 6/16     |
| Zero guidance           | 18.56 | 1.469 [1.371, 1.584] | 0.985 [0.983, 0.988]       | 6/16     |
| TVD, $10^{-5}$          | 18.38 | 1.454 [1.360, 1.567] | 0.976 [0.955, 0.997]       | 4/16     |
| KL, $10^{-5}$           | 18.17 | 1.438 [1.341, 1.552] | 0.965 [0.937, 0.993]       | 9/16     |
| TVD, $4 \times 10^{-6}$ | 18.52 | 1.466 [1.370, 1.574] | 0.984 [0.961, 1.006]       | 6/16     |
| TVD, $2 \times 10^{-5}$ | 18.47 | 1.462 [1.365, 1.570] | 0.981 [0.953, 1.011]       | 6/16     |
| KL, $4 \times 10^{-6}$  | 18.66 | 1.477 [1.384, 1.588] | 0.991 [0.962, 1.016]       | 5/16     |
| KL, $2 \times 10^{-5}$  | 18.42 | 1.458 [1.363, 1.569] | 0.978 [0.955, 1.003]       | 10/16    |

The public SD<sup>2</sup> evaluation configuration uses FP16 target storage, BF16 drafter and steering storage, and BF16 autocast under Transformers 4.52.4. We verify original FP32 training weights before conversion and separately fingerprint the BF16 inference tensors. The best fitted point, KL at  $4 \times 10^{-6}$ , retains 99.11% [96.19, 101.62]% of independent-drafter throughput. This screen does not establish a steering gain. We freeze this rate before checking additional epochs on the same small pool.

Table 33: Released PARD with zero new-target fitting, Transformers 4.51.3, BF16 weights, eager attention and static caches. The released checkpoint carries inherited proposer training.

| Setting          | Tok/s | AR ratio [95% CI]    | Exact AR |
|------------------|-------|----------------------|----------|
| Matched eager AR | 31.27 | 1.000 [1.000, 1.000] | 16/16    |
| Released PARD    | 98.60 | 3.153 [2.831, 3.558] | 4/16     |

Every SD<sup>2</sup> committed token matches its actual verifier decision, and immediate versus deferred observation preserves tokens and acceptance. Each timed PARD request has a separate verifier-observed replica with identical raw output and acceptance counts. PARD’s measured generation omits that added observer. Both timers include prefills and cache setup, preserve raw EOS/cap overshoot and exclude detokenization. Earlier failed exact-AR gates remain failed. Controlled cache, query and attention replays expose changes in rounded target scores, while future-query perturbations preserve earlier logits in the tested calls. The sequence differences in these tables require separate task-quality evidence. Absolute speeds across these public runtimes do not isolate algorithm effects, and shared model residency does not measure isolated serving memory.

#### D.1 ADDITIONAL EPOCHS AND CAPPED ANSWER QUALITY

After the six-rate screen, we fix KL and the selected learning rate and fit for 1, 2, 4 and 8 epochs on the same 512 examples. These are four fresh fits, each with its own learning-rate decay horizon, rather than checkpoints from one training trajectory. The one-epoch fit exactly reproduces the selected earlier training fingerprint. All four endpoints are evaluated together on the same sixteen development requests, with the public SD<sup>2</sup> runtime and matched controls.

Table 34: SD<sup>2</sup> epoch budget at fixed 512 distinct examples. Training KL is the mean over updates in each final epoch. It is not held-out loss. Independent-drafter throughput is 18.75 tokens/s. Intervals resample paired requests and do not adjust for model selection.

| Epochs | Fit seconds | Final-epoch training KL | Tok/s | Independent ratio [95% CI] |
|--------|-------------|-------------------------|-------|----------------------------|
| 1      | 48.44       | 0.3923                  | 18.56 | 0.9900 [0.9607, 1.0149]    |
| 2      | 97.01       | 0.2787                  | 18.45 | 0.9841 [0.9639, 1.0033]    |
| 4      | 193.81      | 0.2027                  | 18.39 | 0.9808 [0.9555, 1.0039]    |
| 8      | 388.08      | 0.1254                  | 18.26 | 0.9738 [0.9488, 0.9997]    |

Training KL decreases from 0.3923 to 0.1254, while every fitted endpoint has a throughput point below the independent drafter. Additional epochs do not establish a decoding improvement in this fixed-pool setting. The highest-throughput fitted endpoint remains one epoch. We freeze this checkpoint before longer quality evaluation. This result concerns the tested frozen-drafter configuration, supervision and pool, and does not establish a general failure of SD<sup>2</sup> or its other training options.

Table 35: PARD capped answer quality on 128 exposed MATH development requests, after an eight-request pilot passed. Both methods use the same 2048-token cap and public BF16 eager runtime. Cap hits include all outputs reaching the cap. None ends in EOS exactly at the cap.

| Setting          | Tok/s  | AR ratio [95% CI]    | Correct | Cap hits |
|------------------|--------|----------------------|---------|----------|
| Matched eager AR | 31.67  | 1.000 [1.000, 1.000] | 103/128 | 11       |
| Released PARD    | 105.63 | 3.335 [3.222, 3.451] | 105/128 | 8        |

PARD has five beneficial and three adverse correctness discordances against AR, a difference of +1.56 percentage points. A conservative paired 95% interval is  $[-6.34, 9.30]$  points: form exact 97.5% Clopper-Pearson intervals for each discordance probability and combine their opposite endpoints using a Bonferroni bound. This construction requires IID request pairs and a fixed candidate. It does not establish a one-percentage-point noninferiority margin. The descriptive paired bootstrap interval is  $[-2.34, 5.47]$  points. Sparse or absent discordances can make such intervals misleadingly narrow. These external-baseline measurements use development questions.

PARD matches AR’s full capped token sequence on 28 of 128 requests. Its mean output length is 664.5 tokens versus AR’s 690.4, so the 3.34-fold token-throughput ratio differs from the 3.47-fold request-time ratio. Every measured PARD request retains a separate, exactly matching verifier-observed replica. These are development outcomes under the specified runtime and scorer, not untouched confirmation or an isolated algorithm ranking across runtimes.

Table 36: Selected one-epoch SD<sup>2</sup> on the same 128 exposed MATH development requests, with a 2048-token cap. The public mixed-precision runtime and matched AR control are retained. Both have 11 cap-length outputs, none with EOS exactly at the cap.

| Setting                  | Tok/s | AR ratio [95% CI]    | Correct | Cap hits |
|--------------------------|-------|----------------------|---------|----------|
| Matched AR               | 12.48 | 1.000 [1.000, 1.000] | 103/128 | 11       |
| Selected SD <sup>2</sup> | 19.92 | 1.596 [1.560, 1.632] | 103/128 | 11       |

SD<sup>2</sup> and matched AR both score 103 of 128, with three beneficial and three adverse correctness discordances. The conservative paired 95% interval is  $[-7.04, 7.04]$  percentage points, which does not establish the one-point noninferiority margin. The descriptive paired bootstrap interval is  $[-3.91, 3.91]$  points. Full capped sequences agree on 42 requests. Mean output lengths are 679.1 versus 680.9 tokens, so the 1.60-fold token-throughput and request-time ratios are close. Both shards retain the same selected training and inference fingerprints, and saved answers reproduce under the pinned scorer.

The public physical-buffer limit can end an untimed warmup before its token cap. We record this termination only during warmup. Measured requests must still reach EOS or the cap and pass all actual-verifier checks. A replacement eight-request pilot passed before the complete quality run. Failed preliminary attempts remain excluded from the reported timings. These results concern the tested frozen-drafter configuration and its public runtime, not all SD<sup>2</sup> training options.

## E ACCEPTANCE AND NUMERICAL AGREEMENT

A retention value of 90% means the reused drafter produces 90% as many tokens per second as the target’s own drafter. It is not the fraction of speedup above AR. We also report the ratio of summed AR request time to summed relay request time. This differs from a throughput ratio when output lengths differ.

Acceptance explains how speed is obtained. We report the pooled number of tokens advanced per proposal-verification cycle, including the implementation’s target-supplied progress. This is distinct from the fraction of proposed draft tokens accepted. Appendix E gives the position-wise curves and precise counting convention.

Let  $c_R$  be the average relay cycle time and  $a_R$  its average progress. Its decode time per output token is approximately  $c_R/a_R$ . If  $c_A$  is AR time per token, then the decode-only approximation is

$$\text{AR-relative decode speed} \approx \frac{a_R c_A}{c_R}. \quad (4)$$

Removing source conditioning reduces cycle cost. Imperfect feature matching may reduce progress. The map is useful when the saved computation outweighs the extra cycles. We measure end-to-end speed directly and use this approximation to interpret the component measurements.

We pool all recorded proposal cycles rather than averaging each request’s mean. This weights cycles equally. DFlash’s recorded length is one already target-selected position plus the accepted draft prefix. EAGLE-3’s length follows its shared decoder’s progress count. These quantities measure work advanced per cycle, including target-supplied progress. A proposed-token acceptance fraction requires separating those positions and accounting for the number proposed.




Figure 13: Historical 8B source-reuse comparisons. Each curve gives the fraction of recorded cycles reaching each position. Summing the curve values gives mean recorded progress per cycle. Solid and dashed lines show source reuse and RelaySpec, respectively.

The main MATH-500 table reports measured full-sequence agreement with AR. A fresh diagnostic selects eight prompts with early differences and saves target inputs, cache lengths, positions and the two leading logits at every call. The DFlash paths share the same first differing choice across native, source and relay drafting. The observed BF16 logits include ties or changed ordering with gaps up to 0.25 at those positions. Such traces identify numerical score differences in the selected cases. They do not establish that all mismatches have the same cause. The task-quality intervals in Table 2 remain the empirical quality evidence.

## F MATCHED-COUNT TRAINING COMPOSITION

We compare two 2,048-record DFlash-8B fitting pools. The math-only arm uses NuminaMath records. The mixed arm replaces half with 1,024 Dolly general-instruction records.<sup>2</sup> Exact and lexical filters exclude matches to fitting validation, recorded evaluation prompts and the confirmation and reserve sets. The common validation set contains 1,024 math and 1,024 general-instruction records. Its cached feature files are identical across arms.

Each arm fits dense, linear-512 and MLP-512 maps at seed 1729, plus a second dense seed, 1730. Each fit uses 8,192 batch-four updates, learning rate 0.0006, no regularization and the same relative

<sup>2</sup>[databricks/databricks-dolly-15k](https://databricks.com/data/databricks-dolly-15k), revision bdd27f4d94b9, CC-BY-SA 3.0. General instructions can include mathematical questions.



interface objective. We retain the 2,048-update checkpoint as a fitting diagnostic, but preselect the 8,192-update endpoint for decoding rather than selecting by validation. Four independent fits run simultaneously on four L40S GPUs. Feature extraction took 111.4 seconds for the math cache and 107.1 for the mixed cache. The full fitting allocations took 4m36s and 4m21s, respectively. Extraction and fitting are separate costs.

Equal record counts and updates do not imply equal token exposure. With a 192-token record cap, the math pool contains 385,492 non-padding tokens and the mixed pool 316,518. Sixteen passes expose 6,167,872 and 5,064,288 tokens, respectively. The experiment therefore measures composition at matched records and updates, not matched tokens.

Table 37: Composition fitting at the preselected 8,192-update endpoint. Validation columns use the same held-out features in both arms. Reported seconds cover per-worker data access, updates and training-log writes, excluding validation, export and setup. Training losses concern different input distributions and are not directly comparable across arms.

| Mapper         | Training | Train loss | Math val. | General val. | Fit seconds |
|----------------|----------|------------|-----------|--------------|-------------|
| Dense          | math     | 0.1695     | 0.1805    | 0.3329       | 177.0       |
| Linear-512     | math     | 0.2629     | 0.2685    | 0.4719       | 114.5       |
| MLP-512        | math     | 0.2812     | 0.2878    | 0.4928       | 110.3       |
| Dense (seed 2) | math     | 0.1695     | 0.1805    | 0.3328       | 173.6       |
| Dense          | mixed    | 0.1854     | 0.1990    | 0.2234       | 167.0       |
| Linear-512     | mixed    | 0.3027     | 0.3015    | 0.3293       | 97.1        |
| MLP-512        | mixed    | 0.3221     | 0.3233    | 0.3479       | 110.2       |
| Dense (seed 2) | mixed    | 0.1852     | 0.1990    | 0.2231       | 152.7       |

Mixed training lowers dense general-instruction validation error by 32.9%, from 0.3329 to 0.2234, while raising math error by 10.2%, from 0.1805 to 0.1990. The second dense seed reproduces this tradeoff. At width 512, the linear and MLP maps show general-error reductions of 30.2% and 29.4%, with math-error increases of 12.3% in both cases. The matched linear map retains lower validation error than the MLP in both domains and both training arms. All three architectures improve in both validation domains between 2,048 and 8,192 updates.

**Fixed cross-domain decoding protocol.** Before observing endpoint results, we declare 32 development inputs from each of MATH-500, GSM8K, HumanEval and MT-Bench. The 128 initial inputs expand to 160 timed requests because MT-Bench includes two turns. All eight fixed endpoints run alongside AR, native DFlash and source reuse, producing 1,760 measured outputs capped at 2,048 tokens. A separate eight-input operational pilot completes in 2m58s before this full run. Methods rotate within requests in the same runtime. Ratios compare mixed and math-only fits of the same architecture and seed. Paired bootstrap intervals resample whole conversations for MT-Bench and individual requests elsewhere. They describe this development sample, without multiplicity adjustment or fitting-seed uncertainty.

The feature-domain tradeoff carries through to decoding, but depends on mapper capacity and task. Mixed dense training changes throughput by  $-1.2\%$  on MATH,  $+1.6\%$  on GSM8K,  $+2.9\%$  on HumanEval and  $+4.9\%$  on MT-Bench. The second dense seed gives  $-1.7\%$ ,  $+1.2\%$ ,  $+2.4\%$  and  $+4.7\%$ , respectively. The first seed’s MATH interval includes no change. Linear-512 and MLP-512 gain 11.6% and 10.8% on chat, but lose 6.2% and 7.8% on MATH and 2.6% and 4.1% on GSM8K. Dense remains faster than either smaller map on every task in both arms. General-domain feature improvement therefore supports useful workload-specific gains, not a uniform advantage from mixed training.

Every matched math/mixed pair produces identical generated token sequences on all 160 requests, including conversation turns. Thus these measured throughput gains do not arise from shorter outputs. All eight maps score 22/32 on MATH and 30/32 on GSM8K. AR scores 22/32 and 31/32. Four MATH outputs per method reach the cap, and none elsewhere does. The conservative paired accuracy-difference interval between matched arms is  $[-12.80, 12.80]$  percentage points on each math benchmark. Equal observed outcomes on this small sample do not establish tight population

quality noninferiority. Code and conversation outputs remain unscored for task quality. The full decoding allocation took 52m30s.




Figure 14: Effect of training composition on measured DFlash-8B throughput. Values above one favor mixed training. Marker shapes distinguish the four matched comparisons. Bars show paired 95% intervals. Code and conversation throughput does not establish output quality.

Table 38: All predeclared composition decoding comparisons. Throughput includes prompt processing. Ratios are mixed divided by math-only throughput, with paired 95% intervals. MT-Bench has 64 timed turns from 32 conversations. Each other task has 32 requests.

| Task      | Mapper         | Math tokens/s | Mixed tokens/s | Ratio (95% CI)      |
|-----------|----------------|---------------|----------------|---------------------|
| MATH      | Dense          | 201.1         | 198.6          | 0.988 [0.975,1.001] |
| GSM8K     | Dense          | 156.5         | 159.0          | 1.016 [1.000,1.032] |
| HumanEval | Dense          | 138.1         | 142.2          | 1.029 [1.018,1.042] |
| MT-Bench  | Dense          | 71.1          | 74.6           | 1.049 [1.038,1.059] |
| MATH      | Linear-512     | 165.4         | 155.1          | 0.938 [0.918,0.959] |
| GSM8K     | Linear-512     | 120.3         | 117.2          | 0.974 [0.954,0.997] |
| HumanEval | Linear-512     | 69.9          | 72.7           | 1.039 [1.022,1.058] |
| MT-Bench  | Linear-512     | 49.1          | 54.8           | 1.116 [1.092,1.141] |
| MATH      | MLP-512        | 155.6         | 143.5          | 0.922 [0.900,0.946] |
| GSM8K     | MLP-512        | 112.7         | 108.0          | 0.959 [0.937,0.982] |
| HumanEval | MLP-512        | 64.4          | 66.7           | 1.036 [1.022,1.050] |
| MT-Bench  | MLP-512        | 46.5          | 51.5           | 1.108 [1.087,1.131] |
| MATH      | Dense (seed 2) | 201.6         | 198.2          | 0.983 [0.969,0.996] |
| GSM8K     | Dense (seed 2) | 156.7         | 158.6          | 1.012 [1.001,1.023] |
| HumanEval | Dense (seed 2) | 138.0         | 141.4          | 1.024 [1.011,1.039] |
| MT-Bench  | Dense (seed 2) | 71.1          | 74.5           | 1.047 [1.037,1.058] |

Table 39: Composition evaluation: correct-answer and output-cap counts. MATH and GSM8K columns show correct answers followed by capped outputs, each out of 32. Code cap counts are out of 32 and chat cap counts out of 64 turns. HumanEval execution and MT-Bench answer quality are not scored in this experiment. Capped outputs remain in every aggregate.

| Method                | MATH correct / cap | GSM8K correct / cap | Code cap | Chat cap |
|-----------------------|--------------------|---------------------|----------|----------|
| AR                    | 22 / 4             | 31 / 0              | 0        | 0        |
| Native DFlash         | 22 / 4             | 30 / 0              | 0        | 0        |
| Source reuse          | 22 / 4             | 30 / 0              | 0        | 0        |
| Dense, math           | 22 / 4             | 30 / 0              | 0        | 0        |
| Dense, mixed          | 22 / 4             | 30 / 0              | 0        | 0        |
| Linear-512, math      | 22 / 4             | 30 / 0              | 0        | 0        |
| Linear-512, mixed     | 22 / 4             | 30 / 0              | 0        | 0        |
| MLP-512, math         | 22 / 4             | 30 / 0              | 0        | 0        |
| MLP-512, mixed        | 22 / 4             | 30 / 0              | 0        | 0        |
| Dense (seed 2), math  | 22 / 4             | 30 / 0              | 0        | 0        |
| Dense (seed 2), mixed | 22 / 4             | 30 / 0              | 0        | 0        |

## G FROZEN-CHECKPOINT GSM8K CONFIRMATION

We freeze the dense 512- and 2,048-example checkpoints at 8,192 updates and seed 1729 before generating confirmation outputs. The fixed test contains 256 GSM8K questions, sampled after exact and lexical exclusion against fitting data and collected evaluation history. A separate 256-question reserve remains unused. Operational pilots use eight previously exposed GSM8K questions, not confirmation requests. The same confirmation questions are evaluated in both drafter families, so the second family is not an independent benchmark sample.

The primary speed criterion requires the lower endpoint of the paired 95% throughput-ratio interval to exceed 0.95. DFlash retains 97.48% [96.90,98.06]% and EAGLE-3 retains 98.90% [98.14,99.66]%. Throughput includes prompt processing. Resampling uses requests as paired units, 10,000 draws and seed 1729. These intervals condition on the frozen fitting checkpoints rather than estimating fitting-seed variation.

Table 40: All frozen-confirmation methods on 256 GSM8K requests per family. At cap counts outputs of exactly 2,048 tokens. Comparisons are within each family’s runtime.

| Family  | Method         | Tokens/s | Correct | At cap |
|---------|----------------|----------|---------|--------|
| DFlash  | AR             | 38.0     | 236/256 | 0      |
| DFlash  | Native drafter | 170.3    | 236/256 | 0      |
| DFlash  | Source reuse   | 99.0     | 236/256 | 0      |
| DFlash  | Dense 512      | 157.8    | 236/256 | 0      |
| DFlash  | Dense 2,048    | 161.9    | 236/256 | 0      |
| EAGLE-3 | AR             | 36.9     | 236/256 | 0      |
| EAGLE-3 | Native drafter | 100.9    | 238/256 | 0      |
| EAGLE-3 | Source reuse   | 70.7     | 238/256 | 0      |
| EAGLE-3 | Dense 512      | 100.0    | 238/256 | 0      |
| EAGLE-3 | Dense 2,048    | 101.1    | 238/256 | 0      |

The predeclared quality criterion requires the conservative paired 95% accuracy-difference lower bound relative to AR to exceed  $-1$  percentage point. DFlash has two beneficial and two adverse discordances, giving  $[-3.07, 3.07]$  points. EAGLE-3 has two beneficial and no adverse discordances, giving  $[-1.63, 3.14]$  points. Both quality outcomes are inconclusive under this criterion. Therefore the joint speed-and-quality criterion is not established, despite both speed criteria passing. Within each family, the two mapper sizes have identical per-question correctness, with a conservative interval of  $\pm 1.70$  points. DFlash also has identical token outputs between mapper sizes on all 256 requests, while EAGLE-3 has identical outputs on 254. Comparisons with AR retain the finite-precision distinctions discussed elsewhere. No reserve extension or outcome-dependent tuning is performed.

Exclusion checks concern the recorded local history and lexical matches, not unknown pretraining exposure or semantic independence.

## H DATA CHECKS AND DEVELOPMENT EXPOSURE

The 4,096-record fitting manifest contains distinct problems with solutions. The loader renders both fields before applying the 192-token cap. Repeating the manifest changes presentations, not distinct records. The 32-question development set informed normalization and objective choices. The historical 468-question complement is computed from saved full-run outputs and retains that exposure history.

Normalized exact matching finds zero overlaps between the 4,096 fitting and 1,250 evaluation problem texts. For a second check, each text is split into unique normalized tokens. Token-set Jaccard overlap is the number of shared tokens divided by the number of tokens in either set. Each evaluation question is compared with its closest fitting record. Table 41 reports the resulting similarities.

Table 41: Closest fitting-to-evaluation token-set overlap. Threshold columns count evaluation records at or above the stated overlap.

| Task      | Maximum overlap | $\geq 0.80$ | $\geq 0.90$ | $\geq 0.95$ |
|-----------|-----------------|-------------|-------------|-------------|
| MATH-500  | 0.980           | 47          | 13          | 4           |
| GSM8K     | 0.378           | 0           | 0           | 0           |
| HumanEval | 0.290           | 0           | 0           | 0           |
| MBPP      | 0.333           | 0           | 0           | 0           |
| MT-Bench  | 0.571           | 0           | 0           | 0           |

MATH-500 includes 47 questions above 0.80 overlap and four above 0.95. These shared templates qualify the interpretation of math generalization. The fixed-map code and conversation evaluations give additional task coverage without changing the fitted map.

## I FITTING TIME AND ISOLATED MEMORY

Table 42: Selected map size and warm fitting-loop duration on four RTX 6000 Ada GPUs. Models are loaded before the recorded loop begins.

| Drafter | Target | Trainable weights (millions) | Fitting loop (seconds) |
|---------|--------|------------------------------|------------------------|
| DFlash  | 8B     | 52.43                        | 85.6                   |
| DFlash  | 14B    | 65.54                        | 118.0                  |
| EAGLE-3 | 8B     | 52.43                        | 86.7                   |
| EAGLE-3 | 14B    | 65.54                        | 118.5                  |

The fitting-loop timer covers source and target feature computation and matrix optimization. A complete setup also loads model weights, writes the map, reloads it and initializes generation. Published original training counts in Table 43 provide context for the additional-data requirement. They are not a wall-time or token-budget comparison with fitting a new native drafter.




Figure 15: Isolated EAGLE-3 peak allocated memory on RTX 6000 Ada. Each method runs in a fresh process on eight paired prompts per target. Source removal saves 7.80 GiB at 8B and 7.63 GiB at 14B.

GPU peak counters are reset before the measured request. Allocated memory counts live tensor allocations and differs from reserved allocator memory. The mixed-arm processes used for timing are not the basis of this source-removal measurement.

## J ADDITIONAL RELATED WORK

**Improving drafting.** EAGLE predicts future features with shifted tokens (Li et al., 2024a). EAGLE-3 combines feature layers and simulated drafting steps (Li et al., 2025). DFlash predicts a block in parallel (Chen et al., 2026), while Medusa uses several prediction heads (Cai et al., 2024). GRIFFIN addresses training-to-decoding token alignment (Hu et al., 2025). RepSpec changes the training structure (Huo et al., 2026), while VSD and Draft-OPD optimize accepted proposals (Zou et al., 2026; Lei et al., 2026). RelaySpec inherits the trained drafter and changes only its conditioning input.

**Proposal structure and execution.** EAGLE-2 and OPT-Tree adapt proposal trees (Li et al., 2024b; Wang et al., 2025). SpecInfer organizes tree verification (Miao et al., 2024). Distributed speculative inference and speculative speculative decoding overlap computation (Timor et al., 2025b; Kumar et al., 2026). Draft & Verify skips target layers (Zhang et al., 2024), LayerSkip trains early exits (Elhoushi et al., 2024), and Lookahead checks candidates without an auxiliary drafter (Fu et al., 2024). RelaySpec retains an external drafter and holds its released proposal structure fixed. We evaluate the cost and accepted progress of changing its feature source.

## K INHERITED DRAFTER TRAINING CONTEXT




Figure 16: Left: fraction of native target-specific drafter throughput retained by RelaySpec in paired MATH-500 runs. Right: published original DFlash and EAGLE-3 recipe sizes versus the additional RelaySpec fitting set. Recipe counts provide training-scale context, not a matched training experiment or an audit of each released checkpoint.

Table 43: Original drafter training and additional target adaptation. Record counts describe different training stages and objectives.

| Stage                                       | Records  | Relative to relay fit | Weights learned |
|---------------------------------------------|----------|-----------------------|-----------------|
| Published DFlash recipe (Chen et al., 2026) | ~800,000 | ~195×                 | Drafter         |
| Published EAGLE-3 recipe (Li et al., 2025)  | ~532,000 | ~130×                 | Drafter         |
| RelaySpec target adaptation                 | 4,096    | 1×                    | Feature map     |

The DFlash recipe reports about 800K target-generated records. The EAGLE-3 recipe uses about 68K ShareGPT and 464K UltraChat entries. Relay fitting uses 0.51% and 0.77% of these respective record counts. This comparison describes marginal adaptation: the original drafter’s training remains inherited. Record lengths, objectives and hardware differ, so these ratios do not represent equivalent reductions in training compute. The evaluated EAGLE-3 checkpoints come from DeepSpec, while the table’s EAGLE-3 count refers specifically to the published training recipe.