③

①

ARYAMAN MISHRA
19BCE1027

2) index.php

```html
<!doctype html>
<html>
    <head>
        <title> Resume Builder </title>
    </head>
    <body>
        <link href= "registration.css" type = text/css
        rel= "stylesheet" />
        <center><h2> Resume Builder </h2></center>
<form name = "form1" action = "modified.php"
    method= "post" enctype = "multipart/form-data">
        <div class = "container1">
            <center> Personal details </center>
        <div class = "form-group">
        <label> Name: </label>
            <input type = "text" name = "name" />
        </div>

        <div class = "form-group">

        <label> Gender </label>
    <input type = "text" name = "gender"
        placeholder = "Enter Male/Female/others"/>

        </div>
```

③
```html
<div class = "container2">
```

```
<center> Educational History ..

<div class = "form-group">
<label for = "birthday"> Birthday: </label>
<input type = "date"    name = "birthday">
</div>
<div class = "form-group">
<label for = "Address"> Address : </label>
    <input type = "text"  name = "address"  size = "100">
</div>
<div class = "form-group">
    <label> City </label>
<input type = "text"  name = "city"  value = ""
    placeholder: "Enter City Name"/>
<div class = "form-group">
<label> Country </label>
<input type = "text"  name = "country"  value = ""
    placeholder = "Enter Country Name"/>
<dev class = "form-group">
        <label> Phone Number: </label>

    <input type = "number"  name = "phone" />

</div>
</div>
```

③

```html
<div class="container2">
  <center> Educational History </center>
  <div>

  <div class="form-group">
  <label> lot 2 </label>
  <input type="text" name="grade" style="width:300px;">
  </div>

  <div class="form-group">
  <label> Higher Secondary Certificate </label>
  <input type="text" name="hsc" style="width:300px;">
  </div>

  <div class="form-group">
  <label> Undergraduate studies </label>
    <input type="text" name="ug" style="width:300px;">
  </div>

  <div class="form-group">
  <label> Doctor of philosophy details </label>
    <input type="text" name="phd" style="width:300px;
              height:inherit">
  </div>

  </div>
  </div>

<div class="container3">
<center> Work Experience </center>
<div>
```

```html
Starting year : <input type = "text" id = "syear" name = "syear"
        style = "width: 40px" value = "1900" >
Lasting year = <input type = "text" id = "lyear" name = "lyear"
        style = "width: 40px" value = "2100" >
Employer: <input type = "text" id = "employer" name = "employer"
        style = "width : 90px" >
Designation : <input type = "text" id = "designation" name = "designation"
        style = "width: 90px" >
From Date < input type = "date" id = "fromdate" name =
        "fromdate" >
To date < input type = "date" name = "todate" >
    </div>

    <div class = "container5" >
    <em> Projects : <input type = "text" id = "activities"
        name = "activities" style = "width : 300px;
            height: inherit " >

        </div>
        <button type = "submit" value = "submit" > Submit </button>

    </form>
</body >
</html>
```

(5)

listing. php

```php
<?php
include = " connection. php";
  if (isset ( $_POST ['fname']) )
    {
    $sql = " delete from db where uid = ' " . $_POST ['uid']. " ' ";
    $result = mysql_query ($sql);
    }

$sql = " select * from db";
$result = mysql_query ($sql);
?>

<html>
<body>
  <table>
    <tr>
      <td> Name </td>
      <td> Gender </td>
      <td> Birthday </td>
      <td> Address </td>
      <td> City </td>
      <td> Country </td>
      <td> Phone </td>
      <td> 1 or 2 </td>
      <td> MSC </td>
      <td> BeUG </td>
      <td> PhD </td>
      <td> Start year </td>
      <td> Last year </td>
      <td> Employer </td>
      <td> Designation </td>
      <td> Salary </td>
      <td> From date </td>
      <td> To date </td>
      <td> Projects <td>
<td colspan = "2"> </td></tr> </table> </body> <html>
```

modified.php

```php
<?php
while ( $row = mysql _ fetch-object ($rent))
    {
    ?>
    <tr>
    <td>
      <?php echo $row -> name; ?>
    </td>
    <td>

    <?php echo $row --> gender; ?>

    <?php echo $row --> birthday ; ?>

    <?php echo $row --> address ; ?>

    <?php echo $row --> city ; ?>

    <?php echo $row --> country; ?>

    <?php echo $row --> pincode; ?>

    <?php echo $row --> phone; ?>

    <?php echo $row --> grade; ?>

    <?php echo $row --> hsc; ?>

    <?php echo $row --> ug; ?>

    <?php echo $row --> phd; ?>

    <td> <?php echo $row --> syear ; ?>
      <?php echo $row --> lyear; ?>
      <?php echo $row --> employers ?>
      <?php echo $row --> projects; ?>
    </td>

.topnav :-
        display: non.
```

```
<td>
<a href = " listing.php? id =
<?php echo $row → id;?> "
onclick= " return confirm ('Are you sure')" > Edit
    </a>
    </td>
<tr>
    <?php } ?>
```

---

a. CSS

①
```css
body {
margin: 0;
font-family: Arial;
background-color: #bbb;
}
.topnav
{
  overflow: hidden;
  background-color: #333;
}
.topnav a {
  color: #f2f2f2;
  text-align: center;
  padding: 14px 16px;
  text-decoration: none;
  font-size: 17px;
}
.topnav a:hover {
    background-color: #ddd;
  color: black;
}
.active { color: white; }
.topnav .icon {background-color: #ddd; colour: black;
      display: none; }
```

```html
<!doctype html>
 <html>
  <head>
   <title> Attendance </title>.
   <script> function myfunction() {
      var present = 0, absent = 0;
      var x = document. getElementById ("myTopNew");
      if ( x. className === "topnew") {
           x. className = "reshnew";
           present = present + 1;
          }
       else
            absent = absent + 1;
        }
   }

      var pper = (present/60) * 100;
      var aper = (absent/60) * 100;
      console. log (absent);
      console. log (present);
      console. log (pper);
      console. log (aper); }
   </script>

   <body>
    <form>
      < div class = "topNew"   id= " myTopnew ">
       <a href = "javascript: void (0);" class = "icon"
                onclick = " myfunction () ">
         <table > <tr> <th> Roll No </th >
                       <th> Prese Attendence </th> <tr>
            <label class = "contuner " >
            <input type = " radio" name = " 1" >
            < span class = " checkmark" > </span >
             </label >   </td >
                # do this fill 60 students (name = "60" )
```

```
</table>
<center> <div id= "button"..>
<input type= "button"  onclick= "myfunction()" 
    <hr noshade width= " 1 px">
        ←th  </form>
            </body >
            </html>
```