




Univon Air All in One Domestic Hot Water Heat Pump Specifications

w.e.f: 01-04-2020

Model		Univon Air 200Ls	Univon Air 250Ls	Univon Air 300Ls
				
Rated heating Capacity	kW	2.5	2.5	2.5
Electric heater*	kW	2	2	2
Rated power input**	W	600 (+2000*)	600 (+2000*)	600 (+2000*)
Rated current**	A	2.9 (+ 8.6*)	2.9 (+ 8.6*)	2.16 (+6.5*)
COP**		4.16	4.16	4.16
Energy class*** (ERP)		A	A	A
Power supply	V/Ph/Hz	220-240/1/50		
Max outlet water temperature (without using E-heater)	°C	60		
Compressor		GMCC(Toshiba) PJ125		
Refrigerant		R134a		
Inner tank material		Steel Enamel tank.		
Heat pump heat exchanger coil		Copper External coil		
Solar thermal connection		Internal coil MS		
Expansion valve		Electronic expansion valve included		
Rated water yield	L/H	61	61	61
Max. water operating pressure	Mpa	1.0	1.0	1.0
Rated water pressure	Mpa	0.6	0.6	0.6
Set point relief valve	Mpa	0.7	0.7	0.7
Sound pressure level	dB (A)	48	48	48
Net weight	kg	88	95	102
Net size (WxHxD)	mm	Φ620×1750	Φ620×1850	Φ620×1950
Package size (WxHxD)	mm	700×700×1930	700×700×2030	700×700×2130
**Testing conditions: Ambient temperature 28°C, water temperature from 20°C to 60°C.				
***Testing conditions: Based on standard ERP, XL cycle: Ambient temperature 30°C/25°C, water temperature from 20°C to 60°C)				

Notes:

- The above specifications are subject to change without prior notice for product improvement. For final parameters, please refer to the nameplate on the machine.
- Warranty: 1 year for the whole unit.

for Unique Business Corporation



(Prashanth M R)
Cell, WhatsApp, WeChat : +91-94482 79449



THANK YOU FOR YOUR BUSINESS!