

Winning Space Race with Data Science

Aryan Rajesh



Outline

- Executive Summary
- Introduction
- Methodology
- Results
- Conclusion
- Appendix

Executive Summary


- **Summary of methodologies**

- SpaceX Data Collection using SpaceX API
- SpaceX Data Collection with Web Scraping
- SpaceX Data Wrangling
- SpaceX Exploratory Data Analysis using SQL
- Space-X EDA DataViz Using Python Pandas and Matplotlib
- Space-X Launch Sites Analysis with Folium-Interactive Visual Analytics and Plotly Dash
- SpaceX Machine Learning Landing Prediction

- **Summary of all results**

- EDA results
- Interactive Visual Analytics and Dashboards
- Predictive Analysis(Classification)

Introduction



- **Project background and context**

SpaceX advertises Falcon 9 rocket launches with a cost of 62 million dollars; other providers cost upward of 165 million dollars each, much of the savings is because SpaceX can reuse the first stage. Therefore if we can determine if the first stage will land, we can determine the cost of a launch. This information can be used if an alternate company wants to bid against SpaceX for a rocket launch.

- **Problems you want to find answers**

In this capstone, we will predict if the Falcon 9 first stage will land successfully using data from Falcon rocket launches advertised on its website.

Methodology

Methodology

Executive Summary

- Data collection methodology:
 - Describes how data sets were collected
- Perform data wrangling
 - Describes how data were processed
- Perform exploratory data analysis (EDA) using visualization and SQL
- Perform interactive visual analytics using Folium and Plotly Dash
- Perform predictive analysis using classification models
 - How to build, tune, evaluate classification models

Data Collection

Description of how SpaceX Falcon9 data was collected:

Data was first collected using SpaceX API (a RESTful API) by making a get request to SpaceX API. This was done by first defining a series helper functions that would help in the use of the API to extract information using identification numbers in the launch data and then requesting rocket launch data from the SpaceX API url. Finally to make the requested JSON results more consistent, the SpaceX launch data and parsed using the GET request and then decoded the response content as a JSON result which was then converted into a Pandas data frame. Also performed web scraping to collect Falcon 9 historical launch records from a Wikipedia page titled [List of Falcon 9 and Falcon Heavy launches](#) of the launch records are stored in a HTML using BeautifulSoup and request Libraries, I extract the Falcon 9 launch HTML table records from the Wikipedia page, Parsed the table and converted it into a Pandas data frame.

Data Collection – SpaceX API

Data collected using SpaceX API (a RESTful API) by making a get request to the SpaceX API then requested and parsed the SpaceX launch data using the GET request and decoded the response content as a Json result which was then converted into a Pandas data frame.

Task 1: Request and parse the SpaceX launch data using the GET request

To make the requested JSON results more consistent, we will use the following static response object for this project:

```
: static_json_url='https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBM-DS0321EN-SkillsNetwork/datasets/API_call_spacex_api.json'
```

We should see that the request was successfull with the 200 status response code

```
: response.status_code
```

```
: 200
```

Now we decode the response content as a Json using `.json()` and turn it into a Pandas dataframe using `.json_normalize()`

```
: # Use json_normalize meethod to convert the json result into a dataframe
respjson = response.json()
data = pd.json_normalize(respjson)
```


Data Collection - WebScraping

Performed web scraping to Falcon 9 historical launch records from a Wikipedia using BeautifulSoup and request, to extract the Falcon 9 launch records from HTML table of the Wikipedia page, then created a data frame by parsing the launch HTML.

```
In [4]: static_url = "https://en.wikipedia.org/w/index.php?title=List_of_Falcon_9_and_Falcon_Heavy_launches&oldid=1027686922"
```

Next, request the HTML page from the above URL and get a `response` object

TASK 1: Request the Falcon9 Launch Wiki page from its URL

First, let's perform an HTTP GET method to request the Falcon9 Launch HTML page, as an HTTP response.

```
In [5]: # use requests.get() method with the provided static_url
# assign the response to a object
response = requests.get(static_url)
```

Create a `BeautifulSoup` object from the HTML `response`

```
In [6]: # Use BeautifulSoup() to create a BeautifulSoup object from a response text content
soup = BeautifulSoup(response.content, 'html.parser')
```

Print the page title to verify if the `BeautifulSoup` object was created properly

```
In [7]: # Use soup.title attribute
soup.title
```

```
Out[7]: List of Falcon 9 and Falcon Heavy launches - Wikipedia
```

TASK 2: Extract all column/variable names from the HTML table header

Next, we want to collect all relevant column names from the HTML table header

Let's try to find all tables on the wiki page first. If you need to refresh your memory about `BeautifulSoup`, please check the external resource [this lab](#)

```
In [10]: # Use the find_all function in the BeautifulSoup object, with element type 'table'
# Assign the result to a list called 'html_tables'
```

Data Wrangling

After obtaining and creating a Pandas DF from the collected data, data was filtered using column to only keep the Falcon 9 launches, then dealt with the missing data values in the ***LandingPad*** and ***PayloadMass*** columns. For the ***PayloadMass***, missing data values were replaced using mean value of column. Also performed some Exploratory Data Analysis (EDA) to find some patterns in the data and determine what would be the label for training supervised models.

TASK 4: Create a landing outcome label from Outcome column

Using the `Outcome`, create a list where the element is zero if the corresponding row in `Outcome` is variable `landing_class`:

```
# landing_class = 0 if bad_outcome
# landing_class = 1 otherwise
df['Class'] = df['Outcome'].apply(lambda x: 0 if x in bad_outcomes else 1)
df['Class'].value_counts()
```

```
1    60
0    30
Name: Class, dtype: int64
```

This variable will represent the classification variable that represents the outcome of each launch. If the first stage landed Successfully



```
landing_class=df['Class']
df[['Class']].head(8)
```

	Class
0	0
1	0
2	0
3	0
4	0
5	0
6	1
7	1

EDA with Data Visualization

- Performed data Analysis and Feature Engineering using Pandas and Matplotlib i.e
 - Exploratory Data Analysis
 - Preparing Data Feature Engineering
- Used scatter plots to Visualize the relationship between Flight Number and Launch
- Payload and Launch Site, FlightNumber and Orbit type, Payload and Orbit type.
- Used Bar chart to Visualize the relationship between success rate of each orbit type
- Line plot to Visualize the launch success yearly trend.

EDA with Data Visualization (Plots Cont....)



EDA with SQL

- **The following SQL queries were performed for EDA:**

- Display the names of the unique launch sites in the space mission

```
%sql SELECT DISTINCT LAUNCH_SITE as "Launch_Sites" FROM SPACEXTBL;
```

- Display 5 records where launch sites begin with the string 'CCA'

```
%sql SELECT * FROM 'SPACEXTBL' WHERE Launch_Site LIKE 'CCA%' LIMIT 5;
```

- Display the total payload mass carried by boosters launched by NASA (CRS)

```
%sql SELECT SUM(PAYLOAD_MASS_KG_) as "Total Payload Mass(Kgs)", Customer FROM 'SPACEXTBL' WHERE Customer = 'NASA (CRS)';
```

- Display average payload mass carried by booster version F9 v1.1

```
%sql SELECT AVG(PAYLOAD_MASS_KG_) as "Payload Mass Kgs", Customer, Booster_Version FROM 'SPACEXTBL' WHERE Booster_Version LIKE 'F9 v1.1%';
```

EDA with SQL (Cont....)

- List the date when the first successful landing outcome in ground pad was achieved

```
%sql SELECT MIN(DATE) FROM 'SPACEXTBL' WHERE "Landing _Outcome" = "Success (ground pad)";
```

- List the total number of successful and failure mission outcomes

```
%sql SELECT "Mission_Outcome", COUNT("Mission_Outcome") as Total FROM SPACEXTBL GROUP BY "Mission_Outcome";
```

Build an Interactive Map with Folium

- Created folium map to marked all the launch sites, and created map objects such as markers, circles, lines to mark the success or failure of launches for each launch site.
- Created a launch set outcomes (failure=0 or success=1).

Build a Dashboard with Plotly Dash

- **Built an interactive dashboard application with Plotly dash by:**
 - Adding a Launch Site Drop-down Input Component
 - Adding a callback function to render success-pie-chart
 - Adding a Range Slider to Select Payload
 - Addeng a callback function to render the success-payload-scatter-chart scatter plot


SpaceX Dash App

SpaceX Launch Records Dashboard

All Sites

100%

Success Count for all launch sites




■ KSC LC-39A
■ CCAFS LC-40
■ VAFB SLC-4E
■ CCAFS SLC-40

Payload range (Kg):



Success count on Payload mass for site CCAFS LC-40



Booster Version Category
● v1.0
● v1.1
● FT

Predictive Analysis (Classification)

- Summary of how I built, evaluated, improved, and found the classification model
- After loading the data as a Pandas Dataframe, I set out to perform exploratory Data Analysis and determine Training Labels by;
 - creating a NumPy array from the column Class in data, by applying the then assigned it to the variable Y as the outcome variable.
 - Then standardized the feature dataset (x) by transforming it using function from Sklearn.
 - After which the data was split into training and testing sets using the function `train_test_split` from `sklearn.model_selection` with the `test_size` parameter set to `random_state` to 2.

Predictive Analysis (Classification)

- In order to find the best ML model/ method that would performs best using the test data between SVM, Classification Trees, k nearest neighbors and
- Logistic Regression;
 - First created an object for each of the algorithms then created a GridSearchCV and assigned them a set of parameters for each model.
 - For each of the models under evaluation, the GridsearchCV object was created then fit the training data into the GridSearch object for each to Find best Hyperparameter.
 - After fitting the training set, we output GridSearchCV object for each of the models then displayed the best parameters using the data attribute `best_params_` and the accuracy on the validation data using the data attribute `best_score_`.
 - Finally using the method score to calculate the accuracy on the test data for each model and plotted a confussion matrix for each using the test and predicted outcomes.

Predictive Analysis (Classification)

- The table below shows the test data accuracy score for each of the
- methods comparing them to show which performed best using the test data
- between SVM, Classification Trees, k nearest neighbors and Logistic
- Regression;

```
Out[68]:
```

Method	Test Data Accuracy
Logistic_Reg	0.833333
SVM	0.833333
Decision Tree	0.833333
KNN	0.833333

Results

- Exploratory data analysis results
- Interactive analytics demo in screenshots
- Predictive analysis results

Completed Source Code (GitHub):


<https://github.com/Aryan-Rajesh-Python/SpaceX-First-Stage-Landing-Prediction>

The background is a complex, abstract composition. It features a dark blue base color. Overlaid on this are numerous diagonal streaks and bands of lighter blue and vibrant red. These streaks vary in thickness and intensity, creating a sense of motion and depth. A faint, semi-transparent grid pattern is also visible, particularly in the upper right quadrant, where it intersects with the colored streaks. The overall effect is a high-tech, digital aesthetic.


Insights drawn
from EDA

Flight Number vs. Launch Site

A scatter plot of Flight Number vs. Launch Site



Flight Number vs. Launch Site with explanations




Now try to explain the patterns you found in the Flight Number vs. Launch Site scatter point plots.

We can deduce that, as the flight number increases in each of the 3 launch sites, so does the success rate. For instance, the success rate for the VAFB SLC 4E launch site is 100% after the Flight number 50. Both KSC LC 39A and CCAFS SLC 40 have a 100% success rates after 80th flight.


Payload vs. Launch Site

A scatter plot of Payload vs. Launch Site



Payload vs. Launch Site with explanations


A scatter plot of Payload vs. Launch Site



Now if you observe Payload Vs. Launch Site scatter point chart you will find for the VAFB-SLC launchsite there are no rockets launched for heavypayload mass(greater than 10000).


Success Rate vs. Orbit Type

- Show a bar chart for the success rate of each orbit type



Success Rate vs. Orbit Type with explanations

- Show the screenshot of the bar chart with explanations




Analyze the plotted bar chart try to find which orbits have high success rate.


Orbits ES-L1, GEO, HEO & SSO have the highest success rates at 100%, with SO orbit having the lowest success rate at ~50%. Orbit SO has 0% success rate.

Flight Number vs. Orbit Type

- A scatter point of flight number vs. Orbit type




Flight Number vs. Orbit Type with explanations



You should see that in the LEO orbit the Success appears related to the number of flights; on the other hand, there seems to be no relationship between flight number when in GTO orbit.

Payload vs. Orbit Type


- With heavy payloads the successful landing or positive landing rate are more LEO, ISS and PO
- However for GTO we cannot distinguish this well as both positive landing rate and negative landing(unsuccesful mission) both have near equal chances.



Launch Success Yearly Trend

A line chart of yearly average success rate

- Since 2013, the Success rate kept on increasing till 2020



All Launch Site Names

- Find the names of unique launch sites

Task 1

Display the names of the unique launch sites in the space mission

```
In [31]: %sql SELECT DISTINCT LAUNCH_SITE as "Launch_Sites" FROM SPACEXTBL;
```

```
* sqlite:///my_data1.db  
Done.
```

```
Out[31]: Launch_Sites
```

```
CCAFS LC-40
```

```
VAFB SLC-4E
```

```
KSC LC-39A
```

```
CCAFS SLC-40
```

Launch Site Names Begin with 'CCA'

- Find 5 records where launch sites begin with 'CCA'

Task 2

Display 5 records where launch sites begin with the string 'CCA'

```
In [72]: %sql SELECT * FROM 'SPACEXTBL' WHERE Launch_Site LIKE 'CCA%' LIMIT 5;
```

```
* sqlite:///my_data1.db  
Done.
```

```
Out[72]:
```

Date	Time (UTC)	Booster_Version	Launch_Site	Payload	PAYLOAD_MASS_KG_	Orbit	Customer	Mission_Outcome	Landing_Outcome
04-06-2010	18:45:00	F9 v1.0 B0003	CCAFS LC-40	Dragon Spacecraft Qualification Unit	0	LEO	SpaceX	Success	Failure (parachute)
08-12-2010	15:43:00	F9 v1.0 B0004	CCAFS LC-40	Dragon demo flight C1, two CubeSats, barrel of Brouere cheese	0	LEO (ISS)	NASA (COTS) NRO	Success	Failure (parachute)
22-05-2012	07:44:00	F9 v1.0 B0005	CCAFS LC-40	Dragon demo flight C2	525	LEO (ISS)	NASA (COTS)	Success	No attempt
08-10-2012	00:35:00	F9 v1.0 B0006	CCAFS LC-40	SpaceX CRS-1	500	LEO (ISS)	NASA (CRS)	Success	No attempt
01-03-2013	15:10:00	F9 v1.0 B0007	CCAFS LC-40	SpaceX CRS-2	677	LEO (ISS)	NASA (CRS)	Success	No attempt

Total Payload Mass

- Calculate and Display the total payload carried by boosters from NASA

Task 3

Display the total payload mass carried by boosters launched by NASA (CRS)

```
In [17]: %sql SELECT SUM(PAYLOAD_MASS__KG_) as "Total Payload Mass(Kgs)", Customer FROM 'SPACEXTBL' WHERE Customer = 'NASA (CRS)';
```

```
* sqlite:///my_data1.db
```

```
Done.
```

```
Out[17]:
```

Total Payload Mass(Kgs)	Customer
45596	NASA (CRS)

Average Payload Mass by F9 v1.1

- Calculate the average payload mass carried by booster version F9 v1.1

Task 4

Display average payload mass carried by booster version F9 v1.1

```
%sql SELECT AVG(PAYLOAD_MASS_KG_) as "Payload Mass Kgs", Customer, Booster_Version FROM 'SPACEXTBL' WHERE Booster_Version LIKE 'F9 v1.1%';
```

```
* sqlite:///my_data1.db  
Done.
```

Payload Mass Kgs	Customer	Booster_Version
2534.6666666666665	MDA	F9 v1.1 B1003

First Successful Ground Landing Date

- Find the dates of the first successful landing outcome on ground pad

Task 5

List the date when the first successful landing outcome in ground pad was achieved.

Hint: Use min function

```
%sql SELECT MIN(DATE) FROM 'SPACEXTBL' WHERE "Landing _Outcome" = "Success (ground pad)";
```

```
* sqlite:///my_data1.db  
Done.
```

MIN(DATE)

01-05-2017

Successful Drone Ship Landing with Payload between 4000 and 6000

- List of Boosters which have successfully landed on drone ship and had payload mass greater than 4000 but less than 6000

Task 6

List the names of the boosters which have success in drone ship and have payload mass greater than 4000 but less than 6000

```
] # %sql SELECT * FROM 'SPACEXTBL'
```

```
] %sql SELECT DISTINCT Booster_Version, Payload FROM SPACEXTBL WHERE "Landing _Outcome" = "Success (drone ship)" AND PAYLOAD_MASS__KG_ > 4000 AND PAYLOAD_MASS__KG_ < 6000
```

```
* sqlite:///my_data1.db  
Done.
```

```
] 

| Booster_Version | Payload               |
|-----------------|-----------------------|
| F9 FT B1022     | JCSAT-14              |
| F9 FT B1026     | JCSAT-16              |
| F9 FT B1021.2   | SES-10                |
| F9 FT B1031.2   | SES-11 / EchoStar 105 |


```


Total Number of Successful and Failure Mission Outcomes

- Calculate the total number of successful and failure mission outcomes

Task 7

List the total number of successful and failure mission outcomes

```
%sql SELECT "Mission_Outcome", COUNT("Mission_Outcome") as Total FROM SPACEXTBL GROUP BY "Mission_Outcome";
```

```
* sqlite:///my_data1.db
```

```
Done.
```

Mission_Outcome	Total
Failure (in flight)	1
Success	98
Success	1
Success (payload status unclear)	1

Boosters Carried Maximum Payload

- List of the boosters which have carried the maximum payload mass

```
%sql SELECT "Booster_Version",Payload, "PAYLOAD_MASS_KG_" FROM SPACEXTBL WHERE "PAYLOAD_MASS_KG_" = (SELECT MAX("PAYLOAD_MASS_KG_") FROM SPACEXTBL)
```

```
* sqlite:///my_data1.db  
Done.
```

Booster_Version	Payload	PAYLOAD_MASS_KG_
F9 B5 B1048.4	Starlink 1 v1.0, SpaceX CRS-19	15600
F9 B5 B1049.4	Starlink 2 v1.0, Crew Dragon in-flight abort test	15600
F9 B5 B1051.3	Starlink 3 v1.0, Starlink 4 v1.0	15600
F9 B5 B1056.4	Starlink 4 v1.0, SpaceX CRS-20	15600
F9 B5 B1048.5	Starlink 5 v1.0, Starlink 6 v1.0	15600
F9 B5 B1051.4	Starlink 6 v1.0, Crew Dragon Demo-2	15600
F9 B5 B1049.5	Starlink 7 v1.0, Starlink 8 v1.0	15600
F9 B5 B1060.2	Starlink 11 v1.0, Starlink 12 v1.0	15600
F9 B5 B1058.3	Starlink 12 v1.0, Starlink 13 v1.0	15600
F9 B5 B1051.6	Starlink 13 v1.0, Starlink 14 v1.0	15600
F9 B5 B1060.3	Starlink 14 v1.0, GPS III-04	15600
F9 B5 B1049.7	Starlink 15 v1.0, SpaceX CRS-21	15600

2015 Launch Records

- List of failed landing outcomes in drone ship, with their booster versions
- and launch site names in 2015

Task 9

List the records which will display the month names, failure landing_outcomes in drone ship, booster versions, launch_site for the months in year 2015.

```
%sql SELECT substr(Date,7,4), substr(Date, 4, 2),"Booster_Version", "Launch_Site", Payload, "PAYLOAD_MASS_KG_", "Mission_Outcome", "Landing _Outcome"
```

```
* sqlite:///my_data1.db
```

Done.

substr(Date,7,4)	substr(Date, 4, 2)	Booster_Version	Launch_Site	Payload	PAYLOAD_MASS_KG_	Mission_Outcome	Landing _Outcome
2015	01	F9 v1.1 B1012	CCAFS LC-40	SpaceX CRS-5	2395	Success	Failure (drone ship)
2015	04	F9 v1.1 B1015	CCAFS LC-40	SpaceX CRS-6	1898	Success	Failure (drone ship)

Rank Landing Outcomes Between 2010-06-04 and 2017-03-20

- Rank the count of landing outcomes (such as Failure (drone ship) or Success (groundpad)) between the date 2010-06-04 and 2017-03-20, in descending order

Task 10

Rank the count of successful landing_outcomes between the date 04-06-2010 and 20-03-2017 in descending order.

```
%sql SELECT * FROM SPACEXTBL WHERE "Landing _Outcome" LIKE 'Success%' AND (Date BETWEEN '04-06-2010' AND '20-03-2017') ORDER BY Date DESC;
```

```
* sqlite:///my_data1.db  
Done.
```


Date	Time (UTC)	Booster_Version	Launch_Site	Payload	PAYLOAD_MASS_KG_	Orbit	Customer	Mission_Outcome	Landing_Outcome
19-02-2017	14:39:00	F9 FT B1031.1	KSC LC-39A	SpaceX CRS-10	2490	LEO (ISS)	NASA (CRS)	Success	Success (ground pad)
18-10-2020	12:25:57	F9 B5 B1051.6	KSC LC-39A	Starlink 13 v1.0, Starlink 14 v1.0	15600	LEO	SpaceX	Success	Success
18-08-2020	14:31:00	F9 B5 B1049.6	CCAFS SLC-40	Starlink 10 v1.0, SkySat-19, -20, -21, SAOCOM 1B	15440	LEO	SpaceX, Planet Labs, PlanetIQ	Success	Success
18-07-2016	04:45:00	F9 FT B1025.1	CCAFS LC-40	SpaceX CRS-9	2257	LEO (ISS)	NASA (CRS)	Success	Success (ground pad)
18-04-2018	22:51:00	F9 B4 B1045.1	CCAFS SLC-40	Transiting Exoplanet Survey Satellite (TESS)	362	HEO	NASA (LSP)	Success	Success (drone ship)

A satellite view of Earth from space, showing the curvature of the planet and the glow of city lights at night. The background is a deep blue gradient.

Section 3

Launch Sites Proximities Analysis


Markers of all launch sites on global map



- All launch sites are in proximity to the Equator, (located southwards of the US)
Also all the launch sites are in very close proximity to the coast.

Launch outcomes for each site on the map


Florida Sites



- In the Eastern coast (Florida) Launch site KSC LC-39A has relatively high success rates compared to CCAFS SLC-40 & CCAFS LC-40.

Launch outcomes for each site on the map With

West Coast/ Carlifonia




- In the West Coast
- (Cala) Launch
- site VAFB SLC-4E has
- relatively lower
- success rates 4/10
- compared to KSC LC-
- 39A launch site in the
- Eastern Coast of
- Florida.

Distances between a launch site to its proximities



- Launch site CCAFS SLC-40 proximity to coastline is 0.86km

Distances between a launch site to its proximities




- Launch site CCAFS SLC-40 closest to highway (Washington Avenue is 23.19km



Section 4


Build a Dashboard with Plotly Dash

Pie-Chart for launch success count for all sites




- Launch site KSC LC-39A has the highest launch success rate at 42% followed by CCAFS LC-10 29%, VAFB SLC-4E at 17% and lastly launch site CCAFS SLC-40 with a success rate of 13%

Pie chart for the launch site with 2nd highest launch success ratio



- Launch site CCAFS LC-40 had the 2nd highest success ratio of 73% success against 27% failed launches

Payload vs. Launch Outcome scatter plot for all sites



- For Launch site CCAFS LC-40 the booster version FT has the largest success rate from a payload mass of >2000kg



Section 5

Predictive Analysis (Classification)

Classification Models Accuracy

Out[68]:


0

Method	Test Data Accuracy
Logistic_Reg	0.833333
SVM	0.833333
Decision Tree	0.833333
KNN	0.833333

All the methods perform equally on the test data: i.e. They all have the same accuracy of 0.833333 on the test Data

Confusion Matrix

- All the 4 models had the same confusion matrixes and were able to equally distinguish between the different classes. The major problem is false positives for all the models.



Conclusions

- Different launch sites have different success rates. CCAFS LC-40, has a success rate of 60 %, while KSC LC-39A and VAFB SLC 4E has a success rate of 77%.
- We can deduce that, as the flight number increases in each of the 3 launch sites, so does the success rate. For instance, the success rate for the VAFB SLC 4E launch site is 100% after the
- Flight number 50. Both KSC LC 39A and CCAFS SLC 40 have a 100% success rates after 80th
- flight
- If you observe Payload Vs. Launch Site scatter point chart you will find for the VAFB-SLC launchsite there are no rockets launched for heavypayload mass(greater than 10000).
- Orbits ES-L1, GEO, HEO & SSO have the highest success rates at 100%, with SO orbit having
- the lowest success rate at ~50%. Orbit SO has 0% success rate.
- LEO orbit the Success appears related to the number of flights; on the other hand, there seems to be no relationship between flight number when in GTO orbit

Conclusions Cont....

- With heavy payloads the successful landing or positive landing rate are more LEO and ISS. However for GTO we cannot distinguish this well as both positive
- landing rate and negative landing(unsuccesful mission) are both there here
- And finally the success rate since 2013 kept increasing till 2020.

Thank you!

