



SYMBIOSIS INSTITUTE OF TECHNOLOGY (SIT)

Constituent of Symbiosis International (Deemed University), Pune

(Established under Section 3 of the UGC Act of 1956 vide notification number F-9-12/2001-U-3 of the Government of India)
Re-Accredited by NAAC with 'A++' Grade

Name of Student: Aryan Singh Kasera

PRN: 25070122052

Subject: Programming with Java

Sem: III AY: 2026-27

Assignment No: 3

TITLE: Develop a Java application demonstrating method overloading and the use of static

variables, methods in class design.

Problem Statement

Develop a Java application demonstrating method overloading and the use of static variables, methods in class design.

Learning Objectives

To implement method overloading and use static variables and methods in Java programs.

Theory

Method overloading allows multiple methods to have the same name with different parameter lists, enabling compile-time polymorphism. The static keyword is used for variables and methods that belong to the class instead of individual objects. Static members share common data among all objects and reduce memory usage. These concepts improve code flexibility, readability, and efficient resource management.

1. Develop a Calculator program using overloaded methods for addition of integers and decimals. Use a static variable to count calculations.

Calculator.java

Share

Run

```
1 class Calculator {
2     static int count = 0;
3
4     int add(int a, int b) {
5         count++;
6         return a + b;
7     }
8
9     double add(double a, double b) {
10        count++;
11        return a + b;
12    }
13
14    public static void main(String[] args) {
15        Calculator c = new Calculator();
16
17        System.out.println("Integer Addition: " + c.add(11, 22));
18        System.out.println("Decimal Addition: " + c.add(14.5, 9.5));
19        System.out.println("Total Calculations: " + count);
20    }
21 }
22
```

OUTPUT


Output

Integer Addition: 33
Decimal Addition: 24.0
Total Calculations: 2

=== Code Execution Successful ===

2. Develop a Restaurant Billing Application where overloaded methods calculate bills for dine-in, takeaway, and delivery orders, while static variables track total orders.

Restaurant.java



Run

```
1 class Restaurant {
2     static int totalOrders = 0;
3
4     double bill(double amount) {
5         totalOrders++;
6         return amount;
7     }
8
9     double bill(double amount, double packingCharge) {
10        totalOrders++;
11        return amount + packingCharge;
12    }
13
14    double bill(double amount, double deliveryCharge, double tax) {
15        totalOrders++;
16        return amount + deliveryCharge + tax;
17    }
18
19    public static void main(String[] args) {
20        Restaurant r = new Restaurant();
21
22        System.out.println("Dine-in Bill: " + r.bill(5500));
23        System.out.println("Takeaway Bill: " + r.bill(5500, 20));
24        System.out.println("Delivery Bill: " + r.bill(5500, 50, 25));
25
26        System.out.println("Total Orders: " + totalOrders);
27    }
```

OUTPUT

Output

Dine-in Bill: 5500.0

Takeaway Bill: 5520.0

Delivery Bill: 5575.0

Total Orders: 3

=== Code Execution Successful ===