# Adaptation is not enough: a pre-registered comparison of adaptation and prediction-error mechanisms in a small spiking network

Aryan Karjagi

November 2026 (draft)

## Abstract

Neurons in the auditory system respond more strongly to a rare “deviant” tone than to a frequent “standard”. A long-running question is how much of this comes from simple adaptation (neurons getting less responsive to what they have just heard) and how much from prediction (the brain signalling that the input did not match what it expected). I compare these explanations in a small, fully reproducible spiking neural network (100 excitatory and 20 inhibitory leaky integrate-and-fire neurons). All predictions and pass rules were written down before each experiment was run, and every result is reported, including the ones that went against my predictions. **(1)** Adaptation alone, in this network, explains the deviant-versus-standard difference entirely as repetition suppression. Short-term synaptic depression gives a stimulus-specific adaptation (SSA) index of 0.19 [0.18, 0.20], but the prediction-error component is indistinguishable from zero (−0.000 [−0.011, 0.011]) and there is no response to an omitted tone. This null holds when adaptation is made ten times slower. **(2)** I then ask what is the smallest addition that produces two signatures that adaptation cannot: a larger response to an unexpected repeat in an alternating sequence (ABAB**AA**), and a response to a missing tone. A predictive-coding core (delay line, learned predictions, positive and negative error cells, a simplified version of Wacongne et al., 2012) produces both only after long training. My proposed addition, a *mismatch gate* that briefly speeds up learning, raises sensory gain and opens candidate predictions after a surprise, produces both at normal training (unexpected repeat +7.57 [3.98, 11.15] spikes against −2.84 [−3.62, −2.07] for adaptation alone). Ablations show error cells, learning and the gate are all needed. Four of my more specific predictions were not supported, including one-shot learning and a steady build-up of the omission response with regularity. The gated mechanism’s main effects disappeared when adaptation was made slower without re-tuning. Re-tuned by the original sanity rules (a 15% change to three weights), they return at $\tau_w$ = 1000 ms (repeat +6.75 [2.95, 10.55], omission 4.98 [3.09, 6.88]); at $\tau_w$ = 3000 ms only a weak repeat effect returns and the omission effect does not. The result is therefore a sufficiency result in a toy model: the gate makes learning faster, not something the predictive core cannot do. It says nothing about real brains.

## 1. Introduction

The *oddball* paradigm plays a frequent tone (the standard) with a rare different one (the deviant). Neurons respond more to the deviant. In single neurons this is called stimulus-specific adaptation (SSA); in the EEG, the mismatch negativity (MMN). Two families of explanation compete:

- **Adaptation.** Neurons tuned to the standard have fired a lot and are tired, so the deviant, which drives fresher neurons, gets a bigger response. May & Tiitinen (2010) argued that synaptic habituation can account for the MMN, and computational models reproduce SSA from adaptation alone (Mill et al., 2011; Yarden & Nelken, 2017).
- **Prediction error.** The brain learns a model of the sequence and responds to what it did not predict. Wacongne, Changeux & Dehaene (2012) built a spiking predictive-coding model that reproduces the MMN, a response to an *unexpected repeat* in an alternating sequence, and a response to an *omitted* tone. A purely stimulus-specific adaptation account predicts the opposite for the repeat (a *smaller* response, since the repeated tone was just heard) and nothing at all for an omission (no input, no response).

Parras et al. (2017) made this distinction measurable in single neurons. With a *many-standards* control (the target tone at the same probability among many tones) and a *cascade* control (the same tones in a predictable ascending run), the deviant-minus-standard response splits into **repetition suppression** (iRS = control − standard) and a **prediction-error** part (iPE = deviant − control). They found iPE grows along the auditory hierarchy (see also the review by Carbajal & Malmierca, 2018, and Ruhnau, Herrmann & Schröger, 2012, on control choice).

This project asks two questions in one small network where every part can be switched on and off:

1. **What does adaptation alone explain?** I implement two adaptation mechanisms separately and apply the Parras-style decomposition.
2. **What is the smallest mechanism that must be added** to produce an unexpected-repeat response and an omission response? I compare a slow predictive-coding core with my proposed *mismatch gate* and ablate the gate's parts.

**Contributions.** (i) A reproducible, open spiking model in which adaptation and prediction mechanisms are tested separately under pre-registered predictions. (ii) A clean negative result: in this network adaptation of either kind, fast or slow, produces SSA but no prediction-error component and no omission response. (iii) A proposed surprise-gated mechanism, with ablations, a robustness sweep over its constants and an honest list of what it does not do.

**Relation to prior work.** Surprise-modulated learning rates are well established (Yu & Dayan, 2002; Faraji, Preuschoff & Gerstner, 2018; Liakoni et al., 2021), including Bayesian models of the MMN (Lieder et al., 2013) and a spiking network with a surprise-gated three-factor rule (Barry & Gerstner, 2024). Holding several sequence predictions at once has also been modelled, in spiking sequence networks (Bouhadjar et al., 2022) and as competing interpretations of sound sequences (Mill et al., 2013). Other network models produce omission responses (Chien, Maess & Knösche, 2019). In a search of about 30 queries (not a systematic review; `docs/NOVELTY_CHECK.md`), I did not find a spiking model in which a single mismatch gate jointly boosts plasticity, raises sensory gain and opens several candidate predictions, tested on oddball, unexpected-repeat and omission paradigms. I present that combination, not its parts, as the contribution.

## 2. Methods

All code, parameters and pre-registrations are in the repository. Simulations use Brian2 2.10.1. Every random draw is seeded, so re-running a command reproduces identical numbers.

### 2.1 Network





**Figure 1. Model.** The Experiment 1 network (N0) is the tone input, the sensory E cells with switchable adaptation, and an inhibitory pool. The predictive core (B) adds a tapped delay line (T), prediction cells with learned weights (L) and positive and negative error cells (E). PE+ fires when input exceeds the prediction and teaches the weights; PE− fires when a prediction is not met by input. Mechanism A adds the mismatch gate (G), driven by PE+, which raises the learning rate and sensory gain and (in A2b) turns on candidate predictions (C).

**Sensory network (N0).** Ten tone channels, each with 10 excitatory leaky integrate-and-fire (LIF) neurons (100 E cells), and one shared pool of 20 inhibitory cells providing feedback inhibition. Each channel receives 20 Poisson input units firing at 100 Hz during a 50 ms tone, with Gaussian tuning (width 0.7 channels, so neighbours get 36% of full weight). Membrane time constant 20 ms, threshold −50 mV, current-based synapses. There are no recurrent excitatory connections. Four constants (noise, input weight, E→I weight, depression utilisation) were calibrated against sanity targets written down beforehand: spontaneous rate 1–5 Hz, an unadapted evoked response of 20–60 spikes per channel, and inhibitory cells active but below 30 Hz. They were never tuned to an experimental outcome.

**Adaptation**, switchable, giving four conditions (none, SFA, depression, both):

- *Spike-frequency adaptation (SFA):* each spike adds 2 mV to an adaptation current that decays with $\tau_w$ = 300 ms.
- *Short-term depression:* Tsodyks–Markram-style depression on the input synapses (utilisation 0.1, recovery 500 ms, no facilitation).

**Predictive core (B).** For each predictive channel: a *tapped delay line* (T; 20 lags of 50 ms, which lets the network know when a tone happened), *prediction cells* P driven by the delay line through plastic weights (L), and *positive and negative error cells* (E). PE+ is excited by the sensory cells and inhibited by P. PE− is excited by P and inhibited by the sensory cells. Weights from the delay line to P grow when PE+ is active while the delay cell carries an eligibility trace, so errors teach and fully predicted tones cause no learning. B is a simplified, loosely Wacongne-style network, **not** a replication: LIF instead of Izhikevich neurons, 10-cell instead of 40-cell populations, a tapped delay line instead of a synfire chain, and no NMDA currents.

**Mechanism A (the proposal).** A *mismatch gate* G jumps with each PE+ spike, decays over 1.5 s and is cut by "match" cells that need both sensory input and a prediction. While the gate is up it (i) multiplies the learning rate by 3, (ii) raises the gain of the input synapses (sensitisation), and, in variant **A2b**, (iii) turns on three *candidate predictions*: the tone that just caused the error repeats, the earlier tone returns, or something new appears. Variant **A1** replaces the candidates with faster forgetting of old predictions. A adds about 13 constants to the roughly 25 of the core. Gate constants were calibrated on development seeds (100–104) against sanity targets, for example that the gated learner predicts a new pair within about three exposures without large over-prediction. Test seeds were separate.

### 2.2 Experiments and measures

**Experiment 1 (adaptation alone).** Oddball blocks of 400 tones (deviant probability 0.1, standard on channel 3, deviant on channel 6, inter-stimulus interval 300–500 ms) in a flip-flop design, plus many-standards and cascade controls matched in target probability. The response is the baseline-corrected spike count of the 10 cells of the target channel in 0–180 ms after onset (window from Parras et al., 2017). From these I compute the SSA index (D − S)/(D + S) and the normalised decomposition iMM = iRS + iPE. Sweeps cover frequency gap (1–6 channels) and deviant probability (0.05–0.3). Omission blocks drop tones from a regular sequence. Pre-registration: `docs/PREREGISTRATION.md`.

**Experiment 2 and Tier 2 (what must be added).** All with both adaptation mechanisms on and a fixed 450 ms tone-to-tone interval, comparing N0, B, A1 and A2b:

- **T1 omission.** Tone A repeated, 20% of tones omitted. Measure (v3, see §2.3): PE− spikes at omitted slots minus at present-tone slots. Pass: 95% CI above 0 and a mean of at least 1 spike.
- **T2 unexpected repeat.** ABAB… with 10% of B replaced by A. Measure: response to the repeated A minus the regular A.
- **M1, the tone after the odd one.** Episodes A×(6–9), B, then a continuation. Measure: the first A after B minus the last A before it, compared against N0.
- **M2, M3, M5:** drop-off slopes, error and gate when the continuation fits a candidate, and continuation types including a random one.
- **One-shot learning, regularity build-up (1, 2, 4, 8 regular tones before an omission), timing jitter (0–60% of the interval)**, an **ablation** over subsets of {T, E, L, G, C}, a **robustness** sweep (40 random draws of A2b's constants), and a **long-training** fairness check for B (600 instead of 160 slots).

**General pass rule:** the 95% CI over seeds excludes 0 and the effect is at least 10% of the reference response. Statistics: 20 seeds per condition (a seed fixes connectivity and noise); mean and Student-t 95% confidence interval over seeds, paired within seed.

### 2.3 Pre-registration and deviations

Each experiment's design, measures and predictions were committed before it ran (`docs/PREREGISTRATION.md`, `docs/PREREGISTRATION_TIER2.md`). Every change made after a run is listed in a change log there. The most important: the pre-registered omission measure subtracted a 75 ms pre-tone baseline. In the gated networks the prediction cells fire *before* the expected tone, so the baseline already contained the omission response and subtracting it cancelled the effect. I replaced it with a raw omitted-minus-present contrast (v3) and wrote it down before re-running. I had inspected spike traces from one test seed while diagnosing the problem, so **the omission result is reported as exploratory**. The superseded numbers are archived in `results/archive/`.

## 3. Results

### 3.1 Adaptation alone produces SSA but no prediction error





**Figure 2. Experiment 1** (20 seeds, 400 trials, mean and 95% CI). **a** SSA index per adaptation condition. **b** Decomposition with the cascade control: iMM (deviant − standard), iRS (control − standard), iPE (deviant − control). **c** Omission: pale bars, response to a present tone; dots, omitted tone. **d–e** SSA against frequency gap and deviant probability. **f** iPE against gap.

**Table 1.** Experiment 1, normalised indices, cascade control, p = 0.1, gap 3 channels.

| Adaptation | SSA index | iRS (control − standard) | iPE (deviant − control) |
|---|---|---|---|
| none | −0.000 [−0.006, 0.006] | 0.008 [−0.006, 0.021] | −0.008 [−0.020, 0.005] |
| SFA | 0.019 [0.012, 0.026] | 0.009 [−0.005, 0.023] | 0.011 [−0.003, 0.025] |
| depression | 0.161 [0.153, 0.169] | 0.178 [0.165, 0.191] | −0.006 [−0.016, 0.004] |
| both | 0.187 [0.178, 0.195] | 0.198 [0.186, 0.209] | −0.000 [−0.011, 0.011] |

Short-term depression accounts for almost all of the deviant-versus-standard difference, and all of it is repetition suppression (Fig. 2a, b). The prediction-error component is zero in every condition, with CI half-widths around 0.01–0.015, so effects bigger than about 0.015 would have been detected. The many-standards control gives the same. There is no omission response (at most 0.21 spikes, against 11–26 spikes for a present tone; Fig. 2c). The “both” condition’s CI just excludes 0, but the effect is 1.8% of the tone response, well below the 10% floor.

**A prediction that failed.** I predicted SSA would fall with deviant probability and rise with frequency gap, as in recordings. It is flat across both (Fig. 2d, e). The reasons lie in the architecture: depression is private to each input channel, and adaptation recovers within the gap between tones, so the standard’s state does not depend on how rare the deviant is. Models with slower or multi-timescale adaptation reproduce this dependence (Mill et al., 2011; Yarden & Nelken, 2017), so this is a limitation of my network, not a finding.

**Sensitivity to slower adaptation.** SFA explains little at $\tau_w$ = 300 ms because it decays before the next tone. I re-ran with $\tau_w$ = 1000 and 3000 ms (labelled exploratory). SSA from SFA alone grows from 0.02 to 0.12 and 0.34, but iPE stays at about 0 (all CIs within ±0.03). **Slower adaptation makes the mismatch response bigger, but all of the increase is repetition suppression.**

### 3.2 What has to be added





**Figure 3. Tier 2** (20 seeds, mean and 95% CI). Top row: omission (v3 measure), unexpected repeat, and the tone after the odd one. Middle: drop-off slopes, candidate fit and continuations. Bottom: one-shot learning, regularity build-up and timing jitter.

**Table 2.** Main Tier 2 results (spikes; mean [95% CI]).

| Test | N0 (adaptation) | B (predictive core) | A1 | A2b | Verdict |
|---|---|---|---|---|---|
| T2 unexpected repeat (repeat − regular) | −2.84 [−3.62, −2.07] | −1.15 [−2.69, 0.39] | +8.58 [5.09, 12.07] | +7.57 [3.98, 11.15] | A passes; N0 shows the adaptation sign |
| T1 omission, PE− omitted − present (v3) | 0 | 0.14 [−0.07, 0.34] | 5.66 [3.83, 7.49] | 5.97 [3.80, 8.15] | A passes (exploratory) |
| B with long training (600 slots) | | repeat +5.84 [2.15, 9.52]; omission 2.76 [1.48, 4.03] | | | B passes too |
| M1 tone after the odd one (post − pre) | 2.68 | 6.36 | 11.70 | 10.83; vs N0 +8.15 [5.78, 10.52] | Supported; B also above N0 |

**Unexpected repeat.** Adaptation alone gives the opposite sign: the repeated tone gets a *smaller* response, as a stimulus-specific adaptation account predicts. Both gated variants reverse it with large effects. The predictive core B fails at normal training. **With long training it passes both tests**, so the gate's contribution is *speed of learning*, not an ability the core lacks.

**Omission.** With the v3 measure, A1 and A2b show about 6 extra negative-error spikes at omitted tones. B shows this only with long training, and N0 has no error cells. Part of this is structural, because PE− cells are built to be silenced by input. The more informative result is that the response **falls as timing gets irregular** (5.97, 5.61, 4.38, 3.23 spikes for jitter 0, 0.1, 0.3, 0.6 of the interval; Fig. 3, bottom right), as a timing-based prediction should.

**Tone after the odd one (M1).** The first standard after a deviant is amplified well beyond adaptation's recovery rise (A2b − N0 = 8.15 [5.78, 10.52]), and this effect survives every check in this paper. B shows a smaller version (3.68 [2.05, 5.31] above N0), so it is not unique to the gate. About 2.6 spikes of A's effect is sensitisation in the sensory cells, which the gate does by design. **This is a model prediction, not a match to data.** Evidence from real recordings is mostly negative: EEG studies report no N1 enhancement (Rosburg & Mager, 2021) and no MMN-like effect (Coy et al., 2024) for standards after deviants, and intracellular recordings show the first standard after a deviant only slightly larger (Hershenhoren et al., 2014). If the size of the effect here were found in recordings, it would support a gain mechanism; current evidence suggests real circuits do not show it at this strength.

**Candidate fit (M3).** After a deviant, total error is lower when the next tone fits a candidate (earlier tone returns: 9.40; deviant repeats: 4.69) than when it is new (12.35), and so is the gate level (0.37, 0.40 vs 0.46). The error ordering also appears in B; the gate ordering is specific to A.

**Ablation.** Both tests pass only with error cells, learning and the gate together (subsets TELGC, TELG, ELGC). The repeat alone needs only error cells plus learning (EL, ELG), and the delay line can be swapped for the candidates.

**Robustness.** Across 40 random draws of A2b's constants (one seed each, effect floor only), omission passes in 82%, the repeat in 75%, and both in 62%.

### 3.3 Predictions that were not supported

**Table 3.** Pre-registered or planned predictions that failed.

| Prediction | Result |
|---|---|
| Steeper response drop-off after the odd one, ordered A > B > C (M2) | Not steeper (−0.17 vs −0.19 initially); order A, C, B |
| One-shot learning: error falls after one exposure | Ratio of pair 2 to pair 1 = 1.11 [0.89, 1.32]; learning takes about 10 exposures |
| Omission response rises steadily with the number of regular tones | Jumps from 1 to 2 tones (+3.54 [1.71, 5.38]), then flat |
| Error in a random sequence decays as randomness is "accepted" (M5) | Does not decay (26.6 → 26.8); no precision mechanism is implemented |
| A's repeat and omission effects survive slower adaptation *without re-tuning* | **No.** Repeat +1.10 [−1.23, 3.43] at τ_w = 1000 ms and −5.74 at 3000 ms; omission 1.02 and 0 (but see §3.4) |

The gate's constants had been calibrated with τ_w = 300 ms and were not re-tuned for that sensitivity run. The next section tests whether re-tuning brings the effects back. M1 survives at both slower values even without re-tuning.

### 3.4 Re-tuning for slower adaptation

To separate "the mechanism needs fast adaptation" from "the circuit was mis-calibrated", I re-tuned it at τ_w = 1000 ms using the original sanity targets (`docs/RETUNE_SLOW_ADAPTATION.md`, committed before any run at the new value). The procedure has three steps:

- **Targets.** Seven sanity targets, for example "an unpredicted tone drives the positive-error cells to 60–100% of the sensory response" and "the gated learner predicts within about 3 exposures". They are measured on development seeds only, and none of them uses an omission, a repeat or a post-deviant tone.

- **Check at the original setting.** I first confirmed that the original constants meet all seven targets at 300 ms. Two ranges had to be widened slightly to match the original “about” wording; this is logged.
- **Search.** A fixed grid of 36 candidate settings. The rule picks the candidate meeting the most targets and, among ties, the smallest change.

At 1000 ms the original constants miss three targets: the error cells respond too weakly, and the gated learner is too slow. Twelve candidates meet all seven. The rule selects a **15% increase of the three weights driven by the sensory cells**, with the learning constants unchanged.

**Table 4.** Tier 2 at τ_w = 1000 ms after re-tuning (20 test seeds).

| net | unexpected repeat | omission (PE− omitted − present) | M1 minus N0 |
|---|---|---|---|
| N0 | −3.38 [−4.00, −2.76] | 0 | |
| B | −3.51 [−4.54, −2.47] | 0.05 [−0.03, 0.13] | 4.35 [2.71, 5.98] |
| A1 | +7.71 [3.61, 11.81] | 4.36 [2.69, 6.03] | 6.96 [4.07, 9.85] |
| A2b | +6.75 [2.95, 10.55] | 4.98 [3.09, 6.88] | 6.79 [4.16, 9.42] |

All pre-stated predictions hold. Adaptation alone keeps the wrong sign on the repeat. Both gated variants pass the repeat and omission tests with effects close to those at 300 ms. The re-tuned core B still fails at normal training. **The earlier failure was a calibration mismatch, not a dependence on fast adaptation.** Caveats: I had seen the untuned results before designing this; only the selected candidate was tested; and the test seeds are the same as before. At τ_w = 3000 ms (secondary), the original constants meet only 2 of 7 targets and only 3 candidates meet all seven (selected: sensory-driven weights +30%, slow learning rate doubled). After re-tuning, the unexpected repeat passes but only just (A2b +3.75 [0.01, 7.49]; A1 +4.19 [0.52, 7.85]), and **the omission test fails** (A2b 0.56 [0.19, 0.93], below the 1-spike floor). The mechanism therefore tolerates threefold slower adaptation but degrades at tenfold.

## 4. Discussion

**What this shows.** In this network, adaptation, whether fast or slow, synaptic or intrinsic, produces a large deviant-minus-standard difference made entirely of repetition suppression. The Parras decomposition finds no prediction-error component, and there is no omission response. Getting an unexpected-repeat response and an omission response requires error cells and learned, timed predictions. A slow predictive core gets there with enough training. A surprise gate that briefly boosts learning, sensitises input and offers candidate predictions gets there within normal training.

**What it does not show.** This is a sufficiency result in a toy network: these mechanisms *can* produce these signatures here. It does not show that brains use them, and nothing here bears on clinical use. Several parts of the predictive circuit (delay lines, separate error populations, candidate drives) are designed structures. The gated effects need the circuit to be calibrated for the adaptation level it runs with, and at very slow adaptation (3000 ms) the omission effect is lost even after re-tuning (§3.4).

**Relation to work on learning.** The gate is a form of surprise-modulated learning rate, an idea with precedent in both neuroscience and machine learning (Yu & Dayan, 2002; Faraji et al., 2018; Liakoni et al., 2021; Barry & Gerstner, 2024). The finding that the gate changes *how fast* rather than *whether* a sequence is learned matches that framing: surprise is a signal for when to update quickly. Error in a random sequence never settled, which suggests that a gate alone is not enough. A system also needs an estimate of how predictable its input is (precision), so it can stop treating noise as surprise.

**Limitations.** One small architecture with single a-priori time constants; deviants only above the standard; weak feedback inhibition (inhibitory cells fire about 3 Hz); spike counts rather than an EEG-like signal; one 10-cell channel

per tone rather than distributed coding; the omission measure revised after a first run; robustness tested with one seed per draw; and several cited works read only at abstract level (marked in `docs/PRIOR_ART.md`).

**Next steps.** (1) Test all candidate settings that meet the targets, not only the selected one. (2) Add a precision or uncertainty term and test whether error in random contexts then falls. (3) Compare learning speed against an ideal Bayesian observer. (4) Test whether the post-deviant gain is reduced to the small effect seen in recordings, and what that costs the other tests. (5) Extend the literature search to a systematic review and read the key papers in full.

## Reproducibility

```
make setup && make test    # pinned dependencies, unit tests (about 3 min)
make fig1-quick            # Experiment 1, 5 seeds (about 10 min on 4 cores)
make fig2-quick            # Tier 2, 5 seeds (about 1 h on 4 cores)
make fig1 && make fig2     # full 20-seed runs (hours, resumable)
```

Results are cached by a hash of each block's specification, so interrupted runs resume. The tests check, among other things, the LIF firing rate against the analytic value, determinism under a fixed seed, and the decomposition arithmetic.

## References

*Verification levels follow `docs/PRIOR_ART.md` and `docs/NOVELTY_CHECK.md`: [F] full text read; [A] abstract or bibliographic record; [S] search-result summary only. Every [S] entry must be checked against the publisher's page before submission.*


- Barry, M. L. L. R. & Gerstner, W. (2024). Fast adaptation to rule switching using neuronal surprise. *PLoS Computational Biology*, 20(2), e1011839. doi:10.1371/journal.pcbi.1011839 [S]
- Bouhadjar, Wouters, Diesmann & Tetzlaff (2022). Sequence learning, prediction, and replay in networks of spiking neurons. *PLoS Computational Biology*. PMC9273101. [S; initials, volume and article number to be checked]
- Carbajal, G. V. & Malmierca, M. S. (2018). The neuronal basis of predictive coding along the auditory pathway: from the subcortical roots to cortical deviance detection. *Trends in Hearing*, 22. doi:10.1177/2331216518784822 [F]
- Chien, V. S. C., Maess, B. & Knösche, T. R. (2019). A generic deviance detection principle for cortical On/Off responses, omission response, and mismatch negativity. *Biological Cybernetics*, 113(5–6), 475–494. doi:10.1007/s00422-019-00804-x [S]
- Coy, N., Bendixen, A., Grimm, S., Roeber, U. & Schröger, E. (2024). Conditional deviant repetition in the oddball paradigm modulates processing at the level of P3a but not MMN. *Psychophysiology*, 61(6), e14545. doi:10.1111/psyp.14545 [S]
- Faraji, M. J., Preuschoff, K. & Gerstner, W. (2018). Balancing new against old information: the role of puzzlement surprise in learning. *Neural Computation*, 30(1), 34–83. doi:10.1162/NECO_a_01025 [S]
- Hershenhoren, I., Taaseh, N., Antunes, F. M. & Nelken, I. (2014). Intracellular correlates of stimulus-specific adaptation. *Journal of Neuroscience*, 34(9), 3303–3319. doi:10.1523/JNEUROSCI.2166-13.2014 [S]
- Liakoni, Modirshanechi, Gerstner & Brea (2021). Learning in volatile environments with the Bayes factor surprise. *Neural Computation*, 33(2), 269–340. [S; initials to be checked]
- Lieder, Daunizeau, Garrido, Friston & Stephan (2013). Modelling trial-by-trial changes in the mismatch negativity. *PLoS Computational Biology*, 9(2), e1002911. [S; initials to be checked]
- May, P. J. C. & Tiitinen, H. (2010). Mismatch negativity (MMN), the deviance-elicited auditory deflection, explained. *Psychophysiology*, 47(1), 66–122. [A]

- Mill, R. W., Bőhm, T. M., Bendixen, A., Winkler, I. & Denham, S. L. (2013). Modelling the emergence and dynamics of perceptual organisation in auditory streaming. *PLoS Computational Biology*, 9(3), e1002925. [S]
- Mill, R., Coath, M., Wennekers, T. & Denham, S. L. (2011). A neurocomputational model of stimulus-specific adaptation to oddball and Markov sequences. *PLoS Computational Biology*, 7(8), e1002117. [A]
- Parras, G. G., Nieto-Diego, J., Carbajal, G. V., Valdés-Baizabal, C., Escera, C. & Malmierca, M. S. (2017). Neurons along the auditory pathway exhibit a hierarchical organization of prediction error. *Nature Communications*, 8, 2148. doi:10.1038/s41467-017-02038-6 [F]
- Rosburg, T. & Mager, R. (2021). *Hearing Research*, 400, 108140. [S; title to be checked]
- Ruhnau, P., Herrmann, B. & Schröger, E. (2012). Finding the right control: the mismatch negativity under investigation. *Clinical Neurophysiology*, 123(3), 507–512. doi:10.1016/j.clinph.2011.07.035 [A]
- Wacongne, C., Changeux, J.-P. & Dehaene, S. (2012). A neuronal model of predictive coding accounting for the mismatch negativity. *Journal of Neuroscience*, 32(11), 3665–3678. doi:10.1523/JNEUROSCI.5003-11.2012 [F]
- Yarden, T. S. & Nelken, I. (2017). Stimulus-specific adaptation in a recurrent network model of primary auditory cortex. *PLoS Computational Biology*, 13(3), e1005437. [A]
- Yu, A. J. & Dayan, P. (2002). Expected and unexpected uncertainty: ACh and NE in the neocortex. *Advances in Neural Information Processing Systems 15*, 173–180. [S; author order to be checked: the NeurIPS listing may put Dayan first, in which case cite as Dayan & Yu (2002)]


Software: Brian2 2.10.1 spiking neural network simulator (briansimulator.org).