

```
Blink.ino
1 void setup() {
2   // Initialize digital pin LED_BUILTIN as an output.
3   pinMode(LED_BUILTIN, OUTPUT);
4
5   // Initialize serial communication at 9600 bits per second:
6   Serial.begin(9600);
7   Serial.println("System Initialized. Starting Blink Loop...");
8 }
9
10 // The loop function runs over and over again forever
11 void loop() {
12   Serial.println("User: Aryan Gupta");
13   digitalWrite(LED_BUILTIN, HIGH); // turn the LED on (HIGH is the voltage level)
14   Serial.println("LED is ON");      // Print status to Serial Monitor
15   delay(1000);                      // wait for a second
16
17   digitalWrite(LED_BUILTIN, LOW);  // turn the LED off by making the voltage LOW
18   Serial.println("LED is OFF");     // Print status to Serial Monitor
19   delay(1000);                      // wait for a second
20 }
21
```

Output Serial Monitor X

Message (Enter to send message to 'Arduino Nano 33 BLE' on 'COM5')

```
LED is ON
LED is OFF
User: Aryan Gupta
LED is ON
LED is OFF
User: Aryan Gupta
LED is ON
LED is OFF
User: Aryan Gupta
LED is ON
LED is OFF
User: Aryan Gupta
LED is ON
LED is OFF
```