

SimpleAccelerometer.ino

```
1  #include <Arduino_LSM9DS1.h>
2
3  void setup() {
4      Serial.begin(9600);
5      while (!Serial);
6      Serial.println("Started");
7
8      if (!IMU.begin()) {
9          Serial.println("Failed to initialize IMU!");
10         while (1);
11     }
12
13     Serial.print("Accelerometer sample rate = ");
14     Serial.print(IMU.accelerationSampleRate());
15     Serial.println(" Hz");
16     Serial.println();
17     Serial.println("Acceleration in g's");
18     Serial.println("X\tY\tZ");
19 }
20
21 void loop() {
22     float x, y, z;
23
24     if (IMU.accelerationAvailable()) {
25         IMU.readAcceleration(x, y, z);
26
27         Serial.print(x);
28         Serial.print('\t');
29         Serial.print(y);
30         Serial.print('\t');
31         Serial.println(z);
32     }
33 }
34
```

Output Serial Monitor ✕		
Message (Enter to send message to 'Arduino Nano 33 BLE' on 'COM5')		
----	----	----
0.01	-0.77	0.62
0.01	-0.76	0.59
0.03	-0.72	0.59
0.06	-0.66	0.60
0.10	-0.63	0.63
0.14	-0.64	0.71
0.17	-0.64	0.72
0.22	-0.62	0.71
0.24	-0.61	0.71
0.2		

