

Naive Pattern Searching

- Naive pattern searching is a simple approach to finding a specific pattern (word or phrase) in a larger body of text.
- **Components:**
 - Text to scan
 - Pattern to search for
- The pattern is slid along the text one character at a time, checking for matches.

Process:

1. Slide the pattern along the text character by character.
2. Count the number of following characters that match the pattern.
3. If the count equals the pattern length, a match is found.

Performance:

- Worst-case scenario: $O(nk)$ comparisons (n : length of text, k : length of pattern).
- Main cause of slow performance: Constant backtracking to the next character of the input text.
- Knuth–Morris–Pratt (KMP) algorithm improves performance by:
 - Tracking pattern prefixes.
 - Intelligently skipping through the text.
 - Preventing excessive backtracking.
 - Achieving runtime of $O(n+k)$.

Press 'space' for AI, '/' for commands...

Advantages of KMP:

- More optimized than naive approach.
- Avoids redundant character comparisons.
- Efficiently integrates pattern and text iterations.
- Prevents unnecessary backtracking.

```
def pattern_search(text, pattern):
    print("Input Text:", text, "Input Pattern:", pattern)
    for index in range(len(text)):
        print("Text Index:", index)
        match_count = 0
        for char in range(len(pattern)):
            print("Pattern Index:", char)
            if pattern[char] == text[index + char]:
                match_count += 1
            else:
                break
        if match_count == len(pattern):
            print(pattern, "found at index", index)
```

```
text = "HAYHAYNEEDLEHAYHAYHAYNEEDLEHAYHAYHAYHAYNEEDLE"
pattern = "NEEDLE"
pattern_search(text, pattern)
```

```
# New inputs to test
text2 = "SOMEMORERANDOMWORDSTOpatternSEARCHTHROUGH"
pattern2 = "pattern"
text3 = "This    still        works with    spaces"
pattern3 = "works"
text4 = "722615457824612704202682179992552072047396"
pattern4 = "42"
pattern_search(text2, pattern2)
pattern_search(text3, pattern3)
pattern_search(text4, pattern4)
```