



Find solutions for your homework

Search

home / study / engineering / computer science / computer science questions and answers / using c++, data structures, c++ stl, all test inputs and o...

Question: Using C++, data structures, C++ STL, all test inputs and output...

Using C++, data structures, C++ STL, all test inputs and outputs are shown below.

Reunion

Description

It's been years since Kyaru and her best friends graduated from high school and they all miss each other very much. Recently, they've finally find a time when everyone is free. However, where to have a reunion becomes another problem to them. The reason is that they are currently living in different cities and plan to reunite in one city by plane, but there aren't many airlines in the whole country, which means there may be some unreachable cities for some of Kyaru's friends no matter how they fly.

More specifically, there're K friends (including Kyaru herself) living in N cities. In the whole country, there're M airlines, each of which is one-way and has one departure city and one destination city.

Of course an airline won't have its destination the same as its departure city. Also, a city is definitely reachable to whom lives there.

Now Kyaru would like you to help her find how many cities can be chose for reunion, i.e. reachable to all of them (You don't need to worry about how they go back after the reunion).

Input

The first line contains three space-separated integers, respectively: K , N , and M

The i -th line of the next K line contains a single integer ($1..N$) representing the index number of the city where the i -th friend currently lives.

The i -th line of the next M line contains two space-separated integers a , b representing that there's an one-way airline from city a to city b .

Output

One integer indicating the number of cities that can be chose for reunion.

Sample Input/Output

Input

```
2 4 4
2
3
1 2
1 4
2 3
3 4
```

Output

```
2
```

Hint

They can reunite in city 3 or city 4

Constraint

$1 \leq K \leq 100, 1 \leq N \leq 1000, 1 \leq M \leq 10^4$.

Show transcribed image text

View comments (1) >

Post a question

Answers from our experts for your tough homework questions

Enter question

Continue to post

20 questions remaining



Snap a photo from your phone to post a question

We'll send you a one-time download link

888-888-8888

Text r

By providing your phone number, you agree to receive a automated text message with a link to get the app. Standard messaging rates may apply.

My Textbook Solutions



Principles...

5th Edition



Fundament...

1st Edition



Fundan

5th Editi

[View all solutions](#)



Anonymous answered this
136 answers

Was this answer helpful?



Coded in c++.

Programming comments are written.

BFS is used to check if any friend can reach the city or not.

Iterated over each location if it is possible for reunion or not.

```
#include <iostream>
```

```
#include <vector>
```

```
#include <queue>
```

```
using namespace std;
```

```
//will return true only if we can go from start to end according to the ways
```

```
bool isPathBFS(vector <vector<int>>& ways, int nodes, int start, int end){
```

```
    bool visited[nodes]; //the nodes which are already visited will not be visited again
```

```
    for(int i = 0; i < nodes; ++i){
```

```
        visited[i] = false; //firstly no node is visited
```

```
    }
```

```
    queue <int> traversal;
```

```
    traversal.push(start);
```

```
    visited[start-1] = true; //start is visited so it is given true
```

```
    while(!traversal.empty()){
```

```
        start = traversal.front();
```

```
        traversal.pop();
```

```
        for(int i = 0; i < (int)ways[start-1].size(); ++i){
```

```
            if(ways[start-1][i] == end)
```

```
                return true;
```

```
            if(visited[ways[start-1][i]-1] == false){
```

```
                traversal.push(ways[start-1][i]);
```

```
                visited[ways[start-1][i]-1] = true;
```

```
            }
```

```
        }
```

```
    }
```

```
    return false;
```

```
}
```

```
int main()
```

```
{
```

```
    int n, k, m;
```

```
    cin >> k >> n >> m;
```

```
    int friends[1000]; //will contain location of ith friend
```

```
    for(int i = 0; i < k; ++i)
```

```
    {
```

```
        cin >> friends[i];
```

```
    }
```

```
    int count = 0;
```

```
    vector <vector<int>> ways;
```

```
    ways.resize(n);
```

```
    for(int i = 0; i < m; ++i)
```

```
    {
```

```
        int start;
```

```
        int end;
```

```
        cin >> start >> end;
```

```
        ways[start-1].push_back(end); //making the directed graph
```

```
    }
```

```
    for(int i = 1; i <= n; ++i) //we will check if ith location is possible for reunion
```

```
    {
```

```
        bool possible = true;
```

```
        for(int j = 0; j < k; ++j)
```

```
        {
```

```
            possible = isPathBFS(ways, n, friends[j], i); //is jth friend can reach ith location
```

```
            if(friends[j] == i)
```

```
            {
```

```
                possible = true;
```

```
            }
```

```
            if(possible == false) //if any friend can't reach ith location we will stop array and look for another reunion city
```

```
            {
```


```
                break;
```

```
            }
```



```
{  
    count++;  
}  
}  
cout<<count;//will print number of places possible  
}
```

Output window, here last entry is the actual output of the code and other are inputs:



[View comments \(2\) >](#)

Up next for you in Computer Science

/* * Instructions: * * 1.
Only
complete the functions
specified below. Do not
create any additional
function. * 2. Use Visual
Studio 2019 to build, test
and

[See answer](#)

3.2. inpost.cpp This file
should contain a
definition
for the following function:
string convert(const
string&
infix) This function
converts

[See answer](#)

[See more questions
for subjects you study](#)

COMPANY

LEGAL & POLICIES

CHEGG PRODUCTS AND SERVICES

CHEGG NETWORK

CUSTOMER SERVICE



