

//Code Optimization Technique

```
#include<stdio.h>
#include<string.h>
struct op
{
char l;
char r[20];
}
op[10],pr[10];
void main()
{
int a,i,k,j,n,z=0,m,q;
char *p,*l;
char temp,t;
char *tem;
printf("Enter the Number of Values:");
scanf("%d",&n);
for(i=0;i<n;i++)
{
printf("left: ");
scanf(" %c",&op[i].l);
printf("right: ");
scanf(" %s",&op[i].r);
}
printf("Intermediate Code\n") ;
for(i=0;i<n;i++)
{
printf("%c=",op[i].l);
printf("%s\n",op[i].r);
}
for(i=0;i<n-1;i++)
{
temp=op[i].l;
for(j=0;j<n;j++)
{
p=strchr(op[j].r,temp);
if(p)
{
pr[z].l=op[i].l;
strcpy(pr[z].r,op[i].r);
z++;
}
}
pr[z].l=op[n-1].l;
strcpy(pr[z].r,op[n-1].r);
z++;
printf("\nAfter Dead Code Elimination\n");
for(k=0;k<z;k++)
{
printf("%c\t=",pr[k].l);
printf("%s\n",pr[k].r);
}
for(m=0;m<z;m++)
{
tem=pr[m].r;
for(j=m+1;j<z;j++)
{
p=strstr(tem,pr[j].r);
if(p)
{
t=pr[j].l;
pr[j].l=pr[m].l;
for(i=0;i<z;i++)
{
```

```

l=strchr(pr[i].r,t) ;
if(l)
{
a=l-pr[i].r;
printf("pos: %d\n",a);
pr[i].r[a]=pr[m].l;
}}}}
printf("Eliminate Common Expression\n");
for(i=0;i<z;i++)
{
printf("%c\t=",pr[i].l);
printf("%s\n",pr[i].r);
}
for(i=0;i<z;i++)
{
for(j=i+1;j<z;j++)
{
q=strcmp(pr[i].r,pr[j].r);
if((pr[i].l==pr[j].l)&&!q)
{
pr[i].l='\0';
}
}
}
printf("Optimized Code\n");
for(i=0;i<z;i++)
{
if(pr[i].l!='\0')
{
printf("%c=",pr[i].l);
printf("%s\n",pr[i].r);
}
}
}

```

OUTPUT:

```

virus@virus-desktop: ~/Desktop/syedvirus
virus@virus-desktop:~/Desktop/syedvirus$ gcc codeop.c -w
virus@virus-desktop:~/Desktop/syedvirus$ ./a.out
Enter the Number of Values:5
left: a
right: 9
left: b
right: c+d
left: e
right: c+d
left: f
right: b+e
left: r
right: :f
Intermediate Code
a=9
b=c+d
e=c+d
f=b+e
r=:f
After Dead Code Elimination
b      =c+d
e      =c+d
f      =b+e
r      =:f
pos: 2
Eliminate Common Expression
b      =c+d
b      =c+d
f      =b+b
r      =:f
Optimized Code
b=c+d
f=b+b
r=:f
virus@virus-desktop:~/Desktop/syedvirus$

```