

FlowDLS L360T

2

Temperature Range	Float Diameter 52MM Dia	Float Length 100MM
-------------------	----------------------------	-----------------------

1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Displacer Type Level Switch
Temperature Range	
Pressure Range	
Float Diameter	52MM Dia
Float Length	100MM
Contact Points	All floats are adjustable in length

2. Fixed Technical Specifications

Parameter	Specification
Process Connection Type	Flange-End
Process Connection MOC	As per Model Code
Process Connection Std	ASA 150 # RF
Process Size	XX NB
Float MOC	As per Model Code
Spring Pipe / Rod MOC	PP (6MM Dia)
Spring MOC	SS 316 PTFE COATING
Housing MOC	As per Model Code
Protection Type	Flameproof
Wire Rope	SS 316+PTFE
Cable Gland MOC	PVC
Cable Entry Standard	M20 X 1.5 (PVC)
Cable Gland Protection	Weather-Proof
Switch	Micro switch 230 VAC 5 Amp
Switch Assembly MOC	SS 316

3. Variable Technical Specifications

Code	Description
POTENTIAL FREE CONTACT	
PC1	1 SPDT (1NO +1NC + 1C) - Default
PC2	2 SPDT - DPDT

Other Details

Parameter	Specification
Hydro Test	Max. 10 Kg/Cm2
IP Rating	IP 67
Magnet	Ferrite (High Temperature)
Branding	Flowtech
Packing	Wooden / Other